L 170/4

EN

COUNCIL REGULATION (EU) No 631/2011

of 21 June 2011

amending Regulation (EC) No 1255/96 temporarily suspending the autonomous Common Customs Tariff duties on certain industrial, agricultural and fishery products

THE COUNCIL OF THE EUROPEAN UNION,

Having regard to the Treaty on the Functioning of the European Union, and in particular Article 31 thereof,

Having regard to the proposal from the European Commission,

Whereas:

- It is in the interest of the Union to suspend totally the autonomous Common Customs Tariff duties on a certain number of new products currently not listed in the Annex to Council Regulation (EC) No 1255/96 (¹).
- (2) Four products with CN and TARIC codes 2933 39 99 70, 2933 39 99 80, 8507 80 30 40 and 8507 80 30 50 which are currently listed in the Annex to Regulation (EC) No 1255/96 should be deleted because it is no longer in the interest of the Union to maintain the suspension of autonomous Common Customs Tariff duties for those products.
- (3) It is necessary to modify the product description of 15 suspensions in the Annex to Regulation (EC) No 1255/96 in order to take account of technical product developments and economic trends on the market. Those suspensions should be deleted from the list in that Annex and reinserted as new suspensions using new descriptions. Moreover, TARIC codes for 12 products should be changed.
- (4) The suspensions for which those technical modifications are necessary should be deleted from the list of suspensions set out in the Annex to Regulation (EC) No 1255/96 and should be reinserted in that list using new product descriptions, or new TARIC codes.
- (5) In the interest of clarity, the modified entries should be marked with an asterisk in the lists of inserted and deleted suspensions set out in Annex I and Annex II to this Regulation.

- (6) Experience has shown that it is necessary to provide an expiry date for the suspensions set out in the Annex to Regulation (EC) No 1255/96 to ensure that account is taken of technological and economic changes. This should not exclude the premature termination of certain measures or their continuation beyond the expiry date, if economic justification is provided, in accordance with the principles laid down in the Commission communication of 1998 concerning autonomous tariff suspensions and quotas (²).
- (7) Regulation (EC) No 1255/96 should therefore be amended accordingly.
- (8) Since the suspensions laid down in this Regulation have to take effect from 1 July 2011, this Regulation should apply from that date and enter into force immediately,

HAS ADOPTED THIS REGULATION:

Article 1

The Annex to Regulation (EC) No 1255/96 is hereby amended as follows:

- (1) the rows for the products listed in Annex I to this Regulation are inserted;
- (2) the rows for the products for which the CN and TARIC codes are set out in Annex II to this Regulation are deleted.

Article 2

This Regulation shall enter into force on the day of its publication in the Official Journal of the European Union.

It shall apply from 1 July 2011.

This Regulation shall be binding in its entirety and directly applicable in all Member States.

Done at Luxembourg, 21 June 2011.

For the Council The President FAZEKAS S.

ANNEX I

Products referred to in Article 1(1)

CN code	TARIC	Description	Rate of autonomous duty	Validity period
0811 90 50 0811 90 70 *ex 0811 90 95	70	Fruit of the genus Vaccinium, uncooked or cooked by steaming or boiling in water, frozen, not containing added sugar or other sweetening matter	0 %	1.7.2011- 31.12.2013
*ex 1517 90 99	10	Vegetable oil, refined, containing by weight 25 % or more but not more than 50 % arachidonic acid or 12 % or more but not more than 50 % docosahexaenoic acid and stan- dardised with high oleic sunflower oil (HOSO)	0 %	1.7.2011- 31.12.2011
ex 2007 99 50 ex 2008 99 48	40 93	Mango puree concentrate: — of the genus Mangifera, — of a Brix value of 28 or more but not more than 30, for use in the manufacture of fruit juices (1)	6 %(3)	1.7.2011- 31.12.2015
ex 2007 99 50 ex 2008 99 49	50 50	Acerola puree concentrate: — of the genus <i>Malpighia</i> , — of a Brix value of 20, for use in the manufacture of fruit juices (1)	9 %(3)	1.7.2011- 31.12.2015
ex 2007 99 50 ex 2008 99 48	60 20	Guava puree concentrate: — of the genus <i>Psidium</i> , — of a Brix value of 20, for use in the manufacture of fruit juices (1)	6 %(3)	1.7.2011- 31.12.2015
ex 2008 99 48	94	Mango puree: — not from concentrate, — of the genus <i>Mangifera</i> , — of a Brix value of 16, for use in the manufacture of fruit juices (1)	6 %	1.7.2011- 31.12.2015
ex 2009 41 10 ex 2009 41 99	70 70	 Pineapple juice: not from concentrate, of the genus Ananas, of a Brix value of 11 or more but not more than 16, for use in the manufacture of fruit juices (1) 	8 %	1.7.2011- 31.12.2015
ex 2818 10 91	10	Sintered corundum with micro crystalline structure, containing by weight: — 94 % or more, but not more than 98,5 % of α -Al2O3, — 2 % (± 1,5 %) of magnesium spinel, — 1 % (± 0,6 %) of yttrium oxide, and — 2 % (± 1,2 %) of each lanthanum oxide and neodymium oxide, with less than 50 % of the total weight having a particle size of more than 10 mm	0 %	1.7.2011- 31.12.2015
*ex 2825 50 00	20	Copper (I or II) oxide containing by weight 78 % or more of copper and not more than 0,03 % of chloride	0 %	1.7.2011- 31.12.2013
ex 2826 19 90	10	Tungsten hexafluoride with a purity of 99,9 % by weight or more	0 %	1.7.2011- 31.12.2015
*ex 2833 29 80	20	Manganese sulphate monohydrate	0 %	1.7.2011- 31.12.2013
ex 2833 29 80	30	Zirconium sulphate	0 %	1.7.2011- 31.12.2015

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*ex 2836 99 17	20	Zirconium (IV) basic carbonate	0 %	1.7.2011- 31.12.2013
ex 2903 69 90	70	α,α,α',α'-Tetrachloro-o-xylen	0 %	1.7.2011- 31.12.2015
ex 2905 29 90	30	Dodeca-8,10-dien-1-ol	0 %	1.7.2011- 31.12.2015
ex 2909 30 90	30	3,4,5-Trimethoxytoluene	0 %	1.7.2011- 31.12.2015
ex 2912 49 00	30	Salicylaldehyde	0 %	1.7.2011- 31.12.2015
ex 2915 39 00	60	Dodec-8-enyl acetate	0 %	1.7.2011- 31.12.2015
ex 2915 39 00	65	Dodeca-7,9-dienyl acetate	0 %	1.7.2011- 31.12.2015
ex 2915 39 00	70	Dodec-9-enyl acetate	0 %	1.7.2011- 31.12.2015
ex 2917 12 00	20	Dimethyl adipate	0 %	1.7.2011- 31.12.2015
ex 2917 39 95	40	Benzene-1,2,4-tricarboxylic acid 1,2-anhydride	0 %	1.7.2011- 31.12.2015
ex 2920 90 85	20	Tris(methylphenyl)phosphite	0 %	1.7.2011- 31.12.2015
ex 2920 90 85	30	2,2'-[[3,3',5,5'-Tetrakis(1,1-dimethylethyl)[1,1'-biphenyl]- 2,2'-diyl]bis(oxy)]bis[biphenyl-1,3,2-dioxaphosphepine]	0 %	1.7.2011- 31.12.2015
ex 2920 90 85	40	Bis(2,4-dicumylphenyl)pentaerythritol diphosphite	0 %	1.7.2011- 31.12.2015
ex 2921 42 00	82	2-Chloro-4-nitroaniline	0 %	1.7.2011- 31.12.2015
ex 2921 43 00	50	4-Aminobenzotrifluoride	0 %	1.7.2011- 31.12.2015
ex 2921 43 00	60	3-Aminobenzotrifluoride	0 %	1.7.2011- 31.12.2015
ex 2921 49 00	80	4-Heptafluoroisopropyl-2-methylaniline	0 %	1.7.2011- 31.12.2015
ex 2922 49 85	45	Glycine	0 %	1.7.2011- 31.12.2015
*ex 2923 90 00	10	Tetramethylammonium hydroxide, in the form of an aqueous solution containing 25 % (\pm 0,5 %) by weight of tetramethylammonium hydroxide	0 %	1.7.2011- 31.12.2013
ex 2923 90 00	75	 Tetraethylammonium hydroxide, in the form of an aqueous solution containing: 35 % (± 0,5 %) by weight of tetraethylammonium hydroxide, not more than 1 000 mg/kg of chloride, not more than 2 mg/kg of iron, and not more than 10 mg/kg of potassium 	0 %	1.7.2011- 31.12.2015

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 2924 29 98	35	2'-Methoxyacetoacetanilide	0 %	1.7.2011- 31.12.2015
ex 2924 29 98	40	N,N'-1,4-Phenylenebis[3-oxobutyramide]	0 %	1.7.2011- 31.12.2015
ex 2924 29 98	45	Propoxur (ISO)	0 %	1.7.2011- 31.12.2015
ex 2924 29 98	50	N,N'-(2,5-Dichloro-1,4-phenylene)bis[3-oxobutyramide]	0 %	1.7.2011- 31.12.2015
ex 2924 29 98	55	N,N'-(2,5-Dimethyl-1,4-phenylene)bis[3-oxobutyramide]	0 %	1.7.2011- 31.12.2015
ex 2924 29 98	60	N,N'-(2-Chloro-5-methyl-1,4-phenylene)bis[3-oxobuty- ramide]	0 %	1.7.2011- 31.12.2015
ex 2926 90 95	30	2-Amino-3-(3,4-dimethoxyphenyl)-2-methylpropanenitrile hydrochloride	0 %	1.7.2011- 31.12.2015
ex 2929 10 00	55	2,5 (and 2,6)-Bis(isocyanatomethyl)bicyclo[2.2.1]heptane	0 %	1.7.2011- 31.12.2015
ex 2930 90 99	10	2,3-Bis((2-mercaptoethyl)thio)-1-propanethiol	0 %	1.7.2011- 31.12.2015
ex 2930 90 99	20	2-Methoxy-N-[2-nitro-5-(phenylthio)phenyl]acetamide	0 %	1.7.2011- 31.12.2015
ex 2930 90 99	55	Thiourea	0 %	1.7.2011- 31.12.2015
ex 2930 90 99	65	Pentaerythritol tetrakis(3-mercaptopropionate)	0 %	1.7.2011- 31.12.2015
ex 2931 00 99	30	Diethylborane isopropoxide	0 %	1.7.2011- 31.12.2015
ex 2933 21 00	80	5,5-Dimethylhydantoin	0 %	1.7.2011- 31.12.2015
ex 2933 39 99	85	2-Chloro-5-chloromethylpyridine	0 %	1.7.2011- 31.12.2015
ex 2933 69 80	55	Terbutryn (ISO)	0 %	1.7.2011- 31.12.2015
ex 2933 99 80	64	((3R)-1-{(1R,2R)-2-[2-(3,4-Dimethoxyphenyl) ethoxy]cyclohexyl}pyrrolidin-3-ol.hydrochloride	0 %	1.7.2011- 31.12.2015
ex 2934 99 90	85	N2-[1-(S)-Ethoxycarbonyl-3-phenylpropyl]-N6-trifluor- oacetyl-L-lysyl-N2-carboxy anhydride	0 %	1.7.2011- 31.12.2015
ex 2934 99 90	86	Dithianon (ISO)	0 %	1.7.2011- 31.12.2015
ex 2934 99 90	87	2,2'-(1,4-Phenylene)bis(4H-3,1-benzoxazin-4-one)	0 %	1.7.2011- 31.12.2015
ex 2935 00 90	40	Imazosulfuron (ISO), of a purity by weight of 98 % or more	0 %	1.7.2011- 31.12.2015
ex 2935 00 90	42	Penoxsulam (ISO)	0 %	1.7.2011- 31.12.2015

CN code	TARIC	Description	Rate of autonomous duty	Validity perio
ex 3204 11 00	10	Dye C.I. Disperse Yellow 54 also known as C.I. Solvent Yellow 114	0 %	1.7.2011- 31.12.2015
ex 3204 11 00	20	Dye C.I. Disperse Yellow 241	0 %	1.7.2011- 31.12.2015
ex 3204 11 00	30	 Preparation of dispersion dyes, containing: C.I. Disperse Orange 61, C.I. Disperse Blue 291:1, C.I. Disperse Violet 93:1, C.I. Disperse Red 54 	0 %	1.7.2011- 31.12.2015
ex 3204 19 00	71	Dye C.I. Solvent Brown 53	0 %	1.7.2011- 31.12.2015
ex 3204 19 00	72	Dye C.I. Solvent Yellow 93	0 %	1.7.2011- 31.12.201
ex 3204 19 00	73	Dye C.I. Solvent Blue 104	0 %	1.7.2011- 31.12.201
*ex 3208 20 10	20	Immersion topcoat solution containing by weight 0,5 % or more but not more than 15 % of acrylate-methacrylate- alkenesulphonate copolymers with fluorinated side chains, in a solution of n-butanol and/or 4-methyl-2-pentanol and/or diisoamylether	0 %	1.7.2011- 31.12.201
ex 3215 90 00	40	Dry ink powder with a base of hybrid resin (made from polystyrene acrilyc resin and polyester resin) mixed with: — wax, — a vinyl-based polymer, and — a colouring agent, for use in the manufacture of toner bottles for photo- copiers, fax machines, printers and multifunction devices (1)	0 %	1.7.2011- 31.12.201
*ex 3707 90 90	85	 Rolls, containing: a dry layer of a photosensitive acrylic resin, on one side a poly(ethylene terephthalate) protecting foil, and on the other side a polyethylene protecting foil 	0 %	1.7.2011- 31.12.2014
ex 3808 93 90	20	 Preparation consisting of benzyl(purin-6-yl)amine in a glycol solution, containing by weight: 1,88 % or more but not more than 2,00 % of benzyl(purin-6-yl)amine, of a kind used in plant growth regulators 	0 %	1.7.2011- 31.12.201
ex 3808 93 90	30	Aqueous solution containing by weight: — 1,8 % of sodium para-nitrophenolate, — 1,2 % of sodium ortho-nitrophenolate, — 0,6 % of sodium 5-nitroguaiacolate, for use in the manufacture of a plant growth regulator (1)	0 %	1.7.2011- 31.12.201
ex 3808 93 90	40	 Mixed white powder containing by weight: 3 % or more but not more than 3,6 % of 1-methyl-cyclopropene with a purity more than 96 %, and containing less than 0,05 % of each impurity of 1-chloro-2-methylpropene and 3-chloro-2-methylpropene, for use in the manufacture of a growth regulator of post-harvest fruits, vegetables and ornamentals with a specific generator (1) 	0 %	1.7.2011- 31.12.201

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 3808 93 90	50	 Preparation in the form of powder, containing by weight: 55% or more of Gibberellin A4, 1% or more but not more than 35% of Gibberellin A7, 90% or more of Gibberellin A4 and Gibberellin A7 combined, not more than 10% of a combination of water and other naturally occurring Gibberellins, of a kind used in plant growth regulators 	0 %	1.7.2011- 31.12.2015
ex 3815 12 00	20	Carbon supported platinum catalyst powder, containing by weight 9,5 % or more but not more than 10,5 % of platinum, for use as a fuel cell catalyst(1)	0 %	1.7.2011- 31.12.2015
ex 3815 12 00	30	Carbon supported platinum alloy catalyst, containing by weight 11% or more but not more than 12,6% of platinum, for use as a fuel cell catalyst(1)	0 %	1.7.2011- 31.12.2015
ex 3815 90 90	30	 Catalyst, consisting of a suspension in mineral oil of: tetrahydrofuran complexes of magnesium chloride and titanium(III) chloride, and silicon dioxide, containing 6,6 % (± 0,6 %) by weight of magnesium, and containing 2,3 % (± 0,2 %) by weight of titanium 	0 %	1.7.2011- 31.12.2015
*ex 3824 90 97	46	Carboxylic acid anhydride based hardener for epoxide resin, in liquid form, of a specific weight at 25 °C of $1,15 \text{ g/cm}^3$ or more but not more than $1,20 \text{ g/cm}^3$	0 %	1.7.2011- 31.12.2013
ex 3824 90 97	58	N2-[1-(S)-Ethoxycarbonyl-3-phenylpropyl]-N6-trifluor- oacetyl-L-lysyl-N2-carboxy anhydride in a solution of dich- loromethane at 37 %	0 %	1.7.2011- 31.12.2015
ex 3824 90 97	59	3',4',5'-Trifluorobiphenyl-2-amine, in the form of a solution in toluene containing by weight 80 % or more but not more than 90 % of 3',4',5'-trifluorobiphenyl-2-amine	0 %	1.7.2011- 31.12.2015
ex 3901 30 00	80	 Ethylene-vinyl acetate copolymer, containing 27,8 % or more but not more than 29,3 % by weight of vinyl acetate, with a melt flow index of 22 g/10 min or more but no more than 28 g/10 min, containing not more than 15 mg/kg vinyl acetate monomer 	0 %	1.7.2011- 31.12.2015
ex 3901 30 00	82	 Ethylene-vinyl acetate copolymer, containing 9,8 % or more but not more than 10,8 % by weight of vinyl acetate, with a melt flow index of 2,5 g/10 min or more but no more than 3,5 g/10 min, containing not more than 15 mg/kg vinyl acetate monomer 	0 %	1.7.2011- 31.12.2015

CN co	ode	TARIC	Description	Rate of autonomous duty	Validity period
ex 3901	90 90	80	 Block copolymer of ethylene with octene in the form of pellets: — with a specific gravity of 0,862 or more, but not more than 0,865, — able to stretch to at least 200 % its original length, — with a hysteresis of 50 % (± 10 %), — with permanent deformation of not more than 20 %, for use in the manufacture of napkin liners for babies (1) 	0 %	1.7.2011- 31.12.2015
ex 3901	90 90	82	Copolymer of ethylene and methacrylic acid	0 %	1.7.2011- 31.12.2015
*ex 3902	10 00	40	 Polypropylene, containing no plasticiser: of a tensile strength: of 32-60 MPa (as determined by the ASTM D638 method), of a flexural strength of 50-90 MPa (as determined by the ASTM D790 method), of a Melt Flow Rate (MFR) at 230 °C/2,16 kg of 5-15 g/10 min (as determined by the ASTM D1238 method), with 40 % or more but not more than 80 % by weight of polypropylene, with 10 % or more but not more than 30 % by weight of glass fibre, with 10 % or more but not more than 30 % by weight of mica 	0 %	1.7.2011- 31.12.2014
ex 3902	90 90	84	Blend of hydrogenated styrenic block copolymer, poly- ethylene wax, and tackifier resin, in the form of pellets, containing by weight: — 70 (± 5) % of styrenic block copolymer, — 15 (± 5) % of polyethylene wax, and — 15 (± 5) % of tackifier resin, with the following physical properties: — able to stretch to at least 200 % of its original length, — with a hysteresis of 50 (± 10) %, — with a permanent deformation of no more than 20 %, for use in the manufacture of napkins and napkin liners for babies (1)	0 %	1.7.2011- 31.12.2015
*ex 3903	90 90	86	 Mixture containing by weight: 45 % or more but not more than 65 % of polymers of styrene, 35 % or more but not more than 45 % of poly(phenylene ether), not more than 10 % of other additives, and with one or more of the following special colour effects: metallic or pearlescent with a visual angular metamerism caused by at least 0,3 % flake-based pigment, fluorescent, as characterised by emitting light during absorption of ultraviolet radiation, bright white, as characterised by L * not less than 92 and b * not more than 2 and a * between -5 and 7 on the CIELab colour scale 	0 %	1.7.2011- 31.12.2013
ex 3907	99 90	80	Copolymer, consisting of 72 % by weight or more of terephthalic acid and/or derivatives thereof and cyclohex- anedimethanol, completed with linear and/or cyclic dioles	0 %	1.7.2011- 31.12.2015

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 3909 40 00	20	Powder of thermosetting resin particles in which magnetic particles have been evenly distributed, for use in the manufacture of toner bottles for photocopiers, fax machines, printers and multifunction devices (1)	0 %	1.7.2011- 31.12.2015
ex 3911 90 99	30	1,4:5,8- Dimethanonaphthalene, 2-ethylidene- 1,2,3,4,4a,5,8,8a-octahydro-, polymer with 3a,4,7,7a- tetrahydro- 4,7-methano-1H-indene, hydrogenated	0 %	1.7.2011- 31.12.2015
ex 3911 90 99	35	Alternated copolymer of ethylene and maleic anhydride (EMA)	0 %	1.7.2011- 31.12.2015
ex 3919 90 00	63	 Co-extruded trilayer film, each layer containing a mixture of polypropylene and polyethylene, containing not more than 3 % by weight of other polymers, whether or not containing titanium dioxide in the core layer, coated with an acrylic pressure sensitive adhesive, and with a release liner, of an overall thickness of not more than 110 µm 	0 %	1.7.2011- 31.12.2015
ex 3921 90 55 *ex 7019 40 00 *ex 7019 40 00	25 21 29	Prepreg sheets or rolls containing polyimide resin	0 %	1.7.2011- 31.12.2014
ex 5603 13 10	20	 Non-woven of spunbonded polyethylene, with a coating, of a weight of more than 80 g/m² but not more than 105 g/m², and an air resistance (Gurley) of 8 seconds or more but not more than 75 seconds (as determined by the ISO 5636/5 method) 	0 %	1.7.2011- 31.12.2015
ex 7009 91 00	10	 Unframed glass mirrors with: a length of 1 516 (± 1 mm), a width of 553 (± 1 mm), a thickness of 3 (± 0,1 mm), the back of the mirror covered with protective polyethylene (PE) film, with a thickness of 0,11 mm or more but not more than 0,13 mm, a lead content of not more than 90 mg/kg, and a corrosion resistance of 72 hours or more according to ISO 9227 salt spray test 	0 %	1.7.2011- 31.12.2015
*ex 7019 19 10	10	Yarn of 33 tex or a multiple thereof (\pm 7,5 %), obtained from continuous spun-glass filaments of a nominal diameter of 3,5 µm or of 4,5 µm, in which filaments of a diameter of 3 µm or more but not more than 5,2 µm predominate, other than those treated so as to improve their adhesion to elastomers	0 %	1.7.2011- 31.12.2013
ex 7019 19 10	20	Yarn of 10,3 tex or more but not more than 11,9 tex, obtained from continuous spun-glass filaments, in which filaments of a diameter of 4,83 μ m or more but not more than 5,83 μ m predominate	0 %	1.7.2011- 31.12.2015
ex 7019 19 10	25	Yarn of 5,1 tex or more but not more than 6,0 tex, obtained from continuous glass-spun filaments, in which filaments of a diameter of 4,83 μ m or more but not more than 5,83 μ m predominate	0 %	1.7.2011- 31.12.2015

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*ex 7019 19 10	30	Yarn of E-glass of 22 tex (\pm 1,6 tex), obtained from continuous spun-glass filaments of a nominal diameter of 7 µm, in which filaments of a diameter of 6,35 µm or more but not more than 7,61 µm predominate	0 %	1.7.2011- 31.12.2013
*ex 7019 19 10	55	 Glass cord impregnated with rubber or plastic, obtained from K or U glass filaments, made up of: 9 % or more but not more than 16 % of magnesium oxide, 19 % or more but not more than 25 % of aluminium oxide, 0 % or more but not more than 2 % of boron oxide, without calcium oxide, coated with a latex comprising at least a resorcinol-formaldehyde resin and chlorosulphonated polyethylene 	0 %	1.7.2011- 31.12.2014
*ex 7019 19 10 *ex 7019 90 99	60 30	High modulus glass cord (K) impregnated with rubber, obtained from twisted high modulus glass filament yarns, coated with a latex comprising a resorcinol-formal- dehyde resin with or without vinylpyridine and/or hydro- genated acrylonitrile-butadiene rubber (HNBR)	0 %	1.7.2011- 31.12.2013
*ex 7019 19 10 *ex 7019 90 99	70 20	Glass cord impregnated with rubber or plastic, obtained from twisted glass filament yarns, coated with a latex comprising at least a resorcinol-formaldehyde- vinylpyridine resin and an acrylonitrile-butadiene rubber (NBR)	0 %	1.7.2011- 31.12.2013
*ex 7019 19 10 *ex 7019 90 99	80 10	Glass cord impregnated with rubber or plastic, obtained from twisted glass filament yarns, coated with a latex comprising at least a resorcinol-formaldehyde resin and chlorosulphonated polyethylene	0 %	1.7.2011- 31.12.2013
*ex 7019 40 00 *ex 7019 40 00	11 19	 Woven fabrics of rovings, impregnated with epoxy resin, with a coefficient of thermal expansion between 30 °C and 120 °C (measured according to IPC-TM-650) of: 10 ppm per °C or more, but not more than 12 ppm per °C in the length and width, and 20 ppm per °C or more, but not more than 30 ppm per °C in the thickness, with a glass transition temperature of 152 °C or more, but not more than 153 °C (measured according IPC-TM-650) 	0 %	1.7.2011- 31.12.2013
ex 7604 29 10 ex 7606 12 99	10 20	Sheets and bars of aluminium-lithium alloys	0 %	1.7.2011- 31.12.2015
ex 7607 20 90	20	 Lubricating entry sheet of a total thickness of not more than 350 µm, comprising of: a layer of aluminium foil of a thickness of 70 µm or more but not more than 150 µm, a water soluble lubricant of a thickness of 20 µm or more but not more than 200 µm and solid at room temperature, for use in the manufacture of printed circuit boards (1) 	0 %	1.7.2011- 31.12.2015
ex 8104 30 00	10	Magnesium powder: — of purity by weight of 98 % or more, — with a particle size of 0,2 mm or more but not more than 0,8 mm	0 %	1.7.2011- 31.12.2015

EN

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*ex 8108 90 50	60	 Plates, sheets, strips and foils of an alloy of titanium, aluminium, silicon and niobium, containing by weight: 0,4 % or more but not more than 0,6 % of aluminium, 0,35 % or more but not more than 0,55 % of silicon, and 0,1 % or more but not more than 0,3 % of niobium 	0 %	1.7.2011- 31.12.2013
ex 8302 42 00 ex 9401 90 80	80 10	Ratchet disk of a kind used in the manufacture of reclining car seats	0 %	1.7.2011- 31.12.2015
ex 8407 90 90	20	 Compact Liquid Petroleum Gas (LPG) Engine System, with: 6 cylinders, an output of 75 kW or more, but not more than 80 kW, inlet and exhaust valves modified to operate continuously in heavy duty applications, for use in the manufacture of vehicles of heading 8427 (1) 	0 %	1.7.2011- 31.12.2015
*ex 8414 30 81	50	Hermetic or semi-hermetic variable-speed electric scroll compressors, with a nominal power rating of 0,5 kW or more, but not more than 10 kW, with a displacement volume of not more than 35 cm ³ , of the type used in refrigeration equipment	0 %	1.7.2011- 31.12.2014
ex 8479 89 97 ex 8479 90 80	50 80	Machinery, being components of a production line for the manufacture of lithium ion batteries for passenger electric motor vehicles, for the construction of such a production line (1)	0 %	1.7.2011- 31.12.2015
ex 8483 40 90	80	Transmission gearbox, with: — not more than 3 gears, — an automatic deceleration system, and — a power reversal system, for use in the manufacture of goods of heading 8427 (1)	0 %	1.7.2011- 31.12.2015
*ex 8501 10 99	79	DC motor with brushes and an internal rotor with a three- phase winding, whether or not equipped with a worm, of a specified temperature range covering at least -20 °C to + 70 °C	0 %	1.7.2011- 31.12.2013
*ex 8501 31 00	40	 Permanently excited DC-motor with: a multiple-phase winding, an external diameter of 30 mm or more, but not more than 80 mm, a rated speed of not more than 15 000 rpm, an output of 45 W or more, but not more than 300 W, and a supply voltage of 9 V or more, but not more than 25 V 	0 %	1.7.2011- 31.12.2014
ex 8507 10 20	80	 Lead acid starter battery, with: a charge acceptance capacity of 200 % or more of the level of an equivalent conventional flooded battery during the first 5 seconds of charge, a liquid electrolyte, for use in the manufacture of passenger cars and light commercial vehicles employing high regenerative alternator controls or start/stop systems with high regenerative alternator controls (1) 	0 %	1.7.2011- 31.12.2015

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*ex 8507 80 30	60	 Lithium-ion rechargeable batteries, with: a length of 1 213 mm or more, but not more than 1 575 mm, a width of 245 mm or more but not more than 1 200 mm, a height of 265 mm or more, but not more than 755 mm, a weight of 265 kg or more but not more than 294 kg, a nominal capacity of 66,6 Ah, put up in packs of 48 modules 	0 %	1.7.2011- 31.12.2015
ex 8508 70 00 ex 8537 10 99	10 96	Electronic circuit card without separate housing for actuating and controlling vacuum cleaner brushes powered by not more than 300 W	0 %	1.7.2011- 31.12.2015
ex 8508 70 00 ex 8537 10 99	20 98	 Electronic circuit cards that: are connected by wire or radio frequency to each other and the motor controller card, and regulate the functioning (switching on or off and suction capacity) of vacuum cleaners according to a stored program, whether or not fitted with indicators that display the functioning of the vacuum cleaner (suction capacity and/or dust bag full and/or filter full) 	0 %	1.7.2011- 31.12.2015
*ex 8522 90 80	83	Blu-ray optical pick-up unit, whether or not recordable, for use with Blu-ray, DVD and CD discs, comprising at least: — laser diodes operating at three different wavelengths, — a photo detector integrated circuit, and — an actuator, for the manufacture of products falling within heading 8521(1)	0 %	1.7.2011- 31.12.2013
*ex 8525 80 19	31	 Closed circuit television (CCTV) camera: of a weight of not more than 5,9 kg, whether or not contained in a housing, of dimensions of not more than 400 mm × 250 mm, with a single Charge-Couple-Device (CCD) or Complementary Metal–Oxide–Semiconductor (CMOS) sensor, with effective pixels of not more than 5 megapixels, for use in CCTV surveillance systems (1) 	0 %	1.7.2011- 31.12.2013
ex 8526 91 20 ex 8528 59 80	80 10	 Integrated audio module (IAM) with a digital video output for connection to an LCD touch screen monitor, interfaced over the Media Oriented Systems Transport (MOST) network and transported over the MOST High protocol, with: a Printed circuit board (PCB) containing a Global Positioning System (GPS) receiver, a gyroscope, and a Traffic Message Channel (TMC) tuner, a hard disk drive supporting multiple maps, a HD radio, a connection to an external CD and DVD drive, Bluetooth, MP3 and USB input connectivity, a voltage of 10 V or more but not more than 16 V, for the use in the manufacture of vehicles in Chapter 87 (1) 	0 %	1.7.2011- 31.12.2015

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 8529 90 92	50	 Colour LCD display panel for LCD monitors of heading 8528: — with a diagonal measurement of the screen of 14,48 cm or more but not more than 31,24 cm, — with background lighting, micro-controller, — with a CAN (Controller area network)-controller with LVDS (Low-voltage differential signalling) interface and CAN/power supply socket or with an APIX (Automotive Pixel Link) controller with APIX interface, — in a housing with an aluminium heat sink at the back of the housing, — without a signal-processing module, for use in the manufacture of vehicles of heading 8703(1) 	0 %	1.7.2011- 31.12.2015
ex 8536 69 90	84	Universal serial bus (USB) female connector in a single or multiple form for connecting with other USB devices, for use in the manufacture of goods falling within headings 8521 and 8528 (1)	0 %	1.7.2011- 31.12.2015
ex 8536 90 85 ex 8538 90 99 ex 8543 90 00	96 94 50	Keypads, wholly of either silicone or polycarbonate, including printed keys with electrical contacting elements	0 %	1.7.2011- 31.12.2015
ex 8537 10 99	97	Electronic controller card for actuating and controlling of a single-phase electric AC commutator motor, with an output of 750 W or more and an input power of more than 1 600 W but not more than 2 700 W	0 %	1.7.2011- 31.12.2015
ex 8543 70 90	95	 Mobile telephone view and control module comprising: a mains power/CAN (Controller Area Network) output socket, a USB (Universal Serial Bus) port and audio IN/OUT ports, and incorporating a video switching device for the interface of smart phone operating systems with the Media Orientated Systems Transport network (MOST) for use in the manufacture of vehicles of Chapter 87(1) 	0 %	1.7.2011- 31.12.2015
ex 8545 90 90	20	Carbon fibre paper of a kind used for gas diffusion layers in fuel cell electrodes	0 %	1.7.2011- 31.12.2015
ex 8708 30 91	10	 Drum type parking brake: operating within the service brake disk, with a diameter of 170 mm or more but not more than 175 mm, for use in the manufacture of motor vehicles (1) 	0 %	1.7.2011- 31.12.2015
*ex 9001 20 00	10	Material consisting of a polarising film, whether or not on rolls, supported on one or both sides by transparent material, whether or not with an adhesive layer, covered on one side or on both sides with a release film	0 %	1.7.2011- 31.12.2012

(*) Suspension relating to a product in the Annex to Regulation (EC) No 1255/96 for which the CN or TARIC code or the product description is modified by this Regulation.

EN

ANNEX II

Products referred to in Article 1(2)

69
10
11
19
10
10
10
70
80
20
55
46
40
86
25
41
42
43
44
45
46
61
62
63

EN

CN code	TARIC
*ex 7019 19 10	64
*ex 7019 19 10	65
*ex 7019 19 10	66
*ex 7019 40 00	10
*ex 7019 40 00	20
*ex 7019 90 99	10
*ex 7019 90 99	20
*ex 7019 90 99	30
*ex 8108 90 50	60
*ex 8414 30 81	50
*ex 8501 10 99	79
*ex 8501 31 00	40
ex 8507 80 30	40
ex 8507 80 30	50
*ex 8507 80 30	60
*ex 8522 90 80	83
*ex 8525 80 19	31
*ex 9001 20 00	10

(*) Suspension relating to a product in the Annex to Regulation (EC) No 1255/96 for which the CN or TARIC code or the product description is modified by this Regulation.