



2025/2605

30.12.2025

COUNCIL REGULATION (EU) 2025/2605

of 12 December 2025

amending Regulation (EU) 2021/2278 suspending the Common Customs Tariff duties referred to in Article 56(2), point (c), of Regulation (EU) No 952/2013 of the European Parliament and of the Council on certain agricultural and industrial products

THE COUNCIL OF THE EUROPEAN UNION,

Having regard to the Treaty on the Functioning of the European Union, and in particular Article 31 thereof,

Having regard to the proposal from the European Commission,

Whereas:

- (1) In order to ensure a sufficient and uninterrupted supply of certain agricultural and industrial products which are not produced in the Union and thereby avoid any disturbances on the market for those products, Common Customs Tariff duties of the type referred to in Article 56(2), point (c), of Regulation (EU) No 952/2013 of the European Parliament and of the Council (⁽¹⁾) ('CCT duties') on those products have been suspended by Council Regulation (EU) 2021/2278 (⁽²⁾). As a result, the products listed in the Annex to Regulation (EU) 2021/2278 can be imported into the Union at reduced or zero duty rates without any limitation as regards their quantity.
- (2) The Union production of certain products that are not listed in the Annex to Regulation (EU) 2021/2278 is inadequate to meet the specific requirements of the user industries in the Union. As it is in the Union's interest to ensure an adequate supply of certain products and having regard to the fact that identical, equivalent or substitute products are not produced in sufficient quantities within the Union, it is necessary to grant a complete suspension of the CCT duties on those products.
- (3) With a view to promoting integrated battery production in the Union, a partial suspension of CCT duties should be granted in respect of certain products related to battery production that are currently not listed in the Annex to Regulation (EU) 2021/2278 and the Union production of which is inadequate to meet the specific requirements of the user industries in the Union. The date for the mandatory review of those suspensions should be 31 December 2026 in order for that review to take into account the short-term evolution of the battery production sector in the Union.
- (4) It is necessary to amend the product description, classification, or end-use requirement for certain products listed in the Annex to Regulation (EU) 2021/2278 in order to take into account technical product developments and economic trends in the market.
- (5) In accordance with Article 2(2) of Regulation (EU) 2021/2278 the Commission has reviewed certain CCT duty suspensions for products listed in the Annex to that Regulation. As it is in the interest of the Union to maintain those CCT duty suspensions for certain of those products, new dates should be set for their next mandatory review.
- (6) It is no longer in the interest of the Union to maintain the suspension of CCT duties for certain products listed in the Annex to Regulation (EU) 2021/2278. Those products should therefore be removed from that Annex with effect from 1 January 2026.
- (7) Regulation (EU) 2021/2278 should therefore be amended accordingly.
- (8) In order to avoid any interruption in the application of the autonomous tariff suspension scheme and to comply with the guidelines set out in the communication from the Commission of 13 December 2011 concerning autonomous tariff suspensions and quotas, the changes provided for in this Regulation regarding the tariff suspensions for the products concerned should apply from 1 January 2026. This Regulation should therefore enter into force as a matter of urgency,

(¹) Regulation (EU) No 952/2013 of the European Parliament and of the Council of 9 October 2013 laying down the Union Customs Code (OJ L 269, 10.10.2013, p. 1, ELI: <http://data.europa.eu/eli/reg/2013/952/oj>).

(²) Council Regulation (EU) 2021/2278 of 20 December 2021 suspending the Common Customs Tariff duties referred to in Article 56(2), point (c), of Regulation (EU) No 952/2013 on certain agricultural and industrial products, and repealing Regulation (EU) No 1387/2013 (OJ L 466, 29.12.2021, p. 1, ELI: <http://data.europa.eu/eli/reg/2021/2278/oj>).

HAS ADOPTED THIS REGULATION:

Article 1

The Annex to Regulation (EU) 2021/2278 is replaced by the text set out in the Annex to this Regulation.

Article 2

This Regulation shall enter into force on the day following that of its publication in the *Official Journal of the European Union*.

It shall apply from 1 January 2026.

This Regulation shall be binding in its entirety and directly applicable in all Member States.

Done at Brussels, 12 December 2025.

For the Council

The President

S. LOSE

ANNEX

'ANNEX

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.3349 | ex 0710 80 95 | 50 | Bamboo shoots, frozen, not put up for retail sale | 0 % | — | 31.12.2029 |
| 0.2829 | ex 0711 59 00 | 11 | Mushrooms, excluding mushrooms of the genera <i>Agaricus</i> , <i>Calocybe</i> , <i>Clitocybe</i> , <i>Lepista</i> , <i>Leucoagaricus</i> , <i>Leucopaxillus</i> , <i>Lyophyllum</i> and <i>Tricholoma</i> , provisionally preserved in brine, in sulphur water, or in other preservative solutions, but unsuitable in that state for immediate consumption, for the food-canning industry (¹) | 0 % | — | 31.12.2026 |
| 0.2463 | ex 0712 32 00 | 10 | Mushrooms, excluding mushrooms of the genus <i>Agaricus</i> , dried, whole or in identifiable slices or pieces, for treatment other than simple repacking for retail sale (¹) (²) | 0 % | — | 31.12.2029 |
| | ex 0712 33 00 | 10 | | | | |
| | ex 0712 34 00 | 31 | | | | |
| | ex 0712 39 00 | 31 | | | | |
| 0.3347 | ex 0804 10 00 | 30 | Dates, fresh or dried, for use in the manufacture (excluding packing) of products of drink or food industries (¹) | 0 % | — | 31.12.2029 |
| 0.3228 | ex 0811 90 95 | 20 | Boysenberries, frozen, not containing added sugar, not put up for retail sale | 0 % | — | 31.12.2029 |
| 0.2409 | ex 0811 90 95 | 30 | Pineapple (<i>Ananas comosus</i>), in pieces, frozen | 0 % | — | 31.12.2029 |
| 0.2864 | ex 1511 90 19 | 20 | Palm oil, coconut (copra) oil, palm kernel oil, for the manufacture of: | 0 % | — | 31.12.2027 |
| | ex 1511 90 91 | 20 | — industrial monocarboxylic fatty acids of subheading 3823 19 10, | | | |
| | ex 1513 11 10 | 20 | — methyl esters of fatty acids of heading 2915 or 2916, | | | |
| | ex 1513 19 30 | 20 | — fatty alcohols of subheadings 2905 17, 2905 19 and 3823 70 used for the manufacture of cosmetics, washing products or pharmaceutical products, | | | |
| | ex 1513 21 10 | 20 | — fatty alcohols of subheading 2905 16, pure or mixed, used for the manufacture of cosmetics, washing products or pharmaceutical products, | | | |
| | ex 1513 29 30 | 20 | — stearic acid of subheading 3823 11 00, | | | |
| | | | — goods of heading 3401, or | | | |
| | | | — fatty acids with high purity of heading 2915 (¹) | | | |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.3341 | ex 1515 90 99 | 92 | Vegetable oil, refined or semi-refined, containing by weight 35 % or more but not more than 57 % of arachidonic acid or 35 % or more but not more than 50 % of docosahexaenoic acid | 0 % | — | 31.12.2029 |
| 0.7686 | 1516 20 10 | | Hydrogenated castor oil, so called "opal-wax" | 0 % | — | 31.12.2029 |
| 0.4080 | ex 1517 90 99 | 30 | Vegetable and/or microbial oil, refined, containing by weight: — 25 % or more but not more than 70 % arachidonic acid and no more than 5 % docosahexaenoic acid, or — 10 % or more but not more than 80 % of eicosapentaenoic acid and a minimum ratio of EPA/(EPA+DHA) over 20 %, standardized with vegetable oil | 0 % | — | 31.12.2026 |
| 0.2423 | ex 1902 30 10 | 40 | Glass noodles containing 60 % or more by weight of mung bean starch in immediate packings of 5 kg or more and not put up for retail sale | 0 % | — | 31.12.2029 |
| 0.2866 | ex 2005 91 00 | 10 | Bamboo shoots, prepared or preserved, in immediate packings of a net content of more than 5 kg | 0 % | — | 31.12.2029 |
| 0.5875 | ex 2007 99 50 | 84 | Papaya puree concentrate, obtained by cooking: — of the genus <i>Carica</i> spp., | 7,8 % ⁽³⁾ | — | 31.12.2029 |
| | ex 2007 99 50 | 94 | — with a sugar content by weight of more than 13 % but not more than 30 % for use in the manufacture of products of food and drink industry ⁽¹⁾ | | | |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|--------------------------------|----------|--|-------------------------|--------------------|-------------------------------------|
| 0.5867 | ex 2007 99 50 ex 2007 99 50 | 85 95 | Guava puree concentrate, obtained by cooking: — of the genus <i>Psidium</i> spp., — with a sugar content by weight of more than 13 % but not more than 30 % for use in the manufacture of products of food and drink industry (¹) | 6 % (³) | — | 31.12.2029 |
| 0.4716 | *ex 2008 93 91 | 20 | Sweetened dried cranberries, for the manufacture of products of food processing industries (excluding packing or pasteurization alone as processing) (¹) (⁴) | 0 % | — | 31.12.2027 |
| 0.5587 | ex 2008 99 49 ex 2008 99 99 | 70 11 | Blanched vine leaves of the genus <i>Karakishmish</i> , in brine, containing by weight: — more than 6 % of salt concentration, — 0,1 % or more but not more than 1,4 % of acidity expressed as citric acid monohydrate and — whether or not but not more than 2 000 mg/kg of sodium benzoate according CODEX STAN 192-1995 for use in the manufacture of stuffed vine leaves with rice (¹) | 0 % | — | 31.12.2027 |
| 0.7767 | ex 2008 99 99 | 35 | Frozen pulp from acai berries: — hydrated and pasteurised, — separated from the kernels by the addition of water, — with a Brix value of less than 6, and — with a sugar content of less than 5,6 % | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.4664 | ex 2009 49 30 | 91 | Pineapple juice, other than in powder form: — with a Brix value of more than 20 but not more than 67, — a value of more than € 30 per 100 kg net weight, — containing added sugar used in the manufacture of products of food or drink industry ⁽¹⁾ | 0 % | — | 31.12.2029 |
| 0.4623 | ex 2009 81 31 | 10 | Cranberry (<i>Vaccinium macrocarpon</i>) juice concentrate: — of a Brix value of 40 or more but not more than 66, — in immediate packings of a content of 50 litres or more | 0 % | 1 | 31.12.2029 |
| 0.6050 | ex 2009 89 79 | 30 | Frozen acerola juice concentrate: — with a Brix value of more than 48 but not more than 67, — in immediate packings of a content of 50 litres or more | 0 % | 1 | 31.12.2029 |
| 0.5206 | ex 2009 89 79 | 85 | Acai berry juice concentrate: — of the species <i>Euterpe oleracea</i> , — frozen, — not sweetened, — not in powder form, — of a Brix value of 23 or more but not more than 32, in immediate packings of a content of 10 kg or more | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|--------------------------------|----------|--|-------------------------|--------------------|-------------------------------------|
| 0.4157 | ex 2009 89 99 | 96 | <p>Coconut water</p> <ul style="list-style-type: none"> — unfermented, — not containing added spirit or sugar, and — in immediate packing of a content of 20 litres or more (2) | 0 % | 1 | 31.12.2026 |
| 0.6152 | ex 2106 10 20 | 20 | Soya protein concentrate having a protein content by weight, calculated on a dry weight basis, of 65 % or more but not more than 90 % in powder or textured form | 0 % | — | 31.12.2029 |
| 0.7284 | ex 2106 90 92 ex 3504 00 90 | 50 10 | <p>Casein protein hydrolysate consisting of:</p> <ul style="list-style-type: none"> — by weight 20 % or more but not more than 70 % free amino acids, and — peptones of which by weight more than 90 % having a molecular weight of not more than 2 000 Da | 0 % | — | 31.12.2027 |
| 0.5246 | ex 2519 90 10 | 10 | Fused magnesia with a purity by weight of 94 % or more | 0 % | — | 31.12.2026 |
| 0.6168 | ex 2707 99 99 | 10 | Heavy and medium oils, whose aromatic content exceeds their non-aromatic content, for use as refinery feedstock to undergo one of the specific processes described in Additional note 5 to Chapter 27 (1) | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|--------------------------------|----------|--|-------------------------|--------------------|-------------------------------------|
| 0.8144 | *ex 2710 12 25 | 20 | Mixture of C6 aliphatic hydrocarbons (CAS RN 92112-69-1), containing by weight 60 % or more but not more than 80 % of n-hexane (CAS RN 110-54-3), with: — a specific gravity of 0,666 or more but not more than 0,686, — a total of carbonyl compounds of less than 1 ppm, — a total of acetylenic compounds of less than 2 ppm | 0 % | — | 31.12.2030 |
| 0.7823 | ex 2710 19 81 ex 2710 19 99 | 30 50 | Catalytically hydroisomerized and dewaxed base oil of hydrogenated, highly isoparaffinic hydrocarbons, containing: — 90 % or more by weight of saturates, and — not more than 0,03 % by weight of sulphur, and with — a viscosity index of 80 or more, but less than 120, and — a kinematic viscosity less than 5,0 cSt at 100 °C or more than 13,0 cSt at 100 °C | 0 % | — | 31.12.2029 |
| 0.7822 | ex 2710 19 81 ex 2710 19 99 | 40 60 | Catalytically hydroisomerized and dewaxed base oil of hydrogenated, highly isoparaffinic hydrocarbons, containing: — 90 % or more by weight of saturates, and — not more than 0,03 % by weight of sulphur, with a viscosity index of 120 or more | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.6495 | ex 2710 19 99 | 20 | Catalytic de-waxed base oil, synthesised from gaseous hydrocarbons, followed by a heavy paraffin conversion process (HPC), containing: — not more than 1 mg/kg of sulphur — more than 99 % by weight of saturated hydrocarbons — more than 75 % by weight of n- and iso-paraffinic hydrocarbons with a carbon chain length of 18 or more but not more than 50; and — a kinematic viscosity at 40 °C of more than 6,5 mm ² /s, or — a kinematic viscosity at 40 °C of more than 11 mm ² /s with a viscosity index of 120 or more | 0 % | — | 31.12.2029 |
| 0.7393 | ex 2712 90 99 | 10 | Blend of 1-alkenes containing by weight 90 % or more 1-alkenes of a chain length of 24 carbon atoms or more but not more than 1 % 1-alkenes of a chain length of more than 70 carbon atoms | 0 % | — | 31.12.2027 |
| 0.8021 | 2804 70 10 | | Red phosphorus | 0 % | — | 31.12.2027 |
| 0.8022 | 2804 70 90 | | Phosphorus, other than red phosphorus | 0 % | — | 31.12.2029 |
| 0.6658 | *ex 2805 12 00 | 10 | Calcium with a purity of 98 % or more by weight, in powder or wire form (CAS RN 7440-70-2) | 0 % | — | 31.12.2030 |
| 0.5609 | ex 2805 19 90 | 20 | Lithium metal (CAS RN 7439-93-2) of a purity by weight of 98,8 % or more | 0 % | — | 31.12.2027 |
| 0.2559 | ex 2805 30 10 | 10 | Alloy of cerium and other rare-earth metals, containing by weight 47 % or more of cerium | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.4979 | *2805 30 21 2805 30 29 2805 30 31 2805 30 39 2805 30 40 | | Rare-earth metals, scandium and yttrium, of a purity by weight of 95 % or more | 0 % | — | 31.12.2030 |
| 0.6836 | ex 2811 22 00 | 15 | Amorphous silicon dioxide (CAS RN 60676-86-0) — in the form of powder — of a purity by weight of 99,0 % or more — with a median grain size of 0,7 µm or more, but not more than 2,1 µm — where 70 % of the particles have a diameter of not more than 3 µm | 0 % | — | 31.12.2029 |
| 0.8865 | ex 2811 22 00 | 80 | Amorphous silicon dioxide (CAS RN 112926-00-8), — in the form of powder, — of a purity by weight of 98 % or more, — with a median grain size of 150 µm or more, but not more than 250 µm, — where 90 % of the particles have a diameter of more than 3 µm, for use in the manufacture of tyres ⁽¹⁾ | 0 % | — | 31.12.2029 |
| 0.7292 | ex 2811 29 90 | 10 | Tellurium dioxide (CAS RN 7446-07-3) | 0 % | — | 31.12.2027 |
| 0.3308 | ex 2812 90 00 | 10 | Nitrogen trifluoride (CAS RN 7783-54-2) | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|--------------------------------|----------|---|-------------------------|--------------------|-------------------------------------|
| 0.5747 | ex 2816 40 00 | 10 | Barium hydroxide (CAS RN 17194-00-2) | 0 % | — | 31.12.2027 |
| 0.7594 | ex 2818 10 11 | 10 | Sol-Gel corundum (CAS RN 1302-74-5) with an aluminium oxide content of 99,6 % or more by weight, having a micro crystalline structure in the form of rods with an aspect ratio of 1,3 or more, but not more than 6,0 | 0 % | — | 31.12.2029 |
| 0.8425 | ex 2818 10 11 ex 2818 10 91 | 20 30 | Sintered corundum with a micro crystalline structure, consisting of aluminium oxide (CAS RN 1344-28-1) and magnesium aluminate (CAS RN 12068-51-8), with a content by weight (calculated as oxides) of: — 92 % or more of aluminium oxide, and — 8 % or less of magnesium oxide | 0 % | — | 31.12.2027 |
| 0.5110 | *ex 2818 10 91 | 20 | Sintered corundum with a micro crystalline structure, consisting of aluminium oxide (CAS RN 1344-28-1), magnesium aluminate (CAS RN 12068-51-8) and the rare earth aluminates of yttrium, lanthanum, and neodymium, with a content by weight (calculated as oxides) of: — 92 % or more, but less than 98,5 % of aluminium oxide, — 2 % (\pm 1,5 %) of magnesium oxide, — 1 % (\pm 0,6 %) of yttrium oxide, and — either 3 % (\pm 2,2 %) of lanthanum oxide or — 2 % (\pm 1,2 %) of lanthanum oxide and neodymium oxide, with less than 50 % of the total weight having a particle size of more than 10 mm | 0 % | — | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.4640 | ex 2818 20 00 | 10 | Activated alumina with a specific surface area of at least 350 m ² /g | 0 % | — | 31.12.2029 |
| 0.6837 | *ex 2818 30 00 | 20 | Aluminium hydroxide (CAS RN 21645-51-2) — in the form of powder, — with a purity by weight of 99,5 % or more, — with a decomposition point of 263 °C or more, — with a particle size of 4 µm (± 1 µm), — with a Total-Na ₂ O-content by weight of not more than 0,06 % | 0 % | — | 31.12.2030 |
| 0.3306 | ex 2818 30 00 | 30 | Aluminium hydroxide oxide in the form of boehmite or pseudoboehmite (CAS RN 1318-23-6) | 0 % | — | 31.12.2029 |
| 0.5369 | ex 2819 90 90 | 10 | Dichromium trioxide (CAS RN 1308-38-9) for use in metallurgy (¹) | 0 % | — | 31.12.2026 |
| 0.5576 | ex 2825 10 00 | 10 | Hydroxylammonium chloride (CAS RN 5470-11-1) | 0 % | — | 31.12.2027 |
| 0.7897 | *ex 2825 20 00 | 10 | Lithium hydroxide monohydrate (CAS RN 1310-66-3) with a purity by weight of 99 % or more | 2,6 % | — | 31.12.2026 |
| 0.3800 | 2825 30 00 | | Vanadium oxides and hydroxides | 0 % | — | 31.12.2026 |
| 0.3303 | ex 2825 50 00 | 20 | Copper (I or II) oxide containing by weight 78 % or more of copper and not more than 0,03 % of chloride | 0 % | — | 31.12.2029 |
| 0.6819 | *ex 2825 50 00 | 30 | Copper (II) oxide (CAS RN 1317-38-0), with a particle size of not more than 100 nm | 0 % | — | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.5555 | ex 2825 60 00 | 10 | Zirconium dioxide (CAS RN 1314-23-4) | 0 % | — | 31.12.2027 |
| 0.7193 | ex 2825 70 00 | 20 | Molybdic Acid (CAS RN 7782-91-4) | 0 % | — | 31.12.2026 |
| 0.5055 | *ex 2826 19 90 | 10 | Tungsten hexafluoride (CAS RN 7783-82-6) with a purity by weight of 99,9 % or more | 0 % | — | 31.12.2030 |
| 0.8296 | *ex 2826 90 80 | 30 | Lithium hexafluorophosphate (CAS RN 21324-40-3) with a purity by weight of 99 % or more | 2,7 % | — | 31.12.2026 |
| 0.2865 | *ex 2827 39 85 | 10 | Copper monochloride (CAS RN 7758-89-6) with a purity by weight of 96 % or more | 0 % | — | 31.12.2029 |
| 0.4180 | ex 2827 39 85 | 20 | Antimony pentachloride (CAS RN 7647-18-9) of a purity by weight of 99 % or more | 0 % | — | 31.12.2026 |
| 0.6143 | ex 2827 39 85 | 40 | Barium chloride dihydrate (CAS RN 10326-27-9) | 0 % | — | 31.12.2029 |
| 0.8936 | *ex 2827 49 90 | 10 | Zirconium dichloride oxide (CAS RN 7699-43-6) with a purity by weight of 95 % or more | 0 % | — | 31.12.2030 |
| 0.6463 | ex 2827 60 00 | 10 | Sodium iodide (CAS RN 7681-82-5) | 0 % | — | 31.12.2029 |
| 0.7596 | ex 2828 10 00 | 10 | Calcium hypochlorite (CAS RN 7778-54-3) having an active chlorine content of 65 % or more | 0 % | — | 31.12.2029 |
| 0.3859 | ex 2833 29 80 | 20 | Manganese sulphate monohydrate (CAS RN 10034-96-5) | 0 % | — | 31.12.2029 |
| 0.4338 | ex 2835 10 00 | 10 | Sodium hypophosphite monohydrate (CAS RN 10039-56-2) | 0 % | — | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.6144 | ex 2835 10 00 | 20 | Sodium hypophosphite (CAS RN 7681-53-0) | 0 % | — | 31.12.2029 |
| 0.7452 | ex 2835 10 00 | 30 | Aluminium Phosphinate (CAS RN 7784-22-7) | 0 % | — | 31.12.2029 |
| 0.8448 | ex 2835 10 00 | 40 | Calcium phosphinate (CAS RN 7789-79-9) with a purity by weight of 98 % or more | 0 % | — | 31.12.2027 |
| 0.2524 | ex 2836 91 00 | 20 | <p>Lithium carbonate, containing one or more of the following impurities at the concentrations indicated:</p> <ul style="list-style-type: none"> — 2 mg/kg or more of arsenic, — 200 mg/kg or more of calcium, — 200 mg/kg or more of chlorides, — 20 mg/kg or more of iron, — 150 mg/kg or more of magnesium, — 20 mg/kg or more of heavy metals, — 300 mg/kg or more of potassium, — 300 mg/kg or more of sodium, — 200 mg/kg or more of sulphates, <p>determined according to the methods specified in the European Pharmacopœia</p> | 0 % | — | 31.12.2029 |
| 0.2863 | ex 2836 99 17 | 30 | Zirconium (IV) basic carbonate (CAS RN 57219-64-4 or 37356-18-6) with a purity by weight of 96 % or more | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.3300 | ex 2837 19 00 | 20 | Copper cyanide (CAS RN 544-92-3) | 0 % | — | 31.12.2029 |
| 0.4078 | ex 2837 20 00 | 10 | Tetrasodium hexacyanoferrate (II) (CAS RN 13601-19-9) | 0 % | — | 31.12.2026 |
| 0.2861 | ex 2839 90 00 | 20 | Calcium silicate (CAS RN 1344-95-2) | 0 % | — | 31.12.2029 |
| 0.6632 | *ex 2840 20 90 | 10 | Zinc borate (CAS RN 12767-90-7) | 0 % | — | 31.12.2030 |
| 0.8520 | ex 2840 20 90 | 20 | Barium borate (CAS RN 13701-59-2) with a purity by weight of 99 % or more | 0 % | — | 31.12.2027 |
| 0.6482 | ex 2841 70 00 | 30 | Hexaammonium heptamolybdate, anhydrous (CAS RN 12027-67-7) or as tetrahydrate (CAS RN 12054-85-2) | 0 % | — | 31.12.2029 |
| 0.4323 | ex 2841 80 00 | 10 | Diammonium wolframate (ammonium paratungstate) (CAS RN 11120-25-5) | 0 % | — | 31.12.2027 |
| 0.8441 | ex 2841 80 00 | 20 | Disodium wolframate (CAS RN 13472-45-2) with a purity by weight of 90 % or more | 0 % | — | 31.12.2027 |
| 0.7301 | ex 2841 90 30 | 10 | Potassium metavanadate (CAS RN 13769-43-2) | 0 % | — | 31.12.2027 |
| 0.5936 | ex 2841 90 70 | 20 | Potassium titanium oxide (CAS RN 12056-51-8) in powder form with a purity of 99 % or more | 0 % | — | 31.12.2029 |
| 0.4416 | ex 2842 10 00 | 10 | Synthetic beta zeolite powder | 0 % | — | 31.12.2029 |
| 0.4588 | ex 2842 10 00 | 20 | Synthetic chabasite zeolite powder | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.7397 | ex 2842 10 00 | 50 | Fluorphlogopite (CAS RN 12003-38-2) | 0 % | — | 31.12.2027 |
| 0.7097 | ex 2842 10 00 | 60 | Aluminosilicate (CAS RN 1318-02-1) with <ul style="list-style-type: none">— a purity by weight of 94 % or more,— a zeolite structure of aluminophosphate-eighteen (AEI), and— a phase purity of 90 % or more for use in the manufacture of copper zeolite (¹) | 0 % | — | 31.12.2026 |
| 0.4642 | ex 2842 90 10 | 10 | Sodium selenate (CAS RN 13410-01-0) | 0 % | — | 31.12.2029 |
| 0.3295 | 2845 10 00 | | Heavy water (deuterium oxide) (Euratom) (CAS RN 7789-20-0) | 0 % | — | 31.12.2029 |
| 0.4189 | 2845 40 00 | | Helium-3 (CAS RN 14762-55-1) | 0 % | — | 31.12.2026 |
| 0.3297 | 2845 90 10 | | Deuterium and compounds thereof; hydrogen and compounds thereof, enriched in deuterium; mixtures and solutions containing these products (Euratom) | 0 % | — | 31.12.2029 |
| 0.4191 | ex 2845 90 90 | 20 | Water enriched at a level of 95 % or more by weight with oxygen-18 (CAS RN 14314-42-2) | 0 % | — | 31.12.2029 |
| 0.4190 | ex 2845 90 90 | 30 | (¹³C)Carbon monoxide (CAS RN 1641-69-6) | 0 % | — | 31.12.2026 |
| 0.8426 | ex 2845 90 90 | 50 | Ytterbium oxide (CAS RN 1380743-42-9), with a purity by weight of 99 % or more, enriched to 99,0 % or more but not more than 99,8 % of Ytterbium-176 | 0 % | — | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|--|----------|---|-------------------------|--------------------|-------------------------------------|
| 0.2859 | ex 2846 10 00 ex 3824 99 96 | 10 53 | Rare-earth concentrate containing by weight 60 % or more but not more than 95 % of rare-earth oxides and not more than 1 % each of zirconium oxide, aluminium oxide or iron oxide, and having a loss on ignition of 5 % or more by weight | 0 % | — | 31.12.2029 |
| 0.3296 | ex 2846 10 00 | 20 | Dicerium tricarbonate (CAS RN 537-01-9), whether or not hydrated | 0 % | — | 31.12.2029 |
| 0.3420 | ex 2846 10 00 | 30 | Cerium lanthanum carbonate, whether or not hydrated | 0 % | — | 31.12.2029 |
| 0.3227 | 2846 90 30 2846 90 40 2846 90 50 2846 90 60 2846 90 70 2846 90 90 | | Compounds, inorganic or organic, of rare-earth metals, of yttrium or of scandium or of mixtures of these metals, other than those of subheading 2846 10 00 | 0 % | — | 31.12.2029 |
| 0.3418 | ex 2850 00 20 | 10 | Silane (CAS RN 7803-62-5) | 0 % | — | 31.12.2029 |
| 0.5497 | ex 2850 00 20 | 40 | Germanium tetrahydride (CAS RN 7782-65-2) | 0 % | — | 31.12.2026 |
| 0.7302 | ex 2850 00 20 | 60 | Disilane (CAS RN 1590-87-0) | 0 % | — | 31.12.2027 |
| 0.7555 | ex 2850 00 20 | 70 | Cubic Boron nitride (CAS RN 10043-11-5) | 0 % | — | 31.12.2029 |
| 0.3419 | *ex 2850 00 20 | 80 | Arsine (CAS RN 7784-42-1) with a purity by volume of 99,999 % or more, for use in the production of semiconductors (1) | 0 % | — | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.4492 | ex 2850 00 60 | 10 | Sodium azide (CAS RN 26628-22-8) | 0 % | — | 31.12.2029 |
| 0.3421 | ex 2853 90 90 | 20 | Phosphine (CAS RN 7803-51-2) | 0 % | — | 31.12.2029 |
| 0.8282 | ex 2903 19 00 | 20 | 1,3-Dichloropropane (CAS RN 142-28-9) with a purity by weight of 99 % or more | 0 % | — | 31.12.2026 |
| 0.8906 | *ex 2903 29 00 | 20 | <i>trans</i> -1,2-Dichloroethylene (CAS RN 156-60-5) with a purity by weight of 99 % or more | 0 % | — | 31.12.2030 |
| 0.6633 | *2903 42 00 | | Disfluoromethane (CAS RN 75-10-5) | 0 % | — | 31.12.2030 |
| 0.2854 | ex 2903 49 30 | 10 | Carbon tetrafluoride (tetrafluoromethane) (CAS RN 75-73-0) | 0 % | — | 31.12.2029 |
| 0.2852 | ex 2903 49 30 | 20 | Perfluoroethane (CAS RN 76-16-4) | 0 % | — | 31.12.2029 |
| 0.5803 | ex 2903 51 00 | 10 | 2,3,3,3-Tetrafluoroprop-1-ene (2,3,3,3-tetrafluoropropene) (CAS RN 754-12-1) | 0 % | — | 31.12.2027 |
| 0.4517 | ex 2903 51 00 | 20 | <i>Trans</i> -1,3,3,3-tetrafluoroprop-1-ene (<i>Trans</i> -1,3,3,3-tetrafluoropropene) (CAS RN 29118-24-9) | 0 % | — | 31.12.2029 |
| 0.4066 | ex 2903 59 00 | 30 | Hexafluoropropene (CAS RN 116-15-4) | 0 % | — | 31.12.2026 |
| 0.7324 | ex 2903 59 00 | 40 | 1,1,2,3,4,4-Hexafluorobuta-1,3-diene (CAS RN 685-63-2) | 0 % | — | 31.12.2027 |
| 0.8553 | ex 2903 69 19 | 25 | (E)-1,4-Dibrombut-2-ene (CAS RN 821-06-7) with a purity by weight of 98 % or more | 0 % | — | 31.12.2028 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8525 | ex 2903 69 19 | 35 | 2,2-Dibromopropane (CAS RN 594-16-1) with a purity by weight of 99 % or more | 0 % | — | 31.12.2028 |
| 0.7974 | *ex 2903 69 19 | 40 | 3-(Bromomethyl)pentane (CAS RN 3814-34-4) with a purity by weight of 99 % or more | 0 % | — | 31.12.2026 |
| 0.8318 | ex 2903 69 19 | 50 | Vinyl bromide (CAS RN 593-60-2) with a purity by weight of 98 % or more, or as a solution in tetrahydrofuran (CAS RN 109-99-9) containing by weight 23 % or more, but not more than 26 % vinylbromide | 0 % | — | 31.12.2027 |
| 0.8151 | ex 2903 69 19 | 60 | 1-Bromo-2-methylpropane (CAS RN 78-77-3) with a purity by weight of 99 % or more | 0 % | — | 31.12.2026 |
| 0.7895 | ex 2903 72 00 | 10 | Dichloro-1,1,1-trifluoroethane (CAS RN 306-83-2) with a purity by weight of 99 % or more | 0 % | — | 31.12.2029 |
| 0.5212 | ex 2903 77 90 | 10 | Chlorotrifluoroethylene (CAS RN 79-38-9) | 0 % | — | 31.12.2026 |
| 0.6485 | ex 2903 79 30 | 10 | Trans-1-chloro-3,3,3-trifluoropropene (CAS RN 102687-65-0) | 0 % | — | 31.12.2029 |
| 0.5765 | ex 2903 89 70 | 50 | Chlorocyclopentane (CAS RN 930-28-9) | 0 % | — | 31.12.2027 |
| 0.7304 | ex 2903 89 70 | 60 | Octafluorocyclobutane (CAS RN 115-25-3) | 0 % | — | 31.12.2027 |
| 0.8803 | ex 2903 99 80 | 10 | 4-Bromo-2-fluorobiphenyl (CAS RN 41604-19-7) with a purity by weight of 99 % or more | 0 % | — | 31.12.2029 |
| 0.8492 | ex 2903 99 80 | 18 | 1-Fluoronaphthalene (CAS RN 321-38-0) with a purity by weight of 99 % or more | 0 % | — | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.3410 | ex 2903 99 80 | 20 | 1,2-Bis(pentabromophenyl)ethane (CAS RN 84852-53-9) | 0 % | — | 31.12.2029 |
| 0.8557 | ex 2903 99 80 | 23 | 3,5-Bis(trifluoromethyl) benzylbromide (CAS RN 32247-96-4) with a purity by weight of 95 % or more | 0 % | — | 31.12.2028 |
| 0.8017 | *ex 2903 99 80 | 25 | 2,2'-Dibromobiphenyl (CAS RN 13029-09-9) with a purity by weight of 95 % or more | 0 % | — | 31.12.2030 |
| 0.8018 | *ex 2903 99 80 | 35 | 2-Bromo-9,9'-spirobi[9H-fluoren] (CAS RN 171408-76-7) with a purity by weight of 95 % or more | 0 % | — | 31.12.2030 |
| 0.3411 | ex 2903 99 80 | 40 | 2,6-Dichlorotoluene (CAS RN 118-69-4), of a purity by weight of 99 % or more and containing: — 0,001 mg/kg or less of tetrachlorodibenzodioxines, — 0,001 mg/kg or less of tetrachlorodibenzofurans, — 0,2 mg/kg or less of tetrachlorobiphenyls | 0 % | — | 31.12.2029 |
| 0.8076 | *ex 2903 99 80 | 45 | 1-Bromo-4-(<i>trans</i> -4-propylcyclohexyl)benzene (CAS RN 86579-53-5) with a purity by weight of 95 % or more | 0 % | — | 31.12.2030 |
| 0.4529 | ex 2903 99 80 | 50 | Fluorobenzene (CAS RN 462-06-6) | 0 % | — | 31.12.2029 |
| 0.8101 | *ex 2903 99 80 | 55 | 1-Bromo-4-(<i>trans</i> -4-ethylcyclohexyl)benzene (CAS RN 91538-82-8) with a purity by weight of 95 % or more | 0 % | — | 31.12.2030 |
| 0.8166 | ex 2903 99 80 | 65 | 2,6-Difluorobenzyl bromide (CAS RN 85118-00-9) with a purity by weight of 97 % or more | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.8177 | ex 2903 99 80 | 70 | 1-[Chloro(phenyl)methyl]-2-methylbenzene (CAS RN 41870-52-4) with a purity by weight of 99 % or more | 0 % | — | 31.12.2026 |
| 0.5917 | *ex 2903 99 80 | 83 | 1-Bromo-3,4,5-trifluorobenzene (CAS RN 138526-69-9) with a purity by weight of 99 % or more | 0 % | — | 31.12.2029 |
| 0.3407 | ex 2904 10 00 | 30 | Sodium p-styrenesulphonate (CAS RN 2695-37-6) | 0 % | — | 31.12.2029 |
| 0.4686 | ex 2904 10 00 | 50 | Sodium 2-methylprop-2-ene-1-sulphonate (CAS RN 1561-92-8) | 0 % | — | 31.12.2029 |
| 0.3409 | *ex 2904 20 00 | 10 | Nitromethane (CAS RN 75-52-5) | 0 % | — | 31.12.2030 |
| 0.3391 | ex 2904 20 00 | 20 | Nitroethane (CAS RN 79-24-3) | 0 % | — | 31.12.2027 |
| 0.3408 | *ex 2904 20 00 | 30 | 1-Nitropropane (CAS RN 108-03-2) | 0 % | — | 31.12.2030 |
| 0.3390 | ex 2904 20 00 | 40 | 2-Nitropropane (CAS RN 79-46-9) | 0 % | — | 31.12.2029 |
| 0.2526 | ex 2904 99 00 | 20 | 1-Chloro-2,4-dinitrobenzene (CAS RN 97-00-7) | 0 % | — | 31.12.2029 |
| 0.6612 | *ex 2904 99 00 | 25 | Difluoromethanesulphonyl chloride (CAS RN 1512-30-7) | 0 % | — | 31.12.2030 |
| 0.3388 | ex 2904 99 00 | 30 | Tosyl chloride (CAS RN 98-59-9) | 0 % | — | 31.12.2029 |
| 0.5745 | ex 2904 99 00 | 40 | 4-Chlorobenzenesulphonyl chloride (CAS RN 98-60-2) | 0 % | — | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.6001 | ex 2904 99 00 | 50 | Ethanesulphonyl chloride (CAS RN 594-44-5) | 0 % | — | 31.12.2029 |
| 0.7957 | *ex 2904 99 00 | 55 | 2,4-Dichloro-1,3-dinitro-5-(trifluoromethyl)benzene (CAS RN 29091-09-6) with a purity by weight of 96 % or more | 0 % | — | 31.12.2030 |
| 0.6407 | ex 2904 99 00 | 60 | 4,4'-Dinitrostilbene-2,2'-disulfonic acid (CAS RN 128-42-7) | 0 % | — | 31.12.2029 |
| 0.8160 | ex 2904 99 00 | 65 | 4-Nitrotoluene-2-sulphonic acid (CAS RN 121-03-9) in powder form, with a purity by weight of 80 % or more and a content of water by weight of 15 % or more | 0 % | — | 31.12.2026 |
| 0.6560 | ex 2904 99 00 | 80 | 1-Chloro-2-nitrobenzene (CAS RN 88-73-3) | 0 % | — | 31.12.2029 |
| 0.6186 | ex 2905 11 00 | 10 | Methanol (CAS RN 67-56-1) with a purity of 99,85 % by weight or more | 0 % | — | 31.12.2029 |
| 0.2967 | ex 2905 19 00 | 11 | Potassium tert-butanolate (CAS RN 865-47-4), whether or not in the form of a solution in tetrahydrofuran according to note 1e) to Chapter 29 of the CN | 0 % | — | 31.12.2029 |
| 0.6118 | ex 2905 19 00 | 20 | Butyltitanate monohydrate, homopolymer (CAS RN 162303-51-7) | 0 % | — | 31.12.2029 |
| 0.6119 | ex 2905 19 00 | 25 | Tetra-(2-ethylhexyl) titanate (CAS RN 1070-10-6) | 0 % | — | 31.12.2029 |
| 0.5534 | ex 2905 19 00 | 70 | Titanium tetrabutanolate (CAS RN 5593-70-4) | 0 % | — | 31.12.2027 |
| 0.5533 | ex 2905 19 00 | 80 | Titanium tetraisopropoxide (CAS RN 546-68-9) | 0 % | — | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.6002 | ex 2905 19 00 | 85 | Titanium tetraethanolate (CAS RN 3087-36-3) | 0 % | — | 31.12.2029 |
| 0.6464 | ex 2905 22 00 | 10 | Linalool (CAS RN 78-70-6) containing by weight 90,7 % or more of (3R)-(-)-Linalool (CAS RN 126-91-0) | 0 % | — | 31.12.2029 |
| 0.7114 | *ex 2905 22 00 | 30 | (±)- β -Citronellol (CAS RN 106-22-9) with a purity by weight of 94 % or more | 0 % | — | 31.12.2026 |
| 0.7388 | ex 2905 29 90 | 10 | Cis-hex-3-en-1-ol (CAS RN 928-96-1) | 0 % | — | 31.12.2027 |
| 0.8544 | ex 2905 39 95 | 15 | 2,5-Dimethylhexane-2,5-diol (CAS RN 110-03-2) with a purity by weight of 98 % or more | 0 % | — | 31.12.2028 |
| 0.8619 | ex 2905 39 95 | 25 | Pinacol (CAS RN 76-09-5) with a purity by weight of 98 % or more | 0 % | — | 31.12.2028 |
| 0.5255 | ex 2905 39 95 | 30 | 2,4,7,9-Tetramethyl-4,7-decanediol (CAS RN 17913-76-7) | 0 % | — | 31.12.2026 |
| 0.8937 | *ex 2905 39 95 | 35 | Propane-1,3-diol (CAS RN 504-63-2) with a purity by weight of 99 % or more | 0 % | — | 31.12.2030 |
| 0.5847 | ex 2905 39 95 | 40 | Decane-1,10-diol (CAS RN 112-47-0) | 0 % | — | 31.12.2027 |
| 0.8932 | *ex 2905 39 95 | 45 | 2,5,7,10,11,14-hexaoxa-1,6-distibabicyclo[4.4.4]tetradecane (CAS RN 29736-75-2) with a purity by weight of 99 % or more | 0 % | — | 31.12.2030 |
| 0.5908 | ex 2905 39 95 | 50 | 2-Methyl-2-propylpropane-1,3-diol (CAS RN 78-26-2) | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.7701 | ex 2905 39 95 | 60 | Dodecane-1,12-diol (CAS RN 5675-51-4) | 0 % | — | 31.12.2029 |
| 0.7914 | ex 2905 39 95 | 70 | 2-Methylpropane-1,3-diol (CAS RN 2163-42-0) with a purity by weight of 98 % or more | 0 % | — | 31.12.2029 |
| 0.8370 | ex 2905 39 95 | 80 | Pentane-1,5-diol (CAS RN 111-29-5) with a purity by weight of 97 % or more | 0 % | — | 31.12.2027 |
| 0.4624 | ex 2905 59 98 | 20 | 2,2,2-Trifluoroethanol (CAS RN 75-89-8) | 0 % | — | 31.12.2029 |
| 0.3378 | ex 2906 19 00 | 10 | Cyclohex-1,4-ylenedimethanol (CAS RN 105-08-8) | 0 % | — | 31.12.2027 |
| 0.3380 | ex 2906 19 00 | 20 | 4,4'-Isopropylidenedicyclohexanol (CAS RN 80-04-6) | 0 % | — | 31.12.2029 |
| 0.6257 | ex 2906 19 00 | 50 | 4- <i>tert</i> -Butylcyclohexanol (CAS RN 98-52-2) | 0 % | — | 31.12.2029 |
| 0.8231 | ex 2906 19 00 | 60 | 5-Methyl-2-(prop-1-en-2-yl)cyclohexanol, mixture of isomers (CAS RN 7786-67-6) with a purity by weight of 90 % or more | 0 % | — | 31.12.2026 |
| 0.8721 | ex 2906 19 00 | 70 | (1 <i>S</i> ,2 <i>S</i> ,3 <i>R</i> ,5 <i>S</i>)-(+)2,3-Pinanediol (CAS RN 18680-27-8) with a purity by weight of 98 % or more | 0 % | — | 31.12.2029 |
| 0.8929 | *ex 2906 29 00 | 25 | (2-Bromo-5-iodophenyl)methanol (CAS RN 946525-30-0) with a purity by weight of 98 % or more | 0 % | — | 31.12.2030 |
| 0.7373 | ex 2906 29 00 | 50 | 2,2'-(<i>m</i> -Phenylene)dipropan-2-ol (CAS RN 1999-85-5) | 0 % | — | 31.12.2027 |
| 0.7806 | ex 2906 29 00 | 60 | 3-[3-(Trifluoromethyl)phenyl]propan-1-ol (CAS RN 78573-45-2) | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.5855 | ex 2906 29 00 | 85 | 2-Phenylethanol (CAS RN 60-12-8) with a purity by weight of 95 % or more | 0 % | — | 31.12.2027 |
| 0.6329 | ex 2907 12 00 | 20 | Mixture of meta-cresol (CAS RN 108-39-4) and para-cresol (CAS RN 106-44-5) with a purity by weight of 99 % or more | 0 % | — | 31.12.2029 |
| 0.6559 | *ex 2907 12 00 | 40 | p-Cresol (CAS RN 106-44-5) with a purity by weight of 99 % or more | 0 % | — | 31.12.2029 |
| 0.5216 | ex 2907 15 90 | 10 | 2-Naphthol (CAS RN 135-19-3) | 0 % | — | 31.12.2026 |
| 0.6256 | *ex 2907 19 10 | 20 | 2,6-Xylenol (CAS RN 576-26-1) with a purity by weight of 99 % or more | 0 % | — | 31.12.2029 |
| 0.4480 | ex 2907 19 90 | 20 | Biphenyl-4-ol (CAS RN 92-69-3) | 0 % | — | 31.12.2029 |
| 0.7753 | ex 2907 19 90 | 30 | 2-Methyl-5-(propan-2-yl)phenol (CAS RN 499-75-2) | 0 % | — | 31.12.2029 |
| 0.3372 | ex 2907 21 00 | 10 | Resorcinol (CAS RN 108-46-3) | 0 % | — | 31.12.2029 |
| 0.8482 | ex 2907 29 00 | 13 | 4,4'-Methylenedi-2,6-xylenol (CAS RN 5384-21-4) with a purity by weight of 98,5 % or more | 0 % | — | 31.12.2027 |
| 0.6026 | ex 2907 29 00 | 15 | 6,6'-Di-tert-butyl-4,4'-butylienedi-m-cresol (CAS RN 85-60-9) | 0 % | — | 31.12.2029 |
| 0.3367 | ex 2907 29 00 | 30 | 4,4',4"-Ethylidynetriphenol (CAS RN 27955-94-8) | 0 % | — | 31.12.2029 |
| 0.2584 | *ex 2907 29 00 | 33 | 2,2',2",6,6',6"-Hexa-tert-butyl- α , α ', α "-(mesitylen-2,4,6-triyl)tri-p-cresol (CAS RN 1709-70-2) with a purity by weight of 98 % or more | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.7402 | *ex 2907 29 00 | 38 | Biphenyl-4,4'-diol (CAS RN 92-88-6) with a purity by weight of 99 % or more | 0 % | — | 31.12.2029 |
| 0.5432 | ex 2907 29 00 | 45 | 2-Methylhydroquinone (CAS RN 95-71-6) | 0 % | — | 31.12.2026 |
| 0.3848 | ex 2907 29 00 | 85 | Phloroglucinol anhydrous (CAS RN 108-73-6) or phloroglucinol dihydrate (CAS RN 6099-90-7) with a purity by weight of 95 % or more | 0 % | — | 31.12.2029 |
| 0.5914 | ex 2908 19 00 | 20 | 4,4'-(Perfluoroisopropylidene)diphenol (CAS RN 1478-61-1) | 0 % | — | 31.12.2029 |
| 0.6260 | ex 2908 19 00 | 30 | 4-Chlorophenol (CAS RN 106-48-9) | 0 % | — | 31.12.2029 |
| 0.8204 | ex 2908 19 00 | 70 | 2,3,6-Trifluorophenol (CAS RN 113798-74-6) with a purity by weight of 98 % or more | 0 % | — | 31.12.2026 |
| 0.3359 | ex 2909 19 90 | 30 | Mixture of isomers of nonafluorobutyl methyl ether or nonafluorobutyl ethyl ether, of a purity by weight of 99 % or more | 0 % | — | 31.12.2029 |
| 0.4035 | ex 2909 19 90 | 50 | 3-Ethoxy-perfluoro-2-methylhexane (CAS RN 297730-93-9) | 0 % | — | 31.12.2026 |
| 0.5407 | ex 2909 20 00 | 10 | 8-Methoxycedrane (CAS RN 19870-74-7) | 0 % | — | 31.12.2026 |
| 0.5503 | ex 2909 30 39 | 20 | 1,1'-Propane-2,2-diylbis[3,5-dibromo-4-(2,3-dibromopropoxy)benzene] (CAS RN 21850-44-2) | 0 % | — | 31.12.2026 |
| 0.6649 | *ex 2909 30 39 | 30 | 1,1'-(1-Methylethylidene)bis[3,5-dibromo-4-(2,3-dibromo-2-methylpropoxy)]-benzene (CAS RN 97416-84-7) | 0 % | — | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.7828 | ex 2909 30 39 | 50 | 2-(1-Adamantyl)-4-Bromoanisole (CAS RN 104224-63-7) with a purity by weight of 99 % or more | 0 % | — | 31.12.2029 |
| 0.4710 | ex 2909 30 90 | 10 | 2-(Phenylmethoxy)naphthalene (CAS RN 613-62-7) | 0 % | — | 31.12.2029 |
| 0.7176 | ex 2909 30 90 | 15 | [(2,2-Dimethylbut-3-yn-1-yl)oxy]methyl]benzene (CAS RN 1092536-54-3) | 0 % | — | 31.12.2026 |
| 0.4711 | ex 2909 30 90 | 20 | 1,2-Bis(3-methyl-phenoxy)ethane (CAS RN 54914-85-1) | 0 % | — | 31.12.2029 |
| 0.7115 | ex 2909 30 90 | 25 | 1,2-Diphenoxymethane (CAS RN 104-66-5) in the form of powder or as an aqueous dispersion containing by weight 30 % or more but not more than 60 % of 1,2-diphenoxymethane | 0 % | — | 31.12.2026 |
| 0.8167 | ex 2909 30 90 | 45 | 5-Bromo-1,3-difluoro-2-(trifluoromethoxy)benzene (CAS RN 115467-07-7) with a purity by weight of 95 % or more | 0 % | — | 31.12.2026 |
| 0.6783 | *ex 2909 30 90 | 50 | 1-Ethoxy-2,3-difluorobenzene (CAS RN 121219-07-6) | 0 % | — | 31.12.2030 |
| 0.5117 | *ex 2909 30 90 | 55 | 3,4,5-Trimethoxytoluene (CAS RN 6443-69-2) with a purity by weight of 98 % or more | 0 % | — | 31.12.2030 |
| 0.6994 | ex 2909 30 90 | 70 | O,O,O-1,3,5-trimethylresorcinol (CAS RN 621-23-8) | 0 % | — | 31.12.2026 |
| 0.7706 | ex 2909 44 00 | 10 | 2-Propoxyethanol (CAS RN 2807-30-9) | 0 % | — | 31.12.2029 |
| 0.6927 | ex 2909 49 80 | 10 | 1-Propoxypropan-2-ol (CAS RN 1569-01-3) | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.8241 | ex 2909 49 80 | 30 | 3,4-Dimethoxybenzyl alcohol (CAS RN 93-03-8) with a purity by weight of 98 % or more | 0 % | — | 31.12.2026 |
| 0.8531 | ex 2909 49 80 | 40 | 2,2'- <i>p</i> -Phenylenedioxydiethanol (CAS RN 104-38-1) with a purity by weight of 99 % or more | 0 % | — | 31.12.2028 |
| 0.8862 | ex 2909 49 80 | 50 | 2,2'-[Oxybis(methylene)]bis[2-ethylpropane-1,3-diol] (CAS RN 23235-61-2) with a purity by weight of 95 % or more | 0 % | — | 31.12.2029 |
| 0.3484 | ex 2909 50 00 | 10 | 4-(2-Methoxyethyl)phenol (CAS RN 56718-71-9) | 0 % | — | 31.12.2029 |
| 0.3682 | ex 2909 60 90 | 40 | Bis(α,α -dimethylbenzyl) peroxide (CAS RN 80-43-3) with a purity by weight of 98 % or more | 2,8 % | — | 31.12.2026 |
| 0.7910 | ex 2909 60 90 | 50 | Solution of 3,6,9-(ethyl and/or propyl)-3,6,9-trimethyl-1,2,4,5,7,8-hexaoxanes (CAS RN 1613243-54-1) in mineral spirits (CAS RN 1174522-09-8), containing by weight 25 % or more, but not more than 41 % of the hexaoxanes | 0 % | — | 31.12.2029 |
| 0.7744 | ex 2910 90 00 | 10 | 2-[(2-Methoxyphenoxy)methyl]oxirane (CAS RN 2210-74-4) | 0 % | — | 31.12.2029 |
| 0.5940 | ex 2910 90 00 | 15 | 1,2-Epoxycyclohexane (CAS RN 286-20-4) | 0 % | — | 31.12.2029 |
| 0.7672 | ex 2910 90 00 | 25 | Phenylloxirane (CAS RN 96-09-3) | 0 % | — | 31.12.2029 |
| 0.2649 | ex 2910 90 00 | 30 | 2,3-Epoxypropan-1-ol (glycidol) (CAS RN 556-52-5) | 0 % | — | 31.12.2029 |
| 0.6660 | *ex 2910 90 00 | 50 | 2,3-Epoxypropyl phenyl ether (CAS RN 122-60-1) | 0 % | — | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.4361 | ex 2910 90 00 | 80 | Allyl glycidyl ether (CAS RN 106-92-3) | 0 % | — | 31.12.2026 |
| 0.7116 | ex 2912 19 00 | 10 | Undecanal (CAS RN 112-44-7) | 0 % | — | 31.12.2026 |
| 0.8073 | *ex 2912 19 00 | 20 | Acrylaldehyde (CAS RN 107-02-8) with a purity by weight of 98 % or more for the production of perfume or pharmaceutical intermediaries (1) | 0 % | — | 31.12.2030 |
| 0.6968 | ex 2912 29 00 | 15 | 2,6,6-Trimethylcyclohexenecarbaldehyde (alpha-beta isomers mixture) (CAS RN 52844-21-0) | 0 % | — | 31.12.2026 |
| 0.7314 | ex 2912 29 00 | 35 | Cinnamaldehyde (CAS RN 104-55-2) | 0 % | — | 31.12.2027 |
| 0.8604 | ex 2912 29 00 | 65 | Terephthalaldehyde (CAS RN 623-27-8) with a purity by weight of 98 % or more | 0 % | — | 31.12.2028 |
| 0.6072 | ex 2912 29 00 | 70 | 4-tert-Butylbenzaldehyde (CAS RN 939-97-9) | 0 % | — | 31.12.2029 |
| 0.5135 | *ex 2912 49 00 | 30 | Salicylaldehyde (CAS RN 90-02-8) | 0 % | — | 31.12.2030 |
| 0.7353 | ex 2912 49 00 | 50 | 2,6-Dihydroxybenzaldehyde (CAS RN 387-46-2) | 0 % | — | 31.12.2027 |
| 0.8582 | ex 2912 49 00 | 60 | 4-Hydroxybenzaldehyde (CAS RN 123-08-0) with a purity by weight of 96 % or more | 0 % | — | 31.12.2028 |
| 0.8911 | *ex 2912 49 00 | 70 | 5-(1,1-Dimethylethyl)-2-methoxybenzaldehyde (CAS RN 85943-26-6) with a purity by weight of 98 % or more | 0 % | — | 31.12.2030 |
| 0.7712 | ex 2913 00 00 | 10 | 2-Nitrobenzaldehyde (CAS RN 552-89-6) | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.8328 | ex 2913 00 00 | 20 | 4-(Difluoromethoxy)-3-hydroxybenzaldehyde (CAS RN 151103-08-1) with a purity by weight of 98 % or more | 0 % | — | 31.12.2029 |
| 0.8552 | ex 2913 00 00 | 30 | 2-Hydroxy-5-nitrobenzaldehyde (CAS RN 97-51-8) with a purity by weight of 95 % or more | 0 % | — | 31.12.2028 |
| 0.4228 | ex 2914 19 90 | 20 | Heptan-2-one (CAS RN 110-43-0) | 0 % | — | 31.12.2027 |
| 0.4274 | ex 2914 19 90 | 30 | 3-Methylbutanone (CAS RN 563-80-4) | 0 % | — | 31.12.2027 |
| 0.4275 | ex 2914 19 90 | 40 | Pentan-2-one (CAS RN 107-87-9) | 0 % | — | 31.12.2027 |
| 0.7554 | ex 2914 19 90 | 60 | Zinc acetylacetone (CAS RN 14024-63-6) | 0 % | — | 31.12.2029 |
| 0.7568 | ex 2914 29 00 | 15 | Oestr-5 (10) -ene-3,17-dione (CAS RN 3962-66-1) | 0 % | — | 31.12.2029 |
| 0.3475 | ex 2914 29 00 | 20 | Cyclohexadec-8-enone (CAS RN 3100-36-5) | 0 % | — | 31.12.2029 |
| 0.7450 | ex 2914 29 00 | 25 | Cyclohex-2-enone (CAS RN 930-68-7) | 0 % | — | 31.12.2029 |
| 0.4933 | *ex 2914 29 00 | 30 | (R)-p-Mentha-1 (6) ,8-dien-2-one (CAS RN 6485-40-1) | 0 % | — | 31.12.2030 |
| 0.8015 | *ex 2914 29 00 | 35 | 4-(<i>trans</i> -4-Propylcyclohexyl)cyclohexanone (CAS RN 82832-73-3) with a purity by weight of 95 % or more | 0 % | — | 31.12.2030 |
| 0.7389 | ex 2914 29 00 | 55 | 1-(Cedr-8-en-9-yl)ethanone (CAS RN 32388-55-9) with a purity by weight of more than 90 % | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8695 | ex 2914 29 00 | 65 | 3-Methylcyclopent-2-enone (CAS RN 2758-18-1) with a purity by weight of 98 % or more | 0 % | — | 31.12.2029 |
| 0.3480 | ex 2914 29 00 | 75 | Bornan-2-one (CAS RN 76-22-2) with a purity by weight of 90 % or more | 0 % | — | 31.12.2029 |
| 0.6265 | ex 2914 39 00 | 15 | 2,6-Dimethyl-1-indanone (CAS RN 66309-83-9) | 0 % | — | 31.12.2029 |
| 0.6447 | ex 2914 39 00 | 25 | 1,3-Diphenylpropane-1,3-dione (CAS RN 120-46-7) | 0 % | — | 31.12.2029 |
| 0.4227 | ex 2914 39 00 | 30 | Benzophenone (CAS RN 119-61-9) | 0 % | — | 31.12.2027 |
| 0.4428 | ex 2914 39 00 | 60 | 4-Methylbenzophenone (CAS RN 134-84-9) | 0 % | — | 31.12.2029 |
| 0.5739 | ex 2914 39 00 | 70 | Benzil (CAS RN 134-81-6) | 0 % | — | 31.12.2029 |
| 0.5535 | ex 2914 39 00 | 80 | 4'-Methylacetophenone (CAS RN 122-00-9) | 0 % | — | 31.12.2027 |
| 0.8288 | ex 2914 40 90 | 10 | Benzoin (CAS RN 119-53-9) with a purity by weight of 99 % or more | 0 % | — | 31.12.2026 |
| 0.7824 | ex 2914 50 00 | 15 | 1,1-Dimethoxyacetone (CAS RN 6342-56-9) with a purity by weight of 98 % or more | 0 % | — | 31.12.2029 |
| 0.8168 | ex 2914 50 00 | 18 | 4'-Hydroxyacetophenone (CAS RN 99-93-4) with a purity by weight of 99 % or more | 0 % | — | 31.12.2026 |
| 0.8179 | ex 2914 50 00 | 23 | 1-[2-(Oxiran-2-ylmethoxy)phenyl]-3-phenylpropan-1-one (CAS RN 22525-95-7) with a purity by weight of 99 % or more | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.5943 | ex 2914 50 00 | 25 | 4'-Methoxyacetophenone (CAS RN 100-06-1) | 0 % | — | 31.12.2029 |
| 0.8195 | ex 2914 50 00 | 28 | 1,1'-(2-Hydroxypropane-1,3-diyl)bis[oxy(6-hydroxybenzene-2,1-diyl)] diethanone (CAS RN 16150-44-0) with a purity by weight of 98 % or more | 0 % | — | 31.12.2026 |
| 0.7797 | ex 2914 50 00 | 35 | 2-Hydroxy-1-[4-[4-(2-hydroxy-2-methylpropanoyl)phenoxy]phenyl]-2-methylpropan-1-one (CAS-RN 71868-15-0) | 0 % | — | 31.12.2029 |
| 0.5435 | ex 2914 50 00 | 40 | 4-(4-Hydroxyphenyl)butan-2-one (CAS RN 5471-51-2) | 0 % | — | 31.12.2026 |
| 0.5809 | ex 2914 50 00 | 45 | 3,4-Dihydroxybenzophenone (CAS RN 10425-11-3) | 0 % | — | 31.12.2027 |
| 0.8922 | *ex 2914 50 00 | 48 | 7-Hydroxy-3,4-dihydronaphthalen-1(2H)-one (CAS RN 22009-38-7) with a purity by weight of 98 % or more | 0 % | — | 31.12.2030 |
| 0.4235 | ex 2914 50 00 | 60 | 2,2-Dimethoxy-2-phenylacetophenone (CAS RN 24650-42-8) | 0 % | — | 31.12.2027 |
| 0.4385 | ex 2914 50 00 | 80 | 2',6'-Dihydroxyacetophenone (CAS RN 699-83-2) | 0 % | — | 31.12.2029 |
| 0.2647 | ex 2914 69 80 | 10 | 2-Ethylanthraquinone (CAS RN 84-51-5) | 0 % | — | 31.12.2029 |
| 0.2643 | ex 2914 69 80 | 30 | 1,4-Dihydroxyanthraquinone (CAS RN 81-64-1) | 0 % | — | 31.12.2029 |
| 0.5430 | ex 2914 69 80 | 40 | p-Benzoquinone (CAS RN 106-51-4) | 0 % | — | 31.12.2029 |
| 0.5782 | ex 2914 79 00 | 20 | 2,4'-Difluorobenzophenone (CAS RN 342-25-6) | 0 % | — | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.7751 | ex 2914 79 00 | 27 | (2-Chloro-5-iodo-phenyl)-(4-fluoro-phenyl)-methanone (CAS RN 915095-86-2) | 0 % | — | 31.12.2029 |
| 0.7467 | ex 2914 79 00 | 30 | 5-Methoxy-1-[4-(trifluoromethyl)phenyl]pentan-1-one (CAS RN 61718-80-7) | 0 % | — | 31.12.2029 |
| 0.8338 | ex 2914 79 00 | 33 | (4R)-4-(2-Fluorophenyl)-3,4-dihydro-2H-naphthalen-1-one (CAS RN 1234356-88-7) with a purity by weight of 99 % or more | 0 % | — | 31.12.2027 |
| 0.3474 | ex 2914 79 00 | 40 | Perfluoro(2-methylpentan-3-one) (CAS RN 756-13-8) | 0 % | — | 31.12.2029 |
| 0.8563 | ex 2914 79 00 | 43 | 5-Chloropentan-2-one (CAS RN 5891-21-4) with a purity by weight of 95 % or more | 0 % | — | 31.12.2028 |
| 0.8591 | ex 2914 79 00 | 48 | 2-Chloro-3',4'-dihydroxyacetophenone (CAS RN 99-40-1) with a purity by weight of 99 % or more | 0 % | — | 31.12.2028 |
| 0.2640 | ex 2914 79 00 | 50 | 3'-Chloropropiophenone (CAS RN 34841-35-5) | 0 % | — | 31.12.2029 |
| 0.4948 | ex 2914 79 00 | 60 | 4'- <i>tert</i> -Butyl-2',6'-dimethyl-3',5'-dinitroacetophenone (CAS RN 81-14-1) | 0 % | — | 31.12.2026 |
| 0.5237 | ex 2914 79 00 | 70 | 4-Chloro-4'-hydroxybenzophenone (CAS RN 42019-78-3) | 0 % | — | 31.12.2026 |
| 0.6120 | ex 2914 79 00 | 80 | Tetrachloro-p-benzoquinone (CAS RN 118-75-2) | 0 % | — | 31.12.2029 |
| 0.7955 | *ex 2915 24 00 | 10 | Acetic anhydride (CAS RN 108-24-7) with a purity by weight of 94 % or more | 0 % | — | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.8543 | ex 2915 39 00 | 15 | 4-(2,2-Dichlorocyclopropyl)phenylacetate (CAS RN 144900-34-5) with a purity by weight of 97 % or more | 0 % | — | 31.12.2028 |
| 0.6155 | ex 2915 39 00 | 25 | 2-Methylcyclohexyl acetate (CAS RN 5726-19-2) | 0 % | — | 31.12.2029 |
| 0.5909 | ex 2915 39 00 | 33 | 2-tert-Butylcyclohexyl acetate (CAS RN 88-41-5) with a purity by weight of 98 % or more, containing by weight 80 % or more of cis-2-tert-butylcyclohexyl acetate (CAS RN 20298-69-5) | 0 % | — | 31.12.2029 |
| 0.7433 | ex 2915 39 00 | 35 | Cis-3-hexenyl acetate (CAS RN 3681-71-8) with a purity by weight of 95 % or more | 0 % | — | 31.12.2027 |
| 0.2957 | ex 2915 39 00 | 40 | tert-Butyl acetate (CAS RN 540-88-5) | 0 % | — | 31.12.2029 |
| 0.7423 | ex 2915 39 00 | 45 | 4-tert-Butylcyclohexyl acetate (CAS RN 32210-23-4) with a purity by weight of 95 % or more | 0 % | — | 31.12.2027 |
| 0.5119 | *ex 2915 39 00 | 55 | Dodec-8-enyl acetate (CAS RN 28079-04-1) with a purity by weight of 90 % or more | 0 % | — | 31.12.2030 |
| 0.5121 | *ex 2915 39 00 | 65 | Dodeca-7,9-dienyl acetate (CAS RN 54364-62-4) | 0 % | — | 31.12.2030 |
| 0.5289 | ex 2915 39 00 | 75 | Isobornyl acetate (CAS RN 125-12-2) | 0 % | — | 31.12.2026 |
| 0.5301 | ex 2915 39 00 | 80 | 1-Phenylethyl acetate (CAS RN 93-92-5) | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.7834 | ex 2915 40 00 | 10 | Ethyl trichloroacetate (CAS RN 515-84-4) with a purity by weight of 98 % or more | 0 % | — | 31.12.2029 |
| 0.5858 | ex 2915 60 19 | 20 | Ethyl butyrate (CAS RN 105-54-4) with a purity by weight of 95 % or more | 0 % | — | 31.12.2027 |
| 0.7540 | ex 2915 70 40 | 10 | Methyl palmitate (CAS RN 112-39-0) | 0 % | — | 31.12.2029 |
| 0.7541 | *ex 2915 90 30 | 10 | Methyl laurate (CAS RN 111-82-0) | 0 % | — | 31.12.2030 |
| 0.8495 | ex 2915 90 30 | 20 | Chloromethyl dodecanoate (CAS RN 61413-67-0) with a purity by weight of 97 % or more | 0 % | — | 31.12.2027 |
| 0.7407 | ex 2915 90 90 | 20 | Methyl (R)-2-fluoropropionate (CAS RN 146805-74-5) | 0 % | — | 31.12.2027 |
| 0.7542 | ex 2915 90 90 | 25 | Methyl octanoate (CAS RN 111-11-5), methyl decanoate (CAS RN 110-42-9) or methyl myristate (CAS RN 124-10-7) | 0 % | — | 31.12.2029 |
| 0.6003 | ex 2915 90 90 | 27 | Triethyl orthoformate (CAS RN 122-51-0) with a purity by weight of 99 % or more | 0 % | — | 31.12.2029 |
| 0.5767 | ex 2915 90 90 | 30 | 3,3-Dimethylbutyryl chloride (CAS RN 7065-46-5) | 0 % | — | 31.12.2027 |
| 0.8154 | ex 2915 90 90 | 33 | Ethyl 8-bromo octanoate (CAS RN 29823-21-0) with a purity by weight of 98 % or more | 0 % | — | 31.12.2026 |
| 0.8423 | ex 2915 90 90 | 43 | Trifluoroacetic anhydride (CAS RN 407-25-0) with a purity by weight of 98 % or more | 0 % | — | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.6255 | ex 2915 90 90 | 45 | Trimethyl orthoformate (CAS RN 149-73-5) | 0 % | — | 31.12.2029 |
| 0.8457 | ex 2915 90 90 | 53 | 3-Chloro-2,2-dimethylpropanoyl chloride (CAS RN 4300-97-4) with a purity by weight of 98 % or more | 0 % | — | 31.12.2027 |
| 0.4954 | *ex 2915 90 90 | 60 | Ethyl-6,8-dichlorooctanoate (CAS RN 1070-64-0) | 0 % | — | 31.12.2030 |
| 0.2585 | ex 2916 12 00 | 10 | 2- <i>tert</i> -Butyl-6-(3- <i>tert</i> -butyl-2-hydroxy-5-methylbenzyl)-4-methylphenyl acrylate (CAS RN 61167-58-6) | 0 % | — | 31.12.2029 |
| 0.3466 | *ex 2916 13 00 | 30 | Zinc monomethacrylate powder (CAS RN 63451-47-8) whether or not containing not more than 17 % by weight of manufacturing impurities | 0 % | — | 31.12.2030 |
| 0.3468 | ex 2916 13 00 | 40 | Zinc Dimethacrylate (CAS RN 13189-00-9) in the form of powder with a purity by weight of 99 % or more, with not more than 1 % of a stabiliser | 0 % | — | 31.12.2029 |
| 0.2638 | ex 2916 14 00 | 10 | 2,3-Epoxypropyl methacrylate (CAS RN 106-91-2) | 0 % | — | 31.12.2029 |
| 0.8863 | ex 2916 14 00 | 40 | Butyl methacrylate (CAS RN 97-88-1) with a purity by weight of 99 % or more | 0 % | — | 31.12.2029 |
| 0.8953 | *ex 2916 14 00 | 50 | 2-Hydroxyethyl methacrylate (CAS RN 868-77-9) with a purity by weight of 97 % or more | 0 % | — | 31.12.2030 |
| 0.5991 | ex 2916 19 95 | 40 | Sorbic acid (CAS RN 110-44-1) for use in the manufacture of animal feeds (¹) | 0 % | — | 31.12.2029 |
| 0.6238 | ex 2916 19 95 | 50 | Methyl 2-fluoroacrylate (CAS RN 2343-89-7) | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.7980 | *ex 2916 19 95 | 60 | Methyl 2-fluoroprop-2-enoate (CAS RN 2343-89-7) with a purity by weight of 93 % or more, whether or not with not more than 7 % of the stabiliser 2,6-di-tert-butyl-p-cresol (CAS RN 128-37-0) and Tetrabutylammonium nitrite (CAS RN 26501-54-2) | 0 % | — | 31.12.2030 |
| 0.7940 | *ex 2916 19 95 | 70 | Methyl 3-methyl-2-butenoate (CAS RN 924-50-5) with a purity by weight of 99,0 % or more | 0 % | — | 31.12.2030 |
| 0.7023 | ex 2916 20 00 | 15 | Transfluthrin (ISO) (CAS RN 118712-89-3) | 0 % | — | 31.12.2026 |
| 0.7931 | *ex 2916 20 00 | 25 | Cyclohexanecarbonyl chloride (CAS RN 2719-27-9) with a purity by weight of 99 % or more | 0 % | — | 31.12.2030 |
| 0.8336 | ex 2916 20 00 | 55 | Methyl 2,2-dimethyl-3-(2-methylprop-1-en-1-yl)cyclopropane-1-carboxylate (CAS RN 5460-63-9) with a purity by weight of 90 % or more | 0 % | — | 31.12.2027 |
| 0.4931 | *ex 2916 20 00 | 60 | 3-Cyclohexylpropionic acid (CAS RN 701-97-3) | 0 % | — | 31.12.2030 |
| 0.8352 | ex 2916 20 00 | 65 | Tefluthrin (ISO)(CAS RN 79538-32-2) with a purity by weight of 96 % or more | 0 % | — | 31.12.2027 |
| 0.5421 | ex 2916 31 00 | 10 | Benzyl benzoate (CAS RN 120-51-4) | 0 % | — | 31.12.2026 |
| 0.8214 | ex 2916 31 00 | 20 | Phenethyl benzoate (CAS RN 94-47-3) with a purity by weight of 95 % or more | 0 % | — | 31.12.2026 |
| 0.6248 | ex 2916 39 90 | 13 | 3,5-Dinitrobenzoic acid (CAS RN 99-34-3) | 0 % | — | 31.12.2029 |
| 0.5214 | ex 2916 39 90 | 15 | 2-Chloro-5-nitrobenzoic acid (CAS RN 2516-96-3) | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.2636 | ex 2916 39 90 | 20 | 3,5-Dichlorobenzoyl chloride (CAS RN 2905-62-6) | 0 % | — | 31.12.2029 |
| 0.6557 | ex 2916 39 90 | 23 | (2,4,6-Trimethylphenyl)acetyl chloride (CAS RN 52629-46-6) | 0 % | — | 31.12.2029 |
| 0.4951 | ex 2916 39 90 | 25 | 2-Methyl-3-(4-Fluorophenyl)-propionyl chloride (CAS RN 1017183-70-8) | 0 % | — | 31.12.2026 |
| 0.7827 | ex 2916 39 90 | 27 | Methyl 6-Bromo-2-naphthoate (CAS RN 33626-98-1) with a purity by weight of 99 % or more | 0 % | — | 31.12.2029 |
| 0.4930 | *ex 2916 39 90 | 30 | 2,4,6-Trimethylbenzoyl chloride (CAS RN 938-18-1) | 0 % | — | 31.12.2030 |
| 0.5944 | ex 2916 39 90 | 35 | Methyl 4- <i>tert</i> -butylbenzoate (CAS RN 26537-19-9) | 0 % | — | 31.12.2029 |
| 0.8489 | ex 2916 39 90 | 40 | Ethyl 4-bromo-3-(bromomethyl)benzoate (CAS RN 347852-72-6) with a purity by weight of 97 % or more | 0 % | — | 31.12.2027 |
| 0.7734 | ex 2916 39 90 | 43 | 2-(3,5-Bis(trifluoromethyl)phenyl)-2-methylpropanoic acid (CAS RN 289686-70-0) | 0 % | — | 31.12.2029 |
| 0.2634 | ex 2916 39 90 | 50 | 3,5-Dimethylbenzoyl chloride (CAS RN 6613-44-1) | 0 % | — | 31.12.2029 |
| 0.4238 | ex 2916 39 90 | 55 | 4- <i>tert</i> -Butylbenzoic acid (CAS RN 98-73-7) | 0 % | — | 31.12.2027 |
| 0.3462 | *ex 2916 39 90 | 58 | Ibuprofen (INN) (CAS RN 15687-27-1) with a purity by weight of 99 % or more | 0 % | — | 31.12.2029 |
| 0.8169 | ex 2916 39 90 | 63 | 2-Phenylbutyric acid (CAS RN 90-27-7) with a purity by weight of 99 % or more | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.8369 | ex 2916 39 90 | 67 | Nitrobenzoic acid (CAS RN 62-23-7) with a purity by weight of 99 % or more | 0 % | — | 31.12.2027 |
| 0.7117 | ex 2916 39 90 | 73 | (2,4-Dichlorophenyl)acetyl chloride (CAS RN 53056-20-5) | 0 % | — | 31.12.2026 |
| 0.5541 | ex 2916 39 90 | 75 | <i>m</i> -Toluic acid (CAS RN 99-04-7) | 0 % | — | 31.12.2027 |
| 0.5543 | ex 2916 39 90 | 85 | (2,4,5-Trifluorophenyl)acetic acid (CAS RN 209995-38-0) | 0 % | — | 31.12.2027 |
| 0.3457 | ex 2917 11 00 | 20 | Bis(<i>p</i> -methylbenzyl) oxalate (CAS RN 18241-31-1) | 0 % | — | 31.12.2029 |
| 0.4746 | ex 2917 11 00 | 30 | Cobalt oxalate (CAS RN 814-89-1) | 0 % | — | 31.12.2029 |
| 0.8946 | *ex 2917 12 00 | 30 | Bis(3,4-epoxycyclohexylmethyl)adipate (CAS RN 3130-19-6) with a purity by weight of 97 % or more | 0 % | — | 31.12.2030 |
| 0.4684 | ex 2917 19 10 | 10 | Dimethyl malonate (CAS RN 108-59-8) | 0 % | — | 31.12.2029 |
| 0.5602 | ex 2917 19 10 | 20 | Diethyl malonate (CAS RN 105-53-3) | 0 % | — | 31.12.2027 |
| 0.7451 | ex 2917 19 80 | 35 | Diethyl methylmalonate (CAS RN 609-08-5) | 0 % | — | 31.12.2029 |
| 0.7880 | ex 2917 19 80 | 45 | Iron fumarate (CAS RN 141-01-5) with a purity by weight of 93 % or more | 0 % | — | 31.12.2029 |
| 0.4918 | *ex 2917 19 80 | 50 | Tetradecanedioic acid (CAS RN 821-38-5) | 0 % | — | 31.12.2030 |
| 0.8302 | *ex 2917 19 80 | 55 | Maleic acid (CAS RN 110-16-7) with a purity by weight of 99 % or more | 0 % | — | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8530 | ex 2917 19 80 | 60 | Oxalyl dichloride (CAS RN 79-37-8) with a purity by weight of 99 % or more | 0 % | — | 31.12.2028 |
| 0.8728 | ex 2917 19 80 | 65 | 20- <i>tert</i> -butoxy-20-oxoicosanoic acid (CAS RN 683239-16-9) with a purity by weight of 98 % or more | 0 % | — | 31.12.2029 |
| 0.3454 | ex 2917 19 80 | 70 | Itaconic acid (CAS RN 97-65-4) | 0 % | — | 31.12.2029 |
| 0.4790 | ex 2917 19 80 | 75 | Ethylene brassylate (CAS RN 105-95-3) with a purity by weight of 97 % or more | 0 % | — | 31.12.2029 |
| 0.8534 | ex 2917 19 80 | 80 | Ethyl chloroglyoxylate (CAS RN 4755-77-5) with a purity by weight of 98 % or more | 0 % | — | 31.12.2028 |
| 0.8945 | *ex 2917 19 80 | 85 | Dibutyl itaconate (CAS RN 2155-60-4) with a purity by weight of 96 % or more | 0 % | — | 31.12.2030 |
| 0.2631 | ex 2917 20 00 | 30 | 1,4,5,6,7,7-Hexachloro-8,9,10-trinorborn-5-ene-2,3-dicarboxylic anhydride (CAS RN 115-27-5) | 0 % | — | 31.12.2029 |
| 0.2627 | ex 2917 20 00 | 40 | 3-Methyl-1,2,3,6-tetrahydronaphthalic anhydride (CAS RN 5333-84-6) | 0 % | — | 31.12.2029 |
| 0.2954 | ex 2917 34 00 | 10 | Diallyl phthalate (CAS RN 131-17-9) | 0 % | — | 31.12.2029 |
| 0.4945 | *ex 2917 39 85 | 20 | Dibutyl-1,4-benzenedicarboxylate (CAS RN 1962-75-0) | 0 % | — | 31.12.2030 |
| 0.6796 | *ex 2917 39 85 | 25 | Naphthalene-1,8-dicarboxylic anhydride (CAS RN 81-84-5) | 0 % | — | 31.12.2030 |
| 0.3640 | *ex 2917 39 85 | 30 | Benzene-1,2:4,5-tetracarboxylic dianhydride (CAS RN 89-32-7) | 0 % | — | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.8255 | ex 2917 39 85 | 45 | 3-(4-Chlorophenyl)glutaric acid (CAS RN 35271-74-0) with a purity by weight of 98 % or more | 0 % | — | 31.12.2026 |
| 0.6553 | ex 2917 39 85 | 50 | 1,4,5,8-Naphthalenetetracarboxylic acid-1,8-monoanhydride (CAS RN 52671-72-4) | 0 % | — | 31.12.2029 |
| 0.8526 | ex 2917 39 85 | 55 | 3-Nitrophthalic acid (CAS RN 603-11-2) with a purity by weight of 98 % or more | 0 % | — | 31.12.2028 |
| 0.6554 | ex 2917 39 85 | 60 | Perylene-3,4:9,10-tetracarboxylic dianhydride(CAS RN 128-69-8) | 0 % | — | 31.12.2029 |
| 0.6366 | ex 2918 19 30 | 10 | Cholic acid (CAS RN 81-25-4) | 0 % | — | 31.12.2029 |
| 0.6367 | ex 2918 19 30 | 20 | 3- α ,12- α -Dihydroxy-5- β -cholan-24-oic acid (deoxycholic acid) (CAS RN 83-44-3) | 0 % | — | 31.12.2029 |
| 0.2950 | ex 2918 19 98 | 20 | L-Malic acid (CAS RN 97-67-6) | 0 % | — | 31.12.2029 |
| 0.8509 | ex 2918 19 98 | 25 | (S)-2-Hydroxy-2-phenylacetic acid (CAS RN 17199-29-0) with a purity by weight of 99 % or more | 0 % | — | 31.12.2027 |
| 0.7702 | ex 2918 19 98 | 30 | Ethyl 1-hydroxycyclopentanecarboxylate (CAS RN 41248-23-1) | 0 % | — | 31.12.2029 |
| 0.7907 | ex 2918 19 98 | 50 | 12-Hydroxyoctadecanoic acid (CAS RN 106-14-9) with a purity by weight of 90 % or more for use in the manufacture of polyglycerin-poly-12-hydroxyoctadecanoic acid esters (¹) | 0 % | — | 31.12.2029 |
| 0.8044 | *ex 2918 19 98 | 60 | (R)- <i>tert</i> -Butyl 2'-(1-hydroxyethyl)-3-methyl-[1,1'-biphenyl]-4-carboxylate (CAS RN 1246560-92-8) with a purity by weight of 98 % or more | 0 % | — | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.8422 | ex 2918 19 98 | 70 | Rac- <i>tert</i> -butyl 3-hydroxy-4-pentenoate (CAS RN 122763-67-1) with a purity by weight of 98 % or more | 0 % | — | 31.12.2027 |
| 0.5781 | ex 2918 29 00 | 35 | Propyl 3,4,5-trihydroxybenzoate (CAS RN 121-79-9) | 0 % | — | 31.12.2027 |
| 0.8917 | *ex 2918 29 00 | 45 | 3-Hydroxy-2-naphthoic acid (CAS RN 92-70-6) with a purity by weight of 98 % or more | 0 % | — | 31.12.2030 |
| 0.3638 | ex 2918 29 00 | 50 | Hexamethylene bis[3-(3,5-di- <i>tert</i> -butyl-4-hydroxyphenyl)propionate] (CAS RN 35074-77-2) | 0 % | — | 31.12.2029 |
| 0.5220 | ex 2918 29 00 | 60 | Methyl-, ethyl-, propyl- or butyl esters of 4-hydroxybenzoic acid or their sodium salts (CAS RN 35285-68-8, 99-76-3, 5026-62-0, 94-26-8, 94-13-3, 35285-69-9, 120-47-8, 36457-20-2 or 4247-02-3) | 0 % | — | 31.12.2026 |
| 0.6456 | ex 2918 29 00 | 70 | 3,5-Diiodosalicylic acid (CAS RN 133-91-5) | 0 % | — | 31.12.2029 |
| 0.4427 | ex 2918 30 00 | 30 | Methyl-2-benzoylbenzoate (CAS RN 606-28-0) | 0 % | — | 31.12.2029 |
| 0.7864 | ex 2918 30 00 | 35 | 3-Oxocyclobutane-1-carboxylic acid with a purity by weight of 98 % or more (CAS RN 23761-23-1) | 0 % | — | 31.12.2029 |
| 0.8861 | ex 2918 30 00 | 43 | Ethyl 4-oxovalerate (CAS RN 539-88-8) with a purity by weight of 98 % or more | 0 % | — | 31.12.2029 |
| 0.8949 | *ex 2918 30 00 | 48 | Prohexadione-calcium (ISOM) (CAS RN 127277-53-6) with a purity by weight of 95 % or more | 0 % | — | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.8950 | *ex 2918 30 00 | 53 | 2-(4-Chlorobenzoyl)benzoic acid (CAS RN 85-56-3) with a purity by weight of 99 % or more | 0 % | — | 31.12.2030 |
| 0.8256 | ex 2918 30 00 | 55 | Methyl 3-oxo-pentanoate (CAS RN 30414-53-0) with a purity by weight of 98 % or more | 0 % | — | 31.12.2026 |
| 0.6250 | ex 2918 30 00 | 60 | 4-Oxovaleric acid (CAS RN 123-76-2) | 0 % | — | 31.12.2029 |
| 0.6455 | ex 2918 30 00 | 70 | 2-[4-Chloro-3-(chlorosulphonyl)benzoyl]benzoic acid (CAS RN 68592-12-1) | 0 % | — | 31.12.2029 |
| 0.8342 | ex 2918 30 00 | 75 | Methyl 2-((1S,2R)-3-oxo-2-pentylcyclopentyl)acetate (CAS RN 151716-35-7) with a purity by weight of 99 % or more | 0 % | — | 31.12.2027 |
| 0.7062 | ex 2918 30 00 | 80 | Methyl benzoylformate (CAS RN 15206-55-0) | 0 % | — | 31.12.2026 |
| 0.7344 | ex 2918 30 00 | 85 | 2-Fluoro-5-formylbenzoic acid (CAS RN 550363-85-4) with a purity by weight of 98 % or more | 0 % | — | 31.12.2029 |
| 0.5857 | ex 2918 30 00 | 87 | Ethyl acetoacetate (CAS RN 141-97-9) with a purity by weight of 98 % or more | 0 % | — | 31.12.2027 |
| 0.6814 | *ex 2918 99 90 | 13 | 3-Methoxy-2-methylbenzoyl chloride (CAS RN 24487-91-0) | 0 % | — | 31.12.2030 |
| 0.5856 | ex 2918 99 90 | 15 | Ethyl 2,3-epoxy-3-phenylbutyrate (CAS RN 77-83-8) | 0 % | — | 31.12.2027 |
| 0.6901 | *ex 2918 99 90 | 18 | Ethyl 2-hydroxy-2-(4-phenoxyphenyl)propanoate (CAS RN 132584-17-9) | 0 % | — | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.6147 | ex 2918 99 90 | 25 | Methyl (E)-3-methoxy-2-(2-chloromethylphenyl)-2-propenoate (CAS RN 117428-51-0) | 0 % | — | 31.12.2029 |
| 0.7256 | ex 2918 99 90 | 27 | Ethyl 3-ethoxypropionate (CAS RN 763-69-9) | 0 % | — | 31.12.2027 |
| 0.6342 | ex 2918 99 90 | 35 | p-Anisic acid (CAS RN 100-09-4) | 0 % | — | 31.12.2029 |
| 0.7358 | ex 2918 99 90 | 38 | Diclofop-methyl (ISO) (CAS RN 51338-27-3) | 0 % | — | 31.12.2027 |
| 0.2945 | ex 2918 99 90 | 40 | <i>trans</i> -4-Hydroxy-3-methoxycinnamic acid (CAS RN 1135-24-6) | 0 % | — | 31.12.2029 |
| 0.6224 | ex 2918 99 90 | 45 | 4-Methylcatechol dimethyl acetate (CAS RN 52589-39-6) | 0 % | — | 31.12.2029 |
| 0.8066 | *ex 2918 99 90 | 48 | 2-Bromo-5-methoxybenzoic acid (CAS RN 22921-68-2) with a purity by weight of 98 % or more | 0 % | — | 31.12.2026 |
| 0.2947 | ex 2918 99 90 | 50 | Methyl 3,4,5-trimethoxybenzoate (CAS RN 1916-07-0) | 0 % | — | 31.12.2029 |
| 0.8623 | ex 2918 99 90 | 58 | 2,4-D (ISO) (CAS RN 94-75-7) with a purity by weight of 98 % or more | 0 % | — | 31.12.2028 |
| 0.2943 | ex 2918 99 90 | 60 | 3,4,5-Trimethoxybenzoic acid (CAS RN 118-41-2) | 0 % | — | 31.12.2029 |
| 0.4742 | ex 2918 99 90 | 67 | Allyl-(3-methylbutoxy)acetate (CAS RN 67634-00-8) with a purity by weight of 95 % or more | 0 % | — | 31.12.2029 |
| 0.2948 | ex 2918 99 90 | 73 | Methyl (2R)-2-(4-hydroxyphenoxy)propionate (CAS RN 96562-58-2) with a purity by weight of 97 % or more | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8947 | *ex 2918 99 90 | 78 | 3,4-Epoxycyclohexylmethyl-3',4'-epoxycyclohexane carboxylate (CAS RN 2386-87-0) with a purity by weight of 91 % or more | 0 % | — | 31.12.2030 |
| 0.6747 | *ex 2918 99 90 | 85 | Trinexapac-Ethyl (ISO) (CAS RN 95266-40-3) with a purity by weight of 96 % or more | 0 % | — | 31.12.2030 |
| 0.5495 | ex 2919 90 00 | 50 | Triethyl phosphate (CAS RN 78-40-0) | 0 % | — | 31.12.2026 |
| 0.6188 | ex 2919 90 00 | 60 | Bisphenol-A bis(diphenyl phosphate) (CAS RN 5945-33-5) | 0 % | — | 31.12.2029 |
| 0.6413 | ex 2919 90 00 | 70 | Tris(2-butoxyethyl)phosphate (CAS RN 78-51-3) | 0 % | — | 31.12.2029 |
| 0.6253 | ex 2920 19 00 | 30 | 2,2'-Oxybis(5,5-dimethyl-1,3,2-dioxaphosphorinane)-2,2'-disulphide (CAS RN 4090-51-1) | 0 % | — | 31.12.2029 |
| 0.3634 | 2920 23 00 | | Trimethyl phosphite (CAS RN 121-45-9) | 0 % | — | 31.12.2029 |
| 0.4158 | 2920 24 00 | | Triethyl phosphite (CAS RN 122-52-1) | 0 % | — | 31.12.2026 |
| 0.2626 | ex 2920 29 00 | 10 | O,O'-Di octadecyl pentaerythritol bis(phosphite) (CAS RN 3806-34-6) | 0 % | — | 31.12.2029 |
| 0.5038 | *ex 2920 29 00 | 20 | Tris(methylphenyl)phosphite (CAS RN 25586-42-9) | 0 % | — | 31.12.2030 |
| 0.6004 | ex 2920 29 00 | 25 | Fosetyl-aluminium (ISOM)(CAS RN 39148-24-8) with a purity by weight of 96 % or more | 0 % | — | 31.12.2029 |
| 0.5045 | *ex 2920 29 00 | 40 | Bis(2,4-dicumylphenyl)pentaerythritol diphosphite (CAS RN 154862-43-8) | 0 % | — | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.8942 | *ex 2920 29 00 | 45 | Tris(2-chloroethyl) phosphite (CAS RN 140-08-9) with a purity by weight of 90 % or more | 0 % | — | 31.12.2030 |
| 0.7898 | ex 2920 29 00 | 80 | 2,4,8,10-Tetrakis(1,1-dimethylethyl)-6-(2-ethylhexyloxy)-12H dibenzo[d,g][1,3,2]dioxaphosphocin (CAS RN 126050-54-2) with a purity by weight of 95 % or more | 0 % | — | 31.12.2029 |
| 0.8522 | ex 2920 90 10 | 13 | Tetraethyl orthocarbonate (CAS RN 78-09-1) with a purity by weight of 99 % or more | 0 % | — | 31.12.2028 |
| 0.2605 | ex 2920 90 10 | 20 | Diallyl 2,2'-oxydiethyl dicarbonate (CAS RN 142-22-3) | 0 % | — | 31.12.2029 |
| 0.8641 | *ex 2920 90 10 | 23 | 1,3,2-Dioxathiolane 2,2-dioxide (CAS RN 1072-53-3) with a purity by weight of 99 % or more | 3,2 % | — | 31.12.2026 |
| 0.7559 | *ex 2920 90 10 | 33 | Ethyl methyl carbonate (CAS RN 623-53-0) with a purity by weight of 98 % or more | 3,2 % | — | 31.12.2026 |
| 0.3685 | ex 2920 90 10 | 40 | Dimethyl carbonate (CAS RN 616-38-6) | 0 % | — | 31.12.2029 |
| 0.8297 | *ex 2920 90 10 | 45 | Ethylene carbonate (CAS RN 96-49-1) with a purity by weight of 99 % or more | 3,2 % | — | 31.12.2026 |
| 0.3868 | ex 2920 90 10 | 50 | Di- <i>tert</i> -butyl dicarbonate (CAS RN 24424-99-5) | 0 % | — | 31.12.2029 |
| 0.8298 | *ex 2920 90 10 | 55 | Vinylene carbonate (CAS RN 872-36-6) with a purity by weight of 99,9 % or more | 3,2 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8299 | *ex 2920 90 10 | 65 | Vinyl ethylene carbonate (CAS RN 4427-96-7) with a purity by weight of 99 % or more | 3,2 % | — | 31.12.2026 |
| 0.8511 | *ex 2920 90 10 | 85 | Diethyl carbonate (CAS RN 105-58-8) with a purity by weight of 99,9 % or more | 3,2 % | — | 31.12.2026 |
| 0.8542 | ex 2920 90 70 | 10 | Tris(2-propylheptyl) borate (CAS RN 1488321-95-4) with a purity by weight of 90 % or more | 0 % | — | 31.12.2028 |
| 0.7588 | ex 2920 90 70 | 20 | Diethyl phosphorochloridate (CAS RN 814-49-3) | 0 % | — | 31.12.2029 |
| 0.8719 | ex 2920 90 70 | 35 | Triisopropyl borate (CAS RN 5419-55-6) with a purity by weight of 99 % or more | 0 % | — | 31.12.2029 |
| 0.5947 | ex 2920 90 70 | 60 | Bis(neopentylglycolato)diboron (CAS RN 201733-56-4) | 0 % | — | 31.12.2029 |
| 0.8490 | ex 2920 90 70 | 70 | 4,4,5,5-Tetramethyl-1,3,2-dioxaborolane (CAS RN 25015-63-8) with a purity by weight of 97 % or more, containing not more than 1 % of the stabiliser triethylamine (CAS RN 121-44-8) | 0 % | — | 31.12.2027 |
| 0.6598 | *ex 2920 90 70 | 80 | Bis(pinacolato)diboron (CAS RN 73183-34-3) | 0 % | — | 31.12.2030 |
| 0.3629 | ex 2921 19 99 | 20 | Ethyl(2-methylallyl)amine (CAS RN 18328-90-0) | 0 % | — | 31.12.2029 |
| 0.3631 | ex 2921 19 99 | 30 | Allylamine (CAS RN 107-11-9) | 0 % | — | 31.12.2029 |
| 0.8477 | ex 2921 19 99 | 35 | N-Ethyl-N-isopropylpropan-2-amine 2-(difluoromethoxy)acetate with a purity by weight of 98 % or more | 0 % | — | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.7073 | ex 2921 19 99 | 45 | 2-Chloro-N-(2-chloroethyl)ethanamine hydrochloride (CAS RN 821-48-7) | 0 % | — | 31.12.2026 |
| 0.8562 | ex 2921 19 99 | 55 | 2,2,2-Trifluoroethylamine hydrochloride (CAS RN 373-88-6) with a purity by weight of 99 % or more | 0 % | — | 31.12.2028 |
| 0.6269 | ex 2921 19 99 | 80 | Taurine (CAS RN 107-35-7), with 0,5 % addition of anti-caking agent silicon dioxide (CAS RN 112926-00-8) | 0 % | — | 31.12.2029 |
| 0.3630 | ex 2921 29 00 | 20 | Tris[3-(dimethylamino)propyl]amine (CAS RN 33329-35-0) | 0 % | — | 31.12.2029 |
| 0.3625 | ex 2921 29 00 | 30 | Bis[3-(dimethylamino)propyl]methylamine (CAS RN 3855-32-1) | 0 % | — | 31.12.2029 |
| 0.8170 | ex 2921 29 00 | 35 | Pentamethylenediamine (CAS RN 462-94-2) with a purity by weight of 99 % or more, also as an aqueous solution containing by weight more than 50 % of pentamethylenediamine | 0 % | — | 31.12.2026 |
| 0.4917 | *ex 2921 29 00 | 40 | Decamethylenediamine (CAS RN 646-25-3) | 0 % | — | 31.12.2030 |
| 0.5256 | ex 2921 29 00 | 50 | N'-[3-(Dimethylamino)propyl]-N,N-dimethylpropane-1,3-diamine (CAS RN 6711-48-4) | 0 % | — | 31.12.2026 |
| 0.7947 | *ex 2921 29 00 | 70 | N,N,N',N'-Tetramethylethylenediamine (CAS RN 110-18-9) with a purity by weight of 99 % or more | 0 % | — | 31.12.2030 |
| 0.5768 | ex 2921 30 99 | 40 | Cyclopropylamine (CAS RN 765-30-0) | 0 % | — | 31.12.2027 |
| 0.8529 | ex 2921 30 99 | 60 | Amantadine hydrochloride (CAS RN 665-66-7) with a purity by weight of 97 % or more | 0 % | — | 31.12.2028 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.3909 | ex 2921 42 00 | 25 | Sodium hydrogen 2-aminobenzene-1,4-disulphonate (CAS RN 24605-36-5) | 0 % | — | 31.12.2029 |
| 0.3978 | ex 2921 42 00 | 35 | 2-Nitroaniline (CAS RN 88-74-4) | 0 % | — | 31.12.2029 |
| 0.2620 | ex 2921 42 00 | 50 | 3-Aminobenzenesulfonic acid (CAS RN 121-47-1) | 0 % | — | 31.12.2029 |
| 0.7739 | *ex 2921 42 00 | 65 | 4-chloroaniline (CAS RN 106-47-8) with a purity by weight of 99 % or more | 0 % | — | 31.12.2029 |
| 0.3623 | ex 2921 42 00 | 70 | 2-Aminobenzene-1,4-disulfonic acid (CAS RN 98-44-2) | 0 % | — | 31.12.2029 |
| 0.3622 | ex 2921 42 00 | 80 | 4-Chloro-2-nitroaniline (CAS RN 89-63-4) | 0 % | — | 31.12.2029 |
| 0.5616 | ex 2921 42 00 | 86 | 2,5-Dichloroaniline (CAS RN 95-82-9) | 0 % | — | 31.12.2027 |
| 0.5603 | ex 2921 42 00 | 87 | N-Methylaniline (CAS RN 100-61-8) | 0 % | — | 31.12.2027 |
| 0.5617 | ex 2921 42 00 | 88 | 3,4-Dichloroaniline-6-sulphonic acid (CAS RN 6331-96-0) | 0 % | — | 31.12.2027 |
| 0.8433 | ex 2921 43 00 | 25 | 6-Chloro-a,a,a-trifluoro-m-toluidine (CAS RN 121-50-6) with a purity by weight of 98 % or more | 0 % | — | 31.12.2027 |
| 0.8568 | ex 2921 43 00 | 35 | 3-Chloro-o-toluidine (CAS RN 87-60-5) with a purity by weight of 95 % or more | 0 % | — | 31.12.2028 |
| 0.3980 | ex 2921 43 00 | 40 | 4-Aminotoluene-3-sulphonic acid (CAS RN 88-44-8) | 0 % | — | 31.12.2029 |
| 0.5124 | *ex 2921 43 00 | 60 | 3-Aminobenzotrifluoride (CAS RN 98-16-8) | 0 % | — | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.3621 | ex 2921 44 00 | 20 | Diphenylamine (CAS RN 122-39-4) | 0 % | — | 31.12.2029 |
| 0.7316 | ex 2921 45 00 | 60 | 1-Naphthylamine (CAS RN 134-32-7) | 0 % | — | 31.12.2027 |
| 0.7592 | ex 2921 49 00 | 35 | 2-Ethylaniline (CAS RN 578-54-1) | 0 % | — | 31.12.2029 |
| 0.2609 | ex 2921 49 00 | 40 | N-1-Naphthylaniline (CAS RN 90-30-2) | 0 % | — | 31.12.2029 |
| 0.8019 | *ex 2921 49 00 | 45 | 2-(4-Biphenyl)amino-9,9-dimethylfluoren (CAS RN 897671-69-1) with a purity by weight of 95 % or more | 0 % | — | 31.12.2030 |
| 0.8020 | *ex 2921 49 00 | 55 | 2-(2-Biphenyl)amino-9,9-dimethylfluoren (CAS RN 1198395-24-2) with a purity by weight of 95 % or more | 0 % | — | 31.12.2030 |
| 0.6825 | *ex 2921 49 00 | 60 | 2,6-Diisopropylaniline (CAS RN 24544-04-5) | 0 % | — | 31.12.2030 |
| 0.8059 | *ex 2921 49 00 | 65 | Bis-(9,9-dimethylfluoren-2-yl)amine (CAS RN 500717-23-7) with a purity by weight of 95 % or more | 0 % | — | 31.12.2030 |
| 0.8558 | ex 2921 49 00 | 75 | N-Methyl-1-(1-naphthyl)methanamine (CAS RN 14489-75-9) with a purity by weight of 99 % or more | 0 % | — | 31.12.2028 |
| 0.3981 | ex 2921 51 19 | 30 | 2-Methyl-p-phenylenediamine sulphate (CAS RN 615-50-9) | 0 % | — | 31.12.2029 |
| 0.4184 | ex 2921 51 19 | 40 | p-Phenylenediamine (CAS RN 106-50-3) | 0 % | — | 31.12.2026 |
| 0.4498 | ex 2921 51 19 | 50 | 2-Chloro-1,4-phenylenediamine (CAS RN 615-66-7) or 2,5-dichloro-1,4-phenylenediamine (CAS RN 20103-09-7) | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.2612 | ex 2921 59 90 | 15 | Mixture of isomers of 3,5-diethyldiethylenediamine (CAS RN 68479-98-1) | 0 % | — | 31.12.2028 |
| 0.3785 | ex 2921 59 90 | 30 | 3,3'-Dichlorobenzidine dihydrochloride (CAS RN 612-83-9) | 0 % | — | 31.12.2027 |
| 0.3870 | ex 2921 59 90 | 40 | 4,4'-Diaminostilbene-2,2'-disulphonic acid (CAS RN 81-11-8) | 0 % | — | 31.12.2029 |
| 0.7860 | ex 2922 19 00 | 15 | Aqueous solution, containing by weight: — 73 % or more 2-amino-2-methyl-1-propanol (CAS RN 124-68-5), — 4,5 % or more, but not more than 27 % water (CAS RN 7732-18-5) | 0 % | — | 31.12.2029 |
| 0.5757 | ex 2922 19 00 | 20 | 2-(2-Methoxyphenoxy)ethylamine hydrochloride (CAS RN 64464-07-9) | 0 % | — | 31.12.2027 |
| 0.7946 | *ex 2922 19 00 | 29 | N-Methyl-N-(2-hydroxyethyl)-p-toluidine (CAS RN 2842-44-6) with a purity by weight of 99 % or more | 0 % | — | 31.12.2030 |
| 0.3617 | ex 2922 19 00 | 30 | N,N,N',N'-Tetramethyl-2,2'-oxybis(ethylamine) (CAS RN 3033-62-3) | 0 % | — | 31.12.2029 |
| 0.8337 | ex 2922 19 00 | 33 | 2-Methoxyethan-1-amine (CAS RN 109-85-3) with a purity by weight of 98 % or more | 0 % | — | 31.12.2027 |
| 0.7179 | ex 2922 19 00 | 40 | (R)-1-((4-Amino-2-bromo-5-fluorophenyl)amino)-3-(benzyloxy)propan-2-ol 4-methylbenzenesulphonate (CAS RN 1294504-64-5) | 0 % | — | 31.12.2026 |
| 0.6947 | *ex 2922 19 00 | 43 | 2-[2-(Dimethylamino)ethoxy]ethanol (CAS RN 1704-62-7) with a purity by weight of 98 % or more | 0 % | — | 31.12.2030 |
| 0.7480 | ex 2922 19 00 | 45 | 2-Methoxymethyl-p-phenylenediamine (CAS RN 337906-36-2) | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.3616 | ex 2922 19 00 | 53 | 2-(2-Methoxyphenoxy)ethanamine (CAS RN 1836-62-0) with a purity by weight of 98 % or more | 0 % | — | 31.12.2029 |
| 0.7587 | ex 2922 19 00 | 55 | 3-Aminoadamantan-1-ol (CAS RN 702-82-9) | 0 % | — | 31.12.2029 |
| 0.3871 | ex 2922 19 00 | 60 | <i>N,N,N'-Trimethyl-N'-(2-hydroxy-ethyl) 2,2'-oxybis(ethylamine)</i> , (CAS RN 83016-70-0) | 0 % | — | 31.12.2029 |
| 0.5905 | ex 2922 19 00 | 65 | <i>trans</i> -4-Aminocyclohexanol (CAS RN 27489-62-9) | 0 % | — | 31.12.2029 |
| 0.7935 | *ex 2922 19 00 | 70 | 2-Benzylaminoethanol (CAS 104-63-2) with a purity by weight of 98 % or more | 0 % | — | 31.12.2030 |
| 0.5986 | ex 2922 19 00 | 75 | 2-Ethoxyethylamine (CAS RN 110-76-9) | 0 % | — | 31.12.2029 |
| 0.4665 | ex 2922 19 00 | 80 | <i>N</i> -[2-[2-(Dimethylamino)ethoxy]ethyl]- <i>N</i> -methyl-1,3-propanediamine (CAS RN 189253-72-3) | 0 % | — | 31.12.2029 |
| 0.5996 | ex 2922 21 00 | 10 | 2-Amino-5-hydroxynaphthalene-1,7-disulphonic acid (CAS RN 6535-70-2) | 0 % | — | 31.12.2029 |
| 0.2703 | ex 2922 21 00 | 30 | 6-Amino-4-hydroxynaphthalene-2-sulphonic acid (CAS RN 90-51-7) | 0 % | — | 31.12.2029 |
| 0.2704 | ex 2922 21 00 | 40 | 7-Amino-4-hydroxynaphthalene-2-sulphonic acid (CAS RN 87-02-5) | 0 % | — | 31.12.2029 |
| 0.3873 | ex 2922 21 00 | 50 | Sodium hydrogen 4-amino-5-hydroxynaphthalene-2,7-disulphonate (CAS RN 5460-09-3) | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.5997 | ex 2922 21 00 | 60 | 4-Amino-5-hydroxynaphthalene-2,7-disulphonic acid with a purity by weight of 80 % or more (CAS RN 90-20-0) | 0 % | — | 31.12.2029 |
| 0.8564 | ex 2922 29 00 | 13 | 2-(4-Chlorophenoxy)-5-(trifluoromethyl)aniline (CAS RN 349-20-2) with a purity by weight of 98 % or more | 0 % | — | 31.12.2028 |
| 0.8832 | ex 2922 29 00 | 18 | Bis[(4-Methoxyphenyl)methyl]amine (CAS RN 17061-62-0) with a purity by weight of 96 % or more | 0 % | — | 31.12.2029 |
| 0.2702 | ex 2922 29 00 | 20 | 3-Aminophenol (CAS RN 591-27-5) | 0 % | — | 31.12.2029 |
| 0.3982 | ex 2922 29 00 | 25 | 5-Amino-o-cresol (CAS RN 2835-95-2) | 0 % | — | 31.12.2029 |
| 0.6624 | *ex 2922 29 00 | 30 | 1,2-Bis(2-aminophenoxy)ethane (CAS RN 52411-34-4) | 0 % | — | 31.12.2030 |
| 0.7642 | ex 2922 29 00 | 33 | o-Phenetidine (CAS RN 94-70-2) | 0 % | — | 31.12.2029 |
| 0.8934 | *ex 2922 29 00 | 38 | 4-Amino-2,3-dichlorophenol (CAS RN 39183-17-0) with a purity by weight of 98 % or more | 0 % | — | 31.12.2030 |
| 0.4627 | ex 2922 29 00 | 65 | 4-Trifluoromethoxyaniline (CAS RN 461-82-5) | 0 % | — | 31.12.2029 |
| 0.7481 | ex 2922 29 00 | 67 | 4-Chloro-2,5-dimethoxyaniline (CAS RN 6358-64-1) | 0 % | — | 31.12.2029 |
| 0.2692 | ex 2922 29 00 | 70 | 4-Nitro-o-anisidine (CAS RN 97-52-9) | 0 % | — | 31.12.2029 |
| 0.7026 | ex 2922 29 00 | 73 | Tris(4-aminophenyl) thiophosphate (CAS RN 52664-35-4) | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.4956 | *ex 2922 29 00 | 75 | 4-(2-Aminoethyl)phenol (CAS RN 51-67-2) | 0 % | — | 31.12.2030 |
| 0.2696 | ex 2922 29 00 | 80 | 3-Diethylaminophenol (CAS RN 91-68-9) | 0 % | — | 31.12.2029 |
| 0.4914 | *ex 2922 39 00 | 20 | 2-Amino-5-chlorobenzophenone (CAS RN 719-59-5) | 0 % | — | 31.12.2030 |
| 0.7713 | ex 2922 39 00 | 30 | (2-Fluorophenyl)-[2-(methylamino)-5-nitrophenyl]methanone (CAS RN 735-06-8) | 0 % | — | 31.12.2029 |
| 0.6761 | *ex 2922 39 00 | 35 | 5-Chloro-2-(methylamino)benzophenone (CAS RN 1022-13-5) | 0 % | — | 31.12.2030 |
| 0.7371 | ex 2922 39 00 | 45 | 2-Amino-3,5-dibromobenzaldehyde (CAS RN 50910-55-9) with a purity by weight of 98 % or more | 0 % | — | 31.12.2029 |
| 0.3546 | ex 2922 43 00 | 10 | Anthranilic acid (CAS RN 118-92-3) | 0 % | — | 31.12.2029 |
| 0.3547 | ex 2922 49 85 | 10 | Ornithine aspartate (INNM) (CAS RN 3230-94-2) | 0 % | — | 31.12.2029 |
| 0.5037 | *ex 2922 49 85 | 17 | Glycine (CAS RN 56-40-6) with a purity by weight of 95 % or more, whether or not with not more than 5 % addition of anti-caking agent silicon dioxide (CAS RN 112926-00-8) | 0 % | — | 31.12.2030 |
| 0.5619 | ex 2922 49 85 | 20 | 3-Amino-4-chlorobenzoic acid (CAS RN 2840-28-0) | 0 % | — | 31.12.2027 |
| 0.8162 | ex 2922 49 85 | 23 | 2-Ethylhexyl 4-aminobenzoate (CAS RN 26218-04-2) with a purity by weight of 99 % or more | 0 % | — | 31.12.2026 |
| 0.6340 | ex 2922 49 85 | 25 | Dimethyl 2-aminobenzene-1,4-dicarboxylate (CAS RN 5372-81-6) | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8948 | *ex 2922 49 85 | 28 | Magnesium diglycinate (CAS RN 14783-68-7) with a purity by weight of 99 % or more | 0 % | — | 31.12.2030 |
| 0.8234 | ex 2922 49 85 | 33 | 4-Amino-2-chlorobenzoic acid (CAS RN 2457-76-3) with a purity by weight of 98 % or more | 0 % | — | 31.12.2026 |
| 0.3544 | ex 2922 49 85 | 40 | Norvaline (CAS RN 6600-40-4) | 0 % | — | 31.12.2029 |
| 0.8236 | ex 2922 49 85 | 43 | (E)-Ethyl 4-(dimethylamino)but-2-enoate maleate (CAS RN 1690340-79-4) with a purity by weight of 98 % or more | 0 % | — | 31.12.2026 |
| 0.3983 | ex 2922 49 85 | 50 | D-(-)-Dihydrophenylglycine (CAS RN 26774-88-9) | 0 % | — | 31.12.2029 |
| 0.8340 | ex 2922 49 85 | 53 | (S)-ethyl 3-amino-3-phenylpropanoate hemi((2R,3R)-2,3-dihydroxysuccinate) with a purity by weight of 98 % or more | 0 % | — | 31.12.2027 |
| 0.4239 | ex 2922 49 85 | 60 | Ethyl-4-dimethylaminobenzoate (CAS RN 10287-53-3) | 0 % | — | 31.12.2027 |
| 0.8726 | ex 2922 49 85 | 63 | Glycine hydrochloride (CAS RN 6000-43-7) with a purity by weight of 95 % or more, whether or not containing not more than 5 % of anti-caking agent silicon dioxide (CAS RN 112926-00-8), used to produce food flavourings (¹) | 0 % | — | 31.12.2029 |
| 0.7254 | ex 2922 49 85 | 75 | L-alanine isopropyl ester hydrochloride (CAS RN 62062-65-1) | 0 % | — | 31.12.2029 |
| 0.7020 | ex 2922 50 00 | 10 | 2-(2-(2-Aminoethoxy)ethoxy)acetic acid hydrochloride (CAS RN 134979-01-4) | 0 % | — | 31.12.2026 |
| 0.7257 | ex 2922 50 00 | 15 | 3,5-Diiodothyronine (CAS RN 1041-01-6) | 0 % | — | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.4702 | ex 2922 50 00 | 20 | 1-[2-Amino-1-(4-methoxyphenyl)-ethyl]-cyclohexanol hydrochloride (CAS RN 130198-05-9) | 0 % | — | 31.12.2029 |
| 0.8445 | ex 2922 50 00 | 25 | L-Threonine (CAS RN 72-19-5) | 0 % | — | 31.12.2027 |
| 0.8473 | ex 2922 50 00 | 45 | (S)-2-Amino-2-(3-fluoro-5-methoxyphenyl)ethanol hydrochloride (CAS RN 2095692-22-9) with a purity by weight of 98 % or more | 0 % | — | 31.12.2027 |
| 0.8364 | ex 2922 50 00 | 55 | 1-{[4-(Benzylxy)phenyl]-2-(dimethylamino)ethyl}cyclohexanol (CAS RN 93413-61-7) with a purity by weight of 98 % or more | 0 % | — | 31.12.2027 |
| 0.8325 | ex 2922 50 00 | 65 | [4-[2-(Dimethylamino)ethoxy]phenyl](4-hydroxyphenyl)methanone (CAS RN 173163-13-8) with a purity by weight of 98 % or more | 0 % | — | 31.12.2027 |
| 0.3543 | ex 2923 90 00 | 10 | Tetramethylammonium hydroxide (CAS RN 75-59-2), in the form of an aqueous solution containing 25 % ($\pm 0,5$ %) by weight of tetramethylammonium hydroxide | 0 % | — | 31.12.2029 |
| 0.8715 | ex 2923 90 00 | 13 | Bis(N,N,N-trimethyladamantan-1-aminium) sulfate (CAS RN 1000777-61-6) with a purity by weight of 95 % or more, whether or not in aqueous solution containing 20 % or more Bis(N,N,N-trimethyladamantan-1-aminium) sulfate (CAS RN 1000777-61-6) | 0 % | — | 31.12.2029 |
| 0.8159 | ex 2923 90 00 | 30 | Tetrabutylammonium tetrahydroborate (CAS RN 33725-74-5) with a purity by weight of 97 % or more | 0 % | — | 31.12.2026 |
| 0.8931 | *ex 2923 90 00 | 33 | Calcium phosphoryl choline chloride tetrahydrate (CAS RN 72556-74-2) with a purity by weight of 90 % or more | 0 % | — | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.7879 | ex 2923 90 00 | 50 | Betaine hydrochloride (CAS RN 590-46-5), with a purity by weight of 93 % or more | 0 % | — | 31.12.2029 |
| 0.7089 | ex 2923 90 00 | 55 | Tetrabutylammonium bromide (CAS RN 1643-19-2) | 0 % | — | 31.12.2026 |
| 0.7615 | ex 2923 90 00 | 65 | N,N,N-Trimethyl-tricyclo[3.3.1.13,7]decan-1-aminium hydroxide (CAS RN 53075-09-5) in form of an aqueous solution with a content of N,N,N-trimethyl-tricyclo[3.3.1.13,7]decan-1-aminium hydroxide by weight of 17,5 % or more but not more than 27,5 % | 0 % | — | 31.12.2029 |
| 0.5063 | *ex 2923 90 00 | 75 | Tetraethylammonium hydroxide, in the form of an aqueous solution containing: — 35 % (\pm 0,5 %) by weight of tetraethylammonium hydroxide, — not more than 1 000 mg/kg of chloride, — not more than 2 mg/kg of iron, and — not more than 10 mg/kg of potassium | 0 % | — | 31.12.2030 |
| 0.3536 | ex 2923 90 00 | 80 | Diallyldimethylammonium chloride (CAS RN 7398-69-8) , in the form of an aqueous solution containing by weight 63 % or more but not more than 67 % of diallyldimethylammonium chloride | 0 % | — | 31.12.2029 |
| 0.6410 | ex 2923 90 00 | 85 | N,N,N-Trimethylanilinium chloride (CAS RN 138-24-9) | 0 % | — | 31.12.2029 |
| 0.2678 | ex 2924 19 00 | 10 | 2-Acrylamido-2-methylpropanesulphonic acid (CAS RN 15214-89-8) or its sodium salt (CAS RN 5165-97-9), or its ammonium salt (CAS RN 58374-69-9) | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8561 | ex 2924 19 00 | 13 | N-(tert-Butoxycarbonyl)glycine (CAS RN 4530-20-5) with a purity by weight of 98 % or more | 0 % | — | 31.12.2028 |
| 0.8000 | *ex 2924 19 00 | 18 | 2-((Butylamino)carbonyl)oxyethyl acrylate (CAS RN 63225-53-6) with a purity by weight of 97 % or more | 0 % | — | 31.12.2030 |
| 0.8705 | ex 2924 19 00 | 20 | Tert-butyl N-methyl-N-(2-oxopropyl)carbamate (CAS RN 532410-39-2) with a purity by weight of 90 % or more | 0 % | — | 31.12.2029 |
| 0.4380 | ex 2924 19 00 | 25 | Methylcarbamate (CAS RN 598-55-0) with a purity by weight of 98 % or more | 0 % | — | 31.12.2029 |
| 0.8027 | *ex 2924 19 00 | 28 | (2S)-2-Amino-5-(carbamoylaminoo)pentanoic acid; 2-hydroxybutanedioic acid (2:1) (CAS RN 54940-97-5) with a purity by weight of 98 % or more | 0 % | — | 31.12.2030 |
| 0.6549 | ex 2924 19 00 | 35 | Acetamide (CAS RN 60-35-5) | 0 % | — | 31.12.2029 |
| 0.8041 | *ex 2924 19 00 | 38 | Diethyl acetamidomalonate (CAS RN 1068-90-2) with a purity by weight of 98 % or more | 0 % | — | 31.12.2026 |
| 0.8283 | ex 2924 19 00 | 48 | N,N-Dimethylcarbamoyl chloride (CAS RN 79-44-7) with a purity by weight of 99 % or more | 0 % | — | 31.12.2026 |
| 0.8429 | ex 2924 19 00 | 53 | Aqueous solution of propamocarb hydrochloride (ISOM)(CAS RN 25606-41-1), containing by weight 64 % or more, but not more than 68 % of propamocarb hydrochloride | 0 % | — | 31.12.2027 |
| 0.7060 | ex 2924 19 00 | 55 | 2-Propynyl butylcarbamate (CAS RN 76114-73-3) | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.4160 | ex 2924 19 00 | 60 | <i>N,N</i> -Dimethylacrylamide (CAS RN 2680-03-7) | 0 % | — | 31.12.2026 |
| 0.5605 | ex 2924 19 00 | 80 | Tetrabutylurea (CAS RN 4559-86-8) | 0 % | — | 31.12.2027 |
| 0.6266 | ex 2924 29 70 | 17 | 2-(Trifluoromethyl)benzamide (CAS RN 360-64-5) | 0 % | — | 31.12.2029 |
| 0.6568 | ex 2924 29 70 | 23 | Benalaxyl-M (ISO) (CAS RN 98243-83-5) | 0 % | — | 31.12.2029 |
| 0.8153 | ex 2924 29 70 | 25 | 2-[2-(Methoxycarbonyl-phenyl-amino)-phenyl]-acetic acid (CAS RN 353497-35-5) with a purity by weight of 98 % or more | 0 % | — | 31.12.2026 |
| 0.7118 | ex 2924 29 70 | 30 | Sodium 4-(4-methyl-3-nitrobenzoylamino)benzenesulphonate (CAS RN 84029-45-8) | 0 % | — | 31.12.2026 |
| 0.8235 | ex 2924 29 70 | 32 | N-(4-Amino-2-ethoxyphenyl)acetamide (CAS RN 848655-78-7) with a purity by weight of 98 % or more | 0 % | — | 31.12.2026 |
| 0.8621 | ex 2924 29 70 | 34 | Acetic acid—tert-butyl [(1-aminocyclohexyl)methyl]carbamate (1/1) with a purity by weight of 98 % or more | 0 % | — | 31.12.2028 |
| 0.8161 | ex 2924 29 70 | 35 | N-(1,1-Dimethylethyl)-4-amino-benzamide (CAS RN 93483-71-7) with a purity by weight of 99 % or more | 0 % | — | 31.12.2026 |
| 0.8258 | ex 2924 29 70 | 36 | <i>N,N</i> -(2-Chloro-5-methyl-1,4-phenylene)bis[3-oxobutyramide] (CAS RN 41131-65-1) with a purity by weight of 97 % or more | 0 % | — | 31.12.2026 |
| 0.6110 | ex 2924 29 70 | 37 | Beflubutamid (ISO) (CAS RN 113614-08-7) | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8595 | ex 2924 29 70 | 38 | 2-Methyl-2-propenyl{(2S,3R)-3-hydroxy-4-[(2-methylpropyl)amino]-1-phenyl-2- butanyl} carbamate (CAS RN 160232-08-6) with a purity by weight of 97 % or more | 0 % | — | 31.12.2028 |
| 0.8696 | ex 2924 29 70 | 39 | N-[(9H-Fluoren-9-ylmethoxy)carbonyl]glycine (CAS RN 29022-11-5) with a purity by weight of 99 % or more | 0 % | — | 31.12.2029 |
| 0.5066 | *ex 2924 29 70 | 40 | N,N'-1,4-Phenylenebis[3-oxobutyramide], (CAS RN 24731-73-5) | 0 % | — | 31.12.2030 |
| 0.8697 | ex 2924 29 70 | 41 | (2S)-6-amino-2-({[(9H-fluoren-9-yl)methoxy]carbonyl}amino)hexanoic acid hydrochloride (CAS RN 139262-23-0) with a purity by weight of 90 % or more | 0 % | — | 31.12.2029 |
| 0.8698 | ex 2924 29 70 | 42 | N-Benzylxycarbonylglycine (CAS RN 1138-80-3) with a purity by weight of 99 % or more | 0 % | — | 31.12.2029 |
| 0.8183 | ex 2924 29 70 | 46 | S-Metolachlor (ISO) (CAS RN 87392-12-9) with a purity by weight of 98 % or more | 0 % | — | 31.12.2026 |
| 0.7841 | ex 2924 29 70 | 47 | (S)-tert-Butyl (1-amino-3-(4-iodophenyl)-1-oxopropan-2-yl)carbamate (CAS RN 868694-44-4) with a purity by weight of 95 % or more | 0 % | — | 31.12.2029 |
| 0.8381 | ex 2924 29 70 | 48 | (3R)-N-(tert-butoxycarbonyl)-3-amino-4-(2,4,5-trifluorophenyl)butanoic acid (CAS RN 486460-00-8) with a purity by weight of 97 % or more | 0 % | — | 31.12.2027 |
| 0.8346 | ex 2924 29 70 | 49 | tert-Butyl [(1R,2S,5S)-2-amino-5-(dimethylcarbamoyl)cyclohexyl]carbamate ethanedioate (CAS RN 1210348-34-7) with a purity by weight of 95 % or more | 0 % | — | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8184 | ex 2924 29 70 | 52 | Zoxamide (ISO) (CAS RN 156052-68-5) with a purity by weight of 97 % or more | 0 % | — | 31.12.2026 |
| 0.5622 | ex 2924 29 70 | 53 | 4-Amino-N-[4-(aminocarbonyl)phenyl]benzamide (CAS RN 74441-06-8) | 0 % | — | 31.12.2027 |
| 0.8362 | ex 2924 29 70 | 54 | 2-[4-(Benzyl)phenyl]-N,N-dimethylacetamide (CAS RN 919475-15-3) with a purity by weight of 98 % or more | 0 % | — | 31.12.2027 |
| 0.5069 | *ex 2924 29 70 | 55 | N,N'-(2,5-Dimethyl-1,4-phenylene)bis[3-oxobutyramide] (CAS RN 24304-50-5) | 0 % | — | 31.12.2030 |
| 0.8315 | ex 2924 29 70 | 56 | Valifenalate (ISO) (CAS RN 283159-90-0) with a purity by weight of 98 % or more | 0 % | — | 31.12.2027 |
| 0.8710 | ex 2924 29 70 | 57 | 2-(Dimethylaminomethylidene)-4-methoxy-3-oxo-N-[(2,4,6-trifluorophenyl)methyl] butanamide (CAS RN 1846582-17-9) with a purity by weight of 95 % or more | 0 % | — | 31.12.2029 |
| 0.8043 | *ex 2924 29 70 | 58 | 2-Chloro-N-[1-(4-chloro-3-fluorophenyl)-2-methylpropan-2-yl] acetamide (CAS RN 787585-35-7) with a purity by weight of 98 % or more | 0 % | — | 31.12.2030 |
| 0.6767 | *ex 2924 29 70 | 62 | 2-Chlorobenzamide (CAS RN 609-66-5) | 0 % | — | 31.12.2030 |
| 0.6766 | *ex 2924 29 70 | 64 | N-(3',4'-dichloro-5-fluoro[1,1'-biphenyl]-2-yl)acetamide (CAS RN 877179-03-8) | 0 % | — | 31.12.2030 |
| 0.7632 | ex 2924 29 70 | 67 | N,N'-(2,5-Dichloro-1,4-phenylene)bis[3-oxobutyramide] (CAS RN 42487-09-2) | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.8919 | *ex 2924 29 70 | 68 | Sacubitril calcium (INNM) (CAS RN 1369773-39-6) with a purity by weight of 98 % or more | 0 % | — | 31.12.2030 |
| 0.6480 | ex 2924 29 70 | 73 | Napropamide (ISO) (CAS RN 15299-99-7) | 0 % | — | 31.12.2029 |
| 0.2672 | ex 2924 29 70 | 75 | 3-Amino- <i>p</i> -anisанилід (CAS RN 120-35-4) | 0 % | — | 31.12.2029 |
| 0.2673 | ex 2924 29 70 | 85 | <i>p</i> -Aminobenzamide (CAS RN 2835-68-9) | 0 % | — | 31.12.2029 |
| 0.4493 | ex 2924 29 70 | 89 | Flutolanil (ISO) (CAS RN 66332-96-5) | 0 % | — | 31.12.2029 |
| 0.3691 | ex 2924 29 70 | 92 | 3-Hydroxy-2-naphthaniлід (CAS RN 92-77-3) | 0 % | — | 31.12.2029 |
| 0.3692 | ex 2924 29 70 | 93 | 3-Hydroxy-2'-methyl-2-naphthaniлід (CAS RN 135-61-5) | 0 % | — | 31.12.2029 |
| 0.3693 | ex 2924 29 70 | 94 | 2'-Ethoxy-3-hydroxy-2-naphthaniлід (CAS RN 92-74-0) | 0 % | — | 31.12.2029 |
| 0.3863 | ex 2924 29 70 | 97 | 1,1-Cyclohexanediacetic acid monoamide (CAS RN 99189-60-3) | 0 % | — | 31.12.2029 |
| 0.3526 | ex 2925 11 00 | 30 | 1,2-benzisothiazol-3(2H)-one 1,1-dioxide (CAS RN 81-07-2) or sodium 1,2-benzothiazol-3-olate 1,1-dioxide (CAS RN 128-44-9) with a purity by weight of 98 % or more | 0 % | — | 31.12.2029 |
| 0.2674 | ex 2925 19 95 | 10 | N-Phenylmaleimide (CAS RN 941-69-5) | 0 % | — | 31.12.2029 |
| 0.5612 | ex 2925 19 95 | 20 | 4,5,6,7-Tetrahydroisoindole-1,3-dione (CAS RN 4720-86-9) | 0 % | — | 31.12.2027 |
| 0.5740 | ex 2925 19 95 | 30 | <i>N,N'</i> -(<i>m</i> -Phenylene)dimaleimide (CAS RN 3006-93-7) | 0 % | — | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8704 | ex 2925 19 95 | 50 | 2-{2-[2-(1,3-Dioxo-2,3-dihydro-1H-isoindol-2-yl)ethoxy]ethoxy}acetic acid (CAS RN 75001-09-1) with a purity by weight of 95 % or more | 0 % | — | 31.12.2029 |
| 0.2934 | ex 2925 29 00 | 10 | Dicyclohexylcarbodiimide (CAS RN 538-75-0) | 0 % | — | 31.12.2029 |
| 0.5891 | ex 2925 29 00 | 20 | N-[3-(Dimethylamino)propyl]-N'-ethylcarbodiimide hydrochloride (CAS RN 25952-53-8) | 0 % | — | 31.12.2029 |
| 0.8339 | ex 2925 29 00 | 25 | 1-(3-(2-Hydroxyethyl)phenyl)guanidinium methanesulfonate (CAS RN 2101429-50-7) with a purity by weight of 99 % or more | 0 % | — | 31.12.2027 |
| 0.8943 | *ex 2925 29 00 | 35 | N-Amidinosarcosine hydrate (CAS RN 6020-87-7) with a purity by weight of 99 % or more | 0 % | — | 31.12.2030 |
| 0.7749 | ex 2925 29 00 | 40 | N-Amidinosarcosine (CAS RN 57-00-1) | 0 % | — | 31.12.2029 |
| 0.7832 | ex 2925 29 00 | 50 | (Chloromethylene)dimethyliminium chloride (CAS RN 3724-43-4) with a purity by weight of 95 % or more | 0 % | — | 31.12.2029 |
| 0.8040 | *ex 2925 29 00 | 70 | Bromomethylidene(dimethyl)azanium bromide (CAS RN 24774-61-6) with a purity by weight of 97 % or more | 0 % | — | 31.12.2030 |
| 0.8873 | ex 2925 29 00 | 80 | Ethyl 4-[(methylphenylamino)methylene]amino]benzoate (CAS RN 57834-33-0) with a purity of 99 % or more by weight | 0 % | — | 31.12.2029 |
| 0.7408 | ex 2926 90 70 | 18 | Flumethrin (ISO) (CAS RN 69770-45-2) | 0 % | — | 31.12.2027 |
| 0.7466 | ex 2926 90 70 | 19 | 2-(4-Amino-2-chloro-5-methylphenyl)-2-(4-chlorophenyl) acetonitrile (CAS RN 61437-85-2) | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.2668 | ex 2926 90 70 | 20 | 2-(<i>m</i> -Benzoylphenyl)propiononitrile (CAS RN 42872-30-0) | 0 % | — | 31.12.2029 |
| 0.7458 | ex 2926 90 70 | 21 | 4-Bromo-2-chlorobenzonitrile (CAS RN 154607-01-9) | 0 % | — | 31.12.2029 |
| 0.7514 | ex 2926 90 70 | 22 | Acetonitrile (CAS RN 75-05-8) | 0 % | — | 31.12.2029 |
| 0.7805 | ex 2926 90 70 | 24 | 2-Hydroxy-2-methylpropiononitrile (CAS RN 75-86-5) with a purity by weight of 99 % or more | 0 % | — | 31.12.2029 |
| 0.5227 | ex 2926 90 70 | 25 | 2,2-Dibromo-3-nitrilopropionamide (CAS RN 10222-01-2) | 0 % | — | 31.12.2026 |
| 0.6149 | ex 2926 90 70 | 27 | Cyhalofop-butyl (ISO) (CAS RN 122008-85-9) | 0 % | — | 31.12.2029 |
| 0.8321 | ex 2926 90 70 | 28 | 3-Bromo-6-chloro-2-fluorobenzonitrile (CAS RN 943830-79-3) with a purity by weight of 98 % or more | 0 % | — | 31.12.2027 |
| 0.7430 | ex 2926 90 70 | 29 | 2-Cyclohexylidene-2-phenylacetonitrile (CAS RN 10461-98-0) with a purity by weight of 95 % or more | 0 % | — | 31.12.2027 |
| 0.7201 | ex 2926 90 70 | 30 | 4,5-Dichloro-3,6-dioxocyclohexa-1,4-diene-1,2-dicarbonitrile (CAS RN 84-58-2) | 0 % | — | 31.12.2026 |
| 0.3522 | ex 2926 90 70 | 32 | Ethyl cyanoacetate (CAS RN 105-56-6) or methyl cyanoacetate (CAS RN 105-34-0) with a purity by weight of 97 % or more | 0 % | — | 31.12.2029 |
| 0.7406 | ex 2926 90 70 | 33 | Deltamethrin (ISO) (CAS RN 52918-63-5) | 0 % | — | 31.12.2027 |
| 0.8907 | *ex 2926 90 70 | 34 | 2,3,3,3-Tetrafluoro-2-(trifluoromethyl)propanenitrile (CAS RN 42532-60-5) with a purity by weight of 99 % or more | 0 % | — | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.7034 | ex 2926 90 70 | 35 | 4-Cyano-2-methoxybenzaldehyde (CAS RN 21962-45-8) | 0 % | — | 31.12.2026 |
| 0.8908 | *ex 2926 90 70 | 36 | 3,4-Dimethoxybicyclo[4.2.0]octa-1,3,5,-triene-7-carbonitrile (CAS RN 35202-54-1) with a purity by weight of 97 % or more | 0 % | — | 31.12.2030 |
| 0.8217 | ex 2926 90 70 | 56 | Methyl 2-cyano-2-propylpentanoate (CAS RN 66546-92-7) with a purity by weight of 97 % or more | 0 % | — | 31.12.2026 |
| 0.4182 | ex 2926 90 70 | 61 | <i>m</i> -(1-Cyanoethyl)benzoic acid (CAS RN 5537-71-3) | 0 % | — | 31.12.2026 |
| 0.4802 | ex 2926 90 70 | 70 | Methacrylonitrile (CAS RN 126-98-7) | 0 % | — | 31.12.2029 |
| 0.3521 | ex 2926 90 70 | 75 | Ethyl 2-cyano-2-ethyl-3-methylhexanoate (CAS RN 100453-11-0) | 0 % | — | 31.12.2029 |
| 0.3516 | ex 2926 90 70 | 80 | Ethyl 2-cyano-2-phenylbutyrate (CAS RN 718-71-8) | 0 % | — | 31.12.2029 |
| 0.3514 | ex 2926 90 70 | 86 | Ethylenediaminetetraacetonitrile (CAS RN 5766-67-6) | 0 % | — | 31.12.2029 |
| 0.3515 | ex 2926 90 70 | 89 | Butyronitrile (CAS RN 109-74-0) | 0 % | — | 31.12.2029 |
| 0.7337 | ex 2927 00 00 | 25 | 2,2'-Azobis(4-methoxy-2,4-dimethylvaleronitrile) (CAS RN 15545-97-8) | 0 % | — | 31.12.2027 |
| 0.2667 | ex 2927 00 00 | 45 | 2,2'-Dimethyl-2,2'-azodipropionamidine dihydrochloride (CAS RN 2997-92-4) with a purity by weight of 97 % or more | 0 % | — | 31.12.2029 |
| 0.2810 | ex 2927 00 00 | 55 | 4'-Aminoazobenzene-4-sulphonic acid (CAS RN 104-23-4) with a purity by weight of 90 % or more | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.2661 | ex 2928 00 90 | 10 | 3,3'-Bis(3,5-di- <i>tert</i> -butyl-4-hydroxyphenyl)-N,N'-bipropionamide (CAS RN 32687-78-8) | 0 % | — | 31.12.2029 |
| 0.6479 | ex 2928 00 90 | 13 | Cymoxanil (ISO) (CAS RN 57966-95-7) | 0 % | — | 31.12.2029 |
| 0.6548 | ex 2928 00 90 | 18 | Acetone oxime (CAS RN 127-06-0) of a purity by weight of 99 % or more | 0 % | — | 31.12.2029 |
| 0.6871 | *ex 2928 00 90 | 23 | Metobromuron (ISO) (CAS RN 3060-89-7) with a purity by weight of 98 % or more | 0 % | — | 31.12.2030 |
| 0.4929 | *ex 2928 00 90 | 25 | Acetaldehyde oxime (CAS RN 107-29-9) in an aqueous solution | 0 % | — | 31.12.2030 |
| 0.6985 | ex 2928 00 90 | 28 | Pentan-2-one oxime (CAS RN 623-40-5) | 0 % | — | 31.12.2026 |
| 0.5438 | ex 2928 00 90 | 30 | N-Isopropylhydroxylamine (CAS RN 5080-22-8) | 0 % | — | 31.12.2026 |
| 0.7448 | ex 2928 00 90 | 33 | 4- Chlorophenylhydrazine Hydrochloride (CAS RN 1073-70-7) | 0 % | — | 31.12.2029 |
| 0.8061 | *ex 2928 00 90 | 38 | Aqueous solution of methoxyammonium chloride (CAS RN 593-56-6), containing by weight: — 30 % or more but not more than 40 % of methoxyammonium chloride — not more than 4 % of hydrochloric acid | 0 % | — | 31.12.2030 |
| 0.8093 | *ex 2928 00 90 | 43 | 2-(3-Methoxy-3-oxopropyl)-1,1,1-trimethylhydrazinium bromide (CAS RN 106966-25-0) with a purity by weight of 99 % or more | 0 % | — | 31.12.2030 |
| 0.5919 | ex 2928 00 90 | 45 | Tebufenozide (ISO) (CAS RN 112410-23-8) | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.8158 | ex 2928 00 90 | 48 | 1-{[(1H-Fluoren-9-ylmetoxi)carbonil]oxi}pyrrolidine-2,5-dione (CAS RN 82911-69-1) with a purity by weight of 98 % or more | 0 % | — | 31.12.2026 |
| 0.6635 | *ex 2928 00 90 | 50 | Aqueous solution of 2,2'-(hydroxyimino) bisethanesulphonic acid disodium salt (CAS RN 133986-51-3) with a content by weight of more than 33,5 % but not more than 36,5 % | 0 % | — | 31.12.2030 |
| 0.8474 | ex 2928 00 90 | 53 | Ethyl chloro[(4-methoxyphenyl)hydrazone]acetate (CAS RN 27143-07-3) with a purity by weight of 98 % or more | 0 % | — | 31.12.2027 |
| 0.5918 | ex 2928 00 90 | 55 | Aminoguanidinium hydrogen carbonate (CAS RN 2582-30-1) | 0 % | — | 31.12.2029 |
| 0.8731 | ex 2928 00 90 | 63 | Daminozide (ISO) (CAS RN 1596-84-5) with a purity by weight of 97 % or more | 0 % | — | 31.12.2029 |
| 0.4544 | ex 2928 00 90 | 70 | Butanone oxime (CAS RN 96-29-7) | 0 % | — | 31.12.2029 |
| 0.5228 | ex 2928 00 90 | 75 | Metaflumizone (ISO) (CAS RN 139968-49-3) | 0 % | — | 31.12.2026 |
| 0.3510 | ex 2928 00 90 | 80 | Cyflufenamid (ISO) (CAS RN 180409-60-3) | 0 % | — | 31.12.2029 |
| 0.5827 | ex 2929 10 00 | 20 | Butyl isocyanate (CAS RN 111-36-4) | 0 % | — | 31.12.2027 |
| 0.4188 | ex 2929 10 00 | 35 | 1,3-Bis(isocyanatomethyl)benzene (CAS RN 3634-83-1) with a purity by weight of 99 % or more | 0 % | — | 31.12.2029 |
| 0.2660 | ex 2929 10 00 | 40 | <i>m</i> -Isopropenyl- <i>a,a</i> -dimethylbenzyl isocyanate (CAS RN 2094-99-7) | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.5033 | ex 2929 10 00 | 45 | 2,5 (and 2,6)-Bis(isocyanatomethyl)bicyclo[2.2.1]heptane (CAS RN 74091-64-8) with a purity by weight of 99 % or more | 0 % | — | 31.12.2029 |
| 0.2657 | ex 2929 10 00 | 50 | <i>m</i> -Phenylenediisopropylidene diisocyanate (CAS RN 2778-42-9) | 0 % | — | 31.12.2029 |
| 0.3509 | ex 2929 10 00 | 60 | Trimethylhexamethylene diisocyanate, mixed isomers | 0 % | — | 31.12.2029 |
| 0.8451 | ex 2929 10 00 | 65 | Ethyl isocyanate (CAS RN 109-90-0) with a purity by weight of 98 % or more | 0 % | — | 31.12.2027 |
| 0.8171 | ex 2929 90 90 | 40 | N-Butylphosphorothioic triamide (CAS RN 94317-64-3) with a purity by weight of 97 % or more | 0 % | — | 31.12.2026 |
| 0.8172 | ex 2929 90 90 | 50 | N-Propylphosphorothioic triamide (CAS RN 916809-14-8) with a purity by weight of 97 % or more | 0 % | — | 31.12.2026 |
| 0.8611 | ex 2929 90 90 | 60 | (2S)-2-[[2-[2-[2-[2-[2-[2-[2-(2-Azidoethoxy)ethoxy]ethoxy]ethoxy]ethoxy]ethoxy]ethoxy]ethoxy]ethylamino]-2-oxoethoxy]acetyl]amino]-N-[4-(hydroxymethyl)phenyl]-6-[[4-methoxyphenyl]-diphenylmethyl]amino]hexanamide (CAS RN 1224601-12-0) with a purity by weight of 98 % or more | 0 % | — | 31.12.2028 |
| 0.8701 | ex 2929 90 90 | 70 | <i>N,N</i> "-[(2S,3E,5S)-1,6-Diphenylhex-3-ene-2,5-diyl]bis(N,N-dimethylsulfuric diamide) (CAS RN 1247119-27-2) in the form of an aqueous solution containing by weight 70 % or more but not more than 95 % of <i>N,N</i> "-[(2S,3E,5S)-1,6-Diphenylhex-3-ene-2,5-diyl]bis(N, N-dimethylsulfuric diamide) | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.4298 | ex 2930 20 00 | 40 | Prosulfocarb (ISO) (CAS RN 52888-80-9) with purity by weight of 97 % or more | 0 % | — | 31.12.2027 |
| 0.8036 | *ex 2930 90 95 | 11 | Benzyl (2S)-2-amino-3-[3-(methanesulphonylphenyl)]propanoate hydrochloride (CAS RN 1194550-59-8) with a purity by weight of 98 % or more | 0 % | — | 31.12.2026 |
| 0.6551 | ex 2930 90 95 | 16 | 3-(Dimethoxymethylsilyl)-1-propanethiol (CAS RN 31001-77-1) | 0 % | — | 31.12.2029 |
| 0.5999 | ex 2930 90 95 | 17 | 2-(3-Aminophenylsulphonyl)ethyl hydrogen sulphate (CAS RN 2494-88-4) | 0 % | — | 31.12.2029 |
| 0.7748 | ex 2930 90 95 | 18 | Dimethyl sulfone (CAS RN 67-71-0) | 0 % | — | 31.12.2029 |
| 0.8050 | *ex 2930 90 95 | 19 | 4-Amino-5-(ethanesulphonyl)-2-methoxybenzoic acid (CAS RN 71675-87-1) with a purity by weight of 98 % or more | 0 % | — | 31.12.2030 |
| 0.7799 | ex 2930 90 95 | 20 | 4-(4-Methylphenylthio)benzophenone (CAS RN 83846-85-9) | 0 % | — | 31.12.2029 |
| 0.6750 | ex 2930 90 95 | 21 | [2,2'-Thio-bis(4- <i>tert</i> -octylphenolato)]-n-butylamine nickel (CAS RN 14516-71-3) | 0 % | — | 31.12.2026 |
| 0.6617 | *ex 2930 90 95 | 25 | Bis(4-chlorophenyl)sulphone (CAS RN 80-07-9) with a purity by weight of 98 % or more | 3,2 % | — | 31.12.2027 |
| 0.6873 | *ex 2930 90 95 | 26 | Folpet (ISO)(CAS RN 133-07-3) with a purity by weight of 97,5 % or more | 0 % | — | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8069 | *ex 2930 90 95 | 28 | Mesotrione (ISO) (CAS RN 104206-82-8) in form of wet cake or wet paste or in its crystalline form, with <ul style="list-style-type: none">— a purity of 74 % or more by weight and,— a maximum water content of 23 % by weight | 0 % | — | 31.12.2030 |
| 0.7833 | ex 2930 90 95 | 31 | (p-Toluenesulphonyl)methyl isocyanide (CAS RN 36635-61-7) with a purity by weight of 98 % or more | 0 % | — | 31.12.2029 |
| 0.8152 | ex 2930 90 95 | 32 | 2-Methoxy-N-[2-nitro-5-(phenylsulfanyl)phenyl]acetamide (CAS RN 63470-85-9) with a purity by weight of 96 % or more | 0 % | — | 31.12.2026 |
| 0.6584 | ex 2930 90 95 | 33 | 2-Amino-5-[(2-(sulfoxy)ethyl)sulfonyl]benzenesulfonic acid (CAS RN 42986-22-1) | 0 % | — | 31.12.2029 |
| 0.3811 | ex 2930 90 95 | 35 | Glutathione (CAS RN 70-18-8) | 0 % | — | 31.12.2026 |
| 0.8510 | ex 2930 90 95 | 36 | Anhydrous potassium O-isopentyl-dithiocarbonate (CAS RN 928-70-1) with a purity by weight of 90 % or more | 0 % | — | 31.12.2027 |
| 0.8447 | ex 2930 90 95 | 39 | Thiodiacetic acid (CAS RN 123-93-3) with a purity by weight of 98 % or more | 0 % | — | 31.12.2027 |
| 0.2928 | ex 2930 90 95 | 40 | 3,3'-Thiodi(propionic acid) (CAS RN 111-17-1) | 0 % | — | 31.12.2029 |
| 0.8481 | ex 2930 90 95 | 41 | 2,2'-Diallyl-4,4'-sulphonyldiphenol (CAS RN 41481-66-7) with a purity by weight of 96 % or more | 0 % | — | 31.12.2027 |
| 0.6167 | ex 2930 90 95 | 43 | Trimethylsulfoxonium iodide (CAS RN 1774-47-6) | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.2931 | ex 2930 90 95 | 45 | 2-[(<i>p</i> -Aminophenyl)sulphonyl]ethyl hydrogen sulphate (CAS RN 2494-89-5) | 0 % | — | 31.12.2029 |
| 0.7689 | ex 2930 90 95 | 50 | 3-Mercaptopropionic acid (CAS RN 107-96-0) | 0 % | — | 31.12.2029 |
| 0.5114 | *ex 2930 90 95 | 55 | Thiourea (CAS RN 62-56-6) | 0 % | — | 31.12.2030 |
| 0.4629 | ex 2930 90 95 | 64 | 3-Chloro-2-methylphenyl methyl sulphide (CAS RN 82961-52-2) | 0 % | — | 31.12.2029 |
| 0.4296 | ex 2930 90 95 | 68 | Clethodim (ISO) (CAS RN 99129-21-2) | 0 % | — | 31.12.2027 |
| 0.4187 | ex 2930 90 95 | 78 | 4-Mercaptomethyl-3,6-dithia-1,8-octanedithiol (CAS RN 131538-00-6) | 0 % | — | 31.12.2026 |
| 0.2999 | ex 2930 90 95 | 80 | Captan (ISO) (CAS RN 133-06-2) | 0 % | — | 31.12.2029 |
| 0.4694 | ex 2930 90 95 | 81 | Disodium hexamethylene-1,6-bisthioulate dihydrate (CAS RN 5719-73-3) | 3 % | — | 31.12.2029 |
| 0.8694 | ex 2930 90 95 | 82 | Propane-1,3-dithiol (CAS RN 109-80-8) with a purity by weight of 98 % or more | 0 % | — | 31.12.2029 |
| 0.7985 | *ex 2930 90 95 | 88 | 1-{4-[(4-Benzoylphenyl)sulphonyl]phenyl}-2-methyl-2-[(4-methylphenyl)sulphonyl]propan-1-one (CAS RN 272460-97-6) with a purity by weight of 94 % or more | 0 % | — | 31.12.2030 |
| 0.4094 | ex 2930 90 95 | 89 | Potassium- or sodium-salt of O-ethyl-, O-isopropyl-, O-butyl-, O-isobutyl- or O-pentyl-dithiocarbonates | 0 % | — | 31.12.2026 |
| 0.7070 | ex 2930 90 95 | 93 | 1-Hydrazino-3-(methylthio)propan-2-ol (CAS RN 14359-97-8) | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.7078 | ex 2930 90 95 | 95 | N-(Cyclohexylthio)phthalimide (CAS RN 17796-82-6) | 0 % | — | 31.12.2026 |
| 0.7086 | ex 2930 90 95 | 97 | Diphenyl sulphone (CAS RN 127-63-9) | 0 % | — | 31.12.2026 |
| 0.5741 | ex 2931 49 80 | 08 | Sodium diisobutyldithiophosphinate (CAS RN 13360-78-6) in an aqueous solution | 0 % | — | 31.12.2027 |
| 0.8546 | ex 2931 49 80 | 10 | Triethyl phosphonoacetate (CAS RN 867-13-0) with a purity by weight of 98 % or more | 0 % | — | 31.12.2028 |
| 0.5492 | ex 2931 49 80 | 13 | Trioctylphosphine oxide (CAS RN 78-50-2) | 0 % | — | 31.12.2026 |
| 0.3492 | ex 2931 49 80 | 20 | Tetrabutylphosphonium acetate (CAS RN 30345-49-4) in the form of an aqueous solution, containing by weight 40 % or more but not more than 50 % of tetrabutylphosphonium acetate | 0 % | — | 31.12.2029 |
| 0.5758 | ex 2931 49 80 | 25 | (Z)-Prop-1-en-1-ylphosphonic acid (CAS RN 25383-06-6) | 0 % | — | 31.12.2027 |
| 0.7533 | ex 2931 49 80 | 35 | Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate (CAS RN 84434-11-7) | 0 % | — | 31.12.2029 |
| 0.2656 | ex 2931 49 80 | 38 | N-(Phosphonomethyl)iminodiacetic acid (CAS RN 5994-61-6) containing by weight not more than 15 % of water, and with a dry weight purity of 97 % or more | 0 % | — | 31.12.2029 |
| 0.5229 | ex 2931 49 80 | 40 | Tetrakis(hydroxymethyl)phosphonium chloride (CAS RN 124-64-1) | 0 % | — | 31.12.2026 |
| 0.3987 | ex 2931 49 80 | 55 | 3-(Hydroxyphenylphosphinoyl)propionic acid (CAS RN 14657-64-8) | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.7709 | ex 2931 59 90 | 50 | 2-Chloroethylphosphonic acid (CAS RN 16672-87-0) solid or in aqueous solution, with a content by weight of 2-Chloroethylphosphonic acid of 65 % or more | 0 % | — | 31.12.2029 |
| 0.4515 | ex 2931 90 00 | 15 | Methylcyclopentadienyl manganese tricarbonyl (CAS RN 12108-13-3) containing not more than 4,9 % by weight of cyclopentadienyl manganese tricarbonyl | 0 % | — | 31.12.2029 |
| 0.8051 | *ex 2931 90 00 | 23 | Ixazomib citrate (INNM) (CAS RN 1239908-20-3) with a purity by weight of 95 % or more | 0 % | — | 31.12.2030 |
| 0.8063 | *ex 2931 90 00 | 28 | Triethoxy(3-isocyanatopropyl)silane (CAS RN 24801-88-5) with a purity by weight of 96 % or more | 0 % | — | 31.12.2030 |
| 0.8272 | ex 2931 90 00 | 30 | Tert-Butylchlorodimethylsilane (CAS RN 18162-48-6) with a purity by weight of 99 % or more | 0 % | — | 31.12.2026 |
| 0.8316 | ex 2931 90 00 | 38 | 2-(Trimethylsilyl)ethoxymethyl chloride (CAS RN 76513-69-4) with a purity by weight of 98 % or more | 0 % | — | 31.12.2027 |
| 0.8442 | ex 2931 90 00 | 40 | Chlorotrimethylsilane (CAS RN 75-77-4) with a purity by weight of 98 % or more | 0 % | — | 31.12.2027 |
| 0.8640 | ex 2931 90 00 | 43 | Trimethylindium (CAS RN 3385-78-2) with a purity by weight of 99 % or more | 0 % | — | 31.12.2028 |
| 0.8649 | ex 2931 90 00 | 48 | 4-Phenoxybenzeneboronic acid (CAS RN 51067-38-0) with a purity by weight of 98 % or more | 0 % | — | 31.12.2028 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.4121 | ex 2931 90 00 | 50 | Trimethylsilane (CAS RN 993-07-7) | 0 % | — | 31.12.2026 |
| 0.8554 | ex 2931 90 00 | 55 | 3-(Hydroxymethyl)phenylboronic acid (CAS RN 87199-15-3) with a purity by weight of 95 % or more | 0 % | — | 31.12.2028 |
| 0.8652 | ex 2931 90 00 | 58 | Trimethylgallium (CAS RN 1445-79-0) with a purity by weight of 99 % or more | 0 % | — | 31.12.2028 |
| 0.8941 | *ex 2931 90 00 | 68 | Hydrogen tetrakis(pentafluorophenyl)borate(1-)—N,N-dimethylaniline (1:1) (CAS RN 118612-00-3) with a purity by weight of 99 % or more | 0 % | — | 31.12.2030 |
| 0.3486 | *ex 2932 13 00 | 10 | Tetrahydrofurfuryl alcohol (CAS RN 97-99-4) | 0 % | — | 31.12.2030 |
| 0.4590 | ex 2932 14 00 | 20 | 1,6-Dichloro-1,6-dideoxy- β -D-fructofuranosyl-4-chloro-4-deoxy- α -D-galactopyranoside (CAS RN 56038-13-2) with a purity by weight of 98 % or more | 0 % | — | 31.12.2029 |
| 0.8615 | ex 2932 19 00 | 15 | 2-Methylfuran (CAS RN 534-22-5) with a purity by weight of 98 % or more | 0 % | — | 31.12.2028 |
| 0.8636 | ex 2932 19 00 | 25 | Methyl tetrahydro-2-furancarboxylate (CAS RN 37443-42-8) with a purity by weight of 98 % or more | 0 % | — | 31.12.2028 |
| 0.8605 | ex 2932 19 00 | 35 | (2S,3S,4S,5R)-3-(3,4-Difluoro-2-methoxyphenyl)-4,5-dimethyl-5-(trifluoromethyl) tetrahydrofuran-2-yl-4-nitrobenzoate (CAS RN 2875066-49-0) with a purity by weight of 97 % or more | 0 % | — | 31.12.2028 |
| 0.4514 | ex 2932 19 00 | 41 | 2,2 Di(tetrahydrofuryl)propane (CAS RN 89686-69-1) | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.8252 | ex 2932 19 00 | 55 | (3S)-3-[4-[(5-Bromo-2-chlorophenyl)methyl]phenoxy]tetrahydro-furan (CAS RN 915095-89-5) with a purity by weight of 97 % or more | 0 % | — | 31.12.2026 |
| 0.7614 | ex 2932 19 00 | 65 | Tefuryltrione (ISO) (CAS RN 473278-76-1) | 0 % | — | 31.12.2029 |
| 0.3487 | ex 2932 19 00 | 70 | Furfurylamine (CAS RN 617-89-0) | 0 % | — | 31.12.2029 |
| 0.5240 | ex 2932 19 00 | 80 | 5-Nitrofurfurylidene di(acetate) (CAS RN 92-55-7) | 0 % | — | 31.12.2026 |
| 0.5257 | ex 2932 20 90 | 15 | Coumarin (CAS RN 91-64-5) | 0 % | — | 31.12.2026 |
| 0.7958 | *ex 2932 20 90 | 18 | 4-Hydroxycoumarin (CAS-RN 1076-38-6) with a purity by weight of 98 % or more | 0 % | — | 31.12.2030 |
| 0.8478 | ex 2932 20 90 | 28 | (R)-3-(3,4-difluoro-2-methoxyphenyl)-4,5-dimethyl-5-(trifluoromethyl)furan-2(5H)-one (CAS RN 2875066-35-4) with a purity by weight of 98 % or more | 0 % | — | 31.12.2027 |
| 0.8532 | ex 2932 20 90 | 33 | 6-Cyclohexyl-4-methyl-2H-pyran-2-one (CAS RN 14818-35-0) with a purity of 99 % by weight or more | 0 % | — | 31.12.2028 |
| 0.8944 | *ex 2932 20 90 | 38 | 6-Dimethylamino-3,3-bis(4-dimethylaminophenyl)phthalide (CAS RN 1552-42-7) with a purity by weight of 96 % or more | 0 % | — | 31.12.2030 |
| 0.5611 | ex 2932 20 90 | 40 | (S)-(-)- α -Amino- γ -butyrolactone hydrobromide (CAS RN 15295-77-9) | 0 % | — | 31.12.2027 |
| 0.6094 | ex 2932 20 90 | 45 | 2,2-Dimethyl-1,3-dioxane-4,6-dione (CAS RN 2033-24-1) | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.7283 | ex 2932 20 90 | 50 | L-Lactide (CAS RN 4511-42-6), D-lactide (CAS RN 13076-17-0), dilactide (CAS RN 95-96-5) or meso-lactide (CAS RN 13076-19-2), each with a purity by weight of 90 % or more | 0 % | — | 31.12.2027 |
| 0.4162 | ex 2932 20 90 | 60 | 6'-(Diethylamino)-3'-methyl-2'-(phenylamino)-spiro[isobenzofuran-1(3H),9'-[9H] xanthen]-3-one (CAS RN 29512-49-0) | 0 % | — | 31.12.2026 |
| 0.7812 | ex 2932 20 90 | 63 | Selamectin (INN) 5Z-isomer (CAS RN 220119-17-5) | 0 % | — | 31.12.2029 |
| 0.6620 | *ex 2932 20 90 | 65 | Sodium 4-(methoxycarbonyl)-5-oxo-2,5-dihydrofuran-3-olate (CAS RN 1134960-41-0) | 0 % | — | 31.12.2030 |
| 0.4161 | ex 2932 20 90 | 71 | 6'-(Dibutylamino)-3'-methyl-2'-(phenylamino)-spiro[isobenzofuran-1(3H),9'-[9H] xanthen]-3-one (CAS RN 89331-94-2) | 0 % | — | 31.12.2026 |
| 0.7599 | ex 2932 20 90 | 75 | 3-Acetyl-6-methyl-2H-pyran-2, 4(3H)-dione (CAS RN 520-45-6) | 0 % | — | 31.12.2029 |
| 0.3990 | ex 2932 20 90 | 80 | Gibberellic acid (CAS RN 77-06-5) with a purity by weight of 88 % or more, for use in the manufacture of plant protection products (¹) | 0 % | — | 31.12.2029 |
| 0.4403 | ex 2932 20 90 | 84 | Decahydro-3a,6,6,9a-tetramethylnaphth [2,1-b] furan-2 (1H)-one (CAS RN 564-20-5) | 0 % | — | 31.12.2029 |
| 0.8528 | ex 2932 99 00 | 03 | 3,4-Dihydro-2-methoxy-2H-pyran (CAS RN 4454-05-1) with a purity by weight of 99 % or more | 0 % | — | 31.12.2028 |
| 0.7202 | ex 2932 99 00 | 13 | (4-Chloro-3-(4-ethoxybenzyl)phenyl)((3aS,5R,6S,6aS)-6-hydroxy 2,2-dimethyltetrahydrofuro [2,3-d][1 ,3]dioxol-5-yl)methanone (CAS RN 1103738-30-2) | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.5269 | ex 2932 99 00 | 15 | 1,3,4,6,7,8-Hexahydro-4,6,6,7,8,8-hexamethylindeno[5,6-c]pyran (CAS RN 1222-05-5) | 0 % | — | 31.12.2026 |
| 0.7178 | ex 2932 99 00 | 18 | 4-(4-Bromo-3-((tetrahydro-2H-pyran-2-yloxy)methyl)phenoxy)benzonitrile (CAS RN 943311-78-2) | 0 % | — | 31.12.2026 |
| 0.7431 | ex 2932 99 00 | 23 | 2-Ethyl-3-hydroxy-4-pyrone (CAS RN 4940-11-8) | 0 % | — | 31.12.2027 |
| 0.5759 | ex 2932 99 00 | 25 | 1-(2,2-Difluorobenzo[d][1,3]dioxol-5-yl)cyclopropanecarboxylic acid (CAS RN 862574-88-7) | 0 % | — | 31.12.2027 |
| 0.7639 | ex 2932 99 00 | 27 | (2-Butyl-3-benzofuranyl)(4-hydroxy-3,5-diiodophenyl)methanone (CAS RN 1951-26-4) with a purity by weight of 99 % or more | 0 % | — | 31.12.2029 |
| 0.8257 | ex 2932 99 00 | 28 | 1,4,7,10,13-Pentaoxacyclopentadecane (CAS RN 33100-27-5) with a purity by weight of 90 % or more, the remainder mainly consisting of linear precursors | 0 % | — | 31.12.2026 |
| 0.7535 | ex 2932 99 00 | 33 | 3-Hydroxy-2-methyl-4-pyrone (CAS RN 118-71-8) | 0 % | — | 31.12.2029 |
| 0.8035 | *ex 2932 99 00 | 38 | 1-Benzofuran-6-carboxylic acid (CAS RN 77095-51-3) with a purity by weight of 98 % or more | 0 % | — | 31.12.2030 |
| 0.6243 | ex 2932 99 00 | 43 | Ethofumesate (ISO) (CAS RN 26225-79-6) with a purity by weight of 97 % or more | 0 % | — | 31.12.2029 |
| 0.5915 | ex 2932 99 00 | 45 | 2-Butylbenzofuran (CAS RN 4265-27-4) | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8384 | ex 2932 99 00 | 48 | (20R,25R)-spirost-5-en-3 β -ol (CAS RN 512-04-9) with a purity by weight of 95 % or more | 0 % | — | 31.12.2027 |
| 0.4907 | ex 2932 99 00 | 50 | 7-Methyl-3,4-dihydro-2H-1,5-benzodioxepin-3-one (CAS RN 28940-11-6) | 0 % | — | 31.12.2029 |
| 0.4063 | ex 2932 99 00 | 51 | 3-(3,4-Methylenedioxyphenyl)-2-methylpropanal (CAS RN 1205-17-0) with a purity by weight of 98 % or more | 0 % | — | 31.12.2027 |
| 0.6771 | *ex 2932 99 00 | 65 | 4,4-Dimethyl-3,5,8-trioxabicyclo[5.1.0]octane (CAS RN 57280-22-5) | 0 % | — | 31.12.2030 |
| 0.7954 | *ex 2932 99 00 | 83 | 6,11-Dihydrodibenz[b,e]oxepin-11-one (CAS RN 4504-87-4) with a purity by weight of 98 % or more | 0 % | — | 31.12.2030 |
| 0.3697 | ex 2932 99 00 | 85 | 1,3:2,4-bis-O-(3,4-Dimethylbenzylidene)-D-glucitol (CAS RN 135861-56-2) | 0 % | — | 31.12.2029 |
| 0.6262 | ex 2933 19 90 | 15 | Pyrasulfotole (ISO) (CAS RN 365400-11-9) with a purity by weight of 96 % or more | 0 % | — | 31.12.2029 |
| 0.7836 | ex 2933 19 90 | 27 | 3-(3,3,3-Trifluoro-2,2-dimethylpropoxy)-1H-pyrazole-4-carboxylic acid (CAS RN 2229861-20-3) with a purity by weight of 95 % or more | 0 % | — | 31.12.2029 |
| 0.7811 | ex 2933 19 90 | 33 | Fipronil (ISO) (CAS RN 120068-37-3) with a purity by weight of 95 % or more for the use in the manufacture of veterinary medicine (¹) | 0 % | — | 31.12.2029 |
| 0.8353 | ex 2933 19 90 | 38 | 4,5-Dimethyl-1H-pyrazole-3-carboxylic acid (CAS RN 89831-40-3) with a purity by weight of 98 % or more | 0 % | — | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.3877 | ex 2933 19 90 | 40 | Edaravone (INN) (CAS RN 89-25-8) | 0 % | — | 31.12.2029 |
| 0.7119 | ex 2933 19 90 | 45 | 5-Amino-1-[2,6-dichloro-4-(trifluoromethyl)phenyl]-1H-pyrazole-3-carbonitrile (CAS RN 120068-79-3) | 0 % | — | 31.12.2026 |
| 0.8046 | *ex 2933 19 90 | 48 | 1-(3-Iodo-1-isopropyl-1H-pyrazol-4-yl)ethanone (CAS RN 1269440-49-4) with a purity by weight of 98 % or more | 0 % | — | 31.12.2030 |
| 0.3992 | ex 2933 19 90 | 50 | Fenpyroximate (ISO) (CAS RN 134098-61-6) | 0 % | — | 31.12.2029 |
| 0.8240 | ex 2933 19 90 | 53 | 3-[2-(Dispiro[2.0.2 ⁴ .1 ³]heptan-7-yl)ethoxy]-1H-pyrazole-4-carboxylic acid (CAS RN 2608048-67-3) with a purity by weight of 98 % or more | 0 % | — | 31.12.2026 |
| 0.8603 | ex 2933 19 90 | 58 | 1H-Pyrazole (CAS RN 288-13-1) with a purity by weight of 98 % or more | 0 % | — | 31.12.2028 |
| 0.4494 | ex 2933 19 90 | 60 | Pyraflufen-ethyl (ISO) (CAS RN 129630-19-9) | 0 % | — | 31.12.2029 |
| 0.6261 | *ex 2933 19 90 | 63 | 3-Difluoromethyl-1-methyl-1H-pyrazole-4-carboxylic acid (CAS RN 176969-34-9) with a purity by weight of 97 % or more | 0 % | — | 31.12.2029 |
| 0.8613 | ex 2933 19 90 | 68 | 1-Methyl-1H-pyrazol-4-amine hydrochloride (CAS RN 127107-23-7) with a purity by weight of 95 % or more | 0 % | — | 31.12.2028 |
| 0.4404 | ex 2933 19 90 | 70 | 4,5-Diamino-1-(2-hydroxyethyl)-pyrazolsulphate (CAS RN 155601-30-2) | 0 % | — | 31.12.2029 |
| 0.8312 | ex 2933 21 00 | 45 | Sodium (5S,8S)-8-methoxy-2,4-dioxo-1,3-diazaspiro[4.5]decan-3-ide (CAS RN 1400584-86-2) with a purity by weight of 90 % or more | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.4084 | ex 2933 21 00 | 50 | 1-Bromo-3-chloro-5,5-dimethylhydantoin (CAS RN 16079-88-2) / (CAS RN 32718-18-6) | 0 % | — | 31.12.2026 |
| 0.6835 | *ex 2933 21 00 | 55 | 1-Aminohydantoin hydrochloride (CAS RN 2827-56-7) | 0 % | — | 31.12.2030 |
| 0.4088 | ex 2933 21 00 | 60 | DL-p-Hydroxyphenylhydantoin (CAS RN 2420-17-9) | 0 % | — | 31.12.2026 |
| 0.5115 | *ex 2933 21 00 | 80 | 5,5-Dimethylhydantoin (CAS RN 77-71-4) | 0 % | — | 31.12.2030 |
| 0.5972 | ex 2933 29 90 | 15 | Ethyl 4-(1-hydroxy-1-methylethyl)-2-propylimidazole-5-carboxylate (CAS RN 144689-93-0) | 0 % | — | 31.12.2029 |
| 0.8150 | ex 2933 29 90 | 20 | tert-Butyl (2S)-2-(5-bromo-1H-imidazol-2-yl)pyrrolidine-1-carboxylate (CAS RN 1007882-59-8) with a purity by weight of 98 % or more | 0 % | — | 31.12.2026 |
| 0.8452 | ex 2933 29 90 | 38 | Cyazofamid (ISO) (CAS RN 120116-88-3) with a purity by weight of 94 % or more | 0 % | — | 31.12.2027 |
| 0.8639 | ex 2933 29 90 | 43 | 2-Octyl-4,5-dihydro-1H-imidazole (CAS RN 10443-60-4) with a purity by weight of 95 % or more | 0 % | — | 31.12.2028 |
| 0.5215 | ex 2933 29 90 | 60 | 1-Cyano-2-methyl-1-[2-(5-methylimidazol-4-ylmethylthio)ethyl]isothiourea (CAS RN 52378-40-2) | 0 % | — | 31.12.2026 |
| 0.7120 | ex 2933 29 90 | 75 | 2,2'-Azobis[2-(2-imidazolin-2-yl)propane] dihydrochloride (CAS RN 27776-21-2) | 0 % | — | 31.12.2026 |
| 0.5821 | ex 2933 29 90 | 80 | Imazalil (ISO) (CAS RN 35554-44-0) | 0 % | — | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.6415 | 2933 39 50 | | Fluroxypyrr (ISO) methyl ester (CAS RN 69184-17-4) | 0 % | — | 31.12.2029 |
| 0.8574 | ex 2933 39 99 | 04 | Methyl 4-aminopicolinate (CAS RN 71469-93-7) with a purity by weight of 98 % or more | 0 % | — | 31.12.2028 |
| 0.8524 | ex 2933 39 99 | 05 | 2,6-Bis-[1-(2- <i>tert</i> -butylphenylimino)-ethyl]pyridine (CAS RN 204203-17-8) with a purity by weight of 95 % or more | 0 % | — | 31.12.2028 |
| 0.8576 | ex 2933 39 99 | 06 | <i>Tert</i> -butyl (3 <i>S</i>)-3-hydroxypiperidine-1-carboxylate (CAS RN 143900-44-1) with a purity by weight of 97 % or more | 0 % | — | 31.12.2028 |
| 0.8535 | ex 2933 39 99 | 07 | 5-Bromo-2-methoxypyridine (CAS RN 13472-85-0) with a purity by weight of 99 % or more | 0 % | — | 31.12.2028 |
| 0.8485 | ex 2933 39 99 | 08 | Fluazinam (ISO) (CAS RN 79622-59-6) with a purity by weight of 97 % or more | 0 % | — | 31.12.2027 |
| 0.7186 | ex 2933 39 99 | 10 | 2-Aminopyridin-4-ol hydrochloride (CAS RN 1187932-09-7) | 0 % | — | 31.12.2026 |
| 0.6462 | ex 2933 39 99 | 11 | 2-(Chloromethyl)-4-(3-methoxypropoxy)-3-methylpyridine hydrochloride (CAS RN 153259-31-5) | 0 % | — | 31.12.2029 |
| 0.5608 | ex 2933 39 99 | 12 | 2,3-Dichloropyridine (CAS RN 2402-77-9) | 0 % | — | 31.12.2027 |
| 0.8238 | ex 2933 39 99 | 15 | (<i>S</i>)-6-Bromo-2-(4-(3-(1,3-dioxoisooindolin-2-yl)propyl)-2,2-dimethylpyrrolidin-1-yl) nicotinamide (CAS RN 2606972-45-4) with a purity by weight of 98 % or more | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8831 | ex 2933 39 99 | 16 | Tert-butyl (3R)-3-aminopiperidine-1-carboxylate (CAS RN 188111-79-7) with a purity by weight of 96 % or more | 0 % | — | 31.12.2029 |
| 0.8833 | ex 2933 39 99 | 17 | 2,4-Dichloro-3-nitropyridine (CAS RN 5975-12-2) with a purity by weight of 99 % or more | 0 % | — | 31.12.2029 |
| 0.8239 | ex 2933 39 99 | 18 | Perfluorophenyl 6-fluoropyridine-2-sulfonate (CAS RN 2608048-81-1) with a purity by weight of 98 % or more | 0 % | — | 31.12.2026 |
| 0.8329 | ex 2933 39 99 | 22 | N-(5-bromo-3-methylpyridin-2-yl)-N-methylbenzamide (CAS RN 446299-80-5) with a purity by weight of 98 % or more | 0 % | — | 31.12.2027 |
| 0.4594 | ex 2933 39 99 | 24 | 2-Chloromethyl-4-methoxy-3,5-dimethylpyridine hydrochloride (CAS RN 86604-75-3) | 0 % | — | 31.12.2029 |
| 0.7091 | ex 2933 39 99 | 27 | Pyridine-2,6-dicarboxylic acid (CAS RN 499-83-2) | 0 % | — | 31.12.2026 |
| 0.6368 | ex 2933 39 99 | 28 | Ethyl-3-[(3-amino-4-methylamino-benzoyl)-pyridin-2-yl-amino]-propionate (CAS RN 212322-56-0) | 0 % | — | 31.12.2029 |
| 0.6458 | ex 2933 39 99 | 31 | 2-(Chloromethyl)-3-methyl-4-(2,2,2-trifluoroethoxy)pyridine hydrochloride (CAS RN 127337-60-4) | 0 % | — | 31.12.2029 |
| 0.5241 | ex 2933 39 99 | 32 | 2-(Chloromethyl)-3,4-dimethoxypyridine hydrochloride (CAS RN 72830-09-2) | 0 % | — | 31.12.2026 |
| 0.7181 | ex 2933 39 99 | 33 | 5-(3-Chlorophenyl)-3-methoxypyridine-2-carbonitrile (CAS RN 1415226-39-9) | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8420 | ex 2933 39 99 | 34 | Pyridin-3-ol (CAS RN 109-00-2) with a purity by weight of 98 % or more | 0 % | — | 31.12.2027 |
| 0.3878 | ex 2933 39 99 | 35 | Aminopyralid (ISO) (CAS RN 150114-71-9) | 0 % | — | 31.12.2029 |
| 0.7296 | ex 2933 39 99 | 36 | 1-[2-[5-Methyl-3-(trifluoromethyl)-1H-pyrazol-1-yl]acetyl]piperidine-4-carbothioamide (CAS RN 1003319-95-6) | 0 % | — | 31.12.2027 |
| 0.5230 | ex 2933 39 99 | 37 | Aqueous solution of pyridine-2-thiol-1-oxide, sodium salt (CAS RN 3811-73-2) | 0 % | — | 31.12.2026 |
| 0.7348 | ex 2933 39 99 | 38 | (2-Chloropyridin-3-yl) methanol (CAS RN 42330-59-6) | 0 % | — | 31.12.2027 |
| 0.8356 | ex 2933 39 99 | 40 | 2-Hydroxypyridine-N-oxide (CAS RN 13161-30-3) with a purity by weight of 98 % or more | 0 % | — | 31.12.2027 |
| 0.8266 | ex 2933 39 99 | 42 | Glasdegib maleate (INN) (CAS RN 2030410-25-2) with a purity by weight of 98 % or more | 0 % | — | 31.12.2026 |
| 0.8711 | ex 2933 39 99 | 44 | Fluroxypyrr-methyl (CAS RN 81406-37-3) with a purity by weight of 95 % or more | 0 % | — | 31.12.2029 |
| 0.8699 | ex 2933 39 99 | 45 | 2,4-Dichloropyridine-3-carboxaldehyde (CAS RN 134031-24-6) with a purity by weight of 95 % or more | 0 % | — | 31.12.2029 |
| 0.4706 | ex 2933 39 99 | 47 | (-)-trans-4-(4'-Fluorophenyl)-3-hydroxymethyl-N-methylpiperidine (CAS RN 105812-81-5) | 0 % | — | 31.12.2026 |
| 0.4749 | ex 2933 39 99 | 48 | Flonicamid (ISO) (CAS RN 158062-67-0) | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8335 | ex 2933 39 99 | 49 | 2-Phenyl-2-(2-pyridyl)acetamide (CAS RN 7251-52-7) with a purity by weight of 98 % or more | 0 % | — | 31.12.2027 |
| 0.6812 | ex 2933 39 99 | 50 | N,4-Dimethyl-1-(phenylmethyl)- 3-piperidinamine hydrochloride (1:2) (CAS RN 1228879-37-5) with a purity by weight of 98 % or more | 0 % | — | 31.12.2029 |
| 0.8709 | ex 2933 39 99 | 51 | 2-Amino-3-bromo-5-nitropyridine (CAS RN 15862-31-4) with a purity by weight of 98 % or more | 0 % | — | 31.12.2029 |
| 0.8637 | ex 2933 39 99 | 53 | 5-Methyl-2-pyridylamine (CAS RN 1603-41-4) with a purity by weight of 99 % or more | 0 % | — | 31.12.2028 |
| 0.8729 | ex 2933 39 99 | 54 | 2,5-Dichloro-4,6-dimethylpyridine-3-carbonitrile (CAS RN 91591-63-8) with a purity by weight of 99 % or more | 0 % | — | 31.12.2029 |
| 0.4646 | ex 2933 39 99 | 55 | Pyriproxyfen (ISO) (CAS RN 95737-68-1) of a purity by weight of 97 % or more | 0 % | — | 31.12.2029 |
| 0.8618 | ex 2933 39 99 | 56 | 2-[[[3-Methyl-4-(2,2,2-trifluoroethoxy)pyridin-2-yl]methyl]sulfanyl]1H-benzimidazole (CAS RN 103577-40-8) with a purity by weight of 99 % or more | 0 % | — | 31.12.2028 |
| 0.5760 | ex 2933 39 99 | 57 | Tert-butyl 3-(6-amino-3-methylpyridin-2-yl)benzoate (CAS RN 1083057-14-0) | 0 % | — | 31.12.2027 |
| 0.8624 | ex 2933 39 99 | 58 | Tert-butyl N-[5-(trifluoromethyl)pyridin-3-yl]carbamate (CAS RN 1187055-61-3) with a purity by weight of 98 % or more | 0 % | — | 31.12.2028 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.2750 | ex 2933 39 99 | 60 | 2-Fluoro-6-(trifluoromethyl)pyridine (CAS RN 94239-04-0) with a purity by weight of 90 % or more | 0 % | — | 31.12.2029 |
| 0.7577 | ex 2933 39 99 | 62 | Ethyl 2,6-Dichloronicotinate (CAS RN 58584-86-4) | 0 % | — | 31.12.2029 |
| 0.8527 | ex 2933 39 99 | 63 | 1-Methyl-4-piperidone (CAS RN 1445-73-4) with a purity by weight of 97 % or more | 0 % | — | 31.12.2028 |
| 0.3602 | ex 2933 39 99 | 65 | Acetamiprid (ISO) (CAS RN 135410-20-7) | 0 % | — | 31.12.2029 |
| 0.8656 | ex 2933 39 99 | 66 | (2S,4S)-4-Ethoxy-2-[4-(methoxycarbonyl)phenyl]piperidin-1-ium (2Z)-3-carboxyprop-2-enoate (CAS RN 2408761-21-5) with a purity by weight of 98 % or more | 0 % | — | 31.12.2028 |
| 0.7616 | ex 2933 39 99 | 68 | 1-(3-Chloropyridin-2-yl)-3-[[5-(trifluoromethyl)-2H-tetrazol-2-yl]methyl]-1H-pyrazole-5-carboxylic acid (CAS RN 1352319-02-8) with a purity by weight of 85 % or more | 0 % | — | 31.12.2029 |
| 0.5494 | ex 2933 39 99 | 70 | 2,3-Dichloro-5-trifluoromethylpyridine (CAS RN 69045-84-7) | 0 % | — | 31.12.2026 |
| 0.8707 | ex 2933 39 99 | 72 | N-[(1S,5R)-8-Benzyl-8-azabicyclo[3.2.1]octane-3-yl]-2-methylpropanamide (CAS RN 376348-67-3) with a purity by weight of 98 % or more | 0 % | — | 31.12.2029 |
| 0.7737 | ex 2933 39 99 | 73 | 6-Chloro-4-(4-fluoro-2-methylphenyl)pyridin-3-amine hydrochloride | 0 % | — | 31.12.2029 |
| 0.8072 | *ex 2933 39 99 | 75 | Clodinafop-propargyl (ISO) (CAS RN 105512-06-9) with a purity by weight of 90 % or more | 0 % | — | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.7813 | ex 2933 39 99 | 76 | Apalutamide (INN) (CAS RN 956104-40-8) | 0 % | — | 31.12.2029 |
| 0.7818 | ex 2933 39 99 | 78 | Niraparib tosylate monohydrate (INNM) (CAS RN 1613220-15-7) | 0 % | — | 31.12.2029 |
| 0.8074 | *ex 2933 39 99 | 80 | Tert-Butyl (3R)-3-(4-amino-2-oxo-2,3-dihydro-1H-imidazo[4, 5-c]pyridin-1-yl) piperidine-1-carboxylate (CAS RN 1971921-33-1) with a purity by weight of 95 % or more | 0 % | — | 31.12.2030 |
| 0.7906 | ex 2933 39 99 | 81 | 4-Hydroxy-3-pyridinesulphonic acid (CAS RN 51498-37-4) with a purity by weight of 98 % or more | 0 % | — | 31.12.2029 |
| 0.7866 | ex 2933 39 99 | 82 | Picloram (ISO) (CAS RN 1918-02-1) containing by weight not more than 15 % of water and with a dry weight purity of 92 % or more | 0 % | — | 31.12.2029 |
| 0.7925 | *ex 2933 39 99 | 84 | Diethyl(3-pyridyl)borane (CAS RN 89878-14-8) with a purity by weight of 98 % or more | 0 % | — | 31.12.2030 |
| 0.5129 | *ex 2933 39 99 | 85 | 2-Chloro-5-chloromethylpyridine (CAS RN 70258-18-3) | 0 % | — | 31.12.2030 |
| 0.8912 | *ex 2933 39 99 | 88 | (1R,2S,4R)-2-Benzhydrylquinuclidin-3-one (2R,3R)-2,3-dihydroxysuccinate (CAS RN 683206-54-4) with a purity by weight of 98 % or more | 0 % | — | 31.12.2030 |
| 0.8096 | *ex 2933 39 99 | 89 | 1-Benzyl-4-phenylpiperidine-4-carbonitrile monohydrochloride (CAS RN 71258-18-9) with a purity by weight of 98 % or more | 0 % | — | 31.12.2030 |
| 0.6545 | *ex 2933 39 99 | 93 | Boscalid (ISO) (CAS RN 188425-85-6) with a purity by weight of 98 % or more | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.4525 | ex 2933 49 10 | 20 | 3-Hydroxy-2-methylquinoline-4-carboxylic acid (CAS RN 117-57-7) | 0 % | — | 31.12.2029 |
| 0.6339 | ex 2933 49 10 | 40 | 4,7-Dichloroquinoline (CAS RN 86-98-6) | 0 % | — | 31.12.2029 |
| 0.3603 | *ex 2933 49 10 | 70 | Quinmerac (ISO) (CAS RN 90717-03-6) with a purity by weight of 98 % or more | 0 % | — | 31.12.2029 |
| 0.7098 | ex 2933 49 90 | 25 | Cloquintocet-mexyl (ISO) (CAS RN 99607-70-2) | 0 % | — | 31.12.2026 |
| 0.4927 | *ex 2933 49 90 | 30 | Quinoline (CAS RN 91-22-5) | 0 % | — | 31.12.2030 |
| 0.8037 | *ex 2933 49 90 | 55 | 2-(<i>tert</i> -Butoxycarbonyl)-5,7-dichloro-1,2,3,4-tetrahydroisoquinoline-6-carboxylic acid (CAS RN 851784-82-2) with a purity by weight of 98 % or more | 0 % | — | 31.12.2030 |
| 0.3880 | ex 2933 49 90 | 70 | Quinolin-8-ol (CAS RN 148-24-3) | 0 % | — | 31.12.2029 |
| 0.8358 | ex 2933 49 90 | 75 | 2-Methyl-4-(1-methyl-1H-1,2,4-triazol-5-yl)quinolin-8-ol (CAS RN 1174132-59-2) with a purity by weight of 98 % or more | 0 % | — | 31.12.2027 |
| 0.8556 | ex 2933 49 90 | 85 | (2 <i>R</i> ,4 <i>S</i>)-2-Ethyl-6-(trifluoromethyl)-1,2,3,4-tetrahydroquinolin-4-amine methanesulfonate (CAS RN 952582-02-4) with a purity by weight of 95 % or more | 0 % | — | 31.12.2028 |
| 0.4043 | ex 2933 52 00 | 10 | Malonylurea (barbituric acid) (CAS RN 67-52-7) | 0 % | — | 31.12.2026 |
| 0.6468 | ex 2933 59 95 | 10 | 6-Amino-1,3-dimethyluracil (CAS RN 6642-31-5) | 0 % | — | 31.12.2029 |
| 0.6151 | ex 2933 59 95 | 13 | 2-Diethylamino-6-hydroxy-4-methylpyrimidine (CAS RN 42487-72-9) | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8597 | ex 2933 59 95 | 14 | 2-Chloro-7-cyclopentyl-N,N-dimethyl-7H-pyrrolo[2,3-d]pyrimidine-6-carboxamide (CAS RN 1211443-61-6) with a purity by weight of 97 % or more | 0 % | — | 31.12.2028 |
| 0.8580 | ex 2933 59 95 | 16 | Tert-butyl 4-(6-aminopyridin-3-yl)piperazine-1-carboxylate (CAS RN 571188-59-5) with a purity by weight of 98 % or more | 0 % | — | 31.12.2028 |
| 0.8555 | ex 2933 59 95 | 19 | Tert-butyl 4-[(2-chloropyrimidin-5-yl)oxy]butanoate (CAS RN 945771-55-1) with a purity by weight of 95 % or more | 0 % | — | 31.12.2028 |
| 0.2745 | ex 2933 59 95 | 20 | 2,4-Diamino-6-chloropyrimidine (CAS RN 156-83-2) | 0 % | — | 31.12.2029 |
| 0.5912 | ex 2933 59 95 | 27 | 2-[(2-Amino-6-oxo-1,6-dihydro-9H-purin-9-yl)methoxy]-3-hydroxypropylacetate (CAS RN 88110-89-8) | 0 % | — | 31.12.2029 |
| 0.8157 | ex 2933 59 95 | 29 | 2-Amino-4-(4-methylpiperazin-1-yl) benzoic acid tert-butyl ester (CAS RN 1034975-35-3) with a purity by weight of 95 % or more | 0 % | — | 31.12.2026 |
| 0.8376 | ex 2933 59 95 | 31 | Sotorasib (INN) (CAS RN 2296729-00-3) with a purity by weight of 99 % or more | 0 % | — | 31.12.2027 |
| 0.8456 | ex 2933 59 95 | 32 | 5-Chloro-3-nitropyrazolo[1,5-a]pyrimidine (CAS RN 1363380-51-1) with a purity by weight of 98 % or more | 0 % | — | 31.12.2027 |
| 0.6240 | ex 2933 59 95 | 33 | 4,6-Dichloro-5-fluoropyrimidine (CAS RN 213265-83-9) | 0 % | — | 31.12.2029 |
| 0.7370 | ex 2933 59 95 | 34 | 6-chloro-1,3-dimethyluracil (CAS RN 6972-27-6) with a purity by weight of 97 % or more | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.7345 | ex 2933 59 95 | 36 | 1-(Cyclopropylcarbonyl)piperazine hydrochloride (CAS RN 1021298-67-8) with a purity by weight of 98 % or more | 0 % | — | 31.12.2029 |
| 0.8248 | ex 2933 59 95 | 38 | 5-(5-Chlorosulfonyl-2-ethoxyphenyl)-1-methyl-3-propyl-1,6-dihydro-7H-pyrazolo[4,3-d]pyrimidin-7-one (CAS RN 139756-22-2) with a purity by weight of 98 % or more | 0 % | — | 31.12.2026 |
| 0.8243 | ex 2933 59 95 | 41 | 2-(4-Phenoxyphenyl)-7-(piperidin-4-yl)-4,5,6,7-tetrahydropyrazolo[1,5-a]pyrimidine-3-carbonitrile (CAS RN 2190506-57-9) with a purity by weight of 98 % or more | 0 % | — | 31.12.2026 |
| 0.8484 | ex 2933 59 95 | 44 | 1,4,5,6-Tetrahydro-1,2-dimethylpyrimidine (CAS RN 4271-96-9) with a purity by weight of 98 % or more | 0 % | — | 31.12.2027 |
| 0.4704 | ex 2933 59 95 | 45 | 1-[3-(Hydroxymethyl)pyridin-2-yl]-4-methyl-2-phenylpiperazine (CAS RN 61337-89-1) | 0 % | — | 31.12.2029 |
| 0.8488 | ex 2933 59 95 | 46 | Trilaciclib (CAS RN 1374743-00-6) with a purity by weight of 99 % or more | 0 % | — | 31.12.2027 |
| 0.6677 | *ex 2933 59 95 | 47 | 6-Methyl-2-oxoperhydropyrimidin-4-ylurea (CAS RN 1129-42-6) with a purity of 94 % or more | 0 % | — | 31.12.2030 |
| 0.4699 | ex 2933 59 95 | 50 | 2-(2-Piperazin-1-ylethoxy)ethanol (CAS RN 13349-82-1) | 0 % | — | 31.12.2029 |
| 0.8612 | ex 2933 59 95 | 51 | (1R,5S)-8-Benzyl-3,8-diazabicyclo[3.2.1]octane; 4-(4-hydroxyphenyl)phenol (2:1) (CAS RN 2642049-87-2) with a purity by weight of 95 % or more | 0 % | — | 31.12.2028 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.6987 | ex 2933 59 95 | 52 | 6-Benzyladenine (CAS RN 1214-39-7) with a purity by weight of 97 % or more | 0 % | — | 31.12.2026 |
| 0.8602 | ex 2933 59 95 | 54 | 2-Chloro-4-methylpyrimidine (CAS RN 13036-57-2) with a purity by weight of 99 % or more | 0 % | — | 31.12.2028 |
| 0.8834 | ex 2933 59 95 | 56 | Ruxolitinib phosphate (INNM) (CAS RN 1092939-17-7) with a purity by weight of 99 % or more | 0 % | — | 31.12.2029 |
| 0.2578 | ex 2933 59 95 | 58 | Sitagliptin phosphate monohydrate (INNM) (CAS RN 654671-77-9) with a purity by weight of 95 % or more, and containing by weight not more than 1 % of a stabiliser | 0 % | — | 31.12.2027 |
| 0.2744 | ex 2933 59 95 | 60 | 2,6-Dichloro-4,8-dipiperidinopyrimido[5,4-d]pyrimidine (CAS RN 7139-02-8) | 0 % | — | 31.12.2029 |
| 0.8717 | ex 2933 59 95 | 61 | 4-Methyl-7H-pyrrolo[2,3-d]pyrimidine (CAS RN 945950-37-8) with a purity by weight of 98 % or more | 0 % | — | 31.12.2029 |
| 0.7578 | ex 2933 59 95 | 63 | 1-(3-Chlorophenyl) piperazine (CAS RN 6640-24-0) | 0 % | — | 31.12.2029 |
| 0.8730 | ex 2933 59 95 | 64 | Thiopental (INNM) (CAS RN 76-75-5) with a purity by weight of 98 % or more | 0 % | — | 31.12.2029 |
| 0.4772 | ex 2933 59 95 | 65 | 1-Chloromethyl-4-fluoro-1,4-diazaabicyclo[2.2.2]octane bis(tetrafluoroborate) (CAS RN 140681-55-6) | 0 % | — | 31.12.2029 |
| 0.8700 | ex 2933 59 95 | 66 | Piperazin-2-one (CAS RN 5625-67-2) with a purity by weight of 96 % or more | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.7825 | ex 2933 59 95 | 68 | Guanine (CAS RN 73-40-5) with a purity by weight of 99 % or more | 0 % | — | 31.12.2029 |
| 0.2735 | ex 2933 59 95 | 70 | N-(4-Ethyl-2,3-dioxopiperazin-1-ylcarbonyl)-D-2-phenylglycine (CAS RN 63422-71-9) | 0 % | — | 31.12.2029 |
| 0.5542 | ex 2933 59 95 | 77 | 3-(Trifluoromethyl)-5,6,7,8-tetrahydro[1,2,4]triazolo[4,3-a]pyrazine hydrochloride (1:1) (CAS RN 762240-92-6) | 0 % | — | 31.12.2027 |
| 0.7071 | ex 2933 59 95 | 87 | 5-Bromo-2,4-dichloropyrimidine (CAS RN 36082-50-5) | 0 % | — | 31.12.2026 |
| 0.6621 | *ex 2933 69 80 | 15 | 2-Chloro-4,6-dimethoxy-1,3,5-triazine (CAS RN 3140-73-6) | 0 % | — | 31.12.2030 |
| 0.6951 | ex 2933 69 80 | 17 | Benzoguanamine (CAS RN 91-76-9) | 0 % | — | 31.12.2026 |
| 0.7721 | ex 2933 69 80 | 23 | 1,3,5-Tris(2,3-dibromopropyl)-1,3,5-triazinane-2,4,6-trione (CAS RN 52434-90-9) | 0 % | — | 31.12.2029 |
| 0.7600 | ex 2933 69 80 | 27 | Troclosene sodium dihydrate (INNM) (CAS RN 51580-86-0) | 0 % | — | 31.12.2029 |
| 0.7952 | *ex 2933 69 80 | 33 | 2,4,6-Trichloro-1,3,5-triazine (CAS RN 108-77-0) with a purity by weight of 99 % or more | 0 % | — | 31.12.2030 |
| 0.5272 | ex 2933 69 80 | 40 | Troclosene sodium (INNM) (CAS RN 2893-78-9) | 0 % | — | 31.12.2026 |
| 0.8718 | ex 2933 69 80 | 43 | 4-(4,6-Bis((biphenyl-4-yl)-1,3,5-triazine-2-yl)-1,3-benzodiole (CAS RN 182918-16-7) with a purity by weight of 96 % or more | 0 % | — | 31.12.2029 |
| 0.7464 | ex 2933 69 80 | 45 | 2-(4,6-Bis-(2,4-dimethylphenyl)-1,3,5-triazin-2-yl)-5-(octyloxy)-phenol (CAS RN 2725-22-6) | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.5131 | *ex 2933 69 80 | 55 | Terbutryn (ISO) (CAS RN 886-50-0) for use as a raw material for the production of technical preservatives, in other sectors than for pesticides (¹) | 0 % | — | 31.12.2030 |
| 0.4957 | *ex 2933 69 80 | 60 | Cyanuric acid (CAS RN 108-80-5) | 0 % | — | 31.12.2030 |
| 0.6127 | ex 2933 69 80 | 65 | 1,3,5-Triazine-2,4,6(1H,3H,5H)-trithione, trisodium salt (CAS RN 17766-26-6) | 0 % | — | 31.12.2029 |
| 0.6477 | ex 2933 69 80 | 75 | Metamitron (ISO) (CAS RN 41394-05-2) | 0 % | — | 31.12.2029 |
| 0.3882 | ex 2933 69 80 | 80 | Tris(2-hydroxyethyl)-1,3,5-triazinetrione (CAS RN 839-90-7) | 0 % | — | 31.12.2029 |
| 0.6960 | ex 2933 79 00 | 15 | Ethyl N-(tert-Butoxycarbonyl)-L-pyroglutamate (CAS RN 144978-12-1) | 0 % | — | 31.12.2026 |
| 0.8354 | ex 2933 79 00 | 23 | (S)-2-Amino-3-[(S)-2-oxopyrrolidin-3-yl]propanamide hydrochloride (CAS RN 2628280-48-6) with a purity by weight of 95 % or more | 0 % | — | 31.12.2027 |
| 0.7346 | ex 2933 79 00 | 25 | Methyl 2-oxo-2,3-dihydro-1H-indole-6-carboxylate (CAS RN 14192-26-8) | 0 % | — | 31.12.2029 |
| 0.4294 | ex 2933 79 00 | 30 | 5-Vinyl-2-pyrrolidone (CAS RN 7529-16-0) | 0 % | — | 31.12.2027 |
| 0.8038 | *ex 2933 79 00 | 45 | 1-Phenyl-3H-indol-2-one (CAS RN 3335-98-6) with a purity by weight of 99 % or more | 0 % | — | 31.12.2030 |
| 0.8203 | ex 2933 79 00 | 55 | (3S,4R)-3-Amino-4-hydroxypyrrolidin-2-one hydrochloride (CAS RN 2446872-13-3) with a purity by weight of 98 % or more | 0 % | — | 31.12.2026 |
| 0.8212 | ex 2933 79 00 | 65 | 1-Dodecyl-2-pyrrolidone (CAS RN 2687-96-9) with a purity by weight of 98 % or more | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8351 | ex 2933 79 00 | 75 | N-(n-octyl)-2-pyrrolidone (CAS RN 2687-94-7) with a purity by weight of 99 % or more | 0 % | — | 31.12.2027 |
| 0.8545 | ex 2933 79 00 | 85 | 3,5-Dibromo-1-methyl-2(1H)-pyridinone (CAS RN 14529-54-5) with a purity by weight of 97 % or more | 0 % | — | 31.12.2028 |
| 0.8547 | ex 2933 99 80 | 01 | 3-Cyanoindole (CAS RN 5457-28-3) with a purity by weight of 98 % or more | 0 % | — | 31.12.2028 |
| 0.8548 | ex 2933 99 80 | 02 | (S)-1-Benzyl-3-pyrrolidinol (CAS RN 101385-90-4) with a purity by weight of 98 % or more | 0 % | — | 31.12.2028 |
| 0.8581 | ex 2933 99 80 | 03 | Tert-butyl 4-formyl-5-methoxy-7-methyl-1H-indole-1-carboxylate (CAS RN 1481631-51-9) with a purity by weight of 97 % or more | 0 % | — | 31.12.2028 |
| 0.8523 | ex 2933 99 80 | 04 | (S)-2,5-Dihydro-pyrrole-1,2-dicarboxylic acid 1-tert-butyl ester 2-methyl ester (CAS RN 74844-93-2) with a purity by weight of 97 % or more | 0 % | — | 31.12.2028 |
| 0.8156 | ex 2933 99 80 | 07 | 4-(2-Oxo-2,3-dihydro-1H-benzimidazol-1-yl)butanoic acid (CAS RN 3273-68-5) with a purity by weight of 98 % or more | 0 % | — | 31.12.2026 |
| 0.8180 | ex 2933 99 80 | 08 | Prothioconazole (ISO) (CAS RN 178928-70-6) with a purity by weight of 98 % or more | 0 % | — | 31.12.2026 |
| 0.8202 | ex 2933 99 80 | 09 | 5,7-Difluoro-2-(4-fluorophenyl)-1H-indole (CAS RN 901188-04-3) with a purity by weight of 98 % or more | 0 % | — | 31.12.2026 |
| 0.8324 | ex 2933 99 80 | 10 | (R)-2-(2,5-difluorophenyl)pyrrolidine hydrochloride (CAS RN 1218935-60-4) with a purity by weight of 98 % or more | 0 % | — | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.5243 | ex 2933 99 80 | 13 | 5-Difluoromethoxy-2-mercaptop-1-H-benzimidazole (CAS RN 97963-62-7) | 0 % | — | 31.12.2026 |
| 0.6872 | *ex 2933 99 80 | 16 | Pyridate (ISO)(CAS RN 55512-33-9) with a purity by weight of 90 % or more | 0 % | — | 31.12.2030 |
| 0.8290 | ex 2933 99 80 | 18 | 2-(2-Ethoxyphenyl)-5-methyl-7-propylimidazo[5,1-f][1,2,4]-triazin-4 (3H)-one (CAS RN 224789-21-3) with a purity by weight of 95 % or more | 0 % | — | 31.12.2026 |
| 0.6829 | *ex 2933 99 80 | 21 | 1-(Bis(dimethylamino)methylene)-1H-[1,2,3]triazolo[4,5-b]pyridinium 3-oxide hexafluorophosphate(V) (CAS RN 148893-10-1) | 0 % | — | 31.12.2030 |
| 0.8249 | ex 2933 99 80 | 22 | Dibenz[b,f]azepine-5-carbonyl chloride (CAS RN 33948-22-0) with a purity by weight of 98 % or more | 0 % | — | 31.12.2026 |
| 0.5625 | ex 2933 99 80 | 24 | 1,3-Dihydro-5,6-diamino-2H-benzimidazol-2-one (CAS RN 55621-49-3) | 0 % | — | 31.12.2027 |
| 0.8089 | *ex 2933 99 80 | 25 | 6-(4-Benzylamino-3-nitrophenyl)-5-methyl-4,5-dihydro-2H-pyridazin-3-one (CAS RN 77469-62-6) with a purity by weight of 95 % or more | 0 % | — | 31.12.2030 |
| 0.8418 | ex 2933 99 80 | 26 | Benzotriazole-1-yl-oxy-tris-pyrrolidino-phosphonium hexafluorophosphate (CAS RN 128625-52-5) with a purity by weight of 97 % or more | 0 % | — | 31.12.2027 |
| 0.6409 | ex 2933 99 80 | 27 | 5,6-Dimethylbenzimidazole (CAS RN 582-60-5) | 0 % | — | 31.12.2029 |
| 0.8357 | ex 2933 99 80 | 28 | 7-(2-Methyl-4-nitrophenoxy)-[1,2,4]triazolo[1,5-a]pyridine (CAS RN 937263-44-0) with a purity by weight of 98 % or more | 0 % | — | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8804 | ex 2933 99 80 | 29 | 1,1-Dimethylethyl (4S)-3-amino-2-(4-fluoro-3,5-dimethylphenyl)-2,4,6,7-tetrahydro-4-methyl-5H-pyrazolo[4,3-c]pyridine-5-carboxylate (CAS RN 2212021-59-3) with a purity by weight of 99 % or more | 0 % | — | 31.12.2029 |
| 0.3593 | ex 2933 99 80 | 30 | Quizalofop-P-ethyl (ISO) (CAS RN 100646-51-3) | 0 % | — | 31.12.2029 |
| 0.8805 | ex 2933 99 80 | 31 | 2-(2H-Benzotriazol-2-yl)-6-(2-phenylpropan-2-yl)-4-(2,4,4-trimethylpentan-2-yl)phenol (CAS RN 73936-91-1) with a purity by weight of 97 % or more | 0 % | — | 31.12.2029 |
| 0.8284 | ex 2933 99 80 | 32 | 1H-1,2,3-Triazole (CAS RN 288-36-8) or 2H-1,2,3-triazole (CAS RN 288-35-7) with a purity by weight of 99 % or more | 0 % | — | 31.12.2026 |
| 0.6249 | ex 2933 99 80 | 33 | Penconazole (ISO) (CAS RN 66246-88-6) | 0 % | — | 31.12.2029 |
| 0.7043 | ex 2933 99 80 | 34 | 2,4-Dihydro-5-methoxy-4-methyl-3H-1,2,4-triazol-3-on (CAS RN 135302-13-5) | 0 % | — | 31.12.2026 |
| 0.8643 | ex 2933 99 80 | 35 | 2-[6-Methyl-2-(4-methylphenyl)imidazo[1,2-a]pyridin-3-yl]acetic acid (CAS RN 189005-44-5) with a purity by weight of 98 % or more | 0 % | — | 31.12.2028 |
| 0.4695 | ex 2933 99 80 | 37 | 8-Chloro-5,10-dihydro-11H-dibenzo [b,e] [1,4]diazepin-11-one (CAS RN 50892-62-1) | 0 % | — | 31.12.2029 |
| 0.7045 | ex 2933 99 80 | 38 | (4aS,7aS)-Octahydro-1H-pyrrolo[3,4-b]pyridine (CAS RN 151213-40-0) | 0 % | — | 31.12.2026 |
| 0.3591 | ex 2933 99 80 | 40 | trans-4-Hydroxy-L-proline (CAS RN 51-35-4) | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.7273 | ex 2933 99 80 | 41 | 5-[4'-(Bromomethyl)biphenyl-2-yl]-1-trityl-1H-tetrazole (CAS RN 124750-51-2) | 0 % | — | 31.12.2027 |
| 0.7185 | ex 2933 99 80 | 42 | (S)-2,2,4-Trimethylpyrrolidine hydrochloride (CAS RN 1897428-40-8) | 0 % | — | 31.12.2026 |
| 0.8455 | ex 2933 99 80 | 43 | 4-([1,2,4]Triazolo[1,5-a]pyridin-7-yloxy)-3-methylaniline (CAS RN 937263-71-3) with a purity by weight of 98 % or more | 0 % | — | 31.12.2027 |
| 0.8914 | *ex 2933 99 80 | 44 | (2R,3R)-2-(2,4-Difluorophenyl)-1-(1H-1,2,4-triazol-1-yl)butane-2,3-diol methanesulfonate (CAS RN 1175536-50-1) with a purity by weight of 98 % or more | 0 % | — | 31.12.2030 |
| 0.7269 | ex 2933 99 80 | 46 | (S)-Indoline-2-carboxylic acid (CAS RN 79815-20-6) | 0 % | — | 31.12.2027 |
| 0.7410 | ex 2933 99 80 | 48 | 5-Amino-6-methyl-2-benzimidazolone (CAS RN 67014-36-2) | 0 % | — | 31.12.2027 |
| 0.8713 | ex 2933 99 80 | 49 | Tert-butyl (2S)-2-carbamoylpyrrolidine-1-carboxylate (CAS RN 35150-07-3) with a purity by weight of 97 % or more | 0 % | — | 31.12.2029 |
| 0.8722 | ex 2933 99 80 | 50 | Tert-butyl (3R)-3-aminopyrrolidine-1-carboxylate (CAS RN 147081-49-0) with a purity by weight of 97 % or more | 0 % | — | 31.12.2029 |
| 0.8702 | ex 2933 99 80 | 51 | (1R,5R)-Ethyl 3-benzyl-3-azabicyclo[3.1.0]hexane-1-carboxylate hydrochloride (CAS RN 2914217-81-3) with a purity by weight of 97 % or more | 0 % | — | 31.12.2029 |
| 0.8703 | ex 2933 99 80 | 52 | (S)-2-Methylpyrrolidine-2-carboxylic acid hydrochloride (CAS RN 1508261-86-6) with a purity by weight of 98 % or more | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.4585 | ex 2933 99 80 | 55 | Pyridaben (ISO) (CAS RN 96489-71-3) | 0 % | — | 31.12.2029 |
| 0.7457 | ex 2933 99 80 | 56 | Methyl 3,5-diamino-6-chloropyrazine-2-carboxylate (CAS RN 1458-01-1) with a purity by weight of 98 % or more | 0 % | — | 31.12.2029 |
| 0.5901 | ex 2933 99 80 | 57 | 2-(5-Methoxyindol-3-yl)ethylamine (CAS RN 608-07-1) | 0 % | — | 31.12.2029 |
| 0.7927 | *ex 2933 99 80 | 60 | 2-[(6,11-Dihydro-5H-dibenz[b,e]azepin-6-yl)-methyl]-1H-isoindole-1,3(2H)-dione (CAS RN 143878-20-0) with a purity by weight of 99 % or more | 0 % | — | 31.12.2030 |
| 0.7624 | ex 2933 99 80 | 61 | (1R,5S)-8-Benzyl-8-azabicyclo(3.2.1)octan-3-one hydrochloride (CAS RN 83393-23-1) | 0 % | — | 31.12.2029 |
| 0.8809 | ex 2933 99 80 | 62 | 6-O- <i>tert</i> -butyl 4a-O-methyl (4a)-1-(4-fluorophenyl)-4,5,7,8-tetrahydropyrazolo[3,4-g]isoquinoline-4a,6-dicarboxylate (CAS RN 864972-21-4) with a purity by weight of 95 % or more | 0 % | — | 31.12.2029 |
| 0.7680 | ex 2933 99 80 | 63 | L-Prolinamide (CAS RN 7531-52-4) | 0 % | — | 31.12.2029 |
| 0.8359 | ex 2933 99 80 | 64 | (1R,2S,5S)-3-[(S)-3,3-dimethyl-2-(2,2,2-trifluoroacetamido)butanoyl]-6,6-dimethyl-3-azabicyclo[3.1.0]hexane-2-carboxylic acid (CAS RN 2755812-45-2) with a purity by weight of 95 % or more | 0 % | — | 31.12.2027 |
| 0.2732 | *ex 2933 99 80 | 65 | 2-(2H-Benzotriazol-2-yl)-4,6-bis(1-methyl-1-phenylethyl)phenol (CAS RN 70321-86-7) with a purity by weight of 99 % or more | 0 % | — | 31.12.2029 |
| 0.5468 | ex 2933 99 80 | 67 | Candesartan ethyl ester (INNM) (CAS RN 139481-58-6) | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.7679 | ex 2933 99 80 | 68 | 5-((1S,2S)-2-((2R,6S,9S,11R,12R,14aS,15S,16S,20R,23S,25aR)-9-Amino-20-((R)-3-amino-1-hydroxy-3-oxopropyl)-2,11,12,15-tetrahydroxy-6-((R)-1-hydroxyethyl)-16-methyl-5,8,14,19,22,25-hexaoxotetracosahydro-1H-dipyrrolo[2,1-c:2',1'-l][1,4,7,10,13,16]hexaazacycloheptacosin-23-yl)-1,2-dihydroxyethyl)-2-hydroxyphenyl hydrogen sulphate (CAS RN 168110-44-9) | 0 % | — | 31.12.2029 |
| 0.7971 | *ex 2933 99 80 | 70 | 5-(Bis-(2-hydroxyethyl)-amino)-1-methyl-1H-benzimidazole-2-butanoic acid ethyl ester (CAS RN 3543-74-6) with a purity by weight of 98 % or more | 0 % | — | 31.12.2030 |
| 0.4384 | ex 2933 99 80 | 71 | 10-Methoxyiminostilbene (CAS RN 4698-11-7) | 0 % | — | 31.12.2029 |
| 0.4503 | ex 2933 99 80 | 72 | 1,4,7-Trimethyl-1,4,7-triazacyclononane (CAS RN 96556-05-7) | 0 % | — | 31.12.2029 |
| 0.8817 | ex 2933 99 80 | 74 | N,N-Dimethyl-N-octadecyl-1-octadecanaminium (SP-4-2)-[29H,31H-phthalocyanine-2-sulfonato-N29,N30,N31,N32]cuprate (CAS RN 70750-63-9) with a purity by weight of 90 % or more | 0 % | — | 31.12.2029 |
| 0.7759 | ex 2933 99 80 | 75 | 1-[Bis(dimethylamino)methylene]-1H-benzotriazolium hexafluorophosphate(1-) 3-oxide (CAS RN 94790-37-1) | 0 % | — | 31.12.2029 |
| 0.8054 | *ex 2933 99 80 | 76 | 2-Methylindoline (CAS RN 6872-06-6) with a purity by weight of 98 % or more | 0 % | — | 31.12.2026 |
| 0.4382 | ex 2933 99 80 | 78 | 3-Amino-3-azabicyclo (3.3.0) octane hydrochloride (CAS RN 58108-05-7) | 0 % | — | 31.12.2029 |
| 0.8014 | *ex 2933 99 80 | 80 | Pyrrole-2-carboxaldehyde (CAS RN 1003-29-8) with a purity by weight of 97 % or more | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.4164 | ex 2933 99 80 | 81 | 1,2,3-Benzotriazole (CAS RN 95-14-7) | 0 % | — | 31.12.2026 |
| 0.4165 | ex 2933 99 80 | 82 | Tolytriazole (CAS RN 29385-43-1) | 0 % | — | 31.12.2029 |
| 0.6933 | *ex 2933 99 80 | 87 | Carfentrazone-ethyl (ISOM) (CAS RN 128639-02-1) with a purity by weight of 90 % or more | 0 % | — | 31.12.2030 |
| 0.3579 | ex 2934 10 00 | 10 | Hexythiazox (ISO) (CAS RN 78587-05-0) | 0 % | — | 31.12.2029 |
| 0.2725 | ex 2934 10 00 | 20 | 2-(4-Methylthiazol-5-yl)ethanol (CAS RN 137-00-8) | 0 % | — | 31.12.2029 |
| 0.5538 | ex 2934 10 00 | 35 | (2-Isopropylthiazol-4-yl)-N-methylmethanamine dihydrochloride (CAS RN 1185167-55-8) | 0 % | — | 31.12.2027 |
| 0.6264 | ex 2934 10 00 | 45 | 2-Cyanimino-1,3-thiazolidine (CAS RN 26364-65-8) | 0 % | — | 31.12.2029 |
| 0.4750 | ex 2934 10 00 | 60 | Fosthiazate (ISO) (CAS RN 98886-44-3) | 0 % | — | 31.12.2029 |
| 0.7312 | ex 2934 20 80 | 15 | Benthiavalicarb-isopropyl (ISO) (CAS RN 177406-68-7) | 0 % | — | 31.12.2027 |
| 0.4346 | ex 2934 20 80 | 25 | 1,2-Benzisothiazol-3(2H)-one (CAS RN 2634-33-5) in the form of a powder with a purity by weight of 95 % or more, or in an aqueous mixture containing by weight 20 % or more of 1,2-benzisothiazol-3(2H)-one | 0 % | — | 31.12.2027 |
| 0.8712 | ex 2934 20 80 | 35 | 3-Methyl-1,2-benzothiazole-1,1-dioxide (CAS RN 34989-82-7) with a purity by weight of 95 % or more | 0 % | — | 31.12.2029 |
| 0.4910 | *ex 2934 20 80 | 70 | N,N-Bis(1,3-benzothiazol-2-ylsulphonyl)-2-methylpropan-2-amine (CAS RN 3741-80-8) | 0 % | — | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.5537 | ex 2934 30 90 | 10 | 2-Methylthiophenothiazine (CAS RN 7643-08-5) | 0 % | — | 31.12.2027 |
| 0.8571 | ex 2934 99 90 | 04 | Silthiomfam (ISO) (CAS RN 175217-20-6) with a purity by weight of 98 % or more | 0 % | — | 31.12.2028 |
| 0.8551 | ex 2934 99 90 | 05 | (S)-2-Methyl-1-(6-nitropyridin-3-yl)-4-(oxetan-3-yl)piperazine (CAS RN 1895867-67-0) with a purity by weight of 97 % or more | 0 % | — | 31.12.2028 |
| 0.8560 | ex 2934 99 90 | 06 | Cis-[2-(2,4-Dichlorodiphenyl)-2-(1H-imidazol-1-ylmethyl)-1,3-dioxolan-4yl]methyl-4-methylbenzenesulfonate (CAS RN 134071-44-6) with a purity by weight of 99 % or more | 0 % | — | 31.12.2028 |
| 0.8487 | ex 2934 99 90 | 07 | Cedazuridine (INN) (CAS RN 1141397-80-9) with a purity by weight of 99 % or more | 0 % | — | 31.12.2027 |
| 0.8472 | ex 2934 99 90 | 08 | (R)-tert-butyl 2-(6-(5-chloro-2-((tetrahydro-2H-pyran-4-yl)amino)pyrimidin-4-yl)-1-oxoisooindolin-2-yl)propanoate (CAS RN 2095665-45-3) with a purity by weight of 98 % or more | 0 % | — | 31.12.2027 |
| 0.8449 | ex 2934 99 90 | 09 | 3-[2-((2R,3S)-3-[(1R)-1-[[tert-butyl(dimethyl)silyl]oxy]ethyl]-4-oxoazetidin-2-yl]propanoyl]-4,4-dimethyl-1,3-oxazolidin-2-one (isomeric mixture of CAS RNs 114341-89-8 and 114418-63-2) with a purity by weight of 99 % or more | 0 % | — | 31.12.2027 |
| 0.6492 | ex 2934 99 90 | 10 | Fluralaner (INN) (CAS RN 864731-61-3) | 0 % | — | 31.12.2029 |
| 0.8388 | ex 2934 99 90 | 11 | Aqueous solution of d(P-thio)(T-G-A-C-T-G-T-G-A-A-C-G-T-T-C-G-A-G-A-T-G-A) deoxyribonucleic acid (CAS RN 937402-51-2), containing by weight 15 % or more, but not more than 25 % of oligodeoxynucleotide | 0 % | — | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.5924 | ex 2934 99 90 | 12 | Dimethomorph (ISO) (CAS RN 110488-70-5) | 0 % | — | 31.12.2029 |
| 0.8348 | ex 2934 99 90 | 13 | (6 <i>S</i>)-6-methyl-5,6-Dihydro-4 <i>H</i> -thieno[2,3- <i>b</i>]thiopyran4-one-7,7-dioxide (CAS RN 148719-91-9) with a purity by weight of 98 % or more | 0 % | — | 31.12.2027 |
| 0.8326 | ex 2934 99 90 | 14 | 2-Mercaptoadenosine (CAS RN 43157-50-2) with a purity by weight of 98 % or more | 0 % | — | 31.12.2027 |
| 0.7843 | ex 2934 99 90 | 17 | (<i>S</i>)-4-(Tert-butoxycarbonyl)-1,4-oxazepane-2-carboxylic acid (CAS RN 1273567-44-4) with a purity by weight of 95 % or more | 0 % | — | 31.12.2029 |
| 0.8250 | ex 2934 99 90 | 18 | Methyl (1 <i>R</i> ,3 <i>R</i>)-1-(1,3-benzodioxol-5-yl)-2-(2-chloroacetyl)-1,3,4,9-tetrahydropyrido[5,4- <i>b</i>]indole-3-carboxylate (CAS RN 171489-59-1) with a purity by weight of 99 % or more | 0 % | — | 31.12.2026 |
| 0.8720 | ex 2934 99 90 | 19 | (4 <i>R</i> ,6 <i>S</i>)-6-Methyl-7,7-dioxo-5,6-dihydro-4 <i>H</i> -thieno[2,3- <i>b</i>]thiopyran-4-ol (CAS RN 147128-77-6) with a purity by weight of 94 % or more | 0 % | — | 31.12.2029 |
| 0.4715 | ex 2934 99 90 | 20 | Thiophene (CAS RN 110-02-1) | 0 % | — | 31.12.2029 |
| 0.8253 | ex 2934 99 90 | 22 | 4-(Oxiran-2-ylmethoxy)-9 <i>H</i> -carbazole (CAS RN 51997-51-4) with a purity by weight of 97 % or more | 0 % | — | 31.12.2026 |
| 0.4942 | *ex 2934 99 90 | 25 | 2,4-Diethyl-9 <i>H</i> -thioxanthen-9-one (CAS RN 82799-44-8) | 0 % | — | 31.12.2030 |
| 0.6252 | ex 2934 99 90 | 26 | 4-Methylmorpholine 4-oxide in an aqueous solution (CAS RN 7529-22-8) | 0 % | — | 31.12.2029 |
| 0.6362 | ex 2934 99 90 | 27 | 2-(4-Hydroxyphenyl)-1-benzothiophene-6-ol (CAS RN 63676-22-2) | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.5242 | ex 2934 99 90 | 28 | 11-(Piperazin-1-yl)dibenzo[b,f][1,4]thiazepine dihydrochloride (CAS RN 111974-74-4) | 0 % | — | 31.12.2026 |
| 0.4700 | ex 2934 99 90 | 30 | Dibenzo[b,f][1,4]thiazepin-11(10H)-one (CAS RN 3159-07-7) | 0 % | — | 31.12.2029 |
| 0.8724 | ex 2934 99 90 | 31 | Thenoic acid (CAS RN 1918-77-0) with a purity by weight of 97 % or more | 0 % | — | 31.12.2029 |
| 0.8267 | ex 2934 99 90 | 35 | Nusinersen sodium (INNM) (CAS RN 1258984-36-9) with a purity by weight of 95 % or more | 0 % | — | 31.12.2026 |
| 0.5813 | ex 2934 99 90 | 37 | 4-Propan-2-ylmorpholine (CAS RN 1004-14-4) | 0 % | — | 31.12.2027 |
| 0.8642 | ex 2934 99 90 | 38 | 2-Chloro-9H-thioxanthen-9-one (CAS RN 86-39-5) with a purity by weight of 98 % or more | 0 % | — | 31.12.2028 |
| 0.6824 | *ex 2934 99 90 | 39 | 4-(Oxiran-2-ylmethoxy)-9H-carbazole (CAS RN 51997-51-4) | 0 % | — | 31.12.2030 |
| 0.8094 | *ex 2934 99 90 | 40 | 2,3-Pyrazinedicarboxylic anhydride (CAS RN 4744-50-7) with a purity by weight of 95 % or more | 0 % | — | 31.12.2026 |
| 0.6823 | *ex 2934 99 90 | 41 | 11-[4-(2-Chloro-ethyl)-1-piperazinyl]dibenzo[b,f][1,4]thiazepine (CAS RN 352232-17-8) | 0 % | — | 31.12.2030 |
| 0.8380 | ex 2934 99 90 | 45 | 4-[4-[(5s)-5-(Aminomethyl)-2-oxo-3-oxazolidinyl] phenyl]-3-morpholinone, hydrochloride (CAS RN 898543-06-1) with a purity by weight of 98 % or more | 0 % | — | 31.12.2027 |
| 0.5453 | ex 2934 99 90 | 48 | Propan-2-ol – 2-methyl-4-(4-methylpiperazin-1-yl)-10H-thieno[2,3-b][1,5]benzodiazepine (1:2) dihydrate (CAS RN 864743-41-9) | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.7188 | ex 2934 99 90 | 49 | Cytidine 5'-(disodium phosphate) (CAS RN 6757-06-8) | 0 % | — | 31.12.2026 |
| 0.8601 | ex 2934 99 90 | 50 | Vutrisiran (INN) (CAS RN 1867157-35-4) with a purity by weight of 98 % or more | 0 % | — | 31.12.2028 |
| 0.8330 | ex 2934 99 90 | 51 | Uridine 5'-triphosphate trisodium salt (CAS RN 19817-92-6) with a dry weight purity of 90 % or more | 0 % | — | 31.12.2027 |
| 0.8031 | *ex 2934 99 90 | 55 | Uridine (CAS RN 58-96-8) with a purity by weight of 98 % or more | 0 % | — | 31.12.2030 |
| 0.7297 | ex 2934 99 90 | 56 | 1-[5-(2,6-Difluorophenyl)-4,5-dihydro-1,2-oxazol-3-yl]ethanone (CAS RN 1173693-36-1) | 0 % | — | 31.12.2027 |
| 0.3575 | *ex 2934 99 90 | 57 | Dimethenamide-P (ISO) (CAS RN 163515-14-8) with a purity by weight of 93 % or more | 0 % | — | 31.12.2029 |
| 0.7387 | ex 2934 99 90 | 59 | Dolutegravir (INN) (CAS RN 1051375-16-6) or dolutegravir sodium (CAS RN 1051375-19-9) | 0 % | — | 31.12.2027 |
| 0.2718 | ex 2934 99 90 | 60 | DL-Homocysteine thiolactone hydrochloride (CAS RN 6038-19-3) | 0 % | — | 31.12.2029 |
| 0.7459 | ex 2934 99 90 | 61 | 5-(1,2-Dithiolan-3-yl)valeric acid (CAS RN 1077-28-7) | 0 % | — | 31.12.2029 |
| 0.7537 | ex 2934 99 90 | 63 | (2b,3a,5a,16b,17b)-2-(Morpholin-4-yl)-16-(pyrrolidin-1-yl)androstane-3,17-diol (CAS RN 119302-20-4) | 0 % | — | 31.12.2029 |
| 0.7449 | ex 2934 99 90 | 64 | 2-Bromo-5-benzoylthiophene (CAS RN 31161-46-3) | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.7926 | *ex 2934 99 90 | 65 | Benzo[b]thiophen-10-methoxycycloheptanone (CAS RN 59743-84-9) with a purity by weight of 98 % or more | 0 % | — | 31.12.2026 |
| 0.4512 | ex 2934 99 90 | 66 | Tetrahydrothiophene-1,1-dioxide (CAS RN 126-33-0) | 0 % | — | 31.12.2029 |
| 0.7842 | ex 2934 99 90 | 69 | 3-Methyl-5-(4,4,5,5-tetramethyl-1,3,2-dioxaborolan-2-yl)benzo[d]oxazol-2(3H)-one (CAS RN 1220696-32-1) with a purity by weight of 95 % or more | 0 % | — | 31.12.2029 |
| 0.7944 | *ex 2934 99 90 | 70 | 1,3,4-Thiadiazolidine-2,5-dithione (CAS RN 1072-71-5) with a purity by weight of 95 % or more | 0 % | — | 31.12.2030 |
| 0.8289 | ex 2934 99 90 | 71 | 3,4-Dichloro-1,2,5-thiadiazole (CAS RN 5728-20-1) with a purity by weight of 99 % or more | 0 % | — | 31.12.2026 |
| 0.8317 | ex 2934 99 90 | 72 | 2-Trifluoromethyl-9-allyl-9-thioxanthen-ol (CAS RN 850808-70-7) with a purity by weight of 98 % or more | 0 % | — | 31.12.2027 |
| 0.4249 | ex 2934 99 90 | 74 | 2-Isopropylthioxanthone (CAS RN 5495-84-1) | 0 % | — | 31.12.2027 |
| 0.4052 | ex 2934 99 90 | 75 | (4R-cis)-1,1-Dimethylethyl-6-[2-[2-(4-fluorophenyl)-5-(1-isopropyl)-3-phenyl-4-[(phenylamino)carbonyl]-1H-pyrrol-1-yl]ethyl]-2,2-dimethyl-1,3-dioxane-4-acetate (CAS RN 125971-95-1) | 0 % | — | 31.12.2026 |
| 0.8933 | *ex 2934 99 90 | 76 | Nedosiran sodium (INNM) (CAS RN 2247026-22-6) with a purity by weight of 95 % or more | 0 % | — | 31.12.2030 |
| 0.8221 | ex 2934 99 90 | 77 | Tazemetostat (INN) (CAS 1403254-99-8) with a purity by weight of 99 % or more and its salts | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.8930 | *ex 2934 99 90 | 78 | Disodium uridine-5'-monophosphate (CAS RN 3387-36-8) with a purity by weight of 98 % or more | 0 % | — | 31.12.2030 |
| 0.8048 | *ex 2934 99 90 | 81 | 1-(4-Aminophenyl)-5-(morpholin-4-yl)-2,3-dihydropyridin-6-one (CAS RN 1267610-26-3) with a purity by weight of 98 % or more | 0 % | — | 31.12.2030 |
| 0.7815 | ex 2934 99 90 | 82 | Rel-(3aR,12bR)-11-Chloro-2,3,3a,12b-tetrahydro-2-methyl-1H-dibenz[2,3:6,7]oxepino[4,5-c]pyrrol-1-one (CAS RN 129385-59-7) with a purity by weight of 97 % or more | 0 % | — | 31.12.2029 |
| 0.4643 | ex 2934 99 90 | 83 | Flumioxazin (ISO) (CAS RN 103361-09-7) of a purity by weight of 96 % or more | 0 % | — | 31.12.2029 |
| 0.8222 | ex 2934 99 90 | 85 | Gilteritinib (INN) (CAS 1254053-43-4) with a purity by weight of 98 % or more and its salts | 0 % | — | 31.12.2026 |
| 0.5133 | *ex 2934 99 90 | 86 | Dithianon (ISO) (CAS RN 3347-22-6) | 0 % | — | 31.12.2030 |
| 0.5136 | *ex 2934 99 90 | 87 | 2,2'-(1,4-Phenylene)bis(4H-3,1-benzoxazin-4-one) (CAS RN 18600-59-4) | 0 % | — | 31.12.2030 |
| 0.7738 | ex 2934 99 90 | 88 | (7S,9aS)-7-((Benzyl)oxy)methyl)octahydropyrazino[2,1-c][1,4]oxazine dioxalate (CAS RN 1268364-46-0) | 0 % | — | 31.12.2029 |
| 0.8905 | *ex 2934 99 90 | 89 | 6R-[6a,7β(Z)]-7-[2-Furyl(methoxyimino)acetamido]-3-(hydroxymethyl)-8-oxo-5-thia-1-azabicyclo[4.2.0]oct-2-ene-2-carboxylic acid (CAS RN 56271-94-4) with a purity by weight of 96 % or more | 0 % | — | 31.12.2030 |
| 0.6486 | ex 2935 90 90 | 10 | Florasulam (ISO) (CAS RN 145701-23-1) | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8479 | ex 2935 90 90 | 16 | 2-Bromo-N-(4,5-dimethyl-1,2-oxazol-3-yl)-N-(methoxymethyl) benzene-1-sulfonamide (CAS RN 415697-57-3) with a purity by weight of 97 % or more | 0 % | — | 31.12.2027 |
| 0.8173 | ex 2935 90 90 | 18 | 4-Amino-2,5-dimethoxy-N-methylbenzenesulfonamide (CAS RN 49701-24-8) with a purity by weight of 98 % or more | 0 % | — | 31.12.2026 |
| 0.8174 | ex 2935 90 90 | 19 | 4-Amino-2,5-dimethoxy-N-phenylbenzenesulphonamide (CAS RN 52298-44-9) with a purity by weight of 98 % or more | 0 % | — | 31.12.2026 |
| 0.3565 | ex 2935 90 90 | 20 | Toluenesulphonamides | 0 % | — | 31.12.2029 |
| 0.8224 | ex 2935 90 90 | 21 | Encorafenib (INN) (CAS 1269440-17-6) with a purity by weight of 99 % or more | 0 % | — | 31.12.2026 |
| 0.8276 | ex 2935 90 90 | 22 | Methyl 2-(chlorosulfonyl)-4-(methylsulfonamidomethyl)benzoate (CAS RN 393509-79-0) with a purity by weight of 90 % or more | 0 % | — | 31.12.2026 |
| 0.5239 | ex 2935 90 90 | 23 | N-[4-(2-Chloroacetyl)phenyl]methanesulphonamide (CAS RN 64488-52-4) | 0 % | — | 31.12.2026 |
| 0.8277 | ex 2935 90 90 | 24 | 3-{{[(4-methylphenyl)sulfonyl]carbamoyl}amino}phenyl 4-methylbenzenesulfonate (CAS RN 232938-43-1) with a purity by weight of 99 % or more | 0 % | — | 31.12.2026 |
| 0.8467 | ex 2935 90 90 | 26 | 5-(2-Fluorophenyl)-1-(pyridin-3-ylsulfonyl)-1H-pyrrole-3-carbaldehyde (CAS RN 881677-11-8) with a purity by weight of 97 % or more | 0 % | — | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.5261 | ex 2935 90 90 | 27 | Methyl (3R,5S,6E)-7-{4-(4-fluorophenyl)-6-isopropyl-2-[methyl(methylsulfonyl)amino]pyrimidin-5-yl}-3,5-dihydroxyhept-6-enoate (CAS RN 147118-40-9) | 0 % | — | 31.12.2026 |
| 0.8350 | ex 2935 90 90 | 29 | Vemurafenib (INN) (CAS RN 918504-65-1) with a purity by weight of 98 % or more | 0 % | — | 31.12.2027 |
| 0.7183 | ex 2935 90 90 | 30 | 6-Aminopyridine-2-sulfonamide (CAS RN 75903-58-1) | 0 % | — | 31.12.2026 |
| 0.8413 | ex 2935 90 90 | 31 | 5-(N-3-methylphenyl-sulfonylamido)-(N,N"-bis-(3-methylphenyl)-isophthalicacid-diamide) (CAS RN 2375645-78-4) with a purity by weight of 95 % or more | 0 % | — | 31.12.2027 |
| 0.8693 | ex 2935 90 90 | 32 | 4-Chloro-3-nitro-5-sulphamoylbenzoic acid (CAS RN 22892-96-2) with a purity by weight of 96 % or more | 0 % | — | 31.12.2029 |
| 0.7677 | ex 2935 90 90 | 33 | 4-Chloro-3-pyridinesulphonamide (CAS RN 33263-43-3) | 0 % | — | 31.12.2029 |
| 0.7572 | ex 2935 90 90 | 37 | 1,3-Dimethyl-1H-pyrazole-4-sulfonamide (CAS RN 88398-53-2) | 0 % | — | 31.12.2029 |
| 0.7438 | ex 2935 90 90 | 40 | Venetoclax (INN) (CAS 1257044-40-8) | 0 % | — | 31.12.2027 |
| 0.8606 | ex 2935 90 90 | 41 | Lenacapavir sodium (INNM) (CAS RN 2283356-12-5) with a purity by weight of 98 % or more | 0 % | — | 31.12.2028 |
| 0.5036 | *ex 2935 90 90 | 42 | Penoxsulam (ISO) (CAS RN 219714-96-2) | 0 % | — | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.7928 | *ex 2935 90 90 | 44 | 4-[2-(7-Methoxy-4,4-dimethyl-1,3-dioxo-3,4-dihydroisoquinolin-2(1H)-yl)ethyl]benzenesulphonamide (CAS RN 33456-68-7) with a purity by weight of 99,5 % or more | 0 % | — | 31.12.2030 |
| 0.3562 | ex 2935 90 90 | 45 | Rimsulfuron (ISO) (CAS RN 122931-48-0) | 0 % | — | 31.12.2029 |
| 0.5451 | ex 2935 90 90 | 48 | (3R,5S,6E)-7-[4-(4-Fluorophenyl)-2-[methyl(methylsulfonyl)amino]-6-(propan-2-yl)pyrimidin-5-yl]-3,5-dihydroxyhept-6-enoic acid – 1-[(R)-(4-chlorophenyl)(phenyl)methyl]piperazine (1:1) (CAS RN 1235588-99-4) | 0 % | — | 31.12.2026 |
| 0.2843 | ex 2935 90 90 | 50 | 4,4'-Oxydi(benzenesulphonohydrazide) (CAS RN 80-51-3) | 0 % | — | 31.12.2029 |
| 0.4636 | ex 2935 90 90 | 53 | 2,4-Dichloro-5-sulphamoylbenzoic acid (CAS RN 2736-23-4) | 0 % | — | 31.12.2029 |
| 0.6777 | *ex 2935 90 90 | 54 | Propoxycarbazone-sodium (ISO) (CAS RN 181274-15-7) with a purity by weight of 95 % or more | 0 % | — | 31.12.2030 |
| 0.3560 | ex 2935 90 90 | 55 | Thifensulfuron-methyl (ISO) (CAS RN 79277-27-3) | 0 % | — | 31.12.2029 |
| 0.6802 | *ex 2935 90 90 | 56 | N-(p-Toluenesulphonyl)-N'-(3-(p-toluenesulphonyloxy)phenyl)urea (CAS RN 232938-43-1) | 0 % | — | 31.12.2030 |
| 0.6903 | *ex 2935 90 90 | 57 | N-{2-[(phenylcarbamoyl)amino]phenyl}benzenesulphonamide (CAS RN 215917-77-4) | 0 % | — | 31.12.2030 |
| 0.6664 | *ex 2935 90 90 | 59 | Flazasulfuron (ISO) (CAS RN 104040-78-0) with a purity of 94 % by weight or more | 0 % | — | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.4586 | ex 2935 90 90 | 63 | Nicosulphuron (ISO), (CAS RN 111991-09-4) of a purity by weight of 91 % or more | 0 % | — | 31.12.2029 |
| 0.3561 | ex 2935 90 90 | 65 | Tribenuron-methyl (ISO) (CAS RN 101200-48-0) | 0 % | — | 31.12.2029 |
| 0.7854 | ex 2935 90 90 | 70 | (4S)-4-Hydroxy-2-(3-methoxypropyl)-3,4-dihydro-2H-thieno[3,2-e]thiazine-6-sulfonamide-1,1-dioxide (CAS RN 154127-42-1) with a purity by weight of 97 % or more | 0 % | — | 31.12.2029 |
| 0.8055 | *ex 2935 90 90 | 80 | 4-Chloro-3-sulphamoylbenzoic acid (CAS RN 1205-30-7) with a purity by weight of 97 % or more | 0 % | — | 31.12.2030 |
| 0.3704 | ex 2935 90 90 | 88 | N-(2-(4-Amino-N-ethyl-m-toluidino)ethyl)methanesulphonamide sesquisulphate monohydrate (CAS RN 25646-71-3) | 0 % | — | 31.12.2029 |
| 0.4048 | ex 2935 90 90 | 89 | 3-(3-Bromo-6-fluoro-2-methylindol-1-ylsulphonyl)-N, N-dimethyl-1,2,4-triazol-1-sulphonamide (CAS RN 348635-87-0) | 0 % | — | 31.12.2026 |
| 0.4944 | *ex 2938 90 30 | 10 | Ammonium glycyrrhizate (CAS RN 53956-04-0) | 0 % | — | 31.12.2030 |
| 0.3554 | ex 2938 90 90 | 10 | Hesperidin (CAS RN 520-26-3) | 0 % | — | 31.12.2029 |
| 0.5927 | ex 2938 90 90 | 20 | Ethylvanillin beta-D-glucopyranoside (CAS RN 122397-96-0) | 0 % | — | 31.12.2029 |
| 0.7329 | ex 2938 90 90 | 30 | Rebaudioside A (CAS RN 58543-16-1) | 0 % | — | 31.12.2027 |
| 0.7047 | ex 2940 00 00 | 30 | D(+) - Trehalose dihydrate (CAS RN 6138-23-4) | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8424 | ex 2940 00 00 | 60 | Methyl α -D-mannopyranoside (CAS RN 617-04-9) with a purity by weight of 98 % or more | 0 % | — | 31.12.2027 |
| 0.8635 | ex 2940 00 00 | 70 | Alpha-D-Mannopyranose, 6-acetate 2,3,4-tribenzoate 1-(2,2,2-trichloroethanimidate) (CAS RN 346441-49-4) with a purity by weight of 95 % or more | 0 % | — | 31.12.2028 |
| 0.5233 | ex 2941 20 30 | 10 | Dihydrostreptomycin sulphate (CAS RN 5490-27-7) | 0 % | — | 31.12.2026 |
| 0.6984 | ex 2942 00 00 | 10 | Sodium triacetoxyborohydride (CAS RN 56553-60-7) | 0 % | — | 31.12.2026 |
| 0.8614 | ex 2942 00 00 | 20 | Dimethylamine—borane (1:1) (CAS RN 74-94-2) with a purity by weight of 98 % or more | 0 % | — | 31.12.2028 |
| 0.3555 | 3201 20 00 | | Wattle extract | 0 % | — | 31.12.2029 |
| 0.7943 | *ex 3201 90 20 | 10 | <i>Rhus chinensis</i> gall (<i>Galla chinensis</i>) water-based extract, with a tannin content by weight of 85 % or less | 0 % | — | 31.12.2030 |
| 0.3553 | ex 3201 90 90 | 20 | Tanning extracts derived from gambier and myrobalan fruits | 0 % | — | 31.12.2029 |
| 0.6183 | ex 3204 11 00 | 15 | Colourant C.I. Disperse Blue 360 (CAS RN 70693-64-0) and preparations based thereon with a colourant C.I. Disperse Blue 360 content of 99 % or more by weight | 0 % | — | 31.12.2029 |
| 0.6277 | ex 3204 11 00 | 25 | N-(2-Chloroethyl)-4-[(2,6-dichloro-4-nitrophenyl)azo]-N-ethyl-m-toluidine (CAS RN 63741-10-6) | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.5264 | ex 3204 11 00 | 50 | Colourant C.I. Disperse Blue 72 (CAS RN 81-48-1) and preparations based thereon with a colourant C.I. Disperse Blue 72 content of 95 % or more by weight | 0 % | — | 31.12.2027 |
| 0.6972 | ex 3204 12 00 | 15 | Colourant C.I. Acid Brown 75 (CAS RN 8011-86-7) and preparations based thereon with a colourant C.I. Acid Brown 75 content of 75 % or more by weight | 0 % | — | 31.12.2026 |
| 0.6975 | ex 3204 12 00 | 17 | Colourant C.I. Acid Brown 355 (CAS RN 84989-26-4 or 60181-77-3) and preparations based thereon with a colourant C.I. Acid Brown 355 content of 75 % or more by weight | 0 % | — | 31.12.2026 |
| 0.7021 | ex 3204 12 00 | 25 | Colourant C.I. Acid Black 210 (CAS RN 85223-29-6 or 99576-15-5) and preparations based thereon with a colourant C.I. Acid Black 210 content of 50 % or more by weight | 0 % | — | 31.12.2026 |
| 0.6976 | ex 3204 12 00 | 27 | Colourant C.I. Acid Brown 425 (CAS RN 75234-41-2 or 119509-49-8) and preparations based thereon with a colourant C.I. Acid Brown 425 content of 75 % or more by weight | 0 % | — | 31.12.2026 |
| 0.6963 | ex 3204 12 00 | 35 | Colourant C.I. Acid Black 234 (CAS RN 157577-99-6) and preparations based thereon with a colourant C.I. Acid Black 234 content of 75 % or more by weight | 0 % | — | 31.12.2026 |
| 0.6964 | ex 3204 12 00 | 37 | Colourant C.I. Acid Black 210 sodium salt (CAS RN 201792-73-6) and preparations based thereon with a colourant C.I. Acid Black 210 sodium salt content of 50 % or more by weight | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.5925 | ex 3204 12 00 | 40 | Liquid dye preparation containing anionic acid dye C.I. Acid Blue 182 (CAS RN 12219-26-0) | 0 % | — | 31.12.2029 |
| 0.6965 | ex 3204 12 00 | 45 | Colourant C.I. Acid Blue 161/193 (CAS RN 12392-64-2) and preparations based thereon with a colourant C.I. Acid Blue 161/193 content of 75 % or more by weight | 0 % | — | 31.12.2026 |
| 0.6971 | ex 3204 12 00 | 47 | Colourant C.I. Acid Brown 58 (CAS RN 70210-34-3 or 12269-87-3) and preparations based thereon with a colourant C.I. Acid Brown 58 content of 75 % or more by weight | 0 % | — | 31.12.2026 |
| 0.6973 | ex 3204 12 00 | 55 | Colourant C.I. Acid Brown 165 (CAS RN 61724-14-9) and preparations based thereon with a colourant C.I. Acid Brown 165 content of 75 % or more by weight | 0 % | — | 31.12.2026 |
| 0.6974 | ex 3204 12 00 | 57 | Colourant C.I. Acid Brown 282 (CAS RN 70236-60-1 or 12219-65-7) and preparations based thereon with a colourant C.I. Acid Brown 282 content of 75 % or more by weight | 0 % | — | 31.12.2026 |
| 0.6535 | ex 3204 12 00 | 60 | Colourant C.I. Acid Red 52 (CAS RN 3520-42-1) and preparations based thereon with a colourant C.I. Acid Red 52 content of 97 % or more by weight | 0 % | — | 31.12.2029 |
| 0.6977 | ex 3204 12 00 | 65 | Colourant C.I. Acid Brown 432 (CAS RN 119509-50-1) and preparations based thereon with a colourant C.I. Acid Brown 432 content of 75 % or more by weight | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.6652 | *ex 3204 12 00 | 70 | Colourant C.I. Acid blue 25 (CAS RN 6408-78-2) and preparations based thereon with a colourant C.I. Acid blue 25 content of 80 % or more by weight | 0 % | — | 31.12.2030 |
| 0.4065 | ex 3204 13 00 | 10 | Colourant C.I. Basic Red 1 (CAS RN 989-38-8) and preparations based thereon with a colourant C.I. Basic Red 1 content of 50 % or more by weight | 0 % | — | 31.12.2029 |
| 0.7394 | ex 3204 13 00 | 15 | Colourant C.I. Basic Blue 41 (CAS RN 12270-13-2) and preparations based thereon with a colourant C.I. Basic Blue 41 content of 50 % or more by weight | 0 % | — | 31.12.2027 |
| 0.7396 | ex 3204 13 00 | 35 | Colourant C.I. Basic Yellow 28 (CAS RN 54060-92-3) and preparations based thereon with a colourant C.I. Basic Yellow 28 content of 50 % or more by weight | 0 % | — | 31.12.2027 |
| 0.5805 | ex 3204 13 00 | 40 | Colourant C.I. Basic Violet 1 (CAS RN 603-47-4 or CAS RN 8004-87-3) and preparations based thereon with a colourant C.I. Basic Violet 1 content of 90 % or more by weight | 0 % | — | 31.12.2027 |
| 0.6475 | ex 3204 13 00 | 60 | Colourant C.I. Basic Red 1:1 (CAS RN 3068-39-1) and preparations based thereon with a colourant C.I. Basic Red 1:1 content of 90 % or more by weight | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8888 | ex 3204 13 00 | 85 | Mixture containing by weight: — 25 % or more but not more than 40 % of Colourant C.I. Basic Blue 3 (CAS RN 33203-82-6) and — 25 % or more but not more than 40 % of C.I. Basic Blue 159 (CAS RN 105953-73-9) | 0 % | — | 31.12.2029 |
| 0.6569 | *ex 3204 14 00 | 10 | Colourant C.I. Direct Black 80 (CAS RN 8003-69-8) and preparations based thereon with a colourant C.I. Direct Black 80 content of 90 % or more by weight | 0 % | — | 31.12.2030 |
| 0.6571 | ex 3204 14 00 | 30 | C.I. Colourant Direct Red 23 (CAS RN 3441-14-3) and preparations based thereon with a colourant C.I. Direct Red 23 content of 90 % or more by weight | 0 % | — | 31.12.2029 |
| 0.8537 | ex 3204 15 00 | 15 | Colourant C.I. Vat Blue 1 (CAS RN 482-89-3) and preparations based thereon with a colourant C.I. Vat Blue 1 content of 94 % or more by weight | 0 % | — | 31.12.2028 |
| 0.8842 | ex 3204 15 00 | 25 | Mixture in a 3:2 ratio of colourants C.I. Vat Blue 1 potassium salt (CAS RN 835912-68-0) and C.I. Vat Blue 1 sodium salt (CAS RN 894-86-0) and preparations based thereon with a combined content of colourants C.I. Vat Blue 1 salts of 40 % or more by weight | 0 % | — | 31.12.2029 |
| 0.6129 | ex 3204 15 00 | 70 | Colourant C.I. Vat Red 1 (CAS RN 2379-74-0) | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.6325 | ex 3204 16 00 | 30 | Preparations based on Colourant Reactive Black 5 (CAS RN 17095-24-8) with a content thereof of 60 % or more but not more than 75 % by weight, and including one or more of the following: — Colourant Reactive Yellow 201 (CAS RN 27624-67-5), — 1-Naphthalenesulphonic acid,4-amino-3-[[4-[[2-(sulphooxy)ethyl]sulphonyl]phenyl]azo]-, disodium salt (CAS RN 250688-43-8), or — 3,5-diamino-4-[[4-[[2-(sulphooxy)ethyl]sulphonyl]fenyl]azo]-2-[[2-sulfo-4-[[2-(sulphooxy)ethyl]sulfonyl]phenyl]azobenzoic acid sodium salt (CAS RN 906532-68-1) | 0 % | — | 31.12.2029 |
| 0.7367 | ex 3204 16 00 | 40 | Aqueous solution of Colourant C.I. Reactive Red 141 (CAS RN 61931-52-0) — with a colourant C.I. Reactive Red 141 content of 13 % or more by weight, and — containing a preservative | 0 % | — | 31.12.2027 |
| 0.2517 | ex 3204 17 00 | 10 | Colourant C.I. Pigment Yellow 81 (CAS RN 22094-93-5) and preparations based thereon with a colourant C.I. Pigment Yellow 81 content of 50 % or more by weight | 0 % | — | 31.12.2029 |
| 0.5433 | ex 3204 17 00 | 15 | Colourant C.I. Pigment Green 7 (CAS RN 1328-53-6) and preparations based thereon with a colourant C.I. Pigment Green 7 content of 40 % or more by weight | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.7092 | ex 3204 17 00 | 18 | Colourant C.I. Pigment Orange 16 (CAS RN 6505-28-8) and preparations based thereon with a colourant C.I. Pigment Orange 16 content of 90 % or more by weight | 0 % | — | 31.12.2026 |
| 0.6130 | ex 3204 17 00 | 19 | Colourant C.I. Pigment Red 48:2 (CAS RN 7023-61-2) and preparations based thereon with a colourant C.I. Pigment Red 48:2 content of 85 % or more by weight | 0 % | — | 31.12.2029 |
| 0.5505 | ex 3204 17 00 | 20 | Colourant C.I. Pigment Blue 15:3 (CAS RN 147-14-8) and preparations based thereon with a colourant C.I. Pigment Blue 15:3 content of 35 % or more by weight | 0 % | — | 31.12.2026 |
| 0.6279 | ex 3204 17 00 | 21 | Colourant C.I. Pigment Blue 15:4 (CAS RN 147-14-8) and preparations based thereon with a colourant C.I. Pigment Blue 15:4 content of 35 % or more by weight | 0 % | — | 31.12.2029 |
| 0.5259 | ex 3204 17 00 | 22 | Colourant C.I. Pigment Red 169 (CAS RN 12237-63-7) and preparations based thereon with a colourant C.I. Pigment Red 169 content of 50 % or more by weight | 0 % | — | 31.12.2026 |
| 0.6246 | ex 3204 17 00 | 23 | Colourant C.I. Pigment Brown 41 (CAS RN 211502-16-8 or CAS RN 68516-75-6) | 0 % | — | 31.12.2029 |
| 0.6453 | ex 3204 17 00 | 24 | Colourant C.I. Pigment Red 57:1 (CAS RN 5281-04-9) and preparations based thereon with a Colourant C.I. Pigment Red 57:1 content of 20 % or more by weight | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.5427 | ex 3204 17 00 | 25 | Colourant C.I. Pigment Yellow 14 (CAS RN 5468-75-7) and preparations based thereon with a colourant C.I. Pigment Yellow 14 content of 25 % or more by weight | 0 % | — | 31.12.2026 |
| 0.7261 | ex 3204 17 00 | 26 | Colourant C.I. Pigment Orange 13 (CAS RN 3520-72-7) and preparations based thereon with a colourant C.I. Pigment Orange 13 content of 80 % or more by weight | 0 % | — | 31.12.2027 |
| 0.8678 | ex 3204 17 00 | 28 | Colourant C.I. Pigment Yellow 12 (CAS RN 6358-85-6) and preparations based thereon with a colourant C.I. Pigment Yellow 12 content of 21 % or more by weight | 0 % | — | 31.12.2028 |
| 0.7659 | ex 3204 17 00 | 31 | Colourant C.I. Pigment Red 63:1 (CAS RN 6417-83-0) and preparations based thereon with a colourant C.I. Pigment Red 63:1 content of 70 % or more by weight | 0 % | — | 31.12.2029 |
| 0.6603 | *ex 3204 17 00 | 33 | Colourant C.I. Pigment Blue 15:1 (CAS RN 147-14-8) and preparations based thereon with a colourant C.I. Pigment Blue 15:1 content of 35 % or more by weight | 0 % | — | 31.12.2030 |
| 0.5426 | ex 3204 17 00 | 35 | Colourant C.I. Pigment Red 202 (CAS RN 3089-17-6) and preparations based thereon with a colourant C.I. Pigment Red 202 content of 70 % or more by weight | 0 % | — | 31.12.2026 |
| 0.7565 | ex 3204 17 00 | 37 | Colourant C.I. Pigment Red 81:2 (CAS RN 75627-12-2) and preparations based thereon with a colourant C.I. Pigment Red 81:2 content of 30 % or more by weight | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.8827 | ex 3204 17 00 | 51 | Colourant C.I. Pigment Yellow 174 (CAS RN 78952-72-4) and preparations based thereon with a colourant C.I. Pigment Yellow 174 content of 50 % or more by weight. | 0 % | — | 31.12.2029 |
| 0.8798 | ex 3204 17 00 | 52 | Colourant C.I. Pigment Red 112 (CAS RN 6535-46-2) and preparations based thereon with a colourant C.I. Pigment Red 112 content of 90 % or more by weight | 0 % | — | 31.12.2029 |
| 0.8795 | ex 3204 17 00 | 53 | Colourant C.I. Pigment Red 122 (CAS RN 980-26-7) and preparations based thereon with a colourant C.I. Pigment Red 122 content of 90 % or more by weight | 0 % | — | 31.12.2029 |
| 0.8801 | ex 3204 17 00 | 54 | Colourant C.I. Pigment Yellow 65 (CAS RN 6528-34-3) and preparations based thereon with a colourant C.I. Pigment Yellow 65 content of 90 % or more by weight | 0 % | — | 31.12.2029 |
| 0.8816 | ex 3204 17 00 | 56 | Colourant C.I. Pigment Red 146 (CAS RN 5280-68-2) and preparations based thereon with a colourant C.I. Pigment Red 146 content of 90 % or more by weight | 0 % | — | 31.12.2029 |
| 0.8821 | ex 3204 17 00 | 57 | Colourant C.I. Pigment Yellow 13 (CAS RN 5102-83-0) and preparations based thereon with a content of colourant C.I. Pigment Yellow 13 of 50 % or more by weight | 0 % | — | 31.12.2029 |
| 0.8892 | ex 3204 17 00 | 58 | Colourant C.I. Pigment Yellow 17 (CAS RN 4531-49-1) and preparations based thereon with a colourant C.I. Pigment Yellow 17 content of 90 % or more by weight | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.8877 | ex 3204 17 00 | 59 | Colourant C.I. Pigment Yellow 180 (CAS RN 77804-81-0) and preparations based thereon with a colourant C.I. Pigment Yellow 180 content of 90 % or more by weight | 0 % | — | 31.12.2029 |
| 0.5832 | ex 3204 17 00 | 75 | Colourant C.I. Pigment Orange 5 (CAS RN 3468-63-1) and preparations based thereon with a colourant C.I. Pigment Orange 5 content of 80 % or more by weight | 0 % | — | 31.12.2027 |
| 0.5700 | ex 3204 17 00 | 85 | Colourant C.I. Pigment Blue 61 (CAS RN 1324-76-1) and preparations based thereon with a colourant C.I. Pigment Blue 61 content of 35 % or more by weight | 0 % | — | 31.12.2027 |
| 0.5680 | ex 3204 17 00 | 88 | Colourant C.I. Pigment Violet 3 (CAS RN 1325-82-2 or CAS RN 101357-19-1) and preparations based thereon with a colourant C.I. Pigment Violet 3 content of 90 % or more by weight | 0 % | — | 31.12.2027 |
| 0.6979 | ex 3204 19 00 | 13 | Colourant C.I. Sulphur Black 1 (CAS RN 1326-82-5) and preparations based thereon with a colourant C.I. Sulphur Black 1 content of 75 % or more by weight | 0 % | — | 31.12.2026 |
| 0.5100 | ex 3204 19 00 | 73 | Colourant C.I. Solvent Blue 104 (CAS RN 116-75-6) and preparations based thereon with a colourant C.I. Solvent Blue 104 content of 97 % or more by weight | 0 % | — | 31.12.2026 |
| 0.8881 | ex 3204 19 00 | 74 | Colourant C.I. Solvent Red 135 (CAS RN 71902-17-5) and preparations based thereon with a colourant C.I. Solvent Red 135 content of 90 % or more by weight | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8883 | ex 3204 19 00 | 76 | Colourant C.I. Solvent Red 52 (CAS RN 81-39-0) and preparations based thereon with a colourant C.I. Solvent Red 52 content of 90 % or more by weight | 0 % | — | 31.12.2029 |
| 0.5282 | ex 3204 19 00 | 77 | Colourant C.I. Solvent Yellow 98 (CAS RN 27870-92-4 or CAS RN 12671-74-8) and preparations based thereon with a colourant C.I. Solvent Yellow 98 content of 95 % or more by weight | 0 % | — | 31.12.2026 |
| 0.8880 | ex 3204 19 00 | 78 | Colourant C.I. Solvent Yellow 114 (CAS RN 17772-51-9) and preparations based thereon with a colourant C.I. Solvent Yellow 114 content of 90 % or more by weight | 0 % | — | 31.12.2029 |
| 0.4058 | ex 3204 20 00 | 10 | Colourant C.I. Fluorescent Brightener 184 (CAS RN 7128-64-5) and preparations based thereon with a colourant C.I. Fluorescent Brightener 184 content of 20 % or more by weight | 0 % | — | 31.12.2026 |
| 0.5395 | ex 3204 20 00 | 30 | Colourant C.I. Fluorescent Brightener 351 (CAS RN 27344-41-8) and preparations based thereon with a colourant C.I. Fluorescent Brightener 351 content of 90 % or more by weight | 0 % | — | 31.12.2026 |
| 0.6473 | ex 3204 90 00 | 10 | Colourant C.I. Solvent Yellow 172 (also known as C.I. Solvent Yellow 135) (CAS RN 68427-35-0) and preparations based thereon with a colourant C.I. Solvent Yellow 172 (also known as C.I. Solvent Yellow 135) content of 90 % or more by weight | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.7658 | ex 3205 00 00 | 20 | Colourant C.I. Solvent Red 48 (CAS RN 13473-26-2) preparation, in a form of dry powder, containing by weight: — 16 % or more but not more than 25 % of Colourant C.I. Solvent Red 48 (CAS RN 13473-26-2) — 65 % or more but not more than 75 % of aluminium hydroxide (CAS RN 21645-51-2) | 0 % | — | 31.12.2029 |
| 0.7699 | ex 3205 00 00 | 30 | Colourant C.I. Pigment Red 174 (CAS RN 15876-58-1) preparation, in a form of dry powder, containing by weight: — 16 % or more but not more than 21 % of Colourant C.I. Pigment Red 174 (CAS RN 15876-58-1) — 65 % or more but not more than 69 % of aluminium hydroxide (CAS RN 21645-51-2) | 0 % | — | 31.12.2029 |
| 0.5378 | ex 3206 19 00 | 10 | Preparation containing by weight: — 72 % (\pm 2 %) of mica (CAS RN 12001-26-2), and — 28 % (\pm 2 %) of titanium dioxide (CAS RN 13463-67-7) | 0 % | — | 31.12.2026 |
| 0.8770 | ex 3206 20 00 | 50 | Nickel iron chromite black spinel (C.I. pigment black 30) (CAS RN 71631-15-7) | 0 % | — | 31.12.2029 |
| 0.8765 | ex 3206 20 00 | 60 | Cobalt chromite green spinel (C.I. pigment green 26) (CAS RN 68187-49-5) | 0 % | — | 31.12.2029 |
| 0.8768 | ex 3206 20 00 | 70 | Copper chromite black spinel (C.I. pigment black 28) (CAS RN 68186-91-4) | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8874 | ex 3206 41 00 | 10 | Colourant C.I. Pigment Blue 29 (CAS RN 57455-37-5) and preparations based thereon with a colourant C.I. Pigment Blue 29 content of 90 % or more by weight | 0 % | — | 31.12.2029 |
| 0.6245 | ex 3206 49 70 | 20 | Colourant C.I. Pigment Blue 27 (CAS RN 14038-43-8) | 0 % | — | 31.12.2029 |
| 0.7390 | ex 3206 49 70 | 40 | Colourant C.I. Pigment Blue 27 (CAS RN 25869-00-5) and preparations thereon with a colourant C.I. Pigment Blue 27 content of 85 % or more by weight | 0 % | — | 31.12.2027 |
| 0.8211 | ex 3206 49 70 | 50 | Concentrated mixture of pigments (masterbatch) in the form of pellets containing by weight: — 50 % or more but not more than 70 % of polyamide-6.6 (CAS RN 32131-17-2), — 15 % or more but not more than 20 % of iron powder (CAS RN 7439-89-6), — 5 % or more but not more than 15 % of barium sulphate (CAS RN 7727-43-7), and — 5 % or more but not more than 10 % of blue pigment, consisting of a mixture of Titanium dioxide (CAS RN 13463-67-7) and Copper(II) pthalocyanine (CAS RN 147-14-8) | 0 % | — | 31.12.2026 |
| 0.8800 | ex 3206 49 70 | 60 | Colourant C.I. Pigment Yellow 164 (CAS RN 68412-38-4) and preparations based thereon with a colourant C.I. Pigment Yellow 164 content of 90 % or more by weight | 0 % | — | 31.12.2029 |
| 0.3673 | 3206 50 00 | | Inorganic products of a kind used as luminophores | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|--------------------------------|----------|--|-------------------------|--------------------|-------------------------------------|
| 0.8676 | ex 3207 30 00 | 30 | Silver paste, containing by weight: — 45 % or more, but not more than 90 % silver (CAS RN 7440-22-4) and — 59 % or more, but not more than 92 % of the total solids (including silver) for use as conductor in the production of solar cells (¹) | 0 % | — | 31.12.2028 |
| 0.8630 | ex 3207 30 00 | 40 | Aluminium paste, containing by weight: — 72 % or more but not more than 82 % aluminium (CAS RN 7429-90-5) — with a viscosity of 10 or more, but not more than 100 Pas (Brookfield RVT, 14 Spindle, 20 rpm, 25 °C ± 0,5 °C) — with an aluminium particle size of not more than 25 µm for use in the production of solar cells (¹) | 0 % | — | 31.12.2028 |
| 0.2511 | ex 3208 20 10 | 10 | Copolymer of N-vinylcaprolactam, N-vinyl-2-pyrrolidone and dimethylaminoethyl methacrylate, in the form of a solution in ethanol containing by weight 34 % or more but not more than 40 % of copolymer | 0 % | — | 31.12.2029 |
| 0.4511 | ex 3208 20 10 | 20 | Immersion topcoat solution containing by weight 0,5 % or more but not more than 15 % of acrylate-methacrylate-alkenesulphonate copolymers with fluorinated side chains, in a solution of n-butanol and/or 4-methyl-2-pentanol and/or diisoamylether | 0 % | — | 31.12.2029 |
| 0.8412 | ex 3208 20 10 ex 3905 91 00 | 50 25 | Copolymer of vinylcaprolactam and vinylpyrrolidone (CAS RN 51987-20-3) in the form of a solution in 2-butoxyethanol (CAS RN 111-76-2) containing by weight 45 % or more but not more than 58 % of copolymer | 0 % | — | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------------------------|----------|--|-------------------------|--------------------|-------------------------------------|
| 0.8137 | *ex 3208 90 19 ex 3911 90 99 | 13 63 | Mixture, containing by weight: — 20 % or more but not more than 40 % of a copolymer of methyl vinyl ether and monobutyl maleate (CAS RN 25119-68-0), — 7 % or more but not more than 20 % of a copolymer of methyl vinyl ether and monoethyl maleate (CAS RN 25087-06-3), — 40 % or more, but not more than 65 % of ethanol (CAS RN 64-17-5), — 1 % or more but not more than 7 % of butan-1-ol (CAS RN 71-36-3) | 0 % | — | 31.12.2030 |
| 0.3967 | ex 3208 90 19 | 15 | Chlorinated polyolefins, in a solution | 0 % | — | 31.12.2029 |
| 0.2504 | ex 3208 90 19 | 40 | Polymer of methylsiloxane, in the form of a solution in a mixture of acetone, butanol, ethanol and isopropanol, containing by weight 5 % or more but not more than 11 % of polymer of methylsiloxane | 0 % | — | 31.12.2029 |
| 0.6154 | ex 3208 90 19 ex 3824 99 92 | 45 63 | Polymer consisting of a polycondensate of formaldehyde and naphthalenediol, chemically modified by reaction with an alkyne halide, dissolved in propylene glycol methyl ether acetate | 0 % | — | 31.12.2029 |
| 0.6989 | ex 3208 90 19 | 47 | Solution containing by weight: — 0,1 % or more but not more than 20 % of alkoxygroups containing siloxane polymer with alkyl or aryl substituents — 75 % or more of an organic solvent containing one or more of propyleneglycolethylether (CAS RN 1569-02-4), propylene glycol mono methylether acetate (CAS RN 108-65-6) or propyleneglycol propylether (CAS RN 1569-01-3) | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.2502 | ex 3208 90 19 | 50 | <p>Solution containing by weight:</p> <ul style="list-style-type: none"> — (63,5 ±10) % of gamma-butyrolactone (CAS RN 96-48-0), — (30 ± 10) % of aromatic polyhydroxyamide resin, — (3,5 ± 1,5) % of naphthoquinone ester derivative, — (1,5 ± 0,5) % of arylsilicic acid, — (1,5 ± 0,5) % of [3-(trimethoxysilyl)propyl]urea (CAS RN 23843-64-3) | 0 % | — | 31.12.2026 |
| 0.6726 | ex 3208 90 19 | 55 | Preparation of 5 % or more but not more than 20 % by weight of a copolymer of propylene and maleic anhydride, or a blend of polypropylene and a copolymer of propylene and maleic anhydride, or a blend of polypropylene and a copolymer of propylene, isobutene and maleic anhydride in an organic solvent | 0 % | — | 31.12.2026 |
| 0.4037 | ex 3208 90 19 | 60 | <p>Copolymer of hydroxystyrene with one or more of the following:</p> <ul style="list-style-type: none"> — styrene — alkoxystyrene — alkylacrylates <p>dissolved in ethyl lactate</p> | 0 % | — | 31.12.2026 |
| 0.6005 | ex 3208 90 19 | 65 | Silicones containing 50 % by weight or more of xylene and not more than 25 % by weight of silica, of a kind used for the manufacture of long term surgical implants | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.5777 | ex 3215 19 00 | 20 | Ink: — consisting of a polyester polymer and a dispersion of silver (CAS RN 7440-22-4) and silver chloride (CAS RN 7783-90-6) in methyl propyl ketone (CAS RN 107-87-9), — with a total solid content by weight of 55 % or more, but not more than 57 %, and — with a specific density of 1,40 g/cm ³ or more, but not more than 1,60 g/cm ³ , for use in the manufacture of electrodes (¹) | 0 % | 1 | 31.12.2027 |
| 0.2501 | ex 3215 90 70 | 20 | Heat sensitive ink fixed on a plastic film | 0 % | — | 31.12.2029 |
| 0.4533 | ex 3215 90 70 | 30 | Disposable cartridge ink, containing by weight: — 1 % or more, but not more than 10 % of amorphous silicon dioxide or — 3,8 % or more of dye C.I. Solvent Black 7 in organic solvents for use in the marking of integrated circuits (¹) | 0 % | — | 31.12.2029 |
| 0.3661 | ex 3301 12 10 | 10 | Essential oil of sweet orange (CAS RN 8028-48-6) or essential oil of sour orange (CAS RN 72968-50-4), not deterpenated | 0 % | — | 31.12.2029 |
| 0.4863 | ex 3402 39 90 | 10 | Sodium lauroyl methyl isethionate | 0 % | — | 31.12.2026 |
| 0.4002 | ex 3402 42 00 | 10 | Vinyl copolymer surface active agent based on polypropylene glycol | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.4277 | ex 3402 42 00 | 20 | Surfactant containing 1,4-dimethyl- 1,4-bis(2-methylpropyl)-2-butyne-1,4-diyl ether, polymerised with oxirane, methyl terminated | 0 % | — | 31.12.2027 |
| 0.6285 | ex 3402 90 10 | 10 | Surface-active mixture of methyltri-C8-C10-alkylammonium chlorides (CAS RN 63393-96-4) | 0 % | — | 31.12.2029 |
| 0.8758 | ex 3402 90 10 | 15 | Silicone surfactant consisting of a mixture of: <ul style="list-style-type: none"> — 60 % or more but not more than 85 % by weight of Polyalkyleneoxidizedimethylsiloxane copolymer (CAS RN 68937-55-3), — 15 % or more but not more than 40 % by weight of poly(oxy-1,2-ethanediyl), α-hydro-ω-hydroxy-Ethane-1,2-diol, ethoxylated (CAS RN 25322-68-3), — 0,8 % or more but not more than 1,5 % by weight Octamethylcyclotetrasiloxane (CAS RN 556-67-2), — 0,6 % or more but not more than 1,0 % by weight Decamethylcyclopentasiloxane (CAS RN 541-02-6), — 0,2 % or more but not more than 0,5 % by weight Dodecamethylcyclohexasiloxane (CAS RN 540-97-6) | 0 % | — | 31.12.2029 |
| 0.3660 | ex 3402 90 10 | 80 | Mixture, containing by weight: <ul style="list-style-type: none"> — 80 % or more but not more than 90 % of docusate sodium (INN) (CAS RN 577-11-7), and — 10 % or more but not more than 20 % of sodium benzoate (CAS RN 532-32-1) | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.4313 | ex 3506 91 90 | 40 | Acrylic pressure sensitive adhesive with a thickness of 0,076 mm or more but not more than 0,127 mm, put up in rolls of a width of 45,7 cm or more but not more than 132 cm supplied on a release liner with an initial peel adhesion release value of not less than 15 N/25 mm (measured according to ASTM D3330) | 0 % | — | 31.12.2029 |
| 0.6293 | ex 3507 90 90 | 10 | Preparation of <i>Achromobacter lyticus</i> protease (CAS RN 123175-82-6) for use in the manufacture of human and analogue insulin products (¹) | 0 % | — | 31.12.2029 |
| 0.7050 | ex 3507 90 90 | 30 | Salicylate 1-monoxygenase (CAS RN 9059-28-3) in aqueous solution with <ul style="list-style-type: none"> — an enzyme concentration of 6,0 U/ml or more, but not more than 7,4 U/ml , — a concentration by weight of sodium azide (CAS RN 26628-22-8) of not more than 0,09 % and — a pH value of 6,5 or more, but not more than 8,5 | 0 % | — | 31.12.2026 |
| 0.4922 | ex 3601 00 00 | 20 | Pyrotechnical mixture in cylindrical shape or granulate form, composed of strontium nitrate or copper nitrate or basic copper nitrate in a matrix of nitroguanidine or guanidine nitrate, also containing a binder and additives, used as a component of airbag inflators (¹) | 0 % | — | 31.12.2026 |
| 0.7318 | ex 3603 50 00 | 10 | Igniters for gas generators with: <ul style="list-style-type: none"> — an overall maximum length of 15,5 mm or more but not more than 29,4 mm, and — a pin length of 6,4 mm or more but not more than 12,6 mm | 0 % | — | 31.12.2028 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.5465 | ex 3801 90 00 | 10 | Expandable graphite (CAS RN 90387-90-9 and CAS RN 12777-87-6) | 0 % | — | 31.12.2026 |
| 0.6759 | *ex 3802 10 00 | 10 | Mixture of activated carbon and polyethylene, in form of powder | 0 % | — | 31.12.2030 |
| 0.7368 | ex 3802 10 00 | 40 | Chemically activated carbon for the absorption and desorption of vapors, in a defined or irregular shape with an effective butane capacity of 5 g butane / 100 ml or more (according to ASTM D 5228) (¹) | 0 % | — | 31.12.2027 |
| 0.2987 | 3805 90 10 | | Pine oil | 1,7 % | — | 31.12.2029 |
| 0.2988 | ex 3808 91 90 | 30 | Preparation containing endospores or spores and protein crystals derived from either: — <i>Bacillus thuringiensis</i> Berliner subsp. <i>aizawai</i> and <i>kurstaki</i> or, — <i>Bacillus thuringiensis</i> subsp. <i>kurstaki</i> or, — <i>Bacillus thuringiensis</i> subsp. <i>israelensis</i> or, — <i>Bacillus thuringiensis</i> subsp. <i>aizawai</i> or, — <i>Bacillus thuringiensis</i> subsp. <i>tenebrionis</i> | 0 % | — | 31.12.2029 |
| 0.2983 | ex 3808 91 90 | 40 | Spinosad (ISO) | 0 % | — | 31.12.2029 |
| 0.5710 | ex 3808 91 90 | 60 | Spinetoram (ISO) (CAS RN 935545-74-7), preparation of two spinosyn components (3'-ethoxy-5,6-dihydro spinosyn J) and (3'-ethoxy- spinosyn L) | 0 % | — | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.4753 | ex 3808 93 90 | 10 | Preparation, in the form of granules, containing by weight: — 38,8 % or more but not more than 41,2 % of Gibberellin A3, or — 9,5 % or more but not more than 10,5 % of Gibberellin A4 and A7 | 0 % | — | 31.12.2029 |
| 0.8727 | ex 3808 93 90 | 70 | Preparation in the form of powder, containing by weight 90 % or more of Gibberellin A4 and Gibberellin A7 combined (CAS RN 8030-53-3) | 0 % | — | 31.12.2029 |
| 0.6532 | ex 3808 94 20 | 30 | Bromochloro-5,5-dimethylimidazolidine-2,4-dione (CAS RN 32718-18-6) containing: — 1,3-Dichloro-5,5-dimethylimidazolidine-2,4-dione (CAS RN 118-52-5), — 1,3-Dibromo-5,5-dimethylimidazolidine-2,4-dione (CAS RN 77-48-5), — 1-Bromo,3-chloro-5,5-dimethylimidazolidine-2,4-dione (CAS RN 16079-88-2), and/or — 1-Chloro,3-bromo-5,5-dimethylimidazolidine-2,4-dione (CAS RN 126-06-7) | 0 % | — | 31.12.2029 |
| 0.8904 | *ex 3808 99 90 | 30 | Milbemycin oxime (CAS RN 129496-10-2), mixture of methyl analogue and ethyl analogue, with a purity by weight of 95 % or more | 0 % | — | 31.12.2030 |
| 0.8830 | ex 3809 91 00 | 20 | Aqueous antimony pentoxide mixture containing by weight: — 48 % or more but not more than 55 % of antimony pentoxide (CAS RN 1314-60-9), — 1 % or more but not more than 5 % of triethanolamine (CAS RN 102-71-6) | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.4510 | ex 3811 19 00 | 10 | <p>Solution of more than 61 % but not more than 63 % by weight of methylcyclopentadienyl manganese tricarbonyl in an aromatic hydrocarbon solvent, containing by weight not more than:</p> <ul style="list-style-type: none"> — 4,9 % of 1,2,4-trimethyl-benzene, — 4,9 % of naphthalene, and — 0,5 % of 1,3,5-trimethyl-benzene | 0 % | — | 31.12.2029 |
| 0.3448 | ex 3811 21 00 | 10 | Salts of dinonylnaphthalenesulphonic acid, in the form of a solution in mineral oils | 0 % | — | 31.12.2029 |
| 0.7223 | ex 3811 21 00 | 11 | <p>Dispersing agent and oxidation inhibitor containing:</p> <ul style="list-style-type: none"> — o-amino polyisobutylenephenol (CAS RN 78330-13-9), — more than 30 % by weight but not more than 50 % by weight of mineral oils, used in the manufacture of blends of additives for lubricating oils (¹) | 0 % | — | 31.12.2029 |
| 0.6904 | *ex 3811 21 00 | 12 | <p>Dispersing agent containing:</p> <ul style="list-style-type: none"> — esters of polyisobutylene succinic acid and pentaerythritol (CAS RN 103650-95-9), — 35 % or more but not more than 55 % by weight of mineral oils, and — with a chlorine content of not more than 0,05 % by weight, used in the manufacture of blends of additives for lubricating oils (¹) | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.6018 | ex 3811 21 00 | 13 | <p>Additives containing:</p> <ul style="list-style-type: none"> — borated magnesium (C16-C24) alkylbenzene sulphonates and — mineral oils, <p>having a total base number (TBN) of more than 250, but not more than 350, for use in the manufacture of lubricating oils (¹)</p> | 0 % | — | 31.12.2027 |
| 0.6906 | *ex 3811 21 00 | 14 | <p>Dispersing agent:</p> <ul style="list-style-type: none"> — containing polyisobutene succinimide derived from reaction products of polyethylenepolyamines with polyisobutylene succinic anhydride (CAS RN 147880-09-9), — containing 35 % or more but not more than 55 % by weight of mineral oils, — with a chlorine content by weight of not more than 0,05 %, — having a total base number of less than 15, <p>used in the manufacture of blends of additives for lubricating oils (¹)</p> | 0 % | — | 31.12.2030 |
| 0.6907 | *ex 3811 21 00 | 16 | <p>Detergent containing:</p> <ul style="list-style-type: none"> — Calcium salt of beta-aminocarbonyl alkylphenol (reaction product Mannich base of alkylphenol) — 40 % or more but not more than 60 % by weight of mineral oils and — having a total base number more than 120 <p>used in the manufacture of blends of additives for lubricating oils (¹)</p> | 0 % | — | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.6430 | ex 3811 21 00 | 19 | Additives containing: — a polyisobutylene succinimide based mixture, and — more than 30 % but not more than 50 % by weight of mineral oils, having a total base number of more than 40, for use in the manufacture of lubricating oils (¹) | 0 % | — | 31.12.2029 |
| 0.3449 | ex 3811 21 00 | 20 | Additives for lubricating oils, based on complex organic molybdenum compounds, in the form of a solution in mineral oil | 0 % | — | 31.12.2029 |
| 0.8583 | ex 3811 21 00 | 21 | Additive containing by weight: — 90 % or more but not more than 97 % of reaction products of butyl-cyclohex-3-enecarboxylate and sulphur (CAS RN 160305-95-3), — 3 % or more but not more than 10 % of mineral oil, for use in the manufacture of blends of additives for lubricating oils (¹) | 0 % | — | 31.12.2028 |
| 0.8196 | ex 3811 21 00 | 22 | Additive consisting essentially of: — Polyisobutetyl succinic anhydride (CAS RN 192662-34-3) reaction product with N, N-diethylaminoethanol (CAS RN 100-37-8), — 25 % or more by weight, but not more than 40 % by weight of mineral oil, used in the manufacture of blends of additives for lubricating oils (¹) | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.8197 | ex 3811 21 00 | 24 | <p>Additive consisting essentially of:</p> <ul style="list-style-type: none"> — Polyisobutylene succinic anhydride reaction product with polyethylenepolyamines, borated (CAS RN 134758-95-5), with a chlorine content by weight of 0,05 % or more but not more than 0,25 % and a total base number (TBN) of more than 20, — 45 % and more by weight and no more than 55 % by weight of mineral oil, used in the manufacture of blends of additives for lubricating oils (¹) | 0 % | — | 31.12.2026 |
| 0.6012 | ex 3811 21 00 | 25 | <p>Additives containing:</p> <ul style="list-style-type: none"> — a (C8-18) alkyl polymethacrylate copolymer with N-[3-(dimethylamino)propyl] methacrylamide, of an average molecular weight (Mw) of more than 10 000 but not more than 20 000, and — more than 15 %, but not more than 30 % by weight of mineral oils, for use in the manufacture of lubricating oils (¹) | 0 % | — | 31.12.2029 |
| 0.8198 | ex 3811 21 00 | 26 | <p>Additive consisting essentially of:</p> <ul style="list-style-type: none"> — Phosphorodithioic acid, mixed O,O-bis (1,3-dimethylbutyl and isopropyl) esters, zinc salts (CAS RN 84605-29-8), — 7 % or more by weight but not more than 12 % by weight of mineral oil, used in the manufacture of blends of additives for lubricating oils (¹) | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.6022 | ex 3811 21 00 | 27 | <p>Additives containing:</p> <ul style="list-style-type: none"> — 10 % or more by weight of an ethylene-propylene copolymer chemically modified by succinic anhydride groups reacted with 3-nitroaniline, and — mineral oils, <p>for use in the manufacture of lubricating oils (¹)</p> | 0 % | — | 31.12.2029 |
| 0.8199 | ex 3811 21 00 | 28 | <p>Additive consisting essentially of:</p> <ul style="list-style-type: none"> — Zinc bis(O,O-bis(2-ethylhexyl)) bis (dithiophosphate) (CAS RN 4259-15-8); — triphenyl phosphite (CAS RN 101-02-0) more than 0,5 % by weight but not more than 6 % by weight, — O,O,O-triphenyl phosphorothioate (CAS RN 597-82-0) more than 0,5 % by weight but not more than 6 % by weight, and not more than 7,5 % by weight of the combination of triphenylphosphorus compounds — 10 % or more by weight but not more than 20 % by weight of mineral oils, <p>used in the manufacture of blends of additives for lubricating oils (¹)</p> | 0 % | — | 31.12.2026 |
| 0.5727 | ex 3811 21 00 | 29 | <p>Additive containing by weight:</p> <ul style="list-style-type: none"> — 25 % or more but not more than 40 % of calcium C16-24 alkylbenzenesulphonates (CAS RN 70024-69-0), — 30 % or more but not more than 65 % of mineral oils, <p>for use in the manufacture of blends of additives for lubricating oils (¹)</p> | 0 % | — | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.5717 | ex 3811 21 00 | 30 | Additives for lubricating oils, containing mineral oils, consisting of calcium salts of reaction products of polyisobutylene substituted phenol with salicylic acid and formaldehyde, used as a concentrated additive for the manufacture of engine oils through a blending process | 0 % | — | 31.12.2027 |
| 0.8201 | ex 3811 21 00 | 32 | Additive consisting essentially of: — Zinc O,O',O',O'-tetrakis (1,3-dimethylbutyl) bis(phosphorodithioate) (CAS RN 2215-35-2), — 4 % or more by weight but not more than 12 % by weight of mineral oil, used in the manufacture of blends of additives for lubricating oils (¹) | 0 % | — | 31.12.2026 |
| 0.6013 | ex 3811 21 00 | 33 | Additives containing: — calcium salts of heptylphenol reaction products with formaldehyde (CAS RN 84605-23-2), and — mineral oils, having a total base number (TBN) of more than 40 but not more than 100, for use in the manufacture of lubricating oils or overbased detergents for use in lubricating oils (¹) | 0 % | — | 31.12.2029 |
| 0.6905 | *ex 3811 21 00 | 34 | Detergent containing: — benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts (CAS RN 722503-68-6), — more than 30 % but not more than 60 % by weight of mineral oils, and, — having a total base number of more than 310 but not more than 340, used in the manufacture of blends of additives for lubricating oils (¹) | 0 % | — | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.6016 | ex 3811 21 00 | 37 | Additives containing: — a styrene-maleic anhydride copolymer esterified with C4-C20 alcohols, modified by aminopropylmorpholine, and — more than 50 % but not more than 75 % by weight of mineral oils, for use in the manufacture of lubricating oils (¹) | 0 % | — | 31.12.2029 |
| 0.6435 | ex 3811 21 00 | 48 | Additives containing: — overbased magnesium (C20-C24) alkylbenzenesulphonates (CAS RN 231297-75-9) and — by weight more than 25 % but not more than 50 % of mineral oils, — having a total base number of more than 350, but not more than 450, for use in the manufacture of lubricating oils or for use in the manufacture of blends of additives for lubricating oils (¹) | 0 % | — | 31.12.2029 |
| 0.6437 | ex 3811 21 00 | 53 | Additives containing: — overbased calcium petroleum sulphonates (CAS RN 68783-96-0) with a sulphonate content by weight of 15 % or more, but not more than 30 % and — by weight more than 40 % but not more than 60 % of mineral oils, having a total base number of 280 or more but not more than 420, for use in the manufacture of lubricating oils (¹) | 0 % | — | 31.12.2029 |
| 0.6434 | ex 3811 21 00 | 55 | Additives containing: — low base number calcium polypropylbenzenesulphonate (CAS RN 75975-85-8) and — by weight more than 40 % but not more than 60 % of mineral oils, having a total base number of more than 10 but not more than 25, for use in the manufacture of lubricating oils (¹) | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.5724 | ex 3811 21 00 | 60 | Additives for lubricating oils, containing mineral oils, — based on calcium polypropylenyl substituted benzenesulphonate (CAS RN 75975-85-8) with a content by weight of 25 % or more but not more than 35 %, — with a total base number (TBN) of 280 or more but not more than 320, used as a concentrated additive for the manufacture of engine oils through a blending process | 0 % | — | 31.12.2027 |
| 0.6431 | ex 3811 21 00 | 63 | Additives containing: — an overbased mixture of calcium petroleum sulphonates (CAS RN 61789-86-4) and synthetic calcium alkylbenzenesulphonates (CAS RN 68584-23-6 and CAS RN 70024-69-0) with a total sulphonate content by weight of 15 % or more, but not more than 25 % and — by weight more than 40 % but not more than 60 % of mineral oils, having a total base number of 280 or more but not more than 320, for use in the manufacture of lubricating oils (¹) | 0 % | — | 31.12.2029 |
| 0.6429 | ex 3811 21 00 | 65 | Additives containing: — a polyisobutylene succinimide based mixture (CAS RN 160610-76-4), and — more than 35 % but not more than 50 % by weight of mineral oils, having a sulphur content of more than 0,7 % but not more than 1,3 % by weight, having a total base number of more than 8, for use in the manufacture of lubricating oils (¹) | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.5711 | ex 3811 21 00 | 70 | <p>Additives for lubricating oils,</p> <ul style="list-style-type: none"> — containing polyisobutylene succinimide derived from reaction products of polyethylenepolyamines with polyisobutylene succinic anhydride (CAS RN 84605-20-9), — containing mineral oils, — with a chlorine content by weight of 0,05 % or more but not more than 0,25 %, — with a total base number (TBN) of more than 20, <p>used as a concentrated additive for the manufacture of engine oils through a blending process</p> | 0 % | — | 31.12.2027 |
| 0.6017 | ex 3811 21 00 | 73 | <p>Additives containing:</p> <ul style="list-style-type: none"> — borated succinimide compounds (CAS RN 134758-95-5), — mineral oils, and — having a total base number (TBN) greater than 40, <p>for use in the manufacture of additive mixtures for lubricating oils (¹)</p> | 0 % | — | 31.12.2029 |
| 0.6671 | ex 3811 21 00 | 75 | <p>Additives containing:</p> <ul style="list-style-type: none"> — Calcium (C10-C14) dialkylbenzenesulfonates, — more than 40 %, but not more than 60 % by weight of mineral oils, <p>with a total base number of not more than 10, for use in the manufacture of blends of additives for lubricating oils (¹)</p> | 0 % | — | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.6669 | ex 3811 21 00 | 77 | Antifoam additives consisting of: — a copolymer of 2-ethylhexyl acrylate and ethyl acrylate, and — more than 50 % but not more than 80 % by weight of mineral oils, for use in the manufacture of additive blends for lubricating oils (¹) | 0 % | — | 31.12.2027 |
| 0.6666 | ex 3811 21 00 | 80 | Additives containing: — polyisobutylene aromatic polyamine succinimide, — more than 40 % but not more than 60 % by weight of mineral oils, with a nitrogen content of more than 0,6 % but not more than 0,9 % by weight, for use in the manufacture of additive blends for lubricating oils (¹) | 0 % | — | 31.12.2027 |
| 0.6498 | ex 3811 21 00 | 83 | Additives containing: — polyisobutene succinimide derived from reaction of polyethylenopolyamines with polyisobutetyl succinic anhydride (CAS RN 84605-20-9), — more than 31,9 % but not more than 43,3 % by weight of mineral oils, — not more than 0,05 % by weight chlorine, and — having a total base number (TBN) greater than 20, for use in the manufacture of additives blends for lubricating oils (¹) | 0 % | — | 31.12.2029 |
| 0.5718 | ex 3811 21 00 | 85 | Additives: — containing more than 20 % but not more than 45 % by weight of mineral oils, — based on a mixture of branched dodecylphenol sulfide calcium salts, whether or not carbonated, for use in the manufacture of blends of additives (¹) | 0 % | — | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.5721 | ex 3811 29 00 | 20 | Additives for lubricating oils, consisting of reaction products of bis(2-methylpentan-2-yl) dithiophosphoric acid with propylene oxide, phosphorus oxide, and amines with C12-14 alkyl chains, used as a concentrated additive for the manufacture of lubricating oils | 0 % | — | 31.12.2027 |
| 0.8655 | ex 3811 29 00 | 23 | Additive for lubricating oils consisting of molybdenum, bis(dibutylcarbamodithioato) di- μ -oxodioxodi-, sulfurized (CAS RN 68412-26-0) | 0 % | — | 31.12.2028 |
| 0.5723 | ex 3811 29 00 | 30 | Additives for lubricating oils, consisting of reaction products of butyl-cyclohex-3-enecarboxylate, sulphur and triphenyl phosphite (CAS RN 93925-37-2), used as a concentrated additive for the manufacture of engine oils through a blending process | 0 % | — | 31.12.2027 |
| 0.5719 | ex 3811 29 00 | 33 | Additives for lubricating oils, consisting of a mixture of N,N-dialkyl -2-hydroxyacetamides with alkyl chain lengths between 12 and 18 carbon atoms (CAS RN 866259-61-2), used in the manufacture of blends of additives for lubricating oils (¹) | 0 % | — | 31.12.2027 |
| 0.6432 | ex 3811 29 00 | 38 | Additives consisting of the C12-C14-tert-alkylamine salts of the esters of C14-C18 saturated and C18 unsaturated alcohols with phosphorus pentoxide (CAS RN 1471315-74-8), for use in the manufacture of blends of additives for lubricating oils or greases (¹) | 0 % | — | 31.12.2029 |
| 0.5728 | ex 3811 29 00 | 40 | Additives for lubricating oils, consisting of reaction products of 2-methyl-prop-1-ene with sulphur monochloride and sodium sulphide (CAS RN 68511-50-2), with a chlorine content by weight of 0,01 % or more but not more than 0,5 %, used as a concentrated additive for the manufacture of lubricating oils | 0 % | — | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.6433 | ex 3811 29 00 | 43 | Reaction products of C14-C18 (branched and linear) and C18 (unsaturated) fatty acids with tetraethylenepentamine (linear, branched, cyclic) (CAS RN 68784-17-8), for use in the manufacture of lubricating oils (¹) | 0 % | — | 31.12.2029 |
| 0.6436 | ex 3811 29 00 | 45 | Additives consisting of a mixture of (C7-C9) dialkyl adipates, in which diisooctyl adipate (CAS RN 1330-86-5) is more than 85 % by weight of the mixture, for use in the manufacture of lubricating oils (¹) | 0 % | — | 31.12.2029 |
| 0.6020 | ex 3811 29 00 | 48 | Mixed C12-C20-alkyl and C14-C18-unsaturated alkyl derivates of phosphonic acid (CAS RN 93925-25-8), containing by weight more than 80 % of oleyl, palmityl and stearyl groups, for use in the manufacture of lubricating oils (¹) | 0 % | — | 31.12.2029 |
| 0.7205 | ex 3811 29 00 | 75 | Oxidation inhibitor mainly containing a mixture of isomers of 1-(tert-dodecylthio) propan-2-ol (CAS RN 67124-09-8), used in the manufacture of blends of additives for lubricating oils (¹) | 0 % | — | 31.12.2029 |
| 0.6023 | ex 3811 29 00 | 85 | Additives consisting of a mixture of 3-((C9-11)-isoalkyloxy)tetrahydrothiophene 1,1-dioxide, C10-rich (CAS RN 398141-87-2), for use in the manufacture of lubricating oils (¹) | 0 % | — | 31.12.2029 |
| 0.5565 | ex 3811 90 00 | 40 | Solution of a quaternary ammonium salt based on polyisobutylene succinimide, containing by weight 10 % or more but not more than 29,9 % of 2-ethylhexanol | 0 % | — | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.7204 | ex 3811 90 00 | 50 | Corrosion inhibitor containing: — polyisobutylene succinic acid and — more than 5 % and not more than 20 % by weight of mineral oils for use in the manufacture of blends of additives for fuels (¹) | 0 % | — | 31.12.2026 |
| 0.5147 | ex 3812 10 00 | 10 | Rubber accelerator based on diphenyl guanidine granules (CAS RN 102-06-7) | 0 % | — | 31.12.2026 |
| 0.8962 | *ex 3812 10 00 | 30 | Vulcanization accelerator, consisting by weight of: — 98 % or more of N-tert-butyl bis(2-benzothiazolesulfen) amide (CAS RN 3741-80-8) — not more than 2 % of white mineral oil (CAS RN 8042-47-5) | 0 % | — | 31.12.2030 |
| 0.6045 | ex 3812 20 90 | 10 | Plasticiser, containing: — bis(2-ethylhexyl)-1,4-benzene dicarboxylate (CAS RN 6422-86-2) — more than 10 % but not more than 60 % by weight of dibutylterephthalate (CAS RN 1962-75-0) | 0 % | — | 31.12.2029 |
| 0.8872 | ex 3812 39 90 | 23 | UV stabilizer, containing by weight: — more than 97 % but not more than 99,8 % of bis(2,4-dicumylphenyl)pentaerythritol diphosphite (CAS RN 154862-43-8) and — more than 0,2 % but not more than 2 % of triisopropanolamine (CAS RN 122-20-3) | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.6055 | ex 3812 39 90 | 25 | <p>UV photo stabiliser containing:</p> <ul style="list-style-type: none"> — α-[3-[3-(2H-Benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-ω-hydroxypoly(oxy-1,2-ethanediyl) (CAS RN 104810-48-2); — α-[3-[3-(2H-Benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-ω-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]poly(oxy-1,2-ethanediyl) (CAS RN 104810-47-1); — polyethylene glycol of a weight average molecular weight (Mw) of 300 (CAS RN 25322-68-3) — bis (1,2,2,6,6-pentamethyl-4-piperidyl)sebacate (CAS RN 41556-26-7), and — methyl-1,2,2,6,6-pentamethyl-4- piperidyl sebacate (CAS RN 82919-37-7) | 0 % | — | 31.12.2029 |
| 0.8806 | ex 3812 39 90 | 28 | <p>UV stabilizer based on a mixture of</p> <ul style="list-style-type: none"> — reaction mass of Poly(oxy-1,2-ethanediyl), α-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-ω-hydroxy- and Poly(oxy-1,2-ethanediyl), α-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-ω-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1- oxopropoxy] (EC number 400-830-7) with a purity by weight of 60 % or more, but not more than 80 %, and — reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (CAS RN 1065336-91-5) with a purity by weight of 25 % or more, but not more than 40 % | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8807 | ex 3812 39 90 | 33 | <p>UV stabilizer based on:</p> <ul style="list-style-type: none"> — a mixture of branched and linear C7-C9 alkyl 3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]propionates (CAS RN 127519-17-9) with a content by weight of 40 % or more, but not more than 60 %, and — a mixture of: bis(2,2,6,6-tetramethyl-1-octyloxypiperidin-4-yl)-1,10-decanedioate and 1,8-bis [(2,2,6,6-tetramethyl-4-((2,2,6,6-tetramethyl-1-octyloxypiperidin-4-yl)-decan-1,10-diyl)piperidin-1-yl)oxy]octane (CAS RN 129757-67-1) with a content by weight of 40 % or more, but not more than 60 % | 0 % | — | 31.12.2029 |
| 0.6054 | ex 3812 39 90 | 35 | <p>Mixture containing by weight:</p> <ul style="list-style-type: none"> — 25 % or more but not more than 55 % of a mixture of C15-18 tetramethylpiperidinyl esters (CAS RN 86403-32-9) — not more than 20 % of other organic compounds — on a carrier of polypropylene (CAS RN 9003-07-0) or amorphous silica (CAS RN 7631-86-9 or 112926-00-8) | 0 % | — | 31.12.2029 |
| 0.8864 | ex 3812 39 90 | 38 | <p>UV stabiliser containing by weight:</p> <ul style="list-style-type: none"> — 75 % or more but not more than 95 % of the reaction product of 2-(4,6-bis (2,4-dimethylphenyl)-1,3,5-triazin-2-yl)-5-hydroxyphenol with ((C10-16, rich in C12-13 alkyloxy) methyl) oxirane — 5 % or more but not more than 25 % of 1-methoxy-2-propanol (CAS RN 107-98-2) | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.4861 | ex 3812 39 90 | 40 | <p>Mixture of:</p> <ul style="list-style-type: none"> — 80 % (± 10 %) by weight of 2-ethylhexyl 10-ethyl-4,4-dimethyl-7-oxo-8-oxa-3,5-dithia-4-stannatetradecanoate (CAS RN 57583-35-4), and — 20 % (± 10 %) by weight of 2-ethylhexyl 10-ethyl-4-[[2-[(2-ethylhexyl)oxy]-2-oxoethyl]thio]-4-methyl-7-oxo-8-oxa-3,5-dithia-4-stannatetradecanoate (CAS RN 57583-34-3) | 0 % | — | 31.12.2029 |
| 0.8870 | ex 3812 39 90 | 43 | <p>Reaction mass containing by weight:</p> <ul style="list-style-type: none"> — more than 45 % but not more than 49 % of Octyl 3-[3-tert-butyl-4-hydroxy-5-(5-chloro-2H-benzotriazol-2-yl)phenyl]propionate (CAS RN 83044-89-7), and — more than 49 % but not more than 53 % of 2-Ethylhexyl 3-[3-tert-butyl-4-hydroxy-5-(5-chloro-2H-benzotriazol-2-yl) phenyl]propionate (CAS RN 83044-90-0) | 0 % | — | 31.12.2029 |
| 0.8273 | ex 3812 39 90 | 45 | 2-Aminoethanol reaction products with cyclohexane and peroxidized N-butyl-2,2,6,6-tetramethyl-4-piperidinamine-2,4,6-trichloro-1,3,5-triazine reaction products (CAS RN 191743-75-6) with a purity by weight of 99 % or more | 0 % | — | 31.12.2026 |
| 0.3444 | ex 3812 39 90 | 48 | <p>UV stabilizer (CAS RN 129757-67-1), reaction mass containing by weight 97 % or more of:</p> <ul style="list-style-type: none"> — bis[2,2,6,6-tetramethyl-1-(octyloxy)piperidin-4-yl] decanedioate, and — 1,1'-bis[2,2,6,6-tetramethyl-1-(octyloxy)piperidin-4-yl] 10,10'-{octane-1,8-diylbis[oxy (2,2,6,6-tetramethylpiperidine-1,4-diyl)]} didecanedioate | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8366 | ex 3812 39 90 | 53 | Light stabilizer, containing by weight more than 90 % of reaction products of stearate methyl ester with 1-(2-hydroxy-2-methylpropoxy)-2,2,6,6-tetramethyl-4-piperidinol (CAS RN 300711-92-6) | 0 % | — | 31.12.2027 |
| 0.5477 | ex 3812 39 90 | 55 | UV-stabilizer, containing: <ul style="list-style-type: none"> — 2-(4,6-bis(2,4-dimethylphenyl)-1,3,5-triazin-2-yl)-5-(octyloxy)-phenol (CAS RN 2725-22-6) and — either N,N'-bis(1,2,2,6,6-pentamethyl-4-piperidinyl)-1,6-hexanediamine, polymer with 2,4- dichloro-6-(4-morpholinyl)-1,3,5-triazine (CAS RN 193098-40-7) or — N,N'-bis(2,2,6,6-tetramethyl-4-piperidinyl)-1,6-hexanediamine, polymer with 2,4- dichloro-6-(4-morpholinyl)-1,3,5-triazine (CAS RN 82451-48-7) | 0 % | — | 31.12.2026 |
| 0.5483 | ex 3812 39 90 | 65 | Stabiliser for plastic material containing: <ul style="list-style-type: none"> — 2-ethylhexyl 10-ethyl-4,4-dimethyl-7-oxo-8-oxa-3,5-dithia-4-stannatetradecanoate (CAS RN 57583-35-4), — 2-ethylhexyl 10-ethyl-4-[[2-[(2-ethylhexyl)oxy]-2-oxoethyl]thio]-4-methyl-7-oxo-8-oxa-3,5-dithia-4-stannatetradecanoate (CAS RN 57583-34-3), and — 2-ethylhexyl mercaptoacetate (CAS RN 7659-86-1) | 0 % | — | 31.12.2026 |
| 0.8533 | ex 3812 39 90 | 75 | UV stabilizer containing a mixture of: <ul style="list-style-type: none"> — branched and linear C7 to C9 alkyl esters of [3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxy]-1-phenylpropanoic acid (CAS RN 127519-17-9) with a content by weight of 85 % or more, and — 2-Methoxy-1-methylethyl acetate (CAS RN 108-65-6) with a content by weight of not more than 8 % | 0 % | — | 31.12.2028 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.5822 | ex 3812 39 90 | 80 | UV-stabilizer, consisting of: — a hindered amine: N,N'-bis(1,2,2,6,6-pentamethyl-4-piperidinyl)-1,6-hexanediamine, polymer with 2,4-dichloro-6-(4-morpholinyl)-1,3,5-triazine (CAS RN 193098-40-7) and — either an o-hydroxyphenyl triazine UV light absorber or — a chemically modified phenolic compound | 0 % | — | 31.12.2027 |
| 0.3731 | ex 3814 00 90 | 40 | Azeotrope mixtures containing isomers of nonafluorobutyl methyl ether and/or nonafluorobutyl ethyl ether | 0 % | — | 31.12.2029 |
| 0.2800 | ex 3815 12 00 | 10 | Catalyst, in the form of granules or rings of a diameter of 3 mm or more but not more than 10 mm, consisting of silver on an aluminium oxide support and containing by weight 8 % or more but not more than 40 % of silver | 0 % | — | 31.12.2029 |
| 0.5508 | ex 3815 19 90 | 10 | Catalysts consisting of chromium trioxide, dichromium trioxide or organometallic compounds of chromium, fixed on a silicon dioxide support with a pore volume of 2 cm ³ /g or more (as determined by the nitrogen absorption method) | 0 % | — | 31.12.2026 |
| 0.3435 | ex 3815 19 90 | 30 | Catalyst containing titanium tetrachloride supported on magnesium dichloride, for use in the manufacture of polypropylene (¹) | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8745 | ex 3815 19 90 | 55 | <p>Components for a catalyst system, imported as single components or as set, made up of at least one of the following preparations:</p> <ul style="list-style-type: none"> — ceramic material (CAS RN 66402-68-4), — molybdenum oxide and nickel oxide supported on aluminium oxide, — molybdenum oxide, nickel oxide and aluminium phosphate supported on aluminium oxide, — molybdenum oxide, nickel oxide, aluminium phosphate, silica, and molybdenum supported on aluminium oxide, <p>for use against organic and inorganic impurities in kerosene production (¹)</p> | 0 % | — | 31.12.2029 |
| 0.2791 | ex 3815 19 90 | 70 | Catalyst consisting of organo-metallic compounds of aluminium and zirconium, fixed on a support of silicon dioxide | 0 % | — | 31.12.2029 |
| 0.2790 | ex 3815 19 90 | 75 | Catalyst consisting of organo-metallic compounds of aluminium and chromium, fixed on a support of silicon dioxide | 0 % | — | 31.12.2029 |
| 0.2793 | ex 3815 19 90 | 80 | Catalyst consisting of organo-metallic compounds of magnesium and titanium, fixed on a support of silicon dioxide, in the form of a suspension in mineral oil | 0 % | — | 31.12.2029 |
| 0.2788 | ex 3815 19 90 | 85 | Catalyst consisting of organo-metallic compounds of aluminium, magnesium and titanium, fixed on a support of silicon dioxide, in the form of powder | 0 % | — | 31.12.2029 |
| 0.3899 | ex 3815 19 90 | 86 | Catalyst containing titanium tetrachloride supported on magnesium dichloride, for use in the manufacture of polyolefins (¹) | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.4005 | ex 3815 90 90 | 16 | Initiator based on dimethylaminopropyl urea | 0 % | — | 31.12.2027 |
| 0.5062 | *ex 3815 90 90 | 30 | Catalyst, consisting of a suspension in mineral oil of: — tetrahydrofuran complexes of magnesium chloride and titanium(III) chloride, and — silicon dioxide, — containing 6,6 % (\pm 0,6 %) by weight of magnesium, and — containing 2,3 % (\pm 0,2 %) by weight of titanium | 0 % | — | 31.12.2026 |
| 0.7998 | *ex 3815 90 90 | 38 | Photoinitiator, containing by weight: — 80 % or more of polyethylene glycol di[β -4-[4-(2-dimethylamino-2-benzyl) butanoylphenyl]piperazine]propionate (CAS RN 886463-10-1), — not more than 17 % of polyethylene glycol [β -4-[4-(2-dimethylamino-2-benzyl) butanoylphenyl]piperazine]propionate | 0 % | — | 31.12.2030 |
| 0.7243 | ex 3815 90 90 | 43 | Catalyst in powder form consisting by weight of — 92,50 % (\pm 2) % titanium dioxide (CAS RN 13463-67-7), — 5 % (\pm 1) % silicon dioxide (CAS RN 112926-00-8), and — 2,5 % (\pm 1,5) % sulphur trioxide (CAS RN 7446-11-9) | 0 % | — | 31.12.2027 |
| 0.7999 | *ex 3815 90 90 | 48 | Photoinitiator containing by weight: — 88 % or more of α -(2-benzoylbenzoyl)- ω -[(2-benzoylbenzoyl)oxy]-poly (oxy-1,2-ethanediyl) (CAS RN 1246194-73-9), — not more than 12 % of α -(2-benzoylbenzoyl)- ω -hydroxy-poly(oxy-1,2-ethanediyl) (CAS RN 1648797-60-7) | 0 % | — | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.3433 | ex 3815 90 90 | 50 | Catalyst containing titanium trichloride, in the form of a suspension in hexane or heptane containing by weight, in the hexane- or heptane-free material, 9 % or more but not more than 30 % of titanium | 0 % | — | 31.12.2029 |
| 0.8840 | ex 3815 90 90 | 55 | Catalytic Additives for fluid catalytic cracking (FCC), not containing Y type zeolite (CAS RN 308079-79-0), and not being a FCC (Fluid Catalytic Cracking) base catalyst, in the form of powder, consisting of a mixture of one or more of the following active substances: — calcium carbonate (CAS RN 471-34-1), — copper oxide (CAS RN 1217-38-0), — iron oxide (CAS RN 1309-37-1), — aluminium magnesium vanadium oxide (CAS RN 70621-8-0), — vanadium pentoxide (CAS RN 1314-62-1), — aluminium phosphate (CAS RN 7784-30-7), — cerium oxide (CAS RN 1306-38-3), — ZSM-5 type zeolite (CAS RN 308081-08-5), and one or more of the following inert substances: — magnesium oxide (CAS RN 1309-48-8), — aluminium oxide (CAS RN 1344-28-1), — kaolin (CAS RN 1332-58-7) | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.8940 | *ex 3815 90 90 | 58 | 1,1'-Bis(4-triethylsilylphenyl)methylene(cyclopentadienyl)(2,7-di-tert-butyl-9-fluorenyl)dimethylhafnium (CAS RN 264926-41-2) in the form of a hexane (CAS RN 110-54-3) solution, containing by weight 2,0 % or more but not more than 2,5 % of 1,1'-bis(4-triethylsilylphenyl)methylene(cyclopentadienyl)(2,7-di-tert-butyl-9-fluorenyl)dimethylhafnium | 0 % | — | 31.12.2030 |
| 0.2783 | *ex 3815 90 90 | 80 | Catalyst consisting predominantly of dinonylnaphthalenedisulphonic acid in the form of a solution in isobutanol | 0 % | — | 31.12.2026 |
| 0.3430 | ex 3815 90 90 | 81 | Catalyst, containing by weight 69 % or more but not more than 79 % of (2-hydroxy-1-methylethyl)trimethylammonium 2-ethylhexanoate (CAS RN 62314-22-1) | 0 % | — | 31.12.2029 |
| 0.2782 | ex 3815 90 90 | 85 | Catalyst based on aluminosilicate (zeolite), for the alkylation of aromatic hydrocarbons, for the transalkylation of alkylaromatic hydrocarbons or for the oligomerization of olefins (¹) | 0 % | — | 31.12.2027 |
| 0.3732 | ex 3815 90 90 | 88 | Catalyst, consisting of titanium tetrachloride and magnesium chloride, containing by weight on an oil- and hexane-free basis: — 4 % or more but not more than 10 % of titanium and — 10 % or more but not more than 20 % magnesium | 0 % | — | 31.12.2029 |
| 0.3733 | ex 3815 90 90 | 89 | <i>Rhodococcus rhodocrous</i> J1 bacteria, containing enzymes, suspended in a polyacrylamide gel or in water, for use as a catalyst in the production of acrylamide by the hydration of acrylonitrile (¹) | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|--------------------------------|----------|--|-------------------------|--------------------|-------------------------------------|
| 0.4408 | *ex 3817 00 50 | 10 | Mixture of alkylbenzenes (C14-26) containing by weight: — 35 % or more but not more than 60 % of eicosylbenzene, — 25 % or more but not more than 50 % of docosylbenzene, — 5 % or more but not more than 25 % of tetracosylbenzene | 0 % | — | 31.12.2026 |
| 0.3427 | ex 3817 00 80 | 10 | Mixture of alkylnaphthalenes, containing by weight: — 88 % or more but not more than 98 % of hexadecylnaphthalene — 2 % or more but not more than 12 % of dihexadecylnaphthalene | 0 % | — | 31.12.2029 |
| 0.4581 | ex 3817 00 80 | 20 | Mixture of branched alkyl benzenes mainly containing dodecyl benzenes | 0 % | — | 31.12.2029 |
| 0.5479 | ex 3817 00 80 | 30 | Mixed alkylnaphthalenes, modified with aliphatic chains, of a chain-length varying from 12 to 56 carbon atoms | 0 % | — | 31.12.2026 |
| 0.6038 | ex 3823 19 30 ex 3823 19 30 | 20 30 | Palm fatty acid distillate, whether or not hydrogenated, with free fatty acid content 80 % or more for use in the manufacture of: — industrial monocarboxylic fatty acids of heading 3823, — stearic acid of heading 3823, — stearic acid of heading 2915, — palmitic acid of heading 2915, or — animal feed preparations of heading 2309 (¹) | 0 % | — | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|--------------------------------|----------|--|-------------------------|--------------------|-------------------------------------|
| 0.6037 | ex 3823 19 90 ex 3823 19 90 | 20 30 | Palm acid oils from refining for use in the manufacture of: — industrial monocarboxylic fatty acids of heading 3823, — stearic acid of heading 3823, — stearic acid of heading 2915, — palmitic acid of heading 2915, or — animal feed preparations of heading 2309 (¹) | 0 % | — | 31.12.2027 |
| 0.8365 | *ex 3824 99 92 | 22 | Solution containing: — 30 % or more but not more than 40 % by weight of lithium hexafluorophosphate (CAS RN 21324-40-3), and — 60 % or more but not more than 70 % by weight of ethyl methyl carbonate (CAS RN 623-53-0), or dimethyl carbonate (CAS RN 616-38-6) | 3,2 % | — | 31.12.2026 |
| 0.6810 | *ex 3824 99 92 | 23 | Butylphosphato complexes of titanium(IV) (CAS RN 109037-78-7), dissolved in ethanol and propan-2-ol | 0 % | — | 31.12.2030 |
| 0.8835 | ex 3824 99 92 | 25 | Mixture containing by weight: — 55 % or more but not more than 65 % of (2S,3S,4S,5R,6R)-2-(((2R,3R,5S,6R)-4-(((2R,3S,4S,5R,6R)-3-acetoxy-4,5-bis(benzyloxy)-6-((benzyloxy)methyl)tetrahydro-2H-pyran-2-yl)oxy)-3,5-bis(benzyloxy)-6-(4-methoxy-4-oxobutoxy)tetrahydro-2H-pyran-2-yl)methoxy)-6-(((2S,3S,4S,5R,6R)-3-acetoxy-4,5-bis(benzyloxy)-6-((benzyloxy)methyl)tetrahydro-2H-pyran-2-yl)oxy)methyl)tetrahydro-2H-pyran-3,4,5-triyl tribenzoate (CAS RN 1233475-58-5), — 35 % or more but not more than 45 % of toluene (CAS RN 108-88-3) | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.8921 | *ex 3824 99 92 | 27 | Methyl 5-(dimethylamino)-2-methyl-5-oxopentanoate (CAS RN 1174627-68-9) with a purity by weight of 75 % or more | 0 % | — | 31.12.2030 |
| 0.8886 | ex 3824 99 92 | 28 | Preparation containing by weight: <ul style="list-style-type: none"> — 30 % or more, but not more than 60 % of 3a,4,4a,5,8a,9,9a-octahydro-4,9:5,8-dimethano-1H-benz[f]indene (CAS RN 7158-25-0), — 10 % or more, but not more than 50 % of 3a,4,7,7a-tetrahydro-4,7-methanoindene (CAS RN 77-73-6), and — whether or not 10 % or more, but not more than 40 % of petroleum hydrocarbon resin (CAS RN 68132-00-3) | 0 % | — | 31.12.2029 |
| 0.4909 | *ex 3824 99 92 | 29 | Preparation containing by weight: <ul style="list-style-type: none"> — 85 % or more but not more than 99 % of polyethylene glycol ether of butyl 2-cyano 3-(4-hydroxy-3-methoxyphenyl) acrylate, and — 1 % or more but not more than 15 % of polyoxyethylene (20) sorbitan trioleate | 0 % | — | 31.12.2030 |
| 0.8955 | *ex 3824 99 92 | 30 | Mixture of C10-C14 tert-alkyl amines (EC number: 701-175-2) | 0 % | — | 31.12.2030 |
| 0.3083 | ex 3824 99 92 | 33 | Anti-corrosion preparations consisting of salts of dinonylnaphthalenesulphonic acid, either: <ul style="list-style-type: none"> — on a support of mineral wax, whether or not modified chemically, or — in the form of a solution in an organic solvent | 0 % | — | 31.12.2029 |
| | ex 3824 99 93 | 40 | | | | |
| | ex 3824 99 96 | 40 | | | | |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.4523 | ex 3824 99 92 | 37 | Mixture of acetates of 3-butene-1,2-diol with a content by weight of 65 % or more of 3-butene-1,2-diol diacetate (CAS RN 18085-02-4) | 0 % | — | 31.12.2029 |
| 0.6779 | *ex 3824 99 92 | 40 | Solution of 2-chloro-5-(chloromethyl)-pyridine (CAS RN 70258-18-3) in organic diluent | 0 % | — | 31.12.2030 |
| 0.8706 | ex 3824 99 92 | 44 | Mixture, containing by weight: — 90 % or more but not more than 95 % of cresol ethoxylate (CAS RN 37281-57-5), and — 5 % or more but not more than 10 % of xlenol ethoxylate (CAS RN 61723-82-8) | 0 % | — | 31.12.2029 |
| 0.8887 | ex 3824 99 92 | 48 | Preparation containing by weight: — 80 % or more, but not more than 90 % of 3a,4,7,7a-tetrahydro-4,7-methanoindene (CAS RN 77-73-6), and — not more than 10 % of 3a,4,4a,5,8,8a,9,9a-octahydro-1H-4,9:5,8-dimethanocyclopenta[b]naphthalene (CAS RN 7158-25-0), and — 0,5 % or more, but not more than 3 % of 2,6-di-tert-butyl-p-cresol (CAS RN 128-37-0) | 0 % | — | 31.12.2029 |
| 0.4279 | ex 3824 99 92 | 49 | Preparation based on 2,5,8,11-tetramethyl-6-dodecyn-5,8-diol ethoxylate (CAS RN 169117-72-0) | 0 % | — | 31.12.2027 |
| 0.3065 | ex 3824 99 92 | 51 | Mixture containing by weight 40 % or more but not more than 50 % of 2-hydroxyethyl methacrylate and 40 % or more but not more than 50 % of glycerol ester of boric acid | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.7742 | *ex 3824 99 92 | 52 | <p>Electrolyte containing:</p> <ul style="list-style-type: none"> — 5 % or more but not more than 20 % lithium hexafluorophosphate (CAS RN 21324-40-3) or lithium tetrafluoroborate (CAS RN 14283-07-9), — 60 % or more but not more than 90 % of a mixture of ethylene carbonate (CAS RN 96-49-1), dimethyl carbonate (CAS RN 616-38-6) and/or ethyl methyl carbonate (CAS RN 623-53-0), — 0,5 % or more but not more than 20 % 1,3,2-dioxathiolane 2,2-dioxide (CAS RN 1072-53-3), <p>for use in the manufacture of motor vehicle batteries (¹)</p> | 3,2 % | — | 31.12.2026 |
| 0.4434 | ex 3824 99 92 | 54 | Poly(tetramethylene glycol) bis[(9-oxo-9H-thioxanthen-1-yloxy)acetate] with an average polymer chain length of less than 5 monomer units (CAS RN 813452-37-8) | 0 % | — | 31.12.2026 |
| 0.6025 | ex 3824 99 92 | 55 | <p>Additives for paints and coatings, containing:</p> <ul style="list-style-type: none"> — a mixture of esters of phosphoric acid obtained from the reaction of phosphoric anhydride with 4-(1,1-dimethylpropyl) phenol and copolymers of styrene-allyl alcohol (CAS RN 84605-27-6), and — 30 % or more but not more than 35 % by weight of isobutyl alcohol | 0 % | — | 31.12.2028 |
| 0.4707 | ex 3824 99 92 | 58 | <p>Mixture containing by weight:</p> <ul style="list-style-type: none"> — 56 % or more but not more than 85 % of divinylbenzene isomers (CAS RN 1321-74-0) — 15 % or more but not more than 44 % of ethylvinylbenzene isomers (CAS RN 28106-30-1) | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.5050 | *ex 3824 99 92 | 61 | 3',4',5'-Trifluorobiphenyl-2-amine, in the form of a solution in toluene containing by weight 80 % or more but not more than 90 % of 3',4',5'-trifluorobiphenyl-2-amine | 0 % | — | 31.12.2030 |
| 0.7831 | ex 3824 99 92 | 62 | Solution of 9-borabicyclo[3.3.1]nonane (CAS RN 280-64-8) in tetrahydrofuran (CAS RN 109-99-9), containing by weight 6 % or more 9-borabicyclo[3.3.1]nonane | 0 % | — | 31.12.2029 |
| 0.6720 | *ex 3824 99 92 | 68 | <p>Preparation containing by weight:</p> <ul style="list-style-type: none"> — 20 % ($\pm 1\%$) ((3-(sec-butyl)-4-(decyloxy)phenyl)methanetriyl) Tribenzene (CAS RN 1404190-37-9) <p>Dissolved in:</p> <ul style="list-style-type: none"> — 10 % ($\pm 5\%$) 2-sec-Butylphenol (CAS RN 89-72-5) — 64 %($\pm 7\%$) Solvent naphtha (petroleum), heavy aromatic (CAS RN 64742-94-5) and — 6 % ($\pm 1,0\%$) Naphthalene (CAS RN 91-20-3) | 0 % | — | 31.12.2030 |
| 0.6719 | *ex 3824 99 92 | 69 | <p>Preparation containing by weight:</p> <ul style="list-style-type: none"> — 80 % or more but not more than 92 % of bisphenol-A bis(diphenyl phosphate) (CAS RN 5945-33-5) — 7 % or more but not more than 20 % oligomers of bisphenol-A bis(diphenyl phosphate) and — not more than 1 % triphenyl phosphate (CAS RN 115-86-6) | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.4409 | ex 3824 99 92 | 70 | Mixture of 80 % (± 10 %) of 1-[2-(2-aminobutoxy)ethoxy]but-2-ylamine and 20 % (± 10 %) of 1-([2-(2-aminobutoxy)ethoxy]methyl) propoxy)but-2-ylamine | 0 % | — | 31.12.2029 |
| 0.8471 | ex 3824 99 92 | 73 | Tri-C8-10-alkyl amines (CAS RN 68814-95-9) with a purity by weight of 95 % or more | 0 % | — | 31.12.2027 |
| 0.8486 | ex 3824 99 92 | 75 | Mixture, containing by weight: — 75 % or more of tetrabutyltin (CAS RN 1461-25-2), — not more than 20 % of tributyltin chloride (CAS RN 1461-22-9), — not more than 4 % of dibutyltin dichloride (CAS RN 683-18-1), for use in the production of butyltin compounds, used in glass manufacture and tributyltin chloride used as a catalyst in the pharmaceutical industry ⁽¹⁾ | 3,2 % | — | 31.12.2027 |
| 0.8506 | ex 3824 99 92 | 79 | Mixture, containing by weight: — tributyltin chloride (CAS RN 1461-22-9) with a purity by weight of 80 % or more, — not more than 5 % tetrabutyltin (CAS RN 1461-25-2), — not more than 6 % dibutyltin dichloride (CAS RN 683-18-1), — not more than 11 % o-xylene (CAS RN 95-47-6), for use in the production of tributyltin chloride used as a catalyst in the pharmaceutical industry ⁽¹⁾ | 3,2 % | — | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.7462 | ex 3824 99 92 | 81 | Reaction mass of 3- [(diphenoxypyrophosphoryl)oxy]phenyl triphenyl 1,3-phenylene bis (phosphate) and tetraphenyl 1,3-phenylene bis(phosphate) | 0 % | — | 31.12.2028 |
| 0.6546 | ex 3824 99 92 | 82 | T-butylchloride dimethylsilane (CAS RN 18162-48-6) solution in toluene | 0 % | — | 31.12.2029 |
| 0.8517 | ex 3824 99 92 | 83 | 1-(Cedr-8-en-9-yl)ethanone (CAS RN 32388-55-9) with a purity by weight of 70 % or more, but not more than 90 % | 0 % | — | 31.12.2029 |
| 0.3074 | ex 3824 99 92 | 84 | Preparation consisting by weight of 83 % or more of 3a,4,7,7a-tetrahydro-4,7-methanoindene (dicyclopentadiene), a synthetic rubber, whether or not containing by weight 7 % or more of tricyclopentadiene, and: — either an aluminium-alkyl compound, — or an organic complex of tungsten — or an organic complex of molybdenum | 0 % | — | 31.12.2029 |
| 0.8499 | ex 3824 99 92 | 86 | Tall oil N,N-dimethyl fatty amides (CAS RN 68308-74-7) with a purity by weight of 99 % or more | 0 % | — | 31.12.2027 |
| 0.3069 | *ex 3824 99 92 | 88 | 2,4,7,9-Tetramethyldec-5-yne-4,7-diol, hydroxyethylated (CAS RN 9014-85-1) | 0 % | — | 31.12.2030 |
| 0.8083 | *ex 3824 99 92 | 92 | Solution consisting of: — 50 (\pm 2) % by weight sodium mentholate (CAS RN 19321-38-1), and — 50 (\pm 2) % by weight light aliphatic solvent naphtha (petroleum) (CAS RN 64742-89-8) | 0 % | — | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8278 | ex 3824 99 92 | 94 | {[[2-(trifluoromethyl)phenyl]carbonyl]amino)methyl acetate (CAS RN 895525-72-1) with a content of at least 45 % by weight dissolved in N,N-dimethylacetamide (CAS RN 127-19-5) | 0 % | — | 31.12.2026 |
| 0.8287 | ex 3824 99 92 | 95 | Solution of methyl cis-1-{{(2,5-dimethylphenyl)acetyl]amino}-4-methoxycyclohexanecarboxylate (CAS RN 203313-47-7) in N,N-dimethylacetamide (CAS RN 127-19-5), containing by weight 25 % or more but not more than 45 % of the carboxylate | 0 % | — | 31.12.2026 |
| 0.5961 | ex 3824 99 93 | 30 | Powder Mixture containing by weight: — 85 % or more of zinc diacrylate (CAS RN 14643-87-9), — not more than 5 % of 2,6-di-tert-butyl-alpha-dimethylamino-p-cresol (CAS RN 88-27-7), and — not more than 10 % of zinc stearate (CAS RN 557-05-1) | 0 % | — | 31.12.2029 |
| 0.8714 | ex 3824 99 93 | 31 | Reaction mass of dihexadecyl hydrogen phosphate (CAS RN 2197-63-9) and hexadecyl dihydrogen phosphate (CAS RN 3539-43-3) | 0 % | — | 31.12.2029 |
| 0.8498 | ex 3824 99 93 | 33 | Preparation containing by weight — 60 % or more but not more than 70 % of calcium <i>rel</i> -(1R,2S)-cyclohexane-1,2-dicarboxylate (CAS RN 491589-22-1), — 30 % or more but not more than 40 % of zinc stearate (CAS RN 557-05-1), — 1 % or more but not more than 5 % of CI Pigment Blue 29 (CAS RN 57455-37-5) and — 1 % or more but not more than 5 % of CI Pigment Violet 15 (CAS RN 12769-96-9) | 0 % | — | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.4719 | ex 3824 99 93 | 35 | Paraffin with a level of chlorination of 70 % or more (CAS RN 63449-39-8) | 0 % | — | 31.12.2029 |
| 0.8497 | ex 3824 99 93 | 36 | Preparation containing by weight 60 % or more but not more than 70 % of calcium <i>rel</i> -(1R,2S)-cyclohexane-1,2-dicarboxylate (CAS RN 491589-22-1) and 30 % or more but not more than 40 % of zinc stearate (CAS RN 557-05-1) | 0 % | — | 31.12.2027 |
| 0.4527 | ex 3824 99 93 | 42 | Mixture of bis{4-(3-(3-phenoxy carbonylamino)tolyl)ureido}phenylsulphone, diphenyltoluene-2,4-dicarbamate and 1-[4-(4-aminobenzenesulphonyl)-phenyl]-3-(3-phenoxy carbonylamino-tolyl)-urea | 0 % | — | 31.12.2029 |
| 0.7153 | ex 3824 99 93 | 45 | Sodium hydrogen 3-aminonaphthalene-1,5-disulphonate (CAS RN 4681-22-5) containing by weight: — not more than 20 % of disodium sulphate, and — not more than 10 % of sodium chloride | 0 % | — | 31.12.2026 |
| 0.7786 | ex 3824 99 93 | 48 | Nonhalogenated flame retardant containing by weight: — 50 % or more, but not more than 65 % of piperazine pyrophosphate (CAS RN 66034-17-1), — 35 % or more, but not more than 45 % of a phosphoric acid derivative and — not more than 6 % of zinc oxide (CAS RN 1314-13-2) | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.6215 | ex 3824 99 93 | 53 | Zinc dimethacrylate (CAS RN 13189-00-9), containing not more than 2,5 % by weight of 2,6-di-tert-butyl-alpha-dimethyl amino-p-cresol (CAS RN 88-27-7), in the form of powder | 0 % | — | 31.12.2029 |
| 0.2939 | ex 3824 99 93 | 61 | Disodium 7,7'-(carbonyldiimino)bis(4-hydroxynaphthalene-2-sulphonate) (CAS RN 20324-87-2) with a purity by weight of 80 % or more | 0 % | — | 31.12.2028 |
| 0.4290 | ex 3824 99 93 | 63 | Mixture of phytosterols, not in the form of powder, containing by weight: — 75 % or more of sterols, — not more than 25 % of stanols, for use in the manufacture of stanols/sterols or stanol/sterol esters (¹) | 0 % | — | 31.12.2027 |
| 0.7460 | ex 3824 99 93 | 65 | Reaction mass of 1,1'-(isopropylidene)bis[3,5-dibromo-4-(2,3-dibromo-2-methylpropoxy)benzene] (CAS RN 97416-84-7) and 1,3-dibromo-2-(2,3-dibromo-2-methylpropoxy)-5-[2-[3,5-dibromo-4-(2,3,3-tribromo-2-methylpropoxy)phenyl]propan-2-yl]benzene | 0 % | — | 31.12.2029 |
| 0.8371 | ex 3824 99 93 | 74 | 1,3-Propanediamine, N1,N1'-1,2-ethanediylbis-, reaction products with cyclohexane and peroxidized N-butyl-2,2,6,6-tetramethyl-4-piperidinamine-2,4,6-trichloro-1,3,5-triazine reaction products (CAS RN 191680-81-6) | 0 % | — | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.4336 | ex 3824 99 93 | 88 | Mixture of phytosterols containing by weight: — 60 % or more, but not more than 80 % of sitosterols, — less than 15 % of campesterol, — less than 5 % of stigmasterols, and — less than 15 % of betasitostanols | 0 % | — | 31.12.2027 |
| 0.3078 | ex 3824 99 96 | 35 | Calcined bauxite (refractory grade) | 0 % | — | 31.12.2029 |
| 0.8514 | ex 3824 99 96 | 43 | 2-(Ethylthio)ethanethiol functionalized silicagel with a purity by weight of 98 % or more | 0 % | — | 31.12.2027 |
| 0.6628 | *ex 3824 99 96 | 46 | Manganese zinc ferrite granulate, containing by weight: — 52 % or more but not more than 76 % of iron(III)oxide, — 13 % or more but not more than 42 % of manganese oxide, and — 2 % or more but not more than 22 % of zinc oxide | 0 % | — | 31.12.2030 |
| 0.6749 | *ex 3824 99 96 | 48 | Zirconium oxide (ZrO_2), calcium oxide stabilised (CAS RN 68937-53-1) with a zirconium oxide content by weight of 92 % or more but not more than 97 % | 0 % | — | 31.12.2030 |
| 0.5607 | ex 3824 99 96 | 50 | Nickel hydroxide, doped with 12 % or more but not more than 18 % by weight of zinc hydroxide and cobalt hydroxide, of a kind used to produce positive electrodes for accumulators | 0 % | — | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.6145 | ex 3824 99 96 | 55 | <p>Carrier in powder form, consisting of:</p> <ul style="list-style-type: none"> — ferrite (Iron oxide) (CAS RN 1309-37-1) — manganese oxide (CAS RN 1344-43-0) — magnesium oxide (CAS RN 1309-48-4) — styrene acrylate copolymer <p>to be mixed with the toner powder, in the manufacturing of ink/toner filled bottles or cartridges for facsimile machines, computer printers and copiers (¹)</p> | 0 % | — | 31.12.2029 |
| 0.5141 | ex 3824 99 96 | 60 | Fused magnesia containing by weight 15 % or more of dichromium trioxide | 0 % | — | 31.12.2026 |
| 0.8587 | ex 3824 99 96 | 62 | <p>Viscous preparation essentially containing:</p> <ul style="list-style-type: none"> — by weight more than 5 % but not more than 15 % of poly(vinyl alcohol) (CAS RN 9002-89-5), — by weight more than 10 % but not more than 20 % of 1-methoxy-2-propanol (CAS RN 107-98-2), — water, <p>for use as a protective coating for wafers during the slicing process in the manufacture of semiconductors (¹)</p> | 0 % | — | 31.12.2028 |
| 0.3050 | ex 3824 99 96 | 65 | <p>Aluminium sodium silicate, in the form of spheres of a diameter of:</p> <ul style="list-style-type: none"> — either 1,6 mm or more but not more than 3,4 mm, — or 4mm or more but not more than 6 mm | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8875 | ex 3824 99 96 | 66 | Vulcanizing agent containing by weight: — 78 % or more but not more than 82 % of insoluble sulphur (CAS RN 9035-99-8), — 18 % or more but not more than 22 % of naphthenic oil (CAS RN 64742-52-5), and — not more than 0,2 % of methyl styrene (CAS RN 98-83-9) | 0 % | — | 31.12.2029 |
| 0.3119 | ex 3824 99 96 | 73 | Reaction product, containing by weight: — 1 % or more but not more than 40 % of molybdenum oxide, — 10 % or more but not more than 50 % of nickel oxide, — 30 % or more but not more than 70 % of tungsten oxide | 0 % | — | 31.12.2029 |
| 0.7010 | ex 3824 99 96 | 74 | Mixture with a non-stoichiometric composition: — with a crystalline structure, — with a content of fused magnesia-alumina spinel and with admixtures of silicate phases and aluminates, at least 75 % by weight of which consists of fractions with a grain size of 1-3 mm and at most 25 % consists of fractions with a grain size of 0-1 mm | 0 % | — | 31.12.2026 |
| 0.8935 | *ex 3824 99 96 | 78 | Zirconium oxide stabilized with yttrium oxide (CAS RN 64417-98-7) containing by weight 90 % or more of zirconium oxide | 0 % | — | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|--------------------------------|----------|---|-------------------------|--------------------|-------------------------------------|
| 0.7147 | ex 3824 99 96 | 80 | <p>Mixture consisting of:</p> <ul style="list-style-type: none"> — 64 % or more, but not more than 74 % by weight of amorphous silica (CAS RN 7631-86-9) — 25 % or more, but not more than 35 % by weight of butanone (CAS RN 78-93-3) and — not more than 1 % by weight of 3-(2,3-epoxypropoxy)propyltrimethoxysilane (CAS RN 2530-83-8) | 0 % | — | 31.12.2026 |
| 0.5820 | ex 3824 99 96 | 87 | <p>Platinum oxide (CAS RN 12035-82-4) fixed on a porous support of aluminium oxide (CAS RN 1344-28-1), containing by weight:</p> <ul style="list-style-type: none"> — 0,1 % or more but not more than 1 % of platinum, and — 0,5 % or more but not more than 5 % of ethylaluminium dichloride (CAS RN 563-43-9) | 0 % | — | 31.12.2027 |
| 0.6132 | ex 3901 10 10 ex 3901 40 00 | 20 10 | <p>High flow linear low density polyethylene-1-butene / LLDPE (CAS RN 25087-34-7) in form of powder, with</p> <ul style="list-style-type: none"> — a melt flow rate (MFR 190 °C/2,16 kg) of 16g/10min or more, but not more than 24 g/10 min and — a density (ASTM D 1505) of 0,922 g/cm³ or more, but not more than 0,926 g/cm³ and — a vicat softening temperature of min. 94 °C | 0 % | m ³ | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|--------------------------------|----------|--|-------------------------|--------------------|-------------------------------------|
| 0.8378 | ex 3901 10 10 ex 3901 40 00 | 50 50 | Copolymer of ethylene and 1-butene (CAS RN 25087-34-7) with: — a density (ASTM D 1505) of 0,924 g/cm ³ or more but not more than 0,928 g/cm ³ , — a melt flow rate (190 °C/2,16 kg) of 48 g/10 min or more but not more than 52 g/10 min, and — a peak melting temperature of 120 °C or more but not more than 124 °C | 0 % | — | 31.12.2027 |
| 0.8379 | ex 3901 10 10 ex 3901 40 00 | 60 60 | Copolymer of ethylene and 1-butene (CAS RN 25087-34-7) with: — a density (ASTM D 1505) of 0,922 g/cm ³ or more but not more than 0,926 g/cm ³ and — a melt flow rate (190 °C/2,16 kg) of 18 g/10 min or more but not more than 22 g/10 min | 0 % | — | 31.12.2029 |
| 0.5142 | ex 3901 10 90 | 30 | Polyethylene granules, containing by weight 10 % or more but not more than 25 % of copper | 0 % | — | 31.12.2026 |
| 0.8757 | ex 3901 30 00 | 20 | Copolymer of ethylene and vinyl acetate (CAS RN 24937-78-8) — containing by weight 28 % or more but not more than 49 % of vinyl acetate, — with a melt flow rate of less than 5g/10 min (190 °C/2,16 kg, ASTM D1238), — in the form of pellets | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8732 | ex 3901 30 00 | 30 | Terpolymer of ethylene, vinyl acetate and methacrylic acid (CAS RN 26375-31-5) | 0 % | — | 31.12.2029 |
| 0.6897 | *ex 3901 40 00 | 30 | Octene linear low-density polyethylene (LLDPE) produced by a Ziegler-Natta catalyst method in the form of pellets with: — more than 10 % but not more than 20 % by weight of copolymer, — a melt flow rate (MFR 190 °C/2,16 kg) of 0,7 g/10 min or more but not more than 0,9 g/10 min, and — a density (ASTM D4703) of 0,911 g/cm ³ or more, but not more than 0,913 g/cm ³ , for use in the co-extrusion processing of films for flexible food packaging (¹) | 0 % | m ³ | 31.12.2030 |
| 0.6920 | *ex 3901 90 80 | 53 | Copolymer of ethylene and acrylic acid (CAS RN 9010-77-9) with: — an acrylic acid content of 18,5 % or more, but not more than 49,5 % by weight (ASTM D4094), and — a melt flow rate of 10g/10 min or more (125 °C/2,16 kg, ASTM D1238) | 0 % | m ³ | 31.12.2030 |
| 0.6734 | *ex 3901 90 80 | 55 | Zinc or sodium salt of an ethylene and acrylic acid copolymer, with: — an acrylic acid content of 6 % or more but not more than 50 % by weight, and — a melt flow rate of 1g/10 min or more at 190 °C/2,16 kg (measured using ASTM D1238) | 0 % | — | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.5049 | *ex 3901 90 80 | 67 | Copolymer made exclusively from ethylene and methacrylic acid monomers in which the methacrylic acid content is 11 % by weight or more | 0 % | — | 31.12.2030 |
| 0.6998 | ex 3901 90 80 | 73 | Mixture containing by weight — 80 % or more, but not more than 94 % of chlorinated polyethylene (CAS RN 64754-90-1) and — 6 % or more, but not more than 20 % of styrene-acrylic copolymer (CAS RN 27136-15-8) | 0 % | — | 31.12.2026 |
| 0.8739 | ex 3901 90 80 | 75 | Terpolymer of ethylene, isobutyl acrylate and methacrylic acid (CAS RN 37433-35-5), in the form of pellets | 0 % | — | 31.12.2029 |
| 0.8736 | ex 3901 90 80 | 85 | Terpolymer of ethylene, n-butyl acrylate and carbon monoxide (CAS RN 61843-70-7) in the form of pellets | 0 % | — | 31.12.2029 |
| 0.2902 | ex 3901 90 80 | 91 | Ionomer resin consisting of a salt of a copolymer of ethylene with methacrylic acid | 0 % | — | 31.12.2029 |
| 0.3906 | ex 3901 90 80 | 92 | Chlorosulphonated polyethylene | 0 % | — | 31.12.2029 |
| 0.2899 | ex 3901 90 80 | 93 | Copolymer of ethylene, vinyl acetate and carbon monoxide, for use as a plasticiser in the manufacture of roof sheets (¹) | 0 % | — | 31.12.2029 |
| 0.3186 | ex 3901 90 80 | 94 | Mixtures of A-B block copolymer of polystyrene and ethylene-butylene copolymer and A-B-A block copolymer of polystyrene, ethylene-butylene copolymer and polystyrene, containing by weight not more than 35 % of styrene | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.2898 | ex 3901 90 80 | 97 | Chlorinated polyethylene, in the form of powder | 0 % | — | 31.12.2029 |
| 0.2895 | ex 3902 10 00 | 20 | Polypropylene, containing no plasticiser, — of a melting point of more than 150 °C (as determined by the ASTM D 3417 method), — of a heat of fusion of 15 J/g or more but not more than 70 J/g, — of an elongation at break of 1 000 % or more (as determined by the ASTM D 638 method), — of a tensile modulus of 69 MPa or more but not more than 379 MPa (as determined by the ASTM D 638 method) | 0 % | — | 31.12.2029 |
| 0.3179 | ex 3902 20 00 | 20 | Hydrogenated polyisobutene, in liquid form | 0 % | — | 31.12.2029 |
| 0.8125 | *ex 3902 30 00 | 20 | Hydrogenated block copolymer of styrene and isoprene (CAS RN 68648-89-5), containing by weight less than 37 % of styrene | 0 % | — | 31.12.2030 |
| 0.8232 | ex 3902 30 00 | 30 | Hydrogenated copolymer of styrene, isoprene and butadiene, containing by weight 28 % or more, but not more than 55 % of propylene | 0 % | — | 31.12.2026 |
| 0.5143 | ex 3902 30 00 | 95 | A-B-A block copolymer, consisting of: — a copolymer of propylene and ethylene and — 21 % (± 3 %) by weight of polystyrene | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.5138 | ex 3902 30 00 | 97 | Liquid ethylene-propylene-copolymer with: — a flashpoint of 250 °C or more, — a viscosity index of 150 or more, — of a number average molecular weight (M_n) of 650 or more | 0 % | — | 31.12.2026 |
| 0.4768 | ex 3902 90 90 | 60 | Non-hydrogenated 100 % aliphatic resin (polymer), with the following characteristics: — liquid at room temperature — obtained by cationic polymerisation of C-5 alkenes monomers — with a number average molecular weight (M_n) of 370 (\pm 50) — with a weight average molecular weight (M_w) of 500 (\pm 100) | 0 % | — | 31.12.2029 |
| 0.7950 | *ex 3902 90 90 | 65 | Brominated butadiene-styrene copolymer (CAS RN 1195978-93-8) with a bromine content of 60 % by weight or more but not more than 68 %, in forms as defined in Note 6 (b) to Chapter 39 | 0 % | — | 31.12.2030 |
| 0.4040 | ex 3902 90 90 | 70 | Synthetic poly-alpha-olefin with a viscosity of 3 or more but not more than 9 centistokes (measured at 100 ° Celsius according to the ASTM D 445 method), obtained by polymerization of dodecene with or without: — not more than 40 % by weight of tetradecene and/or — not more than 2 % by weight decene and/or — not more than 2 % by weight of hexadecene | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|--------------------------------|----------|--|-------------------------|--------------------|-------------------------------------|
| 0.6214 | ex 3902 90 90 | 94 | Chlorinated polyolefins, whether or not in a solution or dispersion | 0 % | — | 31.12.2029 |
| 0.4166 | ex 3903 19 00 | 40 | Crystalline polystyrene with: — a melting point of 268 °C or more but not more than 272 °C — a setting point of 232 °C or more but not more than 247 °C, — whether or not containing additives and filling material | 0 % | — | 31.12.2026 |
| 0.5176 | ex 3903 90 90 | 20 | Copolymer in the form of granules containing by weight: — 83 ± 3 % styrene, — 7 ± 2 % n-butyl acrylate, — 9 ± 2 % n-butyl methacrylate and — 0,01 % or more but not more than 1 % of polyolefinic wax | 0 % | — | 31.12.2026 |
| 0.2891 | ex 3903 90 90 ex 3911 90 99 | 35 43 | Copolymer of α -methylstyrene and styrene, having a softening point of more than 113 °C | 0 % | — | 31.12.2029 |
| 0.7417 | ex 3903 90 90 ex 3904 69 80 | 38 88 | Polytetrafluoroethylene (CAS RN 9002-84-0) encapsulated with an acrylonitrile-styrene copolymer (CAS RN 9003-54-7), with a content by weight of each polymer of 50 % (± 1 %) | 0 % | — | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|--------------------------------|----------|--|-------------------------|--------------------|-------------------------------------|
| 0.8415 | ex 3903 90 90 | 43 | Mixture of polymers consisting by weight of: — 10 % or more but not more than 30 % of a styrene-ethylene-butylene-styrene block copolymer (CAS RN 66070-58-4), — 25 % or more but not more than 45 % of mineral oil (CAS RN 8042-47-5), — 25 % or more but not more than 45 % of calcium carbonate (CAS RN 1317-65-3), — 10 % or more but not more than 20 % of polypropylene (CAS RN 9003-07-0), and — 1 % or more but not more than 3 % of a copolymer of α -methylstyrene and vinyltoluene (CAS RN 9017-27-0) | 0 % | — | 31.12.2027 |
| 0.5473 | ex 3903 90 90 ex 3911 90 99 | 60 60 | Copolymer of styrene with maleic anhydride, either partially esterified or completely chemically modified, in flake or powder form | 0 % | — | 31.12.2026 |
| 0.6804 | *ex 3903 90 90 | 70 | Copolymer in the form of granules containing by weight: — 75 % (\pm 7 %) styrene and — 25 % (\pm 7 %) methylmethacrylate | 0 % | m^3 | 31.12.2030 |
| 0.4410 | ex 3903 90 90 | 86 | Mixture containing by weight: — 45 % or more but not more than 65 % of polymers of styrene, — 30 % or more but not more than 45 % of poly(phenylene ether), and — not more than 11 % of additives | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.2885 | ex 3904 61 00 | 20 | Copolymer of tetrafluoroethylene and trifluoro(hheptafluoropropoxy)ethylene, containing 3,2 % or more but not more than 4,6 % by weight of trifluoro(hheptafluoropropoxy)ethylene and less than 1 mg/kg of extractable fluoride ions | 0 % | — | 31.12.2029 |
| 0.7675 | ex 3904 69 80 | 20 | Copolymer of tetrafluoroethylene, heptafluoro-1-pentene and ethene (CAS RN 94228-79-2) | 0 % | — | 31.12.2029 |
| 0.7626 | ex 3904 69 80 | 30 | Copolymer of tetrafluoroethylene, hexafluoropropene and ethene | 0 % | — | 31.12.2029 |
| 0.5560 | ex 3904 69 80 | 85 | Copolymer of ethylene and chlorotrifluoroethylene, whether or not modified with hexafluoroisobutylene, whether or not containing fillers | 0 % | — | 31.12.2027 |
| 0.2883 | ex 3904 69 80 | 96 | Polychlorotrifluoroethylene, in one of the forms mentioned in note 6 (a) and (b) to Chapter 39 | 0 % | — | 31.12.2029 |
| 0.3745 | ex 3904 69 80 | 97 | Copolymer of chlorotrifluoroethylene and vinylidene difluoride | 0 % | — | 31.12.2029 |
| 0.8414 | ex 3905 91 00 | 35 | Aqueous solution of a copolymer of vinylpyrrolidone and N,N-dimethylaminopropyl methacrylamide sulfate (CAS RN 175893-71-7), containing by weight 8 % or more, but not more than 12 % of copolymer | 0 % | — | 31.12.2027 |
| 0.5774 | ex 3905 91 00 | 40 | Water soluble copolymer of ethylene and vinyl alcohol (CAS RN 26221-27-2), containing by weight not more than 38 % of the monomer unit ethylene | 0 % | — | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8126 | *ex 3905 91 00 | 50 | Aqueous solution consisting by weight of: — 10 % or more but not more than 20 % of a copolymer of vinyl pyrrolidone, N, N-dimethylaminopropyl methacrylamide and 3 (methacryloylamino) propyl lauryldimethylammonium chloride (CAS RN 306769-73-3), — not more than 1 % preservatives | 0 % | — | 31.12.2030 |
| 0.8145 | *ex 3905 91 00 | 60 | Copolymer of vinylpyrrolidone, vinyl caprolactam and dimethylaminoethyl methacrylate (CAS RN 102972-64-5) in solid form, or as an aqueous solution containing by weight: — 27 % or more but not more than 33 % of copolymer, — not more than 1,5 % of ethanol (CAS RN 64-17-5), — not more than 1 % of preservatives | 0 % | — | 31.12.2030 |
| 0.8138 | *ex 3905 91 00 | 70 | Aqueous solution, containing by weight: — 25 % or more but not more than 35 % of a copolymer of vinyl caprolactam, vinyl pyrrolidone, N,N-dimethylaminopropyl methacrylamide and 3-(methacryloylamino) propyl lauryldimethylammonium chloride (CAS RN 748809-45-2), — 10 % or more but not more than 16 % of ethanol (CAS RN 64-17-5) whether or not denatured with tert-butyl alcohol (CAS RN 75-65-0) and/or denatonium benzoate (CAS RN 3734-33-6) | 0 % | — | 31.12.2030 |
| 0.8139 | *ex 3905 91 00 | 80 | Copolymer of vinylpyrrolidone, acrylic acid and dodecyl methacrylate (CAS RN 83120-95-0) | 0 % | — | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.3282 | *ex 3905 99 90 | 30 | Povidone (INN) iodine (CAS RN 25655-41-8) with a purity by weight of 92 % or more | 0 % | — | 31.12.2029 |
| 0.3283 | ex 3905 99 90 | 95 | Hexadecylated or eicosylated polyvinylpyrrolidone | 0 % | — | 31.12.2029 |
| 0.2880 | ex 3905 99 90 | 96 | Polymer of vinyl formal, in one of the forms mentioned in note 6 (b) to Chapter 39, of a weight average molecular weight (M_w) of 25 000 or more but not more than 150 000 and containing by weight: — 9,5 % or more but not more than 13 % of acetyl groups evaluated as vinyl acetate and — 5 % or more but not more than 6,5 % of hydroxy groups evaluated as vinyl alcohol | 0 % | — | 31.12.2029 |
| 0.3278 | ex 3905 99 90 | 98 | Poly(vinyl pyrrolidone) partially substituted by triacontyl groups, containing by weight 78 % or more but not more than 82 % of triacontyl groups | 0 % | — | 31.12.2029 |
| 0.3276 | 3906 90 60 | | Copolymer of methyl acrylate with ethylene and a monomer containing a non-terminal carboxy group as a substituent, containing by weight 50 % or more of methyl acrylate, whether or not mixed with silicon dioxide | 0 % | — | 31.12.2029 |
| 0.7347 | ex 3906 90 90 | 23 | Copolymer of methylmethacrylate, butylacrylate, glycidylmethacrylate and styrene (CAS RN 37953-21-2), with an epoxy equivalent weight of not more than 500, in form of ground flakes with a particle size of not more than 1 cm | 0 % | — | 31.12.2027 |
| 0.6672 | *ex 3906 90 90 | 33 | Core shell copolymer of butyl acrylate and alkyl methacrylate, with a particle size of 5 μm or more but not more than 10 μm | 0 % | — | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.7125 | ex 3906 90 90 | 43 | Copolymer of methacrylic esters, butylacrylate and cyclic dimethylsiloxanes (CAS RN 143106-82-5) | 0 % | — | 31.12.2026 |
| 0.2886 | ex 3906 90 90 | 50 | Polymers of esters of acrylic acid with one or more of the following monomers in the chain: — chloromethyl vinyl ether, — chloroethyl vinyl ether, — chloromethylstyrene, — vinyl chloroacetate, — methacrylic acid, — butenedioic acid monobutyl ester, — butenedioic acid monocyclohexyl ester, containing by weight not more than 5 % of each monomer unit | 0 % | — | 31.12.2029 |
| 0.8579 | ex 3906 90 90 | 58 | Mixture of polymers, containing by weight: — 77 % or more but not more than 81 % of polyacrylamide (CAS RN 9003-05-8), — 18 % or more but not more than 21 % of polyethylene glycol (CAS RN 25322-68-3) | 0 % | — | 31.12.2028 |
| 0.7499 | ex 3906 90 90 | 60 | Aqueous dispersion containing by weight: — more than 10 % but not more than 15 % of ethanol, and — more than 7 % but not more than 11 % of a reaction product of poly (epoxyalkylmethacrylate-co-divinylbenzene) with a glycerol derivative | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.8828 | ex 3906 90 90 | 71 | Acrylonitrile-styrene-acrylate copolymer in the form of granules containing by weight: — 48 % of styrene, — 22 % of acrylonitrile, — 29 % of butylacrylate, and — 1 % of dihydrodicyclopentadienyl acrylate | 0 % | — | 31.12.2029 |
| 0.6425 | ex 3906 90 90 | 73 | Preparation containing by weight: — 33 % or more but not more than 37 % of butyl methacrylate - methacrylic acid copolymer, — 24 % or more but not more than 28 % of propylene glycol, and — 37 % or more but not more than 41 % of water | 0 % | — | 31.12.2029 |
| 0.3272 | ex 3907 29 11 | 10 | Poly(ethylene oxide) of a number average molecular weight (M_n) of 100 000 or more | 0 % | — | 31.12.2029 |
| 0.4378 | ex 3907 29 11 | 20 | Bis[Methoxypoly[ethyleneglycol]]-maleimidopropionamide, chemically modified with lysine, of a number average molecular weight (M_n) of 40 000 | 0 % | — | 31.12.2029 |
| 0.8882 | ex 3907 29 11 | 30 | Mixture containing by weight: — 75 % or more of polyethyleneglycol modified butyl-2-cyano-3-(4-hydroxy-3-methoxyphenyl) acrylate, with an ethylene oxide chain length of not more than 30 (CAS RN 780763-40-8) — not more than 25 % of ethoxylated sorbitan trioleate (CAS RN 9005-70-3) | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8896 | ex 3907 29 11 | 40 | Ethoxylated glycerol (CAS RN 31694-55-0) with a hydroxyl number of 541 or more but not more than 587 (ASTM 4274) | 0 % | — | 31.12.2029 |
| 0.7532 | ex 3907 29 20 | 35 | Mixture containing by weight: — 5 % or more but not more than 15 % of a copolymer of glycerol, propylene oxide and ethylene oxide (CAS RN 9082-00-2), and — 85 % or more but not more than 95 % of a copolymer of sucrose, propylene oxide and ethylene oxide (CAS RN 26301-10-0) | 0 % | — | 31.12.2029 |
| 0.4013 | ex 3907 29 20 | 40 | Copolymer of tetrahydrofuran and tetrahydro-3-methylfuran (CAS RN 38640-26-5) with a number average molecular weight (Mn) of 900 or more but not more than 3 600 | 0 % | — | 31.12.2028 |
| 0.6351 | ex 3907 29 20 | 50 | Poly(p-phenylene oxide) in the form of powder with: — a glass-transition temperature of 210 °C or more, — a weight average molecular weight (Mw) of 35 000 or more but not more than 80 000, — an inherent viscosity of 0,2 or more but not more than 0,6 dl/gram | 0 % | — | 31.12.2029 |
| 0.7478 | ex 3907 29 99 | 20 | 2,3-Bis(methylpolyoxyethylene-oxy)-1-[(3-maleimido-1-oxopropyl)amino]propyloxy propane (CAS RN 697278-30-1) with a number average molecular weight (Mn) of at least 20 kDa whether or not modified with a chemical entity enabling a linkage between the PEG and a protein or a peptide | 0 % | — | 31.12.2029 |
| 0.2920 | ex 3907 29 99 | 30 | Homopolymer of 1-chloro-2,3-epoxypropane (epichlorohydrin) | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.3269 | ex 3907 29 99 | 45 | Copolymer of ethylene oxide and propylene oxide, having aminopropyl and methoxy end-groups | 0 % | — | 31.12.2029 |
| 0.4536 | ex 3907 29 99 | 50 | Vinyl-silyl terminated perfluoropolyether polymer or an assortment of two components consisting of the same type of vinyl-silyl terminated perfluoropolyether polymer as the main ingredient | 0 % | — | 31.12.2029 |
| 0.4546 | ex 3907 29 99 | 55 | Succinimidyl ester of methoxy poly(ethylene glycol)propionic acid, of a number average molecular weight (Mn) of 5 000 | 0 % | — | 31.12.2029 |
| 0.5144 | ex 3907 29 99 | 60 | Polytetramethylene oxide di-p-aminobenzoate | 0 % | — | 31.12.2026 |
| 0.8491 | ex 3907 29 99 | 70 | Poly(oxy-1,4-phenyleneoxy-1,4-phenylene carbonyl-1,4-phenylene) (CAS RN 29658-26-2) containing by weight not more than 35 % of additives | 0 % | — | 31.12.2027 |
| 0.2759 | ex 3907 30 00 | 40 | Epoxide resin, containing by weight 70 % or more of silicon dioxide, for the encapsulation of goods of headings 8504, 8533, 8535, 8536, 8541, 8542 or 8548 (¹) | 0 % | — | 31.12.2029 |
| 0.7427 | ex 3907 30 00 | 70 | Preparation of epoxy resin (CAS RN 29690-82-2) and phenolic resin (CAS RN 9003-35-4) containing by weight: — 65 % or more but not more than 75 % of silicon dioxide (CAS RN 60676-86-0), and — none or not more than 0,5 % of carbon black (CAS RN 1333-86-4) | 0 % | — | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------------------------|----------|--|-------------------------|--------------------|-------------------------------------|
| 0.2541 | ex 3907 40 00 | 35 | α -Phenoxy carbonyl- ω -phenoxy poly[oxy(2,6-dibromo-1,4-phenylene) isopropylidene (3,5-dibromo-1,4-phenylene)oxycarbonyl] (CAS RN 94334-64-2) | 0 % | — | 31.12.2029 |
| 0.2564 | ex 3907 40 00 | 45 | α -(2,4,6-Tribromophenyl)- ω -(2,4,6-tribromophenoxy)poly[oxy(2,6-dibromo-1,4-phenylene) isopropylidene(3,5-dibromo-1,4-phenylene)oxycarbonyl] (CAS RN 71342-77-3) | 0 % | — | 31.12.2029 |
| 0.3263 | ex 3907 69 00 | 10 | Copolymer of terephthalic acid and isophthalic acid with ethylene glycol, butane-1,4-diol and hexane-1,6-diol | 0 % | — | 31.12.2029 |
| 0.2980 | 3907 70 00 | | Poly(lactic acid) | 0 % | — | 31.12.2029 |
| 0.2918 | ex 3907 91 90 | 10 | Diallyl phthalate prepolymer, in powder form | 0 % | — | 31.12.2029 |
| 0.5639 | ex 3907 99 80 | 25 | Copolymer, containing 72 % by weight or more of terephthalic acid and/or isomers thereof and cyclohexanedimethanol | 0 % | — | 31.12.2027 |
| 0.4940 | *ex 3907 99 80 ex 3913 90 00 | 30 20 | Poly(hydroxyalkanoate), predominantly consisting of poly(3-hydroxybutyrate) | 0 % | — | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.7491 | ex 3907 99 80 | 35 | Copolymer in form of a clear, pale yellow liquid, consisting of — phthalic acid isomers and/or aliphatic dicarboxylic acids, — aliphatic diols, and — fatty acid end-caps with: — a hydroxyl number of 120 mg KOH or more but not more than 350 mg KOH, — a viscosity at 25 °C of 2 000 cPs or more but not more than 8 000 cPs, and — an acid value less than 10 mg KOH/g | 0 % | — | 31.12.2029 |
| 0.5057 | *ex 3907 99 80 | 80 | Copolymer, consisting of 72 % by weight or more of terephthalic acid and/ or derivatives thereof and cyclohexanedimethanol, completed with linear and/ or cyclic diolcs | 0 % | — | 31.12.2030 |
| 0.2923 | ex 3908 90 00 | 10 | Poly(iminomethylene-1,3-phenylenemethyleneimino adipoyl), in one of the forms mentioned in note 6 (b) to Chapter 39 | 0 % | — | 31.12.2029 |
| 0.7428 | ex 3909 20 00 | 10 | Polymer mixture, containing by weight: — 60 % or more but not more than 75 % of melamine resin (CAS RN 9003-08-1), — 15 % or more but not more than 25 % of silicon dioxide (CAS RN 14808-60-7 or 60676-86-0), — 5 % or more but not more than 15 % of cellulose (CAS RN 9004-34-6), and — 1 % or more but not more than 15 % of phenolic resin (CAS RN 25917-04-8) | 0 % | — | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.6423 | ex 3909 50 90 | 20 | Preparation containing by weight: — 14 % or more but not more than 18 % of ethoxylated polyurethane modified with hydrophobic groups, — 3 % or more but not more than 5 % of enzymatically modified starch, and — 77 % or more but not more than 83 % of water | 0 % | — | 31.12.2029 |
| 0.6420 | ex 3909 50 90 | 30 | Preparation containing by weight: — 16 % or more but not more than 20 % of ethoxylated polyurethane modified with hydrophobic groups, — 19 % or more but not more than 23 % of diethylene glycol butyl ether, and — 60 % or more but not more than 64 % of water | 0 % | — | 31.12.2029 |
| 0.6424 | ex 3909 50 90 | 40 | Preparation containing by weight: — 34 % or more but not more than 36 % of ethoxylated polyurethane modified with hydrophobic groups, — 37 % or more but not more than 39 % of propylene glycol, and — 26 % or more but not more than 28 % of water | 0 % | — | 31.12.2029 |
| 0.6921 | ex 3910 00 00 | 15 | Dimethyl, methyl(propyl(polypropylene oxide)) siloxane (CAS RN 68957-00-6), trimethylsiloxy-terminated | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.3260 | ex 3910 00 00 | 20 | Block copolymer of poly(methyl-3,3,3-trifluoropropylsiloxane) and poly[methyl(vinyl) siloxane] | 0 % | — | 31.12.2029 |
| 0.7057 | ex 3910 00 00 | 25 | Preparations containing by weight: — 10 % or more, 2-hydroxy-3-[3-[1,3,3,3-tetramethyl-1-[(trimethylsilyl)oxy] disiloxanyl] propoxy] propyl-2-methyl-2-propenoate (CAS RN 69861-02-5), and — 10 % or more, α -Butyldimethylsilyl- ω -3-[(2-methyl-1-oxo-2-propen-1-yl)oxy] propyl-terminated silicone polymer (CAS RN 146632-07-7) | 0 % | — | 31.12.2026 |
| 0.7058 | ex 3910 00 00 | 35 | Preparations containing by weight: — 30 % or more, α -Butyldimethylsilyl- ω -(3-methacryloxy-2-hydroxypropoxy) propyldimethylsilyl-polydimethylsiloxane (CAS RN 662148-59-6) and — 10 % or more, N,N – Dimethylacrylamide (CAS RN 2680-03-7) | 0 % | — | 31.12.2026 |
| 0.4049 | ex 3910 00 00 | 40 | Silicones of a kind used in the manufacture of long term surgical implants | 0 % | — | 31.12.2026 |
| 0.7217 | ex 3910 00 00 | 45 | Dimethyl siloxane, hydroxy-terminated polymer with a viscosity of 38-100 mPa·s (CAS RN 70131-67-8) | 0 % | — | 31.12.2026 |
| 0.4300 | ex 3910 00 00 | 50 | Silicone based pressure sensitive adhesive in solvent containing copoly (dimethylsiloxane/diphenylsiloxane) gum | 0 % | — | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.7218 | ex 3910 00 00 | 55 | <p>Preparation containing by weight:</p> <ul style="list-style-type: none"> — 55 % or more but not more than 65 % of vinyl terminated polydimethylsiloxane (CAS RN 68083-19-2), — 30 % or more but not more than 40 % of dimethylvinylated and trimethylated silica (CAS RN 68988-89-6), and — 1 % or more but not more than 5 % of silicic acid, sodium salt, reaction products with chlorotrimethylsilane and isopropyl alcohol (CAS RN 68988-56-7) | 0 % | — | 31.12.2026 |
| 0.5926 | ex 3910 00 00 | 70 | Passivating silicon coating in primary form, to protect edges and prevent short circuits in semiconductor devices | 0 % | — | 31.12.2029 |
| 0.8670 | ex 3910 00 00 | 85 | Two-component silicone, with a viscosity of the mixture of 3 000 cps or more, but not more than 6 000 cps (according to standard GB/T 2794) for use as an electrical insulation material in solar panels junction box in the production of solar panels (¹) | 0 % | — | 31.12.2028 |
| 0.4413 | ex 3911 10 00 | 81 | <p>Non-hydrogenated hydrocarbon resin, obtained by polymerization of more than 75 % by weight C-5 to C-12 cycloaliphatic alkenes and more than 10 % but not more than 25 % by weight aromatic alkenes yielding a hydrocarbon resin with:</p> <ul style="list-style-type: none"> — an iodine value of more than 120 and — a Gardner Colour of more than 10 for the pure product or — a Gardner Colour of more than 8 for a 50 % solution by weight in toluene (as determined by the ASTM method D6166) | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8220 | *ex 3911 90 19 | 15 | Polyetherimide of <ul style="list-style-type: none"> — 5,5'-(isopropylidene)bis(4,1-phenylene)dioxy]bis(1,3-isobenzofurandione) and 1,3-benzenediamine whether or not as a copolymer with 3-aminopropyl terminated dimethylsilicones (CAS RN 61128-46-9 or 99904-16-2), or — 5,5'-(isopropylidene)bis(4,1-phenylene)dioxy]bis(1,3-isobenzofurandione) and 1,4-benzenediamine (CAS RN 61128-47-0), or — 4,4'-(isopropylidene)bis(4,1-phenylene)dioxy]bis(1,3-isobenzofurandione), 5,5'-(isopropylidene)bis(4,1-phenylene)dioxy]bis(1,3-isobenzofurandione), 4,5'-(isopropylidene)bis(4,1-phenylene)dioxy]bis(1,3-isobenzofurandione), pyromellitic dianhydride, 1,2-benzenediamine, 1,3-benzenediamine and 1,4-benzenediamine with phthalic anhydride endcaps (CAS RN 96557-46-9) | 0 % | — | 31.12.2026 |
| 0.8920 | *ex 3911 90 19 | 25 | Polyamideimide of <ul style="list-style-type: none"> — 4-Chloroformylphthalic anhydride and 4,4'-methylenedianiline (CAS RN 35463-82-2), or — 4-Chloroformylphthalic anhydride, 4,4'-oxydianiline and 1,3-phenylenediamine (CAS RN 25928-85-2), containing by weight not more than 35 % of additives | 0 % | — | 31.12.2030 |
| 0.4280 | ex 3911 90 19 | 30 | Copolymer of ethyleneimine and ethyleneimine dithiocarbamate, in an aqueous solution of sodium hydroxide | 0 % | — | 31.12.2027 |
| 0.5145 | ex 3911 90 19 | 40 | m-Xylene formaldehyde resin | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.8450 | ex 3911 90 19 | 80 | Poly(oxy-1,4-phenylenesulfonyl-1,4-phenylene) (CAS RN 25608-63-3 and CAS RN 25667-42-9) containing by weight not more than 20 % of additives | 0 % | — | 31.12.2027 |
| 0.8218 | ex 3911 90 99 | 23 | Aqueous solution consisting of by weight 25 % or more, but not more than 40 % of a poly (isobutylene-maleic anhydride) modified with: — N,N-dimethylpropane-1,3-diamine, — a copolymer of ethylene oxide and propylene oxide, having aminopropyl and methoxy end-groups, — ethanol (CAS RN 497926-97-3) | 0 % | — | 31.12.2026 |
| 0.3257 | ex 3911 90 99 | 25 | Copolymer of vinyltoluene and α -methylstyrene | 0 % | — | 31.12.2029 |
| 0.5109 | *ex 3911 90 99 | 35 | Alternated copolymer of ethylene and maleic anhydride (EMA) | 0 % | — | 31.12.2030 |
| 0.8009 | *ex 3911 90 99 | 38 | Mixture containing by weight: — 90 % (\pm 1 %) of 1,4:5,8- Dimethanonaphthalene, 2-ethylidene-1,2,3,4,4a,5,8,8a-octahydro-,polymer with 3a,4,7,7a- tetrahydro-4,7-methano-1H-indene, hydrogenated (CAS RN 881025-72-5), and — 10 % (\pm 1 %) of a hydrogenated styrene butadiene copolymer (CAS RN 66070-58-4) | 0 % | — | 31.12.2030 |
| 0.3221 | ex 3911 90 99 | 40 | Mixed calcium and sodium salt of a copolymer of maleic acid and methyl vinyl ether, having a calcium content of 9 % or more but not more than 16 % by weight | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.3256 | ex 3911 90 99 | 45 | Copolymer of maleic acid and methyl vinyl ether | 0 % | — | 31.12.2029 |
| 0.8010 | *ex 3911 90 99 | 48 | Mixture containing by weight: — 90 % (± 1 %) of 1,4:5,8-dimethanonaphthalene, 2-ethylidene-1,2,3,4,4a,5,8,8a-octahydro-, polymer with 3a,4,7,7a-tetrahydro-4,7-methano-1H-indene, hydrogenated (CAS RN 881025-72-5), and — 10 % (± 1 %) of an ethylene-propylene copolymer (CAS RN 9010-79-1) | 0 % | — | 31.12.2030 |
| 0.3255 | ex 3911 90 99 | 65 | Calcium zinc salt of a copolymer of maleic acid and methyl vinyl ether | 0 % | — | 31.12.2029 |
| 0.8918 | *ex 3911 90 99 | 73 | A mixture containing by weight: — 89 % or more but not more than 91 % of 1,4:5,8-dimethanonaphthalene, 2-ethylidene-1,2,3,4,4a,5,8,8a-octahydro-, polymer with 3a,4,7,7a-tetrahydro-4,7-methano-1H-indene, hydrogenated (CAS RN 881025-72-5), and — 9 % or more but not more than 11 % of polypropylene homopolymer (CAS RN 9003-07-0) | 0 % | — | 31.12.2030 |
| 0.4091 | ex 3911 90 99 | 86 | Copolymer of methyl vinyl ether and maleic acid anhydride (CAS RN 9011-16-9) | 0 % | — | 31.12.2026 |
| 0.4912 | ex 3912 11 00 | 30 | Cellulose triacetate (CAS RN 9012-09-3) | 0 % | — | 31.12.2026 |
| 0.4953 | *ex 3912 11 00 | 40 | Cellulose diacetate powder | 0 % | — | 31.12.2030 |
| 0.3251 | ex 3912 39 85 | 10 | Ethylcellulose, not plasticized | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.3253 | ex 3912 39 85 | 20 | Ethylcellulose, in the form of an aqueous dispersion containing hexadecan-1-ol and sodium dodecyl sulphate, containing by weight 27 (± 3) % of ethylcellulose | 0 % | — | 31.12.2029 |
| 0.3252 | ex 3912 39 85 | 30 | Cellulose, both hydroxyethylated and alkylated with alkyl chain-lengths of 3 or more carbon atoms | 0 % | — | 31.12.2029 |
| 0.6718 | *ex 3912 39 85 | 50 | Polyquaternium 10 (CAS RN 68610-92-4) | 0 % | — | 31.12.2030 |
| 0.4017 | ex 3912 90 10 | 20 | Hydroxypropyl methylcellulose phthalate | 0 % | — | 31.12.2029 |
| 0.3749 | ex 3913 90 00 | 85 | Sterile sodium hyaluronate (CAS RN 9067-32-7) | 0 % | — | 31.12.2029 |
| 0.3249 | ex 3913 90 00 | 95 | Chondroitinsulphuric acid, sodium salt (CAS RN 9082-07-9) | 0 % | — | 31.12.2029 |
| 0.8323 | ex 3914 00 00 | 10 | Aqueous suspension, containing by weight — 20 % or more but not more than 30 % of beaded agarose, modified with nitrilotriacetic acid and loaded with divalent nickel ions (CAS RN 1615227-97-8), and — 20 % or more but not more than 30 % of ethanol (CAS RN 64-17-5) | 0 % | — | 31.12.2027 |
| 0.5988 | ex 3916 90 10 | 10 | Rods with cellular structure, containing by weight: — polyamide-6 or poly(epoxy anhydride) — 7 % or more but not more than 9 % of polytetrafluoroethylene if present — 10 % or more but not more than 25 % of inorganic fillers | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---|----------------|--|-------------------------|--------------------|-------------------------------------|
| 0.8116 | ex 3917 31 00 ex 3917 32 00 ex 3917 39 00 | 30 20 20 | Tubings: — with an outer diameter of 0,33 mm or more but not more than 3,3 mm, — with an inner diameter of 0,01 mm or more but not more than 2,1 mm, — suitable for a maximum working pressure rate from 2,7 MPa up to 70 MPa, — suitable for all solutions used in chromatography, — whether or not with fused silica, — whether or not covered with PEEK, for use in chromatographic system (¹) | 0 % | — | 31.12.2026 |
| 0.8268 | ex 3917 32 00 | 30 | Heat shrinkable tube: — containing by weight 80 % or more polymer, — with an insulation resistance of 90 MΩ or more, — with a dielectric strength of 35 kV / mm or more, — with a wall thickness of 0,04 mm or more, but not more than 0,9 mm, — with a lay-flat width of 18 mm or more, but not more than 156 mm, for use in the manufacture of aluminium electrolytic capacitors (¹) | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---|----------------|---|-------------------------|--------------------|-------------------------------------|
| 0.8117 | ex 3917 40 00 | 20 | <p>Plastic fittings (kit of nuts and ferrules or nuts) and connectors:</p> <ul style="list-style-type: none"> — threaded, — supported with or without a stainless steel ring, — suitable for a maximum working pressure rate of 2,7 MPa or more but not more than 114 MPa, <p>for tubings with:</p> <ul style="list-style-type: none"> — outer diameter of 0,33 mm or more but not more than 3,3 mm, — suitable for a maximum working pressure rate of 2,7 MPa or more but not more than 114 MPa, — suitable for all solutions used in chromatography, <p>for use in the production of chromatographic systems ⁽¹⁾</p> | 0 % | — | 31.12.2026 |
| 0.4641 | ex 3917 40 00 | 91 | Plastic connectors containing O-rings, a retainer clip and a release system for insertion into car fuel hoses | 0 % | — | 31.12.2029 |
| 0.2421 | ex 3919 10 19 ex 3919 10 80 ex 3919 90 80 | 10 25 31 | Reflecting film, consisting of a layer of polyurethane, with, on one side, security imprints against counterfeiting, alteration or substitution of data or duplication, or an official mark for an intended use, and embedded glass beads and, on the other side, an adhesive layer, covered on one side or on both sides with a release film | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|--------------------------------|----------|--|-------------------------|--------------------|-------------------------------------|
| 0.4800 | ex 3919 10 80 ex 3919 90 80 | 27 20 | Polyester film: — coated on one side with an acrylic thermal release adhesive that debonds at temperatures of 90 °C or more but not more than 200 °C, and a polyester liner, and — on the other side not coated or coated with an acrylic pressure sensitive adhesive or with an acrylic thermal release adhesive that debonds at temperatures of 90 °C or more but not more than 200 °C, and a polyester liner | 0 % | — | 31.12.2027 |
| 0.2910 | ex 3919 10 80 | 35 | Reflecting film, consisting of a layer of poly(vinyl chloride), a layer of alkyd polyester, with, on one side, security imprints against counterfeiting, alteration or substitution of data or duplication, or an official mark for an intended use, only visible by means of a retroreflecting lighting, and embedded glass beads and, on the other side, an adhesive layer, covered on one side or on both sides with a release film | 0 % | — | 31.12.2029 |
| 0.4303 | ex 3919 10 80 ex 3919 90 80 | 45 45 | Reinforced polyethylene foam tape, coated on both sides with an acrylic micro channelled pressure sensitive adhesive and on one side a liner, with an application thickness of 0,38 mm or more but not more than 1,53 mm | 0 % | — | 31.12.2027 |
| 0.3036 | ex 3919 10 80 ex 3919 90 80 | 55 53 | Acrylic foam tape: — covered on one side with a heat activatable adhesive or an acrylic pressure sensitive adhesive, — covered on the other side with an acrylic pressure sensitive adhesive, — covered on one or both sides with a release sheet, — with a peel adhesion of more than 25 N/cm (at an angle of 90° as determined by the ASTM D 3330 method) | 0 % | — | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---|----------------|---|-------------------------|--------------------|-------------------------------------|
| 0.2416 | ex 3919 10 80 ex 3919 90 80 ex 3920 61 00 | 57 30 30 | Reflecting sheet: — of a polycarbonate or acrylic polymer film embossed on one side in a regular shaped pattern — covered on one or both sides with one or more layers of plastic or metallisation, and — whether or not covered on one side with a self-adhesive layer and a release sheet | 0 % | — | 31.12.2029 |
| 0.6886 | *ex 3919 10 80 | 63 | Reflecting film consisting of — a layer of an acrylic resin with imprints against counterfeiting, alteration or substitution of data or duplication, or an official mark for an intended use, — a layer of an acrylic resin having embedded glass beads, — a layer of an acrylic resin hardened by a melamine cross-linking agent, — a metal layer, — an acrylic adhesive, and — a release film | 0 % | — | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|--------------------------------|----------|--|-------------------------|--------------------|-------------------------------------|
| 0.4545 | ex 3919 10 80 ex 3919 90 80 | 73 50 | Self-adhesive reflecting sheet whether or not in segmented pieces, — whether or not containing a watermark, — with or without an application tape coated on one side with an adhesive; the reflective sheet consists of: — a layer of acrylic or vinyl polymer, — a layer of poly(methyl methacrylate) or polycarbonate containing microprisms, — a layer of metallisation, — an adhesive layer, and — a release sheet — whether or not containing an additional layer of polyester | 0 % | — | 31.12.2029 |
| 0.5166 | ex 3919 10 80 ex 3919 90 80 | 75 80 | Self-adhesive reflecting film, consisting of several layers including: — a copolymer of acrylic resin, — polyurethane, — a metallised layer with, on one side, laser imprints against counterfeiting, alteration or substitution of data or duplications, or an official mark for an intended use, — glass microspheres, and — an adhesive layer, with a release liner on one or both sides | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|--------------------------------|----------|---|-------------------------|--------------------|-------------------------------------|
| 0.8667 | ex 3919 10 80 ex 3919 90 80 | 78 48 | Polytetrafluoroethylene film, — with a thickness of 50 µm or more, — with a width of 6,30 mm or more but not more than 740 mm, — an elongation at break of not more than 200 %, and — coated on one side with a pressure sensitive silicone adhesive with a thickness of not more than 50 µm | 0 % | — | 31.12.2028 |
| 0.3243 | ex 3919 90 80 | 23 | Film consisting of 1 to 3 laminated layers of poly(ethylene terephthalate) and a copolymer of terephthalic acid, sebacic acid and ethylene glycol, coated on one side with an acrylic abrasion resistant coating and on the other side with an acrylic pressure sensitive adhesive, a water soluble methylcellulose coating and a poly(ethylene terephthalate) protective liner | 0 % | — | 31.12.2029 |
| 0.4760 | ex 3919 90 80 | 24 | Reflecting laminated sheet: — consisting of an epoxy acrylate layer embossed on one side in a regular shaped pattern, — covered on both sides with one or more layers of plastic material and — covered on one side with an adhesive layer and a release sheet | 0 % | — | 31.12.2029 |
| 0.4415 | ex 3919 90 80 | 33 | Transparent poly(ethylene) self-adhesive film, free from impurities or faults, coated on one side with an acrylic pressure sensitive adhesive, with a thickness of 60 µm or more, but not more than 70 µm, and with a width of more than 1 245 mm but not more than 1 255 mm | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.4445 | ex 3919 90 80 | 49 | Reflecting laminated sheet consisting of a film of poly(methyl methacrylate) embossed on one side in a regular shaped pattern, a film of a polymer containing glass microspheres, an adhesive layer and a release sheet | 0 % | — | 31.12.2029 |
| 0.5507 | ex 3919 90 80 | 51 | Biaxially-oriented film of poly(methyl methacrylate), of a thickness of 50 µm or more but not exceeding 90 µm, covered on one side with an adhesive layer and a release sheet | 0 % | — | 31.12.2029 |
| 0.4532 | ex 3919 90 80 | 54 | Poly(vinyl chloride) film, on one side covered with <ul style="list-style-type: none"> — a polymer layer — an adhesive layer — a release liner, on one side embossed, containing oblate spheres; whether or not on the other side covered with an adhesive layer and a metallised polymer layer | 0 % | — | 31.12.2029 |
| 0.8629 | ex 3919 90 80 | 55 | Black polyvinyl chloride film: <ul style="list-style-type: none"> — with a gloss of more than 25 degrees according to ASTM D 2457, — whether or not covered on one side with a protective film of polyethylene terephthalate and on the other side with a micro-structured pressure sensitive acrylic adhesive and a release liner for use in the manufacture of die-cut films for interior and exterior surfaces of cars ⁽¹⁾ | 0 % | — | 31.12.2028 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.4314 | ex 3919 90 80 | 56 | Transparent polyethylene film coated on one side with an aqueous acrylic adhesive, of a thickness of 30 µm to 50 µm, put up in rolls of a width of 52 cm or more but not more than 154 cm | 0 % | — | 31.12.2029 |
| 0.4947 | *ex 3919 90 80 | 65 | Self-adhesive film with a thickness of 40 µm or more, but not more than 475 µm, consisting of one or more layers of transparent, metallised or dyed poly(ethylene terephthalate), covered on one side with a scratch resistant coating and on the other side with a pressure sensitive adhesive and a release liner | 0 % | — | 31.12.2030 |
| 0.4925 | *ex 3919 90 80 | 70 | Self-adhesive polishing discs of microporous polyurethane, whether or not coated with a pad | 0 % | — | 31.12.2030 |
| 0.4964 | *ex 3919 90 80 | 82 | Reflecting film consisting of: — a polyurethane layer, — a glass microspheres layer, — a metallised aluminium layer, and — an adhesive, covered on one or both sides with a release liner, — whether or not a poly(vinyl chloride) layer, — a layer whether or not incorporating security imprints against counterfeiting, alteration or substitution of data or duplication, or an official mark for an intended use | 0 % | — | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.4459 | ex 3919 90 80 | 83 | Reflector or diffuser sheets, in rolls, — for protection against ultraviolet or infra-red heat radiation, to be affixed to windows or — for equal transmission and distribution of light, intended for LCD modules | 0 % | — | 31.12.2027 |
| 0.3754 | ex 3920 10 89 | 40 | Composite sheet containing an acrylic coating and laminated to a high-density polyethylene layer, of a total thickness of 0,8 mm or more but not more than 1,2 mm | 0 % | — | 31.12.2027 |
| 0.8205 | ex 3920 20 21 | 50 | Biaxialy oriented film of multiple layers of polypropylene, with a total thickness of not more than 14 micron | 0 % | — | 31.12.2026 |
| 0.3028 | ex 3920 20 29 | 70 | Mono-axial oriented film, consisting of three layers, each layer consisting of a mixture of polypropylene and a copolymer of ethylene and vinyl acetate, with a core layer whether or not containing titanium dioxide, having: — a thickness of 55 µm or more but not more than 97 µm, — a tensile modulus in the machine direction of 0,30 GPa or more but not more than 1,45 GPa, and — a tensile modulus in the transverse direction of 0,20 GPa or more but not more than 0,70 GPa | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.5167 | ex 3920 20 29 | 94 | Mono-axial oriented, co-extruded film: — consisting of 3 to 5 layers, — each layer mainly consisting of polypropylene and/or polyethylene, — each layer containing not more than 10 % by weight of other polymers, — whether or not containing titanium dioxide in the core layer, — of an overall thickness of not more than 75 µm | 0 % | — | 31.12.2027 |
| 0.8848 | ex 3920 30 00 | 30 | Opaque layer, whether or not printed, biaxially oriented, high impact polystyrene foil in rolls with: — a thickness of 0,229 mm or more but not more than 0,279 mm, — an titanium dioxide content by weight of 3 % or more but not more than 3,5 %, — on one side a highly hydrophobic, chemically neutral and non-reactive coating | 0 % | — | 31.12.2029 |
| 0.3024 | ex 3920 43 10 | 92 | Sheeting of poly(vinyl chloride), stabilized against ultraviolet rays, without any holes, even microscopic, of a thickness of 60 µm or more but not more than 80 µm, containing 30 or more but not more than 40 parts of plasticiser to 100 parts of poly(vinyl chloride) | 0 % | — | 31.12.2029 |
| 0.3026 | ex 3920 43 10 | 95 | Reflecting laminated sheet, consisting of a film of poly(vinyl chloride) and a film of an other plastic totally embossed in a regular pyramidal pattern, covered on one side with a release sheet | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.5930 | ex 3920 49 10 | 30 | Film of a (polyvinyl)chloride-copolymer — containing by weight 45 % or more of fillers — on a support | 0 % | — | 31.12.2027 |
| 0.3021 | ex 3920 51 00 | 20 | Plate of poly(methyl methacrylate) containing aluminium trihydroxide, of a thickness of 3,5 mm or more but not more than 19 mm | 0 % | — | 31.12.2029 |
| 0.5506 | ex 3920 51 00 | 30 | Biaxially-oriented film of poly(methyl methacrylate), of a thickness of 50 µm or more but not exceeding 125 µm | 0 % | — | 31.12.2029 |
| 0.5753 | ex 3920 51 00 | 40 | Sheets of polymethylmethacrylate conforming to standard EN 4366 (MIL-PRF-25690) | 0 % | — | 31.12.2029 |
| 0.7949 | *ex 3920 61 00 | 40 | Extruded thermoplastic foils or films of polycarbonate with: — matt surface texture on both sides — a thickness of more than 50 µm but not more than 200 µm, — a width of 800 mm or more, but not more than 1 500 mm, and — a length of 300 m or more, but not more 2 500 m | 0 % | — | 31.12.2030 |
| 0.8274 | ex 3920 61 00 | 50 | Coextruded film of polycarbonate main layer and polymethyl methacrylate top layer with a: — total thickness of more than 230 µm but not more than 270 µm, — top layer thickness of more than 40 µm but not more than 55 µm, — defined surface roughness of the top layer of 0,5 µm or less (according to ISO 4287), — UV-stabilized top layer | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|--------------------------------|----------|---|-------------------------|--------------------|-------------------------------------|
| 0.7418 | ex 3920 62 19 ex 3920 62 90 | 05 10 | Poly(ethylene terephthalate) film in rolls: — with a thickness of 0,335 mm or more but not more than 0,365 mm, and — coated with a gold layer with a thickness of 0,03 µm or more but not more than 0,06 µm | 0 % | — | 31.12.2027 |
| 0.3234 | ex 3920 62 19 | 08 | Poly(ethylene terephthalate) film, not coated with an adhesive, of a thickness of not more than 25 µm, either: — only dyed in the mass, or — dyed in the mass and metallised on one side | 0 % | — | 31.12.2029 |
| 0.8438 | ex 3920 62 19 | 28 | Non-transparent film of poly(ethylene terephthalate) or poly(vinyl difluoride): — each outer layer with a thickness of 7 µm or more but not more than 80 µm, — with a tensile strength of 300 N/cm ² or more (ASTM D-882), — with a total thickness of 200 µm or more but not more than 350 µm, and — with a width of 600 mm or more but not more than 1 600 mm, — covered on one side with a layer of a fluoropolymer, and on the other side with an adhesive and a layer of polyvinylidene difluoride, or coated on both sides with polyvinylidene difluoride or polyvinyl fluoride based on fluorinated polymer composites | 0 % | — | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.4520 | ex 3920 62 19 | 32 | <p>Transparent poly(ethylene terephthalate) film:</p> <ul style="list-style-type: none"> — having thickness of both sides of 7 nm or more but not more than 80 nm, or thickness of both sides of 7 µm or more but not more than 80 µm, whether coated with an acrylic-based organic material or not, — with a surface tension of 36 Dyne/cm or more but not more than 39 Dyne/cm, or transparent 3 or 4 layers, second layer of PET, and other layers contain fluorine resin, — with a light transmittance of more than 70 %, — with a haze value of not more than 1,3 %, — with a total thickness of 10 µm or more but not more than 350 µm, — with a width of 800 mm or more but not more than 1 600 mm | 0 % | — | 31.12.2028 |
| 0.3356 | ex 3920 62 19 | 38 | Poly(ethylene terephthalate) film, of a thickness of not more than 12 µm, coated on one side with a layer of aluminium oxide of a thickness of not more than 35 nm | 0 % | — | 31.12.2029 |
| 0.3357 | *ex 3920 62 19 | 48 | <p>Sheets or rolls of poly(ethylene terephthalate):</p> <ul style="list-style-type: none"> — coated on both sides with a layer of epoxy acrylic resin, — of a total thickness of 37 µm (\pm 3 µm) | 0 % | — | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.2589 | ex 3920 62 19 | 52 | Film of polyethylene terephthalate, polyethylene naphthalate or similar polyester, coated on one side with metal and/or metal oxides, containing by weight less than 0,1 % of aluminium, of a thickness of not more than 300 µm and having a surface resistivity of not more than 10 000 ohms (per square) (as determined by the ASTM D257 method) | 0 % | — | 31.12.2029 |
| 0.4344 | ex 3920 62 19 | 60 | Poly(ethylene terephthalate) film: — of a thickness of not more than 20 µm, — coated on at least one side with a gas barrier layer consisting of a polymeric matrix in which silica or aluminium oxide has been dispersed and of a thickness of not more than 2 µm | 0 % | — | 31.12.2027 |
| 0.8927 | *ex 3920 62 19 | 79 | Reflective film of polyethylene terephthalate, embossed in a pyramidal pattern, with — a thickness of 0,07 mm or more but not more than 0,15 mm — a width of 762 mm or more but not more than 1 350 mm | 0 % | m ² | 31.12.2030 |
| 0.8839 | ex 3920 62 19 | 85 | Three-layer transparent plastic film consisting of a 15 µm fluorinated polymer (FCC) (EVA) layer, a 275 µm polyethylene terephthalate (PET) layer and a 25 µm fluorinated polymer (FCC) layer with: — a total thickness of 300 µm or more, but not more than 330 µm, — a tensile strength of 375 N/cm or more in both the longitudinal and transverse directions (ASTM D-882), — a low thermal shrinkage of 1 % or less at 150 °C for 30 minutes, — a low water vapor permeability of 2,5 g/m ² •d or less, and — a high breakdown voltage of 18 kV or more and — a partial discharge voltage of 1 500 VDC or more (BG/T 123542.2-2009) to be used as a protective layer on the back of photovoltaic modules | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.3328 | ex 3920 69 00 | 20 | Film of poly(ethylene naphthalene-2,6-dicarboxylate) | 0 % | — | 31.12.2029 |
| 0.7882 | ex 3920 69 00 | 30 | Mono- or multilayer, transverse oriented, shrink film: — composed of more than 85 % by weight of polylactic acid, not more than 5 % by weight of inorganic or organic additives and not more than 10 % by weight of additives based on biodegradable polyesters, — with a thickness of 20 µm or more but not more than 100 µm, — with a length of 2 385 m or more but not more than 9 075 m, — biodegradable and compostable (as determined by the method EN 13432) | 0 % | — | 31.12.2029 |
| 0.7883 | ex 3920 69 00 | 70 | Mono- or multilayer, biaxially oriented film: — composed of more than 85 % by weight of polylactic acid, not more than 5 % by weight of inorganic or organic additives, and not more than 10 % by weight of additives based on biodegradable polyesters, — with a thickness of 9 µm or more but not more than 120 µm, — with a length of 1 395 m or more but not more than 21 560 m, — biodegradable and compostable (as determined by the method EN 13432) | 0 % | — | 31.12.2029 |
| 0.4766 | ex 3920 91 00 | 52 | Poly(vinyl butyral) film: — containing by weight 26 % or more but not more than 30 % of triethyleneglycol bis (2-ethyl hexanoate) as a plasticiser, — with a thickness of 0,73 mm or more but not more than 1,50 mm | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.3329 | ex 3920 91 00 | 91 | Poly(vinyl butyral) film having a graduated coloured band | 3 % | — | 31.12.2029 |
| 0.3136 | ex 3920 91 00 | 93 | Film of poly(ethylene terephthalate), whether or not metallised on one or both sides, or laminated film of poly(ethylene terephthalate) films, metallised on the external sides only, and having the following characteristics: — a visible light transmission of 50 % or more, — coated on one or both sides with a layer of poly(vinyl butyral) but not coated with an adhesive or any other material except poly(vinyl butyral), — a total thickness of not more than 0,2 mm without taking the presence of poly(vinyl butyral) into account and a thickness of poly(vinyl butyral) of more than 0,2 mm | 0 % | — | 31.12.2029 |
| 0.4508 | ex 3920 91 00 | 95 | Co-extruded trilayer poly(vinyl butyral) film with a graduated colour band containing by weight 29 % or more but not more than 31 % of 2,2'-ethylenedioxydiethyl bis (2-ethylhexanoate) as a plasticiser | 0 % | — | 31.12.2029 |
| 0.3917 | ex 3920 99 28 | 40 | Polymer film containing the following monomers: — poly (tetramethylene ether glycol), — bis (4-isocyanotocyclohexyl) methane, — 1,4-butanediol or 1,3-butanediol, — with a thickness of 0,25 mm or more but not more than 5,0 mm, — embossed with a regular pattern on one surface, — and covered with a release sheet | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.4192 | *ex 3920 99 28 | 50 | Thermoplastic polyurethane film (TPU) based on an aliphatic polycaprolactone (PCL), transparently backed on one side with a removable protective film (PET film), with a light transmission of more than 93 % (according to DIN EN ISO 13468-1), with a thickness of 25 µm or more but not more than 500 µm | 0 % | m ² | 31.12.2026 |
| 0.6579 | ex 3920 99 28 | 65 | Matt, thermoplastic polyurethane foil in rolls with: <ul style="list-style-type: none"> — a width of 1 640 mm (\pm 10 mm), — a gloss of 3,3 degrees or more but not more than 3,8 (as determined by the method ASTM D2457), — a surface roughness of 1,9 Ra or more but not more than 2,8 Ra (as determined by the method ISO 4287), — a thickness of more than 365 µm but not more than 760 µm, — a hardness of 90 (\pm 4) (as determined by the method: Shore A (ASTM D2240)), — an elongation to break of 470 % (as determined by the method: EN ISO 527) | 0 % | m ² | 31.12.2029 |
| 0.5315 | ex 3920 99 28 | 70 | Sheets on rolls, consisting of epoxy resin, with conducting properties, containing: <ul style="list-style-type: none"> — microspheres with a coating of metal, whether or not alloyed with gold, — an adhesive layer, — with a protective layer of silicone or poly(ethylene terephthalate) on one side, — with a protective layer of poly(ethylene terephthalate) on the other side, and — with a width of 5 cm or more but not more than 100 cm — with a length of not more than 2 000 m | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.3326 | ex 3920 99 59 | 25 | Poly(1-chlorotrifluoroethylene) film | 0 % | — | 31.12.2029 |
| 0.3135 | ex 3920 99 59 | 65 | Film of a vinyl alcohol copolymer, soluble in cold water, of a thickness of 34 µm or more but not more than 90 µm, a tensile strength at break of 20 MPa or more but not more than 55 MPa and an elongation at break of 250 % or more but not more than 900 % | 0 % | — | 31.12.2029 |
| 0.6066 | ex 3921 19 00 | 30 | Blocks with cellular structure, containing by weight: — polyamide-6 or poly(epoxy anhydride) — 7 % or more but not more than 9 % of polytetrafluoroethylene if present — 10 % or more but not more than 25 % of inorganic fillers | 0 % | — | 31.12.2029 |
| 0.7132 | ex 3921 19 00 | 50 | Porous membrane of polytetrafluoroethylene (PTFE) laminated to a polyester spunbonded non-woven cloth with — a total thickness of more than 0,05 mm but not more than 0,20 mm, — a water entry pressure between 5 and 200 kPa according to ISO 811, and — an air permeability of 0,08 cm ³ /cm ² /s or more according to ISO 5636-5 | 0 % | — | 31.12.2026 |
| 0.8913 | *ex 3921 19 00 | 55 | Strip of microporous polytetrafluoroethylene on a support of a non-woven — wound on a roll on a core of 3 inches, — with a width of 69,5 mm, 40,8 mm, 36,5 mm, 20 mm, 13,5 mm or 10 mm for use in the manufacture of filters for kidney dialysis equipment and intravenous application ⁽¹⁾ | 0 % | m ² | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.6911 | *ex 3921 19 00 | 65 | Transparent, microporous, acrylic acid grafted polyethylene film, in the form of rolls, for the manufacture of alkaline battery separators with: — a width of 98 mm or more but not more than 170 mm, — a thickness of 15 µm or more but not more than 36 µm, | 3,2 % | — | 31.12.2026 |
| 0.7263 | *ex 3921 19 00 | 75 | Microporous monolayer film of polypropylene or a microporous trilayer film of polypropylene, polyethylene and polypropylene, each film with: — zero transversal production direction (TD) shrinkage, — a total thickness of 8 µm or more, but not more than 40 µm, — a width of 15 mm or more, but not more than 900 mm, — a length of more than 200 m, but not more than 8 000 m, — an average pore size between 0,02 µm and 0,1 µm, — whether or not laminated with a Polypropylene non-woven mat of 50 to 200 µm thickness, — whether or not coated with surfactant, — whether or not coated on 1 or 2 sides with a ceramic layer of min 1 µm thickness or more, but not more than 5 µm, — whether or not coated on 1 or 2 sides with a sticky binder, PVdF type or similar of min 0,5 µm thickness or more, but not more than 5 µm | 3,2 % | — | 31.12.2026 |
| 0.3002 | ex 3921 19 00 | 95 | Film of polyethersulfone, of a thickness of not more than 200 µm | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.3003 | ex 3921 90 10 | 10 | Composite plate of poly(ethylene terephthalate) or of poly(butylene terephthalate), reinforced with glass fibres | 0 % | — | 31.12.2029 |
| 0.6156 | ex 3921 90 10 | 30 | Multilayer film consisting of: — a poly(ethylene terephthalate) film with a thickness of more than 100 µm but not more than 150 µm, — a primer of phenolic material with a thickness of more than 8 µm but not more than 15 µm, — an adhesive layer of a synthetic rubber with a thickness of more than 20 µm but not more than 30 µm, — and a transparent poly(ethylene terephthalate) liner with a thickness of more than 35 µm but not more than 40 µm | 0 % | m ² | 31.12.2029 |
| 0.4844 | ex 3921 90 55 | 25 | Prepreg sheets or rolls containing polyimide resin | 0 % | — | 31.12.2029 |
| 0.7510 | ex 3921 90 55 | 35 | Glass fiber impregnated with epoxy resin for use in the manufacture of smart cards (¹) | 0 % | m ² | 31.12.2029 |
| 0.6742 | *ex 3921 90 55 | 40 | Three layered fabric sheet, in rolls, — comprising a core layer of 100 % Nylon Taffeta or Nylon/Polyester blended Taffeta, — coated on both sides with polyamide, — of a total thickness not more than 135 µm, — of a total weight not more than 80 g/m ² | 0 % | m ² | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|--------------------------------|----------|--|-------------------------|--------------------|-------------------------------------|
| 0.8291 | ex 3921 90 55 | 70 | Membrane composed of a polyamide layer and a polysulfone layer on a polyethylene terephthalate support layer with: — a total thickness of 0,25 mm or more but not more than 0,40 mm, — a total weight of 109 g/m ² or more but not more than 114 g/m ² | 0 % | m ² | 31.12.2026 |
| 0.5396 | ex 3923 10 90 | 10 | Photomask or wafer compacts: — consisting of antistatic materials or blended thermoplastics proving special electrostatic discharge (ESD) and outgassing properties, — having non porous, abrasion resistant or impact resistant surface properties, — fitted with a specially designed retainer system that protects the photomask or wafers from surface or cosmetic damage and — with or without a gasket seal, of a kind used in the photolithography or other semiconductor production to house photomasks or wafers | 0 % | — | 31.12.2026 |
| 0.7630 | ex 3926 30 00 | 40 | Plastic internal door handle used in the manufacture of motor vehicles ⁽¹⁾ | 0 % | — | 31.12.2029 |
| 0.7335 | ex 3926 30 00 ex 3926 90 97 | 50 48 | Coated interior or exterior decorative parts consisting of: — a copolymer of acrylonitrile-butadiene-styrene (ABS), whether or not mixed with polycarbonate, and — a PVC foil, — not containing layers of copper, nickel or chromium, for use in the manufacturing of parts for motor vehicles of heading 8701 to 8705 ⁽¹⁾ | 0 % | p/st | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.2764 | ex 3926 90 97 | 10 | Microspheres of a polymer of divinylbenzene, of a diameter of 4,5 µm or more but not more than 80 µm | 0 % | — | 31.12.2029 |
| 0.8664 | ex 3926 90 97 | 22 | Gaskets for road vehicles mirrors and their components, made of polyethylene foam, produced by a thermoforming process and with: <ul style="list-style-type: none"> — a density of 20 kg/m³ or more, but not more than 40 kg/m³, — a tensile strength of not less than 170 kPa, — water absorption coefficient of not greater than 1 %, — a length of 5 mm or more but not more than 300 mm, — a height of 10 mm or more but not more than 400 mm, — a depth of 5 mm or more but not more than 250 mm | 0 % | — | 31.12.2028 |
| 0.6717 | *ex 3926 90 97 | 23 | Plastic cover with clips for the exterior rear-view mirror of motor vehicles | 0 % | p/st | 31.12.2030 |
| 0.7445 | ex 3926 90 97 | 27 | Gasket of polyethylene foam, intended to fill-up the space between the body of a motor vehicle and the base of a rear-view mirror | 0 % | — | 31.12.2029 |
| 0.5474 | ex 3926 90 97 | 30 | Parts of car radio and car air-conditioner front panels <ul style="list-style-type: none"> — of acrylonitrile-butadiene-styrene with or without polycarbonate, — coated with a copper, a nickel and a chrome layers, — with a total thickness of coating of 5,54 µm or more but not more than 49,6 µm | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.6301 | ex 3926 90 97 | 33 | Housings, housing parts, drums, setting wheels, frames, covers, upper part, design plate and other parts of acrylonitrile-butadiene-styrene, polycarbonate, polymethylmethacrylate or thermoplastic polyurethane, of a kind used for the manufacture of remote controls | 0 % | p/st | 31.12.2029 |
| 0.7061 | ex 3926 90 97 | 40 | Silicone shell for breast implant | 0 % | — | 31.12.2026 |
| 0.3850 | ex 3926 90 97 | 43 | Mixture of water and by weight 19 % or more but not more than 35 % of expanded hollow microspheres of a copolymer of acrylonitrile, methacrylonitrile and isobornyl methacrylate or other methacrylate, of a diameter of 3 µm or more but not more than 4,95 µm | 0 % | — | 31.12.2029 |
| 0.8118 | ex 3926 90 97 | 58 | Plastic ferrules and/or plugs: — supported with or without a stainless steel ring, — suitable for a maximum working pressure rate of 2,7 MPa or more but not more than 114 MPa, for tubings with: — outer diameter of 0,33 mm or more but not more than 3,3 mm, — suitable for a maximum working pressure rate of 2,7 MPa or more but not more than 114 MPa, — suitable for all solutions used in chromatography, for use in the production of chromatographic systems ⁽¹⁾ | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---|----------------|--|-------------------------|--------------------|-------------------------------------|
| 0.7196 | ex 3926 90 97 | 77 | Silicone decoupling ring with an inner diameter of 14,7 mm or more but not more than 16,0 mm, in immediate packings of 2 500 pieces or more, of a kind used in car parking aid sensor systems | 0 % | p/st | 31.12.2026 |
| 0.8504 | ex 4009 31 00 ex 4009 32 00 | 10 20 | Multilayered rubber pipe, reinforced with aramide fabric, whether or not having polyamide connection elements and steel clamps, for use in the manufacture of automotive heat exchangers and/or condenser in automotive air conditioning systems (¹) | 0 % | — | 31.12.2027 |
| 0.6708 | *ex 4009 42 00 | 20 | Rubber brake hose with: — textile strings, — a wall thickness of 3,2 mm, — a metal hollow terminal pressed on both ends, and — one or more mounting brackets, for use in the manufacture of goods of Chapter 87 (¹) | 0 % | — | 31.12.2026 |
| 0.7042 | ex 4010 31 00 ex 4010 33 00 ex 4010 39 00 | 10 10 10 | Vulcanized rubber endless transmission belt of trapezoidal cross-section (V-belts) with longitudinal V-ribbed pattern on the inner side for use in the manufacture of goods of Chapter 87 (¹) | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.6844 | *ex 4016 93 00 | 30 | Rectangular ethylene-propylene-diene rubber gasket, with: — a length of 72 mm or more but not more than 825 mm, — a width of 18 mm or more but not more than 155 mm, — a peak temperature of 150 °C or more but not more than 240 °C, — a permissible material outflow at the place of the mold split of not more than 0,3 mm | 0 % | — | 31.12.2030 |
| 0.8646 | ex 4016 99 52 | 10 | Hanger of the exhaust muffler consisting of: — a steel bracket with at least one mounting hole and — silent block, for use in the manufacture of goods of Chapter 87 (¹) | 0 % | — | 31.12.2028 |
| 0.7170 | ex 4016 99 57 | 10 | Air intake hose for air supply to the combustion part of the engine comprising at least: — one flexible rubber hose, — one plastic hose, and — metal clips, — whether or not a resonator for use in the manufacture of goods of Chapter 87 (¹) | 0 % | p/st | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|--|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.8925 | *ex 4016 99 57 | 40 | Wiper rubber used in the manufacture of windshield wipers, — made of a mixture of natural rubber and chloroprene rubber — with a Shore hardness of 60A (¹) | 0 % | — | 31.12.2030 |
| 0.5148 | ex 4016 99 97 | 30 | Tyre moulding bladder | 0 % | — | 31.12.2030 |
| 0.5842 | ex 4104 41 19 | 10 | Buffalo leather, split, chrome tanned synthetic retanned ("crust"), dry | 0 % | — | 31.12.2029 |
| 0.2555 | 4105 10 00 4105 30 90 | | Sheep or lamb skin leather, without wool on, tanned or retanned but not further prepared, whether or not split, other than leather of heading 4114 | 0 % | — | 31.12.2029 |
| 0.2553 | 4106 21 00 4106 22 90 | | Goat or kid skin leather, without hair on, tanned or retanned but not further prepared, whether or not split, other than leather of heading 4114 | 0 % | — | 31.12.2029 |
| 0.2554 | 4106 31 00 4106 32 00 4106 40 90 4106 92 00 | | Leather of other animals, without hair on, not further prepared than tanned, other than leather of heading 4114 | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.6223 | ex 4408 39 30 | 10 | <p>Okoumé sheets for veneering for plywood panels</p> <ul style="list-style-type: none"> — with a largest dimension of 900 mm or more, but not more than 3 250 mm, — with a smallest dimension of 95 mm or more but not more than 2 000 mm, — with a thickness of 0,5 mm or more, but not more than 4 mm, — unsanded, — not planed, and — sawn, sliced or peeled lengthwise | 0 % | — | 31.12.2029 |
| 0.8737 | ex 4408 39 95 | 10 | <p>Iroko sheets for veneering for plywood panels:</p> <ul style="list-style-type: none"> — with a largest dimension of 900 mm or more, but not more than 3 250 mm, — with a smallest dimension of 95 mm or more but not more than 2 000 mm, — with a thickness of more than 1 mm, but not more than 4 mm, — unsanded, — not planed, and — sawn, sliced or peeled lengthwise | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.8733 | ex 4408 39 95 | 20 | Igaganga sheets for veneering for plywood panels: — with a largest dimension of 900 mm or more, but not more than 3 250 mm, — with a smallest dimension of 95 mm or more but not more than 2 000 mm, — with a thickness of more than 1 mm, but not more than 4 mm, — unsanded, — not planed, and — sawn, sliced or peeled lengthwise | 0 % | — | 31.12.2029 |
| 0.8738 | ex 4408 39 95 | 30 | Ozigo sheets for veneering for plywood panels: — with a largest dimension of 900 mm or more, but not more than 3 250 mm, — with a smallest dimension of 95 mm or more but not more than 2 000 mm, — with a thickness of more than 1 mm, but not more than 4 mm, — unsanded, — not planed, and — sawn, sliced or peeled lengthwise | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|--------------------------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8372 | ex 4411 12 92 | 10 | Fibreboard: — with a thickness of 2,20 mm or more but not more than 2,80 mm, — with a density of 0,95 g/cm ³ or more, — lacquered or coated with melamine foil on both sides, and — with dimensions of 1 300 mm x 1 100 mm or less | 0 % | — | 31.12.2027 |
| 0.4217 | ex 5004 00 10 | 10 | Silk yarn (other than yarn spun from silk waste) not put up for retail sale, unbleached, scoured or bleached, entirely of silk | 0 % | — | 31.12.2026 |
| 0.2551 | ex 5005 00 10 ex 5005 00 90 | 10 | Yarn spun entirely from silk waste (noil), not put up for retail sale | 0 % | — | 31.12.2029 |
| 0.2544 | 5208 11 10 | | Fabrics for the manufacture of bandages, dressings and medical gauzes | 5,2 % | — | 31.12.2029 |
| 0.7372 | ex 5311 00 90 | 10 | Plain-woven fabric of paper yarns glued on a tissue paper layer: — with a weight of 190 g/m ² or more but not more than 280 g/m ² , and — cut into rectangles with a side length of 40 cm or more but not more than 140 cm | 0 % | — | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8916 | *ex 5402 33 00 | 10 | <p>Textured polyester yarn:</p> <ul style="list-style-type: none"> — textured using single heater and double heater methods in accordance with DIN 53840-T1 standard, — with a linear density of 83 dtex or more, but not more than 666 dtex, — with an average minimum tenacity of 32 cN/tex, — with a filament count of 36 or more, but not more than 192, — with an elongation at break of 16 % or more, but not more than 33 %, — with a boiling water shrinkage of 3 % or more, but not more than 8 %, — containing by weight 1 % or more but not more than 3 % of mineral oil, synthetic oil or mixed oils | 0 % | — | 31.12.2030 |
| 0.2975 | ex 5402 49 00 | 30 | Yarn of a copolymer of glycollic acid with lactic acid, for the manufacture of surgical sutures (¹) | 0 % | — | 31.12.2029 |
| 0.3098 | ex 5402 49 00 | 50 | Non-textured filament yarn of poly(vinyl alcohol) | 0 % | — | 31.12.2029 |
| 0.8108 | *ex 5403 31 00 | 10 | Continuous viscose rayon filament yarn of 105 dtex or more but not more than 117 dtex, and consisting of 36 monofilaments or more but not more than 40 monofilaments | 0 % | — | 31.12.2026 |
| 0.8910 | *ex 5403 31 00 | 20 | <p>Centrifugal viscose rayon filament yarn, with:</p> <ul style="list-style-type: none"> — a linear density of 80 decitex or more, but not more than 88 decitex, and — a filament count of 24 or more, but not more than 36 monofilaments | 0 % | — | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.8225 | ex 5404 19 00 | 60 | Chemically tapered synthetic filaments of polyester with: — a diameter of 0,1 mm or more but not more than 0,6 mm, — a length of 30 mm or more but not more than 120 mm, for use in the manufacture of paintbrushes (¹) | 0 % | — | 31.12.2026 |
| 0.3311 | ex 5404 90 90 | 20 | Strip of polyimide | 0 % | — | 31.12.2029 |
| 0.8382 | ex 5407 30 00 | 10 | Open mesh fabric made of thermally cross-bonded filaments of a polyolefin, with a density of 0,94 g/cm ³ or more, with: — a weight of 21 g/m ² or more but not more than 24 g/m ² , — a width of 560 mm or more but not more than 1 200 mm, — a thickness of 100 µm or more but not more than 120 µm, — an elongation at break of not more than 20 % (ASTM D5034, machine direction), — an elongation at break of not more than 22 % (ASTM D5034, cross direction), — with a stretch of not more than 100 N/5 cm (ASTM D882, machine direction), and — with a stretch of not more than 130 N/5 cm (ASTM D882, cross direction) | 0 % | — | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|--|--|---|-------------------------|--------------------|-------------------------------------|
| 0.3214 | ex 5503 90 00 ex 5506 90 00 ex 5601 30 00 | 20 10 10 | Poly(vinyl alcohol) fibres, whether or not acetalized | 0 % | — | 31.12.2029 |
| 0.3212 | ex 5603 11 10 ex 5603 11 90 ex 5603 12 10 ex 5603 12 90 ex 5603 91 10 ex 5603 91 90 ex 5603 92 10 ex 5603 92 90 | 10 10 10 10 10 10 10 10 | Poly(vinyl alcohol) non-wovens, in the piece or cut into rectangles: — of a thickness of 200 µm or more but not more than 280 µm and — of a weight of 20 g/m ² or more but not more than 50 g/m ² | 0 % | m ² | 31.12.2029 |
| 0.2552 | ex 5603 12 90 ex 5603 13 90 ex 5603 14 80 ex 5603 92 90 ex 5603 93 90 ex 5603 94 80 | 30 30 10 60 40 30 | Non-wovens of aromatic polyamide fibres obtained by polycondensation of <i>m</i> -phenylenediamine and isophthalic acid, in the piece or cut into rectangles | 0 % | m ² | 31.12.2028 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|--------------------------------|----------|--|-------------------------|--------------------|-------------------------------------|
| 0.2548 | ex 5603 12 90 ex 5603 13 90 | 60 60 | Non-woven of spunbonded polyethylene, of a weight of more than 60 g/m ² but not more than 80 g/m ² and an air resistance (Gurley) of 8 seconds or more but not more than 36 seconds (as determined by the ISO 5636/5 method) | 0 % | m ² | 31.12.2029 |
| 0.5059 | *ex 5603 13 10 | 20 | Non-woven of spunbonded polyethylene, with a coating, — of a weight of more than 80 g/m ² but not more than 105 g/m ² and — an air resistance (Gurley) of 8 seconds or more but not more than 75 seconds (as determined by the ISO 5636/5 method) | 0 % | m ² | 31.12.2030 |
| 0.8024 | ex 5603 14 10 | 30 | Non-wovens, consisting of poly(ethylene terephthalate) spun bonded media: — of weight of 160 g/m ² or more but not more than 300 g/m ² , — with a filtration efficiency of class M or better (according to DIN 60335-2-69), — pleatable, with at least one of following treatments: — a coating or covering with polytetrafluoroethylene (PTFE), — a coating with aluminium particles, — a coating of phosphorous based flame retardants, — a nano fiber coating of a polyamide, a polyurethane or a fluorine-containing polymer | 0 % | m ² | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|--------------------------------|----------|--|-------------------------|--------------------|-------------------------------------|
| 0.5987 | ex 5603 14 80 | 60 | Non-wovens, consisting of poly(ethylene terephthalate) spun bonded media: — of weight of 160 g/m ² or more but not more than 300 g/m ² , — with a filtration efficiency of class M or better (according to DIN 60335-2-69), — pleatable, — with or without an expanded polytetrafluoroethylene (ePTFE) membrane | 0 % | m ² | 31.12.2028 |
| 0.3042 | ex 5603 92 90 ex 5603 94 80 | 70 40 | Non-wovens, consisting of multiple layers of a mixture of meltblown fibres and staple fibres of polypropylene and polyester, whether or not laminated on one side or on both sides with spunbonded filaments of polypropylene | 0 % | m ² | 31.12.2028 |
| 0.5197 | ex 5603 92 90 ex 5603 93 90 | 80 50 | Non-woven polyolefin fabric, consisting of an elastomeric layer, laminated on each side with polyolefin filaments: — a weight of 25 g/m ² or more but not more than 150 g/m ² , — in the piece or simply cut into squares or rectangles, — not impregnated, — with cross-directional or machine-directional stretch properties for use in the manufacture of infant/child care products (¹) | 0 % | m ² | 31.12.2026 |
| 0.3210 | ex 5603 94 80 | 20 | Acrylic fibre rods, having a length of not more than 50 cm, for the manufacture of pen tips (¹) | 0 % | m ² | 31.12.2028 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|--------------------------------|----------|---|-------------------------|--------------------|-------------------------------------|
| 0.2415 | ex 5803 00 10 | 91 | Gauze of cotton, of a width of less than 1 500 mm | 0 % | — | 31.12.2029 |
| 0.7081 | ex 5903 20 90 | 20 | Two layers' plastic-laminated textile fabric with: — one layer consisting of knitted or crocheted polyester textile fabric, — other layer consisting of polyurethane foam, — a weight of 150 g/m ² or more, but not more than 500 g/m ² , — a thickness of 1 mm or more, but not more than 5 mm for use in the manufacture of the retractable roof of motor vehicles (¹) | 0 % | — | 31.12.2026 |
| 0.8213 | ex 5906 99 90 | 30 | Woven and coated rubberised textile fabric with the following characteristics: — with three layers, — the outer layers consist of a natural rubber, EPDM and chloropen rubber compound, — the middle layer consists of polyester fabric, for use in the manufacture of life rafts (¹) | 0 % | — | 31.12.2026 |
| 0.2453 | ex 5907 00 00 | 10 | Textile fabrics, coated with adhesive in which are embedded spheres of a diameter of not more than 150 µm | 0 % | — | 31.12.2026 |
| 0.3207 | ex 5911 90 99 ex 8421 99 90 | 30 92 | Parts of equipment for the purification of water by reverse osmosis, consisting essentially of plastic-based membranes, supported internally by woven or non-woven textile materials which are wound round a perforated tube, and enclosed in a cylindrical plastic casing of a wall-thickness of not more than 4 mm, whether or not housed in a cylinder of a wall-thickness of 5 mm or more | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.4638 | ex 5911 90 99 | 40 | Multi-layered non-woven polyester polishing pads, impregnated with polyurethane | 0 % | — | 31.12.2029 |
| 0.7340 | ex 5911 90 99 | 50 | Loudspeaker vibration damper, made from round, corrugated, flexible and cut-to-size tissue of textile fibres of polyester, cotton or aramid or a combination hereof, of a kind used in car loudspeakers | 0 % | — | 31.12.2027 |
| 0.6469 | ex 6804 21 00 | 20 | Discs — of synthetic diamonds which are agglomerated with a metal alloy, ceramic alloy or plastic alloy, — having a self-sharpening effect by constant release of the diamonds, — suitable for abrasive cutting of wafers, — whether or not containing a hole in the centre, — whether or not on a support — with a weight of not more than 377 g per piece and — with an external diameter of not more than 206 mm | 0 % | p/st | 31.12.2029 |
| 0.8666 | ex 6804 21 00 | 40 | Steel wire used for cropping and squaring semiconductors: — coated with diamond grains of 5 µm or more, but not more than 55 µm — wire diameter 23 µm or more but not more than 350 µm, — having a breaking strength of 11 N or more, but not more than 170 N | 0 % | — | 31.12.2028 |
| 0.2755 | ex 6813 89 00 | 20 | Friction material, of a thickness of less than 20 mm, not mounted, for use in the manufacture of friction components (1) | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.5931 | ex 6814 10 00 | 10 | Agglomerated mica with a thickness of not more than 0,15 mm, on rolls, whether or not calcined, whether or not reinforced with aramid fibres | 0 % | — | 31.12.2029 |
| 0.2546 | ex 6903 90 90 | 40 | Silicon carbide reactor tubes and holders having a maximum service temperature of 1 370 °C or more | 0 % | — | 31.12.2029 |
| 0.4978 | *ex 6909 19 00 | 20 | Silicon nitride (Si_3N_4) rollers or balls | 0 % | — | 31.12.2030 |
| 0.6071 | ex 6909 19 00 | 25 | Ceramic proppants, containing aluminium oxide, silicon oxide and iron oxide | 0 % | — | 31.12.2029 |
| 0.3403 | ex 6909 19 00 | 30 | Supports for catalysts, consisting of porous cordierite or mullite ceramic pieces, of an overall volume of not more than 65 l, having, per cm^2 of the cross-section, not less than one continuous channel which may be open at both ends or stopped at one end | 0 % | — | 31.12.2029 |
| 0.8028 | *ex 6909 19 00 | 40 | Ceramic-carbon absorption or adsorption cartridges of fuel motor vehicle systems, with the following characteristics: — extruded fired ceramic bound multicellular cylindrical structure, — 5 % or more by weight but not more than 70 % by weight of activated carbon, — 30 % or more by weight but no more than 90 % by weight of ceramic binder, — with a diameter of 29 mm or more but no more than 41 mm, — a length of not more than 150 mm, — fired at temperature of 800 °C or more | 0 % | p/st | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|--------------------------------|----------|---|-------------------------|--------------------|-------------------------------------|
| 0.2538 | ex 6909 19 00 ex 6914 90 00 | 50 20 | Ceramic articles made of continuous filaments of ceramic oxides, containing by weight: — 2 % or more of diboron trioxide, — 28 % or less of silicon dioxide and — 60 % or more of dialuminium trioxide | 0 % | — | 31.12.2029 |
| 0.3766 | ex 6909 19 00 | 60 | Supports for catalysts, consisting of porous ceramic pieces, of a blend of silicon carbide and silicon, with a hardness of less than 9 on the Mohs scale, with a total volume of not more than 65 litres, having, per cm ² of the surface of the cross section one or more closed channels at the tail end | 0 % | — | 31.12.2029 |
| 0.4582 | ex 6909 19 00 | 70 | Supports for catalysts or filters, consisting of porous ceramics made primarily from oxides of aluminium and titanium; with a total volume of not more than 65 litres and at least one duct (open on one or both ends) per cm ² of cross section | 0 % | — | 31.12.2029 |
| 0.3404 | ex 6914 90 00 | 30 | Ceramic microspheres, transparent, obtained from silicon dioxide and zirconium dioxide, of a diameter of more than 125 µm | 0 % | — | 31.12.2029 |
| 0.8265 | ex 7007 11 10 | 10 | Specifically shaped and toughened safety glass: — with a width of 200 mm or more but not more than 600 mm, — with a height of 150 mm or more but not more than 500 mm, for use in the manufacture of motor vehicle window assemblies (¹) | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8860 | ex 7007 19 80 | 86 | <p>A ready-to-install, circular graded tempered glass of the cover of door assembly in washing machines with:</p> <ul style="list-style-type: none"> — a light transmittance of 34,2 % or more but not more than 37,8 %, — a diameter of 477,2 mm or more but not more than 477,8 mm, — a thickness of 2,9 mm or more but not more than 3,5 mm, — a weight of 1 345 g or more but not more than 1 445 g, — 3-zone structure including Euro Deep Gray colour printed zone (¹) | 0 % | — | 31.12.2029 |
| 0.6380 | ex 7009 10 00 | 30 | <p>Layered glass with mechanical dimming ability by different angles of incident light comprising:</p> <ul style="list-style-type: none"> — whether or not a layer of chrome, — a break-resistance adhesive tape or hot-melt adhesive, and — a release film on the front side and protective paper at the back side, of a kind used for interior rear-view mirrors of vehicles | 0 % | p/st | 31.12.2029 |
| 0.5789 | ex 7009 10 00 | 50 | <p>Unfinished electro-chromic auto-dimming mirror for motor vehicle rear-view mirrors:</p> <ul style="list-style-type: none"> — whether or not equipped with plastic backing plate, — whether or not equipped with a heating element, — whether or not equipped with Blind Spot Module (BSM) display | 0 % | — | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.6870 | *ex 7009 10 00 | 60 | <p>Electrochromic self-dimming inside rear-view mirror:</p> <ul style="list-style-type: none"> — with a mirror support — in a plastic casing and — with an integrated circuit, — whether or not with a high beam assistant, — whether or not with a digital compass, — whether or not with a garage door opener, — whether or not with an integrated toll module, — whether or not with a camera for driver and/or cabin monitoring, — whether or not with an infrared filter, <p>for use in the manufacture of motor vehicles of Chapter 87 (¹)</p> | 0 % | — | 31.12.2030 |
| 0.8663 | ex 7009 91 00 | 10 | <p>Chrome-plated glass mirror with:</p> <ul style="list-style-type: none"> — a length of 155 mm or more, but not more than 158 mm, — a height of 115 mm or more, but not more than 120 mm, — a blind spot sensor with a blind spot motion detection light module, with an edge luminescence greater than or equal to 5 000 cd/m² and a central luminescence greater than or equal to 7 000 cd/m², — a heater foil, with a resistance of 1,1 kΩ or more, but not more than 1,35 kΩ, <p>designed to be mounted in a housing as an exterior vehicle mirror, for use in the manufacture of car mirrors (¹)</p> | 0 % | — | 31.12.2028 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.8682 | ex 7009 91 00 | 20 | Aspherical, convex or flat chrome-plated glass, ready for framing: — with a length of 140 mm or more but not more than 215 mm, — with a height of 104 mm or more but not more than 138 mm, — with curvature radius of 0 mm or more but not more than 1 330 mm, — with a reflectance of more than 40 %, for the manufacture of automotive mirrors (¹) | 0 % | — | 31.12.2028 |
| 0.3400 | ex 7014 00 00 | 10 | Optical elements of glass (other than those of heading 7015), not optically worked, other than signalling glassware | 0 % | — | 31.12.2029 |
| 0.7056 | ex 7019 61 00 | 70 | E-fibre glass fabrics: | 0 % | m ² | 31.12.2026 |
| | ex 7019 63 00 | 30 | — having a weight of 20 g/m ² or more, but not more than 214 g/m ² , — surface treated with an organosilane coupling agent, — in rolls, — having a humidity content by weight of 0,13 % or less, and — having not more than 3 hollow fibres out of 100 000 fibres, for the exclusive use in the manufacture of prepgs and copper clad laminates (¹) | | | |
| 0.7647 | ex 7019 64 00 | 40 | Epoxy resin coated glass woven fabric containing by weight: — 91 % or more but not more than 93 % of glass fibres, — 7 % or more but not more than 9 % of epoxy resin | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|--------------------------------|----------|---|-------------------------|--------------------|-------------------------------------|
| 0.4059 | ex 7019 71 00 ex 7019 72 00 | 50 50 | Non-woven product of non-textile glass fibre, for the manufacture of air filters or catalysts (¹) | 0 % | — | 31.12.2026 |
| 0.8915 | *ex 7019 80 10 | 40 | Vacuum insulated panel consisting of hermetic aluminium foil and stiff core, without air inside, used for thermal reinforcement of fridges and freezers and combination of them, with: — a glass wool filling, — a thickness of 5,6 mm or more but not more than 35 mm, — a length of 195 mm or more but not more than 1 875 mm, — a width of 155 mm or more but not more than 545 mm, — a thermal conductivity lower than or equal to 2,5 mW/mK, — an internal pressure below 1,0 Pa, — an ambient operating temperature of – 50 °C or more but not more than 80 °C | 0 % | p/st | 31.12.2030 |
| 0.3940 | ex 7019 80 90 | 10 | Glass wool in which fibres of a diameter of less than 4,6 µm predominate | 0 % | — | 31.12.2028 |
| 0.4024 | ex 7019 90 00 | 30 | High modulus glass cord (K) impregnated with rubber, obtained from twisted high modulus glass filament yarns, coated with a latex comprising a resorcinol-formaldehyde resin with or without vinylpyridine and/or hydrogenated acrylonitrile-butadiene rubber (HNBR) | 0 % | — | 31.12.2029 |
| 0.8616 | ex 7019 90 00 | 50 | Insulating rigid panels made by vacuum compression of glass fibres wrapped in protective gas-tight film, for use in the manufacture of refrigerators and freezers and their combinations (¹) | 0 % | — | 31.12.2028 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|--------------------------------|----------|---|-------------------------|--------------------|-------------------------------------|
| 0.8903 | *ex 7019 90 00 | 60 | Vacuum insulation panel, consisting of a gas-tight aluminium foil housing surrounding a rigid, air-free core with: — a glass fiber filling, — a thickness of 5,6 mm or more but not more than 32,4 mm, — a length of 195 mm or more but not more than 1 835 mm, — a width of 155 mm or more but not more than 545 mm, — a thermal conductivity lower than or equal to 2,5 mW/mK, — an internal pressure below 1,0 Pa, — an ambient temperature during operation of – 50 °C or more but not more than 80 °C | 0 % | p/st | 31.12.2029 |
| 0.5348 | ex 7020 00 10 ex 7616 99 90 | 10 77 | Television pedestal stands with or without bracket for fixation to and stabilization of television cabinet case/body | 0 % | p/st | 31.12.2026 |
| 0.7266 | ex 7020 00 10 | 20 | Raw material for optical elements of fused silicon dioxide with: — a thickness of 10 cm or more but not more than 40 cm, and — a weight of 100 kg or more | 0 % | p/st | 31.12.2027 |
| 0.4127 | ex 7201 10 11 | 10 | Pig iron ingots with a length of not more than 350 mm, a width of not more than 150 mm, a height of not more than 150 mm | 0 % | — | 31.12.2026 |
| 0.4128 | ex 7201 10 30 | 10 | Pig iron ingots with a length of not more than 350 mm, a width of not more than 150 mm, a height of not more than 150 mm, containing by weight not more than 1 % of silicon | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------------------------|----------|---|-------------------------|--------------------|-------------------------------------|
| 0.3353 | 7202 50 00 | | Ferro-silico-chromium | 0 % | — | 31.12.2029 |
| 0.7502 | ex 7318 24 00 | 40 | Tube or pipe restraint joint elements: — of stainless steel according to specification 17-4PH or of steel according to specification tool steel S7, — produced by metal injection moulding, — with a rockwell hardness of 38 HRC (± 1) or 53 HRC ($+ 2/- 1$), — measuring 7 mm x 4 mm x 5 mm or more, but not more than 40 mm x 20 mm x 10 mm | 0 % | — | 31.12.2029 |
| 0.4126 | ex 7326 20 00 | 20 | Metal fleece, consisting of a mass of stainless steel wires of diameters of 0,001 mm or more but not more than 0,070 mm, compacted by sintering and rolling | 0 % | — | 31.12.2026 |
| 0.6680 | *ex 7326 90 98 ex 7907 00 00 | 40 10 | Iron, steel and/or zinc alloy weights: — with a weight of not more than 500 g and measuring not more than 107 mm x 107 mm x 11 mm, — whether or not with parts of other material, — whether or not with parts of other metals, — whether or not surface treated, — whether or not printed, of a kind used for the production of remote controls | 0 % | — | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.8480 | ex 7326 90 98 | 60 | Vane ring of a kind for fastening gas flow control blades: — of iron or steel alloy, — with a heat resistance of 830 °C or more but not more than 1 050 °C, — with an external diameter of not more than 92 mm, — with holes for holding the gas flow control blades, for use in the manufacture of turbochargers (¹) | 0 % | — | 31.12.2027 |
| 0.8512 | ex 7326 90 98 | 70 | Disc of a kind for ensuring the gas flow channel width: — of iron or steel alloy, — with a heat resistance of 830 °C or more but not more than 1 050 °C, — with an external diameter of not more than 92,5 mm, — with an internal diameter of not more than 62 mm, for use in the manufacture of turbochargers (¹) | 0 % | — | 31.12.2027 |
| 0.3352 | ex 7410 21 00 | 10 | Sheet or plate of polytetrafluoroethylene, containing aluminium oxide or titanium dioxide as filler or reinforced with glass-fibre fabric, covered on both sides with copper foil | 0 % | — | 31.12.2029 |
| 0.7509 | ex 7410 21 00 | 20 | Foils, rolls composed of one layer of glass epoxy of 100 µm colaminated with refined copper foil on one or two sides of 35 µm with a tolerance of 10 % for use in the production of smart cards (¹) | 0 % | m ² | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.3005 | ex 7410 21 00 | 30 | Film of polyimide, whether or not containing epoxide resin and/or glass fibre, covered on one side or on both sides with a copper foil | 0 % | — | 31.12.2029 |
| 0.3926 | ex 7410 21 00 | 40 | Sheet or plates: — consisting of at least a central layer of paper or one central sheet of any type of nonwoven fibre, laminated on each side with glass-fibre fabric and impregnated with epoxide resin, or — consisting of multiple layers of paper, impregnated with phenolic resin, coated on one or both sides with a copper film with a maximum thickness of 0,15 mm | 0 % | — | 31.12.2029 |
| 0.4479 | ex 7410 21 00 | 50 | Plates: — consisting of at least one layer of fibreglass fabric impregnated with thermosetting resin, — covered on one or both sides with copper foil with a thickness of not more than 0,15 mm, and — with a dielectric constant (DK) of less than 3,9 and a loss factor (Df) of less than 0,015 at a measuring frequency of 10 GHz, as measured according to IPC-TM-650 | 0 % | — | 31.12.2029 |
| 0.7341 | ex 7413 00 00 | 20 | Loudspeaker centring ring, consisting of one or more vibration dampers and minimum two non-insulated copper cables, therein woven or pressed | 0 % | — | 31.12.2027 |
| 0.7911 | ex 7506 20 00 | 10 | Sheets and strips in coils of nickel alloy C276 (EN 2.4819) with — a thickness of 0,5 mm or more but not more than 3 mm, — a width of 770 mm or more but not more than 1 250 mm | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|--------------------------------|----------|--|-------------------------|--------------------|-------------------------------------|
| 0.7913 | *ex 7506 20 00 | 20 | Sheets and strips in coils of nickel alloy to standard ASME SB-582/UNS N06030 with: — a thickness of 0,5 mm or more but not more than 3 mm, — a width of 250 mm or more but not more than 1 219 mm | 0 % | — | 31.12.2030 |
| 0.2410 | ex 7605 19 00 | 10 | Not alloyed aluminium wire, of a diameter of 2 mm or more but not more than 6 mm, covered with a layer of copper of a thickness of 0,032 mm or more but not more than 0,117 mm | 0 % | — | 31.12.2029 |
| 0.8344 | ex 7605 21 00 | 10 | Aluminium alloy wire with a diameter of 9,50 mm or more but not more than 19,15 mm, in coils, for use in the manufacture of aeronautical fasteners (¹) | 0 % | — | 31.12.2027 |
| 0.8194 | ex 7609 00 00 ex 8415 90 00 | 30 45 | Aluminium connecting block for automotive air conditioning systems: — with a T6 hardening, — equipped with round stubs with a circumferential outer groove, — with through or non-through holes, made of profiles with an upper radius of 8 mm or more but not more than 11 mm, and a lower radius of 12 mm or more but not more than 17 mm, — with a distance between holes of 15 mm or more but not more than 22 mm, — with sockets designed for brazing or clamping, — with mounting holes for M6 or M8 mounting screw, threaded or not, — with a width of 5 mm or more but not more than 16 mm, — for connecting a compressor, a condenser, an evaporator, a chiller and other lines | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.8464 | ex 7609 00 00 | 40 | <p>Flame brazed aluminium block for connecting tubes in automotive heat exchangers and/or turbocharged air coolers and/or automatic transmission coolers:</p> <ul style="list-style-type: none"> — with extruded, bent connection tubes with an outer diameter of 5 mm or more, but not more than 25 mm, — with a weight of 0,02 kg or more, but not more than 0,25 kg, <p>for use in the manufacture of cooling system in vehicles of Chapter 87 ⁽¹⁾</p> | 0 % | p/st | 31.12.2027 |
| 0.8503 | ex 7609 00 00 | 50 | <p>Machined aluminium components:</p> <ul style="list-style-type: none"> — containing by weight 0,55 %, or more but not more than 0,61 % of magnesium, — containing by weight 0,55 %, or more but not more than 0,61 % of silicon, — with a hardening state of T5 or T6, — with a mass of 0,05 kg or more, but not more than 0,2 kg, <p>for use in the manufacture of CO₂ cooling systems in motor vehicles ⁽¹⁾</p> | 0 % | p/st | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---|----------------|---|-------------------------|--------------------|-------------------------------------|
| 0.8493 | ex 7609 00 00 | 60 | <p>Aluminium connection block:</p> <ul style="list-style-type: none"> — with a weight of 3 g or more but not more than 400 g, — manufactured from 6061-T6 or 6060-T6 or 6082-T6 aluminium grade, — being an integral part of an air conditioning hose assembly or oil cooling line hose assembly or air brake line hose assembly or water cooling line hose assembly, — with holes (sockets) or splines (pilots) or threads that allow installation in an automotive or other air conditioning system (also understood as installation in the line), — with sockets designed for brazing or fastening, — with at least 1 through-hole with a diameter of 3 mm or more but not more than 25 mm, for the manufacture of automotive cooling and air conditioning systems (¹) | 0 % | p/st | 31.12.2027 |
| 0.5357 | ex 7616 99 90 ex 8482 80 00 ex 8807 30 00 | 70 10 40 | Connecting components for use in the production of helicopter tail rotor shafts (¹) | 0 % | p/st | 31.12.2026 |
| 0.6730 | *ex 8101 96 00 | 10 | <p>Tungsten wire containing by weight 99 % or more of tungsten with:</p> <ul style="list-style-type: none"> — a maximum cross-sectional dimension of not more than 50 µm — a resistance of 40 Ω or more but not more than 300 Ω at length of 1 metre | 0 % | — | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.7245 | ex 8101 96 00 | 20 | Tungsten wire — containing by weight 99,95 % or more of tungsten, and — with a maximum cross-sectional dimension of not more than 1,02 mm | 0 % | — | 31.12.2027 |
| 0.5694 | ex 8102 10 00 | 10 | Molybdenum powder with: — a purity by weight of 99 % or more and — a particle size of 1,0 µm or more, but not more than 5,0 µm | 0 % | — | 31.12.2027 |
| 0.5097 | ex 8104 30 00 | 35 | Magnesium powder: — of purity by weight of more than 99,5 %, and — with a particle size of not more than 0,8 mm | 0 % | — | 31.12.2030 |
| 0.3416 | ex 8108 20 00 | 10 | Titanium sponge | 0 % | — | 31.12.2029 |
| 0.4553 | ex 8108 20 00 | 30 | Titanium powder of which 90 % by weight or more passes through a sieve with an aperture of 0,224 mm | 0 % | — | 31.12.2029 |
| 0.3211 | ex 8108 30 00 | 10 | Waste and scrap of titanium and titanium alloys, except those containing by weight 1 % or more but not more than 2 % of aluminium | 0 % | — | 31.12.2029 |
| 0.4363 | ex 8108 90 30 | 10 | Titanium alloy rods complying with standard EN 2002-1, EN 4267 or DIN 65040 | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.7330 | ex 8108 90 30 | 15 | Rods and wire of an alloy of titanium with: — a uniform solid cross-section in the form of a cylinder, — with a diameter of 0,8 mm or more, but not more than 5 mm, — an aluminium content by weight of 0,3 % or more, but not more than 0,7 %, — a silicon content by weight of 0,3 % or more, but not more than 0,6 %, — a niobium content by weight of 0,1 or more, but not more than 0,3 %, and — an iron content by weight of not more than 0,2 % | 0 % | — | 31.12.2027 |
| 0.7942 | *ex 8108 90 30 | 35 | Bars and wires of titanium with a titanium content of 98,8 % or more but not more than 99,9 % of a diameter less than 20 mm | 0 % | — | 31.12.2030 |
| 0.4904 | *ex 8108 90 30 | 45 | Titanium-aluminium-vanadium alloy (TiAl6V4) wire, of a diameter less than 20 mm and complying with AMS standards 4928, 4965 or 4967 | 0 % | — | 31.12.2030 |
| 0.8105 | *ex 8108 90 30 | 55 | Wires of an alloy of titanium: — with a niobium content by weight of 42 % or more, but not more than 47 %, — with a diameter of 2,36 mm or more, but not more than 7,85 mm, — in coils of 15 kg or more, but not more than 45 kg, — complying with standard AMS 4982 | 0 % | — | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.7077 | ex 8108 90 30 | 60 | Forged cylindrical bars of titanium with: — a purity of 99,995 % by weight or more, — a diameter of 140 mm or more but not more than 200 mm, — a weight of 5 kg or more but not more than 300 kg | 0 % | p/st | 31.12.2026 |
| 0.5351 | ex 8108 90 30 | 70 | Wire of an titanium alloy containing by weight: — 22 % (± 1 %) of vanadium, and — 4 % ($\pm 0,5$ %) of aluminium or — 15 % (± 1 %) of vanadium, — 3 % ($\pm 0,5$ %) of chromium, — 3 % ($\pm 0,5$ %) of tin and — 3 % ($\pm 0,5$ %) of aluminium | 0 % | — | 31.12.2026 |
| 0.7285 | ex 8108 90 50 | 45 | Cold or hot rolled plates, sheets and strips of non-alloyed titanium with: — a thickness of 0,4 mm or more, but not more than 100 mm, — a length of not more than 14 m, and — a width of not more than 4 m | 0 % | — | 31.12.2027 |
| 0.5352 | ex 8108 90 50 | 55 | Plates, sheets, strip and foil of an alloy of titanium | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|--------------------------------|----------|---|-------------------------|--------------------|-------------------------------------|
| 0.6524 | ex 8108 90 50 | 80 | Plates, sheets, strips and foil of non-alloyed titanium — of a width of more than 750 mm, — of a thickness of not more than 3 mm | 0 % | — | 31.12.2029 |
| 0.6500 | ex 8108 90 50 | 85 | Strip or foil of non-alloyed titanium: — containing more than 0,07 % by weight of oxygen (O ₂), — of a thickness of 0,4 mm or more but not more than 2,5 mm — conforming to the Vickers hardness HV1 standard of not more than 170 of a kind used in the manufacture of welded tubes for nuclear power plant condensers | 0 % | — | 31.12.2029 |
| 0.5353 | ex 8108 90 90 ex 9003 90 00 | 30 20 | Parts of spectacle frames and mountings, including — temples, — blanks of a kind used for the manufacture of spectacle parts and — bolts of the kind used for spectacle frames and mountings, of a titanium alloy | 0 % | p/st | 31.12.2026 |
| 0.8909 | *ex 8109 29 00 | 10 | Non-alloy zirconium sponges or ingots containing by weight more than 0,01 % of hafnium for use in the manufacture of tubes, bars or ingots enlarged by remelting for the non-nuclear industry ⁽¹⁾ | 0 % | — | 31.12.2030 |
| 0.3415 | ex 8110 10 00 | 10 | Antimony in the form of ingots | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|--|--|--|-------------------------|--------------------|-------------------------------------|
| 0.3413 | ex 8112 99 50 | 10 | Alloy of niobium (columbium) and titanium, in the form of bars and rods | 0 % | — | 31.12.2029 |
| 0.4316 | ex 8113 00 90 | 10 | Carrier plate of aluminium silicon carbide (AlSiC-9) for electronic circuits | 0 % | — | 31.12.2027 |
| 0.6805 | *ex 8113 00 90 | 20 | Cuboid spacer made of aluminium silicon carbide (AlSiC) composite used for packaging in IGBT-modules | 0 % | — | 31.12.2030 |
| 0.5570 | ex 8207 30 10 | 10 | Set of transfer and/or tandem press tools for cold-forming, pressing, drawing, cutting, punching, bending, calibrating, bordering and throating of metal sheets, for use in the manufacture of frame parts or body parts of motor vehicles (¹) | 0 % | p/st | 31.12.2027 |
| 0.5024 | *ex 8301 60 00 ex 8419 90 85 ex 8479 90 70 ex 8481 90 00 ex 8485 90 90 ex 8503 00 99 ex 8515 90 80 ex 8537 10 98 ex 8538 90 99 ex 8708 99 10 ex 8708 99 97 | 30 40 30 50 30 43 40 55 70 55 22 | Silicone or plastic keyboards, comprising: — parts of common metal, and — whether or not comprising parts of plastic, — epoxy resin reinforced with fiberglass or wood, — whether or not printed or surface-treated, — with or without electrical conductors, — with or without a membrane bonded to the keyboard, — with or without mono or multilayer protective film | 0 % | p/st | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8247 | ex 8302 10 00 | 20 | Armrest hinge made of magnesium with: — a length of 239 mm or more but not more than 270 mm, — a width of 150 mm or more but not more than 175 mm, — a height of 110 mm or more but not more than 135 mm, — mounting holes for a lock mechanism | 0 % | — | 31.12.2026 |
| 0.8304 | ex 8302 30 00 | 20 | Two cold-formed steel supports: — with a length of 120 mm or more but not more than 180 mm, — with a width of 50 mm or more but not more than 80 mm, — with a height of 35 mm or more but not more than 80 mm, — with a movable riveted connection, — with or without elastomeric bumper, — forming a mechanism for indirect movement of the mechanism of the longitudinal positioner of car seats, interacting with the safety latch, — attached to the mechanism of the longitudinal positioner by means of a detachable screw connection, riveting, welding or spot welding | 0 % | — | 31.12.2026 |
| 0.2602 | ex 8309 90 90 | 10 | Aluminium can ends: — with a diameter of 99,00 mm or more but not more than 136,5 mm (± 1 mm), — whether or not with a “ring-pull” aperture | 0 % | p/st | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.3947 | *ex 8401 30 00 | 20 | Non-irradiated hexagonal fuel modules (elements) for use in nuclear reactors (¹) | 0 % | — | 31.12.2029 |
| 0.6319 | ex 8401 40 00 | 10 | Stainless steel absorber control rods, filled with neutron absorbing chemical elements | 0 % | p/st | 31.12.2029 |
| 0.8668 | ex 8402 90 00 | 10 | Pre-assembled process module unit of an ethane cracker unit, containing: <ul style="list-style-type: none"> — a dilution steam generator system which produces steam from pretreated quench water for use as dilution steam in steam cracking furnaces, — a condensate system that collects, filters and deaerates steam condensates, which are subsequently recycled as boiler feed water and further distributed within the cracker unit, and — a flare system that collects, separates and vaporizes non-recyclable hydrocarbon containing releases from different equipment in a steam cracker, and transfers those towards flares | 0 % | — | 30.06.2026 |
| 0.8818 | ex 8406 81 00 | 10 | Industrial steam turbine with: <ul style="list-style-type: none"> — an output of more than 40 MW but not more than 90 MW, — designed for a pressure of not more than 165 bar and a temperature of not more than 565 °C, — equipped with double seat valves on the live steam side which are operated with a hydraulic servo of not more than 30 bar | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|--|----------------------|---|-------------------------|--------------------|-------------------------------------|
| 0.8012 | *ex 8406 82 00 | 10 | Industrial steam turbine with: <ul style="list-style-type: none"> — an output of 2 MW or more but not more than 40 MW, — designed for a pressure of not more than 140 bar and a temperature of not more than 540 °C, — equipped with single – or double seat valves on the live steam side which are operated with a hydraulic servo of not more than 30 bar | 0 % | — | 31.12.2030 |
| 0.3830 | ex 8407 33 20 ex 8407 33 80 ex 8407 90 80 ex 8407 90 90 | 10 10 10 10 | Spark-ignition reciprocating or rotary internal combustion piston engines, having a cylinder capacity of not less than 300 cm ³ and a power of not less than 6 kW or more but not more than 20,0 kW, for the manufacture of: <ul style="list-style-type: none"> — lawn mowers of subheadings 8433 11, 8433 19 and 8433 20, — tractors of subheadings 8701 91 90, 8701 92 90 whose main function is that of a lawn mower, — four stroke mowers with motor of a cylinder capacity of not less than 300 cm³ of subheading 8433 20 10 or — snowploughs and snow blowers of subheading 8430 20 (¹) | 0 % | — | 31.12.2027 |
| 0.8753 | ex 8407 33 80 | 20 | New, single-cylinder, four stroke, spark-ignition internal combustion engine with: <ul style="list-style-type: none"> — a cylinder capacity exceeding 500 cm³ but not exceeding 1 000 cm³, — overall dimensions of not more than: 490 mm (length) x 390 mm (width) x 590 mm (height), — a power of 22 kW or more but not more than 35 kW, — equipped with output shaft having an end diameter of 30 mm and a taper of 6 degrees (± 1 degree), — whether or not equipped with starter, throttle body, spark plug wire, fuel rail and injector, for use in the manufacture of all-terrain or utility task vehicles (¹) | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.8754 | ex 8407 33 80 | 30 | <p>New, twin-cylinder, four-stroke, spark-ignition internal combustion engine with:</p> <ul style="list-style-type: none"> — a cylinder capacity exceeding 500 cm³ but not exceeding 1 000 cm³, — overall dimensions of not more than: 470 mm (length) x 450 mm (width) x 600 mm (height), — a power of 40 kW or more but not more than 86 kW, — whether or not equipped with overhead camshaft, starter motor, spark plug wires, fuel rail and injectors, <p>for use in the manufacture of all-terrain or utility task vehicles (¹)</p> | 0 % | — | 31.12.2029 |
| 0.8260 | ex 8407 34 10 | 10 | <p>Spark-ignition reciprocating or rotary internal combustion piston engines, with:</p> <ul style="list-style-type: none"> — a cylinder capacity of 1 200 cm³ or more but not more than 2 000 cm³ — a power of 95 kW but not more than 135 kW, — a weight of not more than 120 kg, <p>for use in the manufacture of motor vehicles of heading 8703 (¹)</p> | 0 % | — | 31.12.2026 |
| 0.8751 | ex 8407 34 91 | 10 | <p>New dual cylinder, four stroke internal combustion spark-ignition engine with:</p> <ul style="list-style-type: none"> — a cylinder capacity exceeding 1 000 cm³ but not exceeding 1 250 cm³, — overall dimensions of not more than: 700 mm (length) x 430 mm (width) x 610 mm (height), — a power of 60 kW or more but not more than 110 kW, — whether or not equipped with a starter, outfitted with a throttle body, two or more fuel injectors, a stator, <p>for use in the manufacture of motorcycle bikes (¹)</p> | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8750 | ex 8407 34 99 | 10 | <p>New dual cylinder, air cooled, four stroke 49 degree V-twin internal combustion spark-ignition engine with:</p> <ul style="list-style-type: none"> — a cylinder capacity exceeding 1 800 cm³, — overall dimensions of not more than: 800 mm (length) x 500 mm (width) x 600 mm (height), — a power of 60 kW or more but not more than 75kW, — equipped with a dry sump system with an intermediate wet receptacle, — whether or not equipped with a starter, outfitted with a throttle body, two or more fuel injectors, a stator, <p>for use in the manufacture of motorcycle bikes (¹)</p> | 0 % | — | 31.12.2029 |
| 0.3828 | ex 8407 90 10 | 10 | Four-stroke petrol engines of a cylinder capacity of not more than 250 cm ³ for use in the manufacture of garden equipment of heading 8432, 8433, 8436 or 8508 (¹) | 0 % | — | 31.12.2026 |
| 0.8403 | ex 8407 90 10 | 40 | <p>A power unit with a two-stroke engine with:</p> <ul style="list-style-type: none"> — an output of 900 W or more, but not more than 1 100 W, — a cylinder displacement of more than 24 cm³ but not more than 30 cm³, — a rotation speed of more than 8 400 rpm but not more than 8 600 rpm at maximum power, — an idling speed of more than 2 800 rpm but not more than 3 200 rpm, and — a fuel tank with a capacity of 0,5 l or more, <p>for use in the manufacture of garden machinery and garden machinery components (¹)</p> | 0 % | — | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.4996 | *ex 8407 90 90 | 20 | Compact Liquid Petroleum Gas (LPG) Engine System, with: — 6 cylinders, — an output of 75 kW or more, but not more than 80 kW, — inlet and exhaust valves modified to operate continuously in heavy duty applications, for use in the manufacture of vehicles of heading 8427 (¹) | 0 % | — | 31.12.2030 |
| 0.8300 | ex 8408 90 65 | 20 | Compression-ignition internal combustion piston engines: — of the inline type, | 0 % | — | 31.12.2026 |
| | ex 8408 90 67 | 20 | — with a cylinder capacity of 7 000 cm ³ or more but not more than 18 100 cm ³ , | | | |
| | ex 8408 90 81 | 20 | — with a power of 205 kW or more but not more than 597 kW, — with an exhaust after-treatment module, — with external width/height/depth dimensions of not more than 1 310/ 1 300/1 040 mm or 2 005/1 505/1 300 mm or 2 005/1 505/1 800 mm, for use in the manufacture of crushing, screening, separation or compost turning machines (¹) | | | |
| 0.8610 | ex 8409 91 00 | 28 | Carburetor with: — 2 mounting holes with a diameter of 31 mm, — a choke bore diameter of 18 mm or more, but not more than 19,05 mm for use in the manufacture of a two-stroke engine grass trimmer (¹) | 0 % | — | 31.12.2028 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|--------------------------------|----------|--|-------------------------|--------------------|-------------------------------------|
| 0.8466 | ex 8409 91 00 | 33 | Camshaft carrier for a spark-ignition piston internal combustion engine, made of ADC12 aluminium alloy, with: — a weight of 4,0 kg or more but not more than 5,5 kg, — a wall thickness of 2,0 mm or more but not more than 6,0 mm, for use in the manufacture of motor vehicle engines (¹) | 0 % | p/st | 31.12.2027 |
| 0.8216 | ex 8409 91 00 | 35 | Fuel distribution pipe complete consisting of rail pipe, high pressure sensor and injectors for direct gasoline fuel injection with: — an operating pressure of not more than 22,5 MPa, — solenoid direct injector, — analog pressure sensor for not more than 22,5 MPa | 0 % | — | 31.12.2026 |
| 0.8469 | ex 8409 91 00 | 38 | Crankcase for 4-cylinder spark-ignition piston internal combustion engine, made of ADC12 aluminium alloy, for use in the manufacture of motor vehicle engines (¹) | 0 % | — | 31.12.2027 |
| 0.7027 | ex 8409 91 00 | 40 | Fuel injector with solenoid valve for optimized atomization in the combustion chamber for use in the manufacture of spark-ignition internal combustion piston engines of motor vehicles (¹) | 0 % | — | 31.12.2026 |
| 0.7234 | ex 8409 91 00 ex 8409 99 00 | 45 70 | Metal alloy intake and exhaust valve, with a Rockwell hardness HRC 20 or more, for use in the manufacture of spark or compression ignition engines of motor vehicles (¹) | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------------------------|----------|--|-------------------------|--------------------|-------------------------------------|
| 0.6752 | ex 8409 91 00 ex 8409 99 00 | 50 55 | Exhaust manifold with turbine housing of turbochargers, with a hole to insert a turbine wheel, whereby the hole has a diameter of 28 mm or more, but not more than 181 mm | 0 % | p/st | 31.12.2029 |
| 0.7961 | *ex 8409 91 00 ex 8481 90 00 | 55 60 | Nozzle body for the regulation of angle and distribution of fuel injection: — of a cylindrical shape, — made of stainless steel, — with 4 or more, but not more than 16 holes, — with a flow rate of 100 cm ³ /minute or more, but not more than 500 cm ³ /minute | 0 % | — | 31.12.2030 |
| 0.7965 | *ex 8409 91 00 | 75 | Housing of fuel injection valve for generating an electromagnetic field to actuate the injection valve with: — an inlet diameter of 2 mm or more, but not more than 10 mm, — an outlet diameter of 2 mm or more, but not more than 10 mm, — an electric coil with a resistance of 10 Ω or more, but not more than 15 Ω, which ends in an electrical connection, — a plastic covering moulded around a stainless steel tube | 0 % | — | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------------------------|----------|---|-------------------------|--------------------|-------------------------------------|
| 0.7967 | *ex 8409 91 00 ex 8481 90 00 | 80 70 | Nozzle needle for opening and closing the flow of fuel in the engine, with: — 2 holes, — 4 grooves, — a diameter of 3 mm or more, but not more than 6 mm, — a length of 25 mm or more, but not more than 35 mm, — made of stainless steel with hard-chrome plating | 0 % | — | 31.12.2030 |
| 0.5199 | ex 8409 99 00 ex 8479 90 70 | 10 85 | Injectors with solenoid valve for optimised atomisation in the engine combustion chamber | 0 % | p/st | 31.12.2026 |
| 0.7667 | ex 8409 99 00 | 35 | The exhaust gas recirculation assembly consisting of: — a control unit, — an air throttle, — an intake pipe, — an outlet hose, for use in the manufacture of compression-ignition combustion engines of motor vehicles ⁽¹⁾ | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.7718 | ex 8409 99 00 | 75 | High pressure fuel rail of galvanised ferrite-pearlite steel with: — at least one pressure sensor and one valve, — a length of 314 mm or more but not more than 322 mm, — an operating pressure not more than 225 MPa, — an inlet temperature not more than 95 °C, — ambient temperature of – 45 °C or more but not more than 145 °C, for use in the manufacture of compression ignition engines of motor vehicles (¹) | 0 % | — | 31.12.2029 |
| 0.6751 | ex 8411 99 00 | 20 | Wheel-shaped gas turbine component with blades, of a kind used in turbochargers: — of a precision-cast nickel based alloy complying with standard DIN G- NiCr13Al6MoNb or DIN G- NiCr13Al16MoNb or DIN G- NiCo10W10Cr9AlTi or DIN G- NiCr12Al6MoNb or AMS AISI:686, — with a heat-resistance of not more than 1 100 °C, — with a diameter of 28 mm or more, but not more than 180 mm, — with a height of 20 mm or more, but not more than 150 mm | 0 % | p/st | 31.12.2027 |
| 0.7225 | ex 8411 99 00 | 30 | Turbine housing of turbochargers, with a hole to insert a turbine wheel, whereby the hole has a diameter of 28 mm or more, but not more than 181 mm | 0 % | p/st | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8851 | ex 8412 21 80 | 30 | Linear acting hydraulic cylinder of a kind used in the machines for handling cargo containers: — with a weight of 45 kg or more but not more than 57 kg, — with a diameter of 119 mm or more but not more than 149 mm, — with a length of 779 mm or more but not more than 1 141 mm, — with a stroke of 450 mm or more but not more than 610 mm, — adapted to work with hydraulic oil at a working pressure of 22 MPa or more but not more than 23 MPa, — whether or not with a maintenance-free bearing without the need for lubrication | 0 % | — | 31.12.2029 |
| 0.8850 | ex 8412 21 80 | 40 | Linear acting hydraulic cylinder of a kind used in the arms of machines for handling cargo containers: — with a weight of 827 kg or more but not more than 935 kg, — with a diameter of 250 mm or more but not more than 330 mm, — with a length of 3 480 mm or more but not more than 4 115 mm, — with a stroke of 2 750 mm or more but not more than 3 180 mm, — adapted to work with hydraulic oil at a working pressure of 23 MPa, — whether or not with a maintenance-free bearing without the need for lubrication | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.5975 | ex 8412 39 00 | 20 | <p>Actuator for a single-stage turbocharger, with:</p> <ul style="list-style-type: none"> — a pressure inlet pipe and a control rod with a working stroke of 15 mm or more but not more than 40 mm, — a maximum length of the actuator including control rod of not more than 400 mm, — a maximum diameter of the can at the widest point of not more than 140 mm, and — a maximum height of the can without control rod of not more than 140 mm | 0 % | p/st | 31.12.2029 |
| 0.8148 | ex 8412 90 70 | 20 | <p>Bedplate made of solution strengthened ductile iron castings (SSDI), for anchoring and aligning the drive train (gearbox, pedestal bearing, rotor shaft) of a wind turbine with:</p> <ul style="list-style-type: none"> — a length of 3,5 m or more but not more than 4,5 m, — a width of 2 m or more but not more than 4,2 m, — a height of 1 m or more, but not more than 1,3 m, — a weight of 11 tons or more but not more than 21,5 tons, — mounting bores for yawdrive, — a mounting flange for gearbox support, — drivetrain mount, — different screw sockets | 0 % | p/st | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8079 | *ex 8412 90 70 | 30 | <p>Gearbox support used as a support and load-carrying component between the gearbox and the bedplate of a wind turbine, made of solution strengthened ductile iron castings (SSDI), with:</p> <ul style="list-style-type: none"> — a diameter of 2 m or more, but not more than 5 m, — a weight of 2 tons or more but not more than 7 tons | 0 % | p/st | 31.12.2030 |
| 0.7161 | ex 8413 30 20 | 30 | <p>Single-cylinder radial-piston high pressure pump for gasoline direct injection with:</p> <ul style="list-style-type: none"> — an operating pressure of 200 bar or more, but not more than 350 bar, — a flow control, and — a pressure relief valve, <p>for use in the manufacture of engines of motor vehicles (¹)</p> | 0 % | — | 31.12.2026 |
| 0.7969 | *ex 8413 30 20 | 40 | <p>High-pressure plunger pump for direct diesel injection, with:</p> <ul style="list-style-type: none"> — an operating pressure of not more than 275 MPa, — a camshaft, — a fluid discharging of 15 cm³ per minute or more, but not more than 1 800 cm³ per minute, — an electric pressure regulating valve | 0 % | — | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.8215 | ex 8413 30 20 | 60 | High-pressure plunger pump for direct petrol injection: — with an operating pressure of not more than 90 MPa, — designed to contact the crankshaft, — with an electromagnetic valve | 0 % | — | 31.12.2026 |
| 0.8332 | ex 8413 30 80 | 20 | Electric water pump ensuring the functionality of the water circuit also when the motor is temporarily switched off, for operating DC voltage of 9 V or more but not more than 16 V, with: — capacity - pressure 0,075 MPa at 3 800 rpm, — discharge of 12 l/min, — whether or not with connecting cable with connector, and — mounting bracket, for use in the manufacture of goods of Chapter 87 (¹) | 0 % | — | 31.12.2027 |
| 0.8185 | ex 8413 70 51 | 20 | Electric brushless direct current motor with single-stage, radial flow pump centrifugal single entry impeller mounted on motor's shaft and volute with integrated heater of nominal power of 1 800 W and soldered safety devices, monobloc with the motor, with: — a discharge outlet diameter of 20 mm or more, — 9 slots stator, — 6 pole rotor, — rated power of 95 W, — volute with straight outlet, — rotor chamber without sand filter | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.8186 | ex 8413 70 51 | 30 | <p>Electric brushless direct current motor with single-stage, radial flow pump centrifugal single entry impeller mounted on motor's shaft and volute with integrated heater of nominal power of 1 800 W and soldered safety devices, monobloc with the motor, with:</p> <ul style="list-style-type: none"> — a discharge outlet diameter of 20 mm or more, — 9 slots stator, — 6 pole rotor, — rated power of 95 W, — volute with clamped rubber hose outlet, — rotor chamber without sand filter | 0 % | — | 31.12.2026 |
| 0.8187 | ex 8413 70 51 | 40 | <p>Electric brushless direct current motor with single-stage, radial flow pump centrifugal single entry impeller mounted on motor's shaft, monobloc with the motor, volute with integrated heater, with:</p> <ul style="list-style-type: none"> — a discharge outlet diameter of 20 mm or more, — 9 slots square or chain pole stator, — 6 pole rotor, — ferritic or rare earth magnets, — rated power of 95 W or 80 W, — heater of nominal power of 1 800 W and soldered or laser welded safety devices, — volute with or without clamped rubber outlet, — rotor chamber with ultrasonic welded sand filter | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.6346 | ex 8413 91 00 | 30 | <p>Fuel pump cover:</p> <ul style="list-style-type: none"> — consisting of aluminium alloys, — with a diameter of 38 mm or 50 mm, — with two concentric, annular grooves formed on its surface, — anodized, <p>of a kind used in motor vehicles with petrol engines</p> | 0 % | p/st | 31.12.2029 |
| 0.7669 | ex 8414 10 25 | 30 | <p>Tandem pump consisting of:</p> <ul style="list-style-type: none"> — an oil pump with displacement of 21,6 cc/rev (\pm 2 cc/rev) and working pressure 1,5 bar at 1 000 revolutions per minute, — vacuum pump with displacement of 120 cc/rev (\pm 12 cc/rev) and performance of -666 mbar in 6 seconds at 750 revolutions per minute <p>for use in the manufacture of engines of motor vehicles ⁽¹⁾</p> | 0 % | — | 31.12.2029 |
| 0.4727 | ex 8414 30 81 | 50 | Hermetic or semi-hermetic variable-speed electric scroll compressors, with a nominal power rating of 0,5 kW or more but not more than 10 kW, with a displacement volume of not more than 35 cm ³ , of the type used in refrigeration equipment | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|--------------------------------|----------|---|-------------------------|--------------------|-------------------------------------|
| 0.6160 | ex 8414 30 81 ex 8414 80 73 | 60 30 | Hermetic rotary compressors for either hydrofluorocarbon (HFC) or hydrocarbon refrigerants: — driven by “on-off” single phase alternate current (AC) or “brushless direct current” (BLDC) variable speed motors, — with a nominal power rating of not more than 1,5 kW, — a rated voltage of 100 V or more but not more than 240 V, — with a height of not more than 300 mm, — an external diameter of not more than 150 mm, — with a unit weight of not more than 15 kg, for use in the manufacture of heat pumps for household appliances, including clothes dryers ⁽¹⁾ | 0 % | — | 31.12.2029 |
| 0.2593 | ex 8414 30 89 | 20 | Vehicle air conditioning system part, consisting of an open shaft reciprocating compressor of a power of more than 0,4 kW but not more than 10 kW | 0 % | — | 31.12.2029 |
| 0.8899 | ex 8414 30 89 | 40 | Electrical compressor for motor vehicle air conditioning system: — with a power output of more than 0,4 kW but not exceeding 10 kW, for use in the manufacture of motor vehicles of subheading 8703 40 ⁽¹⁾ | 0 % | p/st | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8651 | ex 8414 59 25 | 50 | <p>Axial fans with built-in motor, for the generation of an air flow for the cooling of compressors and the distribution of air with</p> <ul style="list-style-type: none"> — a direct current operating voltage of more than 10 V but not more than 14 V, or — an alternating current operating voltage of more than 185 V, but not more than 254 V, — an operating temperature of -40°C or higher, but not higher than 70°C, <p>for use in the manufacture of heat pump tumble dryers and refrigerators or freezers (¹)</p> | 0 % | — | 31.12.2028 |
| 0.8988 | *ex 8414 59 25 | 60 | <p>Axial Fan, for incorporation into instrument clusters, speedometers and infotainment systems of transport vehicles as motor vehicles of headings 8701 to 8705, with:</p> <ul style="list-style-type: none"> — an air flow of not more than $0,75 \text{ m}^3/\text{min}$ (cubic meter per minute) — an air pressure of not more than $10 \text{ mm H}_2\text{O}$ — an overall acoustic noise of not more than 45 dB(A) — a diameter of not more than 65 mm <p>Equipped with DC Brushless motor with:</p> <ul style="list-style-type: none"> — a rated voltage between: 3 to 16 VDC — an operating voltage between: 3 to 16 VDC — a rated current between: 0,03 to 0,30 A — an input power between: 0,3 to 1,5 W — a rotation speed between: 2 500 to 10 000 rpm, <p>With or without a heat sink incorporated</p> | 0 % | p/st | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.7595 | ex 8414 59 35 | 20 | <p>Radial fan, with:</p> <ul style="list-style-type: none"> — a dimension of 25 mm (height) x 85 mm (width) x 85 mm (depth), — a weight of 120 g, — a rated voltage of 13,6 VDC (direct current voltage), — an operating voltage of 9 VDC or more but not more than 16 VDC (direct current voltage), — a rated current of 1,1 A (TYP), — a rated power of 15 W, — a rotation speed of 500 rpm (revolutions per minute) or more but not more than 4 800 rpm (revolutions per minute) (free flow), — an air flow of not more than 17,5 litre/s, — an air pressure of not more than 16 mm H₂O ≈ 157 Pa, — an overall sound pressure of not more than 58 dB(A) at 4 800 rpm (revolutions per minute), and <p>with a FIN (Fan Interconnect Network) interface for communication with the heating and air-conditioning control unit used in car seat ventilation systems</p> | 0 % | — | 31.12.2029 |
| 0.8207 | ex 8414 59 35 | 30 | <p>Electric blower for cooling the high-voltage battery of a hybrid passenger car with:</p> <ul style="list-style-type: none"> — a control unit, — MOSFET inverter, — a voltage of 9 V or more but not more than 16 V, — ambient temperature of – 40 °C or more, but not more than 80 °C, <p>for use in the manufacture of hybrid passenger cars (¹)</p> | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8648 | ex 8414 59 35 | 40 | <p>Electric blower for cooling the battery module:</p> <ul style="list-style-type: none"> — with an operating voltage of 9 VDC or more but not more than 16 VDC, — with a centrifugal electric fan, — with a connector, — with a plastic case, — with or without a control unit for the fan electric motor, <p>for use in the production of rechargeable batteries for hybrid and electric vehicles ⁽¹⁾</p> | 0 % | — | 31.12.2028 |
| 0.7317 | ex 8414 80 22 | 20 | <p>Air membrane compressor with:</p> <ul style="list-style-type: none"> — a flow of 4,5 l/min or more, but not more than 12 l/min, — power input of not more than 14 W, and — a gauge pressure capacity not exceeding 400 hPa (0,4 bar), <p>of a kind used in the production of motor vehicle seats</p> | 0 % | — | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8133 | *ex 8414 80 73 | 50 | Hermetic heat pump compressor for R450A or R290 refrigerants: — not charged with refrigerant, — pre-charged with lubricant oil, — with a single phase induction permanent split capacitor motor or a DC brushless motor, — having suction and/or discharge connections, — with a displacement of 8,05 cm ³ or more, but not more than 55 cm ³ , — running at 900 rpm or more, but not more than 7 800 rpm, and — with a cooling capacity of 920 W or more, but not more than 10 440 W in ASHRAE conditions | 0 % | — | 31.12.2030 |
| 0.8483 | ex 8414 90 00 | 15 | Fan assembly made of aluminium and magnesium alloy: — with an outer diameter of 54 mm or more but not more than 130 mm, — with a height of 8 mm or more but not more than 30 mm, — with two discs connected by blades of involute shape, — with or without dowel, and with or without washer, for use in the manufacture of electromotors (¹) | 0 % | — | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.2507 | ex 8414 90 00 | 20 | Aluminium pistons, for incorporation into compressors of air conditioning machines of motor vehicles (¹) | 0 % | p/st | 31.12.2029 |
| 0.8494 | ex 8414 90 00 | 25 | Scroll type compressor housing of an aluminium alloy of a kind with: — a heat resistance of 200 °C or more but not more than 250 °C, — one or more fixing points suitable for mounting an actuator, for use in the manufacture of turbochargers (¹) | 0 % | — | 31.12.2027 |
| 0.8792 | ex 8414 90 00 | 35 | Compressor head unit made of impregnated aluminium alloy for installation in air-conditioning compressors for motor vehicles with: — a width of 115 mm or more but not more than 160 mm, — a length of 115 mm or more but not more than 170 mm, — a height of 30 mm or more but not more than 100 mm, — a piece of pressure branch with pipe connection, — one or two mounting holes and — more than one overflowing hole | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.8785 | ex 8414 90 00 | 45 | <p>Pressure casted rotor front plate or cover of an electric supercharger:</p> <ul style="list-style-type: none"> — of EN AC-46000 aluminium, — shot-blasted and machined, — with a hardness of 60 or more on the Hardness Brinell Wolfram (HBW) scale (2,5/62,5, according to ISO 6506), — with a tensile strength of 240 N/mm² or more, — with a height of 22 mm or more but not more than 26 mm, — with a diameter of 128 mm or more but not more than 136 mm, — with a weight of 220 g or more but not more than 250 g | 0 % | — | 31.12.2029 |
| 0.8964 | *ex 8414 90 00 | 55 | <p>Air conditioning compressor housing component made of aluminium alloy for installation in electric air conditioning compressors for motor vehicles:</p> <ul style="list-style-type: none"> — with a width of 100 mm or more but not more than 220 mm, — with a length of 100 mm or more but not more than 230 mm, — with a height of 80 mm or more but not more than 180 mm, — with one single central bore, — machined by CNC milling or unwrought, — whether or not impregnated, — with one suction port or without | 0 % | — | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.8465 | ex 8415 90 00 | 15 | <p>Electrically welded manifolds for the condenser in automotive air conditioning systems:</p> <ul style="list-style-type: none"> — consisting of a tube produced by stamping an aluminium strip and joining the edges by electric arc welding, — containing internal baffles responsible for the proper flow of coolant, — with a length of 190 mm or more, but not more than 460 mm, — with a diameter of 9 mm or more, but not more than 42 mm, — with a weight of 0,01 kg or more, but not more than 0,45 kg, — whether or not having aluminium connection blocks, <p>used in the production of air conditioning systems in vehicles of Chapter 87 (¹)</p> | 0 % | p/st | 31.12.2027 |
| 0.6842 | *ex 8415 90 00 | 60 | <p>Flame-soldered aluminium block, for connecting tube with condenser in car air-conditioning systems, with:</p> <ul style="list-style-type: none"> — extruded, bent connector lines of aluminium with an external diameter of 5 mm or more, but not more than 25 mm, — a weight of 0,02 kg or more but not more than 0,25 kg | 0 % | p/st | 31.12.2030 |
| 0.7996 | *ex 8418 99 90 | 20 | <p>Aluminium connecting block for connecting to a condenser manifold in welding process:</p> <ul style="list-style-type: none"> — hardened to T6 or T5 temper, — with a weight of not more than 150 g, — with a length of 20 mm or more but not more than 150 mm, — with a fixing rail in one piece | 0 % | p/st | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8004 | *ex 8418 99 90 | 30 | Receiver dryer profile for connecting to a condenser manifold in welding process with: — a braze flatness of not more than 0,2 mm, — a weight of 100 g or more but not more than 600 g, — a fixing rail in one piece | 0 % | p/st | 31.12.2030 |
| 0.8856 | ex 8418 99 90 | 40 | An evaporator being a type of heat exchanger, consisting of aluminium pipes with copper ends enclosed with aluminium radiators: — measuring 403 x 276 x 70 mm or more, but not more than 464 x 399 x 83 mm, — with a total weight of a set of 236 g or more, but not more than 1 010 g, — with a fixed sensor, — with noise absorber, — with 2, 5 or 7 control and power connection pins terminated with sensor temperature, heater or fuse type of socket, for use in the manufacture of products of subheadings 8418 10, 8418 21, 8418 40 (¹) | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8976 | *ex 8418 99 90 | 50 | <p>Heat exchanger evaporator, used in domestic refrigerators and freezers and their combinations:</p> <ul style="list-style-type: none"> — with external dimensions of 362 mm x 244 mm x 60 mm or more but not more than 398,4 mm x 503 mm x 60 mm, — with 229 mm to 307 mm aluminium radiator fins with external dimensions of 60 mm x 26,7 mm or more but not more than 60,2 mm x 27,3 mm, — with an aluminium tube with an external diameter of 8,3 mm or more but not more than 8,5 mm, — with not more than two heaters with a power of 40 W or more but not more than 140 W, equipped with cables with connectors, — with or without two thermal fuses with a melting point of 77 °C, equipped with cables with connectors | 0 % | — | 31.12.2030 |
| 0.8978 | *ex 8418 99 90 | 60 | <p>Condenser for refrigerators or refrigerators with freezers of the household type equipped at least with:</p> <ul style="list-style-type: none"> — a steel pipe with a diameter from 4,68 mm to 4,81 mm, a wall thickness from 0,52 mm to 0,65 mm, — 26-30 pcs of horizontal pipe sections, each straight with a length from 450 mm to 455 mm, placed every 40 mm between each horizontal part, — from 112 to 174 pcs welded steel rods with a diameter of 1,3 mm and a length of 1 002 mm or more but not more than 1 322 mm, — 3 clips, — 4 brackets welded between the rods | 0 % | — | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.8669 | ex 8419 40 00 | 10 | <p>Pre-assembled process module unit of an ethane cracker unit, containing:</p> <ul style="list-style-type: none"> — quench water circulation loops, which contain a heat exchanger and circulation pumps to cool and recirculate quench water, — a water purification system, which removes hydrocarbon contaminants from quench water which is then re-used for dilution steam production (outside the module), — a pyrolysis oil purification system, which separates pyrolysis gasoline, heavy oil and coke fractions from the hydrocarbon contaminants that have been removed from the quench water, — an ethane feedstock start-up vaporizer and superheater, which vaporizes and heats ethane feedstock before sending the ethane to the cracking furnaces (outside the module), — a propane feedstock preparation system, which filters, vaporizes and superheats propane feedstock, before sending the propane to cracking furnaces (outside the module), and — a chemical grade propylene preparation system, which filters and dries chemical grade propylene before sending it to the deethanizer (outside the module) | 0 % | — | 30.06.2026 |
| 0.8680 | ex 8419 50 80 | 20 | <p>Pre-assembled process module unit of an ethane cracker unit, containing:</p> <ul style="list-style-type: none"> — an open loop ethylene refrigeration system, which is to be integrated with an external ethylene refrigerant compressor, — pumps and a heat exchanger to deliver ethylene to an external pipeline, and — a closed loop propylene refrigeration system, which is to be integrated with an external propylene refrigerant compressor | 0 % | — | 30.06.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.8747 | *ex 8419 50 80 | 30 | <p>Aluminium heat exchanger for gas boilers designed for heat transfer:</p> <ul style="list-style-type: none"> — with a height of 100 mm or more, but not more than 150 mm, — with a width of 235 mm or more, but not more than 300 mm, — with a length of 240 mm or more, but not more than 300 mm, — for a power output of 25 kW or more, but not more than 35 kW, — with a weight of 8 kg or more, but not more than 10 kg | 0 % | — | 31.12.2029 |
| 0.8675 | ex 8419 89 98 | 10 | <p>Pre-assembled process module unit of an ethane cracker unit, containing:</p> <p>equipment associated with an external multi-stage, centrifugal cracked gas compressor which compresses hydrocarbon gases to allow further processing downstream in interconnected equipment containing:</p> <ul style="list-style-type: none"> — coolers, — vapor-liquid separation drums, and — pumps needed to condense and remove water and heavier hydrocarbons and to avoid undesirable formation of polymer by-products, <p>equipment associated with an external caustic wash tower containing:</p> <ul style="list-style-type: none"> — caustic water circulation pumps to support an external caustic wash tower in removing acid gasses (carbon dioxide and hydrogen sulphide) from the cracked gas, — a spent caustic pre-treatment system, containing separation drums, pumps and mixers, — a heat exchanger for the pre-cooling of cracked gas, and — a separation drum for the removal of water from cracker gas | 0 % | — | 30.06.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.6193 | ex 8431 20 00 | 40 | Aluminium core, plastic tank radiator, with integral steel support structure and an open core square wave design of 9 fins per 2,54 cm of core length for use in the manufacture of vehicles of heading 8427 (¹) | 0 % | p/st | 31.12.2029 |
| 0.8853 | ex 8431 20 00 | 70 | Container spreader for lifting empty 20' and 40' cargo containers: — without an integrated carriage, — suitable for machines with a load capacity of not more than 11 000 kg, — designed to carry one or two containers at a time, — with a top or side mounting, — with an anti-corrosion layer coated, — with a weight of 3 200 kg or more but not more than 4 000 kg for use in the manufacture of self-propelled container handlers (¹) | 0 % | — | 31.12.2029 |
| 0.6821 | *ex 8436 99 00 | 10 | Part containing: — a single-phase AC motor, — an epicyclic gearing, — a cutter blade, and whether or not containing: — a capacitor, — a part fitted with a threaded bolt, for use in the manufacture of garden shredders (¹) | 0 % | p/st | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.3374 | ex 8439 99 00 | 10 | Suction-roll shells, produced by centrifugal casting, not drilled, in the form of alloy-steel tubes, of a length of 3 000 mm or more and an external diameter of 550 mm or more | 0 % | p/st | 31.12.2029 |
| 0.8632 | ex 8467 99 00 | 10 | Pole hedge trimmer cutting elements: — in the form of hedge trimmer attachment, — with a knife length of 60 cm and teeth opening of 30 mm, — with angle adjustment of the blade, — with integrated single stage gearbox, — with a magnesium cast body, for use in the manufacture of garden machinery and power tools ⁽¹⁾ | 0 % | — | 31.12.2028 |
| 0.2599 | ex 8477 80 99 | 10 | Machines for casting or for surface modification of plastic membranes of heading 3921 | 0 % | p/st | 31.12.2029 |
| 0.8123 | *ex 8479 89 97 | 28 | Integrated electric brake unit for immediate generation of the hydraulic pressure during braking, full electronic brake control and enabling regenerative braking of motor vehicles with: — electronic brake assistants, — hydraulic unit driven by brushless electric motor, — brake fluid reservoir, for use in the manufacture of hybrid passenger cars ⁽¹⁾ | 0 % | — | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|--------------------------------|----------|---|-------------------------|--------------------|-------------------------------------|
| 0.8673 | ex 8479 89 97 | 33 | <p>Pre-assembled process module unit of an ethane cracker unit, containing:</p> <ul style="list-style-type: none"> — various distillation columns (depropanizer, debutanizer and degreenoiler) and their associated heat exchangers, pumps and drums, — a chilling train containing heat exchangers and a drum which condenses C2 in a gas stream, — a system to separate hydrogen and methane from cracked gas containing heat exchangers, drums, turbines, compressors and a hydrogen purification unit (pressure swing adsorption unit), — associated equipment of a C3 splitter distillation column, containing heat exchanger, pumps and drums, and — a vinyl acetylene hydrogenation system, containing hydrogenation reactors, filters, mixer, drum, condenser, heat exchangers | 0 % | — | 30.06.2026 |
| 0.8206 | ex 8479 89 97 ex 8501 31 00 | 38 68 | <p>Camshaft actuator for controlling the timing of valve opening by using electromotor in a continuous variable valve timing system of an internal combustion piston engine, of:</p> <ul style="list-style-type: none"> — a length of 110 mm or more but not more than 140 mm, — a width of 90 mm or more but not more than 130 mm, — a height of 80 mm or more but not more than 110 mm <p>for use in the manufacture of engines of motor vehicles (¹)</p> | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.8681 | ex 8479 89 97 | 43 | Pre-assembled process module unit of an ethane cracker unit, containing: — a system for filtering and cooling of dried cracked gas, — a deethanizer distillation column and associated equipment for C ₂ -/C ₃ + separation, — an acetylene hydrogenation system to remove acetylene within a C ₂ stream, — a fuel gas drum that stores fuel gas for cracker furnaces, and — a system to regenerate dryers in a cracker installation | 0 % | — | 30.06.2026 |
| 0.6230 | ex 8479 89 97 | 60 | Bioreactor for biopharmaceutical cell culture — having interior surfaces of austenitic stainless steel, and — with a process capacity up to 15 000 litres, — whether or not combined with a “clean-in-process” system and/or a dedicated paired media hold vessel | 0 % | p/st | 31.12.2026 |
| 0.7964 | *ex 8479 90 70 | 40 | Housing of the rotor part of the mechanical unit ensuring the adjustment of movement of the camshaft compared to the crankshaft: — of a circular shape, — made of steel alloy with sintering process, — with not more than 8 oil chambers, — with a Rockwell hardness of 55 or more, — with a density of 6,5 g/cm ³ , or more, but not more than 6,7 g/cm ³ | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------------------------|----------|---|-------------------------|--------------------|-------------------------------------|
| 0.7424 | ex 8481 10 99 | 40 | Pressure reducing valves in a brass case with: — a length of not more than 30 mm (± 1 mm), — a width of not more than 18 mm (± 1 mm), of a kind used for incorporation in fuel delivery modules of motor vehicles | 0 % | — | 31.12.2027 |
| 0.7968 | *ex 8481 30 91 ex 8481 30 99 | 30 50 | Mechanical check (non-return) valve for opening and closing of the flow of fuel: — with an operating pressure of not more than 250 MPa, — with a flow rate of 45 cm ³ /minute or more, but not more than 55 cm ³ /minute, — with 4 input holes, each of them with a diameter of 1,2 mm or more, but not more than 1,6 mm, — made of steel | 0 % | — | 31.12.2026 |
| 0.4668 | ex 8481 30 91 | 91 | Steel check (non-return) valves with: — an opening pressure of not more than 800 kPa, — an external diameter not more than 37 mm | 0 % | p/st | 31.12.2029 |
| 0.7155 | ex 8481 80 59 | 20 | Pressure regulating valve for incorporation into compressors of motor vehicle air condition units ⁽¹⁾ | 0 % | p/st | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.7380 | ex 8481 80 59 | 30 | Two-way flow control valve with housing, with: — at least 5, but not more than 16 outlet holes with at least 0,05 mm, but not more than 0,5 mm diameter, — at least 330 cm ³ /minute, but not more than 5 000 cm ³ /minute flow rate, — at least 19, but not more than 300 MPa operating pressure | 0 % | — | 31.12.2029 |
| 0.7377 | ex 8481 80 59 | 40 | Flow-control valve: — made of steel, — with an outlet hole with a diameter of 0,05 mm or more, but not more than 0,5 mm, — with an inlet hole with a diameter of 0,1 mm or more, but not more than 1,3 mm, — with chromium nitride coating, — with a surface roughness of Rp 0,4 | 0 % | — | 31.12.2027 |
| 0.7381 | ex 8481 80 59 | 50 | Electromagnetic valve for quantity control with: — a plunger, — a solenoid with a coil resistance of at least 1,85 Ohm, but not more than 8,2 Ohm | 0 % | — | 31.12.2027 |
| 0.7382 | ex 8481 80 59 | 60 | Electromagnetic valve for quantity control — with a solenoid with a coil resistance of at least 0,19 Ohm, but not more than 0,66 Ohm, and with an inductance of not more than 1 mH | 0 % | — | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------------------------|----------|--|-------------------------|--------------------|-------------------------------------|
| 0.7960 | *ex 8481 80 59 ex 8481 90 00 | 70 80 | Flow-control valve <ul style="list-style-type: none">— made of steel,— with an outlet hole with a diameter of at least 0,05 mm, but not more than 0,5 mm,— with an inlet hole with a diameter of at least 0,1 mm, but not more than 1,3 mm | 0 % | — | 31.12.2030 |
| 0.8814 | ex 8481 80 59 | 80 | Solenoid valve for combustion engine oil pump to regulate the quantity of oil in the pump: <ul style="list-style-type: none">— with a cable of length of 550 mm or more but not more than 700 mm incorporating an electrical connector,— with an operating pressure of not more than 5,5 bar,— with an operating voltage of 9 VDC or more but not more than 16 VDC,— with a valve's base width of 22 mm or more but not more than 27 mm,— with a valve's length of 55 mm or more but not more than 110 mm, for use in the manufacture of motor vehicle engines (¹) | 0 % | — | 31.12.2029 |
| 0.5575 | ex 8481 80 69 | 60 | Four-way reversing valve for refrigerants, consisting of: <ul style="list-style-type: none">— a solenoid pilot valve— a brass valve body including valve slider and copper connections with a working pressure up to 4,5 MPa | 0 % | p/st | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|--------------------------------|----------|--|-------------------------|--------------------|-------------------------------------|
| 0.7519 | ex 8481 80 73 ex 8481 80 99 | 20 70 | Pressure- and flow-control valve controlled by external electromagnet: — made of steel and/or steel alloy(s), — without integrated circuit, — of not more than 1 000 kPa operating pressure, — with a flow quantity of not more than 5 l/min, — without an electromagnet | 0 % | — | 31.12.2029 |
| 0.8956 | *ex 8481 80 79 | 40 | Service valve which suits for R410A or R32 gas while connecting indoor and outdoor units with: — a withstanding pressure of the valve body of 6,3 MPa, — a leakage ratio of less than 1,6 g/a, — an impurity ratio of less than 1,2 mg/PCS, — an airtight pressure of the valve body of 4,2 Mpa for use in the manufacture of air conditioners ⁽¹⁾ | 0 % | — | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.8752 | ex 8481 80 99 | 80 | <p>Solenoid valve for combustion engine continuous variable valve timing system to control oil flow as a function of engine speed and load:</p> <ul style="list-style-type: none"> — in metal cover, — with electrical connector, — with a force of not more than 10 N, — with an operating voltage of 9 VDC or more but not more than 16 VDC, — with a length of 80 mm or more but not more than 110 mm, — with a width of 80 mm or more but not more than 110 mm, — with a height of 20 mm or more but not more than 30 mm, <p>for use in the manufacture of engines of motor vehicles ⁽¹⁾</p> | 0 % | — | 31.12.2029 |
| 0.8784 | ex 8481 90 00 | 25 | <p>Die-cast aluminium housing for electronic throttle control or exhaust gas recirculation systems, comprising the following features:</p> <ul style="list-style-type: none"> — high-pressure die-cast aluminium EN AC-46000, — shot-blasted and machined, — height of 100 mm or more but not exceeding 135 mm, — width of 115 mm or more but not exceeding 150 mm, — weight of 210 g or more but not more than 500 g | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.7735 | ex 8482 10 10 | 15 | <p>Ball bearings with:</p> <ul style="list-style-type: none"> — an internal diameter of 4 mm or more but not more than 9 mm, — an external diameter of not more than 26 mm, — a width of not more than 8 mm, <p>for use in the manufacture of electromotors with a range of 40 000 rpm or more but not more than 80 000 rpm (¹)</p> | 0 % | — | 31.12.2029 |
| 0.8098 | *ex 8482 50 00 | 20 | <p>Axial roller bearing made of steel:</p> <ul style="list-style-type: none"> — the retainer is made of cold-rolled steel with a carbon content of up to 0,25 percent, complying with standard ASTM A109-98, — the rollers are made of anti-friction steel according to ASTM 295-94, — with an external diameter of 63 mm or more but not more than 66 mm, — with an internal diameter of 44 mm or more but not more than 46 mm, — with a weight of 23 g or more but not more than 27 g, — with 36 rollers or more but not more than 38 rollers | 0 % | p/st | 31.12.2030 |
| 0.8588 | ex 8483 10 95 | 30 | <p>Steel alloy splined shaft (torque shaft) with straight teeth and involute profile, with:</p> <ul style="list-style-type: none"> — external toothing in a diametral pitch standard, — 17 teeth or more, but not more than 50 teeth, — a diameter of 35 mm or more, but not more than 145 mm, — a length of 200 mm or more, but not more than 1 345 mm, — a hardness of 35 HRC or more, but not more than 45 HRC | 0 % | — | 31.12.2028 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8746 | ex 8483 10 95 | 40 | Stepped shaft made of carbon steel with: — rolled, involute profiled, splined shaft end, the helix angle of which is at least $0^{\circ}15,5'$ but not more than $0^{\circ}21,5'$, — a largest diameter of 16 mm or more, but not more than 18 mm, — a length of 137 mm or more, but not more than 155 mm, — a weight of 0,12 kg or more, but not more than 0,28 kg | 0 % | — | 31.12.2029 |
| 0.8857 | ex 8483 10 95 | 50 | Drum shaft for torque transmission, in steel (to SM45C for shaft standard and STS430 for ring standard) with: — a length of 137,8 mm or more but not more than 138,2 mm, — an outer diameter of 23 mm or more but not more than 48,025 mm, — a weight of 1,0245 kg or more but not more than 1,0445 kg, — a hardness of the shaft of 40 or more on the Rockwell C hardness scale (HRC), but not more than 50 HRC, — a ring hardness of 90 or more on the Rockwell B hardness scale (HRB), but not more than 120 HRB, — an external 37-teeth spline with major diameter of 41 mm or more but not more than 48 mm | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|--------------------------------|----------|--|-------------------------|--------------------|-------------------------------------|
| 0.5744 | ex 8483 30 32 ex 8483 30 38 | 30 60 | <p>Bearing housing of a kind used in turbochargers:</p> <ul style="list-style-type: none"> — of precision-cast grey cast iron complying with standard DIN EN 1561 or precision-cast ductile cast iron complying with DIN EN 1560, — with oil chambers, — without bearings, — with a diameter of 50 mm or more, but not more than 250 mm, — with a height of 40 mm or more, but not more than 150 mm, — whether or not with water chambers and connectors | 0 % | p/st | 31.12.2027 |
| 0.8626 | ex 8483 40 23 | 20 | <p>Bevel gear:</p> <ul style="list-style-type: none"> — made of lightweight alloys and steel, — built on straight or helical bevel gears, — with an angle between the shafts of 30 degrees or more but not more than 90 degrees — with a gear 1:1,3 ratio or more but not more than 1:1,46, <p>for use in the manufacture of grass trimmers, brushcutters and other types of garden machinery (¹)</p> | 0 % | — | 31.12.2028 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8625 | ex 8483 40 23 | 30 | <p>Bevel gear:</p> <ul style="list-style-type: none"> — made of lightweight alloys and steel, — built on straight bevel gears, — with an angle between the shafts of 24 degrees or more but not more than 35 degrees, for use in the manufacture of grass trimmers, brushcutters and other types of garden machinery (¹) | 0 % | — | 31.12.2028 |
| 0.8303 | ex 8483 40 25 | 20 | <p>Worm gearbox:</p> <ul style="list-style-type: none"> — in an aluminium alloy housing, — with a plastic or steel worm, — with mounting holes, — with a 90 degree reversible drive direction, — with a 4:19 transmission ratio, — equipped with a lead screw with a length of 310 mm or more but not more than 380 mm, — with a guide nut incorporated into the assembly bracket, — with or without a lead screw support, <p>for indirect connection to the drive motor of a car seat guide system (¹)</p> | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.5202 | ex 8483 40 29 | 50 | Gear set of cycloid gear type with: — a rated torque of 50 Nm or more but not more than 9 000 Nm, — standard ratios of 1:50 or more but not more than 1:475, — lost motion of not more than one arc minute, — an efficiency of more than 80 % of a kind used in robot arms | 0 % | p/st | 31.12.2026 |
| 0.5977 | ex 8483 40 29 | 60 | Epicyclic gearing, of a kind used in driving hand-held power tools with: — a rated torque of 25 Nm or more, but not more than 70 Nm, — standard gear ratios of 1:12,7 or more, but not more than 1:65,3 | 0 % | p/st | 31.12.2029 |
| 0.8585 | ex 8483 40 29 | 70 | Cast steel planetary cage, with: — external or internal toothings in a diametral pitch standard, — 27 teeth or more, but not more than 70 teeth, — a diameter of 300 mm or more, but not more than 725 mm, — a length of 225 mm or more, but not more than 800 mm, — 3 or 4 planetary gears, — a hardness of 40 HRC or more, but not more than 45 HRC | 0 % | — | 31.12.2028 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.7920 | ex 8483 40 59 | 30 | <p>Hydrostatic speed changer:</p> <ul style="list-style-type: none"> — with a hydro pump and a differential with wheel axle, — whether or not with a fan impeller and/or a pulley, <p>for use in the manufacture of lawn mowers of subheadings 8433 11 and 8433 19 or other mowers of subheading 8433 20⁽¹⁾</p> | 0 % | p/st | 31.12.2029 |
| 0.4997 | *ex 8483 40 90 | 80 | <p>Transmission gearbox, with:</p> <ul style="list-style-type: none"> — not more than 3 gears, — an automatic deceleration system, and — a power reversal system, <p>for use in the manufacture of goods of heading 8427⁽¹⁾</p> | 0 % | p/st | 31.12.2030 |
| 0.8100 | *ex 8483 50 80 | 20 | <p>Pulley blocks of non-cast steel:</p> <ul style="list-style-type: none"> — made of structural carbon steel complying with standard JIS G4051, — with an external diameter of 104 mm or more but not more than 142 mm, — with an internal diameter of 33 mm or more but not more than 37 mm, — with a width of 22 mm or more but not more than 40 mm, — with a weight of 0,4 kg or more but not more than 1,6 kg, — with 4 trapezoidal grooves or more but not more than 7 | 0 % | p/st | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8540 | ex 8483 50 80 | 30 | <p>Mechanical tensioner for maintaining the tension of the drive belts of a passenger car engine:</p> <ul style="list-style-type: none"> — with two pulleys made of polyamide, each of them with a diameter of 50 mm or more but not more than 70 mm, — with a spring made of a steel alloy containing chromium and silicon, — with two arms made of aluminium, — with a holder made of aluminium, <p>for use in the manufacture of motor vehicle engines (¹)</p> | 0 % | — | 31.12.2028 |
| 0.8984 | *ex 8483 50 80 | 40 | <p>Flywheel designed for damping torsional vibrations and oscillations within a vehicle drivetrain with:</p> <ul style="list-style-type: none"> — a total moment of inertia of $0,082 \text{ kg}\cdot\text{m}^2$, — a weight of 7 kg or more, but not more than 8 kg, — a diameter of 250 mm or more, but not more than 280 mm, <p>for use in the manufacture of motor vehicles (¹)</p> | 0 % | — | 31.12.2030 |
| 0.8209 | ex 8483 90 89 | 20 | <p>Sprocket for continuous variable valve timing to optimize the process of filling the cylinders of an internal combustion engine with:</p> <ul style="list-style-type: none"> — case, — rotor, — at least 4 screws, — spring, — of an external diameter of 80 mm or more but not exceeding 95 mm, — of a thickness of 25 mm or more but not more than 35 mm, <p>for use in the manufacture of engines of motor vehicles (¹)</p> | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.8584 | ex 8483 90 89 | 30 | <p>Forged steel sprockets with external toothing, whether or not with internal splines in a diametral pitch standard, with:</p> <ul style="list-style-type: none"> — a diameter of 400 mm or more, but not more than 630 mm, — 7 teeth or more, but not more than 15 teeth, — a tooth core hardness of 28 HRC or more, but not more than 45 HRC, — a tooth surface hardness of 50 HRC or more, but not more than 60 HRC, — whether or not, a spline hardness of 30 HRC or more, but not more than 45 HRC, — an effective carburized case depth of 4 mm or more, but not more than 5 mm | 0 % | — | 31.12.2028 |
| 0.8541 | ex 8483 90 89 | 40 | <p>Steel alloy gear wheels with straight teeth and involute profile, with:</p> <ul style="list-style-type: none"> — external and/or internal toothing in a diametral pitch standard, — a diameter of 35 mm or more, but not more than 600 mm, — 13 teeth or more, but not more than 80 teeth, — a tooth core hardness of 28 HRC or more, but not more than 45 HRC, — a tooth surface hardness of 50 HRC or more, but not more than 65 HRC, — an effective carburized case depth of 1,00 mm or more, but not more than 3,1 mm, — a spline hardness of 27 HRC or more, but not more than 62 HRC, — whether or not in combination with a shaft with a spline hardness of 27 HRC or more, but not more than 62 HRC | 0 % | — | 31.12.2028 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.7156 | ex 8484 20 00 | 10 | Mechanical shaft seal for incorporation into rotary compressors for use in the manufacture of motor vehicle air condition units (¹) | 0 % | p/st | 31.12.2026 |
| 0.6854 | ex 8501 10 10 | 20 | Synchronous motor for a dishwasher with a water flow control mechanism with <ul style="list-style-type: none"> — a length without axle of 24 mm ($\pm 0,3$), — a diameter of 49,3 mm ($\pm 0,3$), — a rated voltage of 220 V AC or more but not more than 240 V AC, — a rated frequency of 50 Hz or more but not more than 60 Hz, — an input power of not more than 4 W, — a rotation speed of 4 rpm or more but not more than 4,8 rpm, — an output torque of not less than 10 kgf/cm | 0 % | — | 31.12.2027 |
| 0.7857 | ex 8501 10 10 | 40 | Synchronous hybrid stepper motor with: <ul style="list-style-type: none"> — an output not exceeding 18 W, — two phases, — a rated current of not more than 2,5 A/phase, — a rated voltage of not more than 20 V, — with or without a threaded shaft, for use in the manufacture of 3D printers (¹) | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|--------------------------------|----------|---|-------------------------|--------------------|-------------------------------------|
| 0.8390 | ex 8501 10 10 ex 8501 10 99 | 50 30 | Linear actuator for automotive electric seat adjustment applications: — consisting of a permanently excited DC motor with an integrated gear mechanism and leadscrew, — whether brushed or brushless, — whether or not with electronic control unit, — whether or not with Hall Effect Sensor, — with a nominal voltage of 8 V or higher but not higher than 16 V, — with a rated output mechanical power not exceeding 20 W, and — with a specified temperature range from – 40 °C to 160 °C, for use in the manufacture of automotive components for car seats ⁽¹⁾ | 0 % | — | 31.12.2027 |
| 0.8389 | ex 8501 10 10 ex 8501 10 99 | 60 40 | Rotary actuator for automotive electric seat adjustment applications: — consisting of a permanently excited DC motor with an integrated gear mechanism, — whether brushed or brushless, — whether or not with electronic control unit, — whether or not with Hall Effect Sensor, — with a nominal voltage of 8 V or more but not more than 16 V, — with a rated output mechanical power not exceeding 35 W, and — with a specified temperature range from – 40 °C to 160 °C, for use in the manufacture of automotive components for car seats ⁽¹⁾ | 0 % | — | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8394 | ex 8501 10 99 | 20 | <p>Worm axis motor for automotive electric seat adjustment applications:</p> <ul style="list-style-type: none"> — consisting of a permanently excited DC motor with a worm wheel, — whether brushed or brushless, — whether or not with electronic control unit, — whether or not with Hall Effect Sensor, — with a nominal voltage of 8 V or more but not more than 16 V, — with a rated output mechanical power not exceeding 35 W, and — with a specified temperature range from – 40 °C to 160 °C, <p>for use in the manufacture of automotive components for car seats⁽¹⁾</p> | 0 % | — | 31.12.2027 |
| 0.8396 | ex 8501 10 99 | 50 | <p>Electric (DC) motor powering height adjusting with:</p> <ul style="list-style-type: none"> — a rated output mechanical power not exceeding 35 W, — frame integration with a length of 156 mm, a height of 59 mm, a thickness of 36 mm and a weight of 500 g, — a stall torque of 45 Nm and ultimate torque of 200 Nm, — a maximum current of 15 A, — no load speed of 7 rpm or more but not more than 10 rpm, — a rotation speed of 4 000 rpm or more but not more than 5 600 rpm, — a maximum noise level of 42 dB(A), — a maximum angular backlash up to 3 degrees, and — a 8 tooth pinion module, <p>for use in the manufacture of automotive components for car seats⁽¹⁾</p> | 0 % | — | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.7197 | ex 8501 10 99 | 56 | <p>DC Motor:</p> <ul style="list-style-type: none"> — with a speed rotation of not more than 7 000 rpm without load, — with a nominal voltage of not more than 18 V, — with a maximum power of 24 W, — for a specific temperature range from – 40 °C to 160 °C, — with or without a gear connection, — with or without a mechanical attachment interface, — with 2 electrical connections, — with a maximum torque of 100 Nm | 0 % | — | 31.12.2026 |
| 0.7198 | ex 8501 10 99 | 58 | <p>DC Motor:</p> <ul style="list-style-type: none"> — with a speed rotation of not more than 6 500 rpm (without load), — with a nominal voltage of 12 V (± 4 V), — with a maximal power below than 20 W, — with a specified temperature range from – 40 °C to 160 °C, — with a worm gear drive, — with a mechanical attachment interface, — with 2 electrical connections, — with a maximum torque of 75 Nm | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.5846 | ex 8501 10 99 | 60 | <p>DC motor:</p> <ul style="list-style-type: none"> — with a rotor speed of 3 500 rpm or more but not more than 5 000 rpm loaded and not more than 6 500 rpm when not loaded — with a power supply voltage of 100 V or more but not more than 240 V for use in the manufacture of electric fryers (¹) | 0 % | — | 31.12.2027 |
| 0.6858 | ex 8501 10 99 | 64 | <p>DC motor to control angular position of the flap to adjust gas flow in the Air Throttle and EGR valve:</p> <ul style="list-style-type: none"> — with Ingress Protection (IP) standard of IP69, — with a rotor speed of not more than 6 500 rpm when not loaded, — with a rated voltage of 12,0 V ($\pm 0,1$), — of a specified temperature range of $- 40^{\circ}\text{C}$ or more but not more than $+ 165^{\circ}\text{C}$, — with or without a connecting pinion, — with or without an engine connector, — with or without a flange, — with a diameter of not more than 40 mm (not including the flange), — with an overall height of not more than 90 mm (from the base to the pinion) | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.6880 | *ex 8501 10 99 | 65 | Electric turbocharger actuator, with: — a DC motor, — an integrated gear mechanism, — a (pulling) force of 200 N or more at a minimum of 140 °C elevated ambient temperature, — a (pulling) force of 250 N or more in each position of its stroke, — an effective stroke of 15 mm or more but not more than 25 mm, — with or without an on-board diagnostics interface | 0 % | — | 31.12.2030 |
| 0.6115 | ex 8501 10 99 | 70 | DC stepping motor, with: — a two-phase winding, — a rated voltage of 9 V or more, but not more than 16,0 V, — of a specified temperature range of – 40 °C or more but not more than + 105 °C, — with or without connection pinion, — with or without motor drive connector | 0 % | — | 31.12.2029 |
| 0.6627 | *ex 8501 10 99 | 75 | Permanently excited DC motor with — a multiple-phase winding, — an external diameter of 24 mm or more but not more than 38 mm, — a rated speed of not more than 12 000 rpm, — a power supply voltage of 8 V or more but not more than 27 V, — with or without a pulley, — with or without a gear wheel | 0 % | — | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.2838 | ex 8501 10 99 | 79 | DC motor with brushes and an internal rotor with a three-phase winding, whether or not equipped with a worm or a pinion, of a specified temperature range covering at least – 20 °C to + 70 °C | 0 % | — | 31.12.2029 |
| 0.8345 | ex 8501 20 00 | 50 | Universal AC/DC motor, rotating: — with a nominal supply voltage of 230 V, — with a power of more than 37,5 W but not more than 2 000 W, — with a stator cross-section of 93 mm or more but not more than 103 mm and a thickness of 15 mm or more but not more than 45 mm, and — with or without a worm gear, gears or a gearbox, for the production of a torque to a transmission shaft for small domestic appliances (¹) | 0 % | — | 31.12.2027 |
| 0.8349 | ex 8501 20 00 | 60 | Universal AC/DC motor, rotating: — with a nominal supply voltage of 230 V, — with a power of more than 37,5 W but not more than 1 200 W, — with a stator cross-section of 65 mm or more but not more than 75 mm and a thickness of 15 mm or more but not more than 45 mm, and — with or without a worm gear, gears or a gearbox, for the production of a torque to a transmission shaft for small domestic appliances (¹) | 0 % | — | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8367 | ex 8501 20 00 | 70 | <p>Universal AC/DC motor, rotating:</p> <ul style="list-style-type: none"> — with a nominal supply voltage of 230 V, — with a power of more than 37,5 W but not more than 700 W, — with a stator cross-section of 49 mm or more but not more than 59 mm and a thickness of 15 mm or more but not more than 45mm, and — with or without a worm gear, gears or a gearbox, <p>for the production of a torque to a transmission shaft for small domestic appliances ⁽¹⁾</p> | 0 % | — | 31.12.2027 |
| 0.5954 | ex 8501 31 00 | 45 | <p>DC motors, brushless, with:</p> <ul style="list-style-type: none"> — an external diameter of 90 mm or more, but not more than 110 mm, — a rated speed of not more than 3 680 rpm, — an output of 600 W or more but not more than 740 W at 2 300 rpm and at 80 °C, — a supply voltage of 12 V, — a torque of not more than 5,67 Nm, — a rotor position sensor, — an electronic star-point relay, and — for use with an electric power steering control module | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8395 | ex 8501 31 00 | 47 | <p>Motor for automotive electric seat adjustment applications:</p> <ul style="list-style-type: none"> — with a shaft output on both motor sides, — consisting of a permanently excited DC motor, — whether brushed or brushless, — whether or not with electronic control unit, — whether or not with Hall Effect Sensor, — with a nominal voltage of 8 V or more but not more than 16 V, — with a rated output mechanical power not exceeding 120 W, and — with a specified temperature range from – 40 °C to 160 °C, <p>for use in the manufacture of automotive components for car seats⁽¹⁾</p> | 0 % | — | 31.12.2027 |
| 0.8609 | ex 8501 31 00 | 48 | <p>Brushless DC electric motors:</p> <ul style="list-style-type: none"> — with a rated power of 240 W or more, but not more than 260 W, — with a voltage of 36 V or higher, but not higher than 52 V — with a torque of 20 Nm or more, but not more than 140 Nm, — with a housing made of aluminium, aluminium alloy or plastic, — with or without a built-in controller, — with a communication function in the LIN or UART interface, — weighing 1,5 kg or more, but not more than 5,0 kg, — adapted for mounting in a bicycle frame <p>for use in the manufacture of e-bikes⁽¹⁾</p> | 0 % | — | 31.12.2028 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.8608 | ex 8501 31 00 | 49 | <p>Brushless DC electric motors:</p> <ul style="list-style-type: none"> — with a rated power of 240 W or more, but not more than 260 W, — with a voltage of 24 V or higher, but not higher than 52 V, — with a torque of 30 Nm or more, but not more than 62 Nm, — with a LIN, UART or CAN communication interface, — with an internal planetary gearbox with fixed or variable ratio or direct drive, — with a housing made of aluminium or aluminium alloy, — with a weight of 1,5 kg or more, but not more than 6 kg, — adapted for mounting in the front or rear bicycle wheel, <p>for use in the manufacture of e-bikes⁽¹⁾</p> | 0 % | — | 31.12.2028 |
| 0.5577 | ex 8501 31 00 | 50 | <p>DC motors, brushless, with:</p> <ul style="list-style-type: none"> — an external diameter of 80 mm or more, but not more than 200 mm, — a supply voltage of 4V or more, but not more than 16 V, — an output at 20 °C of 200 W or more, but not more than 750 W, — a torque at 20 °C of 2,00 Nm or more, but not more than 7,00 Nm, — a rated speed at 20 °C of 600 rpm or more, but not more than 3 100 rpm, — with or without a pulley, — with or without an electronic power steering sensor/controller | 0 % | — | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.8847 | ex 8501 31 00 | 52 | <p>Electric brushless direct current motor finished with biocompatible materials such as stainless steel according to specification 17-4 PH or type 303, 316L, 400 with:</p> <ul style="list-style-type: none"> — a three-phase winding, — an output power not exceeding 280 W, — a length with gearhead of 116,1 mm or more but not more than 117,2 mm, — an external diameter of 13,86 mm or more but no more than 13,92 mm, — a maximum torque of motor with gearhead 246,6 mNm in 25 °C, — a no-load radial speed of motor with gearhead with 9 900 rpm, at 24 V in 25 °C, — a weight of motor with gearhead of 70,5 g or more but not more than 71,5 g, a resistance to peak temperature of 140 °C or more (non-operating), a maximal air leak between shaft and shaft seals of 15 Pa/s at given 2 Bars of pressure, — 14 functional pins for power and control purpose, — a flexible printed circuit with length of 245 mm but no longer than 255 mm with mounted 8 pin male connector <p>for use in the manufacture of medical devices with right-left rotation and oscillation function (1)</p> | 0 % | p/st | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|--------------------------------|----------|--|-------------------------|--------------------|-------------------------------------|
| 0.8855 | ex 8501 31 00 | 54 | Brushless DC electric motor, with: — a rated voltage of 310 V, — a rated power of 350 W or more but not more than 368 W, — an input power of 500 W or more but not more than 550 W, — output power of 350 W or more but not more than 400 W, — an external diameter without bracket connector and pulley of 143,2 mm or more but not more than 143,8 mm, — a rated speed of 16 300 rpm or more but not more than 16 500 rpm, — a weight of 2,33 kg or more but not more than 2,40 kg, — a pulley | 0 % | p/st | 31.12.2029 |
| 0.5978 | ex 8501 31 00 ex 8501 32 00 | 55 40 | DC motor with or without commutator, for driving hand-held power tools, lawn mowers or home appliances, with: — an external diameter of 24,2 mm or more, but not more than 140 mm, — a rated speed of 3 300 rpm or more, but not more than 26 200 rpm, — a rated supply voltage of 3,6 V or more, but not more than 230 V, — an output power of more than 37,5 W, but not more than 2 400 W, — a free load current of not more than 20,1 A, — a maximum efficiency of 50 % or more, | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8974 | *ex 8501 31 00 | 56 | <p>DC motor, brushless, integrated with an Electronic Control Unit (ECU), defined as a Power Pack with:</p> <ul style="list-style-type: none"> — a safety feature and mechanism designed for prevention of critical hazards like self-steer by single failure, — a CAN-communication interface, — an external sensor interface, — operating temperature range of – 40 °C to 95 °C or broader, — compliance with standard IP6K9K for water and dustproofness, — supply voltage of 9 V or more, but not more than 16 V, — rated power output of 500 W or more, but not higher than 750 W, — rated torque of 3 Nm or more, but not more than 6 Nm, — length of 150 mm or more, but not more than 250 mm, — width of 100 mm or more, but not more than 150 mm, — height of 80 mm or more, but not more than 120 mm | 0 % | p/st | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8977 | *ex 8501 31 00 | 57 | <p>Brushless DC electric motor with LCD control indicator and/or control unit with buttons:</p> <ul style="list-style-type: none"> — with an output power of 200 W or more, but not more than 700 W, — with a supply voltage of 30 V or more, but not more than 60 V, — with a torque of 30 Nm or more, but not more than 200 Nm, — with a height of 117 mm or more, but not more than 146 mm, — with a length of 117 mm or more, but not more than 223 mm, — with a width of 135 mm or more, but not more than 190 mm, — with a weight of 2 kg or more but not more than 5 kg, — designed to be mounted in a frame, front or rear bicycle wheel, — equipped with sockets, at least for cable connection with LCD control indicator, for use in the manufacture of electric bicycles (¹) | 0 % | p/st | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.4731 | ex 8501 31 00 | 58 | <p>Permanently excited DC motor with:</p> <ul style="list-style-type: none"> — an external diameter of 27 mm or more but not more than 90 mm, including mounting flange, — a rated speed of not more than 25 000 rpm, — an output of 45 W or more but not more than 400 W, and — a supply voltage of 9 V or more but not more than 50 V, — whether or not a multiple-phase winding, — whether or not with a drive disc, — whether or not with a crankcase, — whether or not with a fan, — whether or not with a cap assembly, — whether or not with a sun gear, — whether or not with a speed and rotational direction encoder, — whether or not with or without a speed or rotational direction sensor of resolver type or Hall effect type, — whether or not with a mounting flange <p>for use in the manufacture of air suspension seats in tractors, earthmoving machines and forklifts or for use in the manufacture of actuators for height-adjustable furniture (¹)</p> | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------------------------|----------|---|-----|-------------------------|--------------------|-------------------------------------|
| 0.6809 | *ex 8501 31 00 ex 8501 32 00 | 63 65 | Ready for installation in vehicles or equipment of headings 8432 and 8433, brushless and permanently excited direct current motor with: — a specified speed of not more than 4 100 rpm, — a minimum output of 400 W, but not more than 1,3 kW (at 12 V), or with a minimum output of 750 W but not more than 1,55 kW (at 36 V), — a flange diameter of 85 mm or more but not more than 200 mm, — a maximum length of 335 mm, measured from the beginning of the shaft to the outer ending, — a housing length of not more than 265 mm, measured from the flange to the outer ending, — a maximum of two-piece (basic housing including electric components and flange with minimum 2 and maximum 11 bore holes) aluminium diecast or sheet steel housing whether or not with a sealing compound (groove with an O-ring and grease), — a stator with single T-tooth design and single coil windings in 9/6 or 12/8 topology, and — surface magnets, — whether or not with electronic power steering controller, — whether or not with pulley, — whether or not with rotor position sensor | 0 % | — | 31.12.2030 | |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---|----------------|--|-------------------------|--------------------|-------------------------------------|
| 0.4855 | ex 8501 33 90 ex 8501 40 80 ex 8501 53 50 | 30 50 10 | Electric drive for motor vehicles, with an output of not more than 315 kW: — with an AC or DC motor with or without transmission, — with or without power electronics | 0 % | — | 31.12.2026 |
| 0.8188 | ex 8501 40 20 | 35 | Electric AC motor, single-phase, with: — a rated power of 120 W or more but not more than 150 W, — an input power of 280 W or more but not more than 350 W, — an external diameter without bracket connector and pulley of 145 mm or more but not more than 160 mm, — a rated speed of 2 680 rpm or more but not more than 3 000 rpm, — a weight of 4,2 kg or more but not more than 4,6 kg, — pulleys, a spindle and a tachometer, for use in the manufacture of home appliance products (¹) | 0 % | — | 31.12.2026 |
| 0.8189 | ex 8501 40 20 | 45 | Electric AC motor, single-phase, with: — a rated power of 275 W or more, but not more than 325 W, — an input power of 600 W or more but not more than 700 W, — an external diameter without bracket and connector of 150 mm or more but not more than 170 mm, — a rated speed of 15 000 rpm or more but not more than 20 000 rpm, — a weight of 4,2 kg or more, — a pulley and a tachometer, for use in the manufacture of home appliance products (¹) | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8191 | ex 8501 40 20 | 50 | <p>Electric AC motor, single-phase, with:</p> <ul style="list-style-type: none"> — a rated power of 300 W or more but not more than 370 W, — an input power of 600 W or more but not more than 700 W, — an external diameter without bracket and connector of 150 mm or more but not more than 170 mm, — a rated speed of 15 000 rpm or more but not more than 19 000 rpm, — a weight of 4,8 kg or more, — a pulley, <p>for use in the manufacture of home appliance products ⁽¹⁾</p> | 0 % | — | 31.12.2026 |
| 0.8192 | ex 8501 40 20 | 55 | <p>Electric AC motor, single-phase, with:</p> <ul style="list-style-type: none"> — a rated power of 275 W or more, but not more than 325 W, — an input power of 600 W or more but not more than 700 W, — an external diameter without bracket and connector of 160 mm or more but not more than 180 mm, — a rated speed of 15 000 rpm or more but not more than 19 000 rpm, — a weight of not more than 4,4 kg, — a pulley, <p>for use in the manufacture of home appliance products ⁽¹⁾</p> | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8193 | ex 8501 40 20 | 60 | <p>Electric AC motor, single-phase, with:</p> <ul style="list-style-type: none"> — a rated power of 275 W or more but not more than 325 W, — an output power of 550 W or more but not more than 600 W, — an input power of 800 W or more but not more than 1 000 W, — an external diameter of more than 150 mm but not more than 170 mm without the bracket, — a rated speed of more than 16 000 rpm but not more than 18 000 rpm, — a weight of 3,4 kg or more but not more than 3,7 kg, — a pulley, <p>for use in the manufacture of home appliance products (¹)</p> | 0 % | — | 31.12.2026 |
| 0.8982 | *ex 8501 40 20 | 75 | <p>Incomplete, single-phase brushless AC motor consisting of a rotor and a stator:</p> <ul style="list-style-type: none"> — a rotor on the inside is equipped with a ring of 12 magnets housed in a steel casing, — a stator with an internal diameter of 206,6 mm ($\pm 0,5$ mm), external diameter of 265,0 mm ($\pm 0,2$ mm) and width of 37,2 mm or more but not more than 47,8 mm, — with a rated power not exceeding 750 W, — with a weight of 5 kg or more, <p>for use in the production of washing machines, washer-dryers equipped with a drum with direct drive (¹)</p> | 0 % | p/st | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|--------------------------------|----------|--|-------------------------|--------------------|-------------------------------------|
| 0.8844 | ex 8501 51 00 | 25 | <p>Electric permanent magnet synchronous motor with:</p> <ul style="list-style-type: none"> — an output power of 550 W, — a rotor containing 8 poles generated by permanent magnets composed mainly with neodymium-iron-boron (per GB/T 13560 standard) enclosed in polyethylene cover, — an outer diameter of motor magnet shaft end with dimension of 10,001 mm or more but no more than 10,007 mm, — terminals located across the radius 32,5 mm and separated by an angle of 21,8°, — a motor housing made of ADC12 or AC46000 aluminium alloy die casting with composition of aluminium-silicon-copper (per JIS H5302 or EN1706 standard), — a back electromotive force constant (Ke) of 0,03306 V·sec/rad or more but no more than 0,03654 V·sec/rad, — a back electromotive force harmonic order - 5th of no more than 0,38 % (of fundamental) and 7th of no more than 0,25 % (of fundamental), — a cogging torque of no more than 13 mNm, — a friction torque in ambient temperature of no more than 22 mNm, — a maximum temperature of motor operation of no more than 200 °C | 0 % | p/st | 31.12.2029 |
| 0.5329 | ex 8501 51 00 ex 8501 52 20 | 30 50 | <p>AC synchronous servo motor with resolver and brake for a maximum speed of not more than 6 000 rpm, with:</p> <ul style="list-style-type: none"> — an output of 340 W or more but not more than 7,4 kW, — a flange of dimensions of not more than 180 mm × 180 mm, and — a length from flange to extreme end of resolver of not more than 271 mm | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.8845 | ex 8501 51 00 | 35 | <p>Electric permanent magnet synchronous motor with:</p> <ul style="list-style-type: none"> — an output power of 600 W, — a rotor containing 8 poles generated by permanent magnets composed mainly with neodymium-iron-boron and dysprosium enclosed in aluminium cover, — an outer diameter of motor magnet shaft end with dimension of 10,001 mm or more but no more than 10,007 mm, — terminals located across the diameter 59,2 mm and separated by an angle 30,0°, — a housing made of electrogalvanized steel (per JIS G3313 Grade SECE standard) using a deep-drawing stamping process, — a diameter of 88,600 mm or less but no less than 88,546 mm at the motor-system assembly interface, — a back electromotive force constant (Ke) of 0,03277 V·sec/rad or more but no more than 0,03623 V·sec/rad, — a back electromotive force harmonic order - 5th of no more than 0,35 % (of fundamental) and 7th of no more than 0,30 % (of fundamental), — a cogging torque of no more than 12 mNm, — a friction torque in ambient temperature of no more than 23 mNm, — a maximum temperature of motor operation of no more than 200 °C | 0 % | p/st | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.8190 | ex 8501 51 00 | 40 | <p>Electric AC motor, three-phase, with:</p> <ul style="list-style-type: none"> — a rated power of 280 W or more but not more than 320 W, — an output power of 480 W or more but not more than 540 W, — an input power of 800 W or more but not more than 900 W, — an external diameter of 150 mm or more but not more than 170 mm, — a rated speed of 15 000 rpm or more but not more than 20 000 rpm, — a weight of 6 kg or more but not more than 6,4 kg, — a pulley and a tachometer, <p>for use in the manufacture of home appliance products ⁽¹⁾</p> | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.8590 | ex 8501 51 00 | 45 | <p>Automotive-ready brushless permanently excited magnet synchronous alternating current motor with:</p> <ul style="list-style-type: none"> — a specified speed of not more than 7 000 rpm, — an output of 400 W or more but not more than 750 W (at 12 V), — a flange diameter of 80 mm or more, but not more than 200 mm, — a maximum length of not more than 335 mm, measured from the beginning of the shaft to its outer end, — a housing length of not more than 265 mm, measured from the flange to the outer end, — a steel sheet or die-cast aluminium basic housing consisting of not more than two parts, including electrical components and a flange with two or more but not more than 11 holes, whether or not with a sealing connection (groove with O-ring and protective grease or liquid seal interface), — a stator with single T-tooth design and single coil winding with 9/6 or 12/10 or 12/8 topology and surface magnets, — whether or not with electronic power steering controller, — whether or not with pulley or coupling, — whether or not with rotor position sensor | 0 % | p/st | 31.12.2028 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8404 | ex 8501 51 00 | 50 | <p>Three phase AC synchronous brushless permanent magnet motor with:</p> <ul style="list-style-type: none"> — an output of 500 W or more but not more than 700 W, — an external diameter of 129,7 mm or more but not more than 180,3 mm, — a rated speed of 16 000 rpm or more but not more than 17 000 rpm, — a weight of 2,5 kg or more but not more than 3,1 kg, and — with a pulley, <p>for use in the manufacture of home appliance products ⁽¹⁾</p> | 0 % | — | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8902 | ex 8501 52 20 | 70 | <p>Automotive-ready brushless permanently excited magnet synchronous alternating current motor with:</p> <ul style="list-style-type: none"> — a specified speed of not more than 7 000 rpm, — an output of 750 W or more but not more than 1,8 kW (at 12 V), — a flange diameter of 80 mm or more, but not more than 200 mm, — a maximum length of not more than 335 mm, measured from the beginning of the shaft to its outer end, — a housing length of not more than 265 mm, measured from the flange to the outer end, — a steel sheet or die-cast aluminium basic housing consisting of not more than two parts, including electrical components and a flange with two or more but not more than 11 holes, whether or not with a sealing connection (groove with O-ring and protective grease or liquid seal interface), — a stator with single T-tooth design and single coil winding with 9/6 or 12/10 or 12/8 topology and surface magnets, — whether or not with electronic power steering controller, — whether or not with pulley or coupling, — whether or not with rotor position sensor | 0 % | p/st | 30.06.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.8846 | ex 8501 52 20 | 80 | <p>Electric permanent magnet synchronous motor with:</p> <ul style="list-style-type: none"> — an output power of 850 W, — a rotor containing 8 poles generated by permanent magnets composed mainly with neodymium-iron-boron (per GB/T 13560 standard) enclosed in polyethylene cover, — an outer diameter of motor magnet shaft end with dimension of 10,001 mm or more but no more than 10,007 mm, — terminals located across the radius 26,2 mm and separated by an angle 30,0°, — a housing made of ADC12 or AC46000 aluminium alloy die casting with composition of aluminium-silicon-copper (per JIS H5302 or EN1706 standard) and anodized coating (per ASTM B580 type E standard), — a back electromotive force constant (Ke) of 0,04009 V·sec/rad or more but no more than 0,04431 V·sec/rad, — a back electromotive force harmonic order - 5th of no more than 0,36 % (of fundamental) and 7th of no more than 0,24 % (of fundamental), — a cogging torque of no more than 20 mNm, — a friction torque in ambient temperature of no more than 26,5 mNm, — a maximum temperature of motor operation of no more than 200 °C | 0 % | p/st | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.8129 | *ex 8501 53 50 | 30 | <p>Permanent magnet synchronous traction motor, with:</p> <ul style="list-style-type: none"> — a continuous power of 110 kW or more but not more than 180 kW, — a liquid cooled system, — a total length of 500 mm or more but not more than 650 mm, — a total width of 600 mm or more but not more than 700 mm, — a total height of 550 mm or more but not more than 650 mm, — weighing of not more than 350 kg, — 3 suspension points | 0 % | — | 31.12.2030 |
| 0.8285 | ex 8501 53 50 | 40 | <p>Permanent magnet traction AC motor, with:</p> <ul style="list-style-type: none"> — a continuous power of 110 kW or more but not more than 150 kW, — a liquid cooled system, — a total length of 460 mm or more but not more than 590 mm, — a total width of 450 mm or more but not more than 580 mm, — a total height of 490 mm or more but not more than 590 mm, — a weight of not more than 310 kg, — 4 mounting points | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8458 | ex 8501 53 50 | 50 | <p>Asynchronous traction motor, with:</p> <ul style="list-style-type: none"> — a continuous power of 140 kW or more but not more than 180 kW, — a liquid cooled system, — a total length of 580 mm or more but not more than 730 mm, — a total width of 550 mm or more but not more than 670 mm, — a total height of 510 mm or more but not more than 630 mm, — with a weight of not more than 390 kg, — with or without reduction gear, — with or without starter generator, — 2 mounting points, <p>for use in the manufacture of the electric drive of hybrid buses (¹)</p> | 0 % | — | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|--------------------------------|----------|---|-------------------------|--------------------|-------------------------------------|
| 0.8130 | *ex 8501 62 00 | 40 | AC, 3-phase generator, with: — a continuous power of 147 kVA or more but not more than 222 kVA, — a continuous torque of 650 Nm or more but not more than 900 Nm, — a maximum working speed of 2 700 revolutions per minute (rpm), — a liquid cooled system, — a length of 100 mm or more but not more than 200 mm, — a width of 550 mm or more but not more than 650 mm, — a height of 550 mm or more but not more than 650 mm, — weighing of not more than 150 kg | 0 % | — | 31.12.2030 |
| 0.2837 | ex 8503 00 91 ex 8503 00 98 | 31 32 | Rotor, at the inner side provided with one or two magnetic rings (uniform or sectional) whether or not incorporated in a steel ring or bearing mounted in steel housing | 0 % | p/st | 31.12.2029 |
| 0.4599 | ex 8503 00 98 | 33 | Stator for brushless motor of electrical power steering with a roundness tolerance of 50 µm | 0 % | p/st | 31.12.2026 |
| 0.7496 | ex 8503 00 98 | 37 | Rotor for electric motor, with the rotor cylindrical body made of agglomerated ferrite or sintered neodymium or plastoneodymium, with or without metal shaft and with or without plastic elements: — diameter of the rotor body of 15 mm or more but not more than 37 mm, — length of the rotor body of 12 mm or more but not more than 36 mm | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8658 | ex 8503 00 98 | 40 | Pressure casted inner housing of a cooling channel system for an electrical motor: — of EN AC-47100 aluminium, — shot-blasted and machined, — leakproof to the degree of 3 ml per minute or less under 2,75 bar pressure, — with a hardness of 70 or more on the Hardness Brinell Wolfram (HBW) scale (2,5/62,5, according to ISO 6506), — with a tensile strength of 190 N/mm ² or more, — with a height of 160 mm or more, but not more than 330 mm, — with a diameter of 240 mm or more, but not more than 368 mm, — with a weight of 3 kg or more, but not more than 5,84 kg | 0 % | — | 31.12.2028 |
| 0.8662 | ex 8503 00 98 | 53 | Pressure casted rotor cover of the cooling channel system in the electrical motor: — of EN AC-47100-F aluminium, — with a sealing cap of stainless steel, — shot-blasted and machined, — leakproof to the degree of 1 ml per minute or less under 2,75 bar pressure, — with a hardness of 70 HBW or more (2,5/62,5, according to ISO 6506), — with a tensile strength of 190 N/mm ² or more, — with a height of 42 mm or more, but not more than 64 mm, — with a diameter of 88 mm or more, but not more than 132 mm, — with a weight of 0,3 kg or more, but not more than 0,5 kg | 0 % | — | 31.12.2028 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.6161 | ex 8503 00 98 | 55 | <p>Stator for brushless motor, with:</p> <ul style="list-style-type: none"> — an internal diameter of 206,6 mm ($\pm 0,5$), — an external diameter of 265,0 mm ($\pm 0,2$), and — a width of 37,2 mm or more but not more than 47,8 mm, <p>of a kind used in the manufacture of washing machine, washer-dryer or dryer equipped with direct drive drums</p> | 0 % | p/st | 31.12.2026 |
| 0.8659 | ex 8503 00 98 | 63 | <p>Pressure casted outer housing of an electrical motor:</p> <ul style="list-style-type: none"> — of EN AC-47100 aluminium, — with or without overmolded bearing sleeves of martensitic stainless steel and assembled sealing caps of stainless steel, — shot-blasted and machined, — with or without a rotor chamber, leakproof to the degree of 3 ml per minute or less under 2,75 bar pressure, — with a hardness of 70 or more on the Hardness Brinell Wolfram (HBW) scale (2,5/62,5, according to ISO 6506), — with a tensile strength of 190 N/mm² or more, — with a height of 195 mm or more, but not more than 430 mm, — with a width of 290 mm or more, but not more than 625 mm, — with a length of 270 mm or more, but not more than 535 mm, — with a weight of 5,2 kg or more, but not more than 12,5 kg | 0 % | — | 31.12.2028 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.8783 | ex 8503 00 98 | 73 | Pressure die-cast electric motor stator housing: — of EN AC-46000 aluminium, — shot-blasted and machined, — with a height of 70 mm or more but not more than 76 mm, — with a width of 155 mm or more but not more than 162 mm, — with a weight of 330 g or more but not more than 360 g | 0 % | — | 31.12.2029 |
| 0.7761 | ex 8503 00 98 | 75 | Stator body of stacked electrical sheet having: — an inner diameter of 18 mm or more but not more than 35 mm, — an outer diameter of 35 mm or more but not more than 65 mm, and — a length of 20 mm or more but not more than 65 mm, — whether or not incorporated in a housing | 0 % | — | 31.12.2029 |
| 0.7549 | ex 8504 31 80 | 15 | Electrical Transformer with — a capacity of 192 Watts or 216 Watts — dimensions of not more than 27,1 x 26,6 x 18 mm — an operating temperature range of – 40 °C or more, but not more than + 125 °C — three or four inductively coupled copper wire windings and — 9 connection pins at the bottom | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.4450 | ex 8504 31 80 | 30 | Switching transformers, having a power handling capacity of not more than 1 kVA for use in the manufacture of static converters (¹) | 0 % | — | 31.12.2029 |
| 0.7000 | ex 8504 31 80 | 50 | Transformers for use in the manufacture of electronic drivers, control devices and LED light sources for lighting industry (¹) | 0 % | — | 31.12.2026 |
| 0.7029 | ex 8505 11 10 | 20 | Articles, of an alloy of neodymium, in the shape of a rectangle, triangle, square, or trapezoid, — whether or not arched, — whether or not with rounded corners or oblique sides, — whether or not colour marked — whether or not coated or passivated with a surface treatment, — whether or not consisting of segments bonded together and electrically insulated from one another with: — a length of 9 mm or more, but not more than 105 mm, — a width of 5 mm or more, but not more than 105 mm, — a thickness of 2 mm or more, but not more than 55 mm intended to become permanent magnet after magnetisation | 0 % | — | 31.12.2026 |
| 0.5584 | ex 8505 11 10 | 23 | Bars in the form of arched rectangles, containing alloy containing neodymium, with: — a length of 15 mm or more but not more than 52 mm, — a width of 5 mm or more but not more than 42 mm, — whether or not coated or passivated with a surface treatment, intended to become permanent magnets after magnetisation | 0 % | p/st | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.5585 | ex 8505 11 10 | 28 | <p>Articles containing alloy containing neodymium, in the form of rings, tubes, bushings or collars:</p> <ul style="list-style-type: none"> — with an external diameter of not more than 45 mm, — with a height of not more than 45 mm, — whether or not coated or passivated with a surface treatment, <p>intended to become permanent magnets after magnetisation</p> | 0 % | p/st | 31.12.2027 |
| 0.3740 | ex 8505 11 10 | 30 | <p>Permanent magnets of an alloy of neodymium, either in the shape of a rectangle, whether or not rounded, whether or not coated or passivated with a surface treatment, with:</p> <ul style="list-style-type: none"> — a rectangular or a trapezoidal cross-section, — a length of not more than 140 mm, — a width of not more than 90 mm and — a thickness of not more than 55 mm, <p>or in the shape of an arched rectangle with:</p> <ul style="list-style-type: none"> — a length of not more than 75 mm, — a width of not more than 40 mm, — a thickness of not more than 7 mm and — a radius of curvature of more than 86 mm but not more than 241 mm, — layers of nickel and copper <p>or in the shape of a disc with:</p> <ul style="list-style-type: none"> — a diameter of not more than 90 mm, — whether or not a hole in the centre | 0 % | p/st | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.5948 | ex 8505 11 10 | 35 | Article of an alloy of neodymium, in the shape of a disc, with: — a diameter of not more than 90 mm, — whether or not a hole in the centre, — layers of copper, nickel and/or zinc, intended to become permanent magnets after magnetisation | 0 % | — | 31.12.2029 |
| 0.8508 | ex 8505 11 10 | 78 | Two permanent magnets made of a praseodymium-neodymium alloy, in a rectangular steel holder with an outer casing of rubber with outer dimensions: — a length of 200 mm or more but not more than 205 mm, — a width of 58 mm or more but not more than 62 mm, — a height of 25 mm or more but not more than 30 mm, with a stud mounted in the middle | 0 % | — | 31.12.2027 |
| 0.5937 | ex 8505 19 90 | 30 | Articles of agglomerated ferrite in the shape of a disc, whether or not coated or passivated with a surface treatment, with: — a diameter of not more than 120 mm, — a hole in the centre, intended to become permanent magnets after magnetisation with a remanence between 245 mT and 470 mT | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.7299 | ex 8505 19 90 | 45 | <p>Article of agglomerated ferrite in the shape of a rectangle, whether or not with oblique sides, with:</p> <ul style="list-style-type: none"> — a length of 26,85 mm or more but not more than 32,15 mm, — a width of 7,6 mm or more but not more than 9,55 mm, — a thickness of 5,3 mm or more but not more than 5,8 mm, and — a weight of 6,1 g or more but not more than 8,3 g, <p>intended to become a permanent magnet after magnetisation</p> | 0 % | p/st | 31.12.2027 |
| 0.7511 | ex 8505 19 90 | 60 | <p>Articles of agglomerated ferrite in the shape of arched rectangles,</p> <ul style="list-style-type: none"> — whether or not coated or passivated with a surface treatment, — whether or not with rounded corners, <p>with:</p> <ul style="list-style-type: none"> — a length of 9 mm or more but not more than 101 mm, — a width of 9 mm or more but not more than 101 mm, — a thickness of 1,85 mm or more but not more than 15,15 mm, <p>intended to become permanent magnets after magnetisation</p> | 0 % | — | 31.12.2029 |
| 0.4029 | ex 8505 20 00 | 30 | Electromagnetic clutch, for use in the manufacture of compressors of air conditioning machines of motor vehicles (1) | 0 % | p/st | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8627 | ex 8505 20 00 | 40 | <p>Electromagnetic clutch:</p> <ul style="list-style-type: none"> — transmitting torque from the motor shaft to the cutting device pulley, — containing field coil, rotor, hub and armature, — with an operating voltage of 12 V — a current of 3,93 A current or more but not more than 6,86 A, — a resistance of 1,84 ohm or more but not more than 3,05 ohm (operating at 20 °C), — a static torque of 108 Nm or more but not more than 305 Nm <p>for use in the manufacture of rider type self-propelled mowers (¹)</p> | 0 % | — | 31.12.2028 |
| 0.8095 | ex 8505 90 90 | 20 | <p>Electromagnetic clutch coil in a cylindrical metal housing:</p> <ul style="list-style-type: none"> — the metal housing is made of hot-rolled steel complying with standard JIS G 3131 – SPHE, — the coil is made of copper wire, — with a weight of 0,4 kg or more but not more than 0,85 kg, — with a width of 20 mm or more but not more than 45 mm, — with a plate reinforced to the coil (coil backplate) with an internal diameter of 44 mm or more but not more than 46 mm, — with an external diameter of 87 mm or more but not more than 110 mm, — without plunger, — with one connector | 0 % | p/st | 31.12.2027 |
| 0.2490 | ex 8506 50 90 | 10 | Lithium iodine single cell battery the dimensions of which do not exceed 9 mm × 23 mm × 45 mm and a voltage of not more than 2,8 V | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.2488 | ex 8506 50 90 | 30 | Lithium-iodine or lithium-silver vanadium oxide single cell battery of dimensions of not more than 28 mm × 45 mm × 15 mm and a capacity of not less than 1,05 Ah | 0 % | — | 31.12.2029 |
| 0.6685 | *ex 8507 60 00 | 15 | Cylindrical lithium-ion-accumulators or modules with: — a nominal capacity of 8,8 Ah or more, but not more than 18 Ah, — a nominal voltage of 36 V or more, but not more than 48 V, — a power of 300 W or more, but not more than 648 W, for use in the manufacture of electric bicycles (¹) | 1,3 % | — | 31.12.2026 |
| 0.7663 | *ex 8507 60 00 | 18 | Lithium-ion polymer accumulator pack equipped with a battery management system and can-bus interface with: — 6 modules with 90 cells or more but not more than 192 cells, — a nominal voltage of 280 V or more but not more than 400 V, — a nominal capacity of 9,7 Ah or more but not more than 120 Ah, — a charging voltage of 110 V or more but not more than 495 V, and in a metal casing with: — a length of not more than 1 723 mm, — a width of not more than 1 162,23 mm, — a height of not more than 395 mm, for use in the manufacture of vehicle capable of being charged by plugging to external source of electric power of heading 8703 (¹) | 1,3 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.8593 | *ex 8507 60 00 | 24 | <p>Rechargeable lithium-ion battery, based on lithium-iron-phosphate technology, with:</p> <ul style="list-style-type: none"> — a fuse, — a cell-to-pack design, — a length of 985 mm or more but not more than 1 015 mm, — a width of 1 050 mm or more but not more than 1 070 mm — a height of 145 mm or more but not more than 160 mm, — a weight of 220 kg or more but not more than 250 kg, — a capacity of 200 Ah or more, — a specific energy density of 130 Wh/kg or more, <p>for use in the manufacture of vehicles of subheading 8702 40 (¹)</p> | 1,3 % | — | 31.12.2026 |
| 0.8660 | *ex 8507 60 00 | 26 | <p>Modules for the assembly of electric accumulators using lithium ferrophosphate technology (LFP) with:</p> <ul style="list-style-type: none"> — a length of 670 mm or more, but not more than 882 mm, — a width of 390 mm or more, but not more than 655 mm, — a height of 110 mm or more, but not more than 137 mm, — a weight of 60 kg or more, but not more than 165 kg, and — a power of 11 300 Wh or more, but not more than 29 360 Wh | 1,3 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.8645 | *ex 8507 60 00 | 28 | <p>Lithium-ion rechargeable battery cell with:</p> <ul style="list-style-type: none"> — a length of 190 mm or more but not more than 380 mm, — a width of 90 mm or more but not more than 150 mm, — a height of 4 mm or more but not more than 35 mm, — a weight of 0,1 kg or more but not more than 2,5 kg, — a nominal voltage of 3,0 VDC or more but not more than 5,0 VDC, — a nominal capacity of not more than 150 Ah, <p>for use in the manufacture of rechargeable hybrid and electric vehicle batteries (¹)</p> | 1,3 % | — | 31.12.2026 |
| 0.8368 | *ex 8507 60 00 | 29 | <p>Lithium-ion rechargeable battery pack in a specific housing, suitable for use in digital still cameras, having:</p> <ul style="list-style-type: none"> — a length of 50 mm or more, but not more than 120 mm, — a width of 35 mm or more, but not more than 80 mm, — a height of 15 mm or more, but not more than 45 mm, — a weight of 0,040 kg or more but not more than 0,085 kg; and — a capacity of not more than 2 200 mAh | 1,3 % | — | 31.12.2026 |
| 0.2907 | *ex 8507 60 00 | 30 | Cylindrical lithium-ion accumulator or module, with a length of 63 mm or more and a diameter of 17,2 mm or more, having a nominal capacity of 1 200 mAh or more, for use in the manufacture of rechargeable batteries (¹) | 1,3 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.5548 | *ex 8507 60 00 | 31 | <p>Modules for the assembly of lithium-ion battery packs, using a technology other than lithium ferrophosphate (LFP) with:</p> <ul style="list-style-type: none"> — a length of 298 mm or more, but not more than 500 mm, — a width of 33,5 mm or more, but not more than 209 mm, — a height of 75 mm or more, but not more than 228 mm, — a weight of 3,6 kg or more, but not more than 17 kg, — a power of 458 Wh or more, but not more than 3 510 Wh, and — a voltage of less than 45 V or more than 70 V | 1,3 % | — | 31.12.2026 |
| 0.6703 | *ex 8507 60 00 | 33 | <p>Lithium-ion battery module or accumulator, with:</p> <ul style="list-style-type: none"> — a length of 150 mm or more, but not more than 1 310 mm, — a width of 100 mm or more, but not more than 1 000 mm, — a height of 200 mm or more, but not more than 1 500 mm, — a weight of 50 kg or more, but not more than 200 kg, — cells of a nominal capacity of 58 Ah or more but not more than 500 Ah, — a nominal output voltage of 230 V AC or 45 V or more but not more than 980 V DC | 1,3 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.8654 | *ex 8507 60 00 | 36 | <p>Lithium-ion accumulator, with</p> <ul style="list-style-type: none"> — multiple connected lithium-ion accumulator cells, — charging and monitoring electronics, — a power of 74 Wh or more, but not more than 75 Wh, — in a plastic housing with electrical connection contacts and LCD display, <p>for use in the manufacture of cordless vacuum cleaners or rechargeable power sources therefor⁽¹⁾</p> | 1,3 % | — | 31.12.2026 |
| 0.8115 | *ex 8507 60 00 | 48 | <p>Integrated battery system in a metal or plastic case with or without holders, consisting of:</p> <ul style="list-style-type: none"> — a lithium-ion battery with a voltage of 36 V or more but not more than 50,4 V and a nominal energy between 0,3 kWh and 0,9 kWh, — a Battery Management System, — a power relay, — a cooling system, — one to four connectors, <p>for use in the manufacture of Mild-hybrid (mHEV) motor vehicles⁽¹⁾</p> | 1,3 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.7641 | *ex 8507 60 00 | 58 | <p>Prismatic lithium-ion electric accumulator with:</p> <ul style="list-style-type: none"> — a width of 120,0 mm or more but not more than 305,0 mm, — a thickness of 12,0 mm or more but not more than 67,0 mm, — a height of 72,0 mm or more but not more than 126,0 mm, — a nominal voltage of 3,6 V or more but not more than 3,75 V, and — a nominal capacity of 6,9 Ah or more not more than 265 Ah, <p>for use in the manufacture of rechargeable electric vehicle batteries (¹)</p> | 1,3 % | — | 31.12.2026 |
| 0.6753 | *ex 8507 60 00 | 77 | <p>Lithium-ion rechargeable batteries, with:</p> <ul style="list-style-type: none"> — a length of 700 mm or more, but not more than 2 820 mm, — a width of 935 mm or more, but not more than 1 660 mm, — a height of 85 mm or more, but not more than 700 mm, — a weight of 250 kg or more, but not more than 700 kg, — a power of not more than 175 kWh, — a nominal voltage of 320 V or more, but not more than 430 V <p>for use in the manufacture of vehicles of subheadings 8701 to 8705 (¹)</p> | 1,3 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8275 | *ex 8507 60 00 | 83 | Modules for the assembly of lithium-ion electric accumulators with: — a length of 570 mm or more, but not more than 610 mm, — a width of 210 mm or more, but not more than 240 mm, — a height of 100 mm or more, but not more than 125 mm, — a weight of 28 kg or more, but not more than 35 kg, and — a capacity of not more than 2 500 Ah and a nominal energy of less than 8,4 kW, for use in the manufacture of vehicles of subheadings 8703 60, 8703 70, 8703 80 and 8704 60 (¹) | 1,3 % | — | 31.12.2026 |
| 0.8991 | *ex 8507 90 31 | 20 | Separator for the manufacture of lithium-ion batteries, in rolls, made of transparent, microporous, acrylic acid grafted polyethylene film, with: — a width of 98 mm or more but not more than 170 mm, — a thickness of 15 µm or more but not more than 36 µm | 1,3 % | — | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8992 | *ex 8507 90 31 | 30 | <p>Separator for the manufacture of lithium-ion batteries, in rolls, made of microporous monolayer film of polypropylene or a microporous trilayer film of polypropylene, polyethylene and polypropylene, each film with:</p> <ul style="list-style-type: none"> — zero transversal production direction (TD) shrinkage, — a total thickness of 8 µm or more, but not more than 40 µm, — a width of 15 mm or more, but not more than 900 mm, — a length of more than 200 m, but not more than 8 000 m, — an average pore size between 0,02 µm and 0,1 µm, — whether or not coated with surfactant, — whether or not coated on 1 or 2 sides with a ceramic layer of min 1 µm thickness or more, but not more than 5 µm, — whether or not coated on 1 or 2 sides with a sticky binder, PVdF type or similar of min 0,5 µm thickness or more, but not more than 5 µm | 1,3 % | — | 31.12.2030 |
| 0.7280 | *ex 8507 90 31 | 40 | <p>Separator for the manufacture of lithium-ion batteries made of a multi-porous multilayer separator foil with:</p> <ul style="list-style-type: none"> — one microporous polyethylene layer between two microporous polypropylene layers and whether or not coated with aluminium oxide on both sides, — a width of 65 mm or more but not more than 170 mm, — a total thickness of 10 µm or more but not more than 30 µm, — a porosity of 25 % (vol.) or more but not more than 65 % (vol.) | 1,3 % | m ² | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8419 | *ex 8507 90 80 | 55 | <p>Top cap or housing made of aluminium or ferrous alloy or stainless steel:</p> <ul style="list-style-type: none"> — whether or not including parts made of aluminium and aluminium alloy, — with or without sealing elements or other elements made of polymer material, — with or without a “current interrupt device” and an “evacuation valve” — with or without plastic sockets — with an outer diameter of 17 mm or more, but not more than 18 mm, or rectangular with: — length not greater than 450 mm, — width not greater than 200 mm, and — height not greater than 150 mm, <p>for use in the manufacture of lithium-ion batteries ⁽¹⁾</p> | 1,3 % | — | 31.12.2026 |
| 0.6304 | ex 8511 30 00 | 30 | <p>Igniter integrated coil assembly with:</p> <ul style="list-style-type: none"> — an igniter, — a coil on plug assembly with an integrated mounting bracket, — a housing, — a length of 90 mm or more but not more than 200 mm (± 5 mm), — an operating temperature of -40 °C or more but not more than 130 °C, — a voltage of 10,5 V or more, but not more than 16 V | 0 % | p/st | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.7024 | ex 8511 30 00 | 55 | <p>Ignition coil:</p> <ul style="list-style-type: none"> — with a length of 50 mm or more, but not more than 200 mm, — with an operating temperature of – 40 °C or more, but not more than 140 °C, and — with a voltage of 9 V or more, but not more than 16 V, — with or without connection cable, <p>for use in the manufacture of engines of motor vehicles (¹)</p> | 0 % | — | 31.12.2026 |
| 0.8628 | ex 8511 80 00 | 30 | <p>Ignition module:</p> <ul style="list-style-type: none"> — made with plastics and non-ferrous metals, — with the electric components cast in epoxy resin, — to generate the ignition energy and to electronically control the ignition timing, — to connect spark plug and circuit breaker, <p>for use in the manufacture of two-stroke engines (¹)</p> | 0 % | — | 31.12.2028 |
| 0.8633 | ex 8512 20 00 | 25 | <p>An electrical component with an integrated LED, in an ABS housing, with:</p> <ul style="list-style-type: none"> — a voltage of 11 V or more, but not more than 15 V, — a circular shape, — 2 terminals, — an outer diameter of the housing of 36 mm or more, but not more than 42,5 mm, — a diode voltage of 42 V or more, but not more than 48 V, and — a current of 55 mA or more, but not more than 65 mA | 0 % | — | 31.12.2028 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8961 | *ex 8512 20 00 | 35 | <p>Sub-assembly reflectors and components for car rear lights:</p> <ul style="list-style-type: none"> — containing two or three PCBA with a connection socket and LED, — with central control module (CCE) connected through wired harness, — with a main reflector, a sub-reflector and inner lens scattering the light made of plastic, — with depth of 119 mm or more, but not more than 146 mm, — with width of 142 mm or more, but not more than 490 mm, — with a height of 93 mm or more, but not more than 100 mm, — a weight of 414 g or more, but not more than 578 g, — with lightguide | 0 % | — | 31.12.2030 |
| 0.6562 | ex 8512 20 00 | 60 | <p>Information screen displaying:</p> <ul style="list-style-type: none"> — at least time, date and status of safety features in a vehicle, or — safety information on driving in the lane, blind spot, distance from the vehicle in front, current speed, speed limit, <p>with an operating voltage of 12 V or more but not more than 14,4 V, of a kind used in the manufacturing of goods of Chapter 87</p> | 0 % | p/st | 31.12.2029 |
| 0.8409 | ex 8512 20 00 | 70 | <p>Electrical component with light guide integrated with LED, for motor vehicles with:</p> <ul style="list-style-type: none"> — two parallel ribs in the front area with a distance between them of 1,4 mm or more but not more than 1,8 mm, — four holes with the dimension of 7,3 mm or more but not more than 7,9 mm in the short direction of the guide, and — a 3 pin connector, <p>for use in the manufacture of automotive components ⁽¹⁾</p> | 0 % | — | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|--------------------------------|----------|---|-------------------------|--------------------|-------------------------------------|
| 0.8410 | ex 8512 20 00 | 80 | <p>Grab handle light with integrated LED, for motor vehicles:</p> <ul style="list-style-type: none"> — a distance between integrated spring clip and surface of 0,85 mm or more but not more than 1,85 mm, — a length of the housing to two front vertical ribs of 26,45 mm or more but not more than 26,75 mm, and — four horizontal ribs where the distance on the lower area over the base radii between the two is 18,5 mm or more but not more than 18,7 mm, <p>for use in the manufacture of automotive components (¹)</p> | 0 % | — | 31.12.2027 |
| 0.6863 | ex 8512 30 90 | 20 | <p>Warning buzzer for parking sensor system in a plastic casing operating on the piezo-mechanic principle, containing:</p> <ul style="list-style-type: none"> — a printed circuit board, — a connector, — whether or not a metal holder, <p>for use in the manufacture of goods of chapter 87 (¹)</p> | 0 % | p/st | 31.12.2029 |
| 0.5983 | ex 8512 40 00 ex 8516 80 20 | 10 20 | <p>Car door mirror heating foil:</p> <ul style="list-style-type: none"> — with two electrical contacts, — with an adhesive layer on both sides (on the side of the plastic holder of the mirror and on the side of the mirror glass), — with a protective paper film on both sides | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8391 | ex 8516 10 80 | 10 | <p>Tubular Heating Element with mounting flange for washing machines, with:</p> <ul style="list-style-type: none"> — a nominal output power of 1 700 W at 230 V AC supply voltage, — a weight of 230 g or more but not more than 250 g, — a thickness of the external flange of 2 mm or more, — isolation bushes of steatite or ceramic, and — no flat zones in the design, <p>for use in the manufacture of home appliance products and their components ⁽¹⁾</p> | 0 % | p/st | 31.12.2027 |
| 0.5845 | ex 8516 90 00 | 70 | <p>Inner pot:</p> <ul style="list-style-type: none"> — containing side and central openings, — of annealed aluminium, — with a ceramic coating, heat resistant to more than 200 °C <p>for use in the manufacture of an electric fryer ⁽¹⁾</p> | 0 % | p/st | 31.12.2027 |
| 0.6316 | ex 8528 59 00 | 20 | <p>Liquid crystal display colour video monitor assembly mounted on a frame,</p> <ul style="list-style-type: none"> — excluding those combined with other apparatus, — comprising touch screen facilities, a printed circuit board with drive circuitry and power supply, <p>used for permanent incorporation or permanent mounting into entertainment systems for vehicles ⁽¹⁾</p> | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.7048 | ex 8536 41 10 | 20 | Photoelectric (so called photovoltaic) relay consisting of a GaAlAs light-emitting diode, a galvanically isolated input circuit with a photovoltaic generator and a power MOSFET output switch in a casing with connections for a voltage of 60 volts or less and a current of 2 amps or less | 0 % | — | 31.12.2026 |
| 0.6180 | ex 8536 41 90 | 40 | Power relay with: <ul style="list-style-type: none"> — electromechanical and/or electromagnetical switching function, — a load current of 3 A or more but not more than 16 A, — a coil voltage of 5 V or more but not more than 24 V, and — a distance between the connector pins of the load circuit not more than 15,6 mm | 0 % | p/st | 31.12.2029 |
| 0.8735 | *ex 8536 41 90 | 60 | Power relay with the function of safely connecting or disconnecting the charging and/or power circuit of 48 V batteries in a plastic housing, containing: <ul style="list-style-type: none"> — current sensor 50 A/400 V, — high voltage MILD fuse 70 V/300 A, — whether or not cable with connector, for use in the production of rechargeable batteries for hybrid and electric vehicles ⁽¹⁾ | 1,1 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.7052 | ex 8536 49 00 | 40 | Photoelectric (so called photovoltaic) relay consisting of two GaAlAs light-emitting diodes, two galvanically isolated input circuits with photovoltaic generator(s) and four power MOSFET output switches in a casing with connections for a voltage of more than 60 volts | 0 % | — | 31.12.2026 |
| 0.7796 | ex 8536 49 00 | 60 | Relay in the shape of a cube with: — a coil operating voltage of 12 VDC (Voltage Direct Current) or more, but not more than 24 VDC (Voltage Direct Current), — a contact current carrying capacity of 5A or more, but not more than 15 A, — a contact voltage of 80 VAC (Voltage Alternating Current) or more, but not more than 270 VAC (Voltage Alternating Current), — outer dimensions of 19 mm ($\pm 0,4$ mm) x 15,2 mm ($\pm 0,4$ mm) x 15,5 mm ($\pm 0,4$ mm), for use in the production of control board of household appliances (¹) | 0 % | — | 31.12.2029 |
| 0.4614 | ex 8536 69 90 | 82 | Modular socket or plug for local area networks, whether or not combined with other sockets, integrating at least: — a pulse transformer, including a wide-band ferrite core, — a common mode coil, — a resistor, — a capacitor, for use in the manufacture of products falling within headings 8521 or 8528 (¹) | 0 % | p/st | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.4616 | ex 8536 69 90 | 83 | AC socket with a noise filter, composed of: — AC socket (for power cord connection) of 230 V, — integrated noise filter composed of capacitors and inductors, — cable connector for connecting an AC socket with the PDP (Plasma display panel) power supply unit, whether or not equipped with a metal support, which joins the AC socket to the PDP TV set | 0 % | p/st | 31.12.2029 |
| 0.5318 | ex 8536 69 90 | 85 | Socket or plug, built into a plastic or metal housing, with no more than 96 pins, for use in the manufacture of products falling within headings 8521 or 8528 (¹) | 0 % | p/st | 31.12.2026 |
| 0.5316 | ex 8536 69 90 | 86 | High-Definition Multimedia Interface (HDMI) type socket or plug, built into a plastic or metal housing, with 19 pins or 20 pins in 2 rows, for use in the manufacture of products falling within headings 8521 or 8528 (¹) | 0 % | p/st | 31.12.2026 |
| 0.5181 | ex 8536 70 00 | 10 | Optical socket, plug or connector, for use in the manufacture of goods falling within headings 8521 or 8528 (¹) | 0 % | p/st | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8405 | ex 8537 10 91 | 25 | <p>A control unit being a printed circuit board with at least:</p> <ul style="list-style-type: none"> — a microprocessor, — a programmable memory, — a single connector, — a PPE housing, — a supply of voltage of 220 V or more but not more than 240 V, — a length of 200 mm or more but not more than 210 mm, — a width of 70 mm or more but not more than 100 mm, and — a height of 20 mm or more but not more than 30 mm, <p>for use in the manufacture of dishwashers (¹)</p> | 0 % | — | 31.12.2027 |
| 0.8392 | ex 8537 10 91 | 35 | <p>A control unit being a printed circuit board with at least:</p> <ul style="list-style-type: none"> — a microprocessor, — a programmable memory, — two or more connectors, but not more than twelve, — with or without LCD display, — with or without WiFi module, and — with or without an integrated speaker, <p>for use in the manufacture of built-in ovens (¹)</p> | 0 % | — | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.8460 | ex 8537 10 91 | 43 | <p>Electronic suspension control unit with:</p> <ul style="list-style-type: none"> — a printed circuit board in plastic housing, — LIN and CAN buses, — a programmable memory, — a signal processor, — an operating direct current voltage of 9 V or more but not more than 16 V, — at least one connector, — whether or not with metal mounting bracket, <p>for use in the manufacture of goods of Chapter 87 (¹)</p> | 0 % | — | 31.12.2027 |
| 0.8085 | *ex 8537 10 91 | 45 | <p>Main hybrid system controller, diagnosing and controlling the elements of the hybrid propulsion system, with:</p> <ul style="list-style-type: none"> — a programmable memory, — a microprocessor, — at least one composite connector, — a voltage of 24 V, — with a length of 350 mm or more but not more than 400 mm, — with a width of 200 mm or more but not more than 250 mm, — with a height of 80 mm or more but not more than 120 mm, — in a metal housing | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8985 | *ex 8537 10 91 | 48 | <p>Control unit for the automatic transmission oil pump for efficient cooling and oil pressure regulation in the car's drivetrain:</p> <ul style="list-style-type: none"> — liquid-cooled, — with an operating voltage of 9 V DC or more, but not more than 16 V, — with a height of 165 mm or more, but not more than 190 mm, — with a width of 40 mm or more, but not more than 60 mm, — with a length of 170 mm or more, but not more than 195 mm, — in a casing, — with one or more connectors, and <p>for use in the manufacture of hybrid motor vehicles (¹)</p> | 0 % | — | 31.12.2030 |
| 0.7627 | ex 8537 10 91 | 57 | <p>Programmable memory control board with:</p> <ul style="list-style-type: none"> — 4 or more stepper motor drivers, — 4 or more outputs with MOSFET transistors, — a main processor, — 3 or more inputs for temperature sensors, — for a voltage of 10 V or more but not more than 30 V, <p>for use in the manufacture of 3D printers (¹)</p> | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|--------------------------------|----------|--|-------------------------|--------------------|-------------------------------------|
| 0.6163 | ex 8537 10 91 ex 8537 10 98 | 60 45 | Electronic control units, manufactured according to class 2 of IPC-A-610E standard, with at least: — an AC power input of 208 V or more but not more than 400 V, — a logic power input of 24 V DC, — an automatic circuit breaker, — a main power switch, — internal or external electrical connectors and cables, — in a housing with dimension of 281 mm x 180 mm x 75 mm or more, but not more than 630 mm x 420 mm x 230 mm, of a kind used for manufacturing recycling or sorting machines | 0 % | p/st | 31.12.2029 |
| 0.7251 | ex 8537 10 91 | 70 | Programmable motor memory controller for a voltage not exceeding 1 000 V, comprising at least: — a printed circuit with active and passive components, — an aluminium housing, and — multiple connectors | 0 % | p/st | 31.12.2027 |
| 0.8841 | ex 8537 10 91 | 75 | Printed circuit board equipped with a microcontroller for operating and/or control purposes — with or without operating components, signal components and display, — for operating voltages of 5V DC or more but not more than 12V DC or 220V AC or more but not more than 400V AC, for use in the manufacture of household appliances of subheadings 7321 11, 8414 60, 8418 10, 8418 21, 8418 29, 8418 40, 8422 11, 8450 11, 8450 12, 8450 19, 8450 20, 8451 21, 8451 29, 8516 60 (¹) | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.6140 | ex 8537 10 98 | 30 | <p>Motor bridge ICs without programmable memory consisting of:</p> <ul style="list-style-type: none"> — one or more integrated circuits, not interconnected, on separate lead frames, — also with discrete Metal Oxide Field Effect Transistors (MOSFET) for controlling DC motors in cars — mounted in a plastic housing | 0 % | p/st | 31.12.2029 |
| 0.7194 | ex 8537 10 98 | 33 | <p>Lever for control module under the steering wheel:</p> <ul style="list-style-type: none"> — with several single or multi-positional electrical switches (push-button, rotary or other), — equipped with printed circuit boards and/or electrical cables, — for a voltage of 9 V or more but not more than 16 V, <p>of a kind used in the manufacture of motor vehicles of Chapter 87</p> | 0 % | p/st | 31.12.2026 |
| 0.8401 | ex 8537 10 98 | 38 | <p>Control panel with switches for mirror, windows and other functions in vehicles, with:</p> <ul style="list-style-type: none"> — a total length of 144 mm or more but not more than 150 mm, — a distance between intended screwing interface center points of 31 mm or more but not more than 31,50 mm, and — electric components inside the panel with integrated LEDs, <p>for use in the manufacture of automotive components (¹)</p> | 0 % | — | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.8408 | ex 8537 10 98 | 43 | Switch for motor vehicle seat regulation with a memory function, with: — three single switches, — a five-pin connector, — for a voltage of 9 VDC or more but not more than 16 VDC, and — electric components inside the panel with integrated LED, for use in the manufacture of automotive components (¹) | 0 % | — | 31.12.2027 |
| 0.8400 | ex 8537 10 98 | 48 | Memory switch control panel for seat and lock switch for vehicles with: — a width of 70,2 mm or more but not more than 70,5 mm, — parallel ribs with a distance between them of 2,6 mm or more but not more than 2,8 mm on the rear side, — a 5 pin connector, and — electric components inside the panel with integrated LED, for use in the manufacture of automotive components (¹) | 0 % | — | 31.12.2027 |
| 0.6507 | ex 8537 10 98 | 50 | Electronic control unit BCM (Body Control Module) or IBM (Integrated Body Control Module) or similar: — comprising at least a plastic box with printed circuit board, with operating direct voltage of 9 V or more, but not more than 16 V, — whether or not with metal holder, — able to control, evaluate and manage functions of assisting services in an automobile, at least wiper timing, window heating, interior lighting, seat belt reminder, of a kind used in the manufacture of goods of Chapter 87 | 0 % | p/st | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8407 | ex 8537 10 98 | 53 | <p>A control unit being a printed circuit board with at least:</p> <ul style="list-style-type: none"> — a microprocessor, — two or more connectors but not more than four, — modified resins, — a length of 180 mm or more but not more than 250 mm, — a width of 130 mm or more but not more than 200 mm, and — a height of 40 mm or more but not more than 60 mm, <p>for use in the manufacture of washing machines ⁽¹⁾</p> | 0 % | — | 31.12.2027 |
| 0.8393 | ex 8537 10 98 | 57 | <p>A control unit being a printed circuit board with at least:</p> <ul style="list-style-type: none"> — a microprocessor, — eight connectors or more but not more than eleven, — a supply voltage of 215 V or more but not more than 245 V, — a housing of PA6-MR30, — with or without a transformer, — with or without a high power relay, — with or without insulated-gate bipolar transistor, — a length of 280 mm or more but not more than 345 mm, — a width of 400 mm or more but not more than 470 mm, — a height of 28 mm or more but not more than 45 mm, <p>for use in the manufacture of induction stoves ⁽¹⁾</p> | 0 % | — | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------------------------|----------|--|-------------------------|--------------------|-------------------------------------|
| 0.8406 | ex 8537 10 98 | 63 | <p>A control unit being a printed circuit board with at least:</p> <ul style="list-style-type: none"> — a microprocessor, — two connectors, — a supply voltage of 215 V or more but not more than 245 V, — no housing, — a length of 100 mm or more but not more than 120 mm, — a width of 40 mm or more but not more than 50 mm, and — a height of 20 mm or more but not more than 30 mm, <p>for use in the manufacture of refrigerators (¹)</p> | 0 % | — | 31.12.2027 |
| 0.3663 | ex 8537 10 98 | 93 | Electronic control units for a voltage of 12 V, for use in the manufacture of vehicle mounted temperature control systems (¹) | 0 % | p/st | 31.12.2027 |
| 0.6866 | *ex 8538 90 91 ex 8538 90 99 | 20 50 | <p>Interior antenna for a car door locking system, comprising:</p> <ul style="list-style-type: none"> — an antenna module in a plastic housing, — whether or not a connection cable with a plug, — whether or not a connector, — at least one mounting bracket, — whether or not PCB including integrated circuits, diodes and transistors, <p>for use in the manufacture of goods of Chapter 87 (¹)</p> | 0 % | p/st | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.7195 | ex 8538 90 99 | 60 | Front control panel, in the form of a plastic box, with light guides, rotary switches, pressure switches and buttons switches, or other type of switches, without any electrical component, of a kind used in the dashboard of motor vehicles of Chapter 87 | 0 % | p/st | 31.12.2026 |
| 0.2580 | ex 8540 20 80 | 91 | Photomultiplier | 0 % | — | 31.12.2026 |
| 0.3445 | ex 8540 89 00 | 91 | Displays in the form of a tube consisting of a glass housing mounted on a board the dimensions of which do not exceed 300 mm × 350 mm excluding leads. The tube contains one or more rows of characters or lines arranged in rows, each character or line consisting of fluorescent or phosphorescent elements. These elements are mounted on a metallised base which is covered with fluorescent substances or phosphorescent salts which give off light when bombarded with electrons | 0 % | — | 31.12.2029 |
| 0.7409 | ex 8540 91 00 | 20 | Thermionic electron source (emitter point) of lanthanum hexaboride (CAS RN 12008-21-8) or cerium hexaboride (CAS RN 12008-02-5), with electric connectors <ul style="list-style-type: none">— with or without a metal housing,— with or without a graphite carbon shield mounted in a mini-Vogel type system,— with or without separate pyrolytic carbon blocks used as heating elements, and— a cathode temperature of less than 1 800 K at a filament current of 1,26 A | 0 % | — | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.7130 | ex 8543 70 90 | 15 | Laminated electrochromic film consisting of: — two outer layers of polyester, — a middle layer of acrylic polymer and silicone, and — two electric connection terminals | 0 % | — | 31.12.2026 |
| 0.8333 | ex 8543 70 90 | 27 | Electronic control unit of the 360-degree vehicle situation display system with: — an operating DC voltage of 9 V or more but not more than 16 V, — a videoprocessor, — a signal processor, — one or more connectors, and — whether or not with a metal mounting bracket, for use in the manufacture of goods of Chapter 87 (¹) | 0 % | — | 31.12.2027 |
| 0.2826 | ex 8543 70 90 | 30 | Amplifier, consisting of active and passive elements mounted on a printed circuit, contained in a housing | 0 % | p/st | 31.12.2029 |
| 0.7055 | ex 8543 70 90 | 33 | High-frequency amplifier comprising one or more integrated circuits and one or more discrete capacitor chips, whether or not with IPD (integrated passive devices) on a metal flange in a housing | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.2590 | ex 8543 70 90 | 45 | Piezo-electric crystal oscillator with a fixed frequency, within a frequency range of 1,8 MHz to 67 MHz, contained in a housing | 0 % | p/st | 31.12.2029 |
| 0.3131 | ex 8543 70 90 | 55 | Opto-electronic circuit comprising one or more light-emitting diodes (LEDs), whether or not equipped with an integrated driving circuit, and one photodiode with amplifier circuit, whether or not with an integrated logic gate arrays circuit or one or more light-emitting diodes and at least 2 photodiodes with an amplifier circuit, whether or not with an integrated logic gate arrays circuit or other integrated circuits, contained in a housing | 0 % | p/st | 31.12.2029 |
| 0.2816 | ex 8543 70 90 | 85 | Voltage controlled oscillator (VCO), other than temperature compensated oscillators, consisting of active and passive elements mounted on a printed circuit, contained in a housing | 0 % | p/st | 31.12.2029 |
| 0.6709 | ex 8544 20 00 | 30 | Antenna connecting cable for the transmission of radio (AM/FM) signal and whether or not GPS signal, containing: — a coaxial cable, — two or more connectors, and — 3 or more plastic clips for attachment to the dashboard of a kind used in the manufacture of goods of Chapter 87 | 0 % | — | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------------------------|----------|--|-------------------------|--------------------|-------------------------------------|
| 0.8849 | ex 8544 30 00 | 20 | <p>Insulated electrical multicore cable for the EPS-system (Electrical Power Steering) of a motor vehicle:</p> <ul style="list-style-type: none"> — with a length of 170 mm or more but not more than 301 mm, — with an external diameter of 4,5 mm or more but not more than 7 mm, — with an operating temperature of – 40 °C or more but not more than 125 °C, — with Cross-Linked Polyethylene (XLPE) or Thermoplastic Polyester Elastomer (TPE-E) wire insulation material, — with an operating voltage of 5 V, — fitted with connectors at both ends, — whether or not gold-plated or tin-plated | 0 % | — | 31.12.2029 |
| 0.6377 | ex 8544 30 00 | 40 | <p>Wire harness or cable for steering system:</p> | 0 % | p/st | 31.12.2029 |
| | ex 8544 42 90 | 40 | <ul style="list-style-type: none"> — for an operating voltage of 12 V, — with connectors on both sides, — whether or not with anchor clamps of plastic for mounting on a motor vehicle steering box | | | |
| 0.6710 | *ex 8544 30 00 ex 8544 42 90 | 60 50 | <p>Four-core connecting cable containing two female connectors for the transmission of digital signals from navigation and/or audio systems to a USB connector and/or LCD monitor, for use in the manufacture of goods of Chapter 87⁽¹⁾</p> | 0 % | — | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.8331 | ex 8544 30 00 | 65 | <p>Six core cable connecting the oil pressure sensor and the differential controller of vehicles:</p> <ul style="list-style-type: none"> — with PVC-coating, — with three multiple connectors, and — with or without plastic clip, <p>for use in the manufacture of goods of Chapter 87 (¹)</p> | 0 % | — | 31.12.2027 |
| 0.8647 | ex 8544 30 00 | 75 | <p>Wiring harness to connect the integrated battery system with the car's control systems, containing:</p> <ul style="list-style-type: none"> — an input waterproof connector, — four or more output connectors, — two or more plastic clips for attachment <p>for use in the production of rechargeable batteries for hybrid and electric vehicles (¹)</p> | 0 % | — | 31.12.2028 |
| 0.6867 | *ex 8544 30 00 | 85 | <p>Extension two-core cable with two connectors, containing at least:</p> <ul style="list-style-type: none"> — a rubber grommet, — a metal attachment bracket, <p>of a kind used to connect vehicle speed sensors in the manufacture of vehicles of Chapter 87</p> | 0 % | p/st | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---|----------------|---|-------------------------|--------------------|-------------------------------------|
| 0.4980 | ex 8544 42 90 | 10 | <p>Data transmission cable capable of a bit rate transmission of 600 Mbit/s or more, with:</p> <ul style="list-style-type: none"> — a voltage of 1,25 V ($\pm 0,25$ V) — connectors fitted at one or both ends, at least one of which contains pins with a pitch of 1 mm, — outer screening shielding, <p>used solely for communication between LCD, PDP or OLED panel and video processing electronic circuits</p> | 0 % | p/st | 31.12.2029 |
| 0.4464 | ex 8544 42 90 ex 8544 49 93 ex 8544 49 95 | 20 20 10 | <p>PET or PVC insulated flexible cable with or without connector with:</p> <ul style="list-style-type: none"> — voltage of not more than 250 V, — a current of not more than 1 A, — a heat resistance of not more than 105 °C, — individual wires of a thickness of not more than 0,1 mm ($\pm 0,01$ mm) and a width of not more than 0,8 mm ($\pm 0,03$ mm), — a distance between conductors of not more than 0,5 mm and — a pitch (distance from centreline to centreline of conductors) of not more than 1,25 mm | 0 % | — | 31.12.2028 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|--------------------------------|----------|---|-------------------------|--------------------|-------------------------------------|
| 0.8572 | ex 8544 42 90 ex 8544 60 10 | 45 10 | <p>Specially designed connector for solar power system:</p> <ul style="list-style-type: none"> — as 1-part system with 1 plastic housing with 1 or more but not more than 4 diodes and 2 insulated copper cables with connectors or — as 3-part system with one plastic housing with 1 or more but not more than 4 diodes and 2 plastic housings with insulated copper cables with connectors, — with a current for the diodes of 3 A or more but not more of 50 A, — with a cable length of not more than 1 500 mm, — with a maximum rated voltage of 1 500 V | 0 % | — | 31.12.2028 |
| 0.8859 | ex 8544 42 90 | 55 | <p>Wire harness for the transmission of signals and/or electrical power,</p> <ul style="list-style-type: none"> — with a 26-PIN or 28-PIN wire to board connectors in crimping technology, — bound by rubber or vinyl or electrical tape or conduit or a weave of extruded string or a combination thereof, <p>for connection of power supply with main printed (circuit) board assembly (PBA) and electrical components of refrigerator or washing machine (¹)</p> | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.6853 | *ex 8544 42 90 | 70 | Electric conductors: — of a voltage of not more than 80 V, — with a length of not more than 120 cm, — fitted with connectors, for use in the manufacture of hearing aids, accessory kits and speech processors (¹) | 0 % | p/st | 31.12.2030 |
| 0.2424 | ex 8544 49 93 | 10 | Elastomeric connector, of rubber or silicone, consisting of one or more conductor elements | 0 % | p/st | 31.12.2029 |
| 0.6861 | *ex 8544 49 93 | 30 | Electric conductors: — of a voltage of not more than 80 V, — of a platinum-iridium-alloy, — coated with poly(tetrafluoroethylene), — without connectors, for use in the manufacture of hearing aids, implants and speech processors (¹) | 0 % | m | 31.12.2030 |
| 0.3144 | ex 8548 00 90 | 41 | Unit, consisting of a resonator operating within a frequency range of 1,8 MHz or more but not more than 40 MHz and a capacitor, contained in a housing | 0 % | p/st | 31.12.2029 |
| 0.3193 | ex 8548 00 90 | 43 | Contact image sensor | 0 % | p/st | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------------------------|----------|---|-------------------------|--------------------|-------------------------------------|
| 0.3763 | ex 8548 00 90 | 48 | Optical unit, containing at least <ul style="list-style-type: none">— a laser diode and a photodiode operating at a typical wavelength of 635 nm or more but not more than 815 nm— an optical lens— a “Recording Photodetector Integrated Circuit” (PDIC)— a focussing and tracking actuator | 0 % | p/st | 31.12.2026 |
| 0.8972 | *ex 8549 13 20 | 10 | Spent electric accumulators of lithium-ion or nickel metal hydride | 0 % | — | 31.12.2030 |
| 0.7165 | ex 8708 10 10 ex 8708 10 90 | 10 10 | Plastic cover for filling the space between the fog lights and the bumper whether or not with a chrome strip for use in the manufacture of goods of Chapter 87 (i) | 0 % | p/st | 31.12.2026 |
| 0.6590 | ex 8708 30 10 ex 8708 30 91 | 40 30 | Body of disc type brake in BIR (“Ball in Ramp”) or EPB (“Electronic Parking Brake”) or with hydraulic function only, containing functional and mounting openings and guide grooves, of a kind used in the manufacture of goods of Chapter 87 | 0 % | p/st | 31.12.2029 |
| 0.6707 | *ex 8708 30 10 ex 8708 30 91 | 70 40 | Ductile cast iron brake caliper jaw, of a kind used in the manufacture of goods of Chapter 87 | 0 % | p/st | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------------------------|----------|---|-------------------------|--------------------|-------------------------------------|
| 0.6869 | *ex 8708 40 20 ex 8708 40 50 | 20 10 | Automatic hydrodynamic gearbox — with a hydraulic torque converter, — without transfer box and cardan shaft, — whether or not with front differential, for use in the manufacture of motor vehicles of Chapter 87 (¹) | 0 % | p/st | 31.12.2030 |
| 0.8820 | ex 8708 40 20 | 25 | Transmission assembly consisting of: — double pinion type planetary gear shifting mechanism, — sport sequential shiftmatic system with a speed of 7 or more but not more than 10, — a width of 280 mm or more but no more than 470 mm, — a height of 350 mm or more but no more than 595 mm, — a length of 410 mm or more but no more than 690 mm, — a weight of 70 kg or more but no more than 110 kg, for use in the manufacture of motor vehicles of subheading 8703 22 and 8703 23 (¹) | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------------------------|----------|---|-------------------------|--------------------|-------------------------------------|
| 0.7856 | *ex 8708 40 20 ex 8708 40 50 | 70 60 | Manual gearbox in cast aluminium housing for transverse installation with: — maximum dimensions of 550 x 500 x 600 mm — five or six gears, — a differential gear, — an engine torque of 400 Nm or less, for use in the manufacture of motor vehicles of heading 8703 (¹) | 0 % | — | 31.12.2029 |
| 0.8279 | *ex 8708 40 20 | 80 | Transmission gearbox without torque converter, with: — dual clutch, — 7 or more forward gears, — 1 reverse gear, — a maximum torque of 450 Nm, — whether or not with electric motor integrated, — a height of 350 mm or more but not more than 600 mm, — a width 350 mm or more but not more than 600 mm, and — a weight of 70 kg or more but not more than 110 kg, for use in the manufacture of motor vehicles of heading 8703 (¹) | 0 % | p/st | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8819 | *ex 8708 40 50 | 25 | <p>Transmission assembly housing 3 other shafts inside it and offering a rotating switch for shift position, consisting of:</p> <ul style="list-style-type: none"> — cast aluminium body, — differential gear, — 2 electrical motors and gears, — a width of 280 mm or more but no more than 470 mm, — a height of 350 mm or more but no more than 595 mm, — a length of 410 mm or more but no more than 690 mm, <p>for use in the manufacture of motor vehicles of subheadings 8703 40 and 8703 60⁽¹⁾</p> | 0 % | — | 31.12.2029 |
| 0.8377 | ex 8708 40 50 | 70 | <p>Automatic transmission equipped with double clutch system with:</p> <ul style="list-style-type: none"> — at least 8 gears, — an engine torque of 800 Nm or more, — an electronic differential, — a P-lock safety system, and — a TCU transmission control unit, <p>for use in the manufacture of motor vehicles of heading 8703⁽¹⁾</p> | 0 % | — | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------------------------|----------|---|-------------------------|--------------------|-------------------------------------|
| 0.7987 | *ex 8708 50 20 ex 8708 50 55 | 15 50 | Spherical outboard constant velocity joint ball bearing cage, part of the vehicle's drive system, made of material suitable to be carburized with a carbon content of 0,14 % or more but not more than 0,57 %, forged, turned, punched, milled and hardened | 0 % | — | 31.12.2030 |
| 0.8461 | ex 8708 50 20 | 18 | Propeller shaft for torque transmission from the gearbox to the rear axle, consisting of: — two cardan rods, — central universal joint, — central bearing with suspension in a plastic cover, — universal joints on both ends of the shaft, — slip, tube and end yokes, — of a length of 1,4 m or more but not more than 2,4 m, for use in the production of goods of Chapter 87 (1) | 0 % | — | 31.12.2027 |
| 0.6648 | *ex 8708 50 20 ex 8708 50 99 | 20 10 | Transmission shaft in carbon fibre reinforced plastics consisting of a unique piece without any joint in the middle — of a length of 1 m or more but not more than 2 m, — of a weight of 6 kg or more but not more than 9 kg | 0 % | p/st | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------------------------|----------|--|-------------------------|--------------------|-------------------------------------|
| 0.7988 | *ex 8708 50 20 ex 8708 50 99 | 25 45 | <p>Ball-type outboard constant velocity joint housing for transmitting a torque from the engine and transmission to the wheels of motor vehicles, in a form of an outer race, with:</p> <ul style="list-style-type: none"> — 6 ball tracks or more but not more than 8, with — a thread, — an external involute spline with 21 or more but not more than 38 teeth, — for running with bearing balls made of steel with a carbon content of 0,48 % or more but not more than 0,57 %, — forged, turned, milled and hardened | 0 % | — | 31.12.2030 |
| 0.7989 | *ex 8708 50 20 ex 8708 50 99 | 35 50 | <p>Inboard constant velocity joint tripod housing, with:</p> <ul style="list-style-type: none"> — an outer diameter of 67,0 mm or more but not more than 99,0 mm, — 3 cold calibrated roller tracks with a diameter of 29,95 mm or more but not more than 49,2 mm, — an external spline with 21 teeth or more but not more than 41, — forged, turned, rolled and hardened | 0 % | — | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|--|----------------------|--|-------------------------|--------------------|-------------------------------------|
| 0.7359 | ex 8708 50 20 ex 8708 50 55 ex 8708 50 91 ex 8708 50 99 | 50 20 10 40 | Double flange bearing of 3rd generation, for motor vehicles, — with double-row ball bearing, — whether or not with impulse (encoder) ring, — whether or not with antilock brake system (ABS) sensor, — whether or not with mounted screws, for use in the manufacture of goods of Chapter 87 (¹) | 0 % | — | 31.12.2027 |
| 0.7991 | *ex 8708 50 20 ex 8708 50 99 | 55 60 | Inboard constant velocity joint tripod spider, part of the vehicle's drive system, with: — 3 trunnions with a diameter of 17,128 mm or more but not more than 25,468 mm, — forged, turned, broached and hardened | 0 % | — | 31.12.2030 |
| 0.7593 | ex 8708 50 20 ex 8708 50 99 | 70 25 | Housing of tripod type half shaft inboard joint for transmitting a torque from engine and transmission to wheels of motor vehicles with: — an outer diameter of 67,0 mm or more but not more than 84,5 mm, — 3 cold calibrated roller tracks with a diameter of 29,90 mm or more but not more than 36,60 mm, — sealing diameter 34,0 mm or more but not more than 41,0 mm, without lead angle, — spline with 21 teeth or more but not more than 35, — bearing seat diameter of 25,0 mm or more but not more than 30,0 mm, with or without oil grooves | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------------------------|----------|--|-------------------------|--------------------|-------------------------------------|
| 0.7640 | *ex 8708 50 20 ex 8708 50 99 | 75 35 | Constant velocity joint assembly for transmitting a torque from engine and transmission to wheels of motor vehicles, consisting of: — an inner race with 6 ball tracks or more but not more than 8 for running with the bearing balls with a diameter of 13,0 mm or more but not more than 28,0 mm, — an outer race with 6 ball tracks or more but not more than 8 for running with the bearing balls, made of steel with carbon content of 0,45 % or more but not more than 0,58 %, with thread and with a spline with 22 teeth or more but not more than 44, — a spherical cage keeping bearing balls in the ball tracks of outer race and inner race in proper angular position, made of material suitable for carburizing with carbon content of 0,14 % or more but not more than 0,55 %, and — with a grease compartment, — capable of working at constant speed at variable articulation angle not higher than 52 degrees | 0 % | — | 31.12.2029 |
| 0.6711 | *ex 8708 80 20 ex 8708 80 35 | 10 10 | Upper strut insulator containing: — a metal holder with three mounting screws, and — a rubber bump, for use in the manufacture of goods of Chapter 87 (¹) | 0 % | p/st | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------------------------|----------|---|-------------------------|--------------------|-------------------------------------|
| 0.7365 | ex 8708 80 99 | 30 | <p>Surface-hardened, steel piston rod for a hydraulic or hydropneumatic shock absorber of motor vehicles:</p> <ul style="list-style-type: none"> — with a chrome coating, — of a diameter of 11 mm or more, but not more than 28 mm, — of a length of 80 mm or more, but not more than 600 mm, <p>with a threaded end or a mandrel for resistance welding</p> | 0 % | — | 31.12.2027 |
| 0.6509 | ex 8708 91 20 ex 8708 91 35 | 20 10 | Aluminium cooler using compressed air with a ribbed design of a kind used in the manufacture of goods of Chapter 87 | 0 % | p/st | 31.12.2029 |
| 0.6859 | *ex 8708 91 20 ex 8708 91 99 | 30 30 | <p>Aluminium alloy inlet or outlet air tank of heat exchangers for car cooling systems, manufactured to standard EN AC 42100 or EN AC 43000 T6 with:</p> <ul style="list-style-type: none"> — an insulating area flatness of not more than 0,1 mm, — a permissible particle quantity of 0,3 mg per tank, — a distance between pores of 2 mm or more, — pore sizes of not more than 0,4 mm, and — not more than 3 pores larger than 0,2 mm, — with a weight of 0,2 kg or more but not more than 3 kg | 0 % | p/st | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.7716 | ex 8708 91 35 | 20 | <p>Turbocharger cooling duct containing:</p> <ul style="list-style-type: none"> — an aluminium alloy duct with at least one metal holder and at least two mounting holes, — a rubber pipe with clips, — a stainless steel flange highly resistant to corrosion [SUS430JIL], <p>for use in the manufacture of compression ignition engines of motor vehicles (¹)</p> | 0 % | — | 31.12.2029 |
| 0.8538 | ex 8708 91 35 | 30 | <p>Two-circuit aluminium heat exchanger for automatic transmission of passenger cars:</p> <ul style="list-style-type: none"> — of the stack-plate type, — with two pairs of inlet and outlet, each for the coolant/water circuit and the transmission oil circuit, — with at least two mounting holes, — whether or not with the connection hoses, <p>for use in the manufacture of goods of Chapter 87 (¹)</p> | 0 % | — | 31.12.2028 |
| 0.8812 | ex 8708 91 35 | 40 | <p>Radiators:</p> <ul style="list-style-type: none"> — with corrosion protection, — for pressures up to 150 PSI (1 034 kPa), — with individual replaceable, cooling tubes in brass or copper, <p>for use in the production of engine and charge air cooling with a weight of 265 kg or more but not more than 599 kg (¹)</p> | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8775 | ex 8708 94 99 | 10 | <p>Hub gear made of cold rolled carbon steel (per ASTM A1008), molded into the plastic and pressed on pinion, with:</p> <ul style="list-style-type: none"> — an outer diameter of 81,2 mm or more, but not more than 82,55 mm, — an inner diameter of 25,9 mm or more, but not more than 25,97 mm, — a height of the lower side of inner diameter of 11,63 mm or more, but not more than 12,13 mm, — a height of the upper side of inner diameter of 3,25 mm or more, but not more than 3,5 mm, — an overall height of 11,63 mm or more, but not more than 19,5 mm <p>for use in the manufacture of vehicle's steering system ⁽¹⁾</p> | 0 % | — | 31.12.2029 |
| 0.8777 | ex 8708 94 99 | 20 | <p>Intermediate steering shaft forming part of the steering column with:</p> <ul style="list-style-type: none"> — a torsional rigidity of 25 Nm/degree or more, — a tubular male shaft in welded carbon steel tube (per GB/T 699 grade 20), — a tubular female shaft in welded carbon steel tube (per with GB/T 699 grade 20), — two spiders universal joint made of chromium alloy steel (per GB/T 5216 grade 20CrMnTiH), — a length in nominal telescope position of 396 mm or more but not more than 467 mm, — a coupling interface on both ends with internal toothing, — two cardan joints on both sides, — a telescope shaft function with a range of 74 mm or more but not more than 115 mm, <p>for use in the manufacture of vehicle's steering system ⁽¹⁾</p> | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8778 | ex 8708 94 99 | 30 | <p>Lower assist shaft as part of the steering column made of carbon steel (per GB/T699 grade 45 or JIS G4051 grade S45C) with:</p> <ul style="list-style-type: none"> — an ultimate torsional strength load of 325 Nm or more and Johnson Apparent Elastic Limit (J.A.E.L) values of 275 Nm or more, — a length of 66,39 mm or more but not more than 88,64 mm, — an outer diameter of 27,47 mm or more but not more than 28,38 mm, — an inner hole of diameter 6,50 mm or more but not more than 6,58 mm, — an external 26-teeth spline with major diameter 21,18 mm or more but not more than 21,44 mm, — a knurling on a part of outer surface of major diameter 26,0 mm or more but not more than 26,1 mm, — with or without an external 24-tooth spline and with a major diameter 24,75 mm or more but not more than 25 mm, <p>for use in the manufacture of vehicle's steering system ⁽¹⁾</p> | 0 % | — | 31.12.2029 |
| 0.8779 | ex 8708 94 99 | 40 | <p>Upper assist shaft as part of the steering column made of carbon steel (per GB/T699 grade 45) with:</p> <ul style="list-style-type: none"> — an ultimate torsional strength load of 325 Nm or more and Johnson Apparent Elastic Limit (J.A.E.L) values of 275 Nm or more, — a length of 165,3 mm or more but not more than 204,2 mm, — an outer diameter of 22,87 mm or more but not more than 22,92 mm, — an internal hole of diameter 6,50 or more but not more than 6,58 mm, — an external spline, <p>for use in the manufacture of vehicle's steering system ⁽¹⁾</p> | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.8780 | ex 8708 94 99 | 50 | <p>Lower shaft as part of the steering column made of aluminium alloy (per ASTM B221M grade 6105), air quenched and tempered with:</p> <ul style="list-style-type: none"> — an ultimate torsional strength of 260 Nm or more, — a length of 296,7 mm or more but not more than 297,8 mm, — an external 18-tooth spline on all shaft length with major diameter of 28,7 mm or more but not more than 29 mm, — an 18-tooth internal spline with a minor diameter of 19,7 mm or more but not more than 20 mm, <p>for use in the manufacture of vehicle's steering system ⁽¹⁾</p> | 0 % | — | 31.12.2029 |
| 0.8782 | ex 8708 94 99 | 60 | <p>Torsion bar as part of the steering column made of carbon alloy steel (per SAE J1268, grade 5160H of modified chemistry for carbon content of 0,53 or more, but not more than 0,56) with:</p> <ul style="list-style-type: none"> — a shaft torsional stiffness of 2,5 Nm/degree or more but not more than 2,7 Nm/degree, — a length of 107,75 mm or more but not more than 108,25 mm, — an outer diameter of 6,38 mm or more but not more than 6,42 mm, — two external 18-tooth splines on both shaft ends with a major diameter of 6,70 mm or more but not more than 6,85 mm, as interface to pressing with matting input and output shafts, — entire surface shot peened, <p>for use in the manufacture of vehicle's steering system ⁽¹⁾</p> | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------------------------|----------|--|-------------------------|--------------------|-------------------------------------|
| 0.8781 | ex 8708 94 99 | 70 | <p>Tubular steering shaft as part of the steering column made of carbon steel welded tube (per EN 10305/2, E235 + C or GB/T699 grade 20) with:</p> <ul style="list-style-type: none"> — an ultimate torsional strength of 300 Nm or more and Johnson Apparent Elastic Limit (J. A.E.L) values of 275 Nm or more, — a length of 245,48 mm or more but not more than 287,5 mm, — an outer diameter of 23,95 mm or more but not more than 32,25 mm, — an interface for steering wheel connection either in a form of an external 40-tooth spline with major diameter of 17,1 mm or more but not more than 17,5 mm and an internal thread M12x1,75-6H or in a form of an external hexagon with a short diagonal of 15,05 mm or more but not more than 15,35 mm and an internal thread M10x1,5-6H, — an interface either in a form of an internal 10-tooth spline of length of 98,0 mm or more but not more than 160 mm, with minor diameter of 16,1 mm or more but not more than 16,4 mm or in a form of an internal 48-tooth spline of length of 151 mm or more but not more than 160 mm, with minor diameter of 23,2 mm or more but not more than 23,3 mm, <p>for use in the manufacture of vehicle's steering system (¹)</p> | 0 % | — | 31.12.2029 |
| 0.6688 | *ex 8708 95 10 ex 8708 95 99 | 20 30 | <p>Inflatable safety cushion of high strength polyamide fibre:</p> <ul style="list-style-type: none"> — sewn, — folded, — with three-dimensionally applied silicone bonding for air bag cavity forming and load-regulated air bag sealing, — suitable for cool inflator technology | 0 % | p/st | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------------------------|----------|--|-------------------------|--------------------|-------------------------------------|
| 0.6687 | *ex 8708 95 10 ex 8708 95 99 | 30 40 | Inflatable sewn safety cushion of high strength polyamide fibre: — folded into three-dimensional packing form, fixed by thermal forming, dedicated fixation seams, fabric cover or plastic staples, or — flat safety cushion with or without thermal folding | 0 % | p/st | 31.12.2030 |
| 0.8292 | ex 8708 95 99 | 50 | Airbag inflator containing both pyrotechnics and cold gas as propellant for safety airbags of vehicles, in each individual consignment of 1 000 pieces or more | 0 % | p/st | 31.12.2026 |
| 0.6583 | ex 8708 99 10 ex 8708 99 97 | 60 50 | Aluminium engine bracket, with dimensions of: — height of more than 10 mm but not more than 200 mm, — width of more than 10 mm but not more than 250 mm, — length of more than 10 mm but not more than 200 mm, equipped with at least two fixing holes, made of aluminium alloys ENAC-46100 or ENAC-42100 (based on the norm EN:1706) with following characteristics: — internal porosity not more than 1 mm, — outer porosity not more than 2 mm, — rockwell hardness HRB 10 or more, of a kind used in the production of suspensions systems for engines in motor vehicles | 0 % | p/st | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.8771 | ex 8708 99 97 | 43 | <p>Outer tie rod with a housing made of AISI 4137 (SCM435) steel or EN10083/2- C45R + N steel or JIS G4053-SCM435 low alloy steel, with:</p> <ul style="list-style-type: none"> — a ball stud made of EN 10263/4 – 41CrS4 Q + T steel or AISI 4137 (SCM435) steel or EN10083/3-42CrMoS4Q + T steel or JIS G4053-SCM435 low alloy steel, — a polyoxymethylene plastic ball seat, — a distance between the end of the threaded hole and the centre of the ball stud of 124 mm or more but not more than 194 mm, — a ball stud diameter of 21,98 mm or more but no more than 22 mm, — a threaded hole depth of 40,5 mm or more but no more than 52 mm with dimensions M14x1,5, — a boot seal, — a boot seal protector and retaining ring, — lubricant, <p>for use in the manufacture of vehicle's steering system (¹)</p> | 0 % | — | 31.12.2029 |
| 0.8986 | *ex 8708 99 97 | 53 | <p>Roll rod assembly for the front suspension in vehicles for connecting the stabilizer to the suspension components:</p> <ul style="list-style-type: none"> — made of aluminium, rubber, and plastic, — with a height of 270 mm or more, but not more than 300 mm, — with a width of 50 mm or more, but not more than 65 mm, — with a length of 150 mm or more, but not more than 170 mm, <p>for use in the manufacture of motor vehicles (¹)</p> | 0 % | — | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---|----------------|--|-------------------------|--------------------|-------------------------------------|
| 0.8973 | *ex 8708 99 97 | 58 | Mounting bracket of front radiator or intercooler: — made of iron or steel or of plastics, — whether or not with rubber cushioning, for use in the manufacture of goods of heading 8708 (¹) | 0 % | — | 31.12.2030 |
| 0.6848 | ex 8714 10 90 | 70 | Motor bikes radiators in consignment of 100 pieces or more | 0 % | p/st | 31.12.2027 |
| 0.6172 | ex 8714 91 30 ex 8714 91 30 ex 8714 91 30 | 25 35 72 | Front forks, except rigid (non-telescopic) front forks made entirely of steel, for use in the manufacture of bicycles (including electric bicycles) (¹) | 0 % | — | 31.12.2029 |
| 0.8959 | *ex 8714 93 00 | 20 | Gear set to connect sprockets: — for mounting on a hub drum, — with 7 sprockets or more but not more than 12 sprockets, — with 10 or more but not more than 52 teeth for each sprocket, — with a weight of 200 g or more but not more than 800 g, — sprockets made of nickel-plated steel or aluminium, — with connectors (spacers) between the sprockets made of plastic or aluminium, — without a pawl mechanism, for use in the manufacture of bicycles and e-bikes (¹) | 0 % | — | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|--------------------------------|----------|--|-------------------------|--------------------|-------------------------------------|
| 0.6879 | *ex 8714 96 10 | 10 | Pedals, for use in the manufacture of bicycles (including electric bicycles) (¹) | 0 % | — | 31.12.2030 |
| 0.7421 | ex 8714 99 10 ex 8714 99 10 | 20 89 | Bicycle handlebars: — with or without an integrated stem, — either made out of carbon fibres and synthetic resin or made of aluminium, for use in the manufacture of bicycles (including electric bicycles) (¹) | 0 % | — | 31.12.2027 |
| 0.7710 | ex 8714 99 50 ex 8714 99 50 | 11 91 | Derailleur gears, consisting of: — rear derailleur and mounting articles, — with or without front derailleur, for use in the manufacture of bicycles (including electric bicycles) (¹) | 0 % | p/st | 31.12.2029 |
| 0.6878 | *ex 8714 99 90 | 30 | Seat posts, for use in the manufacture of bicycles (including electric bicycles) (¹) | 0 % | p/st | 31.12.2030 |
| 0.7708 | ex 8714 99 90 | 40 | Stem for bicycle handlebars, for use in the manufacture of bicycles (including electric bicycles) (¹) | 0 % | p/st | 31.12.2029 |
| 0.8507 | ex 8714 99 90 | 50 | Rear air shock absorber in form of a pneumatic spring element with oil damper for use in the manufacture of bicycles, including electrical bicycles (¹) | 0 % | p/st | 31.12.2027 |
| 0.3191 | ex 9001 10 90 | 10 | Image reverser made up from an assembly of optical fibres | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|--------------------------------|----------|---|-------------------------|--------------------|-------------------------------------|
| 0.6402 | ex 9001 50 41 ex 9001 50 49 | 40 40 | Organic uncut corrective eyeglass lens, finished on both sides, to undergo a coating, colouring, edging, mounting or any other substantial process for use in the manufacture of corrective glasses ⁽¹⁾ | 0 % | — | 31.12.2027 |
| 0.6401 | ex 9001 50 80 | 30 | Round organic uncut, semi-finished eyeglass lens with corrective effect, finished on one side, of a kind used for the manufacture of finished eyeglass lenses | 0 % | — | 31.12.2026 |
| 0.7590 | ex 9002 11 00 | 18 | Lens assembly consisting of a cylinder-shaped cover made of metal or plastic and optical elements with: <ul style="list-style-type: none"> — a horizontal field of view range to a maximum of 120 deg, — a diagonal field of view range to a maximum of 105 deg, — a focal length to a maximum of 7,50 mm, — a relative aperture of a maximum of F/2,90, — a maximum diameter of 22 mm | 0 % | — | 31.12.2029 |
| 0.5692 | ex 9002 11 00 | 20 | Lenses: <ul style="list-style-type: none"> — measuring not more than 95 mm × 55 mm × 50 mm, — with a resolution of 160 lines/mm or better, and — with a zoom ratio of 3 or more times | 0 % | — | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.7973 | *ex 9002 11 00 | 23 | <p>Lens with:</p> <ul style="list-style-type: none"> — motorized focus, zoom, aperture, — electronically switchable infrared cut filter, — an adjustable focal length not less than 2,7 mm and not more than 55mm, — a weight of not more than 120 g, — a length of less than 70 mm, — a diameter of not more than 70 mm | 0 % | — | 31.12.2030 |
| 0.7103 | ex 9002 11 00 | 45 | <p>Infrared optical unit:</p> <ul style="list-style-type: none"> — with lenses of silicon, germanium or chalcogenide glass of a diameter not more than 62 mm ($\pm 0,05$ mm), — whether or not mounted on a machined aluminium alloy support of a kind used for thermal cameras or IP network cameras | 0 % | — | 31.12.2026 |
| 0.3177 | ex 9002 11 00 | 50 | <p>Lens unit:</p> <ul style="list-style-type: none"> — having a focal length of 25 mm or more but not more than 150 mm, — consisting of glass or plastic lenses, with a diameter of 60 mm or more but not more than 190 mm | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.6572 | ex 9002 11 00 | 85 | <p>Lens assembly with:</p> <ul style="list-style-type: none"> — a horizontal field of view range of 20 deg or more, but not more than 200 deg, — a focal length of 1,16 mm or more, but not more than 20 mm, — a relative aperture of F/1,2 or more, but not more than F/4, and — a diameter of 5 mm or more, but not more than 40 mm, <p>for use in the manufacture of CMOS automotive cameras or in IP network cameras production (¹)</p> | 0 % | — | 31.12.2029 |
| 0.6288 | ex 9025 80 40 | 50 | <p>Electronic semiconductor sensor for measuring at least two of the following quantities:</p> <ul style="list-style-type: none"> — Atmospheric pressure, temperature, (also for temperature compensation), humidity, or volatile organic compounds, — in a housing suitable for the automatic printing of conductor boards or Bare Die technology, containing: — one or more monolithic application-specific integrated circuits (ASIC), — one or more microelectromechanical sensor elements (MEMS) manufactured with semiconductor technology, with mechanical components arranged in three-dimensional structures on the semiconductor material, <p>of a kind used for incorporation into products of Chapters 84 to 90 and 95</p> | 0 % | p/st | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|----------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.3292 | ex 9032 89 00 | 30 | Electronic controller of electric power steering (EPS controller) | 0 % | p/st | 31.12.2029 |
| 0.4253 | ex 9032 89 00 | 40 | Digital valve controller for controlling liquids and gases | 0 % | p/st | 31.12.2027 |
| 0.7004 | ex 9032 89 00 | 50 | <p>Gas panel for regulating and controlling of the gas flow rate, working with plasma technology, comprising</p> <ul style="list-style-type: none"> — an electronic mass flow regulator, suitable for receiving and sending of analogue and digital signals — four pressure transducers, — two or more pressure valves, — electric interfaces and — several connectors for gas lines — suitable for in-situ plasma bonding processes or for multi frequency bond activating processes | 0 % | — | 31.12.2026 |
| 0.5025 | ex 9401 99 20 | 10 | Ratchet disk for use in the manufacture of reclining car seats ⁽¹⁾ | 0 % | p/st | 31.12.2028 |
| 0.8989 | *ex 9401 99 20 | 20 | <p>A high-mobility positioning cassette,</p> <ul style="list-style-type: none"> — capable of operating within a temperature range of – 40 °C to + 85 °C, — enables controlled forward and backward movement of a vehicle seat, — integrated with the seat backrest via a steel cable system, preventing seat removal when the backrest is open and allowing it only when the backrest is closed, — constructed from glass fiber-reinforced, special alloy aluminium components and fitted with self-lubricating bushings made of polyoxymethylene (POM) and polytetrafluoroethylene (PTFE) to minimize friction, — equipped with a locking system designed to remain secure under forces up to 20G, — requires a minimum force of 40N for normal operation | 0 % | — | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|-------------------------------------|
| 0.8786 | ex 9503 00 95 | 30 | Miniature engine: — consisting of a plastic body, — containing a spring, — providing movement of gear shafts with spring tension, for use in the manufacture of the toys under heading 9503 (¹) | 0 % | — | 31.12.2029 |
| 0.8789 | ex 9503 00 95 | 40 | Miniature engine driven by mechanical friction: — consisting of a plastic body, — with shaft length 10,5 cm or more but not more than 14,5 cm, — containing a metal disc, — creating movement by causing the gears to rotate with the friction force, for use in the manufacture of the toys under heading 9503 (¹) | 0 % | — | 31.12.2029 |
| 0.3286 | ex 9608 91 00 | 10 | Non-fibrous plastic pen-tips with an internal canal | 0 % | — | 31.12.2029 |
| 0.3289 | ex 9608 91 00 | 20 | Felt tips and other porous-tips for markers, without internal canal | 0 % | — | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date envisaged for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|-------------------------------------|
| 0.2737 | ex 9612 10 10 | 10 | Ribbons of plastic with segments of different colours, providing the penetration of dyes by heat into a support (so called dye-sublimation) | 0 % | — | 31.12.2029 |

⁽¹⁾ Suspension of duties is subject to end-use customs supervision in accordance with Article 254 of Regulation (EU) No 952/2013.

⁽²⁾ However, the suspension of tariff duties does not apply where the processing is carried out by retail or catering undertakings.

⁽³⁾ Only the *ad valorem* duty is suspended. The specific duty shall continue to apply.

⁽⁴⁾ A surveillance of imports of goods covered by this tariff suspension shall be established in accordance with the procedure laid down in Articles 55 and 56 of Commission Implementing Regulation (EU) 2015/2447 of 24 November 2015 laying down detailed rules for implementing certain provisions of Regulation (EU) No 952/2013 of the European Parliament and of the Council laying down the Union Customs Code (OJ L 343, 29.12.2015, p. 558, ELI: http://data.europa.eu/eli/reg_impl/2015/2447/oj).

* New or amended measure.'