



COMMISSION OF THE EUROPEAN COMMUNITIES

Brussels, 25.11.2002
COM(2002) 646 final

Proposal for a

COUNCIL REGULATION

**amending Regulation (EC) No 1255/96 temporarily suspending the autonomous
common customs tariff duties on certain industrial, agricultural and fishery products**

(presented by the Commission)

EXPLANATORY MEMORANDUM

The Commission, assisted by the Economic Tariff Questions Group, has reviewed all the requests for temporary suspension of autonomous common customs tariff duties presented to it by the Member States, including requests for extending suspensions at present in force.

The attached proposal concerns certain industrial, agricultural and fishery products.

Requests for suspension relating to the above products were examined in the light of the criteria set out in the communication from the Commission concerning autonomous tariff suspensions and quotas (see OJ C 128, 25.4.1998, p. 2).

Following this review, the Commission considers that the suspension of duties is justified for the products listed in the Annex to the attached proposal for a Regulation.

Some products, for which suspension is no longer in the Community's economic interests, have been withdrawn from the annex.

The period of validity of the proposed measure is unspecified, since its purpose is to amend the annex to Council Regulation (EC) No 1255/96, the period of validity of which is itself unspecified.

Proposal for a

COUNCIL REGULATION

amending Regulation (EC) No 1255/96 temporarily suspending the autonomous common customs tariff duties on certain industrial, agricultural and fishery products

THE COUNCIL OF THE EUROPEAN UNION,

Having regard to the Treaty establishing the European Community, and in particular Article 26 thereof,

Having regard to the proposal from the Commission,

Whereas:

- (1) It is in the interest of the Community to suspend partially or totally the autonomous common customs tariff duties for a number of new products not listed in the Annex to Council Regulation (EC) No 1255/96 temporarily suspending the autonomous common customs tariff duties on certain industrial, agricultural and fishery products¹.
- (2) A number of products which are referred to in the said Regulation should be withdrawn from the list in the Annex because it is no longer in the Community's interest to maintain suspension of autonomous common customs tariff duties or because the description needs to be altered in order to take account of technical product developments and economic trends on the market.
- (3) Accordingly, products whose description needs to be altered should be regarded as new products.
- (4) For ease of comprehension, in view of the large number of amendments coming into force on 1 January 2003, the Annex to Regulation (EC) No 1255/96 should be replaced by a completely new version.
- (5) Regulation (EC) No 1255/96 should be amended accordingly.
- (6) Since this Regulation should apply from 1 January 2003, it should enter into force immediately,

HAS ADOPTED THIS REGULATION:

Article 1

The Annex to Regulation (EC) No 1255/96 shall be replaced by the Annex to this Regulation.

⁽¹⁾ OJ L 158, 29.6.1996, p. 1. Regulation last amended by Regulation (EC) No 1120/2002 (OJ L 171, 29.6.2002, p. 1).

Article 2

This Regulation shall enter into force on the day of its publication in the *Official Journal of the European Communities*.

It shall apply with effect from 1 January 2003.

This Regulation shall be binding in its entirety and directly applicable in all Member States.

Done at Brussels, [...]

*For the Council
The President*

ANNEX

"ANNEX

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--|---|-----------------------------------|
| 0001 | ex 0302 69 99 10 ex 0303 79 98 10 | Sturgeons, fresh, chilled or frozen, for processing (a) (b) | 0 |
| 0002 | ex 0302 69 99 20 | Lump fish (<i>Cyclopterus lumpus</i>) with roe, fresh or chilled, for processing (a) | 0 |
| 0003 | ex 0302 69 99 30 ex 0303 79 98 20 | Red snapper (<i>Lutjanus purpureus</i>), fresh, chilled or frozen, for processing (a) (c) | 0 |
| 0004 | ex 0302 70 00 11 ex 0302 70 00 31 ex 0302 70 00 41 ex 0302 70 00 91 ex 0303 80 90 10 ex 0303 80 90 19 | Hard fish roes, fresh, chilled or frozen | 0 |
| 0005 | ex 0303 11 00 10 ex 0303 19 00 10 | Pacific salmon (<i>Oncorhynchus spp.</i>), frozen and headless, for the processing industry for manufacture into pastes or spreads (a) | 0 |
| 0006 | ex 0304 10 38 45 ex 0304 10 98 60 ex 0304 20 61 10 ex 0304 90 97 31 | Fillets and meat of dogfish (<i>Squalus acanthias</i>), fresh, chilled or frozen | 6 |
| 0007 | ex 0305 20 00 11 ex 0305 20 00 18 ex 0305 20 00 19 ex 0305 20 00 21 ex 0305 20 00 30 | Hard fish roes, salted or in brine | 0 |
| 0008 | ex 0306 19 90 10 ex 0306 29 90 10 | Krill for processing (a) | 0 |
| 0009 | ex 0603 90 00 10 ex 0604 99 90 10 | Flowers, flower buds, foliage, leaves and other parts of plants, not further prepared than dried, dyed or bleached, for use in the manufacture of pot pourri of subheading 3307 49 00 (a) | 0 |
| 0010 | ex 0710 21 00 10 | Peas in pods, of the species <i>Pisum sativum</i> of the variety <i>Hortense axiphium</i> , frozen, of a thickness not exceeding 6 mm, to be used, in their pods, in the manufacture of prepared meals (a) (c) | 0 |
| 0011 | ex 0711 59 00 11 ex 0711 59 00 91 | Mushrooms, excluding mushrooms of the genus <i>Agaricus</i> , provisionally preserved in brine, in sulphur water, or in other preservative solutions, but unsuitable in that state for immediate consumption, for the food-canning industry (a) | 0 |
| 0012 | ex 0712 32 00 11 ex 0712 32 00 21 ex 0712 33 00 11 ex 0712 33 00 21 ex 0712 39 00 11 ex 0712 39 00 21 | Mushrooms, excluding mushrooms of the genus <i>Agaricus</i> , dried, whole or in identifiable slices or pieces, for treatment other than simple repacking for retail sale (a) (c) | 0 |
| 0013 | ex 0804 10 00 11 ex 0804 10 00 21 | Dates, fresh or dried, not put up for retail sale | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--|--|-----------------------------------|
| 0014 | ex 0810 40 50 10 | Fruit of the species <i>Vaccinium macrocarpon</i> , fresh | 0 |
| 0015 | ex 0810 90 95 10 | Rose-hips, fresh | 0 |
| 0016 | 0811 90 50 0811 90 70 ex 0811 90 95 66 ex 0811 90 95 67 | Fruit of the genus <i>Vaccinium</i> , uncooked or cooked by steaming or boiling in water, frozen, not containing added sugar or other sweetening matter | 0 |
| 0017 | ex 0811 90 95 20 | Boysenberries, frozen, not containing added sugar, not put up for retail sale | 0 |
| 0018 | ex 0811 90 95 30 | Pineapple (<i>Ananas comosus</i>), in pieces, frozen | 0 |
| 0019 | ex 0811 90 95 40 | Rose-hips, uncooked or cooked by steaming or boiling in water, frozen, not containing added sugar or other sweetening matter | 0 |
| 0020 | ex 1511 90 19 10 ex 1511 90 91 10 ex 1513 11 10 10 ex 1513 19 30 10 ex 1513 21 11 10 ex 1513 29 30 10 | Palm oil, coconut (copra) oil, palm kernel oil, for the manufacture of: – industrial monocarboxylic fatty acids of subheading 3823 19 10, – mixtures of methyl esters of fatty acids of subheading 3824 90 99, – methyl esters of fatty acids of heading 2915 or 2916, – stearic acid of subheading 3823 11 00 or – goods of heading No 3401 (a) | 0 |
| 0021 | ex 1518 00 91 10 | Soya-bean oil, modified with maleic acid, for the manufacture of cosmetic products (a) | 0 |
| 0022 | ex 1604 11 00 20 ex 1604 20 10 20 | Pacific salmon (<i>Oncorhynchus spp.</i>), for the processing industry for manufacture into pastes or spreads (a) | 0 |
| 0023 | ex 1604 30 90 10 | Hard fish roes, washed, cleaned of adherent organs and simply salted or in brine, for processing (a) | 0 |
| 0024 | ex 1605 10 00 11 ex 1605 10 00 19 | Crabs of the species “King” (<i>Paralithodes camchaticus</i>), “Hanasaki” (<i>Paralithodes brevipes</i>), “Kegani” (<i>Erimacrus isenbecki</i>), “Queen” and “Snow” (<i>Chionoecetes spp.</i>), “Red” (<i>Geryon quinquedens</i>), “Rough stone” (<i>Neolithodes asperrimus</i>), <i>Lithodes antarctica</i> , “Mud” (<i>Scylla serrata</i>), “Blue” (<i>Portunus spp.</i>), simply boiled in water and shelled, whether or not frozen, in immediate packings of a net content of 2 kg or more | 0 |
| 0025 | ex 1605 10 00 92 ex 1605 10 00 94 | Crabs of the species <i>Paralomis granulosa</i> | 0 |
| 0026 | ex 1902 30 10 10 ex 1903 00 00 20 | Transparent noodles, cut in pieces, obtained from beans (<i>Vigna radiata</i> (L.) Wilczek), not put up for retail sale | 0 0 EUR/100 kg/net |
| 0027 | ex 2005 90 80 70 | Bamboo shoots, prepared or preserved, not put up for retail sale | 0 |
| 0028 | ex 2707 99 11 10 | Crude light oils containing by weight: – 10 % or more of vinyltoluenes, – 10 % or more of indene and – 1 % or more but not more than 5 % of naphthalene | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--------------------|---|-----------------------------------|
| 0029 | ex 2805 30 10 10 | Alloy of cerium and other rare-earth metals, containing by weight 47 % or more of cerium | 0 |
| 0030 | ex 2805 30 10 20 | Alloy of lanthanum and other rare-earth metals, containing by weight 43 % or more of lanthanum | 0 |
| 0031 | ex 2805 30 90 10 | Lanthanum of a purity by weight of 99 % or more | 0 |
| 0032 | ex 2811 19 80 10 | Sulfamidic acid | 0 |
| 0034 | ex 2811 22 00 10 | Silicon dioxide in the form of powder, for use in the manufacture of high performance liquid chromatography columns (HPLC) and sample preparation cartridges (a) | 0 |
| 0035 | ex 2811 29 90 10 | Tellurium dioxide | 0 |
| 0036 | ex 2812 90 00 10 | Nitrogen trifluoride | 0 |
| 0037 | ex 2818 30 00 10 | Aluminium hydroxide oxide in the form of pseudo-boehmite | 4 |
| 0038 | ex 2819 90 90 10 | Dichromium trioxide: – of a specific surface of 37 m ² /g or more (as determined by the BET method), – of a purity by weight of 99,5 % or more calculated on the dry substance, – of a specific gravity of 1,2 g/cm ³ or less, for the manufacture of magnetic chromium dioxide (a) | 0 |
| 0039 | ex 2820 90 90 10 | Manganese (II,III) oxide containing by weight 70 % or more of manganese | 0 |
| 0040 | ex 2821 10 00 10 | Diiron trioxide, in the form of powder, of a purity by weight of 99,2 % or more, for the manufacture of goods of heading No 8504 (a) | 0 |
| 0041 | ex 2823 00 00 10 | Titanium dioxide, of a purity by weight of 99,9 % or more, with an average grain-size of 1,2 µm or more but not exceeding 1,8 µm, for the manufacture of goods of heading No 8532 or 8533 (a) | 0 |
| 0042 | ex 2825 50 00 10 | Copper (I or II) oxide containing by weight 78 % or more of copper and not more than 0,03 % of chloride | 0 |
| 0043 | ex 2826 90 90 10 | Potassium hexafluorophosphate | 0 |
| 0044 | ex 2827 39 80 10 | Copper monochloride of a purity by weight of 96 % or more but not exceeding 99 % | 0 |
| 0045 | ex 2827 60 00 10 | Titanium tetraiodide | 0 |
| 0046 | ex 2830 10 00 10 | Disodium tetrasulfide, containing by weight 38 % or less of sodium calculated on the dry weight | 0 |
| 0047 | ex 2830 20 00 10 | Zinc sulfide containing: – 20,0 mg/kg or less of chloride, – 0,2 mg/kg or less of copper, – 0,5 mg/kg or less of iron and – 1,0 mg/kg or less of lead | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--------------------------------------|---|-----------------------------------|
| 0048 | ex 2836 91 00 20 | Lithium carbonate, containing one or more of the following impurities at the concentrations indicated: <ul style="list-style-type: none"> – 2 mg/kg or more of arsenic, – 200 mg/kg or more of calcium, – 200 mg/kg or more of chlorides, – 20 mg/kg or more of iron, – 150 mg/kg or more of magnesium, – 20 mg/kg or more of heavy metals, – 300 mg/kg or more of potassium, – 300 mg/kg or more of sodium, – 200 mg/kg or more of sulfates, determined according to the methods specified in the European Pharmacopœia | 0 |
| 0049 | ex 2837 19 00 10 | Zinc cyanide | 0 |
| 0050 | ex 2837 19 00 20 | Copper cyanide | 0 |
| 0052 | ex 2839 90 00 10 | Lead silicate hydrate, of a lead content by weight of (84,5 ± 1,5) %, evaluated as lead monoxide, in the form of powder | 0 |
| 0051 | ex 2839 90 00 20 | Calcium silicate | 0 |
| 0053 | ex 2843 90 90 20 | Palladium monoxide | 0 |
| 0054 | ex 2843 90 90 30 | Mixture of palladium phthalocyanines | 0 |
| 0055 | 2845 10 00 | Heavy water (deuterium oxide) (<i>Euratom</i>) | 0 |
| 0056 | 2845 90 10 | Deuterium and compounds thereof; hydrogen and compounds thereof, enriched in deuterium; mixtures and solutions containing these products (<i>Euratom</i>) | 0 |
| 0060 | ex 2846 10 00 10 ex 3824 90 99 48 | Rare-earth concentrate containing by weight 60 % or more but not more than 95 % of rare-earth oxides and not more than 1 % each of zirconium oxide, aluminium oxide or iron oxide, and having a loss on ignition of 5 % or more by weight | 0 |
| 0057 | ex 2846 10 00 20 | Dicerium tricarbonat, whether or not hydrated | 0 |
| 0058 | ex 2846 10 00 30 | Cerium lanthanum carbonate, whether or not hydrated | 0 |
| 0059 | ex 2846 10 00 40 | Cerium lanthanum neodymium praseodymium carbonate, whether or not hydrated | 0 |
| 0061 | ex 2846 90 00 30 | Terbium (III,IV) oxide | 0 |
| 0062 | ex 2848 00 00 10 | Phosphine | 0 |
| 0063 | ex 2850 00 20 10 | Silane | 0 |
| 0064 | ex 2850 00 20 20 | Arsine | 0 |
| 0065 | ex 2903 30 80 10 | Carbon tetrafluoride (tetrafluoromethane) | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--------------------------------------|--|-----------------------------------|
| 0066 | ex 2903 30 80 20 | 1,1,1,2,3,3,3-Heptafluoropropane | 0 |
| 0067 | ex 2903 30 80 30 | Perfluoroethane | 0 |
| 0068 | ex 2903 30 80 40 | 1,1-Difluoroethane | 0 |
| 0069 | ex 2903 59 90 10 | 1,6,7,8,9,14,15,16,17,17,18,18-Dodecachloropentacyclo= [12.2.1.1 ^{6,9} ,0 ^{2,13} ,0 ^{5,10}]octadeca-7,15-diene, for use in the manufacture of polyamide, polyethylene, synthetic rubber or polystyrene (a) | 0 |
| 0070 | ex 2903 59 90 20 | Hexachlorocyclopentadiene | 0 |
| 0071 | ex 2903 69 90 10 | Di- or tetrachlorotricyclo[8.2.2.2 ^{4,7}]hexadeca-1(12),4,6,10,13,15-hexaene, mixed isomers | 0 |
| 0072 | ex 2903 69 90 20 | 1,2-Bis(pentabromophenyl)ethane | 0 |
| 0073 | ex 2903 69 90 40 | 2,6-Dichlorotoluene, of a purity by weight of 99 % or more and containing: <ul style="list-style-type: none"> – 0,001 mg/kg or less of tetrachlorodibenzodioxines, – 0,001 mg/kg or less of tetrachlorodibenzofurans, – 0,2 mg/kg or less of tetrachlorobiphenyls | 0 |
| 0074 | ex 2903 69 90 50 | 1-(Chloromethyl)naphthalene | 0 |
| 0075 | ex 2903 69 90 60 | α -Chloro(ethyl)toluenes | 0 |
| 0076 | ex 2904 10 00 30 | Sodium <i>p</i> -styrenesulfonate | 0 |
| 0077 | ex 2904 20 00 10 | Nitromethane | 0 |
| 0078 | ex 2904 20 00 20 | Nitroethane | 0 |
| 0079 | ex 2904 20 00 30 | 1-Nitropropane | 0 |
| 0080 | ex 2904 20 00 40 | 2-Nitropropane | 0 |
| 0081 | ex 2904 90 20 10 | Tosyl chloride | 0 |
| 0082 | ex 2904 90 40 10 | Trichloronitromethane, for the manufacture of goods of subheading 3808 20 (a) | 0 |
| 0084 | ex 2904 90 85 10 | Quintozene (ISO) | 0 |
| 0083 | ex 2904 90 85 20 | 1-Chloro-2,4-dinitrobenzene | 0 |
| 0085 | ex 2905 19 00 11 ex 3824 90 99 56 | Potassium <i>tert</i> -butanolate (potassium <i>tert</i> -butoxide), whether or not in the form of a solution in tetrahydrofuran | 0 |
| 0087 | ex 2905 39 80 10 | 2-Methylpropane-1,3-diol | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--------------------------------------|--|-----------------------------------|
| 0088 | ex 2905 39 80 20 | Hexa-1,5-diene-3,4-diol | 0 |
| 0089 | ex 2905 49 10 10 | Ethylidynetrimethanol | 0 |
| 0090 | 2906 11 00 | Menthol | 0 |
| 0091 | ex 2906 19 00 10 | Cyclohex-1,4-ylenedimethanol | 0 |
| 0092 | ex 2906 19 00 20 | 4,4'-Isopropylidenedicyclohexanol | 0 |
| 0093 | ex 2906 29 00 10 | 2,2'-(<i>m</i> -Phenylene)dipropan-2-ol | 0 |
| 0094 | ex 2907 21 00 10 | Resorcinol | 0 |
| 0096 | ex 2907 29 00 10 | Disodium 1,4-dihydroanthracene-9,10-diolate, in the form of an aqueous solution | 0 |
| 0097 | ex 2907 29 00 20 | 4,4'-(3,3,5-Trimethylcyclohexylidene)diphenol | 0 |
| 0098 | ex 2907 29 00 30 | 4,4',4''-Ethylidynetriphenol | 0 |
| 0099 | ex 2907 29 00 40 | Mixture of isomers of methylenediphenol | 0 |
| 0100 | ex 2907 29 00 50 | 6,6',6''-Tricyclohexyl-4,4',4''-butane-1,1,3-triyltri(<i>m</i> -cresol) | 0 |
| 0101 | ex 2907 29 00 60 | 4,4'-(1,3-Phenylenediisopropylidene)diphenol | 0 |
| 0095 | ex 2907 29 00 70 | 2,2',2'',6,6',6''-Hexa- <i>tert</i> -butyl- α,α',α'' -(mesitylene-2,4,6-triyl)tri- <i>p</i> -cresol | 0 |
| 0102 | ex 2908 20 00 10 | Disodium 3-hydroxynaphthalene-2,7-disulfonate | 0 |
| 0103 | ex 2908 20 00 20 | Dipotassium 7-hydroxynaphthalene-1,3-disulfonate | 0 |
| 0104 | ex 2908 20 00 30 ex 3824 90 99 74 | 6-Hydroxynaphthalene-2-sulfonic acid and its salts | 0 |
| 0105 | ex 2908 90 00 10 | 4-Nitroso- <i>o</i> -cresol | 0 |
| 0106 | ex 2909 19 00 10 | 1,2-Bis(2-chloroethoxy)ethane | 0 |
| 0107 | ex 2909 30 38 10 | Bis(pentabromophenyl) ether | 0 |
| 0108 | ex 2909 30 90 10 | 4-(<i>p</i> -Tolyloxy)biphenyl | 0 |
| 0109 | ex 2909 30 90 20 | 1,2-Bis(<i>m</i> -tolyloxy)ethane | 0 |
| 0110 | ex 2909 30 90 30 | 1,2-Diphenoxyethane | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--------------------------------------|--|-----------------------------------|
| 0111 | ex 2909 44 00 10 | 2-Hexyloxyethanol | 0 |
| 0112 | ex 2909 49 19 10 | 1- <i>tert</i> -Butoxypropan-2-ol | 0 |
| 0113 | ex 2909 50 90 10 | 4-(2-Methoxyethyl)phenol | 0 |
| 0114 | ex 2910 90 00 30 | 2,3-Epoxypropan-1-ol (glycidol) | 0 |
| 0115 | ex 2910 90 00 40 | Perfluoroepoxypropane | 0 |
| 0116 | ex 2910 90 00 60 ex 3824 90 99 59 | 1,2-Epoxyoctadecane, of a purity by weight of 82 % or more | 0 |
| 0117 | ex 2912 29 00 10 | Terephthalaldehyde | 0 |
| 0118 | ex 2912 49 00 10 | 3-Phenoxybenzaldehyde | 0 |
| 0119 | ex 2914 19 90 10 | 3,3-Dimethylbutan-2-one | 0 |
| 0120 | 2914 21 00 | Camphor | 0 |
| 0121 | ex 2914 29 00 10 | Estr-4-ene-3,17-dione | 0 |
| 0122 | ex 2914 29 00 20 | Cyclohexadec-8-enone | 0 |
| 0123 | ex 2914 39 00 10 | Benz[<i>de</i>]anthracen-7-one | 0 |
| 0124 | ex 2914 50 00 30 | 2'-Hydroxyacetophenone | 0 |
| 0125 | ex 2914 50 00 40 | 4'-Hydroxyacetophenone | 0 |
| 0126 | ex 2914 50 00 50 | 6'-Methoxy-2'-acetonaphthone | 0 |
| 0128 | ex 2914 69 90 10 | 2-Ethylanthraquinone | 0 |
| 0129 | ex 2914 69 90 20 | 2-Pentylanthraquinone | 0 |
| 0130 | ex 2914 69 90 30 | 1,4-Dihydroxyanthraquinone | 0 |
| 0131 | ex 2914 69 90 40 | 2,3-Dihydro-1,4-dihydroxyanthraquinone | 0 |
| 0127 | ex 2914 69 90 50 | 2-Methylanthraquinone | 0 |
| 0133 | ex 2914 70 90 10 | 1-Chloro-3,3-dimethylbutan-2-one | 0 |
| 0134 | ex 2914 70 90 30 | 4,4'-Dibromobenzil | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--------------------|--|-----------------------------------|
| 0135 | ex 2915 29 00 10 | Antimony triacetate | 0 |
| 0137 | ex 2915 39 90 20 | 5 α -Bromo-6 β -hydroxy-17-oxo-androstan-3 β -yl acetate | 0 |
| 0138 | ex 2915 39 90 30 | But-3-ene-1,2-diyl di(acetate) | 0 |
| 0136 | ex 2915 39 90 40 | <i>tert</i> -Butyl acetate | 0 |
| 0139 | ex 2915 40 00 10 | Vinyl chloroacetate | 0 |
| 0140 | ex 2915 90 80 20 | Trimethyl orthoacetate | 0 |
| 0141 | ex 2915 90 80 30 | 2-Ethylbutyric acid | 0 |
| 0142 | ex 2915 90 80 40 | Nonanoic acid (pelargonic acid) | 0 |
| 0143 | ex 2916 12 90 10 | 2- <i>tert</i> -Butyl-6-(3- <i>tert</i> -butyl-2-hydroxy-5-methylbenzyl)-4-methylphenyl acrylate | 0 |
| 0144 | ex 2916 12 90 20 | 2-Ethoxyethyl acrylate | 0 |
| 0145 | ex 2916 12 90 30 | Isobutyl acrylate | 0 |
| 0146 | ex 2916 13 00 10 | Hydroxyzinc methacrylate, in the form of powder | 0 |
| 0147 | ex 2916 13 00 20 | Zinc dimethacrylate, in the form of powder | 0 |
| 0148 | ex 2916 14 90 10 | 2,3-Epoxypropyl methacrylate | 0 |
| 0149 | ex 2916 19 80 20 | Methyl 3,3-dimethylpent-4-enoate | 0 |
| 0151 | ex 2916 20 00 10 | Methyl 3-(2,2-dichlorovinyl)-2,2-dimethylcyclopropanecarboxylate | 0 |
| 0152 | ex 2916 20 00 30 | Empenthrin (ISO) | 0 |
| 0153 | ex 2916 20 00 40 | Cyclohexanecarboxylic acid | 0 |
| 0150 | ex 2916 20 00 50 | Ethyl 2,2-dimethyl-3-(2-methylpropenyl)cyclopropanecarboxylate | 0 |
| 0155 | ex 2916 39 00 10 | Methyl 3-chlorobenzoate | 0 |
| 0156 | ex 2916 39 00 20 | 3,5-Dichlorobenzoyl chloride | 3.6 |
| 0157 | ex 2916 39 00 40 | Vinyl 4- <i>tert</i> -butylbenzoate | 0 |
| 0158 | ex 2916 39 00 50 | 3,5-Dimethylbenzoyl chloride | 0 |
| 0159 | ex 2916 39 00 60 | 4-Ethylbenzoyl chloride | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--------------------|--|-----------------------------------|
| 0154 | ex 2916 39 00 70 | Ibuprofen (INN) | 0 |
| 0160 | ex 2917 11 00 20 | Bis(<i>p</i> -methylbenzyl) oxalate | 0 |
| 0162 | ex 2917 19 90 20 | Sodium 1,2-bis(cyclohexyloxycarbonyl)ethanesulfonate | 0 |
| 0163 | ex 2917 19 90 40 | Dodecanedioic acid, of a purity by weight of more than 98,5 % | 0 |
| 0164 | ex 2917 19 90 50 | Glutaric anhydride | 0 |
| 0161 | ex 2917 19 90 60 | Diethyl isobutylmalonate | 0 |
| 0165 | ex 2917 20 00 30 | 1,4,5,6,7,7-Hexachloro-8,9,10-trinorborn-5-ene-2,3-dicarboxylic anhydride | 0 |
| 0166 | ex 2917 20 00 40 | 3-Methyl-1,2,3,6-tetrahydrophthalic anhydride | 0 |
| 0167 | ex 2917 34 00 10 | Diallyl phthalate | 0 |
| 0169 | ex 2917 39 80 10 | Dimethyl naphthalene-2,6-dicarboxylate | 0 |
| 0170 | ex 2917 39 80 20 | Benzene-1,2,4,5-tetracarboxylic acid (pyromellitic acid) | 0 |
| 0171 | ex 2917 39 80 30 | Benzene-1,2,4,5-tetracarboxylic dianhydride (pyromellitic dianhydride) | 0 |
| 0168 | ex 2917 39 80 40 | Biphenyl-3,4:3',4'-tetracarboxylic dianhydride | 0 |
| 0172 | ex 2918 13 00 10 | L-(-)-Di- <i>p</i> -toluoyltartaric acid | 0 |
| 0173 | ex 2918 19 80 20 | L-Malic acid | 0 |
| 0174 | ex 2918 29 10 10 | Monohydroxynaphthoic acids | 0 |
| 0175 | ex 2918 29 50 10 | Gallic acid, of a purity by weight of 98,5 % or more calculated on the dry weight (measured by acidimetry) | 0 |
| 0176 | ex 2918 29 90 10 | Hexamethylene bis[3-(3,5-di- <i>tert</i> -butyl-4-hydroxyphenyl)propionate] | 0 |
| 0177 | ex 2918 30 00 20 | 2-(4-Ethylbenzoyl)benzoic acid | 0 |
| 0180 | ex 2918 90 90 10 | 3,4-Epoxy cyclohexylmethyl 3,4-epoxycyclohexanecarboxylate | 0 |
| 0181 | ex 2918 90 90 20 | Methyl 3-methoxyacrylate | 0 |
| 0178 | ex 2918 90 90 30 | Methyl 2-(4-hydroxyphenoxy)propionate | 0 |
| 0179 | ex 2918 90 90 40 | <i>trans</i> -4-Hydroxy-3-methoxycinnamic acid | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--------------------|---|-----------------------------------|
| 0182 | ex 2919 00 90 10 | 2,2'-Methylenebis(4,6-di- <i>tert</i> -butylphenyl) phosphate, monosodium salt | 0 |
| 0183 | ex 2919 00 90 20 | Diammonium salt of tetramyristoylcardiolipin | 0 |
| 0184 | ex 2920 10 00 10 | Fenitrothion (ISO) | 0 |
| 0185 | ex 2920 10 00 20 | Tolclofos-methyl (ISO) | 0 |
| 0186 | ex 2920 90 10 10 | Diethyl sulfate | 0 |
| 0187 | 2920 90 30 | Trimethyl phosphite | 0 |
| 0188 | ex 2920 90 85 10 | <i>O,O'</i> -Dioctadecyl pentaerythritol bis(phosphite) | 0 |
| 0189 | ex 2920 90 85 30 | <i>O,O'</i> -Bis(2,4-di- <i>tert</i> -butylphenyl)pentaerythritol bis(phosphite) | 0 |
| 0190 | ex 2921 19 80 10 | Triallylamine | 0 |
| 0191 | ex 2921 19 80 20 | Ethyl(2-methylallyl)amine | 0 |
| 0192 | ex 2921 19 80 30 | Allylamine | 0 |
| 0193 | ex 2921 29 00 10 | <i>N,N,N',N'</i> -Tetrabutylhexamethylenediamine | 0 |
| 0194 | ex 2921 29 00 20 | Tris[3-(dimethylamino)propyl]amine | 0 |
| 0195 | ex 2921 29 00 30 | Bis[3-(dimethylamino)propyl]methylamine | 0 |
| 0196 | ex 2921 30 99 10 | Dicyclohexyl(methyl)amine | 0 |
| 0197 | ex 2921 30 99 20 | Cyclohex-1,3-ylenebis(methylamine), for the manufacture of dishwashing products (a) | 0 |
| 0200 | ex 2921 42 10 10 | 2,6-Dichloro-4-nitroaniline | 0 |
| 0201 | ex 2921 42 10 20 | 2-Bromo-4,6-dinitroaniline | 0 |
| 0202 | ex 2921 42 10 30 | 4-Aminobenzene-1,3-disulfonic acid and its salts | 0 |
| 0203 | ex 2921 42 10 40 | 2-Bromo-6-chloro-4-nitroaniline | 0 |
| 0204 | ex 2921 42 10 50 | 3-Aminobenzenesulfonic acid | 0 |
| 0199 | ex 2921 42 10 70 | 2-Aminobenzene-1,4-disulfonic acid | 0 |
| 0205 | ex 2921 43 00 10 | 5-Amino-2-chlorotoluene-4-sulfonic acid | 0 |
| 0206 | ex 2921 43 00 20 | 4-Amino-6-chlorotoluene-3-sulfonic acid | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--------------------------------------|---|-----------------------------------|
| 0207 | ex 2921 43 00 30 | 3-Nitro- <i>p</i> -toluidine | 0 |
| 0208 | ex 2921 44 00 10 | Methyldiphenylamine | 0 |
| 0209 | ex 2921 45 00 10 | 3-Aminonaphthalene-1,5-disulfonic acid, monosodium salt | 0 |
| 0210 | ex 2921 45 00 20 | 2-Aminonaphthalene-1,5-disulfonic acid and its sodium salts | 0 |
| 0211 | ex 2921 45 00 30 | 2-Aminonaphthalene-1-sulfonic acid | 0 |
| 0212 | ex 2921 45 00 40 | 1-Naphthylamine | 0 |
| 0213 | ex 2921 49 10 20 | Pendimethalin (ISO) | 3.5 |
| 0214 | ex 2921 49 80 10 | 8-Anilinonaphthalene-1-sulfonic acid | 0 |
| 0215 | ex 2921 49 80 20 | <i>N</i> -1-Naphthylaniline | 0 |
| 0216 | ex 2921 59 90 10 | Mixture of isomers of 3,5-diethyltoluenediamine | 0 |
| 0217 | ex 2921 59 90 20 ex 3824 90 99 68 | 4-(4-Aminoanilino)-3-nitrobenzenesulfonic acid | 0 |
| 0218 | ex 2922 19 80 10 | 4,4-Dimethoxybutylamine | 0 |
| 0219 | ex 2922 19 80 30 | <i>N,N,N',N'</i> -Tetramethyl-2,2'-oxybis(ethylamine) | 0 |
| 0220 | ex 2922 19 80 40 | 2-Amino-2-methylpropanol, for use in the manufacture of goods of subheadings 3004 90 and 3305 30 (a) | 0 |
| 0221 | ex 2922 21 00 10 | 2-Amino-5-hydroxynaphthalene-1,7-disulfonic acid and its salts, of a purity by weight of 60 % or more | 0 |
| 0222 | ex 2922 21 00 20 | 4-Hydroxy-7-methylaminonaphthalene-2-sulfonic acid | 0 |
| 0223 | ex 2922 21 00 30 | 6-Amino-4-hydroxynaphthalene-2-sulfonic acid | 0 |
| 0224 | ex 2922 21 00 40 | 7-Amino-4-hydroxynaphthalene-2-sulfonic acid | 0 |
| 0225 | ex 2922 22 00 10 | Anisidines | 0 |
| 0226 | ex 2922 29 00 10 | 2-Methyl- <i>N</i> -phenyl- <i>p</i> -anisidine | 0 |
| 0227 | ex 2922 29 00 20 | 3-Aminophenol | 0 |
| 0228 | ex 2922 29 00 30 | 4-Amino-5-methoxy-2-methylbenzenesulfonic acid | 0 |
| 0229 | ex 2922 29 00 40 | 2-Amino-4- <i>tert</i> -pentyl-6-nitrophenol | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--------------------|--|-----------------------------------|
| 0230 | ex 2922 29 00 50 | 6-Methoxy- <i>m</i> -toluidine | 0 |
| 0231 | ex 2922 29 00 60 | 3,5-Dichloro-4-(1,1,2,2-tetrafluoroethoxy)aniline | 0 |
| 0232 | ex 2922 29 00 70 | 4-Nitro- <i>o</i> -anisidine | 0 |
| 0233 | ex 2922 29 00 80 | 3-Diethylaminophenol | 0 |
| 0236 | ex 2922 39 00 10 | 1-Amino-4-bromo-9,10-dioxoanthracene-2-sulfonic acid and its salts | 0 |
| 0237 | ex 2922 39 00 20 | 1-Aminoanthraquinone | 0 |
| 0238 | ex 2922 39 00 30 | 1-Bromo-4-methylaminoanthraquinone | 0 |
| 0239 | ex 2922 39 00 40 | 1,4-Diamino-2,3-dichloroanthraquinone | 0 |
| 0234 | ex 2922 39 00 50 | 2-Aminoanthraquinone | 0 |
| 0235 | ex 2922 39 00 60 | 1,4-Diamino-2,3-dihydroanthraquinone | 0 |
| 0241 | ex 2922 49 95 10 | Ornithine aspartate (INN) | 0 |
| 0242 | ex 2922 49 95 20 | 12-Aminododecanoic acid | 0 |
| 0240 | ex 2922 49 95 30 | DL-Aspartic acid | 0 |
| 0243 | ex 2922 50 00 30 | 2-(3-Amino-4-chlorobenzoyl)benzoic acid | 0 |
| 0244 | ex 2922 50 00 50 | 2-(4-Dibutylaminosalicyloyl)benzoic acid | 0 |
| 0245 | ex 2923 90 00 10 | Tetramethylammonium hydroxide, in the form of an aqueous solution containing: – (25 ± 0,5) % by weight of tetramethylammonium hydroxide, – 500 mg/kg or less of carbonate, – 200 mg/kg or less of chloride and – 5 mg/kg or less of potassium | 0 |
| 0246 | ex 2923 90 00 30 | Tetramethylammonium hydroxide pentahydrate, of a purity by weight of 98 % or more | 0 |
| 0247 | ex 2923 90 00 40 | Benzyltrimethyl(octadecyl)ammonium salts, for use in the manufacture of toner for photocopiers (a) | 0 |
| 0250 | ex 2924 19 00 10 | 2-Acrylamido-2-methylpropanesulfonic acid and its sodium or ammonium salts | 0 |
| 0251 | ex 2924 19 00 20 | <i>N,N'</i> -Methylenediacrylamide | 0 |
| 0248 | ex 2924 19 00 30 | Methyl 2-acetamido-3-chloropropionate | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--------------------------------------|--|-----------------------------------|
| 0249 | ex 2924 19 00 40 | <i>N</i> -(1,1-Dimethyl-3-oxobutyl)acrylamide | 0 |
| 0252 | ex 2924 21 90 10 ex 3824 90 99 62 | 4,4'-Dihydroxy-7,7'-ureylenedi(naphthalene-2-sulfonic acid) and its sodium salts | 0 |
| 0253 | ex 2924 29 95 10 | Alachlor (ISO) | 0 |
| 0254 | ex 2924 29 95 15 | Acetochlor (ISO) | 0 |
| 0255 | ex 2924 29 95 20 | 3'-Amino-4'-methoxyacetanilide | 0 |
| 0256 | ex 2924 29 95 25 | 3'-Diethylaminoacetanilide | 0 |
| 0257 | ex 2924 29 95 30 | Propachlor (ISO) | 0 |
| 0258 | ex 2924 29 95 35 | Diethofencarb (ISO) | 0 |
| 0259 | ex 2924 29 95 40 | 7-Acetamido-4-hydroxynaphthalene-2-sulfonic acid and its sodium salts | 0 |
| 0260 | ex 2924 29 95 45 | 3'-Diethylamino-4'-methoxyacetanilide | 0 |
| 0261 | ex 2924 29 95 50 | 5-[<i>N</i> -(2-Acetoxyethyl)acetoxyacetamido]- <i>N,N'</i> -bis(2,3-diacetoxy= propyl)-2,4,6-triiodoisophthalamide | 0 |
| 0262 | ex 2924 29 95 55 | 4'-Amino- <i>N</i> -methylacetanilide | 0 |
| 0263 | ex 2924 29 95 60 | Beflubutamid (ISO) | 0 |
| 0264 | ex 2924 29 95 65 | 2-(4-Hydroxyphenyl)acetamide | 0 |
| 0265 | ex 2924 29 95 70 | 4-Acetamido-2-aminobenzenesulfonic acid | 0 |
| 0266 | ex 2925 11 00 20 | Saccharin and its sodium salt | 0 |
| 0267 | ex 2925 19 95 10 | <i>N</i> -Phenylmaleimide | 0 |
| 0268 | ex 2925 20 00 10 | Dicyclohexylcarbodiimide | 0 |
| 0274 | ex 2926 90 95 10 | Methacrylonitrile | 0 |
| 0275 | ex 2926 90 95 20 | 2-(<i>m</i> -Benzoylphenyl)propionitrile | 0 |
| 0276 | ex 2926 90 95 30 | 2-Amino-5-nitrobenzonitrile | 0 |
| 0278 | ex 2926 90 95 45 | 2-Cyanoacetamide | 0 |
| 0279 | ex 2926 90 95 50 | Alkyl or alkoxyalkyl esters of cyanoacetic acid | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--------------------------------------|---|-----------------------------------|
| 0280 | ex 2926 90 95 60 | Cyanoacetic acid in crystalline form | 0 |
| 0281 | ex 2926 90 95 65 | Malononitrile | 0 |
| 0282 | ex 2926 90 95 70 | Tetrachloroterephthalonitrile | 0 |
| 0269 | ex 2926 90 95 75 | Ethyl 2-cyano-2-ethyl-3-methylhexanoate | 0 |
| 0270 | ex 2926 90 95 80 | Ethyl 2-cyano-2-phenylbutyrate | 0 |
| 0271 | ex 2926 90 95 85 | Ethyl 2-allyl-2-cyano-3-methylhexanoate | 0 |
| 0272 | ex 2926 90 95 86 | Ethylenediaminetetraacetonitrile | 0 |
| 0273 | ex 2926 90 95 87 | Nitrilotriacetonitrile | 0 |
| 0283 | ex 2927 00 00 10 | 2,2'-Dimethyl-2,2'-azodipropionamidine dihydrochloride | 0 |
| 0284 | ex 2927 00 00 20 | 4-Anilino-2-methoxybenzenediazonium hydrogen sulfate | 0 |
| 0285 | ex 2927 00 00 30 ex 3824 90 99 69 | 4'-Aminoazobenzene-4-sulfonic acid | 0 |
| 0286 | ex 2927 00 00 40 | 2-Hydroxynaphthalene-1-diazonium-4-sulfonate | 0 |
| 0287 | ex 2927 00 00 50 ex 3824 90 99 41 | 2-Hydroxy-6-nitronaphthalene-1-diazonium-4-sulfonate, of a purity by weight of 60 % or more | 0 |
| 0288 | ex 2928 00 90 10 | 3,3'-Bis(3,5-di- <i>tert</i> -butyl-4-hydroxyphenyl)- <i>N,N'</i> -bipropionamide | 0 |
| 0289 | ex 2928 00 90 20 | 2,4,6-Trichlorophenylhydrazine | 0 |
| 0290 | ex 2928 00 90 40 | <i>O</i> -Ethylhydroxylamine, in the form of an aqueous solution | 0 |
| 0291 | ex 2928 00 90 50 | <i>N</i> -Isopropylhydroxylamine, in the form of an aqueous solution | 0 |
| 0293 | ex 2929 10 90 10 | Methylenedicyclohexyl diisocyanates | 0 |
| 0294 | ex 2929 10 90 30 | 3,3'-Dimethylbiphenyl-4,4'-diyl diisocyanate | 0 |
| 0295 | ex 2929 10 90 40 | <i>m</i> -Isopropenyl- α,α -dimethylbenzyl isocyanate | 0 |
| 0296 | ex 2929 10 90 50 | <i>m</i> -Phenylenediisopropylidene diisocyanate | 0 |
| 0297 | ex 2929 10 90 60 | Trimethylhexamethylene diisocyanate, mixed isomers | 0 |
| 0292 | ex 2929 10 90 70 | 9,9'-(3-Heptyl-4-pentylcyclohex-1,2-ylene)dinonyl diisocyanate | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--------------------------------------|--|-----------------------------------|
| 0299 | ex 2930 90 70 10 | Thiophenol | 0 |
| 0300 | ex 2930 90 70 15 | Ethoprophos (ISO) | 0 |
| 0301 | ex 2930 90 70 20 | 3,3-Dimethyl-1-methylthiobutanone oxime | 0 |
| 0302 | ex 2930 90 70 25 | Thiophanate-methyl (ISO) | 0 |
| 0303 | ex 2930 90 70 30 | 4-(4-Isopropoxyphenylsulfonyl)phenol | 0 |
| 0304 | ex 2930 90 70 40 | 3,3'-Thiodi(propionic acid) | 0 |
| 0305 | ex 2930 90 70 45 | 2-[(<i>p</i> -Aminophenyl)sulfonyl]ethyl hydrogen sulfate | 0 |
| 0306 | ex 2930 90 70 50 ex 3824 90 99 51 | 2-Chlorophenylsulfonyl isocyanate, in the form of a solution in xylene | 0 |
| 0307 | ex 2930 90 70 55 ex 3824 90 99 52 | Methyl 2-(isocyanatosulfonyl)methylbenzoate, in the form of a solution in xylene | 0 |
| 0308 | ex 2930 90 70 60 | Methyl phenyl sulfide | 0 |
| 0309 | ex 2930 90 70 65 | Diiodomethyl <i>p</i> -tolyl sulfone | 0 |
| 0310 | ex 2930 90 70 70 ex 3824 90 99 71 | 2-Aminophenyl phenyl sulfone, of a purity by weight of 75 % or more | 0 |
| 0311 | ex 2930 90 70 75 | 4,4'-[Methylenebis(oxyethylenethio)]diphenol | 0 |
| 0312 | ex 2930 90 70 80 | Captan (ISO) | 0 |
| 0313 | ex 2930 90 70 85 | Mesotrione (ISO) | 0 |
| 0298 | ex 2930 90 70 86 | 4-Hydroxybenzenethiol | 0 |
| 0314 | 2931 00 10 | Dimethyl methylphosphonate | 0 |
| 0315 | ex 2931 00 95 05 | Butylethylmagnesium, in the form of a solution in heptane | 0 |
| 0316 | ex 2931 00 95 10 | 2-Diphenylphosphinobenzoic acid | 0 |
| 0317 | ex 2931 00 95 20 | Bis(2-chloroethyl) 2-chloroethylphosphonate | 0 |
| 0318 | ex 2931 00 95 25 | Sodium phenylphosphinate | 0 |
| 0319 | ex 2931 00 95 30 | Bis(2-chloroethyl) vinylphosphonate | 0 |
| 0320 | ex 2931 00 95 35 | Sodium tetraphenylborate | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--------------------|--|-----------------------------------|
| 0321 | ex 2931 00 95 40 | <i>N</i> -(Phosphonomethyl)iminodiacetic acid | 0 |
| 0322 | ex 2931 00 95 45 | Tributylphosphine | 0 |
| 0323 | ex 2931 00 95 50 | Bis(2,4,4-trimethylpentyl)phosphinic acid | 0 |
| 0324 | ex 2931 00 95 55 | Dimethyl[dimethylsilyldiindenyl]hafnium | 0 |
| 0325 | ex 2931 00 95 60 | Trioctylphosphine oxide | 0 |
| 0326 | ex 2931 00 95 65 | Triethylborane | 0 |
| 0327 | ex 2931 00 95 70 | <i>N,N</i> -Dimethylanilinium tetrakis(pentafluorophenyl)borate | 0 |
| 0328 | ex 2931 00 95 75 | {2,7-Di- <i>tert</i> -butyl-9-[(η^5 -cyclopentadienyl)bis(4-triethylsilylphenyl)methyl]-4a,4b,8a,9,9a- η -fluorene}dimethylhafnium, in the form of a solution in hexane | 0 |
| 0329 | ex 2931 00 95 85 | Tributyl(tetradecyl)phosphonium chloride, whether or not in the form of an aqueous solution | 0 |
| 0330 | ex 2931 00 95 95 | Trichloro(3-chloropropyl)silane | 0 |
| 0331 | ex 2932 11 00 10 | Tetrahydrofuran, containing not more than 40 mg per litre in total of tetrahydro-2-methylfuran and tetrahydro-3-methylfuran, for the manufacture of α -4-hydroxybutyl- ω -hydroxypoly(oxytetramethylene) (a) | 0 |
| 0332 | ex 2932 13 00 10 | Tetrahydrofurfuryl alcohol | 0 |
| 0333 | ex 2932 19 00 40 | Furan of a purity by weight of 99 % or more | 0 |
| 0334 | ex 2932 19 00 50 | 2,3-Dihydrofuran | 0 |
| 0335 | ex 2932 29 80 10 | 2'-Anilino-6'-[ethyl(isopentyl)amino]-3'-methylspiro[isobenzofuran= -1(3 <i>H</i>),9'-xanthen]-3-one | 0 |
| 0336 | ex 2932 29 80 15 | 13,14,15,16-Tetranorlabdano-12,8 α -lactone | 0 |
| 0337 | ex 2932 29 80 25 | 2'-(2-Chloroanilino)-6'-dibutylaminospiro[isobenzofuran= -1(3 <i>H</i>),9'-xanthen]-3-one | 0 |
| 0338 | ex 2932 29 80 30 | 2'-Anilino-3'-methyl-6'-methyl(propyl)aminospiro[isobenzofuran= -1(3 <i>H</i>),9'-xanthen]-3-one | 0 |
| 0339 | ex 2932 29 80 35 | 6'-Diethylamino-3'-methyl-2'-(2,4-xylydino)spiro[isobenzofuran= -1(3 <i>H</i>),9'-xanthen]-3-one | 0 |
| 0340 | ex 2932 29 80 40 | 2'-Anilino-6'-(<i>N</i> -ethyl- <i>p</i> -toluidino)-3'-methylspiro[isobenzofuran= -1(3 <i>H</i>),9'-xanthen]-3-one | 0 |
| 0341 | ex 2932 29 80 45 | 2'-Anilino-6'-ethyl(isobutyl)amino-3'-methylspiro[isobenzofuran= -1(3 <i>H</i>),9'-xanthen]-3-one | 0 |
| 0342 | ex 2932 29 80 50 | 2'-Anilino-6'-cyclohexyl(methyl)amino-3'-methylspiro[isobenzofuran= -1(3 <i>H</i>),9'-xanthen]-3-one | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--------------------|---|-----------------------------------|
| 0343 | ex 2932 29 80 55 | 6-Dimethylamino-3,3-bis(4-dimethylaminophenyl)phthalide | 0 |
| 0344 | ex 2932 29 80 70 | 3',6'-Bis(ethylamino)-2',7'-dimethylspiro[isobenzofuran-1(3 <i>H</i>),9'-[9 <i>H</i>]-xanthen]-3-one | 0 |
| 0346 | ex 2932 99 70 10 | Bendiocarb (ISO) | 0 |
| 0347 | ex 2932 99 70 20 | Androsta-1,4-diene-3,17-dione 17-(2,2-dimethylpropylene) acetal | 0 |
| 0349 | ex 2932 99 70 50 | 5-Propyl-1,3-benzodioxole | 0 |
| 0350 | ex 2933 19 90 10 | 4,5-Diamino-1-(2-hydroxyethyl)-1 <i>H</i> -pyrazole sulfate | 0 |
| 0351 | ex 2933 21 00 10 | Hydantoin | 0 |
| 0352 | ex 2933 21 00 20 | 2-(3-Benzyl-2,5-dioxoimidazolidin-1-yl)-2'-chloro-5'-(3-dodecylmethylpropionamido)-4,4-dimethyl-3-oxovaleranilide sulfonyl-2- | 0 |
| 0353 | ex 2933 21 00 40 | 1-[1,3-Bis(hydroxymethyl)-2,5-dioxoimidazolidin-4-yl]-1,3-bis(hydroxymethyl)urea | 0 |
| 0354 | ex 2933 29 90 20 | Reaction product consisting of the methyl esters of (±)-6-(4-isopropyl-4-methyl-5-oxo-2-imidazolin-2-yl)- <i>m</i> -toluic acid and (±)-2-(4-isopropyl-4-methyl-5-oxo-2-imidazolin-2-yl)- <i>p</i> -toluic acid (Imazamethabenz-methyl) | 4 |
| 0355 | ex 2933 29 90 40 | Triflumizole (ISO) | 0 |
| 0356 | ex 2933 29 90 50 | 1,3-Dimethylimidazolidin-2-one | 0 |
| 0360 | ex 2933 39 99 10 | Cloperastine fendizoate (INN) | 0 |
| 0361 | ex 2933 39 99 15 | Pyridine-2,3-dicarboxylic acid | 0 |
| 0362 | ex 2933 39 99 20 | 5-Methyl-2-pyridylamine | 0 |
| 0363 | ex 2933 39 99 25 | Imazethapyr (ISO) | 0 |
| 0364 | ex 2933 39 99 30 | 4,4'-Trimethylenedipiperidine | 0 |
| 0365 | ex 2933 39 99 60 | 2-Fluoro-6-(trifluoromethyl)pyridine | 0 |
| 0357 | ex 2933 39 99 65 | Acetamiprid (ISO) | 0 |
| 0358 | ex 2933 39 99 70 | Etoricoxib (INN) | 0 |
| 0359 | ex 2933 39 99 75 | Picolinafen (ISO) | 0 |
| 0366 | ex 2933 49 10 10 | Quinmerac (ISO) | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--------------------|---|-----------------------------------|
| 0367 | ex 2933 49 90 20 | 5,7-Dichloro-4-(4-fluorophenoxy)quinoline | 0 |
| 0368 | ex 2933 49 90 40 | <i>N</i> -Ethyl-5,6,7,8-tetrahydroquinolinium <i>p</i> -toluenesulfonate, in the form of a solution in water | 0 |
| 0369 | ex 2933 49 90 50 | Methyl 2-[(<i>S</i>)-3-{(<i>E</i>)-3-[2-(7-chloro-2-quinoly)vinyl]phenyl}-3-hydroxypropyl]= benzoate monohydrate | 0 |
| 0370 | ex 2933 49 90 60 | 5,6,7,8-Tetrahydroquinoline | 0 |
| 0371 | ex 2933 59 95 10 | 1-Ethyl-6-fluoro-1,4-dihydro-4-oxo-7-piperazin-1-yl-1,8-naphthyridine= -3-carboxylic acid and its salts and esters | 0 |
| 0372 | ex 2933 59 95 20 | 2,4-Diamino-6-chloropyrimidine | 0 |
| 0373 | ex 2933 59 95 30 | Mepanipirim (ISO) | 0 |
| 0374 | ex 2933 59 95 40 | Guanine | 0 |
| 0375 | ex 2933 59 95 50 | 1-Chloromethyl-4-fluoro-1,4-diazoniabicyclo[2.2.2]octane bis(tetrafluoroborate) | 0 |
| 0376 | ex 2933 59 95 60 | 2,6-Dichloro-4,8-dipiperidinopyrimido[5,4- <i>d</i>]pyrimidine | 0 |
| 0377 | ex 2933 59 95 70 | <i>N</i> -(4-Ethyl-2,3-dioxopiperazin-1-ylcarbonyl)-D-2-phenylglycine | 0 |
| 0378 | ex 2933 59 95 80 | <i>N</i> -(4-Ethyl-2,3-dioxopiperazin-1-ylcarbonyl)-D-2-(4-hydroxyphenyl)glycine | 0 |
| 0379 | ex 2933 69 80 10 | 1,3,5-Tris(4- <i>tert</i> -butyl-3-hydroxy-2,6-dimethylbenzyl)-1,3,5-triazine= -2,4,6(1 <i>H</i> ,3 <i>H</i> ,5 <i>H</i>)-trione | 0 |
| 0380 | ex 2933 69 80 20 | 1,3,5-Tris[(3,5-di- <i>tert</i> -butyl-4-hydroxyphenyl)methyl]-1,3,5-triazine= -2,4,6(1 <i>H</i> ,3 <i>H</i> ,5 <i>H</i>)-trione | 0 |
| 0381 | ex 2933 69 80 40 | Cyanazine (ISO) | 0 |
| 0382 | ex 2933 69 80 50 | 1,3,5-Tris(2,3-dibromopropyl)-1,3,5-triazinane-2,4,6-trione | 0 |
| 0383 | ex 2933 69 80 60 | Hexazinone (ISO) | 0 |
| 0384 | ex 2933 99 30 10 | Azepane, for the manufacture of goods of subheading 3808 30 (a) | 0 |
| 0385 | ex 2933 99 90 10 | 2-(2 <i>H</i> -Benzotriazol-2-yl)-4,6-di- <i>tert</i> -butylphenol | 0 |
| 0386 | ex 2933 99 90 15 | 2-(2 <i>H</i> -Benzotriazol-2-yl)-4,6-di- <i>tert</i> -pentylphenol | 0 |
| 0387 | ex 2933 99 90 20 | 2-(2 <i>H</i> -Benzotriazol-2-yl)-4,6-bis(1-methyl-1-phenylethyl)phenol | 0 |
| 0388 | ex 2933 99 90 25 | 6,6'-Di-2 <i>H</i> -benzotriazol-2-yl-4,4'-bis(1,1,3,3-tetramethylbutyl)= -2,2'-methylenediphenol | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--------------------|--|-----------------------------------|
| 0389 | ex 2933 99 90 30 | Quizalofop-P-ethyl (ISO) | 0 |
| 0390 | ex 2933 99 90 35 | Indoline | 0 |
| 0391 | ex 2933 99 90 45 | Maleic hydrazide (ISO) | 0 |
| 0392 | ex 2933 99 90 50 | Metconazole (ISO) | 3.2 |
| 0393 | ex 2933 99 90 55 | 5-Nitroindole | 0 |
| 0394 | ex 2933 99 90 60 | 1,3-Bis(3-isocyanatomethylphenyl)-1,3-diazetidone-2,4-dione (dimeric 2,4-toluene diisocyanate) | 0 |
| 0395 | ex 2933 99 90 65 | Candesartan cilexetil (INNM) | 0 |
| 0396 | ex 2933 99 90 70 | 6,7-Dihydro-5H-cyclopenta[b]pyridine | 0 |
| 0397 | ex 2933 99 90 75 | 2,3-Dichloropyrazine | 0 |
| 0398 | ex 2933 99 90 80 | 1-Methyltetrazole-5-thiol | 0 |
| 0399 | ex 2934 10 00 10 | Hexythiazox (ISO) | 0 |
| 0400 | ex 2934 10 00 20 | 2-(4-Methylthiazol-5-yl)ethanol | 0 |
| 0401 | ex 2934 20 80 10 | 4-Chloro-1,3-benzothiazol-2(3H)-one | 0 |
| 0402 | ex 2934 20 80 20 | S-(1,3-Benzothiazol-2-yl) (Z)-2-(2-aminothiazol-4-yl)-2-(methoxyimino)thioacetate | 0 |
| 0404 | ex 2934 99 90 10 | 7-Chloro-5-methyl-2H-1,4-benzothiazin-3-(4H)-one | 0 |
| 0405 | ex 2934 99 90 15 | Carboxin (ISO) | 0 |
| 0406 | ex 2934 99 90 20 | 4-[4-(Tridecyl[branched]oxy)phenyl]-1,4-thiazinane 1,1-dioxide | 0 |
| 0407 | ex 2934 99 90 25 | Oxycarboxin (ISO) | 0 |
| 0408 | ex 2934 99 90 30 | Etridiazole (ISO) | 0 |
| 0409 | ex 2934 99 90 35 | Dimethenamide (ISO) | 0 |
| 0410 | ex 2934 99 90 40 | 2,3,5,6-Tetrahydroxy-1,4-diisobutyl-1,4-dioxo-1,4-diphosphinane | 0 |
| 0411 | ex 2934 99 90 45 | Tris(2,3-epoxypropyl)-1,3,5-triazinetrione | 0 |
| 0412 | ex 2934 99 90 50 | 1-[2-(1,3-Dioxan-2-yl)ethyl]-2-ethylpyridinium bromide | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--------------------|--|-----------------------------------|
| 0413 | ex 2934 99 90 55 | Olmesartan medoxomil (INN) | 0 |
| 0414 | ex 2934 99 90 60 | DL-Homocysteine thiolactone hydrochloride | 0 |
| 0403 | ex 2934 99 90 65 | Methyl 3-aminothiophene-2-carboxylate | 0 |
| 0415 | ex 2935 00 90 10 | Salts of sulfathiazole (INN) | 0 |
| 0416 | ex 2935 00 90 20 | Toluenesulfonamides | 0 |
| 0417 | ex 2935 00 90 30 | Mixture of isomers consisting of <i>N</i> -ethyltoluene-2-sulfonamide and <i>N</i> -ethyltoluene-4-sulfonamide | 0 |
| 0418 | ex 2935 00 90 40 | 1-(4,6-Dimethoxypyrimidin-2-yl)-3-(2-ethylsulfonylimidazo[1,2-a]pyridin-3-ylsulfonyl)urea (sulfosulfuron) | 0 |
| 0419 | ex 2935 00 90 50 | 4,4'-Oxydi(benzenesulfonohydrazide) | 0 |
| 0420 | ex 2935 00 90 60 | 5-Amino- <i>N</i> -(2,6-dichloro- <i>m</i> -tolyl)-1 <i>H</i> -1,2,4-triazole-3-sulfonamide | 0 |
| 0421 | ex 2935 00 90 70 | Methyl 3-aminosulfonylthiophene-2-carboxylate | 0 |
| 0198 | ex 2935 00 90 80 | <i>N</i> -(3-Amino-2-hydroxy-4-phenylbutyl)- <i>N</i> -(2-methylpropyl)-4-amino- benzenesulfonamide | 0 |
| 0422 | ex 2938 90 90 10 | Hesperidin | 0 |
| 0423 | 3201 20 00 | Wattle extract | 0 |
| 0424 | ex 3201 90 90 10 | Tanning extracts of eucalyptus | 3.2 |
| 0425 | ex 3201 90 90 20 | Tanning extracts derived from gambier and myrobalan fruits | 0 |
| 0426 | ex 3204 15 00 10 | Dye C.I. Vat Orange 7 | 0 |
| 0427 | ex 3204 15 00 20 | Dye C.I. Vat Red 15 | 0 |
| 0428 | ex 3204 15 00 30 | Dye C.I. Vat Red 14 | 0 |
| 0429 | ex 3204 15 00 40 | Dye C.I. Vat Brown 57 | 0 |
| 0430 | ex 3204 17 00 10 | Dye C.I. Pigment Yellow 81 | 0 |
| 0431 | ex 3204 19 00 10 | Nickel bis {4-methoxy-2-[6-(pentafluoroethylthio)benzothiazol-2-ylazo]= (dipropylamino)benzenesulfonate} | 0 |
| 0432 | ex 3204 19 00 15 | 4-{4-[3-(4-Methoxyphenyl)-13,13-dimethyl-3,13-dihydrobenzo= [h]indeno[2,1-f]chromen-3-yl]phenyl}morpholine | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--------------------------------------|--|-----------------------------------|
| 0433 | ex 3204 19 00 20 | 13-Ethyl-3-[4-(morpholino)phenyl]-3-phenyl-3,13-dihydrobenzo= [h]indeno[2,1-f]chromen-13-ol | 0 |
| 0434 | ex 3204 19 00 25 | Cyclohexyl 8-methyl-2,2-diphenyl-2H-benzo[h]chromene-5-carboxylate | 0 |
| 0435 | ex 3204 19 00 30 | 13-Isopropyl-3,3-bis(4-methoxyphenyl)-6,11-dimethyl-3,13-dihydrobenzo= [h]indeno[2,1-f]chromen-13-ol | 0 |
| 0436 | ex 3204 19 00 35 | 13-Butyl-13-ethoxy-6,11-dimethoxy-3,3-bis(4-methoxyphenyl)-3,13-dihydrobenzo= [h]indeno[2,1-f]chromene | 0 |
| 0437 | ex 3204 19 00 40 | Methyl 8'-acetoxy-1,3,3,5,6-pentamethyl-2,3-dihydrospiro[1H-indole= -2,3'-naphtho[2,1-b][1,4]oxazine]-9'-carboxylate | 0 |
| 0438 | ex 3204 19 00 45 | 6,7-Dimethoxy-3,3-bis(4-methoxyphenyl)-13,13-dimethyl-3,13-dihydrobenzo= [h]indeno[2,1-f]chromene | 0 |
| 0439 | ex 3204 19 00 50 | Methyl 6-(isobutyryloxy)-2,2-diphenyl-2H-benzo[h]chromene-5-carboxylate | 0 |
| 0440 | ex 3204 19 00 60 | Ethoxycarbonylmethyl 8-methyl-2,2-diphenyl-2H-benzo[h]chromene-5-carboxylate | 0 |
| 0441 | ex 3204 19 00 70 | Dye C.I. Solvent Red 49 | 0 |
| 0442 | ex 3206 19 00 10 | Preparation based on titanium dioxide, containing by weight 66 % or more but not more than 71 % of titanium dioxide and 1 % or more but not more than 2 % of isopropoxytitanium triisostearate | 0 |
| 0443 | ex 3206 42 00 10 | Lithopone | 0 |
| 0444 | ex 3206 49 90 10 | Black preparation of iron-oxide pigments, in liquid form, with a maximum particle size not exceeding 20 nanometres and containing by weight 25 % or more of iron evaluated as Fe ₂ O ₃ , for the manufacture of goods of heading No 3304 or 9608 (a) | 0 |
| 0445 | ex 3208 20 10 10 | Copolymer of N-vinylcaprolactam, N-vinyl-2-pyrrolidone and dimethylaminoethyl methacrylate, in the form of a solution in ethanol containing by weight 34 % or more but not more than 40 % of copolymer | 0 |
| 0446 | ex 3208 20 10 20 ex 3905 91 00 92 | Copolymer of vinylpyrrolidone and dimethylaminoethyl methacrylate, partially quaternized by diethyl sulfate, in the form of a solution in ethanol | 0 |
| 0447 | ex 3208 20 10 30 | Solution of diundecyl phthalate and a copolymer of dibutyl maleate and isobutyl methacrylate in a hydrocarbon solvent | 0 |
| 0449 | ex 3208 90 19 10 ex 3911 90 99 35 | Copolymer of maleic acid and methyl vinyl ether, monoesterified with ethyl and/or isopropyl and/or butyl groups, in the form of a solution in ethanol, ethanol and butanol, isopropanol or isopropanol and butanol | 0 |
| 0450 | ex 3208 90 19 20 | Copolymer of polyurethane and silicone, in the form of a solution in a mixture of butanone, toluene and cyclohexanone, containing by weight 13 % or more but not more than 16 % of copolymer | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|------------------|---|-----------------------------|
| 0451 | ex 3208 90 19 30 | Solution containing: <ul style="list-style-type: none"> - (30 ± 5) % by weight of polyamide resin, - (6,5 ± 3,5) % by weight of diazaphthoquinone, - (55 ± 5) % by weight of 1-methyl-2-pyrrolidone, - 1 000 µg/kg or less of chloride, - 1 000 µg/kg or less of potassium and - 1 000 µg/kg or less of iron | 0 |
| 0452 | ex 3208 90 19 40 | Polymer of methylsiloxane, in the form of a solution in a mixture of acetone, butanol, ethanol and isopropanol, containing by weight 5 % or more but not more than 11 % of polymer of methylsiloxane | 0 |
| 0448 | ex 3208 90 19 50 | Solution containing by weight: <ul style="list-style-type: none"> - (65 ± 10) % of γ-butyrolactone, - (30 ± 10) % of polyamide resin, - (3,5 ± 1,5) % of naphthoquinone ester derivative and - (1,5 ± 0,5) % of arylsilicic acid | 0 |
| 0453 | ex 3208 90 99 10 | Solution based on chemically modified natural polymers, containing two or more of the following dyes: <ul style="list-style-type: none"> - methyl 8'-acetoxo-1,3,3,5,6-pentamethyl-2,3-dihydrospiro[1<i>H</i>-indole= -2,3'-naphtho[2,1-<i>b</i>][1,4]oxazine]-9'-carboxylate, - methyl 6-(isobutyryloxy)-2,2-diphenyl-2<i>H</i>-benzo[<i>h</i>]chromene= -5-carboxylate, - 13-isopropyl-3,3-bis(4-methoxyphenyl)-6,11-dimethyl-3,13-dihydrobenzo=[<i>h</i>]indeno[2,1-<i>f</i>]chromen-13-ol, - ethoxycarbonylmethyl 8-methyl-2,2-diphenyl-2<i>H</i>-benzo[<i>h</i>]chromene-5-carboxylate, - 13-ethyl-3-[4-(morpholino)phenyl]-3-phenyl-3,13-dihydrobenzo=[<i>h</i>]indeno[2,1-<i>f</i>]chromen-13-ol | 0 |
| 0454 | ex 3208 90 99 20 | Solution based on chemically modified natural polymers, containing two or more of the following dyes: <ul style="list-style-type: none"> - 4-[4-(13,13-dimethyl-3-phenyl-3,13-dihydrobenzo=[<i>h</i>]indeno[2,1-<i>f</i>]chromen-3-yl)phenyl]morpholine, - 4-{4-[3-(4-methoxyphenyl)-13,13-dimethyl-3,13-dihydrobenzo=[<i>h</i>]indeno[2,1-<i>f</i>]chromen-3-yl]phenyl}morpholine, - cyclohexyl 8-methyl-2,2-diphenyl-2<i>H</i>-benzo[<i>h</i>]chromene-5-carboxylate, - ethoxycarbonylmethyl 6-acetoxo-2,2-diphenyl-2<i>H</i>-benzo[<i>h</i>]chromene-5-carboxylate, - 2-pentyl-7,7-diphenyl-7,8-benzochromeno[6,5-<i>d</i>]-1,3-dioxin-4(7<i>H</i>)-one, - 13-butyl-13-ethoxy-6,11-dimethoxy-3,3-bis(4-methoxyphenyl)-3,13-dihydrobenzo=[<i>h</i>]indeno[2,1-<i>f</i>]chromene, - 3-(4-methoxyphenyl)-13,13-dimethyl-3-phenyl-3,13-dihydrobenzo=[<i>h</i>]indeno[2,1-<i>f</i>]chromene, - 6,7-dimethoxy-3,3-bis(4-methoxyphenyl)-13,13-dimethyl-3,13-dihydrobenzo=[<i>h</i>]indeno[2,1-<i>f</i>]chromene | 0 |
| 0455 | ex 3215 90 80 10 | Ink formulation, for use in the manufacture of ink-jet cartridges (a) | 0 |
| 0456 | ex 3215 90 80 20 | Heat sensitive ink fixed on a plastic film | 0 |
| 0457 | 3301 12 10 | Essential oil of orange, not deterpenated | 0 |
| 0458 | ex 3402 90 10 20 | Mixture of docusate sodium (INN) and sodium benzoate | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--------------------|--|-----------------------------------|
| 0459 | ex 3402 90 10 30 | Non-aqueous surface-active preparation, containing: <ul style="list-style-type: none"> – polyethylene glycol alkylphenyl ether, – 2,4,7,9-tetramethyldec-5-yne-4,7-diol and – phosphoric acid esters | 0 |
| 0460 | ex 3402 90 90 10 | Crystalline powder obtained by the reaction of trisodium phosphate with a mixture of sodium hypochlorite and sodium chloride (“chlorinated trisodium phosphate”), containing by weight: <ul style="list-style-type: none"> – 3,5 % or more of available chlorine, measured iodometrically and – 17,0 % or more of phosphorus evaluated as P₂O₅ | 0 |
| 0461 | ex 3403 99 90 10 | Cutting-fluid preparation based on an aqueous solution of synthetic polypeptides | 0 |
| 0462 | ex 3504 00 00 10 | Purified antigens obtained from genetically manipulated yeast cells, for the manufacture of detection tests for hepatitis-C (a) | 0 |
| 0463 | ex 3504 00 00 20 | Glycoprotein 160 obtained from Human Immunodeficiency Virus, HIV-1 strain | 0 |
| 0464 | ex 3505 10 50 20 | <i>O</i> -(2-Hydroxyethyl)-derivative of hydrolysed maize starch | 0 |
| 0465 | ex 3506 91 00 10 | Adhesive based on an aqueous dispersion of a mixture of dimerised rosin and a copolymer of ethylene and vinyl acetate (EVA) | 0 |
| 0466 | ex 3506 91 00 20 | Heat-activated adhesive based on phenolic resin and rubber, in the form of a film on a release paper, for use in the manufacture of brake pads for the automotive industry (a) | 0 |
| 0469 | ex 3507 90 90 10 | Asparaginase | 0 |
| 0470 | ex 3507 90 90 20 | Enzymatic preparation based on thermolysine | 0 |
| 0471 | ex 3507 90 90 40 | Avian myeloblastosis virus (AMV) reverse transcriptase | 0 |
| 0472 | ex 3507 90 90 50 | Lipase | 0 |
| 0467 | ex 3507 90 90 60 | Trypsin | 0 |
| 0468 | ex 3507 90 90 70 | Chymotrypsin | 0 |
| 0473 | ex 3701 30 00 10 | Relief printing plate, of a kind used for printing on newsprint, consisting of a metal substrate coated with a photopolymer layer of a thickness of 0,2 mm or more but not exceeding 0,8 mm, not covered with a release film, of a total thickness not exceeding 1 mm | 0 |
| 0474 | ex 3701 99 00 10 | Plate of quartz or of glass, covered with a film of chromium and coated with a photosensitive or electron-sensitive resin, for the manufacture of masks for the goods of heading No 8541 or 8542 (a) | 0 |
| 0475 | ex 3702 31 99 10 | Colour negative film, for the manufacture of instant-picture film-packs (a) | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--------------------------------------|---|-----------------------------------|
| 0476 | ex 3702 43 00 10 ex 3702 44 00 10 | Photographic film, of a nominal width of 459, 669 or 761 mm, composed of several layers, including two polyester films, a carbon layer, an adhesive layer and a layer of a copolymer of styrene with acrylonitrile | 0 |
| 0477 | ex 3703 90 10 10 | Paper sheet, coated with silver halide emulsion, for the manufacture of goods of subheading 3701 20 00 (a) | 0 |
| 0478 | ex 3707 10 00 10 | Photosensitive emulsion for the sensitization of silicon discs (a) | 0 |
| 0479 | ex 3707 90 30 10 | Toner, in the form of powder, consisting of a copolymer of styrene and butyl acrylate and either magnetite or carbon black, for use as a developer in the manufacture of cartridges for facsimile machines or computer printers (a) | 0 |
| 0480 | 3805 20 00 | Pine oil | 1.7 |
| 0484 | ex 3808 10 90 10 | Indoxacarb (ISO) and its (<i>R</i>) isomer, fixed on a support of silicon dioxide | 0 |
| 0482 | ex 3808 10 90 20 | Preparation containing by weight 2 % or more but not more than 4 % of azadirachtin (ISO), not put up for retail sale | 0 |
| 0483 | ex 3808 10 90 30 | Preparation containing endospores and protein crystals derived from the hybrid strain GC 91 of <i>Bacillus thuringiensis</i> Berliner subsp. <i>aizawai</i> and <i>kurstaki</i> | 0 |
| 0485 | ex 3808 20 80 10 | Fungicide in the form of a powder, containing by weight 65 % or more but not more than 75 % of hymexazole (ISO), not put up for retail sale | 0 |
| 0486 | ex 3808 20 80 20 | Preparation based on diiodomethyl <i>p</i> -tolyl sulfone, not put up for retail sale | 0 |
| 0487 | ex 3808 20 80 30 | Preparation consisting of a suspension of pyriithione zinc (INN) in water, containing by weight 24 % or more but not more than 26 % of pyriithione zinc (INN) | 0 |
| 0488 | ex 3808 40 20 10 | Preparation containing by weight: <ul style="list-style-type: none"> – 58 % or more but not more than 62 % of 1-bromo-3-chloro-5,5-dimethylhydantoin, – 26 % or more but not more than 29 % of 1,3-dichloro-5,5-dimethylhydantoin, – 10 % or more but not more than 12 % of 1,3-dichloro-5-ethyl-5-methylhydantoin, for the manufacture of swimming-pool disinfectants (a) | 0 |
| 0489 | ex 3808 40 90 10 | 1-Dodecylguanidine hydrochloride, in the form of a solution in isopropanol and water, containing by weight 40 % or less of 1-dodecylguanidine hydrochloride | 0 |
| 0490 | ex 3809 91 00 10 | Mixture of 5-ethyl-2-methyl-2-oxo-1,3,2λ ⁵ -dioxaphosporan-5-ylmethyl methylmethylphosphonate and bis(5-ethyl-2-methyl-2-oxo-1,3,2λ ⁵ -dioxaphosporan-5-ylmethyl)methylphosphonate | 0 |
| 0491 | ex 3809 92 00 10 | Paper anti-fading agent, consisting of a mixture of magnesium trisilicate and monosodium salt of 2,2'-methylenebis(4,6-di- <i>tert</i> -butylphenyl) phosphate | 0 |
| 0492 | ex 3811 21 00 10 | Salts of dinonylnaphthalenesulfonic acid, in the form of a solution in mineral oils | 0 |
| 0493 | ex 3811 21 00 20 | Additives for lubricating oils, based on complex organic molybdenum compounds, in the form of a solution in mineral oil | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--------------------|---|-----------------------------------|
| 0494 | ex 3812 30 80 10 | Tetraaluminium nonamagnesium dicarbonate hexacosahydroxide heptahydrate, coated with a surface-active agent | 0 |
| 0495 | ex 3812 30 80 20 | Mixture containing predominantly bis(2,2,6,6-tetramethyl-1-octyloxy-4-piperidyl) sebacate | 0 |
| 0496 | ex 3812 30 80 30 | Compound stabilisers containing by weight 15 % or more but not more than 40 % of sodium perchlorate and not more than 70 % of 2-(2-methoxyethoxy)ethanol | 0 |
| 0497 | ex 3812 30 80 40 | Dialuminium tetramagnesium monocarbonate dodecahydroxide monohydrate, coated with a surface-active agent | 0 |
| 0498 | ex 3812 30 80 50 | Aluminium magnesium zinc hydroxide carbonate hydrate, coated with a surface-active agent | 0 |
| 0499 | ex 3814 00 90 10 | Mixture containing by weight 25 % or more but not more than 35 % of dimethyl sulfoxide and 65 % or more but not more than 75 % of monoethanolamine | 3 |
| 0500 | ex 3815 12 00 10 | Catalyst, in the form of granules or rings of a diameter of 3 mm or more but not exceeding 10 mm, consisting of silver on an aluminium oxide support and containing by weight 8 % or more but not more than 20 % of silver | 0 |
| 0501 | ex 3815 12 00 20 | Catalyst consisting of palladium and rhenium, fixed on a support of active carbon, in the form of powder, containing: <ul style="list-style-type: none"> – 0,5 % or more but not more than 1,5 % by weight of palladium, – 3 % or more but not more than 5 % by weight of rhenium and – 0,1 mole % or more but not more than 1 mole % of alkaline metals, for use in the manufacture of tetrahydrofuran (a) | 0 |
| 0502 | ex 3815 19 90 10 | Catalyst, consisting of chromium trioxide or dichromium trioxide fixed on a support of silicon dioxide, of a pore volume, as determined by the nitrogen absorption method, of 2 cm ³ /g or more | 0 |
| 0503 | ex 3815 19 90 15 | Catalyst, in the form of a powder, consisting of a mixture of metal oxides fixed on a support of silicon dioxide, containing by weight 20 % or more but not more than 40 % of molybdenum, bismuth and iron evaluated together, for use in the manufacture of acrylonitrile (a) | 0 |
| 0504 | ex 3815 19 90 20 | Catalyst consisting of chromium oxides and titanium dioxide fixed on a support of silicon dioxide, aluminium oxide or aluminium phosphate | 0 |
| 0505 | ex 3815 19 90 30 | Catalyst containing titanium tetrachloride supported on magnesium dichloride, for use in the manufacture of polypropylene (a) | 0 |
| 0506 | ex 3815 19 90 40 | Catalyst, in the form of spheres of a diameter of 4,2 mm or more but not exceeding 9 mm, consisting of a mixture of metals oxides containing predominantly oxides of molybdenum, vanadium and copper, on a support of silicon dioxide and/or aluminium oxide, for use in the manufacture of acrylic acid (a) | 0 |
| 0507 | ex 3815 19 90 45 | Catalyst, consisting predominantly of dichromium copper tetraoxide and copper (II) oxide, containing by weight 38 % or more but not more than 48 % of copper, evaluated as copper (II) oxide, fixed on a support of silicon dioxide, for the hydrogenation of acetophenones (a) | 0 |
| 0508 | ex 3815 19 90 50 | Catalyst consisting of organo-metallic compounds of titanium, magnesium and aluminium on a support of silicon dioxide, in the form of a suspension in tetrahydrofuran | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--------------------|---|-----------------------------------|
| 0509 | ex 3815 19 90 55 | Catalyst consisting of a mixture of metal oxides containing chromium trioxide, fixed on a support of silicon dioxide | 0 |
| 0510 | ex 3815 19 90 60 | Catalyst consisting of dichromium trioxide, fixed on a support of aluminium oxide | 0 |
| 0511 | ex 3815 19 90 65 | Catalyst consisting of phosphoric acid chemically bonded to a support of silicon dioxide | 0 |
| 0512 | ex 3815 19 90 70 | Catalyst consisting of organo-metallic compounds of aluminium and zirconium, fixed on a support of silicon dioxide | 0 |
| 0513 | ex 3815 19 90 75 | Catalyst consisting of organo-metallic compounds of aluminium and chromium, fixed on a support of silicon dioxide | 0 |
| 0514 | ex 3815 19 90 80 | Catalyst consisting of organo-metallic compounds of magnesium and titanium, fixed on a support of silicon dioxide, in the form of a suspension in mineral oil | 0 |
| 0515 | ex 3815 19 90 85 | Catalyst consisting of organo-metallic compounds of aluminium, magnesium and titanium, fixed on a support of silicon dioxide, in the form of powder | 0 |
| 0516 | ex 3815 90 90 15 | Catalyst, consisting of a mixture of oxides containing by weight more than 96 % of oxides of molybdenum, vanadium, nickel and antimony, whether or not mixed with porcelain balls, for use in the manufacture of acrylic acid (a) | 0 |
| 0517 | ex 3815 90 90 20 | Catalyst, in powder form, consisting of a mixture of titanium trichloride and aluminium chloride, containing by weight: <ul style="list-style-type: none"> – 20 % or more but not more than 30 % of titanium and – 55 % or more but not more than 72 % of chlorine | 0 |
| 0518 | ex 3815 90 90 25 | Catalyst, consisting of a mixture of oxides containing by weight more than 96 % of oxides of molybdenum, bismuth, nickel, iron and silicon, whether or not mixed with porcelain balls, for use in the manufacture of acrylaldehyde (a) | 0 |
| 0519 | ex 3815 90 90 30 | Catalyst, in the form of a powder, containing by weight 82 % or more of copper and of a specific surface of 0,5 m ² /g or more but not exceeding 8 m ² /g | 0 |
| 0520 | ex 3815 90 90 35 | Catalyst, in the form of a suspension in oil, consisting of titanium trichloride and aluminium trichloride, containing by weight (on an oil-free basis): <ul style="list-style-type: none"> – 15 % or more but not more than 30 % of titanium and – 40 % or more but not more than 72 % of chlorine | 0 |
| 0521 | ex 3815 90 90 40 | Catalyst, in the form of rodlets of a length of 5 mm or more but not exceeding 8 mm, consisting of a mixture of metals oxides containing predominantly oxides of iron, molybdenum and bismuth, whether or not containing silicon dioxide as filler, for use in the manufacture of acrylic acid (a) | 0 |
| 0522 | ex 3815 90 90 50 | Catalyst containing titanium trichloride, in the form of a suspension in hexane or heptane containing by weight, in the hexane- or heptane-free material, 9 % or more but not more than 30 % of titanium | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--------------------|---|-----------------------------------|
| 0523 | ex 3815 90 90 60 | Catalyst, in the form of rodlets, consisting of an acid aluminosilicate (zeolite): – with a mole-ratio of silicon dioxide : dialuminium trioxide of not less than 500 : 1 and – containing by weight 0,2 % or more but not more than 0,8 % of platinum | 0 |
| 0524 | ex 3815 90 90 65 | Catalyst based on a mordenite zeolite, in the form of granules, for use in the manufacture of mixtures of methylamines containing by weight 50 % or more of dimethylamine (a) | 0 |
| 0525 | ex 3815 90 90 70 | Catalyst, consisting of a mixture of (2-hydroxypropyl)trimethylammonium formate and dipropylene glycols | 0 |
| 0526 | ex 3815 90 90 75 | Catalyst, consisting of a mixture of 1,4-diazabicyclo[2.2.2]octane, 2-hydroxyethyliminodi(acetic acid) and dibutyltin di(acetate), containing by weight 5 % or more but not more than 10 % of 1,4-diazabicyclo[2.2.2]octane | 0 |
| 0527 | ex 3815 90 90 80 | Catalyst consisting predominantly of dinonylnaphthalenedisulfonic acid in the form of a solution in isobutanol | 0 |
| 0528 | ex 3815 90 90 81 | Catalyst, containing by weight 38 % or more but not more than 48 % of (2-hydroxy-1-methylethyl)trimethylammonium 2-ethylhexanoate | 0 |
| 0529 | ex 3815 90 90 82 | Catalyst, containing by weight 35 % or more but not more than 55 % of (2-hydroxy-1-methylethyl)trimethylammonium formate and formic acid | 0 |
| 0530 | ex 3815 90 90 83 | Catalyst, in the form of powder, containing aluminium magnesium hydroxide hydrate, rare-earth metals oxides and divanadium pentaoxide | 0 |
| 0531 | ex 3815 90 90 85 | Catalyst based on aluminosilicate (zeolite), for the transalkylation of alkylaromatic hydrocarbons or the oligomerization of olefins (a) | 0 |
| 0532 | ex 3823 19 10 91 | Mixture of fatty acids containing by weight: – 2 % or more but not more than 6 % of hexanoic acid, – 53 % or more but not more than 60 % of octanoic acid, – 34 % or more but not more than 42 % of decanoic acid and – not more than 2 % of dodecanoic acid | 0 |
| 0533 | ex 3824 90 15 10 | Acid aluminosilicate (artificial zeolite of the Y type) in the sodium form, containing by weight not more than 11 % of sodium evaluated as sodium oxide, in the form of rodlets | 0 |
| 0534 | ex 3824 90 64 01 | Intermediate products of the antibiotics manufacturing process obtained from the fermentation of <i>Micromonospora purpurea</i> , whether or not dried | 0 |
| 0535 | ex 3824 90 64 02 | Cholic acid and 3 α ,12 α -dihydroxy-5 β -cholan-24-oic acid (deoxycholic acid), crude | 0 |
| 0536 | ex 3824 90 64 03 | Products obtained by the <i>N</i> -ethylation of sisomycin (INN) | 0 |
| 0537 | ex 3824 90 64 04 | Intermediate products of the antibiotics manufacturing process obtained from the fermentation of <i>Micromonospora inyoensis</i> , whether or not dried | 0 |
| 0538 | ex 3824 90 64 05 | Residues of manufacture containing by weight 40 % or more of 11 β ,17,20,21-tetrahydroxy-6-methylpregna-1,4-dien-3-one 21-acetate | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--------------------|--|-----------------------------------|
| 0543 | ex 3824 90 99 01 | Colloidal diantimony pentaoxide | 0 |
| 0544 | ex 3824 90 99 02 | Mixture of nitromethane and 1,2-epoxybutane | 0 |
| 0545 | ex 3824 90 99 03 | Grains or granules, consisting of a mixture of dialuminium trioxide and zirconium dioxide, containing by weight: <ul style="list-style-type: none"> – 70 % or more but not more than 78 % of dialuminium trioxide and – 19 % or more but not more than 26 % of zirconium dioxide | 5.2 |
| 0546 | ex 3824 90 99 04 | Crude lithium hypochlorite | 0 |
| 0547 | ex 3824 90 99 05 | Polysilicate, modified with phosphoric acid, in the form of a solution in a mixture of ethanol, isopropanol and tetrahydrofuran, containing by weight 3 % or more but not more than 6 % of polysilicate | 0 |
| 0548 | ex 3824 90 99 06 | Preparation in the form: <ul style="list-style-type: none"> – of powder, containing by weight 75 % or more of zinc bis[3,5-bis(1-phenylethyl)salicylate] or – of aqueous dispersion, containing by weight 22 % or more but not more than 55 % of zinc bis[3,5-bis(1-phenylethyl)salicylate] | 0 |
| 0549 | ex 3824 90 99 07 | Film consisting of the oxides of either barium or calcium and either titanium or zirconium, mixed with binding materials | 0 |
| 0550 | ex 3824 90 99 08 | Preparation consisting essentially of alkaline asphalt sulfonate, of: <ul style="list-style-type: none"> – a specific gravity of 0,9 or more but not exceeding 1,5 and – a solubility in water of 70 % by weight or more | 0 |
| 0551 | ex 3824 90 99 09 | Anti-corrosion preparations consisting of salts of dinonylnaphthalenesulfonic acid, either: <ul style="list-style-type: none"> – on a support of mineral wax, whether or not modified chemically, or – in the form of a solution in an organic solvent | 0 |
| 0552 | ex 3824 90 99 10 | Calcined bauxite (refractory grade) | 0 |
| 0553 | ex 3824 90 99 11 | Magnetisable iron oxide, in the form of powder, containing by weight: <ul style="list-style-type: none"> – 30 % or more but not more than 38 % of bivalent iron in relation to the total iron and – 1 % or more but not more than 4 % of cobalt | 0 |
| 0554 | ex 3824 90 99 12 | Spent catalyst, in the form of rodlets of diameter of 1 mm or more but not exceeding 3 mm, containing a mixture of sulfides of tungsten and of nickel on a support of zeolite, containing by weight not more than 10 % of tungsten and not more than 10 % of nickel, for regeneration as a catalyst for hydrocarbon cracking (a) | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--------------------|---|-----------------------------------|
| 0555 | ex 3824 90 99 13 | Mixture containing by weight: <ul style="list-style-type: none"> – 7 % or more but not more than 9 % of 2-methyl-1,3-phenylene diisocyanate, – 31 % or more but not more than 34 % of 4-methyl-1,3-phenylene diisocyanate, – 10 % or more but not more than 13 % of 2,4'-methylenediphenyl diisocyanate, – 46 % or more but not more than 49 % of 4,4'-methylenediphenyl diisocyanate | 0 |
| 0556 | ex 3824 90 99 14 | Mixture of magnesium bromide 2-oxoperhydroazepin-1-ide and ϵ -caprolactam | 0 |
| 0557 | ex 3824 90 99 15 | Mixture of disodium <i>N</i> -benzyloxycarbonyl-L-aspartate and sodium chloride, in the form of a solution in water | 0 |
| 0558 | ex 3824 90 99 16 | Disodium 9,10-dihydro-9,10-dioxoanthracene-2,7-disulfonate, containing by weight 10 % or more but not more than 20 % of sodium sulfate | 0 |
| 0559 | ex 3824 90 99 17 | Eutectic alloy wholly of potassium and sodium, containing by weight 77 % or more but not more than 79 % of potassium | 0 |
| 0560 | ex 3824 90 99 18 | Blend of terephthaloyl dichloride and isophthaloyl dichloride | 0 |
| 0561 | ex 3824 90 99 20 | Preparation consisting by weight of 83 % or more of 3a,4,7,7a-tetrahydro-4,7-methanoindene (dicyclopentadiene), a synthetic rubber, whether or not containing by weight 7 % or more of tricyclopentadiene, and: <ul style="list-style-type: none"> – either an aluminium-alkyl compound, – or an organic complex of tungsten – or an organic complex of molybdenum | 0 |
| 0562 | ex 3824 90 99 21 | Mixture of tris[2-chloro-1-(chloromethyl)ethyl] phosphate and oligomers of methylphosphonic acid and phosphoric acid with ethane-1,2-diol | 0 |
| 0563 | ex 3824 90 99 22 | Mixture of tris[2-chloro-1-(chloromethyl)ethyl] phosphate and oligomers of 2-chloroethyl phosphate with ethane-1,2-diol | 0 |
| 0564 | ex 3824 90 99 23 | Mixture of sucrose esters, derived from the esterification of sucrose with industrial stearic acid | 0 |
| 0565 | ex 3824 90 99 24 | Preparations consisting predominantly of phosphabicyclononanes and <i>P</i> -alkyl derivatives thereof, in the form of a solution in 4- <i>tert</i> -butyltoluene | 0 |
| 0566 | ex 3824 90 99 25 | Lithium tantalate wafers, undoped | 0 |
| 0567 | ex 3824 90 99 28 | Preparation consisting predominantly of ethylene glycol and <i>N,N</i> -dimethylformamide or ethylene glycol and γ -butyrolactone, for the manufacture of electrolytic capacitors (a) | 0 |
| 0568 | ex 3824 90 99 29 | Preparation consisting predominantly of γ -butyrolactone and quaternary ammonium salts, for the manufacture of electrolytic capacitors (a) | 0 |
| 0569 | ex 3824 90 99 30 | 2,4,7,9-Tetramethyldec-5-yne-4,7-diol, hydroxyethylated | 0 |
| 0570 | ex 3824 90 99 31 | Copper zinc ferrite, coated with a silicone resin, in the form of granules of a size not exceeding 120 μ m | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--------------------|---|-----------------------------------|
| 0571 | ex 3824 90 99 32 | Styrene oligomer | 0 |
| 0572 | ex 3824 90 99 33 | Preparation consisting of α -(4-allyloxycarbonylbenzoyl)- ω -allyloxypoly= [oxy(2-methylethylene)oxyterephthaloyl] and either diallyl-2,2'-oxydiethyl dicarbonate or diallyl isophthalate | 0 |
| 0573 | ex 3824 90 99 35 | Nitrosylsulfuric acid of a purity by weight of 70 % or more but not exceeding 73 % | 0 |
| 0574 | ex 3824 90 99 36 | Mixtures of silanol and diphosphorus pentaoxide, in the form of a solution in a mixture of ethanol and ethyl acetate, containing by weight 6 % or more but not more than 10 % of silanol and 0,1 % or more but not more than 0,3 % of diphosphorus pentaoxide | 0 |
| 0575 | ex 3824 90 99 37 | Sintered bauxite pellets, of a diameter not exceeding 2 mm | 0 |
| 0576 | ex 3824 90 99 39 | Mixture containing by weight 40 % or more but not more than 50 % of 2-hydroxyethyl methacrylate and 40 % or more but not more than 50 % of glycerol ester of boric acid | 0 |
| 0577 | ex 3824 90 99 40 | Azelaic acid of a purity by weight of 75 % or more but not exceeding 85 % | 0 |
| 0578 | ex 3824 90 99 42 | Mixed metals oxides, in the form of powder, containing by weight: <ul style="list-style-type: none"> – either 5 % or more of barium, neodymium or magnesium and 15 % or more of titanium, – or 30 % or more of lead and 5 % or more of niobium, for use in the manufacture of dielectric films or for use as dielectric materials in the manufacture of multilayer ceramic capacitors (a) | 0 |
| 0579 | ex 3824 90 99 43 | 7-Aminonaphthalene-1,3,6-trisulfonic acid and its salts, of a purity by weight of 65 % or more | 0 |
| 0580 | ex 3824 90 99 44 | Mixture containing by weight: <ul style="list-style-type: none"> – 60 % or more of 2-[N-(2-cyanoethyl)anilino]ethyl acetate and – 20 % or more of acetic acid | 0 |
| 0581 | ex 3824 90 99 45 | Preparations consisting predominantly of ethylene glycol and: <ul style="list-style-type: none"> – either diethylene glycol, dodecandioic acid and ammonia water, – or silicon oxide, – or ammonium hydrogen azelate, – or ammonium hydrogen azelate and silicon oxide, – or dodecandioic acid, ammonia water and silicon oxide, for the manufacture of electrolytic capacitors (a) | 0 |
| 0582 | ex 3824 90 99 46 | Carboxylic acid anhydride based hardener for epoxyde resin, in liquid form, of a specific weight at 25 °C of 1,15 g/cm ³ or more but not exceeding 1,18 g/cm ³ | 0 |
| 0583 | ex 3824 90 99 49 | Mixed oxides of metals, in the form of powder, containing by weight: <ul style="list-style-type: none"> – 70 % or more but not more than 75 % of iron oxide, – 10 % or more but not more than 20 % of zinc oxide, – 10 % or more but not more than 15 % of magnesium oxide, – 1 % or more but not more than 5 % of manganese oxide and – 1 % or more but not more than 3 % of copper oxide | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--------------------|---|-----------------------------------|
| 0584 | ex 3824 90 99 50 | Zeolites consisting of oxides of barium, aluminium and silicon, containing by weight 30 % or more but not more than 40 % of barium oxide, in the form of spheres of which 80 % or more by weight have a diameter of 0,3 mm or more but not more than 1,2 mm | 0 |
| 0585 | ex 3824 90 99 53 | Sodium 4-hydroxynaphthalene-1-sulfonate, of a purity by weight of 70 % or more but not exceeding 80 % | 0 |
| 0586 | ex 3824 90 99 54 | 2-Hydroxybenzointrile, in the form of a solution in <i>N,N</i> -dimethylformamide, containing by weight 45 % or more but not more than 50 % of 2-hydroxybenzointrile | 0 |
| 0587 | ex 3824 90 99 55 | Mixture containing by weight 75 % or more of pentaerythritol triallyl ether | 0 |
| 0588 | ex 3824 90 99 57 | Mixture of trialkylphosphine oxides | 0 |
| 0589 | ex 3824 90 99 58 | Platinum oxide fixed on a porous support of aluminium oxide, containing by weight 0,1 % or more but not more than 1 % of platinum and 0,5 % or more but not more than 5 % of ethylaluminium dichloride | 0 |
| 0590 | ex 3824 90 99 60 | α -Phenoxycarbonyl- ω -phenoxypoly[oxy(2,6-dibromo-1,4-phenylene)= isopropylidene(3,5-dibromo-1,4-phenylene)oxycarbonyl] | 0 |
| 0591 | ex 3824 90 99 61 | Mixture of metal oxides, in the form of powder, containing by weight: <ul style="list-style-type: none"> – 20 % or more of barium, – 10 % or more of titanium and – 4 % or more of lead or 3 % or more of niobium or 0,7 % or more of zirconium, for use as dielectric material in the manufacture of multilayer ceramic capacitors (a) | 0 |
| 0592 | ex 3824 90 99 63 | Triethylborane, in the form of a solution in tetrahydrofuran | 0 |
| 0593 | ex 3824 90 99 64 | Aluminium sodium silicate, in the form of spheres of a diameter of: <ul style="list-style-type: none"> – either 1,6 mm or more but not exceeding 3,4 mm, – or 4 mm or more but not exceeding 6 mm | 0 |
| 0594 | ex 3824 90 99 65 | Mixture of tris(alkoxycarbonylamino)-1,3,5-triazines in which alkoxy groups are methoxy and butoxy | 0 |
| 0595 | ex 3824 90 99 66 | Mixture of primary <i>tert</i> -alkylamines | 0 |
| 0596 | ex 3824 90 99 67 | Preparation consisting of indium tin oxide dispersed in organic solvents | 0 |
| 0597 | ex 3824 90 99 72 | Solution containing by weight 80 % or more of 2,4,6-trimethylbenzaldehyde in acetone | 0 |
| 0598 | ex 3824 90 99 73 | Particles of silicon dioxide on which are covalently bonded organic compounds, for use in the manufacture of high performance liquid chromatography columns (HPLC) and sample preparation cartridges (a) | 0 |
| 0599 | ex 3824 90 99 75 | Mixture of 2,2-bis[2-(perfluoroalkyl)ethylthiomethyl]propane-1,3-diols | 0 |
| 0600 | ex 3824 90 99 77 | Diethylmethoxyborane, in the form of a solution in tetrahydrofuran | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--------------------------------------|--|-----------------------------------|
| 0601 | ex 3824 90 99 81 | Calcium oxide stabilised zirconia in the form of lumps of which 94 % or more by weight is retained on a 16 mm sieve, containing by weight: <ul style="list-style-type: none"> - 92 % or more of zirconium dioxide and - 2 % or more but not more than 6 % of calcium oxide | 0 |
| 0602 | ex 3824 90 99 82 ex 3907 40 00 20 | α -(2,4,6-Tribromophenyl)- ω -(2,4,6-tribromophenoxy)poly[oxy(2,6-dibromo-1,4-phenylene)isopropylidene(3,5-dibromo-1,4-phenylene)oxycarbonyl] | 0 |
| 0540 | ex 3824 90 99 83 | Mixture containing: <ul style="list-style-type: none"> - unsaturated, dimerised fatty acids, hydrogenated and polymerized with ethylenediamine and octadecan-1-ol, - white oil, - 2-methylpentane-2,4-diol and - glycerides of decanoic and octanoic acids | 0 |
| 0541 | ex 3824 90 99 84 | Reaction product, containing by weight: <ul style="list-style-type: none"> - 1 % or more but not more than 40 % of molybdenum oxide, - 10 % or more but not more than 50 % of nickel oxide, - 30 % or more but not more than 70 % of tungsten oxide | 0 |
| 0542 | ex 3824 90 99 85 | Particles of magnesium sodium silicate on which are ionically bonded chiral complexes of tris(1,10-phenanthroline)ruthenium, for use in the manufacture of high performance liquid chromatography columns (HPLC) (a) | 0 |
| 0603 | ex 3901 10 10 10 | Linear polyethylene, of a specific gravity of 0,928 or more but not exceeding 0,935 and of a melt flow index of less than 0,6 g/min, for the manufacture of shrinkmelt binder fibres (a) | 0 |
| 0604 | ex 3901 10 90 10 | Polyethylene for the manufacture of photo-resist film for semiconductors or printed circuits (a) | 0 |
| 0605 | ex 3901 10 90 20 | Polyethylene, in the form of granules, of a specific gravity of 0,925 (\pm 0,0015), a melt flow index of 0,3 g/10 min (\pm 0,05 g/10 min), for the manufacture of blown films of a Haze value not exceeding 6 % and an elongation at break (MD/TD) of 210/340 (a) | 0 |
| 0606 | ex 3901 20 90 10 | Polyethylene, in one of the forms mentioned in note 6 (b) to Chapter 39, of a specific gravity of 0,945 or more but not exceeding 0,985, for the manufacture of films for typewriter ribbon or similar ribbon (a) | 0 |
| 0607 | ex 3901 20 90 20 | Polyethylene, containing by weight 35 % or more but not more than 45 % of mica | 0 |
| 0608 | ex 3901 90 90 81 | Copolymer of ethylene and propylene, modified with maleic anhydride, containing by weight more than 55 % of ethylene and not more than 3 % of maleic anhydride | 0 |
| 0609 | ex 3901 90 90 82 | Polyethylene modified with maleic anhydride, containing by weight not more than 4 % of maleic anhydride, for use in the manufacture of fuel tanks for motor vehicles (a) | 0 |
| 0610 | ex 3901 90 90 91 | Ionomer resin consisting of a salt of a copolymer of ethylene with methacrylic acid | 4 |
| 0611 | ex 3901 90 90 93 | Copolymer of ethylene, vinyl acetate and carbon monoxide, for use as a plasticizer in the manufacture of roof sheets (a) | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--|---|-----------------------------------|
| 0612 | ex 3901 90 90 94 | Mixtures of A-B block copolymer of polystyrene and ethylene-butylene copolymer and A-B-A block copolymer of polystyrene, ethylene-butylene copolymer and polystyrene, containing by weight not more than 35 % of styrene | 0 |
| 0613 | ex 3901 90 90 95 ex 3902 90 90 95 | Copolymer of ethylene and butylene, having hydroxyl or acrylate end-groups, containing by weight 40 % or more but not more than 60 % of butylene | 0 |
| 0614 | ex 3901 90 90 96 ex 3902 90 90 96 ex 3903 90 90 50 | Linear A-B block copolymer of polyisoprene, whether or not epoxidized, and either ethylene-butylene copolymer or styrene-ethylene-butylene copolymer, having hydroxyl end-groups | 0 |
| 0615 | ex 3902 10 00 10 | Polypropylene containing no plasticizer and not more than: <ul style="list-style-type: none"> – 7 mg/kg of aluminium, – 2 mg/kg of iron, – 1 mg/kg of magnesium, – 8 mg/kg of chloride | 0 |
| 0616 | ex 3902 10 00 20 | Polypropylene, containing no plasticiser, <ul style="list-style-type: none"> – of a melting point of more than 150 °C (as determined by the ASTM D 3417 method), – of a heat of fusion of 15 J/g or more but not exceeding 70 J/g, – of an elongation at break of 1 000 % or more (as determined by the ASTM D 638 method), – of a tensile modulus of 69 MPa or more but not exceeding 379 MPa (as determined by the ASTM D 638 method) | 0 |
| 0617 | ex 3902 10 00 30 | Polypropylene, containing not more than 1 mg/kg of aluminium, 0,05 mg/kg of iron, 1 mg/kg of magnesium and 1 mg/kg of chloride, for use in the manufacture of packaging for disposable contact lenses (a) | 0 |
| 0619 | ex 3902 30 00 91 ex 3903 90 90 25 | A-B Block copolymer of polystyrene and an ethylene-propylene copolymer, containing by weight 40 % or less of styrene, in one of the forms mentioned in note 6 (b) to Chapter 39 | 0 |
| 0620 | ex 3902 30 00 92 | Copolymer of propylene, butylene and ethylene, containing by weight more than 65 % but less than 80 % of propylene and not less than 20 % of butylene | 0 |
| 0618 | ex 3902 30 00 94 | Chlorinated polypropylene, chemically modified with maleic anhydride, containing by weight 23 % or more but not more than 26 % of chlorine and less than 5 % of epoxy resin | 0 |
| 0621 | ex 3902 90 90 92 | Polymers of 4-methylpent-1-ene | 0 |
| 0622 | ex 3902 90 90 97 | Hydrogenated polyisobutene, in liquid form | 0 |
| 0623 | ex 3903 19 00 20 | Polystyrene of a molecular weight (M_n) not exceeding 5 000 | 0 |
| 0625 | ex 3903 90 90 10 | Copolymer, entirely of styrene with maleic anhydride, or entirely of styrene with maleic anhydride and an acrylic monomer, whether or not containing a styrene-butadiene block copolymer, in one of the forms mentioned in note 6 (b) to Chapter 39, for the manufacture of sheetings for head-liners for cars (a) | 0 |
| 0626 | ex 3903 90 90 15 | Copolymer, entirely of styrene with maleic anhydride, or entirely of styrene with maleic anhydride and an acrylic monomer, also partially esterified, of an average molecular weight (M_n) not exceeding 3 000, in one of the forms mentioned in note 6 (a) and (b) to Chapter 39 | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--|--|-----------------------------------|
| 0627 | ex 3903 90 90 20 | Copolymer of styrene with 2-ethylhexyl acrylate or with <i>n</i> -butyl acrylate, containing: <ul style="list-style-type: none"> – 10 mole % or more but not more than 16 mole % of acrylate, – 0,2 mg/kg or less of sodium and – 0,1 mg/kg or less of calcium | 0 |
| 0628 | ex 3903 90 90 35 ex 3911 90 99 30 | Copolymer of α -methylstyrene and styrene, having a softening point exceeding 113 °C | 0 |
| 0629 | ex 3903 90 90 40 ex 3906 90 90 40 ex 3911 90 99 50 | Copolymer of styrene with α -methylstyrene and acrylic acid, of a molecular weight (M_n) of 500 or more but not exceeding 6 000 | 0 |
| 0630 | ex 3903 90 90 55 ex 3906 90 90 45 | Copolymer of styrene, methyl methacrylate, butyl acrylate and either acrylic acid or hydroxyethyl methacrylate, of a molecular weight (M_n) of 500 or more but not exceeding 6 000 | 0 |
| 0631 | ex 3903 90 90 65 | Copolymer of styrene, butyl acrylate, butyl methacrylate, methyl methacrylate and acrylic acid, in the form of powder, containing by weight (81 \pm 1) % of styrene, (6 \pm 1) % of butyl acrylate, (5 \pm 1) % of butyl methacrylate, (7 \pm 1) % of methyl methacrylate and (1 \pm 0,5) % of acrylic acid | 0 |
| 0632 | ex 3903 90 90 70 | Ammonium polystyrenesulfonate, in the form of an aqueous solution | 0 |
| 0633 | ex 3904 22 00 91 ex 3926 90 99 80 | Poly(vinyl chloride), dyed in the mass, in the form of flakes, grains, pebbles or rectangular chips, for use as decorative elements in floor and wall coverings (a) | 0 |
| 0634 | ex 3904 30 00 10 | Copolymer of vinyl chloride with vinyl acetate and maleic acid, containing by weight: <ul style="list-style-type: none"> – 81,5 % or more but not more than 84,5 % of vinyl chloride, – 13,8 % or more but not more than 16,2 % of vinyl acetate and – 0,8 % or more but not more than 1,2 % of maleic acid, for the manufacture of goods of heading No 3215 or for use in the manufacture of coatings for containers and closures of a kind used for preserving food and drink (a) | 0 |
| 0635 | ex 3904 30 00 20 | Copolymer of vinyl chloride, vinyl acetate and maleic acid, for use in the manufacture of poly(vinyl chloride)-metal heat-sealing adhesive (a) | 0 |
| 0636 | ex 3904 40 00 91 | Copolymer of vinyl chloride with vinyl acetate and vinyl alcohol, containing by weight: <ul style="list-style-type: none"> – 87 % or more but not more than 92 % of vinyl chloride, – 2 % or more but not more than 9 % of vinyl acetate and – 1 % or more but not more than 8 % of vinyl alcohol, in one of the forms mentioned in note 6 (a) or (b) to Chapter 39, for the manufacture of goods of heading No 3215 or 8523 or for use in the manufacture of coatings for containers and closures of a kind used for preserving food and drink (a) | 0 |
| 0637 | ex 3904 40 00 92 | Copolymer of vinyl chloride, vinyl acetate, hydroxypropyl acrylate and maleic acid, containing by weight 80 % or more but not more than 83 % of vinyl chloride, 1,6 % or more but not more than 2 % of hydroxy groups and 0,25 % or more but not more than 0,38 % of carboxyl groups | 0 |
| 0638 | ex 3904 40 00 93 | Copolymer of vinyl chloride and methyl acrylate, containing by weight (80 \pm 1) % of vinyl chloride and (20 \pm 1) % of methyl acrylate, in the form of a aqueous emulsion | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--------------------|--|-----------------------------------|
| 0639 | ex 3904 50 90 91 | Copolymer of vinylidene chloride with vinyl chloride, containing by weight 79,5 % or more of vinylidene chloride, in one of the forms mentioned in note 6 (a) or (b) to Chapter 39, for the manufacture of fibres, monofilament or strip (a) | 0 |
| 0640 | ex 3904 61 00 10 | Mixture of polytetrafluoroethylene and mica, in one of the forms mentioned in note 6 (b) to Chapter 39 | 0 |
| 0641 | ex 3904 61 00 20 | Copolymer of tetrafluoroethylene and trifluoro(heptafluoropropoxy)ethylene, containing 3,2 % or more but not more than 4,6 % by weight of trifluoro(heptafluoropropoxy)ethylene and less than 1 mg/kg of extractable fluoride ions | 0 |
| 0642 | ex 3904 69 90 92 | Copolymer of tetrafluoroethylene and trifluoro(trifluoromethoxy)ethylene | 0 |
| 0643 | ex 3904 69 90 93 | Copolymer of ethylene with chlorotrifluoroethylene, in one of the forms mentioned in note 6 (b) to Chapter 39 | 0 |
| 0644 | ex 3904 69 90 94 | Copolymer of ethylene and tetrafluoroethylene | 0 |
| 0645 | ex 3904 69 90 96 | Polychlorotrifluoroethylene, in one of the forms mentioned in note 6 (a) and (b) to Chapter 39 | 0 |
| 0646 | ex 3905 29 00 91 | Copolymer of vinyl acetate, dibutyl maleate and acrylic acid, in the form of a solution in isopropyl acetate and toluene | 0 |
| 0647 | ex 3905 91 00 91 | Copolymer of <i>N</i> -vinylcaprolactam, <i>N</i> -vinyl-2-pyrrolidone and dimethylaminoethyl methacrylate | 0 |
| 0652 | ex 3905 99 90 93 | Poly(vinyl acetate phthalate) | 0 |
| 0653 | ex 3905 99 90 94 | Polymer of vinylpyrrolidone and dimethylaminoethyl methacrylate, containing by weight 97 % or more but not more than 99 % of vinylpyrrolidone, in the form of a solution in water | 0 |
| 0654 | ex 3905 99 90 95 | Hexadecylated or eicosylated polyvinylpyrrolidone | 0 |
| 0655 | ex 3905 99 90 96 | Polymer of vinyl formal, in one of the forms mentioned in note 6 (b) to Chapter 39, of a molecular weight (M_w) of 25 000 or more but not exceeding 150 000 and containing by weight: <ul style="list-style-type: none"> – 9,5 % or more but not more than 13 % of acetyl groups evaluated as vinyl acetate and – 5 % or more but not more than 6,5 % of hydroxy groups evaluated as vinyl alcohol | 0 |
| 0651 | ex 3905 99 90 97 | Povidone (INN)-iodine | 0 |
| 0656 | ex 3906 10 00 10 | Poly(methyl methacrylate), in the form of expansible beads containing 2-methylpentane as blowing agent | 0 |
| 0657 | 3906 90 60 | Copolymer of methyl acrylate with ethylene and a monomer containing a non-terminal carboxy group as a substituent, containing by weight 50 % or more of methyl acrylate, whether or not mixed with silicon dioxide | 0 |
| 0662 | ex 3906 90 90 10 | Polymerization product of acrylic acid with small quantities of a polyunsaturated monomer, for the manufacture of medicaments of heading No 3003 or 3004 (a) | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--------------------------------------|--|-----------------------------------|
| 0663 | ex 3906 90 90 20 | Polymerization product of acrylic acid with small quantities of a polyunsaturated monomer, for use as a stabilizer in emulsions or dispersions with a pH of more than 13 (a) | 6 |
| 0664 | ex 3906 90 90 30 | Copolymer of styrene with hydroxyethyl methacrylate and 2-ethylhexyl acrylate, of a molecular weight (M_n) of 500 or more but not exceeding 6 000 | 0 |
| 0665 | ex 3906 90 90 50 | Polymers of esters of acrylic acid with one or more of the following monomers in the chain: <ul style="list-style-type: none"> – chloromethyl vinyl ether, – chloroethyl vinyl ether, – chloromethylstyrene, – vinyl chloroacetate, – methacrylic acid, containing by weight not more than 5 % of each of the monomeric units | 0 |
| 0666 | ex 3906 90 90 60 | Copolymer of butyl acrylate and vinyl chloride, containing by weight (58 ± 1) % of butyl acrylate and (42 ± 1) % of vinyl chloride, in the form of a aqueous emulsion | 0 |
| 0667 | ex 3906 90 90 70 | Copolymer of ethylene dimethacrylate with either methyl methacrylate or dodecyl methacrylate | 0 |
| 0668 | ex 3906 90 90 80 | Polydimethylsiloxane-graft-(polyacrylates; polymethacrylates) | 0 |
| 0669 | ex 3907 20 11 10 | Poly(ethylene oxide) of an average molecular weight (M_n) of 100 000 or more | 0 |
| 0670 | ex 3907 20 29 10 | Polymer of dextrose, sorbitol and citric or phosphoric acid, containing by weight 90 % or more of dextrose monomer units | 0 |
| 0671 | ex 3907 20 29 20 | Poly[oxy-1,4-phenyleneisopropylidene-1,4-phenyleneoxy-(2-hydroxytrimethylene)], of an average molecular weight (M_w) of more than 26 000, in one of the forms mentioned in note 6 (b) to Chapter 39 | 0 |
| 0672 | ex 3907 20 99 10 | Bis{2-[ω -hydroxy-poly(ethyleneoxy)]ethyl} hydroxymethylphosphonate | 0 |
| 0673 | ex 3907 20 99 15 | Poly(oxypropylene) having alkoxyethyl end-groups | 0 |
| 0674 | ex 3907 20 99 25 | α -4-Hydroxybutyl- ω -hydroxypoly(oxytetramethylene), containing less than 1 mg/kg of halogen and less than 1 mg/kg of metal, and of a colour not exceeding 20 units on the Hazen scale | 0 |
| 0675 | ex 3907 20 99 30 | Homopolymer of 1-chloro-2,3-epoxypropane (epichlorohydrin) | 0 |
| 0676 | ex 3907 30 00 20 | Epoxyde resin in the form of powder, containing by weight 44 % or more but not more than 55 % of quartz and 0,5 % or more but not more than 1 % of diantimony trioxide, for the coating of film capacitors (a) | 0 |
| 0677 | ex 3907 30 00 30 | Epoxyde resin, without solvent, containing mineral fillers (silica), without glass fibre, of a specific weight at 25 °C of 1,55 g/cm ³ or more but not exceeding 1,60 g/cm ³ | 0 |
| 0678 | ex 3907 30 00 40 ex 3926 90 99 70 | Epoxyde resin, containing by weight 70 % or more of silicon dioxide, for the encapsulation of goods of heading No 8533, 8535, 8536, 8541, 8542 or 8548 (a) | 0 |
| 0679 | ex 3907 40 00 10 | Copolymer of hexane-1,6-diol, cyclohexane-1,4-dimethanol and ethylene carbonate | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--------------------------------------|--|-----------------------------------|
| 0680 | ex 3907 60 80 10 | Copolymer of terephthalic acid and isophthalic acid with ethylene glycol, butane-1,4-diol and hexane-1,6-diol | 0 |
| 0681 | ex 3907 60 80 20 | Oxygen binding copolymer (as determined by the ASTM D 1434 and 3985 methods), obtained from benzenedicarboxylic acids, ethylene glycol and polybutadiene substituted by hydroxy groups | 0 |
| 0682 | ex 3907 91 90 10 | Diallyl phthalate prepolymer, in the form of powder | 0 |
| 0684 | ex 3907 99 19 10 ex 3907 99 99 10 | Poly(oxy-1,4-phenylenecarbonyl), in the form of powder | 0 |
| 0685 | ex 3907 99 19 20 | Liquid crystal copolyester with a melting point of not less than 270 °C, whether or not containing fillers | 0 |
| 0683 | ex 3907 99 19 30 | Poly(lactic acid) | 0 |
| 0686 | ex 3908 90 00 10 | Poly(iminomethylene-1,3-phenylenemethyleneiminoadipoyl), in one of the forms mentioned in note 6 (b) to Chapter 39 | 0 |
| 0687 | ex 3908 90 00 20 | Copolymer consisting of hexamethylenediamine, isophthalic acid and terephthalic acid, in one of the forms mentioned in note 6(b) to Chapter 39 | 0 |
| 0688 | ex 3909 40 00 10 | Polycondensation product of phenol with formaldehyde, in the form of hollow spheres of a diameter of less than 150 µm | 0 |
| 0689 | ex 3910 00 00 10 | 3-[(2-Aminoethyl)amino]propyl(methyl)cyclosiloxane | 0 |
| 0690 | ex 3910 00 00 20 | Block copolymer of poly(methyl-3,3,3-trifluoropropylsiloxane) and poly[methyl(vinyl)siloxane] | 0 |
| 0691 | ex 3911 90 19 10 | Poly(oxy-1,4-phenylenesulfonyl-1,4-phenyleneoxy-4,4'-biphenylene) | 0 |
| 0692 | ex 3911 90 99 20 | Copolymer of dibutyl maleate and <i>N</i> -vinyl-2-pyrrolidone, in one of the forms mentioned in note 6 (a) of Chapter 39 | 0 |
| 0693 | ex 3911 90 99 25 | Copolymer of vinyltoluene and α -methylstyrene | 0 |
| 0694 | ex 3911 90 99 40 | Mixed calcium and sodium salt of a copolymer of maleic acid and methyl vinyl ether, having a calcium content of 9 % or more but not more than 16 % by weight | 0 |
| 0695 | ex 3911 90 99 45 | Copolymer of maleic acid and methyl vinyl ether | 0 |
| 0696 | ex 3911 90 99 55 | Solution containing: <ul style="list-style-type: none"> – (36 ± 0,5) % by weight of polyamide with lateral ester groups, – (2 ± 0,5) % by weight of acrylic ester, – (48 ± 0,5) % by weight of 1-methyl-2-pyrrolidone, – (12 ± 0,5) % by weight of bis(2-methoxyethyl) ether, – 500 µg/kg or less of potassium and – 500 µg/kg or less of iron, for use in the manufacture of goods of heading No 8542 (a) | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--|---|-----------------------------------|
| 0697 | ex 3911 90 99 60 | Hydrocarbon prepolymer, obtained by the reaction of cyclopentadiene and 1,3-pentadiene | 0 |
| 0648 | ex 3911 90 99 65 | Calcium zinc salt of a copolymer of maleic acid and methyl vinyl ether | 0 |
| 0698 | ex 3912 11 00 10 | Non-plasticized cellulose triacetate, in the form of flakes, for the manufacture of cellulose triacetate yarn (a) | 0 |
| 0699 | ex 3912 39 10 10 | Ethylcellulose, not plasticized | 0 |
| 0700 | ex 3912 39 10 20 | Ethylcellulose, in the form of aqueous dispersion containing hexadecan-1-ol and sodium dodecyl sulfate, containing by weight (27 ± 3) % of ethylcellulose | 0 |
| 0701 | ex 3912 39 80 10 | Cellulose, both hydroxyethylated and ethylated, insoluble in water | 0 |
| 0702 | ex 3912 39 80 20 | Cellulose, both hydroxyethylated and alkylated with alkyl chain-lengths of 3 or more carbon atoms | 0 |
| 0703 | ex 3912 90 10 10 | Cellulose acetate propionate, non-plasticised, in the form of powder: <ul style="list-style-type: none"> – containing by weight 25 % or more of propionyl (as determined by the ASTM D 817-72 method) and – of a viscosity not exceeding 120 poise (as determined by the ASTM D 817-72 method), for the manufacture of printing inks, paints, lacquers and other coatings, and reprographic coatings (a) | 0 |
| 0704 | ex 3913 90 80 30 | Chondroitinsulfuric acid, sodium salt | 0 |
| 0705 | ex 3913 90 80 40 | Chitosonium pyrrolidonecarboxylate | 0 |
| 0706 | ex 3915 90 93 30 | Waste, parings and scrap of photographic, cinematographic and radiographic films | 0 |
| 0707 | ex 3917 32 10 10 | Flexible pipe of silicone foam, with continuous channels, of a Shore A hardness of 7 or more but not exceeding 48 and a density of 0,28 g/cm ³ or more but not exceeding 0,92 g/cm ³ | 0 |
| 0708 | ex 3917 32 31 91 ex 3917 32 99 10 ex 3926 90 99 45 | Assembly of heat-shrinkable tubing of polyethylene with poly(vinyl acetate), arranged in parallel at equally spaced intervals and attached at one or both ends by perforated plastic strips, in rolls | 0 |
| 0709 | ex 3917 32 39 20 | Pipe consisting of a block copolymer of polytetrafluoroethylene and polyperfluoroalkoxytrifluoroethylene, of a length of not more than 600 mm, a diameter of not more than 85 mm and a wall-thickness of 30 µm or more but not exceeding 110 µm | 0 |
| 0710 | ex 3919 10 31 10 ex 3919 10 38 30 ex 3919 90 31 50 | Reflecting laminated sheet, consisting of a film of polycarbonate totally embossed on one side in a regular shaped pattern, covered on both sides with one or more layers of plastic material and on one side with an adhesive layer and a release sheet | 0 |
| 0711 | ex 3919 10 38 10 | Self-adhesive tape of metallised polyurethane containing glass beads for use in the manufacture of marine life-saving equipment (a) | 0 |
| 0712 | ex 3919 10 38 20 ex 3919 90 38 10 ex 3920 99 28 20 | Reflecting film, consisting of a layer of polyurethane with security imprints and embedded glass beads on one side and an adhesive layer on the other side, covered on one side or on both sides with a release film | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--|--|-----------------------------------|
| 0713 | ex 3919 10 61 91 ex 3919 90 61 94 | Reflecting film, consisting of a layer of poly(vinyl chloride), a layer of alkyd polyester, with security imprints and embedded glass beads on one side and an adhesive layer on the other side, covered on one side or on both sides with a release film | 0 |
| 0714 | ex 3919 90 10 10 | Shaped sheet of plastic, with an adhesive layer containing polyisobutylene and pectin, for the manufacture of colostomy bags (a) | 0 |
| 0715 | ex 3919 90 10 20 | Poly(ethylene terephthalate) film, covered on one side with an antistatic layer and a hardcoat layer and on the other side with an adhesive layer and a release sheet, in the form of sheets of dimensions not exceeding 450 × 750 mm | 0 |
| 0716 | ex 3919 90 31 40 ex 3920 62 19 20 ex 3920 62 90 20 ex 3920 63 00 30 ex 3920 69 00 30 | Reflecting polyester sheeting embossed in a pyramidal pattern, for the manufacture of safety stickers and badges, safety clothing and accessories thereof, or of school satchels, bags or similar containers (a) | 0 |
| 0717 | ex 3919 90 61 92 ex 3919 90 69 92 | Poly(vinyl chloride) sheeting, of a thickness of less than 1 mm, coated with an adhesive in which are embedded glass balls of a diameter not exceeding 100 µm | 0 |
| 0718 | ex 3919 90 61 93 ex 3919 90 69 93 ex 3920 10 89 25 | Adhesive film consisting of a base of a copolymer of ethylene and vinyl acetate (EVA) of a thickness of 120 µm or more and an adhesive part of acrylic type of a thickness of 10 µm or more, for the protection of the surface of silicon discs (a) | 0 |
| 0720 | ex 3919 90 69 94 | Reflecting laminated sheet, consisting of a film of poly(methyl methacrylate) embossed on one side in a regular pyramidal or other shaped pattern, a film of a polymer of methyl methacrylate containing glass microprisms or microspheres, an adhesive layer and a release sheet | 0 |
| 0719 | ex 3919 90 69 95 ex 3920 51 00 30 | Biaxially-oriented film of poly(methyl methacrylate), of a thickness of 50 µm or more but not exceeding 90 µm, whether or not covered on one side with an adhesive layer and a release sheet | 0 |
| 0721 | ex 3920 10 26 20 | Film of polyethylene, of a thickness of 20 µm or more but not exceeding 45 µm, containing calcium carbonate in the mass, for the manufacture of napkins for babies or of sanitary towels or of tampons or of disposable surgical gowns (a) | 0 |
| 0722 | ex 3920 10 26 30 ex 3920 10 89 20 | Film of a thickness not exceeding 0,20 mm, of a blend of polyethylene and a copolymer of ethylene with oct-1-ene, embossed in a regular rhomboidal pattern, for coating both sides of a layer of unvulcanized rubber (a) | 0 |
| 0725 | ex 3920 10 40 91 | Synthetic paper pulp, in the form of moist sheets, made from unconnected finely-branched polyethylene fibrils, whether or not blended with cellulose fibres in a quantity not exceeding 15 %, containing poly(vinyl alcohol) dissolved in water as the moistening agent | 0 |
| 0726 | ex 3920 10 40 92 | Laminated sheet or strip consisting of a film composed of a blend of a copolymer of ethylene with vinyl acetate and a modified ethylene-propylene-elastomer (EPM) or a modified ethylene-propylene-diene elastomer (EPDM), coated or covered on both sides with a film of a copolymer of ethylene with vinyl acetate | 0 |
| 0727 | ex 3920 10 89 35 | Reflecting film, consisting of a layer of polyethylene, a layer of polyurethane, with security imprints and embedded glass beads on one side and a hot-melt adhesive layer on the other side, covered on one side or on both sides with a release film | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--------------------------------------|---|-----------------------------------|
| 0728 | ex 3920 20 29 91 | Mono-axial oriented film, consisting of three layers, each layer consisting of a mixture of polypropylene and a copolymer of ethylene and vinyl acetate, having: <ul style="list-style-type: none"> – a thickness of 55 µm or more but not exceeding 97 µm, – a tensile modulus in the machine direction of 0,75 GPa or more but not exceeding 1,45 GPa and – a tensile modulus in the transverse direction of 0,20 GPa or more but not exceeding 0,55 GPa | 0 |
| 0729 | ex 3920 20 90 91 | Synthetic paper pulp, in the form of moist sheets, made from unconnected finely-branched polypropylene fibrils, whether or not blended with cellulose fibres in a quantity not exceeding 15 %, containing poly(vinyl alcohol) dissolved in water as the moistening agent | 0 |
| 0730 | ex 3920 20 90 92 | Laminated sheet or strip, consisting of a film of a thickness of 181 µm or more but not exceeding 223 µm composed of a blend of a copolymer of propylene with ethylene and a copolymer of styrene-ethylene-butylene-styrene (SEBS) coated or covered on one side with a layer of a copolymer of styrene-ethylene-butylene-styrene (SEBS) and a layer of polyester | 0 |
| 0731 | ex 3920 20 90 93 | Polypropylene sheet, of a thickness of 0,5 mm or more but not exceeding 1,0 mm, having a tensile strength at break of 14,7 MPa or more but not exceeding 21 MPa (as determined by the ASTM D 638 method), in rolls of a width of 3,81 m | 0 |
| 0732 | ex 3920 30 00 20 | Laminated sheet or strip, consisting of a film composed of a blend of a thermoplastic elastomer (TPE) of styrene-butadiene-styrene (SBS) with polyethylene or polypropylene, of a thickness of 100 µm or more but not exceeding 200 µm, coated or covered on both sides with a film of polypropylene of a thickness not exceeding 20 µm | 0 |
| 0735 | ex 3920 43 10 91 ex 3920 49 10 91 | Reflecting sheeting, consisting solely of a single layer of poly(vinyl chloride), wholly embossed on one side in a regular pyramidal pattern | 0 |
| 0736 | ex 3920 43 10 92 | Sheeting of poly(vinyl chloride), stabilized against ultraviolet rays, without any holes, even microscopic, of a thickness of 60 µm or more but not exceeding 80 µm, containing 30 or more but not more than 40 parts of plasticizer to 100 parts of poly(vinyl chloride) | 0 |
| 0737 | ex 3920 43 10 93 | Poly(vinyl chloride) sheet, with relief printing, of a kind used in the templates for textile printing | 0 |
| 0738 | ex 3920 43 10 94 ex 3920 49 10 93 | Film of a gloss level of 70 or more, measured at 60 ° using a gloss meter (as determined by the ISO 2813:2000 method), consisting of one or two layers of poly(vinyl chloride) coated on both sides with a layer of plastic, of a thickness of 0,26 mm or more but not exceeding 1,0 mm, covered on the gloss surface with a protective film of polyethylene, in rolls of a width of 1 000 mm or more but not exceeding 1 450 mm, for use in the manufacture of goods of heading No 9403 (a) | 0 |
| 0739 | ex 3920 43 10 95 ex 3920 49 10 92 | Reflecting laminated sheet, consisting of a film of poly(vinyl chloride) and a film of an other plastic totally embossed in a regular pyramidal pattern, covered on one side with a release sheet | 0 |
| 0734 | ex 3920 43 10 96 | Film of a gloss level of 70 or more, measured at an angle of 60 ° using a gloss meter (as determined by the ISO 2813:2000 method), consisting of a layer of poly(ethylene terephthalate) and a layer of colored poly(vinyl chloride), for coating panels and doors of a kind used in the manufacture of domestic appliances (a) | 0 |
| 0740 | ex 3920 51 00 10 | Poly(methyl methacrylate) plate, with an antistatic coating, of dimensions of 738 × 972 mm (± 1,5 mm) | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--------------------|---|-----------------------------------|
| 0741 | ex 3920 51 00 20 | Plate of poly(methyl methacrylate) containing aluminium trihydroxide, of a thickness of 3,5 mm or more but not exceeding 19 mm | 0 |
| 0742 | ex 3920 61 00 10 | Polycarbonate film of a thickness not exceeding 15 µm, for the manufacture of film capacitors (a) | 0 |
| 0744 | ex 3920 62 19 05 | Coextruded opaque sheet of poly(ethylene terephthalate), of a thickness of 50 µm or more but not exceeding 350 µm, consisting especially of a layer containing carbon black | 0 |
| 0745 | ex 3920 62 19 10 | Poly(ethylene terephthalate) film, of a thickness of less than 11 µm, for the manufacture of audiodigital tapes for cassettes (a) | 0 |
| 0746 | ex 3920 62 19 15 | Poly(ethylene terephthalate) film, not coated with an adhesive, of a thickness not exceeding 25 µm, either: <ul style="list-style-type: none"> – only dyed in the mass, or – dyed in the mass and metallized on one side | 0 |
| 0747 | ex 3920 62 19 25 | Film of poly(ethylene terephthalate) only, of a total thickness not exceeding 120 µm, consisting of one or two layers each containing a colouring and/or UV-absorbing material throughout the mass, uncoated with an adhesive or any other material | 0 |
| 0748 | ex 3920 62 19 30 | Poly(ethylene terephthalate) film, of a thickness of 20 µm or more but not exceeding 30 µm, coated on one side with silicone, for use in the manufacture of window film (a) | 5.6 |
| 0749 | ex 3920 62 19 35 | Laminated film of poly(ethylene terephthalate) only, of a total thickness not exceeding 120 µm, consisting of one layer which is metallised only and one or two layers each containing a colouring and/or UV-absorbing material throughout the mass, uncoated with an adhesive or any other material | 0 |
| 0750 | ex 3920 62 19 40 | Film of poly(ethylene terephthalate), coated or covered on one side or on both sides with a layer of modified polyester, of a total thickness of 7 µm or more but not exceeding 11 µm, for the manufacture of video tapes with a magnetic layer of metallic pigments and a width of 8 mm or of 12,7 mm (a) | 0 |
| 0751 | ex 3920 62 19 45 | Single ply film of poly(ethylene terephthalate) only, of a thickness not exceeding 120 µm, which only: <ul style="list-style-type: none"> – contains a colouring and/or UV-absorbing material throughout the mass and – is metallised on one side, whether or not coated on one or both sides with a vinyl acrylate polymer but having no other coating or adhesive | 0 |
| 0752 | ex 3920 62 19 50 | Film of poly(ethylene terephthalate), of a total thickness not exceeding 120 µm, of a width of 100 mm or more but not exceeding 115 mm, coated on both sides with one or more layers containing different chemicals, for the manufacture of goods of subheading 3701 20 00 (a) | 0 |
| 0753 | ex 3920 62 19 55 | Film of poly(ethylene terephthalate), on one side metallised and coated with white ink and a protective layer and on the other side coated with a thermosensitive seal layer, of a width of 100 mm or more but not exceeding 150 mm, for the manufacture of goods of subheading 3701 20 00 (a) | 0 |
| 0754 | ex 3920 62 19 60 | Film of poly(ethylene terephthalate), coated on one side with a layer of modified polyester, of a thickness of 20 µm (± 0,7 µm) or of 30 µm (± 0,9 µm), for the manufacture of audio magnetic tapes of a total thickness of 33 µm or more (a) | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--------------------------------------|---|-----------------------------------|
| 0755 | ex 3920 62 19 62 | Poly(ethylene terephthalate) film, of a thickness not exceeding 12 µm, coated on one side with a layer of aluminium oxide of a thickness not exceeding 35 nm | 0 |
| 0756 | ex 3920 62 19 64 | Poly(ethylene terephthalate) film, of a thickness of 18 µm or more but not exceeding 25 µm, having: <ul style="list-style-type: none"> – a shrinkage of (3,4 ± 0,1) % in the machine direction (as determined by the ASTM D 1204 method) and – a shrinkage of (0,3 ± 0,2) % in the transverse direction (as determined by the ASTM D 1204 method) | 0 |
| 0757 | ex 3920 62 19 65 | Poly(ethylene terephthalate) film, of a thickness not exceeding 19 µm or of a weight of 20 g/m ² or more but not exceeding 26,7 g/m ² , for use in the manufacture of photo-resist film (a) | 0 |
| 0758 | ex 3920 62 19 70 | Film of poly(ethylene terephthalate), coated on both sides with a layer of epoxy acrylic resin, of a total thickness of 37 µm (± 3 µm) | 0 |
| 0768 | ex 3920 62 19 71 ex 3920 69 00 70 | Non-metallised reflecting film, consisting of outside layers of poly(ethylene terephthalate) or poly(ethylene naphthalate) and multiple layers of poly(methyl methacrylate), of a reflectance coefficient of 95 % or more (as determined by the ASTM E 1164-94 and ASTM E 387-95 methods) and a total thickness not exceeding 70 µm | 0 |
| 0769 | ex 3920 62 19 72 | Non-metallised reflecting film, consisting of outside layers of poly(ethylene terephthalate) and multiple layers of poly(methyl methacrylate), of a total thickness of 51 µm (± 10 %), for use in the manufacture of laminated solar-reflecting automotive glass (a) | 0 |
| 0759 | ex 3920 62 19 75 | Film of poly(ethylene terephthalate), coated on one side with metal and/or metal oxides, containing by weight less than 0,1 % of aluminium, of a thickness not exceeding 300 µm and having a surface resistivity not exceeding 10 000 ohms (per square) (as determined by the ASTM D 257-93 method) | 0 |
| 0760 | ex 3920 62 19 80 | Mat film of poly(ethylene terephthalate), of a gloss of 15 at an angle of 45 ° and 18 at an angle of 60 ° (as determined by the ASTM D 523 method) and a width of 1 600 mm or more | 0 |
| 0761 | ex 3920 62 19 81 | Film of white poly(ethylene terephthalate), dyed in the mass, of a thickness of 185 µm or more but not exceeding 253 µm, coated on both sides with an antistatic layer | 0 |
| 0762 | ex 3920 62 19 85 | Film of a total thickness of 4,5 µm (± 0,16 µm), consisting of a biaxially-oriented poly(ethylene terephthalate) film, of an elastic modulus (in the machine direction) of 12 kg/mm ² (± 2 kg/mm ²) and a tensile strength (in the machine direction) of more than 28 kg/mm ² , and of an anti-adherent coating | 0 |
| 0763 | ex 3920 62 19 87 | Poly(ethylene terephthalate) film, coated with a wax layer, a scratch resistant layer and a thermoadhesive layer, of a nominal width of 790 mm and a total thickness of 23 µm or more but not exceeding 26 µm | 0 |
| 0764 | ex 3920 62 19 88 | Laminated sheet, consisting of a biaxially oriented film of poly(ethylene terephthalate), covered on one side or on both sides with a layer of poly(ethylene terephthalate), for use in the manufacture of identity cards, credit cards and similar products (including “smart” cards) (a) | 0 |
| 0765 | ex 3920 62 19 89 | Multilayer film of a thickness not exceeding 150 µm, consisting of a polyester film coated on one side with polycarbonate resin, metallized on the other side with titanium coated with polycarbonate resin and other layers containing <i>N,N'</i> -diphenyl- <i>N,N'</i> -di- <i>m</i> -tolylbiphenyl-4,4'-ylenediamine | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--|---|-----------------------------------|
| 0766 | ex 3920 62 90 30 | Film of poly(ethylene terephthalate), of a thickness of 500 µm (± 25 µm) | 0 |
| 0767 | ex 3920 62 90 40 | Strips of poly(ethylene terephthalate), covered on both sides with a layer of chemically modified polyester, of a width not exceeding 16 mm and a thickness of 0,5 mm or more but not exceeding 2 mm, having a tensile strength at break of 0,7 GPa or more (as determined by the ASTM D 638 method) | 0 |
| 0770 | ex 3920 69 00 20 | Film of poly(ethylene naphthalene-2,6-dicarboxylate), of a thickness of 0,6 µm or more but not exceeding 10 µm or 82 µm or more but not exceeding 88 µm | 0 |
| 0771 | ex 3920 69 00 40 | Iridescent film of polyester and poly(methyl methacrylate) | 0 |
| 0772 | ex 3920 69 00 50 | Polycondensation product of terephthalic acid with a mixture of cyclohex-1,4-ylenedimethanol and ethane-1,2-diol, in the form of a film | 0 |
| 0773 | ex 3920 69 00 60 | Film of a copolymer of ethylene terephthalate and ethylene isophthalate, of a thickness not exceeding 2 µm | 0 |
| 0774 | ex 3920 91 00 91 | Poly(vinyl butyral) film having a graduated coloured band | 3 |
| 0775 | ex 3920 91 00 92 | Plasticized film of polyvinyl butyral, containing by weight: <ul style="list-style-type: none"> – either 14,5 % or more but not more than 17,5 % of dihexyl adipate, – or 14,5 % or more but not more than 28,5 % of dibutyl sebacate | 0 |
| 0776 | ex 3920 91 00 93 | Film of poly(ethylene terephthalate), metallised on one or both sides, or laminated film of poly(ethylene terephthalate) films, metallised on the external sides only, and having the following characteristics: <ul style="list-style-type: none"> – a visible light transmission of 50 % or more, – coated on both sides with a layer of poly(vinyl butyral) but not coated with an adhesive or any other material except poly(vinyl butyral), – a total thickness not exceeding 0,2 mm without taking the presence of poly(vinyl butyral) into account, for use in the manufacture of heat-reflecting laminated glass (a) | 0 |
| 0777 | ex 3920 99 28 10 | Reflecting sheet of metallised polyurethane, containing glass beads, coated with a hot-melt adhesive layer, covered on one or both sides with a release sheet, in rolls of a width of 1 020 mm (± 20 mm), for slitting into safety clothing reflecting strip (a) | 0 |
| 0778 | ex 3920 99 28 30 ex 3921 90 55 10 ex 7410 21 00 30 | Film of polyimide, not containing epoxyde resin and/or glass fibres,: <ul style="list-style-type: none"> – metallized by sputtering with copper on one side or on both sides, – metallized by sputtering with copper and plated on one side or on both sides with refined copper or – covered on one side or on both sides with a copper foil | 0 |
| 0779 | 3920 99 53 ex 3920 99 59 55 | Ion-exchange membranes of fluorinated plastic material | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--------------------|--|-----------------------------------|
| 0781 | ex 3920 99 59 20 | Film entirely of poly(vinyl alcohol), of a thickness not exceeding 1 mm and containing by weight: – 2 % or less of unhydrolysed acetate groups evaluated as vinyl acetate and – 5 % or more but not more than 25 % of glycerol as plasticizer, for the manufacture of roof-windows (a) | 0 |
| 0782 | ex 3920 99 59 25 | Poly(1-chlorotrifluoroethylene) film | 0 |
| 0783 | ex 3920 99 59 30 | Film and sheet of a copolymer of ethylene with chlorotrifluoroethylene, of a thickness of 12 µm or more but not exceeding 400 µm | 0 |
| 0784 | ex 3920 99 59 35 | Film entirely of poly(vinyl alcohol), of a thickness not exceeding 1 mm and of a width of 2,20 m or more, with an extension at break, in the transverse direction, of 350 % or more | 0 |
| 0785 | ex 3920 99 59 40 | Biaxially-oriented film of poly(vinyl alcohol), coated on both sides, of a total thickness of less than 1 mm | 0 |
| 0786 | ex 3920 99 59 45 | Iridescent film of polyester, polyethylene and an ethylene-vinyl acetate copolymer | 0 |
| 0787 | ex 3920 99 59 50 | Polytetrafluoroethylene film, non-microporous, in the form of rolls, of a thickness of 0,019 mm or more but not exceeding 0,14 mm, impermeable to water vapour | 0 |
| 0780 | ex 3920 99 59 60 | Film of a vinyl alcohol copolymer, soluble in cold water, of a thickness of 34 µm or more but not exceeding 90 µm, a tensile strength at break of $3,28 \cdot 10^7$ ($\pm 1,21 \cdot 10^7$) N/m ² and an elongation at break of (675 ± 225) % | 0 |
| 0788 | ex 3921 14 00 10 | Cellular film of regenerated cellulose, of a thickness not exceeding 350 µm | 0 |
| 0790 | ex 3921 19 00 91 | Microporous polypropylene film of a thickness not exceeding 100 µm | 0 |
| 0791 | ex 3921 19 00 92 | Microporous film consisting of mixtures of cellulose acetate and cellulose nitrate, of a thickness not exceeding 200 µm | 0 |
| 0792 | ex 3921 19 00 93 | Strip of microporous polytetrafluoroethylene on a support of a non-woven, for use in the manufacture of filters for kidney dialysis equipment (a) | 0 |
| 0723 | ex 3921 19 00 94 | Polyethylene film, of a thickness of 16 µm or more but not exceeding 24 µm, having: – a weight of 19 g/m ² (± 2 g/m ²), – a water vapour transmission rate of 5 000 g/m ² or more but not exceeding 30 000 g/m ² per day (as determined by the ASTM D 6701-01 method), – an elongation in the transverse direction of 25 % or more at a load of 500 g or less, – an elongation in the machine direction of 50 % or more but not exceeding 100 % (as determined by the ASTM D 882-91 method), for use in the manufacture of napkins and napkin liners for babies and similar sanitary articles (a) | 0 |
| 0789 | ex 3921 19 00 95 | Film of polyethersulfone, of a thickness not exceeding 200 µm | 0 |
| 0793 | ex 3921 90 19 35 | Composite plate of polycarbonate and poly(butylene terephthalate), reinforced with glass fibres | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--|--|-----------------------------------|
| 0794 | ex 3921 90 19 45 | Composite plate of poly(ethylene terephthalate) or of poly(butylene terephthalate), reinforced with glass fibres | 0 |
| 0795 | ex 3921 90 60 91 ex 5407 71 00 20 ex 5903 90 99 10 | Woven polytetrafluoroethylene fabric, coated or covered with a copolymer of tetrafluoroethylene and trifluoroethylene having perfluorinated alkoxy side-chains ending in carboxylic acid or sulfonic acid groups, whether or not in the potassium or sodium salt form | 0 |
| 0796 | ex 3921 90 60 92 | Reinforced polypropylene sheet, of a thickness of 0,91 mm or more but not exceeding 1,12 mm, having a breaking strength of 890 N or more but not exceeding 1 500 N (as determined by the ASTM D 751 method), in rolls of a width of 3,81 m | 0 |
| 0733 | ex 3921 90 60 93 | Film of a gloss level of 30 or more but not exceeding 60, measured at an angle of 60 ° using a gloss meter (as determined by the ISO 2813:2000 method), consisting of a layer of poly(ethylene terephthalate) and a layer of colored poly(vinyl chloride), joined by a metalized adhesive coating, for coating panels and doors of a kind used in the manufacture of domestic appliances (a) | 0 |
| 0797 | ex 3923 10 00 10 | Boxes of a kind used for the transport and stocking of rigid magnetic discs, fitted with slots to embody 25 rigid magnetic discs of a diameter of less than 100 mm, of exterior dimensions not exceeding 110 × 110 × 200 mm | 0 |
| 0798 | ex 3926 90 91 20 | Reflecting sheeting or tape, consisting of a facing-strip of poly(vinyl chloride) embossed in a regular pyramidal pattern, heat-sealed in parallel lines or in a grid-pattern to a backing-strip of plastic material, or of knitted or woven fabric covered on one side with plastic material | 0 |
| 0799 | ex 3926 90 99 10 | Microspheres of polymer of divinylbenzene, of a diameter of 4,5 µm or more but not exceeding 80 µm | 0 |
| 0800 | ex 3926 90 99 20 | Tape pad, for use in the manufacture of goods of heading No 8523 (a) | 0 |
| 0801 | ex 3926 90 99 30 | Guide pin and pole, for use in the manufacture of goods of subheadings 8523 11 00, 8523 12 00 and 8523 13 00 (a) | 0 |
| 0802 | ex 3926 90 99 35 | Microspheres of polyalkylsiloxane, on which are covalently bonded organic compounds, of a diameter of 1 µm or more but not exceeding 30 µm | 0 |
| 0803 | ex 3926 90 99 55 | Flat product of polyethylene, perforated in opposing directions, of a thickness of 600 µm or more but not exceeding 1 200 µm and of a weight of 21 g/m ² or more but not exceeding 42 g/m ² | 0 |
| 0804 | ex 4007 00 00 10 | Siliconated vulcanised rubber thread and cord | 0 |
| 0807 | ex 4008 11 00 10 | Blocks or sheets of cellular vulcanised rubber of modified ethylene-propylene-diene (EPDM) blended with chloroprene, which satisfy the Underwriters Laboratories Flammability Standard UL94HF-1 | 0 |
| 0808 | ex 4016 99 88 10 | Soft rubber sealing stoppers for the manufacture of electrolytic capacitors (a) | 0 |
| 0809 | 4105 10 10 4105 10 90 4105 30 91 4105 30 99 | Sheep or lamb skin leather, without wool on, tanned or retanned but not further prepared, whether or not split, other than leather of heading No 4114 | 0 |
| 0810 | 4106 21 10 4106 21 90 4106 22 90 | Goat or kid skin leather, without hair on, tanned or retanned but not further prepared, whether or not split, other than leather of heading No 4114 | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--|--|-----------------------------------|
| 0811 | 4106 31 10 4106 31 90 4106 32 10 4106 32 90 4106 40 90 4106 91 00 4106 92 00 | Leather of other animals, without hair on, not further prepared than tanned, other than leather of heading No 4114 | 0 |
| 0812 | ex 4802 54 90 10 ex 4802 55 00 10 ex 4802 57 00 10 ex 4802 61 90 10 ex 4802 69 90 10 | Overlay paper, of a width of more than 110 cm and containing by weight more than 5 % of corundum | 0 |
| 0813 | ex 4803 00 90 10 ex 5603 13 90 80 ex 5603 93 90 30 | Polyethylene non-woven, covered on both sides with a non-woven of polypropylene and wood pulp, containing by weight 45 % or more but not more than 56 % of wood pulp, of a weight of 70 g/m ² or more but not exceeding 90 g/m ² , in rolls, for use in the manufacture of wet wipes (a) | 0 |
| 0814 | ex 4805 91 99 20 | Paper, in cross-wise rewinded spiral rolls, of a weight of less than 150 g/m ² and of a thickness not exceeding 0,05 mm, for the manufacture of electrolytic capacitors (a) | 0 |
| 0815 | ex 4810 99 10 10 | Bleached paper coated with kaolin, for use in the manufacture of tampons applicators (a) | 0 |
| 0816 | ex 4811 41 10 10 | Impregnated paper coated or covered with a pressure-sensitive self-adhesive layer, the whole: <ul style="list-style-type: none"> – of a tensile of 2 700 N/m or more but not exceeding 3 700 N/m in the machine direction (as determined by the EN ISO 1924-2 and ISO 3781 methods), – of a stretch factor of 1,5 % or more but not exceeding 3,0 % in the machine direction (as determined by the EN ISO 1924-2 and ISO 3781 methods) | 0 |
| 0817 | ex 4811 51 00 10 | Paper coated with acrylic polymer, with a gloss of 75 or more but not exceeding 90 (as determined by the Hunter method), of a weight of 160 g/m ² or more but not exceeding 180 g/m ² , for use as casting paper in the manufacture of films of plastics (a) | 0 |
| 0818 | ex 4811 59 00 10 | Kraft paper impregnated with an acrylic polymer, of a weight of 83 g/m ² or more but not exceeding 87 g/m ² or 176 g/m ² or more but not exceeding 216 g/m ² | 0 |
| 0819 | ex 4823 90 50 10 | Paper coated with dye retention and dye releasing agents used to produce a positive image, for the manufacture of goods of subheading 3701 20 00 (a) | 0 |
| 0820 | ex 4823 90 50 20 | Honeycomb filter, of paper impregnated with carbon, of a thickness greater than 10 mm but not exceeding 30 mm | 0 |
| 0821 | ex 4823 90 90 12 | Strips of paper glued to one another to form a honeycomb of a height not exceeding 13 cm, for agricultural purposes (a) | 0 |
| 0822 | ex 4911 99 00 10 | Polyester film, partially coated with a magnetic metal layer showing a regular repeating logo or motif, for the manufacture of security threads (a) | 0 |
| 0823 | ex 5004 00 10 10 ex 5004 00 90 10 | Yarn spun entirely from silk, not put up for retail sale | 2.5 |
| 0824 | ex 5005 00 10 10 ex 5005 00 90 10 | Yarn spun entirely from silk waste (noil), not put up for retail sale | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--|--|-----------------------------------|
| 0825 | 5208 11 10 | Fabrics for the manufacture of bandages, dressings and medical gauzes | 5.2 |
| 0826 | ex 5402 41 00 10 | Polyamide yarn, not textured, untwisted or with a twist not exceeding 22 turns per metre, of crimpable bicomponent filaments consisting of poly(hexamethylene adipamide) with a copolyamide, for the manufacture of: <ul style="list-style-type: none"> – knee-length stockings of subheadings 6115 20 11 and 6115 93 30, – women's stockings of subheadings 6115 20 19 and 6115 93 91 or – panty hose (tights) of subheading 6115 11 00 (a) | 0 |
| 0827 | ex 5402 41 00 20 | Yarn of synthetic textile fibres solely of aromatic polyamides obtained by the polycondensation of <i>m</i> -phenylenediamine and isophthalic acid | 0 |
| 0828 | ex 5402 43 00 20 | Synthetic bicomponent filament yarn, not textured, untwisted, measuring 1 650 decitex, consisting of 110 filaments each having a core of poly(ethylene terephthalate) and a skin of polyamide-6, containing by weight 75 % or more but not exceeding 77 % of poly(ethylene terephthalate), for use in the manufacture of roofings (a) | 0 |
| 0829 | ex 5402 49 99 10 ex 5402 69 90 20 | Multifilaments yarn of polytetrafluoroethylene | 0 |
| 0830 | ex 5402 49 99 30 | Yarn of a copolymer of glycollic acid with lactic acid, for the manufacture of surgical sutures (a) | 0 |
| 0831 | ex 5402 49 99 50 ex 5402 59 90 20 ex 5402 69 90 40 | Non-textured filament yarn of poly(vinyl alcohol) | 0 |
| 0832 | ex 5402 49 99 60 ex 5402 69 90 10 | Yarn wholly of poly(glycollic acid) | 0 |
| 0833 | ex 5402 49 99 70 | Synthetic filament yarn, single, containing by weight 85 % or more of acrylonitrile, in the form of a wick containing 1 000 continuous filaments or more but not more than 25 000 continuous filaments, of a weight per metre of 0,12 g or more but not exceeding 3,75 g and of a length of 100 m or more, for the manufacture of carbon-fibre yarn (a) | 0 |
| 0834 | ex 5402 49 99 80 | Polyethylene filament yarn, untwisted, of either 55, 110, 165 or 1 760 decitex, for the manufacture of goods of heading No 5607 (a) | 0 |
| 0835 | ex 5402 49 99 85 | Synthetic filament yarn, single, untwisted, wholly of poly(thio-1,4-phenylene) | 0 |
| 0836 | ex 5404 10 90 10 | Monofilament of polytetrafluoroethylene | 0 |
| 0837 | ex 5404 10 90 20 | Monofilament of poly(1,4-dioxanone) | 0 |
| 0838 | ex 5404 10 90 30 | Monofilament of a copolymer of 1,3-dioxan-2-one with 1,4-dioxan-2,5-dione, for the manufacture of surgical sutures (a) | 0 |
| 0839 | ex 5404 10 90 40 | Monofilaments of a stabilised blend of polyester with polyurethane, of 67 decitex or more and of which no cross-sectional dimension exceeds 1 mm | 0 |
| 0840 | ex 5404 90 90 20 | Strip of polyimide | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--|---|-----------------------------------|
| 0841 | ex 5407 71 00 10 | Woven fabrics of poly(vinyl alcohol) fibres, for machine embroidery | 0 |
| 0842 | ex 5501 90 90 10 | Poly(vinyl alcohol) tow | 0 |
| 0843 | ex 5503 20 00 10 | Polyester staple fibres, loaded with zeolite impregnated with a mixture of salts of copper and silver or of salts of zinc and silver | 4 |
| 0844 | ex 5503 90 10 10 ex 5503 90 90 30 | Acetalized, multicomponent spun fibres with a matrix fibril structure, consisting of emulsion-polymerized poly(vinyl alcohol) and poly(vinyl chloride) | 0 |
| 0845 | ex 5503 90 90 10 | Textile fibres of polytetrafluoroethylene | 4 |
| 0846 | ex 5503 90 90 20 ex 5506 90 90 10 ex 5601 30 00 10 | Poly(vinyl alcohol) fibres, whether or not acetalized | 0 |
| 0847 | ex 5503 90 90 40 | Fibres wholly of poly(thio-1,4-phenylene) | 0 |
| 0849 | ex 5601 30 00 20 | Polyester fibres, measuring 0,56 decitex, of a length of 3 mm or more but not exceeding 5 mm | 0 |
| 0850 | ex 5601 30 00 30 | Acrylic fibres, measuring 0,11 and 0,56 decitex, of a length of 3 mm or more but not exceeding 5 mm | 0 |
| 0851 | ex 5603 11 10 10 ex 5603 11 90 10 ex 5603 12 10 10 ex 5603 12 90 10 ex 5603 91 10 10 ex 5603 91 90 10 ex 5603 92 10 10 ex 5603 92 90 10 | Poly(vinyl alcohol) non-wovens, in the piece or cut into rectangles: – of a thickness of 200 µm or more but not exceeding 280 µm and – of a weight of 20 g/m ² or more but not exceeding 50 g/m ² | 0 |
| 0852 | ex 5603 11 10 20 ex 5603 11 90 20 ex 5603 12 10 20 ex 5603 12 90 50 | Non-wovens, containing spunbonded fibres of polypropylene or of polypropylene and polyethylene, for the manufacture of napkins and napkin liners for babies and similar sanitary articles (a) | 0 |
| 0853 | ex 5603 12 90 30 ex 5603 13 90 30 ex 5603 14 90 10 ex 5603 92 90 60 ex 5603 93 90 40 ex 5603 94 90 30 | Non-wovens of aromatic polyamide fibres obtained by polycondensation of <i>m</i> -phenylenediamine and isophthalic acid, in the piece or cut into rectangles | 0 |
| 0854 | ex 5603 12 90 60 ex 5603 13 90 60 | Non-woven of spunbonded polyethylene, of a weight of more than 60 g/m ² but not exceeding 80 g/m ² and an air resistance (Gurley) of 8 s or more but not exceeding 36 s (as determined by the ISO 5636/5 method) | 0 |
| 0855 | ex 5603 12 90 70 ex 5603 13 90 70 ex 5603 92 90 40 ex 5603 93 90 10 | Non-wovens of polypropylene, consisting of a meltblown layer, laminated on each side with spunbonded filaments of polypropylene, of a thickness not exceeding 550 µm and of a weight not exceeding 80 g/m ² , in the piece or simply cut into squares or rectangles, not impregnated | 0 |
| 0856 | ex 5603 13 90 40 ex 5603 14 90 20 | Non-wovens consisting of a central layer of polycarbonate fibres, laminated on each side with spunbonded filaments of polyester, of a weight of more than 130 g/m ² but not exceeding 200 g/m ² | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--|--|-----------------------------------|
| 0857 | ex 5603 92 90 20 ex 5603 93 90 20 | Non-wovens consisting of a meltblown central layer of a thermoplastic elastomer laminated on each side with spunbonded filaments of polypropylene | 0 |
| 0858 | ex 5603 92 90 50 | Non-wovens of staple fibres, in rolls, of a width of 78 mm or more but not exceeding 252 mm, for the manufacture of floppy discs (a) | 0 |
| 0859 | ex 5603 94 90 20 | Acrylic fibre rods, having a length of not more than 50 cm, for the manufacture of pen tips (a) | 0 |
| 0860 | ex 5607 50 90 10 | Twine, unsterilised, wholly of poly(glycollic acid), plaited or braided, with an inner core, for the manufacture of surgical sutures (a) | 0 |
| 0861 | ex 5903 10 90 10 ex 5903 20 90 10 ex 5903 90 99 20 | Knitted or woven fabrics, coated or covered on one side with artificial plastic material in which are embedded microspheres | 0 |
| 0862 | ex 5903 20 90 20 | Tape of polyester fabric laminated with a metallised polyurethane film containing glass beads, for use in the manufacture of marine life-saving equipment (a) | 0 |
| 0863 | ex 5907 00 90 10 | Textile fabrics, coated with adhesive in which are embedded spheres of a diameter not exceeding 75 µm | 0 |
| 0864 | ex 5911 10 00 10 | Needle-punched synthetic-fibre felts, not containing polyester, whether or not containing catalytic particles entrapped within the synthetic fibres, coated or covered on one side with polytetrafluoroethylene film, for the manufacture of filtration products (a) | 0 |
| 0865 | ex 5911 90 90 10 | Yarn and strip of impregnated polytetrafluoroethylene, whether or not oiled or graphited | 0 |
| 0866 | ex 5911 90 90 30 ex 8421 99 00 92 | Parts of equipment for the purification of water by reverse osmosis, consisting essentially of plastic-based membranes, supported internally by woven or non-woven textile materials which are wound round a perforated tube, and enclosed in a cylindrical plastic casing of a wall-thickness not exceeding 4 mm, whether or not housed in a cylinder of a wall-thickness of 5 mm or more | 0 |
| 0867 | 6305 10 10 | Sacks and bags, of a kind used for the packing of goods, used, of jute or of other textile bast fibres of heading No 5303 | 0 |
| 0868 | ex 6305 90 00 10 ex 6305 90 00 91 | Sacks and bags, of a kind used for the packing of goods, used, of flax or of sisal | 0 |
| 0869 | ex 6307 90 10 10 | Sterile mesh-implant, consisting of a knitted fabric of polypropylene monofilaments, with rounded edges, in forms covered by a square of dimensions not exceeding 31 × 31 cm | 0 |
| 0870 | ex 6813 90 90 10 | Friction material, of a thickness of less than 20 mm, not mounted, for the manufacture of friction components of a kind used in automatic transmissions and clutches (a) | 0 |
| 0871 | ex 6903 20 90 10 | Yarn of continuous ceramic filaments, each filament containing by weight: <ul style="list-style-type: none"> – 12 % or more of diboron trioxide, – 26 % or less of silicon dioxide and – 60 % or more of dialuminium trioxide | 0 |
| 0872 | ex 6903 90 80 10 ex 6909 19 00 40 | Beryllium oxide, of a purity by weight of more than 99 %, in the form of blanks, bars, blocks or plates | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--------------------|--|-----------------------------------|
| 0873 | ex 6903 90 80 20 | Silicon carbide reactor tubes and holders, of a kind used for insertion into diffusion and oxidation furnaces for production of semiconductor materials | 0 |
| 0874 | ex 6909 12 00 20 | Plate, of dialuminium trioxide and titanium carbide, of dimensions not exceeding 48 × 48 mm, or of a diameter not exceeding 125 mm, for the manufacture of magnetic heads (a) | 0 |
| 0875 | ex 6909 19 00 30 | Supports for catalysts, consisting of porous cordierite or mullite ceramic pieces, of an overall volume not exceeding 65 l, having, per cm ² of the cross-section, not less than one continuous channel which may be open at both ends or stopped at one end | 0 |
| 0876 | ex 7006 00 90 10 | Glass plate, coated on one side with chromium and/or with a mixture of diindium trioxide and tin dioxide, of dimensions of 260 × 320 mm or more but not exceeding 400 × 400 mm, of a thickness not exceeding 1,2 mm, for the manufacture of liquid crystal displays (a) | 0 |
| 0877 | ex 7006 00 90 20 | Colour filter, consisting of a glass plate with red, blue and green pixels, having a total thickness of 1,1 mm (± 0,1 mm) and exterior dimensions of 320 × 352 mm or more but not exceeding 320 × 400 mm, for the manufacture of liquid crystal displays (a) | 0 |
| 0878 | ex 7006 00 90 30 | Glass plate, uncoated, of dimensions of 320 × 352 mm or more but not exceeding 320 × 400 mm, of a thickness of 0,6 mm or more but not exceeding 1,2 mm, for the manufacture of liquid crystal displays (a) | 0 |
| 0879 | ex 7006 00 90 40 | Disk of glass, with a hole in the centre, with the edges having been worked, of a total thickness not exceeding 1,5 mm | 0 |
| 0880 | ex 7011 10 00 10 | Glass lenses with a stippled front refractor or with a front refractor composed of prismatic elements, with an external diameter of more than 121 mm but not exceeding 125 mm | 0 |
| 0881 | ex 7011 10 00 20 | Parabolic glass cup, with an external diameter of more than 121 mm but not exceeding 125 mm | 0 |
| 0882 | ex 7011 20 00 40 | Glass face-plate: <ul style="list-style-type: none"> – with a diagonal measurement of 366,4 mm (± 1,5 mm) and of dimensions of 246,4 × 315,4 mm (± 1,5 mm), – with a diagonal measurement of 391 mm (± 1,5 mm) and of dimensions of 261,4 × 326,8 mm (± 1,5 mm), – with a diagonal measurement of 442 mm (± 1,5 mm) and of dimensions of 293,4 × 369,2 mm (± 1,5 mm), – with a diagonal measurement of 544,5 mm (± 1,6 mm) and of dimensions of 358 × 454 mm (± 1,6 mm), having a cylindrical curvature, – with a diagonal measurement of 570,5 mm (± 1,6 mm) and of dimensions of 360 × 486 mm (± 1,6 mm), – with a diagonal measurement of 629,8 mm (± 3 mm) and of dimensions of 406,5 × 519 mm (± 2 mm), having a cylindrical curvature, or – with a diagonal measurement of 753 mm (± 1,6 mm) and of dimensions of 471 × 640 mm (± 1,6 mm), and with a raised edge, for the manufacture of colour cathode-ray tubes (a) | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--------------------------------------|---|-----------------------------------|
| 0883 | ex 7011 20 00 75 | Glass face-plate: <ul style="list-style-type: none"> – with a diagonal measurement of 604,5 mm (\pm 3 mm) and of dimensions of 340 \times 541 mm (\pm 2 mm), – with a diagonal measurement of 639,3 mm (\pm 3 mm) and of dimensions of 413,6 \times 527 mm (\pm 2 mm), – with a diagonal measurement of 708 mm (\pm 3 mm) and of dimensions of 404 \times 633 mm (\pm 2 mm), – with a diagonal measurement of 723 mm (\pm 3 mm) and of dimensions of 477 \times 602 mm (\pm 2 mm), or – with a diagonal measurement of 812,8 mm (\pm 3 mm) and of dimensions of 463,8 \times 725,5 mm (\pm 2 mm), having a cylindrical curvature, for the manufacture of colour cathode-ray tubes (a) | 0 |
| 0884 | ex 7011 20 00 80 | Glass bulb for monochrome cathode-ray tube, of a diagonal measurement of 3,8 cm or more but not exceeding 51 cm and a nominal neck diameter of 13 mm, 20 mm, 29 mm or 37 mm | 0 |
| 0885 | ex 7014 00 00 10 | Optical elements of glass (other than those of heading No 7015), not optically worked, other than signalling glassware | 0 |
| 0889 | ex 7019 12 00 10 | Rovings, measuring 2 600 tex or more but not more than 3 300 tex and of a loss on ignition of 4 % or more but not exceeding 8 % by weight (as determined by the ASTM D 2584-94 method) | 0 |
| 0890 | ex 7019 12 00 15 | Rovings, measuring 650 tex or more but not more than 2 500 tex, coated with a layer of polyurethane whether or not mixed with other materials | 0 |
| 0891 | ex 7019 12 00 30 | Rovings, measuring 1 693 tex (\pm 10%), coated with a layer of styrene-butadiene rubber (SBR) | 0 |
| 0892 | ex 7019 12 00 40 | Rovings, measuring 2 040 tex (\pm 10 %), coated with carbon | 0 |
| 0886 | ex 7019 12 00 50 | Rovings, measuring 392 tex or more but not more than 2 884 tex, coated with a layer of an acrylic copolymer | 0 |
| 0887 | ex 7019 12 00 60 | Rovings, measuring 517 tex or more but not more than 3 569 tex, coated with a layer of paraffin | 0 |
| 0888 | ex 7019 12 00 70 | Rovings, measuring 417 tex or more but not more than 3 180 tex, coated with a layer of poly(sodium acrylate) and poly(acrylic acid) | 0 |
| 0893 | ex 7019 19 10 10 | Yarn of 33 tex or a multiple thereof, \pm 7,5 %, obtained from continuous spun-glass filaments of a nominal diameter of 3,5 μ m or of 4,5 μ m, in which filaments of a diameter of 3 μ m or more but not exceeding 5,2 μ m predominate, other than those treated so as to improve their adhesion to elastomers | 0 |
| 0894 | ex 7019 19 10 30 | Yarn of 22 tex \pm 7,5 %, obtained from continuous spun-glass filaments of a nominal diameter of 5 μ m, in which filaments of a diameter of 4,2 μ m or more but not exceeding 5,8 μ m predominate | 0 |
| 0895 | ex 7019 19 10 40 | Yarn of 33, 34 or 51 tex or a multiple thereof, \pm 7,5 %, obtained from continuous spun-glass filaments of a nominal diameter of 6 μ m, in which filaments of a diameter of 5,1 μ m or more but not exceeding 6,9 μ m predominate | 0 |
| 0896 | ex 7019 32 00 10 ex 7019 39 00 10 | Non-woven product of non-textile glass fibre, for the manufacture of air-filters or of air-filtration products (a) | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--------------------------------------|---|-----------------------------------|
| 0897 | ex 7019 90 10 10 | Non-textile glass fibres in which fibres of a diameter of less than 3,5 µm predominate | 0 |
| 0898 | ex 7019 90 10 20 | Non-textile E-glass fibres, of a length not exceeding 3 mm and a diameter of 5 µm, for the manufacture of catalysts for the purification of smokes (a) | 0 |
| 0899 | ex 7116 20 90 10 | Disc of silicon on sapphire | 0 |
| 0900 | 7202 50 00 | Ferro-silico-chromium | 0 |
| 0901 | ex 7202 99 80 10 | Ferro-silicon, nitrided, containing by weight 55 % or more of silicon and 25 % or more of nitrogen | 0 |
| 0902 | ex 7212 50 91 10 | Perforated steel strip, plated or coated with nickel, of a width of 140 mm or more but not exceeding 400 mm and a thickness of 40 µm or more but not exceeding 140 µm | 0 |
| 0903 | ex 7212 50 99 10 | Cold-rolled steel, coated on both sides with a nickel-zinc layer, in the form of strip of a width of 40,15 (± 0,08) mm and a thickness of 0,3 (± 0,01) mm, containing by weight: <ul style="list-style-type: none"> – not more than 0,1 % of carbon, – not more than 0,04 % of phosphorus, – not more than 0,05 % of sulfur and – 0,2 % or more but not more than 0,5 % of manganese | 0 |
| 0904 | ex 7306 30 29 91 | Non-alloy steel precision tube, welded and cold finished, of an external diameter exceeding 160 mm and a wall thickness exceeding 2 mm | 0 |
| 0905 | ex 7409 19 00 10 | Sheet or plate of polytetrafluoroethylene, with aluminium oxide or titanium dioxide as a filler or reinforced with glass-fibre fabric, laminated on both sides with copper foil | 0 |
| 0906 | ex 7410 21 00 10 | Sheet or plate of polytetrafluoroethylene, containing aluminium oxide or titanium dioxide as filler or reinforced with glass-fibre fabric, covered on both sides with copper foil | 0 |
| 0907 | ex 7419 99 00 91 ex 7616 99 90 60 | Disc (target) with deposition material, consisting of molybdenum silicide: <ul style="list-style-type: none"> – containing 1 mg/kg or less of sodium and – mounted on a copper or aluminium support | 0 |
| 0908 | ex 7419 99 00 92 ex 7616 99 90 70 | Disc (target) with deposition material, of tungsten or an alloy containing by weight 90 % of tungsten and 10 % of titanium: <ul style="list-style-type: none"> – containing 100 µg/kg or less of sodium and – mounted on a copper or aluminium support | 0 |
| 0909 | ex 7419 99 00 93 ex 7616 99 90 80 | Disc (target) with deposition material, of titanium: <ul style="list-style-type: none"> – containing 50 µg/kg or less of sodium and – mounted on a copper or aluminium support | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--------------------------------------|--|-----------------------------------|
| 0910 | ex 7605 19 00 10 | Not alloyed aluminium wire, of a diameter of 2 mm or more but not exceeding 6 mm, covered with a layer of copper of a thickness of 0,032 mm or more but not exceeding 0,117 mm | 0 |
| 0911 | ex 7606 11 91 20 ex 7606 11 93 20 | Strip with depth-etching, of band-anodic oxidation treated aluminium of a purity by weight of 99,9 % and a thickness of less than 3 mm, for incorporation in bodies for motor vehicles (a) | 0 |
| 0912 | ex 7613 00 00 20 ex 8708 99 98 10 | Aluminium container, seamless, for compressed natural gas or compressed hydrogen, wholly embedded in an overwrap of epoxy-carbon fibres composite, of a capacity of 172 l (\pm 10 %) and an unfilled weight not exceeding 64 kg | 0 |
| 0913 | ex 7616 99 90 40 | Discs of aluminium alloy, coated or covered on both sides with a nickel-phosphorus layer, having a total thickness not exceeding 3,02 mm | 0 |
| 0914 | ex 7616 99 90 50 | Discs of aluminium alloy, of a thickness not exceeding 0,84 mm, for the manufacture of goods of subheading 8523 20 10 (a) | 0 |
| 0915 | ex 7905 00 00 10 | Plate of an alloy of zinc, ground and polished on one surface and coated with an epoxide resin on the other surface, of rectangular or square shape, of a length of 300 mm or more but not exceeding 2 000 mm and of a width of 300 mm or more but not exceeding 1 000 mm, and containing: <ul style="list-style-type: none"> – 10 mg/kg or less of iron, – 10 mg/kg or less of lead, – 700 mg/kg or more but not more than 900 mg/kg of aluminium and – 500 mg/kg or more but not more than 900 mg/kg of magnesium, for the manufacture of sensitised printing plates (a) | 0 |
| 0916 | ex 8103 90 90 10 | Welded tube solely of tantalum, or solely of an alloy of tantalum with tungsten containing by weight 3,5 % or less of tungsten | 0 |
| 0917 | ex 8104 11 00 30 | Unwrought magnesium, of a purity by weight of 99,95 % or more, in the form of ingots, for the manufacture of zirconium sponge or elements used in the nuclear industry (a) | 0 |
| 0918 | ex 8104 90 00 10 | Ground and polished magnesium sheets, of dimensions not exceeding 1 500 \times 2 000 mm, coated on one side with an epoxy resin insensitive to light | 0 |
| 0919 | ex 8104 90 00 20 | Sections, of extruded magnesium, of a length of 800 mm or more but not exceeding 2 900 mm and a width of 15 mm or more but not exceeding 70 mm | 0 |
| 0920 | ex 8108 20 00 10 | Titanium sponge | 0 |
| 0921 | 8108 30 00 | Waste and scrap of titanium | 0 |
| 0922 | ex 8108 90 70 20 | Welded titanium tubes, of an external diameter of 19,0 (\pm 0,1) mm, having an external structure of 36 fins per 2,54 cm, for use in the manufacture of refrigerant condensers (a) | 0 |
| 0923 | ex 8109 20 00 10 | Non-alloy zirconium, in the form of ingots, containing by weight more than 0,01 % of hafnium, for use in the manufacture of tubes for the chemical industry (a) | 0 |
| 0924 | ex 8110 10 00 10 | Antimony in the form of ingots | 0 |
| 0925 | ex 8112 19 00 10 | Beryllium, of a purity by weight of 94 % or more, in the form of bars, plates and sheets | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|--------|--------------------------------------|---|-----------------------------------|
| 0926 | ex 8112 99 30 10 | Alloy of niobium (columbium) and titanium, in the form of bars and rods | 0 |
| 0001 | ex 8407 31 00 10 | Two stroke internal combustion engine, of a cylinder capacity not exceeding 30 cm ³ for use in the manufacture of portable motorised scooters falling within subheading 8711 10 00 (a) | 0 |
| 0001bi | ex 8407 90 10 20 | Two-stroke internal combustion engines, having a cylinder capacity not exceeding 125 cm ³ , for the manufacture of lawnmowers of sub-heading 8433 11 (a) | 0 |
| 0002 | ex 8408 90 31 10 | Diesel engines of a power not exceeding 15 kW, with 2 or 3 cylinders, for use in the manufacture of vehicle mounted temperature control systems (a) | 0 |
| 0003 | ex 8408 90 33 10 | Diesel engines of a power not exceeding 30 kW, with 4 cylinders, for use in the manufacture of vehicle mounted temperature control systems (a) | 0 |
| 0004 | ex 8414 30 99 10 | Open shaft reciprocating compressor, for use in the manufacture of vehicle mounted temperature control systems (a) | 0 |
| 0005 | ex 8414 90 90 10 | Aluminium pistons, partially covered with polytetrafluoroethylene, for incorporation into compressors of air conditioning machines of motor vehicles (a) | 0 |
| 0006 | ex 8414 90 90 20 | Pressure-regulating system, for incorporation into compressors of air conditioning machines of motor vehicles (a) | 0 |
| 0007 | ex 8418 99 90 91 | Welded cooling micro-elements, of an alloy of aluminium, for the manufacture of condensers (a) | 0 |
| 0008 | ex 8419 19 00 10 | Heat accumulator for motor vehicles, of a coolant capacity of 4 l or more but not exceeding 10 l | 0 |
| 0009 | ex 8419 89 98 10 | Immersion-tube (coils) bundles, consisting of an assembly of plastic tubes terminating at each end in a honeycomb-structure (end-fitting) surrounded by a pipe-connector | 0 |
| 0010 | ex 8419 89 98 20 ex 8543 89 95 58 | Sputtering machines and apparatus, comprising disk handling equipment, for use in the manufacture of products falling within subheading 8523 20 10 (a) | 0 |
| 0011 | ex 8421 99 00 91 | Parts of equipment, for the purification of water by reverse osmosis, consisting of a bundle of hollow fibres of artificial plastic material with permeable walls, embedded in a block of artificial plastic material at one end and passing through a block of artificial plastic material at the other end, whether or not housed in a cylinder | 0 |
| 0012 | ex 8421 99 00 93 | Components of separators for the separation or purification of gases from gas mixtures, consisting of a bundle of permeable hollow fibres enclosed within a container, whether or not perforated, of an overall length of 300 mm or more but not exceeding 3 700 mm and a diameter not exceeding 500 mm | 0 |
| 0013 | ex 8421 99 00 95 | Parts of equipment for the filtration of magnetic dispersions, consisting essentially of nylon-6 fibres, enclosed in a plastic casing of a diameter of 70 mm (± 2 mm) and a length of 520 mm (± 5 mm) | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--|---|-----------------------------------|
| 0014 | ex 8422 30 00 10 ex 8479 89 98 70 | Machines and apparatus, other than injection moulding machines, for the manufacture of ink-jet printer cartridges (a) | 0 |
| 0015 | ex 8424 89 95 10 ex 8460 21 90 10 ex 8460 40 10 10 ex 8460 90 90 10 ex 8464 20 19 10 ex 8479 89 98 10 | Machines and apparatus providing automated lapping, polishing, grinding, cleaning or surface lubrication of disks, comprising disk handling equipment, for use in the manufacture of products falling within subheading 8523 20 10 (a) | 0 |
| 0016 | ex 8424 89 95 20 ex 8479 89 98 30 | Machines and apparatus providing automated cleaning or cleaning and drying of disks, by means of de-ionised water, ultra sonic waves, chemical solutions, heat or a combination of these processes, comprising disk handling equipment, for use in the manufacture of products falling within subheading 8523 20 10 (a) | 0 |
| 0017 | ex 8439 99 10 10 ex 8439 99 90 10 | Suction-roll shells, not drilled, in the form of alloy-steel tubes, of a length of 5 207 mm or more and an external diameter of 754 mm or more, for use in machinery for making paper or paperboard (a) | 0 |
| 0018 | ex 8454 30 10 10 | Casting machines for casting under pressure of metal alloys in thixotropic (semi-solid) form | 0 |
| 0019 | ex 8455 90 00 10 | Helical turn device for cold-rolling mill | 0 |
| 0020 | ex 8456 10 90 10 | Machine-tool operating by laser beam, for the cutting of slots on the surface of a cylindrical tube for use in the manufacture of endo-vascular prosthesis (so-called "stents") (a) | 0 |
| 0024 | ex 8460 90 90 20 ex 8463 90 00 10 ex 8479 89 98 20 | Machine-tool providing automated creation of a texture (a head landing zone) on the surface of disks by means of abrasion or exposure to laser beams, comprising disk handling equipment, for use in the manufacture of products falling within subheading 8523 20 10 (a) | 0 |
| 0025 | ex 8473 40 19 20 | Thermal printer head | 0 |
| 0026 | ex 8479 89 98 40 ex 8501 10 99 78 | Motor, whether or not mounted on a baseplate, for use in the manufacture of products falling within subheading 8525 20 91 or 8527 90 92 (a) | 0 |
| 0027 | ex 8481 80 59 10 | Air control valve, consisting of a stepping motor and a valve pintle, for the regulation of idle air flow in fuel injection engines | 0 |
| 0028 | ex 8483 10 80 10 | Integrally forged and roughly shaped generator and turbine shafts of a weight exceeding 215 tonnes | 0 |
| 0029 | ex 8501 10 99 54 | DC motor, brushless, with an external diameter not exceeding 25,4 mm, a rated speed of 2 260 (±15 %) or 5 420 (±15 %) rpm, a supply voltage of 1,5 or 3 V | 0 |
| 0030 | ex 8501 10 99 59 | DC stepping motor, with an angle of step of 1,8° (±0,09°), a holding torque of 0,156 Nm or more, a coupling flange the exterior dimensions of which do not exceed 43 × 43 mm, a chuck of a diameter of 4 mm (±0,1 mm), a two-phase winding and an output not exceeding 5 W | 0 |
| 0031 | ex 8501 10 99 73 | DC motor, whether or not mounted on a baseplate, for use in the manufacture of products falling within subheading 8471 70 53 (a) | 0 |
| 0032 | ex 8501 10 99 77 | DC motor, with brushes, with a typical running torque of 0,004 Nm (±0,001 Nm), with a coupling flange of a diameter of 32 mm (±0,5 mm) and a chuck of a diameter of 2 mm (±0,004 mm), with an internal rotor, a three-phase winding, a rated speed of 2 800 (±10 %) rpm and a supply voltage of 12 V (±15 %) | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--|--|-----------------------------------|
| 0033 | ex 8502 40 90 10 | Rotary converter, with a ferrite core, having coils with 2 or 6 windings and a diameter of 0,1 mm, connected to a flexible printed circuit | 0 |
| 0034 | ex 8503 00 91 31 ex 8503 00 99 32 | Rotor, at the innerside provided with one or two magnetic rings whether or not incorporated in a steel ring | 0 |
| 0035 | ex 8503 00 99 31 | Stamped collector of an electric motor, having an external diameter not exceeding 16 mm | 0 |
| 0036 | ex 8504 31 90 | [AC] transformer, [comprising a primary and a secondary coil] having an input voltage of 230-240 V and a rated frequency of 50 Hz, an output voltage of 2245 V (± 20 V), for use in the manufacture of goods of subheading 8516 50 00 (a) | 0 |
| 0037 | ex 8504 40 99 20 | Direct current to direct current converter | 0 |
| 0038 | ex 8504 40 99 30 | Static converter comprising a power switch with insulated-gate bipolar transistors (IGBTs), contained in a housing, for use in the manufacture of microwave ovens of subheading 8516 50 00 (a) | 0 |
| 0039 | ex 8504 50 80 30 | Inductor with an inductance not exceeding 62 mH | 0 |
| 0040 | ex 8504 50 80 40 | Multilayer monolithic inductors, contained in a housing of the SMD (surface mounted device) type the exterior dimensions of which do not exceed $1,8 \times 3,4$ mm, for use in the manufacture of products falling within subheading 8517 11 00, 8525 20 91 or 8527 90 92 (a) | 0 |
| 0041 | 8504 90 11 | Ferrite cores | 0 |
| 0042 | ex 8504 90 18 32 | Part of a rotary transformer, comprising a ferrite core provided with circular grooves with copper wire windings | 0 |
| 0043 | ex 8505 11 00 31 | Ferrite magnet having a remanence of 455 mT (± 15 mT) | 0 |
| 0044 | ex 8505 19 90 31 | Neodymium-ferro ring with an external diameter not exceeding 13 mm, an internal diameter not exceeding 9 mm | 0 |
| 0045 | ex 8505 90 10 91 | Solenoid with a plunger, operating at a nominal supply voltage of 24 V at a nominal DC of 0,08 A, for use in the manufacture of products falling within heading No 8517 (a) | 0 |
| 0046 | ex 8505 90 10 92 | Electro-mechanical throttle plate actuator for automotive engines | 0 |
| 0047 | ex 8506 50 90 10 | Lithium iodine single cell battery the dimensions of which do not exceed $9 \times 23 \times 45$ mm and a voltage not exceeding 2,8 V | 0 |
| 0048 | ex 8506 50 90 20 | Unit consisting of not more than 2 lithium batteries embedded in a socket for integrated circuits (battery-buffered socket), with not more than 32 connections and incorporating a control circuit | 0 |
| 0049 | ex 8506 50 90 30 | Lithium-iodine or lithium-silver vanadium oxide single cell battery of dimensions not exceeding $28 \times 45 \times 15$ mm and a capacity of not less than 1,05 Ah | 0 |
| 0050 | ex 8507 30 91 20 ex 8507 80 91 10 ex 8507 80 99 10 | Rectangular accumulator, with a length not exceeding 69 mm, a width not exceeding 36 mm and a thickness not exceeding 12 mm, for use in the manufacture of rechargeable batteries (a) | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--------------------|--|-----------------------------------|
| 0051 | ex 8507 30 91 30 | Cylindrical nickel-cadmium accumulator, with a length of 65,3 mm ($\pm 1,5$ mm) and a diameter of 14,5 mm (± 1 mm), having a nominal capacity of 1 000 mAh or more, for use in the manufacture of rechargeable batteries (a) | 0 |
| 0052 | ex 8507 80 91 80 | Cylindrical nickel-hydride accumulator, of a diameter not exceeding 14,5 mm, for the manufacture of rechargeable batteries (a) | 0 |
| 0053 | ex 8507 80 99 20 | Cylindrical lithium-ion accumulator, with a length of 64,6 mm or more and a diameter of 18,1 mm or more, having a nominal capacity of 1 200 mAh or more, for use in the manufacture of rechargeable batteries (a) | 0 |
| 0054 | ex 8516 90 00 31 | Dual diode, consisting of a power rectifying diode connected with a transformer protector diode through a wire, with a peak reverse power rate of 2 J or more, for use in the manufacture of products falling within subheading 8516 50 00 (a) | 0 |
| 0055 | ex 8518 29 80 20 | Loudspeaker having a power of 5 W and an impedance of 4 ohms, with a diameter not exceeding 50 mm, for use in the manufacture of portable phones (a) | 0 |
| 0056 | ex 8518 30 80 20 | Headphone and earphone for hearing aids, contained in a housing the exterior dimensions of which, excluding connecting points, do not exceed $5 \times 6 \times 8$ mm | 0 |
| 0057 | ex 8518 90 00 91 | Integrally cold-upsetted steel coreplate, in the form of a disk on one side provided with a cylinder, for use in the manufacture of loudspeakers (a) | 0 |
| 0058 | ex 8520 90 90 20 | Drive-unit capable of magneto-optical signal recording and optical signal reproducing, comprising at least an optical unit, DC motors and a printed circuit on which are mounted integrated circuits providing drive and signal processing functions for reading optical discs having an external diameter not exceeding 70 mm, not comprising circuits with amplification functions or power supply drive functions | 0 |
| 0059 | ex 8522 90 59 93 | Optical unit consisting of a laser diode with one photodiode, emitting light of a nominal wavelength of 780 nm, contained in a housing with a diameter of not more than 10 mm and a height of not more than 9 mm, with not more than 10 connections and bearing: <ul style="list-style-type: none"> – an identification marking consisting of or including (one of) the following combination(s): LDGU LT 022 or – other identification markings relating to devices complying with the abovementioned description | 0 |
| 0060 | ex 8522 90 59 94 | Electronic assembly for a laser read-head of a compact disc player, comprising: <ul style="list-style-type: none"> – a printed circuit, – a photo-detector, in the form of a monolithic integrated circuit, contained in a housing, – not more than 3 connectors, – not more than 1 transistor, – not more than 3 variable and 4 fixed resistors, – not more than 5 capacitors, the whole mounted on a support | 0 |
| 0061 | ex 8522 90 98 31 | Thin-film recording and reproducing device, having at least 9 parallel channels for digital signals and at least 2 channels for analogue signals, to which a non-magnetic ceramic substrate is fixed, the whole rounded at one side, for use in the manufacture of magnetic heads for digital sound recording and digital/analogue sound reproducing apparatus of the cassette-type (a) | 0 |
| 0062 | ex 8522 90 98 34 | Cassette-deck sub-assembly for sound recording and reproducing apparatus, for use in the manufacture of telephone answering machines (a) | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--------------------|--|-----------------------------------|
| 0063 | ex 8522 90 98 35 | Sound reproducing assembly, comprising a tape deck mechanism of the cassette type, comprising a DC motor, for use in the manufacture of products falling within heading No 8519 (a) | 0 |
| 0064 | ex 8522 90 98 36 | Roll for magnetic tape guiding and winding, for use in the manufacture of products falling within heading No 8521 or 8522 (a) | 0 |
| 0065 | ex 8522 90 98 37 | Magnetic head for erasing video tapes, for use in the manufacture of products falling within heading No 8521 or 8522 (a) | 0 |
| 0066 | ex 8522 90 98 39 | Assembly consisting of a driver circuit, a tachometer and a brushless DC motor | 0 |
| 0067 | ex 8522 90 98 43 | Analogue sound recording and reproducing assembly, comprising a record/playback head and a twin tape deck mechanism of the cassette type, not comprising circuits with amplification functions or power supply drive functions, for use in the manufacture of products falling within subheadings 8527 31 91 and 8527 31 98 (a) | 0 |
| 0068 | ex 8522 90 98 44 | Assembly for optical discs, comprising at least an optical unit and DC motors, not capable of double layer recording | 0 |
| 0069 | ex 8528 21 90 20 | Colour video monitor having an operating voltage of not less than 10 V and not exceeding 35 V, comprising a liquid crystal display (LCD), whether or not contained in a housing | 0 |
| 0070 | ex 8528 22 00 10 | Video monitor comprising: <ul style="list-style-type: none"> – a flat screen monochrome cathode-ray tube with a diagonal measurement of the screen not exceeding 110 mm and equipped with a deflector yoke, and – a printed circuit on which are mounted a deflection unit, a video-amplifier and a transformer, the whole mounted on a chassis, for the manufacture of video entry-phones, video telephones or surveillance apparatus (a) | 0 |
| 0071 | ex 8529 10 70 10 | Ceramic filter package comprising 2 ceramic filters and 1 ceramic resonator for a frequency of 10,7 MHz (± 30 kHz), contained in a housing | 0 |
| 0072 | ex 8529 10 70 15 | Ceramic filter for a centre frequency of 10,7 MHz, with a bandwidth not exceeding 330 kHz at 3 dB and not exceeding 950 kHz at 20 dB, contained in a housing | 0 |
| 0073 | ex 8529 10 70 20 | Ceramic filters for frequencies of 4,5 MHz or more but not exceeding 6,6 MHz contained in a housing | 0 |
| 0074 | ex 8529 10 70 25 | Ceramic filter for a centre frequency of 450 kHz or more but not exceeding 470 kHz, with a bandwidth not exceeding 13 kHz at 3 dB, contained in a housing | 0 |
| 0075 | ex 8529 10 70 30 | Ceramic filter for a frequency of 450 kHz, with a bandwidth not exceeding 18 kHz at 10 dB, contained in a housing | 0 |
| 0076 | ex 8529 10 70 35 | Ceramic filter for a centre frequency of 455 kHz ($\pm 1,5$ kHz), with a bandwidth not exceeding 25 kHz at 6 dB and not exceeding 60 kHz at 40 dB, contained in a housing | 0 |
| 0077 | ex 8529 10 70 45 | Ceramic filter for a centre frequency of 450 kHz ($\pm 1,5$ kHz) or 455 kHz ($\pm 1,5$ kHz), with a bandwidth not exceeding 30 kHz at 6 dB and not exceeding 70 kHz at 40 dB, contained in a housing | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--------------------------------------|---|-----------------------------------|
| 0078 | ex 8529 10 70 50 | Radio frequency (RF) signal isolator for frequencies of 890 MHz or more but not exceeding 1 990 MHz, having an insertion loss not exceeding 0,7 dB, contained in a housing | 0 |
| 0079 | ex 8529 10 70 55 | Filters, excluding surface acoustic wave filters, for a center frequency of 485 MHz or more but not exceeding 1 990 MHz with an insertion loss not exceeding 3,5 dB, contained in a housing | 0 |
| 0080 | ex 8529 10 70 80 | Ceramic filter package, excluding surface acoustic wave filters, consisting of: – a transmit filter with a centre frequency of 1 747,5 MHz and an insertion loss not exceeding 2,3 dB at a bandwidth of 75 MHz and – a receive filter with a centre frequency of 1 842,5 MHz and an insertion loss not exceeding 3,3 dB at a bandwidth of 75 MHz, the whole contained in a housing | 0 |
| 0081 | ex 8529 10 70 85 | Ceramic filter package, excluding surface acoustic wave filters, comprising 2 filters with one of the following combinations of characteristics: – a transmit centre frequency of 902,5 MHz, a receive centre frequency of 947,5 MHz and an insertion loss not exceeding 3,2 dB at a bandwidth of 25 MHz or – a transmit centre frequency of 1 747,5 MHz, a receive centre frequency of 1 842,5 MHz and an insertion loss not exceeding 3,5 dB at a bandwidth of 75 MHz, the whole contained in a housing | 0 |
| 0082 | ex 8529 10 90 20 | Antenna switch, comprising:- a transmit filter with a centre frequency of 942,5 MHz or more but not exceeding 1990 MHz and- a receive filter with a centre frequency of 847,5 MHz or more but not exceeding 1990 MHz, the whole contained in a housing | 0 |
| 0083 | ex 8529 90 81 31 | Demagnetisation coil, with cables and connectors | 0 |
| 0084 | ex 8529 90 81 32 | Optical unit for video projection, comprising a colour separation system, a positioning mechanism and lenses, for use in the manufacture of products falling within heading No 8528 (a) | 0 |
| 0085 | ex 8529 90 81 34 | Assembly consisting of a lens unit, having an adjustable focal length of 4 mm or more but not exceeding 69 mm and comprising a zoom encoder, a stepping motor unit, a zoom motor unit, an iris motor unit and a photo interrupter | 0 |
| 0086 | ex 8529 90 81 35 | Video recording and reproducing assembly, comprising a tape deck mechanism of the cassette type, comprising a DC motor, for use in the manufacture of products falling within heading No 8525 (a) | 0 |
| 0087 | ex 8529 90 81 36 | Assembly consisting of a monochrome cathode-ray tube with a diagonal measurement of the screen of 143 mm or more but not exceeding 230 mm and a concave focus lens mounted on a liquid-filled cooling armature | 0 |
| 0088 | ex 8529 90 81 37 ex 8529 90 88 33 | Filter, consisting of 2 piezo-electric crystals each with a frequency of 21 MHz or more but not exceeding 30 MHz and separately mounted on a bracket, with not more than 7 connections | 0 |
| 0089 | ex 8529 90 81 40 | Assembly comprising prisms, digital micromirror device (DMD)-chips and electronic control circuits, for use in the manufacture of video projectors (a) | 0 |
| 0090 | ex 8529 90 81 41 | Digital micromirror device (DMD)-chips, for use in the manufacture of video projectors (a) | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--|---|-----------------------------------|
| 0091 | ex 8531 80 80 01 | Indicator lamp, consisting of 4 light-emitting diodes made from silicon-carbide (SiC) semiconductor material, operating at a nominal wavelength of 481, 560 or 630 nm, contained in a housing | 0 |
| 0092 | ex 8531 80 80 15 | Indicator lamp, consisting of 2 light-emitting diodes made from aluminium-gallium-arsenic (AlGaAs) or gallium-phosphor (GaP) semiconductor material, having a rectangular base, contained in a housing of the SMD (surface mounted device) type and having a lens | 0 |
| 0093 | ex 8531 80 80 25 | Electro-acoustic transducer | 0 |
| 0094 | ex 8531 80 80 30 | An electromagnetic display, consisting of 7 electromagnetic coils which by means of the residual magnetism in the stators provide that the last indication remains available (set state), and 7 pivoting light-reflecting segments each of which is attached to a bar magnet; assembly comprising such displays | 0 |
| 0095 | ex 8536 30 30 11 ex 8536 30 90 31 ex 8536 50 80 96 | Thermo-electric switch with a cut-off current of 50 A or more, comprising a snap action switch, for direct mounting on an electric motor coil, contained in a hermetically sealed housing | 0 |
| 0096 | ex 8536 41 10 91 ex 8536 41 90 91 ex 8536 49 00 91 | Thermal relays contained in a hermetically sealed glass cartridge not exceeding 35 mm in length excluding wires, with a maximum leakage rate of 10^{-6} cm ³ He/sec at one bar in the temperature range 0 to 160 °C, to be incorporated into compressors for refrigerating equipment (a) | 0 |
| 0097 | ex 8536 50 11 31 | Switch of the printed circuit mount type, operating at a force of 4,9 N ($\pm 0,9$ N), contained in a housing | 0 |
| 0098 | ex 8536 50 15 32 | Rotary switch in form of a wheel with a diameter of between 15 and 16 mm and contacts for closing the circuit, for a rated voltage of 12 V at 50 mA | 0 |
| 0099 | ex 8536 50 19 91 | Hall effect switch, comprising 1 magnet, 1 Hall effect sensor and 2 capacitors, contained in a housing with 3 connections and bearing: <ul style="list-style-type: none"> – an identification marking consisting of or including (one of) the following combination(s): 2AV28E 2AV31E 2AV56 or – other identification markings relating to devices complying with the abovementioned description | 0 |
| 0100 | ex 8536 50 19 92 | Hydraulic pressure switch, incorporating a pressure sensitive snap action disc, operating at a supply voltage of 6 V or more but not exceeding 18 V | 0 |
| 0101 | ex 8536 50 80 93 | Switch unit for coaxial cable, comprising 3 electromagnetic switches, with a switching time not exceeding 50 ms and an actuating current not exceeding 500 mA at a voltage of 12 V | 0 |
| 0102 | ex 8536 50 80 95 | Reed switch having a switching power of 20 W or more within the range of 17-43 A.turn, in the form of a glass capsule, not containing mercury, the dimensions of which do not exceed 3 × 21 mm, for use in the manufacture of automotive airbag shock-sensors (a) | 0 |
| 0103 | ex 8536 90 85 92 | Metallic stamped frame with connections | 0 |
| 0104 | ex 8536 90 85 93 | Contact element with a hold-force of more than 3 N, in the form of 2 rectangular plastic frames interconnected by electric conductors | 0 |
| 0105 | ex 8536 90 85 94 ex 8544 49 80 10 | Elastomeric connector, consisting of one or more conductor elements and of a rubber or silicon substrate | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--------------------------------------|--|-----------------------------------|
| 0106 | ex 8537 10 99 92 | Touch sensitive screen panel, consisting of a conductive grid between two glass or plastic plates or sheets, fitted with electric conductors and connectors | 0 |
| 0107 | ex 8537 10 99 93 | Electronic control units for a voltage of 12 V, for use in the manufacture of vehicle mounted temperature control systems (a) | 0 |
| 0108 | ex 8538 90 99 92 | Part of an electrothermal fuse, consisting of a tin coated copper wire attached to a cylindrical casing, the exterior dimensions of which do not exceed 5 × 48 mm | 0 |
| 0109 | ex 8540 11 11 91 | Colour cathode-ray tube with a slit or slot mask, equipped with electron guns placed side by side (in-line technology) and with a diagonal measurement of the screen of 12 cm or more but not exceeding 26 cm | 0 |
| 0110 | ex 8540 11 11 93 | Colour cathode-ray tube, equipped with 1 gun with 3 rays and with a diagonal measurement of the screen of 22 cm or more but not exceeding 26 cm | 0 |
| 0111 | ex 8540 11 13 91 | Colour cathode-ray tube with a slit or slot mask, having a distance between stripes of the same colour of less than 0,42 mm and a diagonal measurement of the screen of 49 cm, for use in the manufacture of professional video monitors including security and medical monitor applications (a) | 0 |
| 0112 | ex 8540 11 19 91 | Colour cathode-ray tube equipped with electron guns placed side by side (in-line technology), with a diagonal measurement of the screen of 85 cm or more | 0 |
| 0113 | ex 8540 11 91 31 | Colour cathode-ray tube with a screen width/height ratio of 16/9 and a diagonal measurement of the screen of 39,8 cm (±0,3 cm) | 0 |
| 0116 | ex 8540 12 00 82 | Monochrome cathode-ray tube with a diagonal measurement of the screen of 250 mm or more but not exceeding 320 mm and an anode voltage of 18 kV or more but not exceeding 22 kV | 0 |
| 0117 | ex 8540 12 00 83 | Monochrome cathode-ray tube, with a diagonal measurement of the screen of 150 mm or more but not exceeding 182 mm, a neck diameter of less than 30 mm and an anode voltage of 25 kV or more but not exceeding 32 kV | 0 |
| 0118 | ex 8540 12 00 84 | Flat screen monochrome cathode-ray tube, with a diagonal measurement of the screen not exceeding 102 mm | 0 |
| 0119 | ex 8540 20 80 91 | Photomultiplier consisting of a photocathode tube with 9 dynodes, for light of a wavelength of 160 nm or more but not exceeding 930 nm, of a diameter not exceeding 14 mm and a height not exceeding 94 mm | 0 |
| 0120 | ex 8540 40 00 31 ex 8540 60 00 31 | Colour cathode-ray tube with a dot mask, equipped with 3 electron guns placed side by side (in-line technology) or 1 gun with 3 rays, with a diagonal measurement of the screen of more than 72 cm and a distance of less than 0,5 mm between dots of the same colour | 0 |
| 0121 | ex 8540 40 00 32 ex 8540 60 00 32 | Colour cathode-ray tube with a dot mask, equipped with 3 electron guns placed side by side (in-line technology) or 1 gun with 3 rays, having a diagonal measurement of the screen not exceeding 72 cm | 0 |
| 0122 | ex 8540 40 00 33 | Colour cathode-ray tube with a slit or slot mask, having a distance between stripes of the same colour of less than 0,35 mm and a diagonal measurement of the screen not exceeding 53 cm | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--------------------------------------|--|-----------------------------------|
| 0123 | ex 8540 40 00 34 | Colour cathode-ray tube with a slit or slot mask, having a distance between stripes of the same colour of less than 0,39 mm and a diagonal measurement of the screen of 33 cm or more but not exceeding 38 cm | 0 |
| 0124 | ex 8540 40 00 35 | Colour cathode-ray tube with a slit or slot mask, having a distance between stripes of the same colour of less than 0,35 mm and a diagonal measurement of the screen not exceeding 72 cm, for use in the manufacture of monitors (a) | 0 |
| 0125 | ex 8540 40 00 36 | Colour cathode-ray tube with a slit or slot mask, having a distance between stripes of the same colour of less than 0,30 mm and a diagonal measurement of the screen not exceeding 58 cm | 0 |
| 0126 | ex 8540 50 00 31 ex 8540 60 00 33 | Flat screen monochrome cathode-ray tube, with a diagonal measurement of the screen of 142 mm or more but not exceeding 190 mm, a luminescence of 300 lumen or more but not exceeding 2 000 lumen, a resolution of 0,06 mm or more but not exceeding 0,1 mm, phosphor types P1 or P22 or P53 or P55 or P56, an anode voltage of more than 34 kV, a focus voltage of more than 7 kV and a cathode current of 3 mA or more | 0 |
| 0127 | ex 8540 50 00 32 ex 8540 60 00 34 | Monochrome cathode-ray tube with a diagonal measurement of the screen of 176 mm or more but not exceeding 520 mm and a neck diameter not exceeding 21 mm | 0 |
| 0128 | ex 8540 89 00 91 | Displays in the form of a tube consisting of a glass housing mounted on a board the dimensions of which do not exceed 300 × 350 mm excluding leads. The tube contains one or more rows of characters or lines arranged in rows, each character or line consisting of fluorescent or phosphorescent elements. These elements are mounted on a metallised base which is covered with fluorescent substances or phosphorescent salts which give off light when bombarded with electrons | 0 |
| 0129 | ex 8540 89 00 92 | Vacuum fluorescent display tube | 0 |
| 0130 | ex 8540 91 00 31 | Electron gun, for use in the manufacture of colour cathode-ray tubes of subheading 8540 40 00 with a diagonal measurement of the screen of 34 cm or more but not exceeding 39 cm (a) | 0 |
| 0131 | ex 8540 91 00 32 | Electron gun of colour cathode-ray tubes with an anode voltage of 27,5 kV or more but not exceeding 33 kV | 0 |
| 0132 | ex 8540 91 00 91 | Deflector yoke for cathode-ray tubes with an operating frequency of 31 250 Hz or more but not exceeding 64 000 Hz, incorporating a quadripolar magnet | 0 |
| 0133 | ex 8540 91 00 92 | Slit or slot mask, excluding masks with continuously vertical slits, with a diagonal measurement of 39 cm or less | 0 |
| 0134 | ex 8540 91 00 93 | Electron gun for the production of monochrome cathode-ray tubes with a diagonal measurement of the screen of 7,6 cm or more but not exceeding 30,5 cm (a) | 0 |
| 0135 | ex 8540 91 00 94 | Deflector yoke for colour cathode-ray tubes, with an operating frequency of 15 625 or 31 250 Hz, comprising 2 two-pole ring magnets, 2 four-pole ring magnets and 2 six-pole ring magnets | 0 |
| 0136 | ex 8540 91 00 96 | Assembly for cathode-ray tubes with 2 or more but not more than 6 coils, a plastic support and a metal fixing ring, for the adjustment of display sharpness and/or convergence | 0 |
| 0137 | ex 8540 91 00 97 | Slit mask, consisting of continuously vertical slits measuring more than 275 mm in the length | 0 |
| 0138 | ex 8540 91 00 98 | Frame of molybdenum chrome steel, for use in the manufacture of cathode-ray tubes (a) | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--------------------|---|-----------------------------------|
| 0139 | ex 8540 99 00 91 | Anode, cathode or output part, or an assembly comprising these components (magnetron core tube), for the manufacture of magnetrons of subheading 8540 71 00 (a) | 0 |
| 0140 | ex 8543 19 00 10 | Electron beam accelerator systems, with an operating voltage not exceeding 1,5 MV and a beam current not exceeding 70 mA | 0 |
| 0142 | ex 8543 89 95 46 | Amplifier, consisting of active and passive elements mounted on a printed circuit, contained in a housing bearing: <ul style="list-style-type: none"> – an identification marking consisting of or including (one of) the following combination(s): FA 01314 MHW 2707 MHW 9002 PF 0144 PHW 902 FA 01317 MHW 607 MHW 910 PF 0146 PHW 925 FA 01321 MHW 704 MHW 914 PF 0148 SHW 5115 FMC 1717 MHW 707 MHW 915 PF 0412 XHW 105 FMC 1819 MHW 720 MHW 916 PHW 2905 XHW 2803 ISO 122 MHW 803 MHW 926 PHW 2907 XHW 2902 MHW 105 MHW 820-1 MHW 927 PHW 5113 XHW 5115 MHW 1815 MHW 820-2 MHW 953 PHW 9012 XHW 903 MHW 2701 or – other identification markings relating to devices complying with the abovementioned description | 0 |
| 0143 | ex 8543 89 95 48 | Radio frequency (RF) modulator, operating with a frequency range of 43 MHz or more but not exceeding 870 MHz, capable of switching VHF and UHF signals, consisting of active and passive elements mounted on a printed circuit, contained in a housing | 0 |
| 0144 | ex 8543 89 95 49 | Rectifier assembly of power barrier diodes, consisting of 2 diodes with an average forward current not exceeding 600 A and a repetitive reverse peak voltage not exceeding 40 V, each contained in a housing and connected by a common cathode | 0 |
| 0145 | ex 8543 89 95 50 | Piezo-electric crystal clock oscillator with a fixed frequency, within a frequency range of 1,8 MHz to 67 MHz, contained in a housing bearing: <ul style="list-style-type: none"> – an identification marking consisting of or including (one of) the following combination(s): R4000.8 R4000.9 or – other identification markings relating to devices complying with the abovementioned description | 0 |
| 0146 | ex 8543 89 95 51 | Mechanical vibratory gyroscope driven by a 25 or 26 kHz oscillator, comprising a differential amplifier and a detector circuit, contained in a housing bearing: <ul style="list-style-type: none"> – an identification marking consisting of or including (one of) the following combination(s): ENC05D or – other identification markings relating to devices complying with the abovementioned description | 0 |
| 0147 | ex 8543 89 95 52 | Opto-electronic circuit comprising one or more light-emitting diodes (LEDs) and one photodiode with amplifier circuit and an integrated logic gate arrays circuit or one or more light-emitting diodes and at least 2 photodiodes with an amplifier circuit, contained in a plastic housing bearing: <ul style="list-style-type: none"> – an identification marking consisting of or including (one of) the following combination(s): HC PL 2400 HC PL 2730 or – other identification markings relating to devices complying with the abovementioned description | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--------------------|--|-----------------------------------|
| 0148 | ex 8543 89 95 53 | Oscillator, with a centre frequency of 20 GHz or more but not exceeding 42 GHz, consisting of active and passive elements not mounted on a substrate, contained in a housing bearing: <ul style="list-style-type: none"> – an identification marking consisting of or including (one of) the following combination(s): 372-02 372-03 or – other identification markings relating to devices complying with the abovementioned description | 0 |
| 0149 | ex 8543 89 95 55 | Audio recording and reproducing circuit, capable of stereo audio data storage and simultaneous record and playback, comprising 2 or 3 monolithic integrated circuits mounted on a printed circuit or a lead frame, contained in a housing bearing: <ul style="list-style-type: none"> – an identification marking consisting of or including (one of) the following combination(s): RWA010 RWA100 RWA200 RWA300 or – other identification markings relating to devices complying with the abovementioned description | 0 |
| 0150 | ex 8543 89 95 56 | Overvoltage suppression assembly, comprising 8 diodes, having a reverse stand-off voltage not exceeding 4,5 V, a reverse leakage current not exceeding 10 µA, a peak pulse current not exceeding 30 A and a nominal capacitance of 50 pF, contained in a housing | 0 |
| 0151 | ex 8543 89 95 59 | Charged coupled device (CCD) scanner assembly, for a real-time film scanning system, having optical functions, illumination functions and signal processing functions | 0 |
| 0152 | ex 8543 89 95 60 | Temperature compensated oscillator, comprising a printed circuit on which are mounted at least a piezo-electric crystal and an adjustable capacitor, contained in a housing | 0 |
| 0153 | ex 8543 89 95 61 | Voltage controlled oscillator (VCO), other than temperature compensated oscillators, consisting of active and passive elements mounted on a printed circuit, contained in a housing | 0 |
| 0154 | ex 8543 90 80 40 | Stainless steel cathode in the form of a plate with a hanger bar, whether or not with plastic side strips | 0 |
| 0155 | ex 8543 90 80 50 | Assembly of products falling within heading No 8541 or 8542 mounted on a printed circuit, contained in a housing | 0 |
| 0156 | ex 8545 90 90 01 | Cell and battery carbon, in the form of rods, with a length of 34 mm or more but not exceeding 160 mm and a diameter not exceeding 12 mm | 0 |
| 0157 | ex 8548 90 90 38 | Parts, for use in the manufacture or the repair of products falling within subheading 8517 21 00 (a) | 0 |
| 0158 | ex 8548 90 90 39 | Optical unit, consisting of a laserdiode and a photodiode, operating at a typical wavelength of 635 or 670 nm | 0 |
| 0159 | ex 8548 90 90 40 | Infrared signal receiver unit, consisting of a photodiode and at least an amplifier in the form of a monolithic integrated circuit, contained in a housing bearing: <ul style="list-style-type: none"> – an identification marking consisting of or including (one of) the following combination(s): GP1U58XB SBX 1610 or – other identification markings relating to devices complying with the abovementioned description | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--------------------------------------|---|-----------------------------------|
| 0160 | ex 8548 90 90 41 | Unit, consisting of a resonator operating within a frequency range of 1,8 MHz or more but not exceeding 40 MHz and a capacitor, contained in a housing | 0 |
| 0161 | ex 8548 90 90 42 ex 9110 90 00 94 | Clock/calendar circuit, consisting of a printed circuit on which are mounted at least a quartz oscillator and a monolithic integrated circuit, the whole contained in a housing bearing: <ul style="list-style-type: none"> – an identification marking consisting of or including (one of) the following combination(s): DS 1287 DS 1387 MK 48T08 MK 48T18 RTC 65271 DS 12887A MK 48T02 MK 48T12 RTC 63421 RTC 72423 or – other identification markings relating to devices complying with the abovementioned description | 0 |
| 0162 | ex 8548 90 90 43 | Contact image sensor | 0 |
| 0163 | ex 8711 10 00 10 | Portable motorised scooter, in disassembled kit | 0 |
| 0164 | ex 9001 10 90 10 | Image reverser made up from an assembly of optical fibres | 0 |
| 0165 | ex 9001 20 00 10 | Material consisting of a polarising film, supported on one or both sides by transparent material | 0 |
| 0166 | ex 9001 90 90 20 | Rear projection screen, comprising a Fresnel lens of plastic and a polarising sheet of plastic, for use in the manufacture of products falling within heading No 8528 (a) | 0 |
| 0167 | ex 9001 90 90 30 | Lens of plastic, unmounted, having a focal length of 3,86 mm ($\pm 0,1$ mm) and with a diameter not exceeding 8 mm, for use in the manufacture of compact disc players (a) | 0 |
| 0168 | ex 9001 90 90 40 | Optical fibre plate, for use in the manufacture of screens and photocathodes for image intensifiers (a) | 0 |
| 0169 | ex 9001 90 90 50 | Rear projection screen, comprising a lenticular plastic plate | 0 |
| 0170 | ex 9001 90 90 60 | Prism for the splitting of light, unmounted, for use in the manufacture of charged-coupled image (CCD) cameras (a) | 0 |
| 0171 | ex 9001 90 90 70 | Rod of neodymium-doped yttrium-aluminium garnet (YAG) material, polished at both ends | 0 |
| 0172 | ex 9001 90 90 80 | Lens of plastic, unmounted, for use in the manufacture of products falling within subheading 9006 40 00 (a) | 0 |
| 0173 | ex 9002 11 00 10 | Adjustable lens unit, having a focal length of 90 mm or more but not exceeding 180 mm and comprising a combination of between 4 and 8 glass or methacrylic lenses with a diameter of 120 mm or more but not exceeding 180 mm, each lens coated on at least one side with a magnesium fluoride layer, for use in the manufacture of video projectors (a) | 0 |
| 0174 | ex 9002 11 00 50 | Lens unit, having a focal length of 25 mm or more but not exceeding 150 mm, consisting of glass or plastic lenses, with a diameter of 60 mm or more but not exceeding 190 mm | 0 |
| 0175 | ex 9002 11 00 60 | Optical element, comprising one or more mounted lenses of plastic, for use in the manufacture of products falling within subheading 9006 40 00 (a) | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--|---|-----------------------------------|
| 0176 | ex 9002 19 00 10 | Lens unit, having a focal length of 24,96 mm ($\pm 0,1$ mm), a diameter of 16 mm and a length of 16 mm, for use in the manufacture of products falling within subheading 8517 21 00 (a) | 0 |
| 0177 | ex 9002 20 00 10 | Filter, consisting of a plastic polarising membrane, a glass plate and a transparent protective film, mounted on a metal frame, for use in the manufacture of products falling within heading 8528 (a) | 0 |
| 0178 | ex 9002 90 90 20 | Lens, mounted, having a fixed focal length of 3,8 mm ($\pm 0,19$ mm) or 8 mm ($\pm 0,4$ mm), with a relative aperture of F2.0 and a diameter not exceeding 33 mm, for use in the manufacture of charged-coupled (CCD) cameras (a) | 0 |
| 0179 | ex 9002 90 90 30 | Optical unit, comprising 1 or 2 rows of optical glass fibres in the form of lenses and with a diameter of 0,85 mm or more but not exceeding 1,15 mm, embedded between 2 plastic plates | 0 |
| 0180 | ex 9002 90 90 50 | Lens and image gate assembly, for a real-time film scanning system, comprising a lens consisting of 9 or 11 elements and having an illumination function | 0 |
| 0181 | ex 9006 91 90 10 | Parts, for use in the manufacture of products falling within subheading 9006 40 00 (a) | 0 |
| 0182 | ex 9013 80 90 10 | Polarisation insensitive fibre-optic isolator, operating at a wavelength of 1 200 nm or more, contained in a cylindrical housing | 0 |
| 0183 | ex 9013 80 90 20 | Optical switch, comprising at least one optical input and two optical outputs and with electrical connectors | 0 |
| 0184 | ex 9017 90 90 20 | Thermal printer head, comprising at least 7 168 heater elements mounted on 2 or more ceramic supports, the whole contained in a housing the exterior dimensions of which exceed 21 × 39 × 639 mm | 0 |
| 0185 | ex 9022 30 00 10 | X-ray tube with a target voltage of 4 kV or more but not exceeding 30 kV, a power not exceeding 9 W and a target current not exceeding 2 mA | 0 |
| 0186 | ex 9027 10 90 10 | Sensor element for gas or smoke analysis in motor vehicles, essentially consisting of a zirconium-ceramic element in a metal housing | 0 |
| 0187 | ex 9031 80 34 10 ex 9031 80 39 30 ex 9031 80 99 10 | Machines and apparatus providing automated quality inspection of rigid magnetic disks, for use in the manufacture of products falling within subheading 8523 20 10 (a) | 0 |
| 0188 | ex 9031 80 34 30 ex 9031 80 39 50 | Apparatus for measuring the angle and direction of rotation of motor vehicles, consisting of at least one yaw rate sensor in the form of a monocrystalline quartz, whether or not combined with one or more measuring sensors, the whole contained in a housing | 0 |
| 0189 | ex 9031 80 39 10 | Acceleration measurement device for automotive applications, comprising one or more active and/or passive elements and one or more sensors, the whole contained in a housing | 0 |
| 0190 | ex 9031 80 39 40 | Machines and apparatus for the automatic testing of the integrity of ink-jet cartridge housings (a) | 0 |
| 0191 | ex 9031 90 80 20 | Read and write test head for checking the quality of rigid magnetic disks, mounted on a carrier arm | 0 |
| 0192 | ex 9031 90 80 30 | Assembly for a laser align sensor, in the form of a printed circuit comprising optical filters and a charge-coupled image (CCD) sensor, the whole contained in a housing | 0 |

| | CN code & TARIC | Description | Rate of autonomous duty (%) |
|------|--------------------------------------|---|-----------------------------------|
| 0193 | ex 9031 90 80 40 | Test head for checking the mechanical quality of rigid magnetic disks, mounted on a carrier arm | 0 |
| 0194 | ex 9031 90 80 50 | Burnishing head, for removing asperities on and polishing of the surface of rigid magnetic disks, mounted on a carrier arm | 0 |
| 0195 | ex 9032 10 91 10 | Thermostat, comprising a snap-action switch, for direct mounting on an electric motor coil, contained in a hermetically sealed housing | 0 |
| 0196 | ex 9032 89 90 10 | Automotive airbag shock-sensor, comprising a contact capable of switching a current of 12 A at a voltage of 30 V, having a typical contact resistance of 80 mohm | 0 |
| 0197 | ex 9106 90 10 10 | Timer assembly, for use in the manufacture of goods of subheading 8516 50 00 (a) | 0 |
| 0198 | ex 9110 12 00 91 | Assembly consisting of a printed circuit on which are mounted one quartz oscillator, at least one watch circuit and, whether or not integrated, at least one capacitor, of a thickness not exceeding 5 mm | 0 |
| 0199 | ex 9110 90 00 92 ex 9114 90 00 91 | Assembly consisting of a printed circuit on which is mounted a watch circuit or a watch circuit and a quartz oscillator, of a thickness not exceeding 5 mm | 0 |
| 0200 | ex 9110 90 00 93 | Assembly consisting of a printed circuit on which is mounted at least one watch circuit, a quartz oscillator and a piezo-electric sound element, with a thickness exceeding 5 mm | 0 |
| 0201 | ex 9608 91 00 10 | Non-fibrous plastic pen-tips with an internal channel | 0 |
| 0202 | ex 9608 91 00 20 | Felt tips and other porous-tips for markers, without internal canal | 0 |
| 0203 | ex 9612 10 10 10 | Ribbons of plastic with segments of different colours, providing the penetration of dyes by heat into a support (so called dye-sublimation) | 0 |
| 0204 | ex 9613 90 00 20 | Piezo-electric ignition mechanism, whether or not with complementary elements | 0 |

| | |
|-----|---|
| (a) | Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions. |
| (b) | <p>The suspension shall apply to fish intended to undergo any operation unless they are intended to undergo exclusively one or more of the following operations:</p> <ul style="list-style-type: none"> – cleaning, gutting, tailing, heading, – cutting (excluding filleting or cutting of frozen blocks), – sampling, sorting, – labelling, – packing, – chilling, – freezing, – deep freezing, – thawing, separation. <p>The suspension is not allowed for products intended, in addition, to undergo treatment</p> |

| | |
|-----|--|
| | (or operations) qualifying for suspension where such treatment (or operations) is (are) carried out at retail or catering level. The suspension of customs duties shall apply only to fish intended for human consumption. |
| (c) | However, the suspension is not allowed where processing is carried out by retail or catering undertakings. |

"

FINANCIAL STATEMENT

1. TITLE OF OPERATION

Proposal for a Council Regulation amending Regulation (EC) No 1255/96 temporarily suspending the autonomous common customs tariff duties on certain industrial, agricultural and fishery products.

2. BUDGET HEADING(S) INVOLVED

Chapter 12 Article 120.

3. LEGAL BASIS

Article 26 of the EC Treaty.

4. DESCRIPTION OF OPERATION

Suspension of the common customs tariff duties for the above products.

7. FINANCIAL IMPACT

In order to reduce the economic problems arising from the period of validity of previous Regulations, Council Regulation (EC) No 1255/96, now in force, does not have an expiry date.

This proposal contains only the amendments which must be made to the annex to the existing Regulation in order to take account of the following:

1. new requests for suspension which have been presented and accepted;
2. technical product developments and economic trends on the market resulting in the lifting of certain existing suspensions;
3. amendments to Nomenclature codes.

This time the amendments take the form of a consolidated annex.

Obviously only the amendments described in 1 and 2 have a financial impact.

Addition

This Annex, in addition to the amendments resulting from changes to CN codes, contains 65 new products. The uncollected duties corresponding to these suspensions, calculated on the basis of expected imports into the requesting Member State for 2003, total MEUR 15.0.

On the basis of the existing statistics for the preceding years, it would appear, however, that this amount must be increased by an average factor, estimated at 1.8,

to take account of imports into other Member States using the same suspensions. This means **a loss of revenue of some MEUR 27.1.**

Withdrawal:

7 products have been withdrawn from this annex reflecting the reintroduction of customs duties. This represents **an increase of MEUR 9.9 in resources**, as calculated from requests for suspension or available statistics (2001).

Estimated cost of this operation

Taking available statistics (2001) as a basis, the impact on the loss of revenue resulting from this Regulation may therefore be estimated at **27.1 - 9.9 = MEUR 17.2**, then an increase of loss of revenue, with a **total loss estimated for 2003 of 668.3 + 17.2 = MEUR 685.5.**

The shortfall in traditional own resources will have to be made up by the Member States by topping up the GNP component.

8. FRAUD PREVENTION MEASURES

Checks on the end-use of some of the products covered by this Council Regulation will be carried out in accordance with Articles 291 to 300 of Commission Regulation (EEC) No 2454/93 laying down provisions for the implementation of the Community Customs Code.