

This text is meant purely as a documentation tool and has no legal effect. The Union's institutions do not assume any liability for its contents. The authentic versions of the relevant acts, including their preambles, are those published in the Official Journal of the European Union and available in EUR-Lex. Those official texts are directly accessible through the links embedded in this document

► **B**

► **M4** COMMISSION REGULATION (EC) No 1275/2008

of 17 December 2008

implementing Directive 2005/32/EC of the European Parliament and of the Council with regard to ecodesign requirements for standby and off mode, and networked standby, electric power consumption of electrical and electronic household and office equipment ◀

(Text with EEA relevance)

(OJ L 339, 18.12.2008, p. 45)

Amended by:

		Official Journal		
		No	page	date
► <u>M1</u>	Commission Regulation (EC) No 278/2009 of 6 April 2009	L 93	3	7.4.2009
► <u>M2</u>	Commission Regulation (EC) No 642/2009 of 22 July 2009	L 191	42	23.7.2009
► <u>M3</u>	Commission Regulation (EU) No 617/2013 of 26 June 2013	L 175	13	27.6.2013
► <u>M4</u>	Commission Regulation (EU) No 801/2013 of 22 August 2013	L 225	1	23.8.2013
► <u>M5</u>	Commission Regulation (EU) 2016/2282 of 30 November 2016	L 346	51	20.12.2016
► <u>M6</u>	Commission Regulation (EU) 2019/2021 of 1 October 2019	L 315	241	5.12.2019
► <u>M7</u>	Commission Regulation (EU) 2019/2022 of 1 October 2019	L 315	267	5.12.2019
► <u>M8</u>	Commission Regulation (EU) 2019/2023 of 1 October 2019	L 315	285	5.12.2019

▼ B

▼ M4

COMMISSION REGULATION (EC) No 1275/2008

of 17 December 2008

implementing Directive 2005/32/EC of the European Parliament and of the Council with regard to ecodesign requirements for standby and off mode, and networked standby, electric power consumption of electrical and electronic household and office equipment

▼ B

(Text with EEA relevance)

▼ M4

Article 1

Subject matter and scope

This Regulation establishes ecodesign requirements related to standby and off mode, and networked standby, electric power consumption for the placing on the market of electrical and electronic household and office equipment.

This Regulation shall not apply to electrical and electronic household and office equipment placed on the market with a low voltage external power supply to work as intended.

▼ B

Article 2

Definitions

For the purposes of this Regulation, the definitions set out in Directive 2005/32/EC shall apply. The following definitions shall also apply:

1. ‘electrical and electronic household and office equipment’ (hereafter referred to as ‘equipment’), means any energy-using product which:
 - (a) is made commercially available as a single functional unit and is intended for the end-user;
 - (b) falls under the list of energy-using products of Annex I;
 - (c) is dependent on energy input from the mains power source in order to work as intended; and
 - (d) is designed for use with a nominal voltage rating of 250 V or below,also when marketed for non-household or non-office use;
2. ‘standby mode(s)’ means a condition where the equipment is connected to the mains power source, depends on energy input from the mains power source to work as intended and provides **only** the following functions, which may persist for an indefinite time:

— reactivation function, or reactivation function and only an indication of enabled reactivation function, and/or

▼ B

— information or status display;

3. ‘reactivation function’ means a function facilitating the activation of other modes, including active mode, by remote switch, including remote control, internal sensor, timer to a condition providing additional functions, including the main function;
4. ‘information or status display’ means a continuous function providing information or indicating the status of the equipment on a display, including clocks;
5. ‘active mode(s)’ means a condition in which the equipment is connected to the mains power source and at least one of the main function(s) providing the intended service of the equipment has been activated;
6. ‘off mode’ means a condition in which the equipment is connected to the mains power source and is not providing any function; the following shall also be considered as off mode:
 - (a) conditions providing only an indication of off-mode condition;
 - (b) conditions providing only functionalities intended to ensure electromagnetic compatibility pursuant to Directive 2004/108/EC of the European Parliament and of the Council ⁽¹⁾;
7. ‘information technology equipment’ means any equipment which has a primary function of either entry, storage, display, retrieval, transmission, processing, switching, or control, of data and of telecommunication messages or a combination of these functions and may be equipped with one or more terminal ports typically operated for information transfer;
8. ‘domestic environment’ means an environment where the use of broadcast radio and television receivers may be expected within a distance of 10 m of the apparatus concerned;

▼ M1

9. ‘low voltage external power supply’ means an external power supply with a nameplate output voltage of less than 6 volts and a nameplate output current greater than or equal to 550 milliamperes;

▼ M4

10. ‘network’ means a communication infrastructure with a topology of links, an architecture, including the physical components, organisational principles, communication procedures and formats (protocols);
11. ‘networked standby’ means a condition in which the equipment is able to resume a function by way of a remotely initiated trigger from a network connection;
12. ‘remotely initiated trigger’ means a signal that comes from outside the equipment via a network;

⁽¹⁾ OJ L 390, 31.12.2004, p. 24.

▼ M4

13. 'network port' means a wired or wireless physical interface of the network connection located on the equipment through which the equipment can be remotely activated;
14. 'logical network port' means the network technology running over a physical network port;
15. 'physical network port' means the physical (hardware) medium of a network port. A physical network port can host two or more network technologies;
16. 'network availability' means the capability of the equipment to resume functions after a remotely initiated trigger has been detected by a network port;
17. 'networked equipment' means equipment that can connect to a network and has one or more network ports;
18. 'networked equipment with high network availability' (HiNA equipment) means equipment with one or more of the following functionalities, but no other, as the main function(s): router, network switch, wireless network access point, hub, modem, VoIP telephone, video phone;
19. 'networked equipment with high network availability functionality' (equipment with HiNA functionality) means equipment with the functionality of a router, network switch, wireless network access point or combination thereof included, but not being HiNA equipment;
20. 'router' means a network device whose primary function is to determine the optimal path along which network traffic should be forwarded. Routers forward packets from one network to another, based on network layer information (L3);
21. 'network switch' means a network device whose primary function is to filter, forward and distribute frames based on the destination address of each frame. All switches operate at least at the data link layer (L2);
22. 'wireless network access point' means a device whose primary function is to provide IEEE 802.11 (Wi-Fi) connectivity to multiple clients;
23. 'hub' means a network device that contains multiple ports and is used to connect segments of a Local Area Network;
24. 'modem' means a device whose primary function is to transmit and receive digitally modulated analogue signals over a wired network;
25. 'printing equipment' means equipment that generates paper output from electronic input. Printing equipment may have additional functions and may be marketed as a multifunctional device or multifunctional product;

▼M4

26. 'large format printing equipment' means printing equipment designed for printing on A2 media and larger, including equipment designed to accommodate continuous-form media of at least 406 mm width;
27. 'tele-presence system' means a dedicated system for high-definition video conferencing and collaboration which includes a user interface, a high-definition camera, a display, a sound system and processing capabilities for encoding and decoding video and audio;
28. 'household coffee machine' means a non-commercial appliance for brewing coffee;
29. 'drip filter household coffee machine' means a household coffee machine which uses percolation to extract the coffee;
30. 'heating element' means a component of the coffee machine which converts electricity into heat to warm up water;
31. 'cup preheating' means a function for warming cups that are stored on the coffee machine;
32. 'brewing cycle' means the process that has to be completed to produce coffee;
33. 'self-cleaning' means a process that the coffee machine carries out to clean its interior. This process can either be a simple rinse or a washing process using specific additives;
34. 'descaling' means a process that the coffee machine carries out to remove totally or partially potential scale in its interior;
35. 'desktop thin client' means a computer that relies on a connection to remote computing resources (e.g. computer server, remote workstation) to obtain primary functionality and has no rotational storage media integral to the product. The main unit of a desktop thin client must be intended for use in a permanent location (e.g. on a desk) and not for portability. Desktop thin clients can output information to either an external or, where included with the product, an internal display;
36. 'workstation' means a high-performance, single-user computer primarily used for graphics, Computer Aided Design, software development, financial and scientific applications among other compute intensive tasks, and which has the following characteristics:
 - (a) has a mean time between failures (MTBF) of at least 15 000 hours;
 - (b) has error-correcting code (ECC) and/or buffered memory;
 - (c) meets three of the following five characteristics:
 - (1) has supplemental power support for high-end graphics (i.e. peripheral component interconnect (PCI)-E 6-pin 12 V supplemental power feed);

▼M4

- (2) its system is wired for greater than $\times 4$ PCI-E on the motherboard in addition to the graphics slot(s) and/or PCI-X support;
 - (3) does not support uniform memory access (UMA) graphics;
 - (4) includes five or more PCI, PCI-E or PCI-X slots;
 - (5) is capable of multi-processor support for two or more CPU (must support physically separate CPU packages/sockets, i.e. not met with support for a single multi core CPU);
37. 'mobile workstation' means a high-performance, single-user computer primarily used for graphics, Computer Aided Design, software development, financial and scientific applications among other compute intensive tasks, excluding game play, and which is designed specifically for portability and to be operated for extended periods of time either with or without a direct connection to an AC power source. Mobile workstations utilise an integrated display and are capable of operation on an integrated battery or other portable power source. Most mobile workstations use an external power supply and most have an integrated keyboard and pointing device.

A mobile workstation has the following characteristics:

- (a) has a mean time between failures (MTBF) of at least 13 000 hours;
 - (b) has at least one discrete graphics card (dGfx) meeting the G3 (with FB Data Width > 128-bit), G4, G5, G6 or G7 classification;
 - (c) supports the inclusion of three or more internal storage devices;
 - (d) supports at least 32 GB of system memory;
38. 'small-scale server' means a type of computer that typically uses desktop computer components in a desktop form factor but is designed primarily to be a storage host for other computers and to perform functions such as providing network infrastructure services and hosting data/media, and which has the following characteristics:
- (a) is designed in a pedestal, tower, or other form factor similar to those of desktop computers such that all data processing, storage, and network interfacing is contained within one box;
 - (b) is designed to be operational 24 hours per day and 7 days per week;
 - (c) is primarily designed to operate in a simultaneous multi-user environment serving several users through networked client units;

▼M4

- (d) where placed on the market with an operating system, the operating system is designed for home server or low-end server applications;
 - (e) is not placed on the market with a discrete graphics card (dGfx) meeting any classification other than G1;
39. 'computer server' means a computing product that provides services and manages networked resources for client devices, such as desktop computers, notebook computers, desktop thin clients, internet protocol (IP) telephones, or other computer servers. A computer server is typically placed on the market for use in data centres and office/corporate environments. A computer server is primarily accessed via network connections, and not through direct user input devices, such as a keyboard or a mouse;

A computer server has the following characteristics:

- (a) is designed to support computer server operating systems (OS) and/or hypervisors, and targeted to run user-installed enterprise applications;
- (b) supports error-correcting code (ECC) and/or buffered memory (including both buffered dual in-line memory modules (DIMMs) and buffered on board (BOB) configurations);
- (c) is placed on the market with one or more AC-DC power supply(ies);
- (d) all processors have access to shared system memory and are independently visible to a single OS or hypervisor.

*Article 3***Ecodesign requirements**

The ecodesign requirements related to standby and off mode, and networked standby electric power consumption, are set out in Annex II.

▼B*Article 4***Conformity assessment**

The procedure for assessing conformity referred to in Article 8(2) of Directive 2005/32/EC shall be the internal design control system set out in Annex IV to Directive 2005/32/EC or the management system set out in Annex V to Directive 2005/32/EC.

*Article 5***Verification procedure for market surveillance purposes**

Surveillance checks shall be carried out in accordance with the verification procedure set out in Annex III.

▼ B*Article 6***Benchmarks**

The indicative benchmarks for the best-performing products and technology currently available on the market are identified in Annex IV.

▼ M4*Article 7***Revision**

The Commission shall review this Regulation and present the results of the review to the Consultation Forum no later than 7 January 2016, in the light of technological progress. The review will in particular address the scope and the requirements for standby/off mode and the appropriateness and level of the requirements for networked standby with regard to the third stage of implementation (2019).

The review could address, inter alia, professional equipment and products equipped with electric motors operated by remote control.

*Article 8***Entry into force**

This Regulation shall enter into force on the twentieth day following that of its publication in the *Official Journal of the European Union*.

Point 1 of Annex II shall apply as from 7 January 2010.

Point 2 of Annex II shall apply as from 7 January 2013.

Point 3 of Annex II shall apply as from 1 January 2015.

Point 4 of Annex II shall apply as from 1 January 2017.

Point 5 of Annex II shall apply as from 1 January 2019.

Point 6 of Annex II shall apply as from 1 January 2015.

Point 7 of Annex II shall apply as from 1 January 2015.

This Regulation shall be binding in its entirety and directly applicable in all Member States.

▼ B*ANNEX I***List of energy-using products covered by this Regulation**

1. Household appliances

▼ M8

▼ B

Clothes dryers

▼ M7

▼ B

Cooking:

Electric ovens

Electric hot plates

Microwave ovens

Toasters

Fryers

Grinders, coffee machines and equipment for opening or sealing containers or packages

Electric knives

▼ M8

Other appliances for cooking and other processing of food, cleaning and maintenance of clothes with the exception of household washing machines and household washer-dryers

▼ B

Appliances for hair cutting, hair drying, tooth brushing, shaving, massage and other body care appliances

Scales

▼ M62. Information technology equipment intended primarily for use in the domestic environment, but excluding desktop computers, integrated desktop computers and notebook computers as defined in Commission Regulation (EU) No 617/2013, as well as electronic displays covered by Regulation (EU) 2019/2021 ⁽¹⁾.**▼ B**

3. Consumer equipment

▼ M2

Radio sets

Videocameras

Video recorders

Hi-fi recorders

Audio amplifiers

⁽¹⁾ Commission Regulation (EU) 2019/2021 of 1 October 2019 laying down eco-design requirements for electronic displays pursuant to Directive 2009/125/EC of the European Parliament and of the Council, amending Commission Regulation (EC) No 1275/2008 and repealing Commission Regulation (EC) 642/2009 (OJ L 315, 5.12.2019, p. 241).

▼ **M2**

Home theatre systems

Musical instruments

▼ **M6**

And other equipment for the purpose of recording or reproducing sound or images, including signals or other technologies for the distribution of sound and image other than by telecommunications, but excluding electronic displays covered by Regulation (EU) 2019/2021

▼ **B**

4. Toys, leisure and sports equipment

Electric trains or car racing sets

Hand-held video game consoles

Sports equipment with electric or electronic components

Other toys, leisure and sport equipment

▼B*ANNEX II***Ecodesign requirements**

1. One year after this Regulation has come into force:

(a) Power consumption in ‘off mode’:

Power consumption of equipment in any off-mode condition shall not exceed 1,00 W.

(b) Power consumption in ‘standby mode(s)’:

The power consumption of equipment in any condition providing only a reactivation function, or providing only a reactivation function and a mere indication of enabled reactivation function, shall not exceed 1,00 W.

The power consumption of equipment in any condition providing only information or status display, or providing only a combination of reactivation function and information or status display, shall not exceed 2,00 W.

(c) Availability of off mode and/or standby mode

Equipment shall, except where this is inappropriate for the intended use, provide off mode and/or standby mode, and/or another condition which does not exceed the applicable power consumption requirements for off mode and/or standby mode when the equipment is connected to the mains power source.

2. Four years after this Regulation has come into force:

(a) Power consumption in ‘off mode’:

Power consumption of equipment in any off-mode condition shall not exceed 0,50 W.

(b) Power consumption in ‘standby mode(s)’:

The power consumption of equipment in any condition providing only a reactivation function, or providing only a reactivation function and a mere indication of enabled reactivation function, shall not exceed 0,50 W.

The power consumption of equipment in any condition providing only information or status display, or providing only a combination of reactivation function and information or status display shall not exceed 1,00 W.

(c) Availability of off mode and/or standby mode

Equipment shall, except where this is inappropriate for the intended use, provide off mode and/or standby mode, and/or another condition which does not exceed the applicable power consumption requirements for off mode and/or standby mode when the equipment is connected to the mains power source.

▼M4

(d) Power management for all equipment other than networked equipment

Equipment shall, unless inappropriate for the intended use, offer a power management function or a similar function. When equipment is not providing the main function, and other energy-using product(s) are not dependent on its functions, the power management function shall switch equipment after the shortest possible period of time appropriate for the intended use of the equipment, automatically into:

— standby mode, or

— off mode, or

▼ M4

- another condition which does not exceed the applicable power consumption requirements for off mode and/or standby mode when the equipment is connected to the mains power source.

The power management function shall be activated.

3. As of 1 January 2015:

(a) Possibility of deactivating wireless network connection(s)

Any networked equipment that can be connected to a wireless network shall offer the user the possibility to deactivate the wireless network connection(s). This requirement does not apply to products which rely on a single wireless network connection for intended use and have no wired network connection.

(b) Power management for networked equipment

Equipment shall, unless inappropriate for the intended use, offer a power management function or a similar function. When equipment is not providing a main function, and other energy-using product(s) are not dependent on its functions, the power management function shall switch equipment after the shortest possible period of time appropriate for the intended use of the equipment, automatically into a condition having networked standby.

In a condition providing networked standby, the power management function may switch equipment automatically into standby mode or off mode or another condition which does not exceed the applicable power consumption requirements for standby and/or off mode.

The power management function, or a similar function, shall be available for all network ports of the networked equipment.

The power management function, or a similar function, shall be activated, unless all network ports are deactivated. In that latter case the power management function, or a similar function, shall be activated if any of the network ports is activated.

The default period of time after which the power management function, or a similar function, switches the equipment automatically into a condition providing networked standby shall not exceed 20 minutes.

(c) Networked equipment that has one or more standby modes shall comply with the requirements for these standby mode(s) when all network ports are deactivated.

(d) Networked equipment other than HiNA equipment shall comply with the provisions under 2(d) when all network ports are deactivated.

(e) Power consumption in a condition providing networked standby:

The power consumption of HiNA equipment or equipment with HiNA functionality in a condition providing networked standby into which the equipment is switched by the power management function, or a similar function shall not exceed 12,00 W.

The power consumption of other networked equipment in a condition providing networked standby into which the equipment is switched by the power management function, or a similar function, shall not exceed 6,00 W.

▼ M4

The power consumption limits as stipulated in point (e) shall not apply to:

- (i) printing equipment with a power supply of a rated power larger than 750 W;
- (ii) large format printing equipment;
- (iii) tele-presence systems;
- (iv) desktop thin clients;
- (v) workstations;
- (vi) mobile workstations;
- (vii) small-scale servers;
- (viii) computer servers.

4. As of 1 January 2017:

In addition to the requirements set out in point 3(a) and (b), the following provisions shall apply:

- (a) Networked equipment that has one or more standby mode(s) shall comply with the requirements for these standby mode(s) when all wired network ports are disconnected and when all wireless network ports are deactivated.
- (b) Networked equipment other than HiNA equipment shall comply with the provisions under 2(d) when all wired network ports are disconnected and when all wireless network ports are deactivated.
- (c) Power consumption in a condition providing ‘networked standby’:

The power consumption of HiNA equipment or equipment with HiNA functionality, in a condition providing networked standby into which the equipment is switched by the power management function, or a similar function, shall not exceed 8,00 W.

The power consumption of other networked equipment in a condition providing networked standby into which the equipment is switched by the power management function, or a similar function, shall not exceed 3,00 W.

The power consumption limits as stipulated in point (c) shall not apply to:

- (i) large format printing equipment;
- (ii) desktop thin clients;
- (iii) workstations;
- (iv) mobile workstations;
- (v) small-scale servers;
- (vi) computer servers.

5. As of 1 January 2019:

In addition to the requirements set out in point 3(a) and (b) and point 4(a), (b) and (c), the following provision shall apply for networked equipment other than HiNA equipment or other than equipment with HiNA-functionality:

▼ M4

The power consumption of networked equipment other than HiNA equipment or other than equipment with HiNA functionality, in a condition providing networked standby into which the equipment is switched by the power management function, or a similar function, shall not exceed 2,00 W.

6. As of 1 January 2015:

For coffee machines, the delay time after which the product switches automatically into the modes and conditions referred to in Annex II, point 2, paragraph (d) shall be as follows:

- for domestic drip filter coffee machines storing the coffee in an insulated jug, a maximum of five minutes after completion of the last brewing cycle or 30 minutes after completion of a descaling or self-cleaning process,
- for domestic drip filter coffee machines storing the coffee in a non-insulated jug, a maximum of 40 minutes after completion of the last brewing cycle, or 30 minutes after completion of a descaling or self-cleaning process,
- for domestic coffee machines other than drip filter coffee machines, a maximum of 30 minutes after completion of the last brewing cycle, or a maximum of 30 minutes after activation of the heating element, or a maximum of 60 minutes after activation of the cup preheating function, or a maximum of 30 minutes after completion of a descaling or self-cleaning process, unless an alarm has been triggered requiring users' intervention to prevent possible damage or accident.

Until the above date the ecodesign requirements set out in Annex II.2.d shall not apply.

7. Product information requirements

As of 1 January 2015, the following information for networked equipment shall be visibly displayed on manufacturers' freely accessible websites:

- (a) for each standby and/or off mode and the condition providing networked standby into which the equipment is switched by the power management function or similar function:
 - the power consumption data in Watt rounded to the first decimal place,
 - the period of time after which the power management function, or a similar function, switches the equipment automatically into standby and/or off mode and/or the condition providing networked standby;
- (b) the power consumption of the product in networked standby if all wired network ports are connected and all wireless network ports are activated;
- (c) guidance on how to activate and deactivate wireless network ports.

The power consumption of the product in networked standby as referred to in point (b) and the guidance as referred to in point (c) shall also be included in the user manual.

▼ M4

8. Measurements

The power consumption referred to in point 1(a) and (b), point 2(a) and (b), points 3(e) and 4(c) and point 5, and the delay times referred to in point 6, shall be established by a reliable, accurate and reproducible measurement procedure, which takes into account the generally recognised state of the art.

9. Information to be provided by manufacturers

For the purposes of conformity assessment pursuant to Article 4, the technical documentation shall contain the following elements:

(a) for each standby and/or off mode:

- the power consumption data in Watt rounded to the first decimal place,
- the measurement method used,
- a description of how the equipment mode was selected or programmed,
- the sequence of events leading to the condition where the equipment automatically changes modes,
- any notes regarding the operation of the equipment, e.g. information on how the user switches the equipment into a condition having networked standby,
- if applicable, the default time after which the power management function, or similar function, has switched the equipment into the applicable low power mode or condition;

(b) for networked equipment:

- the number and type of network ports and, with the exception of wireless network ports, where these ports are located on the equipment; in particular it shall be declared if the same physical network port accommodates two or more types of network ports,
- whether all network ports are deactivated before delivery,
- whether the equipment qualifies as HiNA equipment or equipment with HiNa functionality; where no information is provided, this is considered not to be the case;

and for each type of network port:

- the default time after which the power management function, or a similar function, switches the equipment into a condition providing networked standby,
- the trigger that is used to reactivate the equipment,
- the (maximum) performance specifications,
- the (maximum) power consumption of the equipment in a condition providing networked standby into which the power management function, or a similar function, will switch the equipment, if only this port is used for remote activation,
- the communication protocol used by the equipment;

If no information is provided, the equipment is considered not to be networked equipment unless it provides the functionalities of a router, network switch, wireless network access point (not being a terminal), hub, modem, VoIP telephone, video phone.

▼ M4

- (c) test parameters for measurements:
- ambient temperature,
 - test voltage in V and frequency in Hz,
 - total harmonic distortion of the electricity supply system,
 - information and documentation on the instrumentation, set-up and circuits used for electrical testing;
- (d) the equipment characteristics relevant for assessing conformity with the requirements set out in point 1(c), or the requirements set out in points 2(c) and/or 2(d) and/or 3(b), as applicable, including the time taken to automatically reach standby, or off mode, or another condition which does not exceed the applicable power consumption requirements for off mode and/or standby mode.

In particular, if applicable, a technical justification shall be provided that the requirements set out in point 1(c), or the requirements set out in points 2(c) and/or 2(d) and/or 3(b), are inappropriate for the intended use of equipment. The need to maintain one or more network connections or to wait for a remotely initiated trigger is not considered a technical justification for exemption from the requirements set out in 2(d) in the case of equipment that is not defined as networked equipment by the manufacturer.

*ANNEX III***Product compliance verification by market surveillance authorities**

The verification tolerances defined in this Annex relate only to the verification of the measured parameters by Member State authorities and shall not be used by the manufacturer or importer as an allowed tolerance to establish the values in the technical documentation or in interpreting these values with a view to achieving compliance or to communicate better performance by any means.

1. VERIFICATION PROCEDURE

When verifying the compliance of a product model with the requirements laid down in this Regulation pursuant to Article 3(2) of Directive 2009/125/EC, for the requirements referred to in this Annex, the authorities of the Member States shall apply the following procedure:

- (1) The Member State authorities shall verify one single unit of the model.
- (2) The model shall be considered to comply with the applicable requirements if:
 - (a) the values given in the technical documentation pursuant to point 2 of Annex IV to Directive 2009/125/EC (declared values), and, where applicable, the values used to calculate these values, are not more favourable for the manufacturer or importer than the results of the corresponding measurements carried out pursuant to paragraph (g) thereof; and
 - (b) the declared values meet any requirements laid down in this Regulation, and any required product information published by the manufacturer or importer does not contain values that are more favourable for the manufacturer or importer than the declared values; and
 - (c) when the Member State authorities test the unit of the model, the determined values (the values of the relevant parameters as measured in testing and the values calculated from these measurements) comply with the respective verification tolerances as given in the table below.
- (3) If the results referred to in point 2(a) or (b) are not achieved, the model shall be considered not to comply with this Regulation.
- (4) If the result referred to in point 2(c) is not achieved, the Member State authorities shall select three additional units of the same model for testing.
- (5) The model shall be considered to comply with the applicable requirements if, for these three units, the arithmetical mean of the determined values complies with the respective verification tolerances given in the table below.
- (6) If the result referred to in point 5 is not achieved, the model shall be considered not to comply with this Regulation.
- (7) The Member State authorities shall provide all relevant information to the authorities of the other Member States and to the Commission without delay after a decision being taken on the non-compliance of the model according to points 3 and 6.

▼ **M5**

The Member State authorities shall use the measurement and calculation methods set out in point 8 of Annex II and in part 2 of this Annex. The Member State authorities shall only apply the verification tolerances that are set out in the table below and shall only use the procedure described in points 1 to 7 for the requirements referred to in this Annex. No other tolerances, such as those set out in harmonised standards or in any other measurement method, shall be applied.

Verification tolerances

Type of requirement	Category	Tolerance
Annex II, points 1(a) and (b), or points 2(a) and (b)	For power consumption requirements above 1,00 W	The determined value shall not exceed the declared value by more than 10 %.
	For power consumption requirements less than or equal to 1,00 W	The determined value shall not exceed the declared value by more than 0,10 W.
Annex II, points 3(c) and 4(a)	n/a	The determined value shall not exceed the declared value by more than 10 %.

2. TEST PROCEDURE FOR NETWORKED EQUIPMENT

To test compliance with the requirements set out in points 3(c) and 4(a) of Annex II, Member State authorities shall use the procedure set out in part 1 of this Annex, after having deactivated and/or disconnected, as applicable, all network ports of the unit.

To test compliance with the other requirements set out in points 3 and 4 of Annex II, Member State authorities shall test one single unit as follows:

If the equipment has, as indicated in the technical documentation, one type of network port and if two or more ports of that type are available, one of these ports is randomly chosen and that port is connected to the appropriate network complying with the maximum specification of the port. In the event of multiple wireless network ports of the same type, the other wireless ports shall be deactivated if possible. In the event of multiple wired network ports of the same type for verifying requirements set out in Annex II, point 3, the other network ports shall be deactivated if possible. If only one network port is available, that port is connected to the appropriate network complying with the maximum specification of the port.

The unit is put in on mode. Once the unit in on mode is working properly, it is allowed to go into the condition providing networked standby and the power consumption is measured. Then the appropriate trigger is given to the equipment through the network port and a check is made on whether the equipment is reactivated.

If the equipment has, as indicated in the technical documentation, more than one type of network port for each type of network port the following procedure is repeated. If two or more network ports of a type are available, one port is chosen randomly for each type of network port and that port is connected to the appropriate network complying with the maximum specification of the port.

If for a certain type of network port only one port is available, that port is connected to the appropriate network complying with the maximum specification of the port. Wireless ports not used shall be deactivated if possible. In the event of verification of requirements set out in Annex II, point 3, the wired network ports not used shall be deactivated if possible.

▼ M5

The unit is put in on mode. Once the unit in on mode is working properly, it is allowed to go into the condition providing networked standby and the power consumption is measured. Then the appropriate trigger is given to the equipment through the network port and a check is made whether the equipment is reactivated. If one physical network port is shared by two or more types of (logical) network ports this procedure is repeated for each type of logical network port, with the other logical network ports being logical-disconnected.

▼ B*ANNEX IV***Benchmarks**

The following benchmarks are identified for the purpose of Annex I, Part 3, point 2, to Directive 2005/32/EC:

Off mode: 0 W-0,3 W with hard-off switch on the primary side, depending, *inter alia*, on the characteristics related to electromagnetic compatibility pursuant to Directive 2004/108/EC.

Standby — reactivation function: 0,1 W.

Standby — display: simple displays and low power LEDs 0,1 W, larger displays (e.g. for clocks) require more power.

▼ M4

Networked standby: 3 W for HiNA equipment; 1 W or less for non-HiNA equipment.