This text is meant purely as a documentation tool and has no legal effect. The Union's institutions do not assume any liability for its contents. The authentic versions of the relevant acts, including their preambles, are those published in the Official Journal of the European Union and available in EUR-Lex. Those official texts are directly accessible through the links embedded in this document

$ightharpoonup \underline{B}$ COMMISSION IMPLEMENTING REGULATION (EU) 2019/1916

of 15 November 2019

laying down detailed provisions as regards the use of rear aerodynamic devices pursuant to Council Directive 96/53/EC

(OJ L 297, 18.11.2019, p. 3)

Amended by:

Official Journal

		No	page	date
► <u>M1</u>	Commission Implementing Regulation (EU) 2020/349 of 2 March 2020	L 63	1	3.3.2020

COMMISSION IMPLEMENTING REGULATION (EU) 2019/1916

of 15 November 2019

laying down detailed provisions as regards the use of rear aerodynamic devices pursuant to Council Directive 96/53/EC

Article 1

Subject matter

This Regulation lays down detailed provisions for the use of aerodynamic rear devices mounted on vehicles and vehicle combinations in accordance with Directive 96/53/EC.

Article 2

Definitions

For the purposes of this Regulation, the following definitions apply:

- (a) 'devices' means aerodynamic devices mounted at the rear of vehicles or vehicle combinations;
- (b) 'in-use position' means the position of devices in a deployed aerodynamic drag-reducing position;
- (c) 'closed position' means the position of devices in a folded or retracted position, which is safely secured.

Article 3

Operational conditions

▼M1

1. Member States may prohibit the circulation of vehicles or vehicle combinations equipped with devices in the in-use position in view of the special characteristics of urban or interurban areas where speed limits are 50 km/h or lessand where vulnerable road users are likely to be present.

▼B

- 2. The devices shall be in the closed position in situations or areas where special attention or consideration is necessary. This may occur:
- (a) while manoeuvring, reversing or parking the vehicle;
- (b) when the vehicle is parked;
- (c) while loading or unloading goods.
- 3. The use of devices in intermodal transport operations shall be subject to the following requirements:
- (a) in preparation of and during intermodal transport the devices shall be in the closed position;

- (b) the devices shall not protrude more than 25 mm on each side of the vehicle and the total width of the vehicle including the devices shall not exceed 2 600 mm;
- 4. Defective, unsafe or malfunctioning devices shall be kept in the closed position or, where possible, immediately removed.
- 5. By way of exception to paragraphs 2 and 3(a), devices are not required to be in the closed position where, in accordance with Part B point 1.3.1.1.3, Part C point 1.3.1.1.3, and Part D point 1.4.1.1.3 of Annex I to Regulation (EU) No 1230/2012, they are not required to be retractable or foldable if the maximum dimensional requirements are complied with under all conditions.

Article 4

Entry into force

This Regulation shall enter into force on the twentieth day following that of its publication in the Official Journal of the European. Union

This Regulation shall be binding in its entirety and directly applicable in all Member States.Union