

## I

*(Acts whose publication is obligatory)*

## COUNCIL REGULATION (EC) No 1359/98

of 29 June 1998

amending the Annex to Council Regulation (EC) No 1255/96 temporarily suspending the autonomous Common Customs Tariff duties on certain industrial and agricultural products

THE COUNCIL OF THE EUROPEAN UNION,

HAS ADOPTED THIS REGULATION:

Having regard to the Treaty establishing the European Community, and in particular Article 28 thereof,

Having regard to the proposal from the Commission,

Whereas it is in the interest of the Community to suspend partially or totally the autonomous Common Customs Tariff duties for a number of new products not listed in the Annex to Regulation (EC) No 1255/96 <sup>(1)</sup>;

Whereas the products referred to in the said Regulation, for which it is no longer in the Community's interest to maintain suspension of autonomous Common Customs Tariff duties or for which it is necessary to amend the description in the light of technical developments, must be withdrawn from the list in the Annex thereto;

Whereas, for the sake of clarity, products whose description requires amendment should be regarded as new products,

*Article 1*

The products set out in Annex I to this Regulation shall be added to the Annex to Regulation (EC) No 1255/96. The autonomous Common Customs Tariff duties on these products shall be suspended at the rate indicated for each product.

*Article 2*

The products for which the codes are set out in Annex II to this Regulation shall be removed from the Annex to Regulation (EC) No 1255/96.

*Article 3*

This Regulation shall enter into force on the day of its publication in the *Official Journal of the European Communities*.

It shall apply with effect from 1 July 1998.

This Regulation shall be binding in its entirety and directly applicable in all Member States.

Done at Luxembourg, 29 June 1998.

*For the Council*

*The President*

R. COOK

---

<sup>(1)</sup> OJ L 158, 29.6.1996, p. 1. Regulation as last amended by Regulation (EC) No 2590/97 (OJ L 355, 30.12.1997, p. 1).

## ANNEX I

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 2812 90 00	10	Nitrogen trifluoride	0
ex 2825 50 00	10	Copper (I or II) oxide containing by weight 78 % or more of copper and not more than 0,03 % of chloride	0
ex 2837 19 00	10	Zinc cyanide	0
ex 2850 00 20	10	Silane	0
ex 2903 30 10	30	Perfluoroethane	0
ex 2905 19 10 ex 3824 90 95	10 56	Potassium <i>tert</i> -butanolate (potassium <i>tert</i> -butoxide), whether or not in the form of a solution in tetrahydrofuran	0
ex 2905 39 80	20	2-Ethylhexane-1,3-diol	0
ex 2906 19 00	10	Cyclohex-1,4-ylenedimethanol	0
ex 2906 19 00	20	4,4'-Isopropylidenedicyclohexanol	0
ex 2910 90 00 ex 3824 90 95	60 59	1,2-Epoxyoctadecane, of a purity by weight of 82 % or more	0
ex 2912 29 00	10	Terephthalaldehyde	0
ex 2915 90 80	40	Nonanoic acid (pelargonic acid)	0
ex 2916 12 90	20	2-Ethoxyethyl acrylate	0
ex 2916 39 00	40	Vinyl 4- <i>tert</i> -butylbenzoate	0
ex 2917 19 90	50	Glutaric anhydride	0
ex 2921 45 00	20	2-Aminonaphthalene-1,5-disulphonic acid and its sodium salts	0
ex 2922 21 00	20	4-Hydroxy-7-methylaminonaphthalene-2-sulphonic acid	0
ex 2922 29 00	60	3,5-Dichloro-4-(1,1,2,2-tetrafluoroethoxy)aniline	0
ex 2926 90 99	60	Cyanoacetic acid in crystalline form	0
ex 2929 10 90	60	Trimethylhexamethylene diisocyanate, mixed isomers	0
ex 2931 00 95	55	Dimethyl[dimethylsilyldiindenyl]hafnium	0
ex 2931 00 95	60	Trioctylphosphine oxide	0
ex 2934 90 97	70	2,3,5,6-Tetrahydroxy-1,4-diisobutyl-1,4-dioxo-1,4-diphosphinane	0
ex 2934 90 97	75	Tris(2,3-epoxypropyl)-1,3,5-triazinetrione	0
ex 2935 00 90	50	4,4'-Oxydi(benzenesulfonohydrazide)	0

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 3204 19 00	10	Nickel bis{4-methoxy-2-[6-(pentafluoroethylthio)benzothiazol-2-ylazo]-5-(dipropylamino)benzenesulfonate}	0
ex 3208 90 19	20	Copolymer of polyurethane and silicone, in the form of a solution in a mixture of butanone, toluene and cyclohexanone, containing by weight 13 % or more but not more than 16 % of copolymer	0
ex 3402 90 10	30	Non aqueous surface-active preparation, containing: <ul style="list-style-type: none"> <li>– polyethylene glycol alkylphenyl ether,</li> <li>– 2,4,7,9-tetramethyldec-5-yne-4,7-diol</li> <li>and</li> <li>– phosphoric acid esters</li> </ul>	0
ex 3702 43 00	10	Photographic film, of a nominal width of 459, 669 or 761 mm, composed of several layers, including two polyester films, a carbon layer, an adhesive layer, a layer of a copolymer of styrene with acrylonitrile and a release layer	0
ex 3702 44 00	10		
ex 3808 20 80	10	Fungicide in the form of a powder, containing by weight 65 % or more but not more than 75 % of hymexazole (ISO), not put up for retail sale	0
ex 3808 40 20	10	Preparation containing by weight: <ul style="list-style-type: none"> <li>– 58 % or more but not more than 62 % of 1-bromo-3-chloro-5,5-dimethylhydantoin,</li> <li>– 26 % or more but not more than 29 % of 1,3-dichloro-5,5-dimethylhydantoin,</li> <li>– 10 % or more but not more than 12 % of 1,3-dichloro-5-ethyl-5-methylhydantoin,</li> </ul> for the manufacture of swimming pool disinfectants (a)	0
ex 3815 19 90	55	Catalyst consisting of a mixture of metal oxides containing chromium trioxide, fixed on a support of silicon dioxide	0
ex 3815 19 90	60	Catalyst consisting of dichromium trioxide, fixed on a support of aluminium oxide	0
ex 3815 19 90	75	Catalyst consisting of organo-metallic compounds of aluminium and chromium, fixed on a support of silicon dioxide	0
ex 3815 19 90	80	Catalyst consisting of organo-metallic compounds of magnesium and titanium, fixed on a support of silicon dioxide, in the form of a suspension in mineral oil	0
ex 3815 19 90	85	Catalyst consisting of organo-metallic compounds of aluminium, magnesium and titanium, fixed on a support of silicon dioxide, in the form of powder	0
ex 3824 90 95	31	Copper zinc ferrite, coated with a silicone resin, in the form of granules of a size not exceeding 120 micrometres	0
ex 3824 90 95	57	Mixture of trialkylphosphine oxides	0
ex 3824 90 95	58	Platinum oxide fixed on a porous support of aluminium oxide, containing by weight 0,1 % or more but not more than 1 % of platinum and 0,5 % or more but not more than 5 % of ethylaluminium dichloride	0

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 3824 90 95	60	$\alpha$ -Phenoxycarbonyl- $\omega$ -phenoxy poly[oxy(2,6-dibromo-1,4-phenylene)isopropylidene(3,5-dibromo-1,4-phenylene)oxycarbonyl]	0
ex 3901 10 90	20	Polyethylene, in the form of granules, of a specific gravity of 0,925 ( $\pm$ 0,0015), a melt flow index of 0,3 g/10 min ( $\pm$ 0,05 g/10 min), for the manufacture of blown films of a Haze value not exceeding 6 % and an elongation at break (MD/TD) of 210/340 (a)	0
ex 3903 19 00	20	Polystyrene of a molecular weight ( $M_n$ ) not exceeding 5 000	0
ex 3903 90 90	15	Copolymer, entirely of styrene with maleic anhydride, or entirely of styrene with maleic anhydride and an acrylic monomer, also partially esterified, of an average molecular weight ( $M_n$ ) not exceeding 3 000, in one of the forms mentioned in note 6(a) and (b) to Chapter 39	0
ex 3903 90 90 ex 3906 90 90 ex 3911 90 99	40 40 50	Copolymer of styrene with $\alpha$ -methylstyrene and acrylic acid, of a molecular weight ( $M_n$ ) of 500 or more but not exceeding 6 000	0
ex 3903 90 90 ex 3906 90 90	55 45	Copolymer of styrene, methyl methacrylate, butyl acrylate and either acrylic acid or hydroxyethyl methacrylate, of a molecular weight ( $M_n$ ) of 500 or more but not exceeding 6 000	0
ex 3904 40 00	91	Copolymer of vinyl chloride with vinyl acetate and vinyl alcohol, containing by weight: – 87 % or more but not more than 92 % of vinyl chloride, – 2 % or more but not more than 9 % of vinyl acetate and – 1 % or more but not more than 8 % of vinyl alcohol, in one of the forms mentioned in note 6(a) or (b) to Chapter 39, for the manufacture of goods of heading No 3215 or 8523 or for use in the manufacture of coatings for containers and closures of a kind used for preserving food and drink (a)	0
ex 3905 99 90	96	Poly(vinyl formal), in one of the forms mentioned in note 6(b) to Chapter 39, of a molecular weight ( $M_w$ ) of 25 000 or more but not exceeding 150 000 and containing by weight: – 9,5 % or more but not more than 13 % of acetyl groups evaluated as vinyl acetate and – 5 % or more but not more than 6,5 % of hydroxy groups evaluated as vinyl alcohol	0
ex 3906 90 90	30	Copolymer of styrene with hydroxyethyl methacrylate and 2-ethylhexyl acrylate, of a molecular weight ( $M_n$ ) of 500 or more but not exceeding 6 000	0
3907 20 11		Polyethylene glycols	0
ex 3907 20 29	10	Polymer of dextrose, sorbitol and citric or phosphoric acid, containing by weight 90 % or more of dextrose monomer units	0
ex 3907 20 29	20	Poly[oxy-1,4-phenyleneisopropylidene-1,4-phenyleneoxy-(2-hydroxytrimethylene)], of an average molecular weight ( $M_w$ ) of more than 26 000, in one of the forms mentioned in note 6(b) to Chapter 39	0

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 3911 90 99	55	Solution containing: — (36 ± 0,5) % by weight of polyamide with lateral ester groups, — (2 ± 0,5) % by weight of acrylic ester, — (48 ± 0,5) % by weight of 1-methyl-2-pyrrolidone, — (12 ± 0,5) % by weight of bis(2-methoxyethyl) ether, — 500 microgram/kg or less of potassium and — 500 microgram/kg or less of iron, for use in the manufacture of goods of heading No 8542 (a)	0
ex 3919 90 31 ex 3920 62 19 ex 3920 62 90 ex 3920 63 00 ex 3920 69 00	40 20 20 30 30	Reflecting polyester sheeting embossed in a regular pyramidal pattern, for the manufacture of safety stickers and badges, safety clothing and accessories thereof, or of school satchels, bags or similar containers (a)	0
ex 3920 62 19	80	Matt film of polyethylene terephthalate, of a gloss of 15 at an angle of 45° and 18 at an angle of 60° (as determined by the ASTM D 523 method) and a width of 1 600 mm or more	0
ex 3920 62 19	85	Film of a thickness of 4,5 µm (± 0,16 µm), consisting of a biaxially-oriented polyethylene terephthalate film, of a thickness of 4,4 µm, an elastic module (in the machine direction) of 12 kg/mm <sup>2</sup> (± 2 kg/mm <sup>2</sup> ) and a tensile strength (in the machine direction) of more than 28 kg/mm <sup>2</sup> , and of an anti-adherent coating of a thickness of 0,1 µm	0
ex 3920 62 19	87	Polyethylene terephthalate film, coated with a wax layer, a scratch resistant layer and a thermoadhesive layer, of a nominal width of 790 mm and a total thickness of 23 µm or more but not exceeding 26 µm	0
ex 3920 62 19	89	Multilayer film of a thickness not exceeding 150 micrometres, consisting of a polyester film coated on one side with polycarbonate resin, metallised on the other side with titanium coated with polycarbonate resin and other layers containing N,N'-diphenyl-N,N'-di- <i>m</i> -tolylbiphenyl-4,4'-ylenediamine	0
ex 3920 99 29	10	Reflecting sheet of metallised polyurethane, containing glass beads, coated with a hot-melt adhesive layer, covered on one or both sides with a release sheet, in rolls of a width of 1 020 mm (± 20 mm), for slitting into safety clothing reflecting strip (a)	0
ex 3926 90 99	10	Microspheres of polymer of divinylbenzene, of a diameter of 4,5 µm or more but not exceeding 8,5 µm	0
ex 5402 43 00	20	Synthetic bicomponent filament yarn, not textured, untwisted, measuring 1 650 decitex, consisting of 110 filaments each having a core of polyethylene terephthalate and a skin of polyamide-6, containing by weight 75 % or more but not exceeding 77 % of polyethylene terephthalate, for use in the manufacture of roofings (a)	0
ex 5501 90 90	10	Polyvinyl alcohol tow	0
ex 5503 20 00	10	Polyester staple fibres, loaded with zeolite impregnated with a mixture of salts of copper and silver or of salts of zinc and silver	4

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 5503 90 90 ex 5506 90 99 ex 5601 30 00	20 10 10	Polyvinyl alcohol fibres, whether or not acetalised	0
ex 6909 19 00 ex 8102 99 00	50 10	Disc (target) with deposition material, consisting of molybdenum silicide, — containing 1 mg/kg or less of sodium and — mounted on a metal support	0
ex 7006 00 90	10	Glass plate, coated on one side with chromium and/or with a mixture of diindium trioxide and tin dioxide, of dimensions of 260 × 320 mm or more but not exceeding 400 × 400 mm, of a thickness not exceeding 1,2 mm, for the manufacture of liquid crystal displays (a)	0
ex 7006 00 90	20	Colour filter, consisting of a glass plate with red, blue and green pixels, having a total thickness of 1,1 mm ( $\pm$ 0,1 mm) and exterior dimensions of 320 × 352 mm or more but not exceeding 320 × 400 mm, for the manufacture of liquid crystal displays (a)	0
ex 7006 00 90	30	Glass plate, uncoated, of dimensions of 320 × 352 mm or more but not exceeding 320 × 400 mm, of a thickness of 0,6 mm or more but not exceeding 1,2 mm, for the manufacture of liquid crystal displays (a)	0
ex 7011 20 00	40	Glass face-plate: — with a diagonal measurement of 366,4 mm ( $\pm$ 1,5 mm) and dimensions of 246,4 × 315,4 mm ( $\pm$ 1,5 mm), — with a diagonal measurement of 391 mm ( $\pm$ 1,5 mm) and dimensions of 261,4 × 326,8 mm ( $\pm$ 1,5 mm), — with a diagonal measurement of 442 mm ( $\pm$ 1,5 mm) and dimensions of 293,4 × 369,2 mm ( $\pm$ 1,5 mm), — with a diagonal measurement of 544,5 mm ( $\pm$ 1,6 mm) and dimensions of 358 × 454 mm ( $\pm$ 1,6 mm), having a cylindrical curvature, — with a diagonal measurement of 570,5 mm ( $\pm$ 1,6 mm) and dimensions of 360 × 486 mm ( $\pm$ 1,6 mm), — with a diagonal measurement of 629,8 mm ( $\pm$ 3 mm) and dimensions of 406,5 × 519 mm ( $\pm$ 2 mm), having a cylindrical curvature, or — with a diagonal measurement of 753 mm ( $\pm$ 1,6 mm) and dimensions of 471 × 640 mm ( $\pm$ 1,6 mm), and with a raised edge, for the manufacture of colour cathode-ray tubes (a)	0
ex 7616 99 90	50	Discs of aluminium alloy, of a thickness not exceeding 0,84 mm, for the manufacture of goods of subheadings 8523 20 11 and 8523 20 19 (a)	0
ex 8101 99 00	10	Disc (target) with deposition material, of tungsten or an alloy containing by weight 90 % of tungsten and 10 % of titanium, — containing 100 micrograms/kg or less of sodium and — mounted on a copper or aluminium support	0

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 8108 90 90	92	Disc (target) with deposition material, of titanium, — containing 50 micrograms/kg or less of sodium and — mounted on a copper or aluminium support	0
ex 8419 89 98 ex 8543 89 95	20 58	Sputtering machines and apparatus, comprising disc handling equipment, for use in the manufacture of products falling within subheading 8523 20 11 or 8523 20 19 (a)	0
ex 8424 89 95 ex 8460 21 90 ex 8460 40 10 ex 8460 90 90 ex 8464 20 19 ex 8479 89 98	10 10 10 10 10 10	Machines and apparatus providing automated lapping, polishing, grinding, cleaning or surface lubrication of discs, comprising disc handling equipment, for use in the manufacture of products falling within subheading 8523 20 11 or 8523 20 19 (a)	0
ex 8424 89 95 ex 8479 89 98	20 30	Machines and apparatus providing automated cleaning or cleaning and drying of discs, by means of de-ionised water, ultra sonic waves, chemical solutions, heat or a combination of these processes, comprising disc handling equipment, for use in the manufacture of products falling within subheading 8523 20 11 or 8523 20 19 (a)	0
ex 8460 90 90 ex 8463 90 00 ex 8479 89 98	20 10 20	Machine-tool providing automated creation of a texture (a head landing zone) on the surface of discs by means of abrasion or exposure to laser beams, comprising disc handling equipment, for use in the manufacture of products falling within subheading 8523 20 11 or 8523 20 19 (a)	0
ex 8479 89 98 ex 8501 10 99	40 78	Motor, whether or not mounted on a baseplate, for use in the manufacture of products falling within subheading 8525 20 91 or 8527 90 92 (a)	0
ex 8504 50 30 ex 8504 50 80	10 30	Inductor with an inductance not exceeding 62 mH	0
ex 8505 19 90	31	Neodymium-ferro ring with an external diameter not exceeding 13 mm, an internal diameter not exceeding 9 mm and a thickness not exceeding 0,9 mm	0
ex 8507 30 91	30	Cylindrical nickel-cadmium accumulator, with a length of 65,3 mm ( $\pm 1,5$ mm) and a diameter of 14,5 mm ( $\pm 1$ mm), having a nominal capacity of 1 000 mAh or more, for use in the manufacture of rechargeable batteries (a)	0
ex 8517 50 90 ex 8517 80 90	50 50	Receive and transmit unit, only for cables with optical fibres, capable of converting light pulses into electrical signals and converting electrical signals into light pulses, operating at a nominal wavelength of 1 300 nm	0
ex 8522 90 98	43	Analogue sound recording and reproducing assembly, comprising a record/playback head and a twin tape deck mechanism of the cassette type, not comprising circuits with amplification functions or power supply drive functions, for use in the manufacture of products falling within subheading 8527 31 98 (a)	0

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 8529 10 70	80	Ceramic filter package, excluding surface acoustic wave filters, consisting of: <ul style="list-style-type: none"> <li>– a transmit filter with a centre frequency of 1 747,5 MHz and an insertion loss not exceeding 2,3 dB at a bandwidth of 75 MHz</li> <li>and</li> <li>– a receive filter with a centre frequency of 1 842,5 MHz and an insertion loss not exceeding 3,3 dB at a bandwidth of 75 MHz,</li> </ul> the whole contained in a housing	0
ex 8529 10 70	85	Ceramic filter package, excluding surface acoustic wave filters, comprising 2 filters with one of the following combinations of characteristics: <ul style="list-style-type: none"> <li>– a transmit centre frequency of 902,5 MHz, a receive centre frequency of 947,5 MHz and an insertion loss not exceeding 3,2 dB at a bandwidth of 25 MHz</li> <li>or</li> <li>– a transmit centre frequency of 1 747,5 MHz, a receive centre frequency of 1 842,5 MHz and an insertion loss not exceeding 3,5 dB at a bandwidth of 75 MHz,</li> </ul> the whole contained in a housing	0
ex 8534 00 90	95	Bandpass filter for a centre frequency of 1 627,5, 1 743, 1 842,5 or 1 960 MHz, in the form of a printed circuit, only consisting of a ceramic insulating base and of resonance elements, for use in the manufacture of products of subheading 8525 20 91 (a)	0
ex 8534 00 90	96	Bandpass filter for centre frequencies of 732,5 and 947,5 MHz or of 1 627,5 and 1 842,5 MHz or of 1 738 and 1 960 MHz, in the form of a printed circuit, only consisting of a ceramic insulating base and of resonance elements, for use in the manufacture of products of subheading 8525 20 91 (a)	0
ex 8536 30 30 ex 8536 30 90 ex 8536 50 80	11 31 96	Thermo–electric switch with a cut–off current of 50 A or more, comprising a snap action switch, for direct mounting on an electric motor coil, contained in a hermetically sealed housing	0
ex 8536 90 85	94	Elastomeric connector, consisting of one or more conductor elements coated with carbon or gold and of a rubber or silicon substrate	0
ex 8537 10 99	92	Touch sensitive screen panel, consisting of a conductive grid between two glass or plastic plates or sheets, fitted with electric conductors and connectors	0
ex 8540 11 11	91	Colour cathode–ray tube with a slit or slot mask, equipped with electron guns placed side by side (in–line technology) and with a diagonal measurement of the screen of 12 cm or more but not exceeding 26 cm	0



CN code	TARIC	Description	Rate of autonomous duty (%)
ex 8540 11 13	91	Colour cathode-ray tube with a slit or slot mask, having a distance between stripes of the same colour of less than 0,42 mm and a diagonal measurement of the screen of 49 cm, for use in the manufacture of professional video monitors including security and medical monitor applications (a)	0
ex 8540 40 00	33	Colour cathode-ray tube with a slit or slot mask, having a distance between stripes of the same colour of less than 0,35 mm and a diagonal measurement of the screen not exceeding 53 cm	0
ex 8540 40 00	34	Colour cathode-ray tube with a slit or slot mask, having a distance between stripes of the same colour of less than 0,39 mm and a diagonal measurement of the screen of 33 cm or more but not exceeding 38 cm	0
ex 8540 40 00	35	Colour cathode-ray tube with a slit or slot mask, having a distance between stripes of the same colour of less than 0,35 mm and a diagonal measurement of the screen not exceeding 72 cm, for use in the manufacture of monitors (a)	0
ex 8540 40 00	36	Colour cathode-ray tube with a slit or slot mask, having a distance between stripes of the same colour of less than 0,30 mm and a diagonal measurement of the screen not exceeding 58 cm	0
ex 8540 91 00	92	Slit or slot mask, excluding masks with continuously vertical slits, with a diagonal measurement of 39 cm or less	0
ex 8543 89 95	47	An electromagnetic display, consisting of 7 electromagnetic coils which by means of the residual magnetism in the stators provide that the last indication remains available (set state), and 7 pivoting light-reflecting segments each of which is attached to a bars magnet; assembly comprising such displays	0
ex 8543 89 95	59	Charged coupled device (CCD) scanner assembly, for a real-time film scanning system, having optical functions, illumination functions and signal processing functions	0
8548 90 10		Memory in multicombinational forms such as stack D-RAMs and modules	0
ex 9001 10 90	10	Image reverser made up from an assembly of optical fibres	0
ex 9001 90 90	50	Rear projection screen, comprising a lenticular plastic plate	0
ex 9001 90 90	70	Rod of neodymium-doped yttrium-aluminium garnet (YAG) material, polished at both ends	0
ex 9002 90 90	50	Lens and image gate assembly, for a real-time film scanning system, comprising a lens consisting of 9 or 11 elements and having an illumination function	0

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 9024 80 99	10	Machines and apparatus providing automated quality inspection of rigid magnetic discs, for use in the manufacture of products falling within subheading 8523 20 11 or 8523 20 19 (a)	0
ex 9027 30 00	10		
ex 9031 20 00	10		
ex 9031 49 90	10		
ex 9031 80 34	10		
ex 9031 80 39	30		
ex 9031 80 99	10		
ex 9031 90 80	40	Test head for checking the mechanical quality of rigid magnetic discs, mounted on a carrier arm	0
ex 9031 90 80	50	Burnishing head, for removing asperities on and polishing of the surface of rigid magnetic discs, mounted on a carrier arm	0
ex 9032 10 91	10	Thermostat, comprising a snap-action switch, for direct mounting on an electric motor coil, contained in a hermetically sealed housing	0

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

ANEXO II – BILAG II – ANHANG II – ΠΑΡΑΡΤΗΜΑ II – ANNEX II – ANNEXE II – ALLEGATO II –  
 BIJLAGE II – ANEXO II – LIITE II – BILAGA II

Código NC KN-kode KN-Code Κωδικός ΣΟ CN code Code NC Codice NC GN-code Código NC CN-koodi KN-nummer	Taric	Código NC KN-kode KN-Code Κωδικός ΣΟ CN code Code NC Codice NC GN-code Código NC CN-koodi KN-nummer	Taric
ex 2825 50 00	10	ex 5402 33 00	10
ex 2905 19 10	10	ex 5402 43 00	10
ex 2920 90 85	60	ex 5503 90 90	20
ex 2930 90 70	60	ex 5601 30 00	10
ex 2933 69 80	30	ex 7006 00 90	10
ex 3808 20 80	10	ex 7006 00 90	20
ex 3815 19 90	60	ex 7006 00 90	30
ex 3824 90 95	31	ex 7011 20 00	40
ex 3903 19 00	20	ex 8101 99 00	10
ex 3903 90 90	15	ex 8108 90 90	92
ex 3903 90 90	40	ex 8501 10 99	78
ex 3903 90 90	55	ex 8504 50 30	10
ex 3903 90 90	60	ex 8504 50 80	30
ex 3904 40 00	91	ex 8517 50 90	50
ex 3906 90 90	30	ex 8517 80 90	50
ex 3906 90 90	40	ex 8536 90 85	91
ex 3906 90 90	45	ex 8540 11 11	91
ex 3907 20 11	10	ex 8540 11 13	91
ex 3907 20 29	10	ex 8540 40 00	33
ex 3907 20 29	20	ex 8540 40 00	34
ex 3911 90 99	50	ex 8540 91 00	92
ex 3919 90 31	40	ex 8543 89 95	47
ex 3920 62 19	20	ex 9001 10 10	10
ex 3920 62 90	20	ex 9001 10 90	10
ex 3920 63 00	30	ex 9001 90 90	10
ex 3920 69 00	30	ex 9001 90 90	50
ex 3921 90 19	50	ex 9013 90 90	10