

**DIRECTIVE 2000/4/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL
of 28 February 2000**

amending Council Directive 74/60/EEC on the approximation of the laws of the Member States relating to the interior fittings of motor vehicles (interior parts of the passenger compartment other than the interior rear-view mirrors, layout of controls, the roof or sliding roof, the backrest and rear part of the seats)

THE EUROPEAN PARLIAMENT AND THE COUNCIL OF THE EUROPEAN UNION,

Having regard to the Treaty establishing the European Community, and in particular Article 95 thereof,

Having regard to the proposal from the Commission ⁽¹⁾,

Having regard to the opinion of the Economic and Social Committee ⁽²⁾,

Acting in accordance with the procedure laid down in Article 251 of the Treaty ⁽³⁾,

Whereas:

(1) It is desirable to introduce into Council Directive 74/60/EEC ⁽⁴⁾, requirements concerning power-operated windows with the aim of eliminating the danger to children, which can occur when closing these windows; similar requirements should also apply to power-operated roof panel systems and partition systems; for this purpose the title and the scope of Directive 74/60/EEC should be amended accordingly.

(2) Directive 74/60/EEC is one of the separate directives of the EC type-approval procedure which has been established by Council Directive 70/156/EEC of 6 February 1970 on the approximation of the laws of the Member States relating to the type-approval of motor vehicles and their trailers ⁽⁵⁾; consequently, the provisions laid down in Directive 70/156/EEC relating to vehicles, vehicle systems, components and separate technical units apply to Directive 74/60/EEC.

(3) In particular, Articles 3(4) and 4(3) of Directive 70/156/EEC require that each separate Directive has attached to it an information document incorporating the relevant items of Annex I to Directive 70/156/EEC and also a type-approval certificate based on Annex VI to Directive 70/156/EEC in order that type-approval may be computerised.

⁽¹⁾ OJ C 149, 15.5.1998, p. 10.

⁽²⁾ OJ C 407, 28.12.1998, p. 56.

⁽³⁾ Opinion of the European Parliament of 9 February 1999 (OJ C 150, 28.5.1999, p. 26), Council Common Position of 28 October 1999 (OJ C 346, 2.12.1999, p. 17) and Decision of the European Parliament of 3 February 2000.

⁽⁴⁾ OJ L 38, 11.2.1974, p. 2. Directive as amended by Commission Directive 78/632/EEC (OJ L 206, 29.7.1978, p. 26).

⁽⁵⁾ OJ L 42, 23.2.1970, p. 1. Directive as last amended by Directive 98/91/EC of the European Parliament and of the Council (OJ L 11, 16.1.1999, p. 25).

(4) It is important that vehicles in categories other than M₁, in particular those in categories M₂ and N₁, are able at the earliest opportunity to afford the driver and passengers, more particularly children, the level of safety provided by Directive 74/60/EEC; to that end it should be made possible for the scope of Directive 74/60/EEC to be extended to cover such vehicles in accordance with the procedure laid down in Article 13 of Directive 70/156/EEC.

(5) The amendments to Directive 74/60/EEC relate only to its administrative provisions and to power-operated windows, roof panel and/or partition systems; it is not necessary therefore to invalidate existing approvals granted under Directive 74/60/EEC nor to prevent the registration, sale and entry into service of new vehicles, which are not fitted with power-operated windows, roof panel and/or partition systems and which are covered by such approvals.

(6) In accordance with the principle of proportionality as set out in the third paragraph of Article 5 of the Treaty, the measures contained in this Directive do not go beyond what is necessary to achieve the objectives of the Treaty,

HAS ADOPTED THIS DIRECTIVE:

Article 1

Directive 74/60/EEC is hereby amended as follows:

1. The title shall be replaced by the following:

‘Council Directive 74/60/EEC of 17 December 1973 on the approximation of the laws of the Member States relating to the interior fittings of motor vehicles.’

2. Articles 1, 2 and 3 shall be replaced by the following:

‘Article 1

For the purpose of this Directive, “vehicle” means any vehicle as defined in Article 2 of Directive 70/156/EEC.

Article 2

No Member State may refuse to grant EC type-approval or national type-approval of a vehicle on grounds relating to the interior fittings of the vehicles if these meet the requirements set out in the Annexes hereto.

Article 3

No Member State may refuse to register or prohibit the sale, entry into service or use of any vehicle on grounds relating to the interior fittings of the vehicles if these meet the requirements set out in the Annexes.'

3. Articles 4 and 5 shall be deleted.
4. The Annexes shall be amended in accordance with the Annex to this Directive.

Article 2

1. With effect from 8 April 2001, Member States may not, on grounds relating to the interior fittings of the motor vehicles,

- refuse, in respect of a type of vehicle, to grant EC type-approval or national type-approval, or
- prohibit the registration, sale or entry into service of vehicles,

if the vehicles comply with the requirements of Directive 74/60/EEC.

2. With effect from 8 April 2002, Member States shall no longer grant EC type-approval for a new type of vehicle on grounds relating to the interior fittings of the motor vehicles if the requirements of Directive 74/60/EEC are not complied with.

3. With effect from 8 April 2003, Member States:

- shall consider certificates of conformity which accompany new vehicles in accordance with the provisions of Directive 70/156/EEC to be no longer valid for the purposes of Article 7(1) of that Directive, and
- may refuse the registration, sale and entry into service of new vehicles which are not accompanied by a certificate of conformity unless Article 8(2) of Directive 70/156/EEC is invoked,

on grounds relating to the interior fittings of motor vehicles if the vehicles are fitted with power-operated windows, roof

panel and/or partition systems and the requirements of Directive 74/60/EEC, are not complied with.

4. This Directive will not invalidate any approval for types of vehicles which are not fitted with power-operated windows, roof panel and/or partition systems previously granted under Directive 74/60/EEC nor prevent extensions of such approvals under the terms of the Directive under which they were originally granted.

Article 3

1. Member States shall bring into force the laws, regulations and administrative provisions necessary to comply with this Directive before 8 April 2001 and shall forthwith inform the Commission thereof.

2. When Member States adopt these measures, they shall contain a reference to this Directive or shall be accompanied by such reference on the occasion of their official publication. The methods of making such reference shall be laid down by the Member States.

3. Member States shall communicate to the Commission the texts of the main provisions of national law which they adopt in the field governed by this Directive.

Article 4

This Directive shall enter into force on the day of its publication in the *Official Journal of the European Communities*.

Article 5

This Directive is addressed to the Member States.

Done at Brussels, 28 February 2000.

For the European Parliament

The President

N. FONTAINE

For the Council

The President

J. PINA MOURA

ANNEX

AMENDMENTS TO THE ANNEXES TO DIRECTIVE 74/60/EEC

1. The following List of Annexes shall be inserted between the Articles and Annex I:

LIST OF ANNEXES

ANNEX I:	Scope, definitions, application for EC type-approval of a vehicle type, specifications, granting of EC type-approval of a vehicle type, modifications of the type and amendments to approvals and conformity of production
	Appendix 1: Information document
	Appendix 2: EC type-approval certificate
	Appendix 3: Position of cylindrical test rod in the opening roof and window openings
	Appendix 4: Symbol for driver controlled switch
ANNEX II:	Determination of the head-impact zone
ANNEX III:	Procedure for testing energy-dissipating materials
ANNEX IV:	Procedure for determining the H point and the actual seat-back angle and for verifying the relative positions of the R and H points and the relationship between the design seat-back angle and the actual seat-back angle
	Appendix: Components of three-dimensional manikin and dimensions and mass of manikin
ANNEX V:	Method of measuring projections
	Appendix: Apparatus for measuring projections
ANNEX VI:	Apparatus and procedure for application of Item 5.2.1 of Annex I'

2. Annex I is amended as follows.

(a) Footnote 1 is deleted.

(b) The title is replaced by the following:

'SCOPE, DEFINITIONS, APPLICATION FOR EC TYPE-APPROVAL OF A VEHICLE TYPE, SPECIFICATIONS, GRANTING OF EC TYPE-APPROVAL OF A VEHICLE TYPE, MODIFICATIONS OF THE TYPE AND AMENDMENTS TO APPROVALS AND CONFORMITY OF PRODUCTION'.

(c) Item 1 is replaced by the following:

'1. SCOPE

This Directive applies to vehicles of category M₁ as defined in Annex II, Section A to Directive 70/156/EEC'.

(d) Items 2.1 and 2.2 are replaced by the following:

'2.1. "Interior fittings" are:

2.1.1. interior parts of the passenger compartment other than the interior rear-view mirrors;

2.1.2. the layout of the controls;

2.1.3. the roof or opening roof;

2.1.4. the backrest and the rear part of the seats;

2.1.5. power-operated windows, roof panel and partition systems.

2.2. "Vehicle type" with respect to the interior fittings of a passenger compartment means motor vehicles which do not differ in such essential respects as:'.

- (e) The following items are inserted:
- ‘2.2.3. the roof or opening roof;
 - 2.2.4. the backrest and the rear part of the seats;
 - 2.2.5. power-operated windows, roof panel and partition systems’.
- (f) The following items are inserted:
- ‘2.10. “Power-operated windows” means windows which are closed by power supply of the vehicle.
 - 2.11. “Power-operated roof-panel systems” means movable panels in the vehicle roof which are closed by power supply of the vehicle by either a sliding or tilting motion, and which do not include convertible top systems.
 - 2.12. “Power-operated partition systems” means systems which divide a passenger car compartment into at least two sections and which are closed using the power supply of the vehicle.
 - 2.13. “Opening” is the maximum unobstructed aperture between the upper edge or the leading edge, depending on the closing direction, of a power-operated window or partition or roof panel and the vehicle structure which forms the boundary of the window, partition or roof panel, when viewed from the interior of the vehicle or, in the case of partition system, from the rear part of the passenger compartment.
- To measure an opening, a cylindrical test rod shall (without exerting force) be placed through it normally perpendicular to the window, roof panel or partition as shown in Figure 1, from the interior of the vehicle or, as applicable, from the rear part of passenger compartment’.
- (g) Items 3 to 3.3 are replaced by the following:
- ‘3. APPLICATION FOR EC TYPE-APPROVAL OF A VEHICLE TYPE
 - 3.1. The application for EC type-approval pursuant to Article 3(4) of Directive 70/156/EEC of a vehicle type with regard to its interior fittings shall be submitted by the manufacturer.
 - 3.2. A model of the information document is given in Appendix 1.
 - 3.3. The following must be submitted to the technical service responsible for conducting the type-approval tests:’.
- (h) The following items are inserted:
- ‘5.5.2. *Power-operated roof-panel systems*
 - 5.5.2.1. In addition, power-operated roof-panel systems and their controls shall meet the requirements of Item 5.8 below’.
- (i) Items 5.8 and 5.8.1 are renumbered as Items 5.9 and 5.9.1.
- (j) The following items are inserted:
- ‘5.8. **Power-operated windows, roof-panel systems and partition systems**
 - 5.8.1. The requirements below apply to power-operated windows/roof-panel systems/partition systems to minimise the possibility of injuries caused by accidental or improper operation.
 - 5.8.2. *Normal operating requirements*
- Except as provided in Item 5.8.3, power-operated windows/roof-panel systems/partition systems may be closed under one or more of the following conditions:
- 5.8.2.1. when the ignition key is inserted in the ignition control in any position of use;
 - 5.8.2.2. by muscular force unassisted by power supply of the vehicle;
 - 5.8.2.3. on continuous activation by a locking system on the outside of the vehicle;
 - 5.8.2.4. during the interval of time between the moment the ignition has been switched from “on” to “off” and/or the key has been removed and the moment that neither of the two front doors has been opened sufficiently to permit egress of occupants;
 - 5.8.2.5. when the closing movement of a power-operated window, roof panel or partition starts at an opening not exceeding 4 mm;

- 5.8.2.6. when the power-operated window of a vehicle's door without an upper door frame closes automatically whenever the pertinent door is closed. In this case the maximum opening, as defined in Item 2.13, prior to window closing, shall not exceed 12 mm.
- 5.8.2.7. Remote closing shall be allowed by continuous activation of a remote actuation device, provided one of the following conditions is fulfilled:
- 5.8.2.7.1. the remote actuation device shall be incapable of closing the power-operated window/roof panel/partition from a distance of more than 11 metres from the vehicle;
- 5.8.2.7.2. the remote actuation device shall be incapable of closing the power-operated window/roof panel/partition:
- if the actuation device and the vehicle are separated by an opaque surface
 - and
 - if from the distance between the remote actuation device and the vehicle is more than 6 metres.
- 5.8.2.8. One-touch closing shall be permitted only for the power-operated window of the driver's door and the roof panel, and only during the time when the ignition key is in the engine running position.
- 5.8.3. *Auto-reversing requirements*
- 5.8.3.1. None of the requirements in Item 5.8.2 shall apply if a power-operated window/roof panel system/partition is fitted with an auto-reversing device.
- 5.8.3.1.1. This device shall reverse the window/roof panel/partition before it exerts a pinch force of more than 100 N within the opening of 200 mm to 4 mm above the top edge of a power-operated window/partition or in front of the leading edge of a sliding roof panel and at the trailing edge of a tilting roof panel.
- 5.8.3.1.2. After such an auto-reversal, the window or roof panel or partition shall open to one of the following positions:
- 5.8.3.1.2.1. a position that permits a semi-rigid cylindrical rod of a diameter of 200 mm to be placed through the opening at the same contact point(s) used to determine the reversing behaviour in Item 5.8.3.1.1;
- 5.8.3.1.2.2. a position that represents at least the initial position before closing was initiated;
- 5.8.3.1.2.3. a position at least 50 mm more open than the position at the time when reversing was initiated;
- 5.8.3.1.2.4. in the case of tilting motion of a roof panel, the maximum angular opening.
- 5.8.3.1.3. To check power-operated windows/roof-panel systems/partition systems with reversing devices, a measuring instrument/test rod shall be placed through the opening from the inside of the vehicle or, in the case of a partition system, from the rear part of the passenger compartment in such a way that the cylindrical surface of the rod contacts any part of the vehicle structure which forms the boundary of the window/roof-panel aperture/partition. The force deflection ratio of the measuring instrument shall be not more than 10 N/mm. The position of the test rods (normally located perpendicular to the window/roof panel/-partition) are illustrated in Appendix 3, Figure 1.
- 5.8.4. *Switch location and operation*
- 5.8.4.1. Switches of power-operated windows/roof panels/partitions shall be located or operated in such a way to minimise the risk of accidental closing. The switches shall require continuous actuation for closing except in the case of Items 5.8.2.6, 5.8.2.8 or 5.8.3.
- 5.8.4.2. All rear-window, roof-panel and partition switches intended for use by occupants in the rear of the vehicle shall be capable of being switched off by a driver-controlled switch which is located forward of a vertical transverse plane passing through the R points of the front seats. The driver controlled switch is not required if a rear window, roof panel or partition is equipped with an auto-reversing device. If, however, the driver-controlled switch is present, it shall not be able to override the auto-reversing device.

The driver-controlled switch shall be located so as to minimise any accidental manipulating. It shall be identified by the symbol shown in Appendix 4.

5.8.5. *Protection devices*

All protection devices which are used to prevent damage to the power source in the case of an overload or stalling shall be capable of resetting automatically while the switch controlling the window/roof panel/partition is activated.

5.8.6. *Handbook instructions*

5.8.6.1. The owner's manual of the vehicle shall contain clear instructions relating to the power-operated window/roof panel/partition, including:

5.8.6.1.1. explanation of possible consequences (entrapment),

5.8.6.1.2. use of the driver-controlled switch,

5.8.6.1.3. a "WARNING" message indicating the dangers, particularly to children in the case of improper use/activation of the power-operated windows/roof-panel systems/partition systems. This information should indicate the responsibilities of the driver, including instructions for other occupants and the recommendation to leave the vehicle only if the key is removed from the ignition lock,

5.8.6.1.4. a "WARNING" message indicating that special care should be taken when using remote closing systems (see Item 5.8.2.7), for example to actuate it only when the operator has a clear view of the vehicle to be sure that nobody can be trapped by power-operated windows/roof-panel/partition equipment'.

(k) Items 6, 7 and 8 are replaced by the following:

‘6. GRANTING OF EC TYPE-APPROVAL OF A VEHICLE TYPE

6.1. If the relevant requirements are satisfied, EC type-approval shall be granted pursuant to Article 4(3) of Directive 70/156/EEC.

6.2. A model for the EC type-approval certificate is given in Appendix 2.

6.3. An approval number in accordance with Annex VII to Directive 70/156/EEC shall be assigned to each type of vehicle approved. The same Member State shall not assign the same number to another type of vehicle.

7. MODIFICATIONS OF THE TYPE AND AMENDMENTS TO APPROVALS

7.1. In the case of modifications of the type approved pursuant to this Directive, the provisions of Article 5 of Directive 70/156/EEC shall apply.

8. CONFORMITY OF PRODUCTION

8.1. Measures to ensure the conformity of production shall be taken in accordance with the provisions laid down in Article 10 to Directive 70/156/EEC'.

(l) The following Appendices are inserted:

*Appendix 1***INFORMATION DOCUMENT No ...****Pursuant to Annex I of Council Directive 70/156/EEC ⁽¹⁾ relating to EC-type-approval of a vehicle with respect to the interior fittings****(Directive 74/60/EEC, as last amended by Directive 2000/4/EC)**

The following information, if applicable, must be supplied in triplicate and include a list of contents. Any drawings must be supplied in appropriate scale and in sufficient detail on size A4 or on a folder of A4 format. Photographs, if any, must show sufficient detail. If the systems, components or separate technical units have electronic controls, information concerning their performance must be supplied.

- 0. GENERAL
 - 0.1. Make (trade name of manufacturer):
 - 0.2. Type:
 - 0.3. Means of identification of type, if marked on the vehicle (b):
 - 0.3.1. Location of that marking:
 - 0.4. Category of vehicle (c):
 - 0.5. Name and address of manufacturer:
 - 0.8. Address(es) of assembly plant(s):
- 9. BODYWORK
 - 9.10. Interior fittings
 - 9.10.1. Interior protection for occupants
 - 9.10.1.1. Layout drawing or photographs showing the position of the attached sections or views:
 - 9.10.1.2. Photographs or drawing showing the reference line including the exempted area (Annex I, Item 2.3.1 to Directive 74/60/EEC):
 - 9.10.1.3. Photographs, drawings and/or an exploded view of the interior fittings, showing the parts in the passenger compartment and the materials used, (with the exception of interior rear-view mirrors,) arrangement of controls, roof and opening roof, backrest, seats and the rear part of seats:
 - 9.10.3. Seats
 - 9.10.3.5. Coordinates or drawing of the R point ^(*)
 - 9.10.3.5.1. Driver's seat:
 - 9.10.3.5.2. All other seating positions:
 - 9.10.3.6. Design seat back angle
 - 9.10.3.6.1. Driver's seat:
 - 9.10.3.6.2. All other seating positions:

.....
(Date, file)

⁽¹⁾ The item numbers and footnotes used in this information document correspond to those set out in Annex I to Directive 70/156/EEC. Items not relevant for the purpose of this document are omitted.

Appendix 2

MODEL

(maximum format: A4 (210 mm x 297 mm))

EC TYPE-APPROVAL CERTIFICATE



Communication concerning the

- type-approval (1),
- extension of type-approval (1),
- refusal of type-approval (1),
- withdrawal of type-approval (1),

of a type of a vehicle/component/separate technical unit (1) with regard to Directive 74/60/EEC, as last amended by Directive 2000/4/EC

Type-approval number:

Reason for extension:

Section I

- 0.1. Make (trade name of manufacturer):
0.2. Type:
0.3. Means of identification of type if marked on the vehicle/component/separate technical unit (1) (?):
0.3.1. Location of that marking:
0.4. Category of vehicle (?):
0.5. Name and address of manufacturer:
0.7. In the case of components and separate technical units, location and method of affixing of the EC approval mark:
0.8. Address(es) of assembly plant(s):

Section II

- 1. Additional information (where applicable): see addendum
2. Technical service responsible for carrying out the tests:
3. Date of test report:
4. Number of test report:
5. Remarks (if any): see addendum
6. Place:
7. Date:
8. Signature:
9. The index to the information package lodged with the approval authority, which may be obtained on request, is attached.

Addendum to EC type-approval certificate No ... concerning the type-approval of a vehicle with regard to Directive 74/60/EEC, as last amended by Directive 2000/4/EC

- 1. Additional information
1.1. Type of bodywork:
1.2. Number of seats:
5. Remarks:
(e.g. valid for both left-hand drive and right-hand drive vehicles)

(1) Delete where not applicable.
(2) If the means of identification of type contains characters not relevant to describe the vehicle, component or separate technical unit covered by this type-approval certificate such characters shall be represented in the documentation by the symbol: "?" (e.g. ABC??123??).
(3) As defined in Annex II, Section A to Directive 70/156/EEC.

Appendix 3

POSITION OF CYLINDRICAL TEST ROD IN THE OPENING ROOF AND WINDOW OPENINGS




Figure 1



Appendix 4

SYMBOL FOR DRIVER CONTROLLED SWITCH

