

I

(Acts whose publication is obligatory)

COUNCIL

COUNCIL REGULATION (EC) No 1241/2004

of 5 July 2004

**amending Regulation (EC) No 1255/96 temporarily suspending the autonomous Common Customs
Tariff duties on certain industrial, agricultural and fishery products**

THE COUNCIL OF THE EUROPEAN UNION,

Having regard to the Treaty establishing the European Community, and in particular Article 26 thereof,

Having regard to the proposal from the Commission,

Whereas:

- (1) It is in the interest of the Community to suspend partially or totally the autonomous Common Customs Tariff duties for a number of new products not listed in the Annex to Regulation (EC) No 1255/96 ⁽¹⁾.
- (2) A number of products should be withdrawn from the list in the Annex to Regulation (EC) No 1255/96 because it is no longer in the Community's interest to maintain suspension of autonomous Common Customs Tariff duties or because the description needs to be altered in the light of technical developments.
- (3) Products whose description needs to be altered should be regarded as new products.
- (4) It is therefore appropriate to amend Regulation (EC) No 1255/96 accordingly,

HAS ADOPTED THIS REGULATION:

Article 1

The Annex to Regulation (EC) No 1255/96 is hereby amended as follows:

1. The products set out in Annex I to this Regulation are inserted in the Annex to Regulation (EC) No 1255/96.
2. The products for which the codes are set out in Annex II to this Regulation are deleted from the Annex to Regulation (EC) No 1255/96.

Article 2

This Regulation shall enter into force on the third day following that of its publication in the *Official Journal of the European Union*.

It shall apply with effect from 1 July 2004.

This Regulation shall be binding in its entirety and directly applicable in all Member States.

Done at Brussels, 5 July 2004.

For the Council

The President

G. ZALM

⁽¹⁾ OJ L 158, 29.6.1996, p. 1. Regulation as last amended by Regulation (EC) No 2285/2003 (OJ L 341, 30.12.2003, p. 1).

ANNEX I

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 2812 90 00 20	20	Silicon tetrafluoride	0
ex 2903 30 80 50	50	1,1,1,3,3-Pentafluoropropane, for use as non-flammable liquid blowing agent in the formation of insulating foams ⁽⁴⁾	0
ex 2903 30 80 60	60	Octafluoropropane	0
ex 2905 19 00 30	30	2,6-Dimethylheptan-4-ol	0
ex 2909 19 00 30	30	Mixture of isomers of nonafluorobutyl methyl ether or nonafluorobutyl ethyl ether, of a purity by weight of 99 % or more	0
ex 2912 42 00 10	10	Ethylvanillin (3-ethoxy-4-hydroxybenzaldehyde)	0
ex 2914 70 00 40	40	Perfluoro(2-methylpentan-3-one)	0
ex 2915 39 90 50	50	3-Acetylphenyl acetate	0
ex 2920 90 10 30	30	4-Ethyl-1,3-dioxolan-2-one	0
ex 2921 29 00 40	40	N,N'-Di-tert-butylethylenediamine	0
ex 2922 19 80 50	50	2-(2-Methoxyphenoxy)ethylamine	0
ex 2923 90 00 80	80	Diallyldimethylammonium chloride, in the form of an aqueous solution containing by weight 63 % or more but not more than 67 % of diallyldimethylammonium chloride	0
ex 2925 19 95 20	20	N-(9-Fluorenylmethoxycarbonyloxy)succinimide	0
ex 2928 00 90 80	80	Cyflufenamid (ISO)	0
ex 2930 90 70 88	88	Methylene dithiocyanate	0
ex 2932 19 00 70	70	Furfurylamine	0
ex 2932 19 00 75	75	Tetrahydro-2-methylfuran	0
ex 2932 19 00 80	80	Octafluorotetrahydrofuran	0
ex 2932 99 70 60	60	Calcium bis[4-O-(β -D-galactopyranosyl)-D-gluconate] dihydrate	0
ex 2933 99 30 20	20	5H-Dibenz[b,f]azepine-5-carbonyl chloride	0
ex 2934 99 90 72	72	1-[3-(5-Nitro-2-furyl)allylideneamino]imidazolidine-2,4-dione	0
ex 2934 99 90 73	73	N-(5-Mercapto-1,3,4-thiadiazol-2-yl)acetamide	0
ex 2935 00 90 15	15	Flupyr-sulfuron-methyl-sodium (ISO)	0
ex 2935 00 90 25	25	Triflurosulfuron-methyl (ISO)	0
ex 2935 00 90 35	35	Chlorsulfuron (ISO)	0
ex 2935 00 90 45	45	Rimsulfuron (ISO)	0
ex 2935 00 90 55	55	Thifensulfuron-methyl (ISO)	0
ex 2935 00 90 65	65	Tribenuron-methyl (ISO)	0
ex 2935 00 90 75	75	Metsulfuron-methyl (ISO)	0
ex 2935 00 90 87	87	4'-Sulfamoylacetanilide	0
3206 50 00		Inorganic products of a kind used as luminophores	0
ex 3207 40 80 30	30	Glass frit, for use in the manufacture of cathode-ray tubes ⁽⁴⁾	0
ex 3215 11 00 10	10	Printing ink, liquid, consisting of a dispersion of a vinyl acrylate copolymer and colour pigments in isoparaffins, containing by weight not more than 13 % of vinyl acrylate copolymer and colour pigments	0
ex 3215 19 00 10	10		

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 3215 90 80 30	30	Ink preparation, in the form of powder, for use in the manufacture of ink-filled bottles of a kind used in colour digital presses of heading No 8443 (*)	0
ex 3707 90 30 20	20	Toner, based on a polyol resin, in the form of powder	0
ex 3707 90 30 30	30	Two-component toner, liquid, in the form of a set consisting of a container containing a dispersion of a vinyl acrylate copolymer and colour pigments in isoparaffins, containing by weight not more than 13 % of vinyl acrylate copolymer and colour pigments, and a container containing isoparaffins	0
ex 3801 20 90 10	10	Colloidal graphite in suspension in water, for use as internal coating in colour cathode-ray tubes (*)	0
ex 3814 00 90 20	20	Mixture containing by weight: — 69 % or more but not more than 71 % of 1-methoxypropan-2-ol, — 29 % or more but not more than 31 % of 2-methoxy-1-methylethyl acetate	0
ex 3814 00 90 30	30	Azeotrope mixture containing by weight 30 % or more but not more than 50 % of trans-dichloroethylene and a mixture of isomers of nonafluorobutyl methyl ether or nonafluorobutyl ethyl ether	0
ex 3815 19 90 35	35	Catalyst, in the form of rodlets of a length of 5,5 mm or more but not exceeding 6,5 mm, consisting of copper oxide and zinc oxide fixed on a support of aluminium oxide, containing by weight: — 55 % or more but not more than 60 % of copper oxide and — 30 % or more but not more than 35 % of zinc oxide	0
ex 3824 90 99 92	92	Bis{4-[(5-chloro-2-hydroxyphenyl)azo]-3-hydroxy-N-phenyl-2-naphthalene= carboxyamidate}ferate with a mixture of ammonium, sodium and hydrogen cations	0
ex 3824 90 99 93	93	Prepared resin, based on diallyl 2,2'-oxydiethyl dicarbonate and oligomers thereof, containing by weight 42 % or more but not more than 52 % of diallyl 2,2'-oxydiethyl dicarbonate and 33 % or more but not more than 43 % of a copolymer of terephthalic acid, propane-1,2-diol and allyl alcohol	0
ex 3824 90 99 94	94	Prepared resin, based on diallyl 2,2'-oxydiethyl dicarbonate and oligomers thereof, containing by weight 73 % or more of diallyl 2,2'-oxydiethyl dicarbonate	0
ex 3824 90 99 95	95	Mixture of phytosterols, in the form of flakes, containing by weight 80 % or more of sterols and not more than 4 % of stanols	0
ex 3901 20 90 30	30	Polyethylene, in one of the forms mentioned in note 6(b) to Chapter 39, of a specific gravity of 0,940 or more but not exceeding 0,943 and a melt flow index of 27 g/10 min (\pm 5 g/10 min) (MFI 190 °C/2,16 kg as determined by the ISO 1133 method), for the manufacture of bicomponent spunbonded non-wovens (*)	0
ex 3904 61 00 30	30	Polytetrafluoroethylene, in the form of powder, of a specific surface of 8 m ² /g or more but not exceeding 12 m ² /g, a particle size distribution of 10 % of less than 10 μ m and 90 % of less than 35 μ m and an average particle size of 20 μ m	0
ex 3906 90 90 50	50	Polymers of esters of acrylic acid with one or more of the following monomers in the chain: — chloromethyl vinyl ether, — chloroethyl vinyl ether, — chloromethylstyrene, — vinyl chloroacetate, — methacrylic acid, — butenedioic acid monobutyl ester, containing by weight not more than 5 % of each of the monomeric units, in one of the forms mentioned in note 6(b) to Chapter 39	0

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 3907 20 99 45	45	Copolymer of ethylene oxide and propylene oxide, having aminopropyl and methoxy end-groups	0
ex 3907 20 99 50	50	Copolymer of ethylene oxide and propylene oxide, having 2-aminopropyl end-groups	0
ex 3911 90 99 75	75	Microspheres of a copolymer of divinylbenzene and styrene, of an average diameter of 325 µm or more but not exceeding 575 µm	0
ex 3926 90 99 75	75		
ex 3911 90 99 80	80	Poly[(8-methyl-8-methoxycarbonyltricyclo[5.2.1.0 ^{2,6}]decane-3,5-diyl)ethylene]	0
ex 3916 90 90 10	10	Composite profile shape, reinforced with glass fibres, produced by pultrusion, for the manufacture of window frames ^(*)	0
ex 3920 10 26 40	40	Film of polyethylene, of a kind used for typewriter ribbon	0
ex 3920 43 10 96	96	Film, of a specular gloss of 70 or more measured at an angle of 60 ° using a glossmeter (as determined by the ISO 2813:2000 method), consisting of a layer of poly(ethylene terephthalate) and a layer of colored poly(vinyl chloride), for coating panels and doors of a kind used in the manufacture of domestic appliances ^(*)	0
ex 3920 62 19 01	01	Coextruded opaque sheet of poly(ethylene terephthalate), of a thickness of 50 µm or more but not exceeding 350 µm, consisting especially of a layer containing carbon black	0
ex 3920 62 19 03	03		
ex 3920 62 19 04	04	Poly(ethylene terephthalate) film, of a thickness of less than 11 µm, for the manufacture of audiodigital tapes for cassettes ^(*)	0
ex 3920 62 19 06	06		
ex 3920 62 19 07	07	Poly(ethylene terephthalate) film, not coated with an adhesive, of a thickness not exceeding 25 µm, either:	0
ex 3920 62 19 09	09	— only dyed in the mass, or — dyed in the mass and metallized on one side	
ex 3920 62 19 11	11	Film of poly(ethylene terephthalate) only, of a total thickness not exceeding 120 µm, consisting of one or two layers each containing a colouring and/or UV-absorbing material throughout the mass, uncoated with an adhesive or any other material	0
ex 3920 62 19 13	13		
ex 3920 62 19 14	14	Poly(ethylene terephthalate) film, of a thickness of 20 µm or more but not exceeding 30 µm, coated on one side with silicone, for use in the manufacture of window film ^(*)	3
ex 3920 62 19 16	16		
ex 3920 62 19 17	17	Laminated film of poly(ethylene terephthalate) only, of a total thickness not exceeding 120 µm, consisting of one layer which is metallised only and one or two layers each containing a colouring and/or UV-absorbing material throughout the mass, uncoated with an adhesive or any other material	0
ex 3920 62 19 19	19		
ex 3920 62 19 21	21	Film of poly(ethylene terephthalate), coated or covered on one side or on both sides with a layer of modified polyester, of a total thickness of 7 µm or more but not exceeding 11 µm, for the manufacture of video tapes with a magnetic layer of metallic pigments and a width of 8 mm or of 12,7 mm ^(*)	0
ex 3920 62 19 23	23		
ex 3920 62 19 24	24	Single ply film of poly(ethylene terephthalate) only, of a thickness not exceeding 120 µm, which only:	0
ex 3920 62 19 26	26	— contains a colouring and/or UV-absorbing material throughout the mass and — is metallised on one side, whether or not coated on one or both sides with a vinyl acrylate polymer but having no other coating or adhesive	
ex 3920 62 19 27	27	Film of poly(ethylene terephthalate), of a total thickness not exceeding 120 µm, of a width of 100 mm or more but not exceeding 115 mm, coated on both sides with one or more layers containing different chemicals, for the manufacture of goods of subheading 3701 20 00 ^(*)	0
ex 3920 62 19 29	29		

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 3920 62 19 31	31	Film of poly(ethylene terephthalate), on one side metallised and coated with white ink and a protective layer and on the other side coated with a thermosensitive seal layer, of a width of 100 mm or more but not exceeding 150 mm, for the manufacture of goods of subheading 3701 20 00 ⁽⁴⁾	0
ex 3920 62 19 33	33		
ex 3920 62 19 34	34	Film of poly(ethylene terephthalate), coated on one side with a layer of modified polyester, of a thickness of 20 µm (± 0,7 µm) or of 30 µm (± 0,9 µm), for the manufacture of audio magnetic tapes of a total thickness of 33 µm or more ⁽⁴⁾	0
ex 3920 62 19 36	36		
ex 3920 62 19 37	37	Poly(ethylene terephthalate) film, of a thickness not exceeding 12 µm, coated on one side with a layer of aluminium oxide of a thickness not exceeding 35 nm	0
ex 3920 62 19 39	39		
ex 3920 62 19 41	41	Poly(ethylene terephthalate) film, of a thickness of 18 µm or more but not exceeding 25 µm, having:	0
ex 3920 62 19 43	43	— a shrinkage of (3,4 ± 0,1) % in the machine direction (as determined by the ASTM D 1204 method) and — a shrinkage of (0,3 ± 0,2) % in the transverse direction (as determined by the ASTM D 1204 method)	
ex 3920 62 19 44	44	Poly(ethylene terephthalate) film, of a thickness not exceeding 19 µm or of a weight of 20 g/m ² or more but not exceeding 26,7 g/m ² , for use in the manufacture of photo-resist film ⁽⁴⁾	0
ex 3920 62 19 46	46		
ex 3920 62 19 47	47	Film of poly(ethylene terephthalate), coated on both sides with a layer of epoxy acrylic resin, of a total thickness of 37 µm (± 3 µm)	0
ex 3920 62 19 49	49		
ex 3920 62 19 51	51	Film of poly(ethylene terephthalate), coated on one side with metal and/or metal oxides, containing by weight less than 0,1 % of aluminium, of a thickness not exceeding 300 µm and having a surface resistivity not exceeding 10 000 ohms (per square) (as determined by the ASTM D 257-93 method)	0
ex 3920 62 19 53	53		
ex 3920 62 19 54	54	Matt film of poly(ethylene terephthalate), of a specular gloss of 15 measured at an angle of 45 ° and 18 measured at an angle of 60 ° using a glossmeter (as determined by the ISO 2813:2000 method) and a width of 1 600 mm or more	0
ex 3920 62 19 56	56		
ex 3920 62 19 57	57	Film of white poly(ethylene terephthalate), dyed in the mass, of a thickness of 185 µm or more but not exceeding 253 µm, coated on both sides with an antistatic layer	0
ex 3920 62 19 59	59		
ex 3920 62 19 61	61	Film of a total thickness of 4,5 µm (± 0,16 µm), consisting of a biaxially-oriented poly(ethylene terephthalate) film, of an elastic modulus (in the machine direction) of 12 kg/mm ² (± 2 kg/mm ²) and a tensile strength (in the machine direction) of more than 28 kg/mm ² , and of an anti-adherent coating	0
ex 3920 62 19 63	63		
ex 3920 62 19 67	67	Poly(ethylene terephthalate) film, coated with among other a scratch resistant layer based on polyacrylate and a thermo-adhesive layer, of a nominal width of 790 mm and a total thickness of 23 µm or more but not exceeding 26 µm	0
ex 3920 62 19 69	69		
ex 3920 62 19 74	74	Multilayer film of a thickness not exceeding 150 µm, consisting of a polyester film coated on one side with polycarbonate resin, metallized on the other side with titanium coated with polycarbonate resin and other layers containing N,N'-diphenyl-N,N'-di-m-tolylbiphenyl-4,4'-ylenediamine	0
ex 3920 62 19 76	76		
ex 3920 62 90 31	31	Film of poly(ethylene terephthalate), of a thickness of 500 µm (± 25 µm)	0
ex 3920 62 90 33	33		
ex 3921 90 60 93	93	Film, of a specular gloss of 30 or more but not exceeding 60 measured at an angle of 60 ° using a glossmeter (as determined by the ISO 2813:2000 method), consisting of a layer of poly(ethylene terephthalate) and a layer of colored poly(vinyl chloride), joined by a metalized adhesive coating, for coating panels and doors of a kind used in the manufacture of domestic appliances ⁽⁴⁾	0
ex 3926 90 99 85	85	Unexpandable microspheres of a copolymer of acrylonitrile, methacrylonitrile and isobornyl methacrylate, of a diameter of 3 µm or more but not exceeding 3,3 µm	0
ex 5803 10 00 91	91	Gauze of cotton, of a width of less than 1 500 mm	0
ex 6914 90 90 30	30	Ceramic microspheres, transparent, obtained from silicon dioxide and zirconium dioxide, of a diameter of more than 125 µm	0

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 7019 90 99 20	20	Glass cord impregnated with rubber or plastic, obtained from twisted glass filament yarns, coated with a latex comprising at least a resorcinol-formaldehyde-vinylpyridine resin and an acrylonitrile-butadiene rubber (NBR)	0
ex 7606 11 10 20	20	Tape of not alloyed aluminium, with a reflecting film, a transparent polyurethane topcoat, a netting and ceramic anti-skid particles	0
ex 8505 19 90 32	32	Magnet, for use in the manufacture of deflection yokes ⁽⁴⁾	0
ex 8522 90 59 95	95	Printed circuit board mounted with electronic circuits operating at a voltage of 12 V, for use in the manufacture of television sets combined with video units ⁽⁴⁾	0
ex 8522 90 98 45	45	Video tape recording/reproducing assembly comprising at least a motor and a printed circuit board containing integrated circuits with driver or control functions, whether or not incorporating a transformer, for use in the manufacture of products falling within heading No 8521 ⁽⁴⁾	0
ex 8522 90 98 47	47	Laser optical drive unit assembly (so called mecha units) for the recording and/or reproduction of digital video and/or audio signals, comprising at least a laser optical reading and/or writing unit, one or more DC motors and not containing a printed circuit board or containing a printed circuit board not capable of signal processing for sounds and images, for use in the manufacture of products falling within headings No 8519, 8520, 8521, 8526, 8527, 8528 or 8543 ⁽⁴⁾	0
ex 8548 90 90 45	45		
ex 8525 30 90 30	30	Compact chassis-type closed circuit television (CCTV) cameras, of a weight of not more than 250 g, contained in a housing of dimensions not exceeding 50 × 60 × 89,5 mm, with a single sensor Charge-Couple Device (CCD), with effective pixels not exceeding 440 000, for use in CCTV surveillance systems ⁽⁴⁾	0
ex 8528 21 90 20	20	Liquid cristal display colour video monitor having a DC input voltage of 10 V or more but not exceeding 30 V or a fix DC input voltage of 12 V, with a diagonal measurement of the screen of 33,2 cm or less, suitable for the incorporation into goods of chapters 84 to 90 and 94	0
ex 8529 90 81 40	40	Assembly comprising prisms, digital micromirror device (DMD) chips and electronic control circuits, for the manufacture of television projection equipments or video projectors ⁽⁴⁾	0
ex 8540 11 11 93	93	Colour cathode-ray tube, equipped with one gun with three rays and with a diagonal measurement of the screen of 19 cm or more but not exceeding 26 cm	0
ex 8544 60 10 10	10	Anode cap cable, for use in the manufacture of fly back transformers ⁽⁴⁾	0
ex 8548 90 90 46	46	Optical unit, consisting at least of a laser diode and a photodiode, operating at a typical wavelength of 654 nm or more but not exceeding 787 nm	0
ex 9032 89 90 20	20	Electronic controller of electric power steering (EPS controller)	0

⁽⁴⁾ Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

ANNEX II

CN code	TARIC
ex 3215 90 80	30
ex 3904 30 00	20
ex 3906 90 90	50
ex 3920 43 10	96
ex 3920 62 19	05
ex 3920 62 19	10
ex 3920 62 19	15
ex 3920 62 19	25
ex 3920 62 19	30
ex 3920 62 19	35
ex 3920 62 19	40
ex 3920 62 19	45
ex 3920 62 19	50
ex 3920 62 19	55
ex 3920 62 19	60
ex 3920 62 19	62
ex 3920 62 19	64
ex 3920 62 19	65
ex 3920 62 19	70
ex 3920 62 19	75
ex 3920 62 19	80
ex 3920 62 19	81
ex 3920 62 19	85
ex 3920 62 19	87
ex 3920 62 19	89
ex 3920 62 90	30
ex 3921 90 60	93
ex 3923 10 00	10

CN code	TARIC
ex 7006 00 90	40
ex 7616 99 90	40
ex 8419 89 98	20
ex 8424 89 95	10
ex 8424 89 95	20
ex 8460 21 90	10
ex 8460 40 10	10
ex 8460 90 90	10
ex 8460 90 90	20
ex 8463 90 00	10
ex 8464 20 19	10
ex 8479 89 98	10
ex 8479 89 98	20
ex 8479 89 98	30
ex 8522 90 59	95
ex 8522 90 98	45
ex 8522 90 98	47
ex 8528 21 90	20
ex 8529 90 81	40
ex 8540 11 11	93
ex 8543 89 95	58
ex 8548 90 90	45
ex 9031 80 34	10
ex 9031 80 39	30
ex 9031 80 99	10
ex 9031 90 80	20
ex 9031 90 80	40
ex 9031 90 80	50