

**COMMISSION DECISION**  
**of 19 December 2008**  
**authorising methods for grading pig carcasses in Denmark**

(notified under document number C(2008) 8498)

(Only the Danish text is authentic)

(2009/12/EC)

THE COMMISSION OF THE EUROPEAN COMMUNITIES,

Having regard to the Treaty establishing the European Community,

Having regard to Council Regulation (EEC) No 3220/84 of 13 November 1984 determining the Community scale for grading pig carcasses <sup>(1)</sup>, and in particular Article 5(2) thereof,

Whereas:

- (1) Under Article 2(3) of Regulation (EEC) No 3220/84, the grading of pig carcasses is to be determined by estimating the lean-meat content by means of statistically proven assessment methods based on the physical measurement of one or more anatomical parts of the pig carcass. The authorisation of grading methods is subject to compliance with a maximum tolerance for statistical error in assessment. This tolerance is defined in Article 3(2) of Commission Regulation (EEC) No 2967/85 of 24 October 1985 laying down detailed rules for the application of the Community scale for grading pig carcasses <sup>(2)</sup>.
- (2) Commission Decision 92/469/EEC <sup>(3)</sup> authorises four methods for grading pig carcasses in Denmark.
- (3) Due to technical adaptations, Denmark has asked the Commission to authorise the update of four authorised methods and the utilisation of two updated methods (Autofom DK and FOM II), and has presented the results of its dissection trials in the second part of the protocol provided for in Article 3(3) of Regulation (EEC) No 2967/85.
- (4) Examination of this request has revealed that the conditions for authorising these grading methods are fulfilled.
- (5) No modification of the apparatus or grading methods may be authorised except by means of a new Commission Decision adopted in the light of experience gained. For this reason, the present authorisation may be revoked.

(6) For the sake of clarity, Decision 92/469/EEC should be repealed and replaced by a new decision.

(7) The measures provided for in this Decision are in accordance with the opinion of the Management Committee for the Common Organisation of the Agricultural Markets,

HAS ADOPTED THIS DECISION:

*Article 1*

The use of the following methods is hereby authorized for grading pig carcasses pursuant to Regulation (EEC) No 3220/84 in Denmark:

- (a) the apparatus termed 'Klassificeringscenter (KC)' and assessment methods related thereto, details of which are given in Part 1 of the Annex;
- (b) the apparatus termed 'Fat-O-Meater/Manuel Klassificering (FOM/MK)' and assessment methods related thereto, details of which are given in Part 2 of the Annex;
- (c) the apparatus termed 'Uni-Fat-O-Meater (Unifom)' and assessment methods related thereto, details of which are given in Part 3 of the Annex;
- (d) the apparatus termed 'Fully automatic ultrasonic equipment (AutoFOM 1)' and assessment methods related thereto, details of which are given in Part 4 of the Annex;
- (e) the apparatus termed 'Updated fully automatic ultrasonic equipment (AutoFOM DK)' and assessment methods related thereto, details of which are given in Part 5 of the Annex;
- (f) the apparatus termed 'Fat-O-Meater II (FOM II)' and assessment methods related thereto, details of which are given in Part 6 of the Annex.

<sup>(1)</sup> OJ L 301, 20.11.1984, p. 1.

<sup>(2)</sup> OJ L 285, 25.10.1985, p. 39.

<sup>(3)</sup> OJ L 265, 11.9.1992, p. 39.

*Article 2*

Modifications of the apparatus or the assessment methods shall not be authorised.

*Article 3*

Decision 92/469/EEC is hereby repealed.

*Article 4*

This Decision is addressed to the Kingdom of Denmark.

Done at Brussels, 19 December 2008.

*For the Commission*  
Mariann FISCHER BOEL  
*Member of the Commission*

---

## ANNEX

## METHODS FOR GRADING PIG CARCASSES IN DENMARK

## Part 1

## KLASSIFICERINGSCENTER (KC)

1. Grading of pig carcasses shall be carried out by means of the apparatus termed 'Klassificeringscenter (KC)'.
2. The apparatus shall be equipped with nine probes of six millimetres each containing a photodiode (Siemens of the type SFH 950 LD242 II or similar) and a photodetector (Siemens of the type SFH 960 — PB 103 or similar) and having an operation distance of between one and 180 millimetres. The results of the measurements are converted into estimated lean meat content by means of a central unit.
3. The lean meat content of the carcase shall be calculated on the basis of 10 measurements taken from seven measuring-points as are indicated in paragraph 4 and according to the following formula

$$\hat{Y} = 70,5489 - 0,1572 x_1 - 0,1698 x_2 - 0,1537 x_3 - 0,1803 x_4 - 0,2115 x_5 - 0,1669 x_6 - 0,1269 x_7 + 0,04278 x_8 + 0,0234 x_9 + 0,0371 x_{10}$$

where:

$\hat{Y}$  = the estimated percentage of lean meat in carcase.

4. The measurement points are:

$x_1$  = the thickness of backfat (including rind) in millimetres, measured at the centre of the third cervical vertebra, at 10,5 cm off the midline of the carcase.

$x_2$  = the thickness of backfat (including rind) in millimetres, measured at the centre of fourth cervical vertebra, at 7 cm off the midline of the carcase.

$x_3$  = the thickness of backfat (including rind) in millimetres, measured between fourth and fifth hindmost thoracic vertebra, at 3 cm off the midline of the carcase.

$x_4$  = the thickness of backfat (including rind) in millimetres, measured between second and third hindmost thoracic vertebra, at 7 cm off the midline of the carcase.

$x_5$  = the thickness of backfat (including rind) in millimetres, measured between first lumbar vertebra and last thoracic vertebra, at 6 cm off the midline of the carcase.

$x_6$  = the thickness of backfat (including rind) in millimetres, measured 4 cm before the fore edge of the pubic bone, at 7 cm off the midline of the carcase.

$x_7$  = the thickness of backfat (including rind) in millimetres, measured at the fore edge of the pubic bone, at 11 cm off the midline of the carcase.

$x_8$  = muscle thickness in millimetres, measured between fourth and fifth hindmost thoracic vertebra, at 3 cm off the midline of the carcase.

$x_9$  = muscle thickness in millimetres, measured between second and third hindmost thoracic vertebra, at 7 cm off the midline of the carcase.

$x_{10}$  = muscle thickness in millimetres, measured between first lumbar vertebra and hindmost thoracic vertebra, at 6 cm off the midline of the carcase.

The formulae shall be valid for carcasses weighing between 50 and 110 kg.

**Part 2**

## FAT-O-MEATER/MANUEL KLASSIFICERING (FOM/MK)

1. Pig carcass grading shall be carried out using the apparatus termed 'Fat-O-Meater/Manuel Klassificering (FOM/MK)'.
2. The apparatus is a Fat-O-Meater type of equipment and it shall be equipped with a probe of six millimetres diameter containing a photodetector (Siemens of the type SFH 960 — BP 103 or similar) and having an operation distance of between one and 94 millimetres.
3. The results of the measurements are converted into estimated lean meat content by means of a central unit.

The lean meat content of the carcass shall be calculated according to the following formula

$$\hat{Y} = 68,1746 - 0,3220 x_1 - 0,5326 x_2 + 0,0836 x_3$$

where:

$\hat{Y}$  = the estimated percentage of lean meat in carcass.

4. The measurement points are:

$x_1$  = the thickness of backfat (including rind) in millimetres, measured at 8 cm off the midline of the carcass between the third and fourth last lumbar vertebrae.

$x_2$  = the thickness of backfat (including rind) in millimetres, measured at 6 cm off the midline of the carcass between the third and fourth last ribs.

$x_3$  = the thickness of muscle in millimetres, measured at the same time and in the same place as  $x_2$ .

The formulae shall be valid for carcasses weighing between 50 and 110 kg.

**Part 3**

## UNI-FAT-O-MEATER (UNIFOM)

1. Grading of pig carcasses shall be carried out by means of the apparatus termed 'Uni-Fat-O-Meater' (Unifom).
2. The apparatus is the same as the apparatus described under point 2 of part 2. However, Unifom differs from MK with regard to computer and software for the interpretation of the reflection profile from the optical probe.
3. The lean meat content of the carcass shall be calculated according to the following formula

$$\hat{Y} = 66,7393 - 0,2655 x_1 - 0,5432 x_2 + 0,0838 x_3$$

where:

$\hat{Y}$  = the estimated percentage of lean meat in carcass.

4. The measurement points are:

$x_1$  = the thickness of backfat (including rind) in millimetres, measured at 8 cm off the midline of the carcass between the third and fourth last lumbar vertebrae.

$x_2$  = the thickness of backfat (including rind) in millimetres, measured at 6 cm off the midline of the carcass between the third and fourth last ribs.

$x_3$  = the thickness of muscle in millimetres, measured at the same time and in the same place as  $x_2$ .

The formulae shall be valid for carcasses weighing between 50 and 110 kg.

**Part 4**

## FULLY AUTOMATIC ULTRASONIC EQUIPMENT (AutoFOM 1)

1. Grading of the pig carcasses shall be carried out by means of the apparatus termed 'Fully automatic ultrasonic equipment (AutoFOM 1)'.
2. The apparatus shall be equipped with 16 ultrasonic transducers, 2MHz (Krautkrämer, SFK 2 NP or similar) with a distance of 25 mm between each transducer.

The results of the measurements are converted into estimated lean mean content by means of a central data-processing unit.

3. The lean meat content of the carcase shall be calculated on the basis of 127 individual measuring points according to the following formula

$$\hat{Y} = c + c_0 \times IP000 + c_1 \times IP001 + \dots + c_{126} \times IP126$$

where:

$\hat{Y}$  = the estimated percentage of lean meat in carcase. The constants  $c$  and  $c_0$  up to  $c_{126}$  appear from the Danish Protocol, Part II, submitted to the Commission under the terms of Article 3(3) of Commission Regulation (EEC) No 2967/85.

4. The description of the measurement points and the description of the statistical method are laid down in the Danish Protocol, Part II, submitted to the Commission under the terms of Article 3(3) of Commission Regulation (EEC) No 2967/85.

The formula shall be valid for carcasses weighing between 50 and 110 kg.

**Part 5**

## UPDATED FULLY AUTOMATIC ULTRASONIC EQUIPMENT (AutoFOM DK)

1. Grading of pig carcase shall be carried out by means of the apparatus termed 'Updated fully automatic ultrasonic equipment (AutoFOM DK)'.
2. The apparatus is mechanically compatible with the AutoFOM 1 concerning the scanner array itself. Likewise, the measuring principle itself remains unchanged. AutoFOM DK differs from AutoFOM 1 with regard to a fixture which ensures that the carcase passes the measuring unit in a straight position, and which together with a laser sensor detecting the carcase, provides symmetric measurements, with more computation power and a new software packages providing the opportunity to enhance the imaging speed and resolution.
3. The lean meat content of carcase shall be calculated according to the following formula:

$$\hat{Y} = 63,4322 - 0,1429 x_1 - 0,0438 x_2 - 0,0715 x_3 + 0,9420 x_4 + 0,0911 x_5$$

where:

$\hat{Y}$  = the estimated percentage of lean meat in carcase.

4. The description of the measurement points and the description of the statistical method are laid down in the Danish Protocol, Part II, submitted to the Commission under the terms of Article 3(3) of Commission Regulation (EEC) No 2967/85.

The formula shall be valid for carcasses weighing between 50 and 110 kg.

**Part 6**

## FAT-O-MEATER II (FOM II)

1. Grading of pig carcase shall be carried out by means of the apparatus termed 'Fat-O-Meater II (FOM II)'.
2. The apparatus is a new version of the FAT-O-Meater measurement system. The basic measurement principle, as described in point 2 in Part 2 and 3, is unchanged, but all software, hardware as well as the mechanical design is redesigned. The FOM II pistol consists of an optical probe with a knife, a depth measurement device and a data acquisition and analysis board. All legally relevant acquisition and analysis are contained within the FOM II pistol.

3. The lean meat content of carcase shall be calculated according to the following formula:

$$\hat{Y} = 66,5015 - 0,3568 x_1 - 0,4704 x_2 + 0,0947 x_3$$

where:

$\hat{Y}$  = the estimated percentage of lean meat in carcase.

4. The measurement points are:

$x_1$  = the thickness of backfat (including rind) in millimetres, measured at 8 cm off the midline of the carcase between the third and fourth last lumbar vertebrae.

$x_2$  = the thickness of backfat (including rind) in millimetres, measured at 6 cm off the midline of the carcase between the third and fourth last ribs.

$x_3$  = the thickness of muscle in millimetres, measured at the same time and in the same place as  $x_2$ .

The formula shall be valid for carcasses weighing between 50 and 110 kg.

---