

## II

(Non-legislative acts)

## REGULATIONS

## COUNCIL REGULATION (EU) No 1387/2013

of 17 December 2013

**suspending the autonomous Common Customs Tariff duties on certain agricultural and industrial products and repealing Regulation (EU) No 1344/2011**

THE COUNCIL OF THE EUROPEAN UNION,

Having regard to the Treaty on the Functioning of the European Union, and in particular Article 31 thereof,

Having regard to the proposal from the European Commission,

Whereas:

- (1) The Union production of the agricultural and industrial products set out in Annex I is currently inadequate or non-existent, and thus the needs of user industries in the Union cannot be met.
- (2) It is therefore in the interests of the Union to suspend partially or totally the autonomous Common Customs Tariff duties for those products.
- (3) Council Regulation (EU) No 1344/2011<sup>(1)</sup> has been amended many times. In addition, following its amendment by Council Regulation (EU) No 1220/2012<sup>(2)</sup>, fishery products were removed from the scope of Regulation (EU) No 1344/2011. In the interest of transparency, Regulation (EU) No 1344/2011 should therefore be replaced in its entirety.
- (4) Regulations suspending the autonomous Common Customs Tariff duties on certain industrial and agri-

cultural products have renewed previous measures to a great extent. Therefore, in the interests of rationalising the implementation of the measures concerned, it is appropriate not to limit the period of validity of this Regulation, as its scope can be adapted and products can be added to or removed from Annex I to this Regulation by means of a Council Regulation.

- (5) In view of their temporary nature, the suspensions listed in Annex I to this Regulation should be reviewed systematically, and at the latest five years after their date of application or renewal. Moreover, it might be necessary at any time to close certain suspensions, following a proposal of the Commission on the basis of a review carried out on its own initiative or at the request of one or more Member States if it is no longer in the Union's interest to maintain the suspensions or due to technical product developments, changed circumstances or economic trends on the market.
- (6) Statistics for certain products listed in Annex I to this Regulation are frequently expressed in pieces, square meters or measurement units other than weight. However, there are no such supplementary units in the Combined Nomenclature laid down in Annex I to Council Regulation (EEC) No 2658/87<sup>(3)</sup>. It is therefore necessary to provide that not only the weight in kilograms or tonnes, but also the relevant supplementary units for the imports of the products concerned, are entered in the declaration for release for free circulation.
- (7) Since the suspensions laid down in this Regulation must take effect on 1 January 2014, this Regulation should enter into force immediately upon its publication in the *Official Journal of the European Union* and should apply from 1 January 2014.

<sup>(1)</sup> Council Regulation (EU) No 1344/2011 of 19 December 2011 suspending the autonomous Common Customs Tariff duties on certain agricultural, fishery and industrial products and repealing Regulation (EC) No 1255/96 (OJ L 349, 31.12.2011, p. 1).

<sup>(2)</sup> Council Regulation (EU) No 1220/2012 of 3 December 2012 on trade related measures to guarantee the supply of certain fishery products to Union processors from 2013 to 2015, amending Regulations (EC) No 104/2000 and (EU) No 1344/2011 (OJ L 349, 19.12.2012, p. 4).

<sup>(3)</sup> Council Regulation (EEC) No 2658/87 of 23 July 1987 on the tariff and statistical nomenclature and on the Common Customs Tariff (OJ L 256, 7.9.1987, p. 1).

(8) In accordance with the principle of proportionality, it is necessary and appropriate for the achievement of the basic objectives of improving the competitive capacity of the Union industry, thereby enabling that industry to maintain or create employment and modernise its structures, to lay down rules on the suspension of the Common Customs Tariff duties for the products set out in Annex I. In accordance with Article 5(4) of the Treaty on European Union, this Regulation does not go beyond what is necessary to achieve the objectives pursued,

HAS ADOPTED THIS REGULATION:

*Article 1*

The autonomous Common Customs Tariff duties for the agricultural and industrial products listed in Annex I are hereby suspended.

*Article 2*

1. The Commission may at any time review the suspensions for the products listed in Annex I in the following cases:

(a) at its own initiative;

(b) at the request of Member States.

2. The Commission shall review the suspensions in the year set out in Annex I.

*Article 3*

Where a declaration for release for free circulation is presented in respect of the products falling under the CN codes or TARIC codes listed in Annex II, the supplementary unit provided in that Annex shall be entered in the relevant field of that declaration.

*Article 4*

Regulation (EU) No 1344/2011 is hereby repealed.

*Article 5*

This Regulation shall enter into force on the day of its publication in the *Official Journal of the European Union*.

It shall apply from 1 January 2014.

This Regulation shall be binding in its entirety and directly applicable in all Member States.

Done at Brussels, 17 December 2013.

*For the Council*  
*The President*  
L. LINKEVIČIUS

## ANNEX I

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
| ex 0710 21 00 | 10    | Peas in pods, of the species <i>Pisum sativum</i> of the variety <i>Hortense axiphium</i> , frozen, of a thickness of not more than 6 mm, to be used, in their pods, in the manufacture of prepared meals <sup>(1)</sup> <sup>(2)</sup>   | 0 %                     | 31.12.2018                         |
| ex 0710 80 95 | 50    | Bamboo shoots, frozen, not put up for retail sale   | 0 %                     | 31.12.2018                         |
| ex 0711 59 00 | 11    | Mushrooms, excluding mushrooms of the genera <i>Agaricus</i> , <i>Calocybe</i> , <i>Clitocybe</i> , <i>Lepista</i> , <i>Leucoagaricus</i> , <i>Leucopaxillus</i> , <i>Lyophyllum</i> and <i>Tricholoma</i> , provisionally preserved in brine, in sulphur water, or in other preservative solutions, but unsuitable in that state for immediate consumption, for the food-canning industry <sup>(1)</sup>   | 0 %                     | 31.12.2016                         |
| ex 0712 32 00 | 10    | Mushrooms, excluding mushrooms of the genus <i>Agaricus</i> , dried, whole or in identifiable slices or pieces, for treatment other than simple repacking for retail sale <sup>(1)</sup> <sup>(2)</sup>   | 0 %                     | 31.12.2018                         |
| ex 0712 33 00 | 10    |   |                         |                                    |
| ex 0712 39 00 | 31    |   |                         |                                    |
| ex 0804 10 00 | 30    | Dates, fresh or dried, for use in the manufacture (excluding packing) of products of drink or food industries <sup>(1)</sup>  | 0 %                     | 31.12.2018                         |
| ex 0810 40 50 | 10    | Cranberries of the species <i>Vaccinium macrocarpon</i> , fresh, for use in the manufacture (excluding packing) of products of drink or food industries <sup>(1)</sup>  | 0 %                     | 31.12.2018                         |
| 0811 90 50    | 70    | Fruit of the genus <i>Vaccinium</i> , uncooked or cooked by steaming or boiling in water, frozen, not containing added sugar or other sweetening matter   | 0 %                     | 31.12.2018                         |
| 0811 90 70    |       |   |                         |                                    |
| ex 0811 90 95 |       |   |                         |                                    |
| ex 0811 90 95 | 20    | Boysenberries, frozen, not containing added sugar, not put up for retail sale   | 0 %                     | 31.12.2018                         |
| ex 0811 90 95 | 30    | Pineapple ( <i>Ananas comosus</i> ), in pieces, frozen  | 0 %                     | 31.12.2018                         |
| ex 0811 90 95 | 40    | Rose-hips, uncooked or cooked by steaming or boiling in water, frozen, not containing added sugar or other sweetening matter  | 0 %                     | 31.12.2018                         |
| ex 1511 90 19 | 10    | Palm oil, coconut (copra) oil, palm kernel oil, for the manufacture of:<br>— industrial monocarboxylic fatty acids of subheading 3823 19 10,<br>— methyl esters of fatty acids of heading 2915 or 2916,<br>— fatty alcohols of subheadings 2905 17, 2905 19 and 3823 70 used for the manufacture of cosmetics, washing products or pharmaceutical products,<br>— fatty alcohols of subheading 2905 16, pure or mixed, used for the manufacture of cosmetics, washing products or pharmaceutical products,<br>— stearic acid of subheading 3823 11 00 or<br>— goods of heading 3401 <sup>(1)</sup> | 0 %                     | 31.12.2018                         |
| ex 1511 90 91 | 10    |   |                         |                                    |
| ex 1513 11 10 | 10    |   |                         |                                    |
| ex 1513 19 30 | 10    |   |                         |                                    |
| ex 1513 21 10 | 10    |   |                         |                                    |
| ex 1513 29 30 | 10    |   |                         |                                    |
| ex 1515 90 99 | 92    |   |                         |                                    |
| ex 1516 20 96 | 20    | Jobba oil, hydrogenated and interesterified, without any further chemical modification and not subjected to any texturisation process   | 0 %                     | 31.12.2014                         |
| ex 1517 90 99 | 10    | Vegetable oil, refined, containing by weight 25 % or more but not more than 50 % arachidonic acid or 12 % or more but not more than 50 % docosahexaenoic acid and standardized with high oleic sunflower oil (HOSO)   | 0 %                     | 31.12.2016                         |
| ex 1902 30 10 | 10    | Transparent noodles, cut in pieces, obtained from beans ( <i>Vigna radiata</i> (L.) Wilczek), not put up for retail sale  | 0 %                     | 31.12.2018                         |
| ex 1903 00 00 | 20    |   |                         |                                    |
| ex 2005 91 00 | 10    | Bamboo shoots, prepared or preserved, in immediate packings of a net content of more than 5 kg  | 0 %                     | 31.12.2018                         |

| CN code       | TARIC | Description  | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|------------------------------------|
| ex 2007 99 50 | 81    | Acerola puree concentrate, obtained by cooking:  | 9 % <sup>(3)</sup>      | 31.12.2017                         |
| ex 2007 99 50 | 91    | — of the Genus <i>Malpighia spp.</i> ,<br>— with a sugar content by weight of more than 13 % but not more than 30 %<br>for use in the manufacture of products of food and drink industry <sup>(1)</sup>  |                         |                                    |
| ex 2007 99 50 | 82    | Acidified banana puree concentrate, obtained by cooking:   | 11,5 % <sup>(3)</sup>   | 31.12.2017                         |
| ex 2007 99 50 | 92    | — of the Genus <i>Musa cavendish</i> ,<br>— with a sugar content by weight of more than 13 % but not more than 30 %<br>for use in the manufacture of products of food and drink industry <sup>(1)</sup>  |                         |                                    |
| ex 2007 99 50 | 83    | Mango puree concentrate, obtained by cooking:  | 6 % <sup>(3)</sup>      | 31.12.2017                         |
| ex 2007 99 50 | 93    | — of the Genus <i>Mangifera spp.</i> ,   |                         |                                    |
| ex 2007 99 93 | 10    | — with a sugar content by weight of not more than 30 %<br>for use in the manufacture of products of food and drink industry <sup>(1)</sup>   |                         |                                    |
| ex 2007 99 50 | 84    | Papaya puree concentrate, obtained by cooking:   | 7,8 % <sup>(3)</sup>    | 31.12.2017                         |
| ex 2007 99 50 | 94    | — of the Genus <i>Carica spp.</i> ,<br>— with a sugar content by weight of more than 13 % but not more than 30 %<br>for use in the manufacture of products of food and drink industry <sup>(1)</sup>   |                         |                                    |
| ex 2007 99 50 | 85    | Guava puree concentrate, obtained by cooking:  | 6 % <sup>(3)</sup>      | 31.12.2017                         |
| ex 2007 99 50 | 95    | — of the Genus <i>Psidium spp.</i> ,<br>— with a sugar content by weight of more than 13 % but not more than 30 %<br>for use in the manufacture of products of food and drink industry <sup>(1)</sup>  |                         |                                    |
| ex 2008 93 91 | 20    | Sweetened dried cranberries, excluding packing alone as processing, for the manufacture of products of food processing industries <sup>(4)</sup>   | 0 %                     | 31.12.2017                         |
| ex 2008 99 48 | 94    | Mango puree:<br>— not from concentrate,<br>— of the genus <i>Mangifera</i> ,<br>— of a Brix value of 14 or more, but not more than 20<br>used in the manufacture of products of drink industry <sup>(1)</sup>  | 6 %                     | 31.12.2015                         |
| ex 2008 99 49 | 30    | Seedless boysenberry puree not containing added spirit, whether or not containing added sugar  | 0 %                     | 31.12.2014                         |
| ex 2008 99 99 | 40    |  |                         |                                    |
| ex 2008 99 49 | 70    | Blanched vine leaves of the genus <i>Karakishmish</i> , in brine, containing by weight:  | 0 %                     | 31.12.2017                         |
| ex 2008 99 99 | 11    | — more than 6 % of salt concentration,<br>— 0,1 % or more but not more than 1,4 % of acidity expressed as citric acid monohydrate and<br>— whether or not but not more than 2 000 mg/kg of sodium benzoate according CODEX STAN 192-1995<br>for use in the manufacture of stuffed vine leaves with rice <sup>(1)</sup> |                         |                                    |
| ex 2009 41 92 | 20    | Pineapple juice:   | 8 %                     | 31.12.2015                         |
| ex 2009 41 99 | 70    | — not from concentrate,<br>— of the genus <i>Ananas</i> ,<br>— of a Brix value of 11 or more but not more than 16,<br>used in the manufacture of products of drink industry <sup>(1)</sup>   |                         |                                    |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
| ex 2009 49 30 | 91    | Pineapple juice, other than in powder form:<br>— with a Brix value of more than 20 but not more than 67,<br>— a value of more than EUR 30 per 100 kg net weight,<br>— containing added sugars<br>used in the manufacture of products of food or drink industry <sup>(1)</sup> | 0 %                     | 31.12.2014                         |
| ex 2009 81 31 | 10    | Cranberry juice concentrate:<br>— of a Brix value of 40 or more but not more than 66,<br>— in immediate packings of a content of 50 litres or more  | 0 %                     | 31.12.2014                         |
| ex 2009 89 79 | 20    | Frozen boysenberry juice concentrate with a Brix value of 61 or more, but not more than 67, in immediate packing of a content of 50 litres or more  | 0 %                     | 31.12.2016                         |
| ex 2009 89 79 | 30    | Frozen acerola juice concentrate:<br>— with a Brix value of more than 48 but not more than 67,<br>— in immediate packings of a content of 50 litres or more   | 0 %                     | 31.12.2018                         |
| ex 2009 89 79 | 85    | Acai berry juice concentrate:<br>— of the species <i>Euterpe oleracea</i> ,<br>— frozen,<br>— not sweetened,<br>— not in powder form,<br>— of a Brix value of 23 or more but not more than 32,<br>in immediate packings of a content of 10 kg or more                         | 0 %                     | 31.12.2016                         |
| ex 2009 89 99 | 93    | Untreated frozen coconut water, in immediate packing of a content of 50 litres or more  | 0 %                     | 31.12.2016                         |
| ex 2106 10 20 | 10    | Soya protein isolate, containing by weight 6,6 % or more but not more than 8,6 % of calcium phosphate   | 0 %                     | 31.12.2018                         |
| ex 2106 90 92 | 45    | Preparation containing by weight:<br>— more than 30 % but not more than 35 % licorice extract,<br>— more than 65 % but not more than 70 % tricapyrylin,<br>standardized by weight to 3 % or more but not more than 4 % glabridin  | 0 %                     | 31.12.2016                         |
| ex 2519 90 10 | 10    | Fused magnesia with a purity by weight of 97 % or more  | 0 %                     | 31.12.2016                         |
| ex 2804 50 90 | 10    | Tellurium of a purity by weight of 99,99 % or more, but not more than 99,999 % by weight (CAS RN 13494-80-9)  | 0 %                     | 31.12.2018                         |
| 2804 70 00    |       | Phosphorus  | 0 %                     | 31.12.2018                         |
| ex 2805 19 90 | 10    | Lithium metal of a purity by weight of 99,7 % or more (CAS RN 7439-93-2)  | 0 %                     | 31.12.2017                         |
| ex 2805 30 10 | 10    | Alloy of cerium and other rare-earth metals, containing by weight 47 % or more of cerium  | 0 %                     | 31.12.2018                         |
| ex 2805 30 90 | 45    | Rare-earth metals, scandium and yttrium, of a purity by weight of 95 % or more  | 0 %                     | 31.12.2015                         |
| ex 2805 30 90 | 55    |   | 0 %                     |                                    |
| ex 2805 30 90 | 65    |   | 0 %                     |                                    |
| ex 2811 19 80 | 10    | Sulphamidic acid (CAS RN 5329-14-6)   | 0 %                     | 31.12.2018                         |
| ex 2811 19 80 | 20    | Hydrogen iodide (CAS RN 10034-85-2)   | 0 %                     | 31.12.2016                         |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
| ex 2811 19 80 | 30    | Phosphorous acid (CAS RN 10294-56-1)/phosphonic acid (CAS RN 13598-36-2) used as an ingredient for production of additives used in poly(vinyl chloride) industry <sup>(1)</sup>   | 0 %                     | 31.12.2017                         |
| ex 2811 22 00 | 10    | Silicon dioxide (CAS RN 7631-86-9) in the form of powder, for use in the manufacture of high performance liquid chromatography columns (HPLC) and sample preparation cartridges <sup>(1)</sup>  | 0 %                     | 31.12.2018                         |
| ex 2811 22 00 | 30    | Balls of porous white silica of a particle size of more than 1 µm for use in the manufacture of cosmetic products <sup>(1)</sup>  | 0 %                     | 31.12.2016                         |
| ex 2812 90 00 | 10    | Nitrogen trifluoride (CAS RN 7783-54-2)   | 0 %                     | 31.12.2018                         |
| ex 2816 40 00 | 10    | Barium hydroxide (CAS RN 17194-00-2)  | 0 %                     | 31.12.2017                         |
| ex 2818 10 91 | 10    | Sintered corundum with micro crystalline structure, containing by weight:<br>— 94 % or more, but not more than 98,5 % of α-Al <sub>2</sub> O <sub>3</sub> (CAS RN 1344-28-1),<br>— 2 % (± 1,5 %) of magnesium spinel (CAS RN 1309-48-4),<br>— 1 % (± 0,6 %) of yttrium oxide (CAS RN 1314-36-9),<br>and<br>— either 2 % (± 1,2 %) of lanthanum oxide (CAS RN 1312-81-8)<br>— or 2 % (± 1,2 %) of lanthanum oxide (CAS RN 1312-81-8) and neodymium oxide (CAS RN 1313-97-9)<br>with less than 50 % of the total weight having a particle size of more than 10 µm | 0 %                     | 31.12.2015                         |
| ex 2818 20 00 | 10    | Activated alumina with a specific surface area of at least 350 m <sup>2</sup> /g  | 0 %                     | 31.12.2014                         |
| ex 2818 30 00 | 10    | Aluminium hydroxide oxide in the form of pseudo-boehmite  | 4 %                     | 31.12.2018                         |
| 2819 10 00    |       | Chromium trioxide (CAS RN 1333-82-0)  | 0 %                     | 31.12.2016                         |
| ex 2819 90 90 | 10    | Dichromium trioxide for use in metallurgy (CAS RN 1308-38-9) <sup>(1)</sup>   | 0 %                     | 31.12.2016                         |
| ex 2823 00 00 | 10    | Titanium dioxide (CAS RN 13463-67-7):<br>— of a purity by weight of 99,9 % or more,<br>— with an average grain-size of 1,2 µm or more but not more than 1,8 µm<br>— with a specific surface of 5,0 m <sup>2</sup> /g or more, but not more than 7,5 m <sup>2</sup> /g   | 0 %                     | 31.12.2017                         |
| ex 2823 00 00 | 20    | Titanium dioxide (CAS RN 13463-67-7) with a purity by weight of 99,7 % or more and containing by weight:<br>— not more than 0,005 % of potassium and sodium combined (expressed as elemental sodium and elemental potassium),<br>— not more than 0,01 % of phosphorus (expressed as elemental phosphorus),<br>for use in the metallurgy <sup>(1)</sup>  | 0 %                     | 31.12.2017                         |
| ex 2825 10 00 | 10    | Hydroxylammonium chloride (CAS RN 5470-11-1)  | 0 %                     | 31.12.2017                         |
| ex 2825 50 00 | 20    | Copper (I or II) oxide containing by weight 78 % or more of copper and not more than 0,03 % of chloride   | 0 %                     | 31.12.2018                         |
| ex 2825 60 00 | 10    | Zirconium dioxide (CAS RN 1314-23-4)  | 0 %                     | 31.12.2017                         |
| ex 2826 19 90 | 10    | Tungsten hexafluoride with a purity of 99,9 % by weight or more (CAS RN 7783-82-6)  | 0 %                     | 31.12.2015                         |
| ex 2826 90 80 | 15    | Lithium hexafluorophosphate (CAS RN 21324-40-3)   | 0 %                     | 31.12.2016                         |

| CN code       | TARIC | Description  | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|------------------------------------|
| ex 2827 39 85 | 10    | Copper monochloride of a purity by weight of 96 % or more but not more than 99 % (CAS RN 7758-89-6)  | 0 %                     | 31.12.2018                         |
| ex 2827 39 85 | 20    | Antimony pentachloride of a purity by weight of 99 % or more (CAS RN 7647-18-9)  | 0 %                     | 31.12.2016                         |
| ex 2827 39 85 | 30    | Manganese dichloride (CAS RN 7773-01-5)  | 0 %                     | 31.12.2014                         |
| ex 2827 49 90 | 10    | Hydrated zirconium dichloride oxide  | 0 %                     | 31.12.2018                         |
| ex 2830 10 00 | 10    | Disodium tetrasulphide, containing by weight 38 % or less of sodium calculated on the dry weight   | 0 %                     | 31.12.2018                         |
| ex 2833 29 80 | 20    | Manganese sulphate monohydrate (CAS RN 10034-96-5)   | 0 %                     | 31.12.2018                         |
| ex 2833 29 80 | 30    | Zirconium sulphate (CAS RN 14644-61-2)   | 0 %                     | 31.12.2015                         |
| ex 2835 10 00 | 10    | Sodium hypophosphite monohydrate (CAS RN 10039-56-2)   | 0 %                     | 31.12.2017                         |
| ex 2836 91 00 | 20    | Lithium carbonate, containing one or more of the following impurities at the concentrations indicated:<br>— 2 mg/kg or more of arsenic,<br>— 200 mg/kg or more of calcium,<br>— 200 mg/kg or more of chlorides,<br>— 20 mg/kg or more of iron,<br>— 150 mg/kg or more of magnesium,<br>— 20 mg/kg or more of heavy metals,<br>— 300 mg/kg or more of potassium,<br>— 300 mg/kg or more of sodium,<br>— 200 mg/kg or more of sulphates,<br>determined according to the methods specified in the European Pharmacopœia | 0 %                     | 31.12.2018                         |
| ex 2836 99 17 | 20    | Zirconium (IV) basic carbonate (CAS RN 15667-84-2)   | 0 %                     | 31.12.2018                         |
| ex 2837 19 00 | 20    | Copper cyanide (CAS RN 544-92-3)   | 0 %                     | 31.12.2018                         |
| ex 2837 20 00 | 10    | Tetrasodium hexacyanoferrate (II) (CAS RN 13601-19-9)  | 0 %                     | 31.12.2016                         |
| ex 2837 20 00 | 20    | Ammonium iron (III) hexacyanoferrate (II) (CAS RN 25869-00-5)  | 0 %                     | 31.12.2017                         |
| ex 2839 19 00 | 10    | Disodium disilicate (CAS RN 13870-28-5)  | 0 %                     | 31.12.2017                         |
| ex 2839 90 00 | 20    | Calcium silicate (CAS RN 1344-95-2)  | 0 %                     | 31.12.2018                         |
| 2841 30 00    |       | Sodium dichromate (CAS RN 10588-01-9)  | 0 %                     | 31.12.2018                         |
| ex 2841 80 00 | 10    | Diammonium wolframate (ammonium paratungstate) (CAS RN 11120-25-5)   | 0 %                     | 31.12.2017                         |
| ex 2841 90 85 | 10    | Lithium cobalt(III) oxide with a cobalt content of at least 59 % (CAS RN 12190-79-3)   | 0 %                     | 31.12.2017                         |
| ex 2841 90 85 | 20    | Potassium titanium oxide in powder form with a purity of 99 % or more (CAS RN 12056-51-8)  | 0 %                     | 31.12.2018                         |
| ex 2842 10 00 | 10    | Synthetic Beta Zeolite powder  | 0 %                     | 31.12.2018                         |
| ex 2842 10 00 | 20    | Synthetic Chabasite Zeolite Powder   | 0 %                     | 31.12.2014                         |
| ex 2842 90 10 | 10    | Sodium selenate (CAS RN 13410-01-0)  | 0 %                     | 31.12.2014                         |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
| ex 2843 29 00 | 10    | Silver oxide, nitrate- and carbonate-free, with a silver content of at least 99,99 % by weight of the metal content, for the manufacture of silver oxide batteries <sup>(1)</sup>   | 0 %                     | 31.12.2016                         |
| 2845 10 00    |       | Heavy water (deuterium oxide) ( <i>Euratom</i> ) (CAS RN 7789-20-0)   | 0 %                     | 31.12.2018                         |
| 2845 90 10    |       | Deuterium and compounds thereof; hydrogen and compounds thereof, enriched in deuterium; mixtures and solutions containing these products ( <i>Euratom</i> )   | 0 %                     | 31.12.2018                         |
| ex 2845 90 90 | 10    | Helium-3 (CAS RN 14762-55-1)  | 0 %                     | 31.12.2016                         |
| ex 2845 90 90 | 20    | Water enriched at a level of 95 % or more by weight with oxygen-18 (CAS RN 14314-42-2)  | 0 %                     | 31.12.2018                         |
| ex 2845 90 90 | 30    | <sup>(13)</sup> C Carbon monoxide (CAS RN 1641-69-6)  | 0 %                     | 31.12.2016                         |
| ex 2845 90 90 | 40    | Iron boride enriched at a level of more than 95 % by weight with boron-10 (CAS RN 200513-39-9)  | 0 %                     | 31.12.2018                         |
| ex 2846 10 00 | 10    | Rare-earth concentrate containing by weight 60 % or more but not more than 95 % of rare-earth oxides and not more than 1 % each of zirconium oxide, aluminium oxide or iron oxide, and having a loss on ignition of 5 % or more by weight | 0 %                     | 31.12.2018                         |
| ex 3824 90 97 | 48    |   |                         |                                    |
| ex 2846 10 00 | 20    | Dicermium tricarboxylate, whether or not hydrated (CAS RN 537-01-9)   | 0 %                     | 31.12.2018                         |
| ex 2846 10 00 | 30    | Cerium lanthanum carbonate, whether or not hydrated   | 0 %                     | 31.12.2018                         |
| ex 2846 10 00 | 40    | Cerium lanthanum neodymium praseodymium carbonate, whether or not hydrated  | 0 %                     | 31.12.2014                         |
| 2846 90 00    |       | Compounds, inorganic or organic, of rare-earth metals, of yttrium or of scandium or of mixtures of these metals, other than those of subheading 2846 10 00  | 0 %                     | 31.12.2018                         |
| ex 2848 00 00 | 10    | Phosphine (CAS RN 7803-51-2)  | 0 %                     | 31.12.2018                         |
| ex 2850 00 20 | 10    | Silane (CAS RN 7803-62-5)   | 0 %                     | 31.12.2018                         |
| ex 2850 00 20 | 20    | Arsine (CAS RN 7784-42-1)   | 0 %                     | 31.12.2018                         |
| ex 2850 00 20 | 30    | Titanium nitride with a particle size of not more than 250 nm (CAS RN 25583-20-4)   | 0 %                     | 31.12.2017                         |
| ex 2850 00 20 | 40    | Germanium tetrahydride (CAS RN 7782-65-2)   | 0 %                     | 31.12.2016                         |
| ex 2850 00 20 | 50    | Sodium tetrahydroborate (CAS 16940-66-2) with:<br>— a purity by weight of 98 % or more and<br>— not more than 10ppm iron<br>for use as an additive in the manufacture of oxygen barrier polymer articles <sup>(1)</sup>                   | 0 %                     | 31.12.2017                         |
| ex 2850 00 60 | 10    | Sodium azide (CAS RN 26628-22-8)  | 0 %                     | 31.12.2018                         |
| ex 2853 00 90 | 10    | Chlorosulphonyl isocyanate (CAS RN 1189-71-5)   | 0 %                     | 31.12.2016                         |
| ex 2903 39 90 | 10    | Carbon tetrafluoride (tetrafluoromethane) (CAS RN 75-73-0)  | 0 %                     | 31.12.2018                         |

| CN code       | TARIC | Description  | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|------------------------------------|
| ex 2903 39 90 | 15    | Perfluoro(4-methyl-2-pentene) (CAS RN 84650-68-0)  | 0 %                     | 31.12.2016                         |
| ex 2903 39 90 | 25    | 2,3,3,3-Tetrafluoroprop-1-ene (CAS RN 754-12-1)  | 0 %                     | 31.12.2017                         |
| ex 2903 39 90 | 30    | Perfluoroethane (CAS RN 76-16-4)   | 0 %                     | 31.12.2018                         |
| ex 2903 39 90 | 40    | 1,1-Difluoroethane (CAS RN 75-37-6)  | 0 %                     | 31.12.2018                         |
| ex 2903 39 90 | 50    | 1,1,1,3-Pentafluoropropane (CAS RN 460-73-1)   | 0 %                     | 31.12.2018                         |
| ex 2903 39 90 | 70    | 1,1,1,2-Tetrafluoroethane, certified odourless containing a maximum:<br>— 600 ppm by weight of 1,1,2-tetrafluoroethane,<br>— 2 ppm by weight of pentafluoroethane,<br>— 2 ppm by weight of chlorodifluoromethane,<br>— 2 ppm by weight of chloropentafluoroethane,<br>— 2 ppm by weight of dichlorodifluoromethane<br>for use in the manufacture of pharmaceutical grade propellant for medical metred dose inhalers (CAS RN 811-97-2) (!) | 0 %                     | 31.12.2016                         |
| ex 2903 39 90 | 75    | <i>Trans</i> -1,3,3,3-tetrafluoroprop-1-ene (CAS RN 1645-83-6)   | 0 %                     | 31.12.2018                         |
| ex 2903 39 90 | 80    | Hexafluoropropene (CAS RN 116-15-4)  | 0 %                     | 31.12.2016                         |
| ex 2903 77 30 | 10    | 1,1,1-Trichlorotrifluoroethane (CAS RN 354-58-5)   | 0 %                     | 31.12.2018                         |
| ex 2903 77 90 | 10    | Chlorotrifluoroethylene (CAS RN 79-38-9)   | 0 %                     | 31.12.2016                         |
| ex 2903 89 90 | 10    | 1,6,7,8,9,14,15,16,17,17,18,18-Dodecachloropentacyclo [12.2.1.1 <sup>6,9</sup> .0 <sup>2,13</sup> .0 <sup>5,10</sup> ]octadeca-7,15-diene (CAS RN 13560-89-9)  | 0 %                     | 31.12.2018                         |
| ex 2903 89 90 | 30    | Octafluorocyclopentene (CAS RN 559-40-0)   | 0 %                     | 31.12.2016                         |
| ex 2903 89 90 | 40    | Hexabromocyclododecane   | 0 %                     | 31.12.2016                         |
| ex 2903 89 90 | 50    | Chlorocyclopentane (CAS RN 930-28-9)   | 0 %                     | 31.12.2017                         |
| ex 2903 99 90 | 20    | 1,2-Bis(pentabromophenyl)ethane (CAS RN 84852-53-9)  | 0 %                     | 31.12.2018                         |
| ex 2903 99 90 | 40    | 2,6-Dichlorotoluene, of a purity by weight of 99 % or more and containing:<br>— 0,001 mg/kg or less of tetrachlorodibenzodioxines,<br>— 0,001 mg/kg or less of tetrachlorodibenzofurans,<br>— 0,2 mg/kg or less of tetrachlorobiphenyls  | 0 %                     | 31.12.2018                         |
| ex 2903 99 90 | 50    | Fluorobenzene (CAS RN 462-06-6)  | 0 %                     | 31.12.2018                         |
| ex 2903 99 90 | 70    | $\alpha,\alpha,\alpha',\alpha'$ -Tetrachloro- <i>o</i> -xylene (CAS RN 25641-99-0)   | 0 %                     | 31.12.2015                         |
| ex 2903 99 90 | 80    | 1-Bromo-3,4,5-trifluorobenzene (CAS RN 138526-69-9)  | 0 %                     | 31.12.2018                         |
| ex 2903 99 90 | 85    | 2-Bromo-9H-fluorene (CAS RN 1133-80-8)   | 0 %                     | 31.12.2018                         |
| ex 2904 10 00 | 30    | Sodium <i>p</i> -styrenesulphonate (CAS RN 2695-37-6)  | 0 %                     | 31.12.2014                         |
| ex 2904 10 00 | 50    | Sodium 2-methylprop-2-ene-1-sulphonate (CAS RN 1561-92-8)  | 0 %                     | 31.12.2014                         |
| ex 2904 20 00 | 10    | Nitromethane (CAS RN 75-52-5)  | 0 %                     | 31.12.2015                         |
| ex 2904 20 00 | 20    | Nitroethane (CAS RN 79-24-3)   | 0 %                     | 31.12.2015                         |
| ex 2904 20 00 | 30    | 1-Nitropropane (CAS RN 108-03-2)   | 0 %                     | 31.12.2015                         |
| ex 2904 20 00 | 40    | 2-Nitropropane (CAS RN 79-46-9)  | 0 %                     | 31.12.2014                         |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
| ex 2904 90 40 | 10    | Trichloronitromethane, for the manufacture of goods of subheading 3808 92 (CAS RN 76-06-2) (1)  | 0 %                     | 31.12.2014                         |
| ex 2904 90 95 | 20    | 1-Chloro-2,4-dinitrobenzene (CAS RN 97-00-7)  | 0 %                     | 31.12.2014                         |
| ex 2904 90 95 | 30    | Tosyl chloride (CAS RN 98-59-9)   | 0 %                     | 31.12.2014                         |
| ex 2904 90 95 | 40    | 4-Chlorobenzenesulphonyl chloride (CAS RN 98-60-2)  | 0 %                     | 31.12.2017                         |
| ex 2904 90 95 | 50    | Ethanesulphonyl chloride (CAS RN 594-44-5)  | 0 %                     | 31.12.2018                         |
| ex 2905 19 00 | 11    | Potassium tert-butanolate (CAS RN 865-47-4), whether or not in the form of a solution in tetrahydrofuran according to note 1e to Chapter 29 of the CN | 0 %                     | 31.12.2018                         |
| ex 2905 19 00 | 30    | 2,6-Dimethylheptan-4-ol (CAS RN 108-82-7)   | 0 %                     | 31.12.2018                         |
| ex 2905 19 00 | 40    | 2,6-Dimethylheptan-2-ol (CAS RN 13254-34-7)   | 0 %                     | 31.12.2014                         |
| ex 2905 19 00 | 70    | Titanium tetrabutanolate (CAS RN 5593-70-4)   | 0 %                     | 31.12.2017                         |
| ex 2905 19 00 | 80    | Titanium tetraisopropoxide (CAS RN 546-68-9)  | 0 %                     | 31.12.2017                         |
| ex 2905 19 00 | 85    | Titanium tetraethanolate (CAS RN 3087-36-3)   | 0 %                     | 31.12.2018                         |
| ex 2905 29 90 | 10    | 3,5-Dimethylhex-1-yn-3-ol (CAS RN 107-54-0)   | 0 %                     | 31.12.2014                         |
| ex 2905 29 90 | 20    | Dec-9-en-1-ol (CAS RN 13019-22-2)   | 0 %                     | 31.12.2014                         |
| ex 2905 29 90 | 30    | Dodeca-8,10-dien-1-ol (CAS RN 33956-49-9)   | 0 %                     | 31.12.2015                         |
| ex 2905 39 95 | 10    | Propane-1,3-diol (CAS RN 504-63-2)  | 0 %                     | 31.12.2015                         |
| ex 2905 39 95 | 20    | Butane-1,2-diol (CAS RN 584-03-2)   | 0 %                     | 31.12.2016                         |
| ex 2905 39 95 | 30    | 2,4,7,9-Tetramethyl-4,7-decanediol (CAS RN 17913-76-7)  | 0 %                     | 31.12.2016                         |
| ex 2905 39 95 | 40    | Decane-1,10-diol (CAS RN 112-47-0)  | 0 %                     | 31.12.2017                         |
| ex 2905 39 95 | 50    | 2-Methyl-2-propylpropane-1,3-diol (CAS RN 78-26-2)  | 0 %                     | 31.12.2018                         |
| ex 2905 49 00 | 10    | Ethylidynetrimethanol (CAS RN 77-85-0)  | 0 %                     | 31.12.2014                         |
| ex 2905 59 98 | 20    | 2,2,2-Trifluoroethanol (CAS RN 75-89-8)   | 0 %                     | 31.12.2014                         |
| 2906 11 00    |       | Menthol (CAS RN 1490-04-6)  | 0 %                     | 31.12.2018                         |
| ex 2906 19 00 | 10    | Cyclohex-1,4-ylenedimethanol (CAS RN 105-08-8)  | 0 %                     | 31.12.2018                         |
| ex 2906 19 00 | 20    | 4,4'-Isopropylidenedicyclohexanol (CAS RN 80-04-6)  | 0 %                     | 31.12.2018                         |
| ex 2906 29 00 | 10    | 2,2'-( <i>m</i> -Phenylene)dipropan-2-ol (CAS RN 1999-85-5)   | 0 %                     | 31.12.2014                         |
| ex 2906 29 00 | 20    | 1-Hydroxymethyl-4-methyl-2,3,5,6-tetrafluorobenzene (CAS RN 79538-03-7)   | 0 %                     | 31.12.2018                         |
| ex 2906 29 00 | 30    | 2-Phenylethanol (CAS RN 60-12-8)  | 0 %                     | 31.12.2017                         |
| ex 2907 15 90 | 10    | 2-Naphthol (CAS RN 135-19-3)  | 0 %                     | 31.12.2016                         |
| ex 2907 19 90 | 10    | 2,3,5-Trimethylphenol (CAS RN 697-82-5)   | 0 %                     | 31.12.2014                         |
| ex 2907 19 90 | 20    | Biphenyl-4-ol (CAS RN 92-69-3)  | 0 %                     | 31.12.2018                         |
| ex 2907 21 00 | 10    | Resorcinol (CAS RN 108-46-3)  | 0 %                     | 31.12.2018                         |

| CN code       | TARIC | Description  | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|------------------------------------|
| ex 2907 23 00 | 10    | 4,4'-Isopropylidenediphenol (CAS RN 80-05-7)   | 0 %                     | 31.12.2017                         |
| ex 2907 29 00 | 15    | 6,6'-Di-tert-butyl-4,4'-butylidenedi-m-cresol (CAS RN 85-60-9)   | 0 %                     | 31.12.2018                         |
| ex 2907 29 00 | 20    | 4,4'-(3,3,5-Trimethylcyclohexylidene)diphenol (CAS RN 129188-99-4)   | 0 %                     | 31.12.2018                         |
| ex 2907 29 00 | 30    | 4,4',4''-Ethylidynetriphenol (CAS RN 27955-94-8)   | 0 %                     | 31.12.2018                         |
| ex 2907 29 00 | 35    | 4-[2-(4-Hydroxy-3-prop-2-enylphenyl)propan-2-yl]-2-prop-2-enylphenol (CAS RN 1745-89-7)  | 0 %                     | 31.12.2016                         |
| ex 2907 29 00 | 40    | 2,3,5-Trimethylhydroquinone (CAS RN 700-13-0)  | 0 %                     | 31.12.2016                         |
| ex 2907 29 00 | 45    | 2-Methylhydroquinone (CAS RN 95-71-6)  | 0 %                     | 31.12.2016                         |
| ex 2907 29 00 | 50    | 6,6',6''-Tricyclohexyl-4,4',4''-butane-1,1,3-triyltri ( <i>m</i> -cresol) (CAS RN 111850-25-0)                                 | 0 %                     | 31.12.2018                         |
| ex 2907 29 00 | 55    | Biphenyl-2,2'-diol (CAS RN 1806-29-7)  | 0 %                     | 31.12.2017                         |
| ex 2907 29 00 | 70    | 2,2',2'',6,6',6''-Hexa-tert-butyl- $\alpha,\alpha',\alpha''$ -(mesitylene-2,4,6-triyl)tri- <i>p</i> -cresol (CAS RN 1709-70-2) | 0 %                     | 31.12.2018                         |
| ex 2907 29 00 | 85    | Phloroglucinol whether or not hydrated   | 0 %                     | 31.12.2018                         |
| ex 2908 19 00 | 10    | Pentafluorophenol (CAS RN 771-61-9)  | 0 %                     | 31.12.2018                         |
| ex 2908 19 00 | 20    | 4,4'-(Perfluoroisopropylidene)diphenol (CAS RN 1478-61-1)  | 0 %                     | 31.12.2018                         |
| ex 2908 99 00 | 30    | 4-Nitrophenol (CAS RN 100-02-7)  | 0 %                     | 31.12.2018                         |
| ex 2908 99 00 | 40    | 4,5-Dihydroxynaphthalene-2,7-disulphonic acid (CAS RN 148-25-4)  | 0 %                     | 31.12.2017                         |
| ex 2909 19 90 | 20    | Bis(2-chloroethyl) ether (CAS RN 111-44-4)   | 0 %                     | 31.12.2018                         |
| ex 2909 19 90 | 30    | Mixture of isomers of nonafluorobutyl methyl ether or nonafluorobutyl ethyl ether, of a purity by weight of 99 % or more       | 0 %                     | 31.12.2018                         |
| ex 2909 19 90 | 50    | 3-Ethoxy-perfluoro-2-methylhexane (CAS RN 297730-93-9)   | 0 %                     | 31.12.2016                         |
| ex 2909 19 90 | 60    | 1-Methoxyheptafluoropropane (CAS RN 375-03-1)  | 0 %                     | 31.12.2018                         |
| ex 2909 20 00 | 10    | 8-Methoxycedrane (CAS RN 19870-74-7)   | 0 %                     | 31.12.2016                         |
| ex 2909 30 38 | 10    | Bis(pentabromophenyl) ether (CAS RN 1163-19-5)   | 0 %                     | 31.12.2018                         |
| ex 2909 30 38 | 20    | 1,1'-Propane-2,2-diylbis[3,5-dibromo-4-(2,3-dibromopropoxy)benzene] (CAS RN 21850-44-2)  | 0 %                     | 31.12.2016                         |
| ex 2909 30 90 | 10    | 2-(Phenylmethoxy)naphthalene (CAS RN 613-62-7)   | 0 %                     | 31.12.2014                         |
| ex 2909 30 90 | 20    | 1,2-Bis(3-methyl-phenoxy)ethane (CAS RN 54914-85-1)  | 0 %                     | 31.12.2014                         |
| ex 2909 30 90 | 30    | 3,4,5-Trimethoxytoluene (CAS RN 6443-69-2)   | 0 %                     | 31.12.2015                         |
| ex 2909 50 00 | 10    | 4-(2-Methoxyethyl)phenol (CAS RN 56718-71-9)   | 0 %                     | 31.12.2018                         |
| ex 2909 50 00 | 20    | Ubiquinol (CAS RN 992-78-9)  | 0 %                     | 31.12.2015                         |
| ex 2909 60 00 | 10    | Bis( $\alpha,\alpha$ -dimethylbenzyl) peroxide (CAS RN 80-43-3)  | 0 %                     | 31.12.2018                         |
| ex 2909 60 00 | 20    | 1,4-Di(2-tert-butylperoxyisopropyl)benzene (CAS RN 25155-25-3)   | 0 %                     | 31.12.2016                         |
| ex 2910 90 00 | 15    | 1,2-Epoxy-cyclohexane (CAS RN 286-20-4)  | 0 %                     | 31.12.2018                         |

| CN code       | TARIC | Description  | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|------------------------------------|
| ex 2910 90 00 | 30    | 2,3-Epoxypropan-1-ol (glycidol) (CAS RN 556-52-5)  | 0 %                     | 31.12.2018                         |
| ex 2910 90 00 | 80    | Allyl glycidyl ether (CAS RN 106-92-3)   | 0 %                     | 31.12.2016                         |
| ex 2912 29 00 | 40    | (2E,4E,6E,8E,10E,12E)-2,7,11-Trimethyl-13-(2,6,6-trimethyl-1-cyclohexen-1-yl)-2,4,6,8,10,12-tridecahexaenal (CAS RN 1638-05-7) | 0 %                     | 31.12.2016                         |
| ex 2912 29 00 | 50    | 4-Isobutylbenzaldehyde (CAS RN 40150-98-9)   | 0 %                     | 31.12.2017                         |
| ex 2912 29 00 | 60    | 3,4-Dimethylbenzaldehyde (CAS RN 5973-71-7)  | 0 %                     | 31.12.2018                         |
| ex 2912 49 00 | 10    | 3-Phenoxybenzaldehyde (CAS RN 39515-51-0)  | 0 %                     | 31.12.2018                         |
| ex 2912 49 00 | 20    | 4-Hydroxybenzaldehyde (CAS RN 123-08-0)  | 0 %                     | 31.12.2017                         |
| ex 2912 49 00 | 30    | Salicylaldehyde (CAS RN 90-02-8)   | 0 %                     | 31.12.2015                         |
| ex 2914 19 90 | 20    | Heptan-2-one (CAS RN 110-43-0)   | 0 %                     | 31.12.2017                         |
| ex 2914 19 90 | 30    | 3-Methylbutanone (CAS RN 563-80-4)   | 0 %                     | 31.12.2017                         |
| ex 2914 19 90 | 40    | Pentan-2-one (CAS RN 107-87-9)   | 0 %                     | 31.12.2017                         |
| ex 2914 29 00 | 20    | Cyclohexadec-8-enone (CAS RN 3100-36-5)  | 0 %                     | 31.12.2018                         |
| ex 2914 29 00 | 30    | (R)-p-Mentha-1(6),8-dien-2-one (CAS RN 6485-40-1)  | 0 %                     | 31.12.2015                         |
| ex 2914 29 00 | 40    | Camphor  | 0 %                     | 31.12.2018                         |
| ex 2914 29 00 | 50    | <i>trans</i> - $\beta$ -Damascone (CAS RN 23726-91-2)  | 0 %                     | 31.12.2016                         |
| ex 2914 39 00 | 30    | Benzophenone (CAS RN 119-61-9)   | 0 %                     | 31.12.2017                         |
| ex 2914 39 00 | 50    | 4-Phenylbenzophenone (CAS RN 2128-93-0)  | 0 %                     | 31.12.2018                         |
| ex 2914 39 00 | 60    | 4-Methylbenzophenone (CAS RN 134-84-9)   | 0 %                     | 31.12.2018                         |
| ex 2914 39 00 | 70    | Benzil (CAS RN 134-81-6)   | 0 %                     | 31.12.2017                         |
| ex 2914 39 00 | 80    | 4'-Methylacetophenone (CAS RN 122-00-9)  | 0 %                     | 31.12.2017                         |
| ex 2914 50 00 | 20    | 3'-Hydroxyacetophenone (CAS RN 121-71-1)   | 0 %                     | 31.12.2015                         |
| ex 2914 50 00 | 25    | 4'-Methoxyacetophenone (CAS RN 100-06-1)   | 0 %                     | 31.12.2018                         |
| ex 2914 50 00 | 30    | 2'-Hydroxyacetophenone (CAS RN 118-93-4)   | 0 %                     | 31.12.2018                         |
| ex 2914 50 00 | 36    | 2,7-Dihydroxy-9-fluorenone (CAS RN 42523-29-5)   | 0 %                     | 31.12.2018                         |
| ex 2914 50 00 | 40    | 4-(4-Hydroxyphenyl)butan-2-one (CAS RN 5471-51-2)  | 0 %                     | 31.12.2016                         |
| ex 2914 50 00 | 45    | 3,4-Dihydroxybenzophenone (CAS RN 10425-11-3)  | 0 %                     | 31.12.2017                         |
| ex 2914 50 00 | 60    | 2,2-Dimethoxy-2-phenylacetophenone (CAS RN 24650-42-8)   | 0 %                     | 31.12.2017                         |
| ex 2914 50 00 | 70    | 16 $\alpha$ ,17 $\alpha$ -Epoxy-3 $\beta$ -hydroxypregn-5-en-20-one (CAS RN 974-23-2)  | 0 %                     | 31.12.2017                         |
| ex 2914 50 00 | 80    | 2',6'-Dihydroxyacetophenone (CAS RN 699-83-2)  | 0 %                     | 31.12.2018                         |
| ex 2914 69 90 | 10    | 2-Ethylanthraquinone (CAS RN 84-51-5)  | 0 %                     | 31.12.2018                         |
| ex 2914 69 90 | 20    | 2-Pentylanthraquinone (CAS RN 13936-21-5)  | 0 %                     | 31.12.2014                         |
| ex 2914 69 90 | 30    | 1,4-Dihydroxyanthraquinone (CAS RN 81-64-1)  | 0 %                     | 31.12.2018                         |
| ex 2914 69 90 | 40    | p-Benzoquinone (CAS RN 106-51-4)   | 0 %                     | 31.12.2016                         |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
| ex 2914 70 00 | 20    | 2,4'-Difluorobenzophenone (CAS RN 342-25-6)   | 0 %                     | 31.12.2017                         |
| ex 2914 70 00 | 40    | Perfluoro(2-methylpentan-3-one) (CAS RN 756-13-8)   | 0 %                     | 31.12.2018                         |
| ex 2914 70 00 | 50    | 3'-Chloropropiophenone (CAS RN 34841-35-5)  | 0 %                     | 31.12.2018                         |
| ex 2914 70 00 | 60    | 4'-tert-Butyl-2',6'-dimethyl-3',5'-dinitroacetophenone (CAS RN 81-14-1)                               | 0 %                     | 31.12.2015                         |
| ex 2914 70 00 | 70    | 4-Chloro-4'-hydroxybenzophenone (CAS RN 42019-78-3)   | 0 %                     | 31.12.2016                         |
| ex 2915 29 00 | 10    | Antimony triacetate (CAS RN 6923-52-0)  | 0 %                     | 31.12.2018                         |
| ex 2915 39 00 | 20    | Isopentyl acetate (CAS RN 123-92-2)   | 0 %                     | 31.12.2017                         |
| ex 2915 39 00 | 40    | tert-Butyl acetate (CAS RN 540-88-5)  | 0 %                     | 31.12.2018                         |
| ex 2915 39 00 | 50    | 3-Acetylphenyl acetate (CAS RN 2454-35-5)   | 0 %                     | 31.12.2014                         |
| ex 2915 39 00 | 60    | Dodec-8-enyl acetate (CAS RN 28079-04-1)  | 0 %                     | 31.12.2015                         |
| ex 2915 39 00 | 65    | Dodeca-7,9-dienyl acetate (CAS RN 54364-62-4)   | 0 %                     | 31.12.2015                         |
| ex 2915 39 00 | 70    | Dodec-9-enyl acetate (CAS RN 16974-11-1)  | 0 %                     | 31.12.2015                         |
| ex 2915 39 00 | 75    | Isobornyl acetate (CAS RN 125-12-2)   | 0 %                     | 31.12.2016                         |
| ex 2915 39 00 | 80    | 1-Phenylethyl acetate (CAS RN 93-92-5)  | 0 %                     | 31.12.2016                         |
| ex 2915 39 00 | 85    | 2-tert-Butylcyclohexyl acetate (CAS RN 88-41-5)   | 0 %                     | 31.12.2018                         |
| ex 2915 60 19 | 10    | Ethyl butyrate (CAS RN 105-54-4)  | 0 %                     | 31.12.2017                         |
| ex 2915 90 70 | 30    | 3,3-Dimethylbutyryl chloride (CAS RN 7065-46-5)   | 0 %                     | 31.12.2017                         |
| ex 2915 90 70 | 40    | Nonanoic acid (pelargonic acid) (CAS RN 112-05-0)   | 0 %                     | 31.12.2018                         |
| ex 2915 90 70 | 50    | Allyl heptanoate (CAS RN 142-19-8)  | 0 %                     | 31.12.2014                         |
| ex 2915 90 70 | 55    | Triethyl orthoformate (CAS RN 122-51-0)   | 0 %                     | 31.12.2018                         |
| ex 2915 90 70 | 60    | Ethyl-6,8-dichlorooctanoate (CAS RN 1070-64-0)  | 0 %                     | 31.12.2015                         |
| ex 2915 90 70 | 70    | Cobalt borate neodecanoate complexes, with a purity by weight of 92 % or more (CAS RN 68457-13-6)     | 0 %                     | 31.12.2016                         |
| ex 2915 90 70 | 75    | 2,2-Dimethylbutyryl chloride (CAS RN 5856-77-9)   | 0 %                     | 31.12.2017                         |
| ex 2915 90 70 | 80    | Ethyl difluoroacetate (CAS RN 454-31-9)   | 0 %                     | 31.12.2016                         |
| ex 2916 12 00 | 10    | 2-tert-Butyl-6-(3-tert-butyl-2-hydroxy-5-methylbenzyl)-4-methylphenyl acrylate (CAS RN 61167-58-6)    | 0 %                     | 31.12.2018                         |
| ex 2916 12 00 | 40    | 2,4-Di-tert-pentyl-6-[1-(3,5-di-tert-pentyl-2-hydroxyphenyl)ethyl]phenylacrylate (CAS RN 123968-25-2) | 0 %                     | 31.12.2018                         |
| ex 2916 12 00 | 70    | 2-(2-Vinyloxyethoxy)ethyl acrylate (CAS RN 86273-46-3)  | 0 %                     | 31.12.2017                         |
| ex 2916 13 00 | 10    | Hydroxyzinc methacrylate powder (CAS RN 63451-47-8)   | 0 %                     | 31.12.2014                         |
| ex 2916 13 00 | 20    | Zinc dimethacrylate, in the form of powder (CAS RN 13189-00-9)  | 0 %                     | 31.12.2018                         |
| ex 2916 14 00 | 10    | 2,3-Epoxypropyl methacrylate (CAS RN 106-91-2)  | 0 %                     | 31.12.2018                         |
| ex 2916 19 95 | 20    | Methyl 3,3-dimethylpent-4-enoate (CAS RN 63721-05-1)  | 0 %                     | 31.12.2018                         |
| ex 2916 19 95 | 40    | Sorbic acid for use in the manufacture of animal feeds (CAS RN 110-44-1) <sup>(1)</sup>               | 0 %                     | 31.12.2018                         |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
| ex 2916 20 00 | 50    | Ethyl 2,2-dimethyl-3-(2-methylpropenyl)cyclopropanecarboxylate (CAS RN 97-41-6)             | 0 %                     | 31.12.2018                         |
| ex 2916 20 00 | 60    | 3-Cyclohexylpropionic acid (CAS RN 701-97-3)  | 0 %                     | 31.12.2015                         |
| ex 2916 31 00 | 10    | Benzyl benzoate (CAS RN 120-51-4)   | 0 %                     | 31.12.2016                         |
| ex 2916 39 90 | 10    | 2,3,4,5-Tetrafluorobenzoic acid (CAS RN 1201-31-6)  | 0 %                     | 31.12.2016                         |
| ex 2916 39 90 | 15    | 2-Chloro-5-nitrobenzoic acid (CAS RN 2516-96-3)   | 0 %                     | 31.12.2016                         |
| ex 2916 39 90 | 20    | 3,5-Dichlorobenzoyl chloride (CAS RN 2905-62-6)   | 3,6 %                   | 31.12.2018                         |
| ex 2916 39 90 | 25    | 2-Methyl-3-(4-Fluorophenyl)-propionyl chloride (CAS RN 1017183-70-8)                        | 0 %                     | 31.12.2015                         |
| ex 2916 39 90 | 30    | 2,4,6-Trimethylbenzoyl chloride (CAS RN 938-18-1)   | 0 %                     | 31.12.2015                         |
| ex 2916 39 90 | 35    | Methyl 4- <i>tert</i> -butylbenzoate (CAS RN 26537-19-9)                                    | 0 %                     | 31.12.2018                         |
| ex 2916 39 90 | 38    | 6-Bromonaphthalene-2-carboxylic acid (CAS RN 5773-80-8)                                     | 0 %                     | 31.12.2018                         |
| ex 2916 39 90 | 45    | 2-Chlorobenzoic acid (CAS RN 118-91-2)  | 0 %                     | 31.12.2016                         |
| ex 2916 39 90 | 50    | 3,5-Dimethylbenzoyl chloride (CAS RN 6613-44-1)   | 0 %                     | 31.12.2018                         |
| ex 2916 39 90 | 55    | 4- <i>tert</i> -Butylbenzoic acid (CAS RN 98-73-7)  | 0 %                     | 31.12.2017                         |
| ex 2916 39 90 | 60    | 4-Ethylbenzoyl chloride (CAS RN 16331-45-6)   | 0 %                     | 31.12.2018                         |
| ex 2916 39 90 | 70    | Ibuprofen (INN) (CAS RN 15687-27-1)   | 0 %                     | 31.12.2018                         |
| ex 2916 39 90 | 75    | <i>m</i> -Toluic acid (CAS RN 99-04-7)  | 0 %                     | 31.12.2017                         |
| ex 2916 39 90 | 85    | (2,4,5-Trifluorophenyl)acetic acid (CAS RN 209995-38-0)                                     | 0 %                     | 31.12.2017                         |
| ex 2917 11 00 | 20    | Bis( <i>p</i> -methylbenzyl) oxalate (CAS RN 18241-31-1)                                    | 0 %                     | 31.12.2018                         |
| ex 2917 11 00 | 30    | Cobalt oxalate (CAS RN 814-89-1)  | 0 %                     | 31.12.2014                         |
| ex 2917 19 10 | 10    | Dimethyl malonate (CAS RN 108-59-8)   | 0 %                     | 31.12.2014                         |
| ex 2917 19 10 | 20    | Diethyl malonate (CAS RN 105-53-3)  | 0 %                     | 31.12.2017                         |
| ex 2917 19 90 | 20    | Sodium 1,2-bis(cyclohexyloxycarbonyl)ethanesulphonate (CAS RN 23386-52-9)                   | 0 %                     | 31.12.2018                         |
| ex 2917 19 90 | 30    | Ethylene brassylate (CAS RN 105-95-3)   | 0 %                     | 31.12.2014                         |
| ex 2917 19 90 | 50    | Tetradecanedioic acid (CAS RN 821-38-5)   | 0 %                     | 31.12.2015                         |
| ex 2917 19 90 | 70    | Itaconic acid (CAS RN 97-65-4)  | 0 %                     | 31.12.2018                         |
| ex 2917 20 00 | 30    | 1,4,5,6,7,7-Hexachloro-8,9,10-trinorborn-5-ene-2,3-dicarboxylic anhydride (CAS RN 115-27-5) | 0 %                     | 31.12.2018                         |
| ex 2917 20 00 | 40    | 3-Methyl-1,2,3,6-tetrahydrophthalic anhydride (CAS RN 5333-84-6)                            | 0 %                     | 31.12.2018                         |
| ex 2917 34 00 | 10    | Diallyl phthalate (CAS RN 131-17-9)   | 0 %                     | 31.12.2018                         |
| ex 2917 39 95 | 20    | Dibutyl-1,4-benzenedicarboxylate (CAS RN 1962-75-0)   | 0 %                     | 31.12.2015                         |

| CN code       | TARIC | Description  | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|------------------------------------|
| ex 2917 39 95 | 30    | Benzene-1,2:4,5-tetracarboxylic dianhydride (CAS RN 89-32-7)   | 0 %                     | 31.12.2015                         |
| ex 2918 16 00 | 20    | Calcium digluconate monohydrate (CAS RN 66905-23-5) for use in the manufacture of calcium gluconate lactate (CAS RN 11116-97-5) (1)  | 0 %                     | 31.12.2018                         |
| ex 2918 19 98 | 20    | L-Malic acid (CAS RN 97-67-6)  | 0 %                     | 31.12.2018                         |
| ex 2918 29 00 | 10    | Monohydroxynaphthoic acids   | 0 %                     | 31.12.2018                         |
| ex 2918 29 00 | 35    | Propyl 3,4,5-trihydroxybenzoate (CAS RN 121-79-9)  | 0 %                     | 31.12.2017                         |
| ex 2918 29 00 | 50    | Hexamethylene bis[3-(3,5-di- <i>tert</i> -butyl-4-hydroxyphenyl)propionate] (CAS RN 35074-77-2)  | 0 %                     | 31.12.2018                         |
| ex 2918 29 00 | 60    | Methyl-, ethyl-, propyl- or butyl esters of 4-hydroxybenzoic acid or their sodium salts (CAS RN 35285-68-8, 99-76-3, 5026-62-0, 94-26-8, 94-13-3, 35285-69-9, 120-47-8, 36457-20-2 or 4247-02-3) | 0 %                     | 31.12.2016                         |
| ex 2918 30 00 | 30    | Methyl-2-benzoylbenzoate (CAS RN 606-28-0)   | 0 %                     | 31.12.2018                         |
| ex 2918 30 00 | 50    | Ethyl acetoacetate (CAS RN 141-97-9)   | 0 %                     | 31.12.2017                         |
| ex 2918 99 90 | 10    | 3,4-Epoxy-cyclohexylmethyl 3,4-epoxy-cyclohexanecarboxylate (CAS RN 2386-87-0)   | 0 %                     | 31.12.2018                         |
| ex 2918 99 90 | 15    | Ethyl 2,3-epoxy-3-phenylbutyrate (CAS RN 77-83-8)  | 0 %                     | 31.12.2017                         |
| ex 2918 99 90 | 20    | Methyl 3-methoxyacrylate (CAS RN 5788-17-0)  | 0 %                     | 31.12.2014                         |
| ex 2918 99 90 | 30    | Methyl 2-(4-hydroxyphenoxy)propionate (CAS RN 96562-58-2)  | 0 %                     | 31.12.2018                         |
| ex 2918 99 90 | 40    | <i>trans</i> -4-Hydroxy-3-methoxycinnamic acid (CAS RN 1135-24-6)  | 0 %                     | 31.12.2018                         |
| ex 2918 99 90 | 50    | Methyl 3,4,5-trimethoxybenzoate (CAS RN 1916-07-0)   | 0 %                     | 31.12.2018                         |
| ex 2918 99 90 | 60    | 3,4,5-Trimethoxybenzoic acid (CAS RN 118-41-2)   | 0 %                     | 31.12.2018                         |
| ex 2918 99 90 | 70    | Allyl-(3-methylbutoxy)acetate (CAS RN 67634-00-8)  | 0 %                     | 31.12.2014                         |
| ex 2918 99 90 | 80    | Sodium 5-[2-chloro-4-(trifluoromethyl)phenoxy]-2-nitrobenzoate (CAS RN 62476-59-9)   | 0 %                     | 31.12.2016                         |
| ex 2919 90 00 | 10    | 2,2'-Methylenebis(4,6-di- <i>tert</i> -butylphenyl) phosphate, monosodium salt (CAS RN 85209-91-2)   | 0 %                     | 31.12.2018                         |
| ex 2919 90 00 | 30    | Aluminium hydroxybis[2,2'-methylenebis(4,6-di- <i>tert</i> -butylphenyl)phosphate] (CAS RN 151841-65-5)  | 0 %                     | 31.12.2018                         |
| ex 2919 90 00 | 40    | Tri- <i>n</i> -hexylphosphate (CAS RN 2528-39-4)   | 0 %                     | 31.12.2018                         |
| ex 2919 90 00 | 50    | Triethyl phosphate (CAS RN 78-40-0)  | 0 %                     | 31.12.2016                         |
| ex 2920 19 00 | 10    | Fenitrothion (ISO) (CAS RN 122-14-5)   | 0 %                     | 31.12.2018                         |
| ex 2920 19 00 | 20    | Tolclofos-methyl (ISO) (CAS RN 57018-04-9)   | 0 %                     | 31.12.2018                         |
| ex 2920 90 10 | 10    | Diethyl sulphate (CAS RN 64-67-5)  | 0 %                     | 31.12.2018                         |
| ex 2920 90 10 | 20    | Diallyl 2,2'-oxydiethyl dicarbonate (CAS RN 142-22-3)  | 0 %                     | 31.12.2018                         |
| ex 2920 90 10 | 40    | Dimethyl carbonate (CAS RN 616-38-6)   | 0 %                     | 31.12.2018                         |
| ex 2920 90 10 | 50    | Di- <i>tert</i> -butyl dicarbonate (CAS RN 24424-99-5)   | 0 %                     | 31.12.2018                         |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
| ex 2920 90 10 | 60    | 2,4-Di- <i>tert</i> -butyl-5-nitrophenyl methyl carbonate (CAS RN 873055-55-1)  | 0 %                     | 31.12.2017                         |
| 2920 90 30    |       | Trimethyl phosphite (CAS RN 121-45-9)   | 0 %                     | 31.12.2018                         |
| 2920 90 40    |       | Triethyl phosphite (CAS RN 122-52-1)  | 0 %                     | 31.12.2016                         |
| ex 2920 90 85 | 10    | O,O'-Dioctadecyl pentaerythritol bis(phosphite) (CAS RN 3806-34-6)  | 0 %                     | 31.12.2018                         |
| ex 2920 90 85 | 20    | Tris(methylphenyl)phosphite (CAS RN 25586-42-9)   | 0 %                     | 31.12.2015                         |
| ex 2920 90 85 | 30    | 2,2'-[[3,3',5,5'-Tetrakis(1,1-dimethylethyl)[1,1'-biphenyl]-2,2'-diyl]bis(oxy)]bis[biphenyl-1,3,2-dioxaphosphepine], (CAS RN 138776-88-2) | 0 %                     | 31.12.2015                         |
| ex 2920 90 85 | 40    | Bis(2,4-dicumylphenyl)pentaerythritol diphosphite (CAS RN 154862-43-8)  | 0 %                     | 31.12.2015                         |
| ex 2920 90 85 | 50    | Fosetyl-aluminium (CAS RN 39148-24-8)   | 0 %                     | 31.12.2018                         |
| ex 2920 90 85 | 60    | Bis(neopentylglycolato)diboron (CAS RN 201733-56-4)   | 0 %                     | 31.12.2018                         |
| ex 2921 19 50 | 10    | Diethylamino-triethoxysilane (CAS RN 35077-00-0)  | 0 %                     | 31.12.2014                         |
| ex 2929 90 00 | 20    |   |                         |                                    |
| ex 2921 19 60 | 10    | 2-( <i>N,N</i> -Diethylamino)ethyl chloride hydrochloride (CAS RN 869-24-9)   | 0 %                     | 31.12.2017                         |
| ex 2921 19 99 | 20    | Ethyl(2-methylallyl)amine (CAS RN 18328-90-0)   | 0 %                     | 31.12.2018                         |
| ex 2921 19 99 | 30    | Allylamine (CAS RN 107-11-9)  | 0 %                     | 31.12.2018                         |
| ex 2921 19 99 | 60    | Tetrakis(ethylmethylamino) zirconium (IV), (CAS RN 175923-04-3)   | 0 %                     | 31.12.2018                         |
| ex 2921 19 99 | 70    | <i>N,N</i> -Dimethyloctylamine – boron trichloride (1:1) (CAS RN 34762-90-8)  | 0 %                     | 31.12.2017                         |
| ex 2921 29 00 | 20    | Tris[3-(dimethylamino)propyl]amine (CAS RN 33329-35-0)  | 0 %                     | 31.12.2018                         |
| ex 2921 29 00 | 30    | Bis[3-(dimethylamino)propyl]methylamine (CAS RN 3855-32-1)  | 0 %                     | 31.12.2018                         |
| ex 2921 29 00 | 40    | Decamethylenediamine (CAS RN 646-25-3)  | 0 %                     | 31.12.2015                         |
| ex 2921 29 00 | 50    | <i>N'</i> -[3-(Dimethylamino)propyl]- <i>N,N</i> -dimethylpropane-1,3-diamine, (CAS RN 6711-48-4)   | 0 %                     | 31.12.2016                         |
| ex 2921 30 99 | 30    | 1,3-Cyclohexanedimethanamine (CAS RN 2579-20-6)   | 0 %                     | 31.12.2015                         |
| ex 2921 30 99 | 40    | Cyclopropylamin (CAS RN 765-30-0)   | 0 %                     | 31.12.2017                         |
| ex 2921 42 00 | 15    | 4-Amino-3-nitrobenzenesulphonic acid (CAS RN 616-84-2)  | 0 %                     | 31.12.2018                         |
| ex 2921 42 00 | 20    | 3-Chloroaniline (CAS RN 108-42-9)   | 0 %                     | 31.12.2018                         |
| ex 2921 42 00 | 25    | Sodium hydrogen 2-aminobenzene-1,4-disulphonate (CAS RN 24605-36-5)   | 0 %                     | 31.12.2018                         |
| ex 2921 42 00 | 35    | 2-Nitroaniline (CAS RN 88-74-4)   | 0 %                     | 31.12.2018                         |
| ex 2921 42 00 | 45    | 2,4,5-Trichloroaniline (CAS RN 636-30-6)  | 0 %                     | 31.12.2018                         |
| ex 2921 42 00 | 50    | 3-Aminobenzenesulfonic acid (CAS RN 121-47-1)   | 0 %                     | 31.12.2018                         |
| ex 2921 42 00 | 70    | 2-Aminobenzene-1,4-disulfonic acid (CAS RN 98-44-2)   | 0 %                     | 31.12.2014                         |
| ex 2921 42 00 | 80    | 4-Chloro-2-nitroaniline (CAS RN 89-63-4)  | 0 %                     | 31.12.2018                         |
| ex 2921 42 00 | 82    | 2-Chloro-4-nitroaniline (CAS RN 121-87-9)   | 0 %                     | 31.12.2015                         |

| CN code       | TARIC | Description  | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|------------------------------------|
| ex 2921 42 00 | 85    | 3,5-Dichloroaniline (CAS RN 626-43-7)  | 0 %                     | 31.12.2018                         |
| ex 2921 42 00 | 86    | 2,5-Dichloroaniline of a purity by weight of 99,5 % or more (CAS RN 95-82-9)   | 0 %                     | 31.12.2017                         |
| ex 2921 42 00 | 87    | N-Methylaniline (CAS RN 100-61-8)  | 0 %                     | 31.12.2017                         |
| ex 2921 42 00 | 88    | 3,4-Dichloroaniline-6-sulphonic acid (CAS RN 6331-96-0)  | 0 %                     | 31.12.2017                         |
| ex 2921 43 00 | 20    | 4-Amino-6-chlorotoluene-3-sulphonic acid (CAS RN 88-51-7)  | 0 %                     | 31.12.2018                         |
| ex 2921 43 00 | 30    | 3-Nitro- <i>p</i> -toluidine (CAS RN 119-32-4)   | 0 %                     | 31.12.2018                         |
| ex 2921 43 00 | 40    | 4-Aminotoluene-3-sulphonic acid (CAS RN 88-44-8)   | 0 %                     | 31.12.2018                         |
| ex 2921 43 00 | 50    | 4-Aminobenzotrifluoride (CAS RN 455-14-1)  | 0 %                     | 31.12.2015                         |
| ex 2921 43 00 | 60    | 3-Aminobenzotrifluoride (CAS RN 98-16-8)   | 0 %                     | 31.12.2015                         |
| ex 2921 43 00 | 70    | N-Ethyl- <i>m</i> -toluidine (CAS RN 102-27-2)   | 0 %                     | 31.12.2016                         |
| ex 2921 43 00 | 80    | 6-Chloro- $\alpha,\alpha,\alpha$ -trifluoro- <i>m</i> -toluidine (CAS RN 121-50-6)   | 0 %                     | 31.12.2017                         |
| ex 2921 44 00 | 20    | Diphenylamine (CAS RN 122-39-4)  | 0 %                     | 31.12.2018                         |
| ex 2921 45 00 | 10    | Sodium hydrogen 3-aminonaphthalene-1,5-disulphonate (CAS RN 4681-22-5)   | 0 %                     | 31.12.2014                         |
| ex 2921 45 00 | 20    | 2-Aminonaphthalene-1,5-disulphonic acid (CAS RN 117-62-4) or one of its sodium salts (CAS RN 19532-03-7) or (CAS RN 62203-79-6)  | 0 %                     | 31.12.2018                         |
| ex 2921 45 00 | 40    | 1-Naphthylamine (CAS RN 134-32-7)  | 0 %                     | 31.12.2014                         |
| ex 2921 45 00 | 50    | 7-Aminonaphthalene-1,3,6-trisulphonic acid (CAS RN 118-03-6)   | 0 %                     | 31.12.2018                         |
| ex 2921 49 00 | 20    | Pendimethalin (ISO) (CAS RN 40487-42-1)  | 3,5 %                   | 31.12.2018                         |
| ex 2921 49 00 | 40    | N-1-Naphthylaniline (CAS RN 90-30-2)   | 0 %                     | 31.12.2018                         |
| ex 2921 49 00 | 60    | N-Benzyl-N-ethylaniline (CAS RN 92-59-1)   | 0 %                     | 31.12.2014                         |
| ex 2921 49 00 | 70    | 2-Chlorobenzylamine (CAS RN 89-97-4)   | 0 %                     | 31.12.2015                         |
| ex 2921 49 00 | 80    | 4-Heptafluoroisopropyl-2-methylaniline (CAS RN 238098-26-5)  | 0 %                     | 31.12.2015                         |
| ex 2921 49 00 | 85    | 4-Isopropylaniline (CAS RN 99-88-7)  | 0 %                     | 31.12.2017                         |
| ex 2921 51 19 | 20    | Toluene diamine (TDA), containing by weight 78 % or more but not more than 82 % of 4-methyl- <i>m</i> -phenylenediamine and 18 % or more but not more than 22 % of 2-methyl- <i>m</i> -phenylenediamine, and with a residual tar content of not more than 0,23 % by weight | 0 %                     | 31.12.2018                         |
| ex 2921 51 19 | 30    | 2-Methyl- <i>p</i> -phenylenediamine sulphate (CAS RN 615-50-9)  | 0 %                     | 31.12.2018                         |
| ex 2921 51 19 | 40    | <i>p</i> -Phenylenediamine (CAS RN 106-50-3)   | 0 %                     | 31.12.2016                         |
| ex 2921 51 19 | 50    | Mono- and dichloroderivatives of <i>p</i> -phenylenediamine and <i>p</i> -diaminotoluene   | 0 %                     | 31.12.2014                         |
| ex 2921 51 19 | 60    | 2,4-Diaminobenzenesulphonic acid (CAS RN 88-63-1)  | 0 %                     | 31.12.2018                         |
| ex 2921 59 90 | 10    | Mixture of isomers of 3,5-diethyltoluenediamine  | 0 %                     | 31.12.2018                         |
| ex 2921 59 90 | 30    | 3,3'-Dichlorobenzidine dihydrochloride (CAS RN 612-83-9)   | 0 %                     | 31.12.2017                         |
| ex 2921 59 90 | 40    | 4,4'-Diaminostilbene-2,2'-disulphonic acid (CAS RN 81-11-8)  | 0 %                     | 31.12.2018                         |

| CN code       | TARIC | Description  | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|------------------------------------|
| ex 2921 59 90 | 50    | N-Ethyl-N',N'-dimethyl-N-phenyl-ethylene-1,2-diamine (CAS RN 27692-91-7)                                   | 0 %                     | 31.12.2014                         |
| ex 2921 59 90 | 60    | (2R,5R)-1,6-Diphenylhexane-2,5-diamine dihydrochloride (CAS RN 1247119-31-8)                               | 0 %                     | 31.12.2017                         |
| ex 2922 19 85 | 20    | 2-(2-Methoxyphenoxy)ethylamine hydrochloride (CAS RN 64464-07-9)   | 0 %                     | 31.12.2017                         |
| ex 2922 19 85 | 25    | Titanium bis(triethanolamine)diisopropoxide (CAS RN 36673-16-2)  | 0 %                     | 31.12.2017                         |
| ex 2922 19 85 | 30    | N,N,N',N'-Tetramethyl-2,2'-oxybis(ethylamine) (CAS RN 3033-62-3)   | 0 %                     | 31.12.2018                         |
| ex 2922 19 85 | 40    | 2-(Dimethylamino)ethyl benzoate (CAS RN 2208-05-1)   | 0 %                     | 31.12.2014                         |
| ex 2922 19 85 | 45    | 2-[2-Hydroxyethyl(octadecyl)amino]ethanol (CAS RN 10213-78-2)  | 0 %                     | 31.12.2016                         |
| ex 2922 19 85 | 50    | 2-(2-Methoxyphenoxy)ethylamine (CAS RN 1836-62-0)  | 0 %                     | 31.12.2018                         |
| ex 2922 19 85 | 60    | N,N,N'-trimethyl-N'-(2-hydroxy-ethyl) 2,2'-oxybis(ethylamine), (CAS RN 83016-70-0)                         | 0 %                     | 31.12.2018                         |
| ex 2922 19 85 | 65    | trans-4-Aminocyclohexanol (CAS RN 27489-62-9)  | 0 %                     | 31.12.2018                         |
| ex 2922 19 85 | 70    | D-(-)-threo-2-amino-1-(p-nitrophenyl)propane-1,3-diol (CAS RN 716-61-0)                                    | 0 %                     | 31.12.2016                         |
| ex 2922 19 85 | 75    | 2-Ethoxyethylamine (CAS RN 110-76-9)   | 0 %                     | 31.12.2018                         |
| ex 2922 19 85 | 80    | N-[2-[2-(Dimethylamino)ethoxy]ethyl]-N-methyl-1,3-propanediamine, (CAS RN 189253-72-3)                     | 0 %                     | 31.12.2014                         |
| ex 2922 19 85 | 85    | (1S,4R)-cis-4-Amino-2-cyclopentene-1-methanol-D-tartrate (CAS RN 229177-52-0)                              | 0 %                     | 31.12.2018                         |
| ex 2922 21 00 | 10    | 2-Amino-5-hydroxynaphthalene-1,7-disulphonic acid (CAS RN 6535-70-2)                                       | 0 %                     | 31.12.2018                         |
| ex 2922 21 00 | 30    | 6-Amino-4-hydroxynaphthalene-2-sulphonic acid (CAS RN 90-51-7)   | 0 %                     | 31.12.2014                         |
| ex 2922 21 00 | 40    | 7-Amino-4-hydroxynaphthalene-2-sulphonic acid (CAS RN 87-02-5)   | 0 %                     | 31.12.2018                         |
| ex 2922 21 00 | 50    | Sodium hydrogen 4-amino-5-hydroxynaphthalene-2,7-disulphonate, (CAS RN 5460-09-3)                          | 0 %                     | 31.12.2014                         |
| ex 2922 21 00 | 60    | 4-Amino-5-hydroxynaphthalene-2,7-disulphonic acid with a purity by weight of 80 % or more (CAS RN 90-20-0) | 0 %                     | 31.12.2018                         |
| ex 2922 29 00 | 20    | 3-Aminophenol (CAS RN 591-27-5)  | 0 %                     | 31.12.2018                         |
| ex 2922 29 00 | 25    | 5-Amino-o-cresol (CAS RN 2835-95-2)  | 0 %                     | 31.12.2018                         |
| ex 2922 29 00 | 45    | Anisidines   | 0 %                     | 31.12.2018                         |
| ex 2922 29 00 | 55    | 3-Amino-4-hydroxybenzenesulphonic acid (CAS RN 98-37-3)  | 0 %                     | 31.12.2014                         |
| ex 2922 29 00 | 65    | 4-Trifluoromethoxyaniline (CAS RN 461-82-5)  | 0 %                     | 31.12.2014                         |
| ex 2922 29 00 | 70    | 4-Nitro-o-anisidine (CAS RN 97-52-9)   | 0 %                     | 31.12.2018                         |
| ex 2922 29 00 | 75    | 4-(2-Aminoethyl)phenol (CAS RN 51-67-2)  | 0 %                     | 31.12.2015                         |
| ex 2922 29 00 | 80    | 3-Diethylaminophenol (CAS RN 91-68-9)  | 0 %                     | 31.12.2018                         |
| ex 2922 29 00 | 85    | 4-Benzyloxyaniline hydrochloride (CAS RN 51388-20-6)   | 0 %                     | 31.12.2018                         |
| ex 2922 39 00 | 10    | 1-Amino-4-bromo-9,10-dioxoanthracene-2-sulphonic acid and its salts  | 0 %                     | 31.12.2018                         |

| CN code       | TARIC | Description  | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|------------------------------------|
| ex 2922 39 00 | 20    | 2-Amino-5-chlorobenzophenone (CAS RN 719-59-5)   | 0 %                     | 31.12.2015                         |
| ex 2922 39 00 | 70    | <i>p</i> -[(2-Chloroethyl)ethylamino]benzaldehyde (CAS RN 2643-07-4)   | 0 %                     | 31.12.2016                         |
| ex 2922 43 00 | 10    | Anthranilic acid (CAS RN 118-92-3)   | 0 %                     | 31.12.2018                         |
| ex 2922 49 85 | 10    | Ornithine aspartate (INN) (CAS RN 3230-94-2)   | 0 %                     | 31.12.2018                         |
| ex 2922 49 85 | 15    | DL-Aspartic acid used for the manufacture of food-integrators, (CAS RN 617-45-8) (1)   | 0 %                     | 31.12.2014                         |
| ex 2922 49 85 | 20    | 3-Amino-4-chlorobenzoic acid (CAS RN 2840-28-0)  | 0 %                     | 31.12.2017                         |
| ex 2922 49 85 | 40    | Norvaline  | 0 %                     | 31.12.2018                         |
| ex 2922 49 85 | 45    | Glycine (CAS RN 56-40-6)   | 0 %                     | 31.12.2015                         |
| ex 2922 49 85 | 50    | D-(-)-Dihydrophenylglycine (CAS RN 26774-88-9)   | 0 %                     | 31.12.2014                         |
| ex 2922 49 85 | 60    | Ethyl-4-dimethylaminobenzoate (CAS RN 10287-53-3)  | 0 %                     | 31.12.2017                         |
| ex 2922 49 85 | 70    | 2-Ethylhexyl-4-dimethylaminobenzoate (CAS RN 21245-02-3)   | 0 %                     | 31.12.2018                         |
| ex 2922 50 00 | 20    | 1-[2-Amino-1-(4-methoxyphenyl)-ethyl]-cyclohexanol hydrochloride, (CAS RN 130198-05-9)   | 0 %                     | 31.12.2014                         |
| ex 2922 50 00 | 70    | 2-(1-Hydroxycyclohexyl)-2-(4-methoxyphenyl)ethylammonium acetate   | 0 %                     | 31.12.2018                         |
| ex 2923 90 00 | 10    | Tetramethylammonium hydroxide, in the form of an aqueous solution containing 25 % ( $\pm$ 0,5 %) by weight of tetramethylammonium hydroxide  | 0 %                     | 31.12.2018                         |
| ex 2923 90 00 | 25    | Tetrakis(dimethyliditetradecylammonium) molybdate, (CAS RN 117342-25-3)  | 0 %                     | 31.12.2018                         |
| ex 2923 90 00 | 45    | Tetraethylammonium hydroxide in the form of an aqueous solution containing 55 % ( $\pm$ 1 %) by weight of tetraethylammonium hydroxide, (CAS RN 2052-49-5)   | 0 %                     | 31.12.2014                         |
| ex 2923 90 00 | 70    | Tetrapropylammonium hydroxide, in the form of an aqueous solution containing:<br>— 40 % ( $\pm$ 2 %) by weight of tetrapropylammonium hydroxide,<br>— 0,3 % by weight or less of carbonate,<br>— 0,1 % by weight or less of tripropylamine,<br>— 500 mg/kg or less of bromide and<br>— 25 mg/kg or less of potassium and sodium taken together | 0 %                     | 31.12.2018                         |
| ex 2923 90 00 | 75    | Tetraethylammonium hydroxide, in the form of an aqueous solution containing:<br>— 35 % ( $\pm$ 0,5 %) by weight of tetraethylammonium hydroxide,<br>— not more than 1 000 mg/kg of chloride,<br>— not more than 2 mg/kg of iron and<br>— not more than 10 mg/kg of potassium   | 0 %                     | 31.12.2015                         |
| ex 2923 90 00 | 80    | Diallyldimethylammonium chloride, in the form of an aqueous solution containing by weight 63 % or more but not more than 67 % of diallyldimethylammonium chloride, (CAS RN 7398-69-8)  | 0 %                     | 31.12.2018                         |
| ex 2924 19 00 | 10    | 2-Acrylamido-2-methylpropanesulphonic acid (CAS RN 15214-89-8) or its sodium salt (CAS RN 5165-97-9), or its ammonium salt (CAS RN 58374-69-9)   | 0 %                     | 31.12.2018                         |

| CN code       | TARIC | Description  | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|------------------------------------|
| ex 2924 19 00 | 30    | Methyl 2-acetamido-3-chloropropionate (CAS RN 87333-22-0)                                  | 0 %                     | 31.12.2018                         |
| ex 2924 19 00 | 40    | N-(1,1-Dimethyl-3-oxobutyl)acrylamide (CAS RN 2873-97-4)                                   | 0 %                     | 31.12.2018                         |
| ex 2924 19 00 | 50    | Acrylamide (CAS RN 79-06-1)  | 0 %                     | 31.12.2018                         |
| ex 2924 19 00 | 60    | N,N-Dimethylacrylamide (CAS RN 2680-03-7)  | 0 %                     | 31.12.2016                         |
| ex 2924 19 00 | 70    | Methylcarbamate (CAS RN 598-55-0)  | 0 %                     | 31.12.2018                         |
| ex 2924 19 00 | 80    | Tetrabutylurea (CAS RN 4559-86-8)  | 0 %                     | 31.12.2017                         |
| ex 2924 21 00 | 10    | 4,4'-Dihydroxy-7,7'-ureylenedi(naphthalene-2-sulfonic acid) and its sodium salts           | 0 %                     | 31.12.2018                         |
| ex 2924 21 00 | 20    | (3-Aminophenyl)urea hydrochloride (CAS RN 59690-88-9)                                      | 0 %                     | 31.12.2018                         |
| ex 2924 29 98 | 10    | Alachlor (ISO), (CAS RN 15972-60-8)  | 0 %                     | 31.12.2018                         |
| ex 2924 29 98 | 12    | 4-(Acetylamino)-2-aminobenzenesulphonic acid (CAS RN 88-64-2)                              | 0 %                     | 31.12.2018                         |
| ex 2924 29 98 | 15    | Acetochlor (ISO), (CAS RN 34256-82-1)  | 0 %                     | 31.12.2018                         |
| ex 2924 29 98 | 20    | 2-Chloro-N-(2-ethyl-6-methylphenyl)-N-(propan-2-yloxymethyl)acetamide, (CAS RN 86763-47-5) | 0 %                     | 31.12.2014                         |
| ex 2924 29 98 | 27    | 2-Bromo-4-fluoroacetanilide (CAS RN 1009-22-9)   | 0 %                     | 31.12.2016                         |
| ex 2924 29 98 | 40    | N,N'-1,4-Phenylenebis[3-oxobutyramide], (CAS RN 24731-73-5)                                | 0 %                     | 31.12.2015                         |
| ex 2924 29 98 | 45    | Propoxur (ISO) (CAS RN 114-26-1)   | 0 %                     | 31.12.2015                         |
| ex 2924 29 98 | 50    | N,N'-(2,5-Dichloro-1,4-phenylene)bis[3-oxobutyramide], (CAS RN 42487-09-2)                 | 0 %                     | 31.12.2015                         |
| ex 2924 29 98 | 51    | Methyl 2-amino-4-[[2,5-dichlorophenyl]amino]carbonyl]benzoate (CAS RN 59673-82-4)          | 0 %                     | 31.12.2017                         |
| ex 2924 29 98 | 53    | 4-Amino-N-[4-(aminocarbonyl)phenyl]benzamide (CAS RN 74441-06-8)                           | 0 %                     | 31.12.2017                         |
| ex 2924 29 98 | 55    | N,N'-(2,5-Dimethyl-1,4-phenylene)bis[3-oxobutyramide], (CAS RN 24304-50-5)                 | 0 %                     | 31.12.2015                         |
| ex 2924 29 98 | 60    | N,N'-(2-Chloro-5-methyl-1,4-phenylene)bis[3-oxobutyramide], (CAS RN 41131-65-1)            | 0 %                     | 31.12.2015                         |
| ex 2924 29 98 | 63    | N-Ethyl-2-(isopropyl)-5-methylcyclohexanecarboxamide (CAS RN 39711-79-0)                   | 0 %                     | 31.12.2016                         |
| ex 2924 29 98 | 65    | 2-(4-Hydroxyphenyl)acetamide (CAS RN 17194-82-0)   | 0 %                     | 31.12.2018                         |
| ex 2924 29 98 | 75    | 3-Amino-p-anisanilide (CAS RN 120-35-4)  | 0 %                     | 31.12.2018                         |
| ex 2924 29 98 | 80    | 5'-Chloro-3-hydroxy-2',4'-dimethoxy-2-naphthanilide (CAS RN 92-72-8)                       | 0 %                     | 31.12.2018                         |
| ex 2924 29 98 | 85    | p-Aminobenzamide (CAS RN 2835-68-9)  | 0 %                     | 31.12.2018                         |
| ex 2924 29 98 | 86    | Anthranilamide of a purity by weight of 99,5 % or more (CAS RN 88-68-6)                    | 0 %                     | 31.12.2017                         |
| ex 2924 29 98 | 87    | Paracetamol (INN) (CAS RN 103-90-2)  | 0 %                     | 31.12.2018                         |
| ex 2924 29 98 | 88    | 5'-Chloro-3-hydroxy-2'-methyl-2-naphthanilide (CAS RN 135-63-7)                            | 0 %                     | 31.12.2018                         |
| ex 2924 29 98 | 89    | Flutolanil (ISO) (CAS RN 66332-96-5)   | 0 %                     | 31.12.2018                         |
| ex 2924 29 98 | 91    | 3-Hydroxy-2'-methoxy-2-naphthanilide (CAS RN 135-62-6)                                     | 0 %                     | 31.12.2018                         |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
| ex 2924 29 98 | 92    | 3-Hydroxy-2-naphthanilide (CAS RN 92-77-3)  | 0 %                     | 31.12.2014                         |
| ex 2924 29 98 | 93    | 3-Hydroxy-2'-methyl-2-naphthanilide (CAS RN 135-61-5)   | 0 %                     | 31.12.2018                         |
| ex 2924 29 98 | 94    | 2'-Ethoxy-3-hydroxy-2-naphthanilide (CAS RN 92-74-0)  | 0 %                     | 31.12.2018                         |
| ex 2924 29 98 | 97    | 1,1-Cyclohexanediactic acid monoamide (CAS RN 99189-60-3)   | 0 %                     | 31.12.2018                         |
| ex 2925 11 00 | 20    | Saccharin and its sodium salt   | 0 %                     | 31.12.2018                         |
| ex 2925 19 95 | 10    | N-Phenylmaleimide (CAS RN 941-69-5)   | 0 %                     | 31.12.2018                         |
| ex 2925 19 95 | 20    | 4,5,6,7-Tetrahydroisindole-1,3-dione (CAS RN 4720-86-9)   | 0 %                     | 31.12.2017                         |
| ex 2925 19 95 | 30    | N,N'-( <i>m</i> -Phenylene)dimalimide (CAS RN 3006-93-7)  | 0 %                     | 31.12.2017                         |
| ex 2925 29 00 | 10    | Dicyclohexylcarbodiimide (CAS RN 538-75-0)  | 0 %                     | 31.12.2018                         |
| ex 2925 29 00 | 20    | N-[3-(Dimethylamino)propyl]-N'-ethylcarbodiimide hydrochloride (CAS RN 25952-53-8)                      | 0 %                     | 01.01.2018                         |
| ex 2926 90 95 | 13    | alpha-Bromo- <i>o</i> -toluonitrile (CAS RN 22115-41-9)   | 0 %                     | 31.12.2018                         |
| ex 2926 90 95 | 20    | 2-( <i>m</i> -Benzoylphenyl)propionitrile (CAS RN 42872-30-0)   | 0 %                     | 31.12.2014                         |
| ex 2926 90 95 | 25    | 2,2-Dibromo-3-nitrilopropionamide (CAS RN 10222-01-2)   | 0 %                     | 31.12.2016                         |
| ex 2926 90 95 | 30    | 2-Amino-3-(3,4-dimethoxyphenyl)-2-methylpropanenitrile hydrochloride, (CAS RN 2544-13-0)                | 0 %                     | 31.12.2015                         |
| ex 2926 90 95 | 50    | Alkyl or alkoxyalkyl esters of cyanoacetic acid   | 0 %                     | 31.12.2018                         |
| ex 2926 90 95 | 55    | Methyl-2-cyano-2-phenylbutyrate (CAS RN 24131-07-5)   | 0 %                     | 31.12.2016                         |
| ex 2926 90 95 | 60    | Cyanoacetic acid in crystalline form (CAS RN 372-09-8)  | 0 %                     | 31.12.2014                         |
| ex 2926 90 95 | 61    | <i>m</i> -(1-Cyanoethyl)benzoic acid (CAS RN 5537-71-3)   | 0 %                     | 31.12.2016                         |
| ex 2926 90 95 | 63    | 1-(Cyanoacetyl)-3-ethylurea (CAS RN 41078-06-2)   | 0 %                     | 31.12.2014                         |
| ex 2926 90 95 | 64    | Esfenvalerate of a purity by weight of 83 % or more in a mixture of its own isomers (CAS RN 66230-04-4) | 0 %                     | 31.12.2014                         |
| ex 2926 90 95 | 65    | Malononitrile (CAS RN 109-77-3)   | 0 %                     | 31.12.2018                         |
| ex 2926 90 95 | 70    | Methacrylonitrile (CAS RN 126-98-7)   | 0 %                     | 31.12.2014                         |
| ex 2926 90 95 | 74    | Chlorothalonil (ISO) (CAS RN 1897-45-6)   | 0 %                     | 31.12.2014                         |
| ex 2926 90 95 | 75    | Ethyl 2-cyano-2-ethyl-3-methylhexanoate (CAS RN 100453-11-0)  | 0 %                     | 31.12.2014                         |
| ex 2926 90 95 | 80    | Ethyl 2-cyano-2-phenylbutyrate (CAS RN 718-71-8)  | 0 %                     | 31.12.2018                         |
| ex 2926 90 95 | 86    | Ethylenediaminetetraacetoneitrile (CAS RN 5766-67-6)  | 0 %                     | 31.12.2018                         |
| ex 2926 90 95 | 89    | Butyronitrile (CAS RN 109-74-0)   | 0 %                     | 31.12.2018                         |
| ex 2927 00 00 | 10    | 2,2'-Dimethyl-2,2'-azodipropionimidine dihydrochloride  | 0 %                     | 31.12.2018                         |

| CN code       | TARIC | Description  | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|------------------------------------|
| ex 2927 00 00 | 20    | 4-Anilino-2-methoxybenzenediazonium hydrogen sulphate (CAS RN 36305-05-2)  | 0 %                     | 31.12.2018                         |
| ex 2927 00 00 | 30    | 4'-Aminoazobenzene-4-sulphonic acid (CAS RN 104-23-4)  | 0 %                     | 31.12.2018                         |
| ex 2927 00 00 | 70    | Tetrasodium 3,3'-[azoxybis[(2-methoxy-4,1-phenylene)azo]]bis[4,5-dihydroxynaphthalene-2,7-disulphonate], (CAS RN 83968-64-3) | 0 %                     | 31.12.2014                         |
| ex 2927 00 00 | 80    | 4-[(2,5-Dichlorophenyl)azo]-3-hydroxy-2-naphthoic acid (CAS RN 51867-77-7)   | 0 %                     | 31.12.2017                         |
| ex 2928 00 90 | 10    | 3,3'-Bis(3,5-di- <i>tert</i> -butyl-4-hydroxyphenyl)- <i>N,N'</i> -bipropionamide (CAS RN 32687-78-8)                        | 0 %                     | 31.12.2018                         |
| ex 2928 00 90 | 25    | Acetaldehyde oxime in an aqueous solution (CAS RN 107-29-9)  | 0 %                     | 31.12.2015                         |
| ex 2928 00 90 | 30    | <i>N</i> -Isopropylhydroxylamine (CAS RN 5080-22-8)  | 0 %                     | 31.12.2016                         |
| ex 2928 00 90 | 35    | 2-Chloro- <i>N</i> -methoxy- <i>N</i> -methylacetamide (CAS RN 67442-07-3)   | 0 %                     | 31.12.2018                         |
| ex 2928 00 90 | 40    | <i>O</i> -Ethylhydroxylamine, in the form of an aqueous solution (CAS RN 624-86-2)   | 0 %                     | 31.12.2018                         |
| ex 2928 00 90 | 45    | Tebufenozide (ISO) (CAS RN 112410-23-8)  | 0 %                     | 31.12.2018                         |
| ex 2928 00 90 | 55    | Aminoguanidinium hydrogen carbonate (CAS RN 2582-30-1)   | 0 %                     | 31.12.2018                         |
| ex 2928 00 90 | 60    | Adipohydrazide (CAS RN 1071-93-8)  | 0 %                     | 31.12.2018                         |
| ex 2928 00 90 | 70    | Butanone oxime (CAS RN 96-29-7)  | 0 %                     | 31.12.2018                         |
| ex 2928 00 90 | 75    | Metaflumizone (ISO) (CAS RN 139968-49-3)   | 0 %                     | 31.12.2016                         |
| ex 2928 00 90 | 80    | Cyflufenamid (ISO) (CAS RN 180409-60-3)  | 0 %                     | 31.12.2018                         |
| ex 2928 00 90 | 85    | Daminozide (ISO) with a purity by weight of 99 % or more (CAS RN 1596-84-5)  | 0 %                     | 31.12.2016                         |
| ex 2929 10 00 | 10    | Methylenedicyclohexyl diisocyanates (CAS RN 28605-81-4)  | 0 %                     | 31.12.2018                         |
| ex 2929 10 00 | 15    | 3,3'-Dimethylbiphenyl-4,4'-diyl diisocyanate (CAS RN 91-97-4)  | 0 %                     | 31.12.2014                         |
| ex 2929 10 00 | 20    | Butyl isocyanate (CAS RN 111-36-4)   | 0 %                     | 31.12.2017                         |
| ex 2929 10 00 | 40    | <i>m</i> -Isopropenyl- $\alpha,\alpha$ -dimethylbenzyl isocyanate (CAS RN 2094-99-7)   | 0 %                     | 31.12.2018                         |
| ex 2929 10 00 | 50    | <i>m</i> -Phenylenediisopropylidene diisocyanate (CAS RN 2778-42-9)  | 0 %                     | 31.12.2018                         |
| ex 2929 10 00 | 55    | 2,5 (and 2,6)-Bis(isocyanatomethyl)bicyclo[2.2.1]heptane (CAS RN 74091-64-8)   | 0 %                     | 31.12.2015                         |
| ex 2929 10 00 | 60    | Trimethylhexamethylene diisocyanate, mixed isomers   | 0 %                     | 31.12.2018                         |
| ex 2929 10 00 | 80    | 1,3-Bis(isocyanatomethyl)benzene (CAS RN 3634-83-1)  | 0 %                     | 31.12.2016                         |
| ex 2930 20 00 | 10    | Prosulfocarb (ISO) (CAS RN 52888-80-9)   | 0 %                     | 31.12.2017                         |
| ex 2930 20 00 | 20    | 2-Isopropylethylthiocarbamate (CAS RN 141-98-0)  | 0 %                     | 31.12.2016                         |
| ex 2930 90 99 | 10    | 2,3-Bis((2-mercaptoethyl)thio)-1-propanethiol (CAS RN 131538-00-6)   | 0 %                     | 31.12.2015                         |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
| ex 2930 90 99 | 13    | Mercaptamine hydrochloride (CAS RN 156-57-0)  | 0 %                     | 31.12.2016                         |
| ex 2930 90 99 | 14    | 4-(Methylthio)benzaldehyde (CAS RN 3446-89-7)   | 0 %                     | 31.12.2018                         |
| ex 2930 90 99 | 15    | Ethoprophos (ISO) (CAS RN 13194-48-4)   | 0 %                     | 31.12.2018                         |
| ex 2930 90 99 | 17    | 2-(3-Aminophenylsulphonyl)ethyl hydrogen sulphate (CAS RN 2494-88-4)                                    | 0 %                     | 31.12.2018                         |
| ex 2930 90 99 | 18    | 1-Methyl-5-[3-methyl-4-[4-[(trifluoromethyl)thio]phenoxy]phenyl]biuret (CAS RN 106310-17-2)             | 0 %                     | 31.12.2016                         |
| ex 2930 90 99 | 20    | 2-Methoxy-N-[2-nitro-5-(phenylthio)phenyl]acetamide (CAS RN 63470-85-9)                                 | 0 %                     | 31.12.2015                         |
| ex 2930 90 99 | 23    | Dimethyl [(methylsulphonyl)methylidene]biscarbamate (CAS RN 34840-23-8)                                 | 0 %                     | 31.12.2018                         |
| ex 2930 90 99 | 25    | Thiophanate-methyl (ISO), (CAS RN 23564-05-8)   | 0 %                     | 31.12.2018                         |
| ex 2930 90 99 | 30    | 4-(4-Isopropoxyphenylsulphonyl)phenol (CAS RN 95235-30-6)   | 0 %                     | 31.12.2018                         |
| ex 2930 90 99 | 35    | Glutathione (CAS RN 70-18-8)  | 0 %                     | 31.12.2016                         |
| ex 2930 90 99 | 40    | 3,3'-Thiodi(propionic acid) (CAS RN 111-17-1)   | 0 %                     | 31.12.2018                         |
| ex 2930 90 99 | 45    | 2-[(p-Aminophenyl)sulphonyl]ethyl hydrogen sulphate (CAS RN 2494-89-5)                                  | 0 %                     | 31.12.2018                         |
| ex 2930 90 99 | 50    | [S-(R*,R*)]-2-Amino-1-[4-(methylthio)-phenyl]-1,3-propanediol, (CAS RN 23150-35-8)                      | 0 %                     | 31.12.2015                         |
| ex 2930 90 99 | 55    | Thiourea (CAS RN 62-56-6)   | 0 %                     | 31.12.2015                         |
| ex 2930 90 99 | 60    | Methyl phenyl sulphide (CAS RN 100-68-5)  | 0 %                     | 31.12.2018                         |
| ex 2930 90 99 | 62    | Zinc bis(benzenesulfinate) (CAS RN 24308-84-7)  | 0 %                     | 31.12.2014                         |
| ex 2930 90 99 | 64    | 3-Chloro-2-methylphenyl methyl sulphide (CAS RN 82961-52-2)   | 0 %                     | 31.12.2014                         |
| ex 2930 90 99 | 65    | Pentaerythritol tetrakis(3-mercaptopropionate) (CAS RN 7575-23-7)                                       | 0 %                     | 31.12.2015                         |
| ex 2930 90 99 | 66    | Diphenyl sulphide (CAS RN 139-66-2)   | 0 %                     | 31.12.2017                         |
| ex 2930 90 99 | 67    | 3-Bromomethyl-2-chloro-4-(methylsulphonyl)-benzoic acid (CAS RN 120100-05-2)                            | 0 %                     | 31.12.2018                         |
| ex 2930 90 99 | 68    | Clethodim (ISO) (CAS RN 99129-21-2)   | 0 %                     | 31.12.2017                         |
| ex 2930 90 99 | 77    | 4-[4-(2-Propenyloxy)phenylsulphonyl]phenol (CAS RN 97042-18-7)  | 0 %                     | 31.12.2018                         |
| ex 2930 90 99 | 78    | 4-Mercaptomethyl-3,6-dithia-1,8-octanedithiol (CAS RN 131538-00-6)                                      | 0 %                     | 31.12.2016                         |
| ex 2930 90 99 | 80    | Captan (ISO) (CAS RN 133-06-2)  | 0 %                     | 31.12.2018                         |
| ex 2930 90 99 | 81    | Disodium hexamethylene-1,6-bisthiosulfate dihydrate (CAS RN 5719-73-3)                                  | 3 %                     | 31.12.2014                         |
| ex 2930 90 99 | 83    | Methyl-p-tolyl sulphone (CAS RN 3185-99-7)  | 0 %                     | 31.12.2017                         |
| ex 2930 90 99 | 84    | 2-Chloro-4-(methylsulphonyl)benzoic acid (CAS RN 53250-83-2)  | 0 %                     | 31.12.2014                         |
| ex 2930 90 99 | 87    | 3-Sulphinobenzoic acid (CAS RN 15451-00-0)  | 0 %                     | 31.12.2018                         |
| ex 2930 90 99 | 89    | Potassium- or sodium-salt of O-ethyl-, O-isopropyl-, O-butyl-, O-isobutyl- or O-pentyl-dithiocarbonates | 0 %                     | 31.12.2016                         |
| ex 2931 90 90 | 05    | Butylethylmagnesium (CAS RN 62202-86-2), in the form of a solution in heptane                           | 0 %                     | 31.12.2018                         |

| CN code       | TARIC | Description  | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|------------------------------------|
| ex 2931 90 90 | 10    | Diethylmethoxyborane (CAS RN 7397-46-8), whether or not in the form of a solution in tetrahydrofuran according to note 1e to Chapter 29 of the CN    | 0 %                     | 31.12.2015                         |
| ex 2931 90 90 | 14    | Sodium diisobutylidithiophosphate (CAS RN 13360-78-6) in an aqueous solution   | 0 %                     | 31.12.2017                         |
| ex 2931 90 90 | 15    | Triethylborane (CAS RN 97-94-9)  | 0 %                     | 31.12.2015                         |
| ex 2931 90 90 | 18    | Trioctylphosphine oxide (CAS RN 78-50-2)   | 0 %                     | 31.12.2016                         |
| ex 2931 90 90 | 20    | Methylcyclopentadienyl manganese tricarbonyl containing not more than 4,9 % by weight of cyclopentadienyl manganese tricarbonyl, (CAS RN 12108-13-3) | 0 %                     | 31.12.2014                         |
| ex 2931 90 90 | 24    | Methyl tris (2-pentanoneoxime) silane (CAS RN 37859-55-5)  | 0 %                     | 31.12.2014                         |
| ex 2931 90 90 | 30    | Diethylborane isopropoxide (CAS RN 74953-03-0)   | 0 %                     | 31.12.2015                         |
| ex 2931 90 90 | 35    | (Z)-Prop-1-en-1-ylphosphonic acid (CAS RN 25383-06-6)  | 0 %                     | 31.12.2017                         |
| ex 2931 90 90 | 40    | N-(Phosphonomethyl)iminodiacetic acid (CAS RN 5994-61-6)   | 0 %                     | 31.12.2014                         |
| ex 2931 90 90 | 50    | Bis(2,4,4-trimethylpentyl)phosphinic acid (CAS RN 83411-71-6)  | 0 %                     | 31.12.2018                         |
| ex 2931 90 90 | 55    | Dimethyl[dimethylsilyldiindenyl]hafnium (CAS RN 220492-55-7)   | 0 %                     | 31.12.2014                         |
| ex 2931 90 90 | 70    | N,N-Dimethylanilinium tetrakis(pentafluorophenyl)borate (CAS RN 118612-00-3)   | 0 %                     | 31.12.2014                         |
| ex 2931 90 90 | 72    | Phenylphosphonic dichloride (CAS RN 824-72-6)  | 0 %                     | 31.12.2016                         |
| ex 2931 90 90 | 75    | Tetrakis(hydroxymethyl)phosphonium chloride (CAS RN 124-64-1)  | 0 %                     | 31.12.2016                         |
| ex 2931 90 90 | 86    | Mixture of the isomers 9-icosyl-9-phosphabicyclo[3.3.1]nonane and 9-icosyl-9-phosphabicyclo[4.2.1]nonane   | 0 %                     | 31.12.2018                         |
| ex 2931 90 90 | 87    | Tris(4-methylpentan-2-oximino)methylsilane (CAS RN 37859-57-7)   | 0 %                     | 31.12.2018                         |
| ex 2931 90 90 | 89    | Tetrabutylphosphonium acetate in the form of an aqueous solution (CAS RN 30345-49-4)   | 0 %                     | 31.12.2014                         |
| ex 2931 90 90 | 91    | Trimethylsilane (CAS RN 993-07-7)  | 0 %                     | 31.12.2016                         |
| ex 2931 90 90 | 92    | Trimethylborane (CAS RN 593-90-8)  | 0 %                     | 31.12.2014                         |
| ex 2931 90 90 | 96    | 3-(Hydroxyphenylphosphinoyl)propionic acid (CAS RN 14657-64-8)   | 0 %                     | 31.12.2018                         |
| ex 2932 13 00 | 10    | Tetrahydrofurfuryl alcohol (CAS RN 97-99-4)  | 0 %                     | 31.12.2018                         |
| ex 2932 19 00 | 40    | Furan (CAS RN 110-00-9) of a purity by weight of 99 % or more  | 0 %                     | 31.12.2014                         |
| ex 2932 19 00 | 41    | 2,2 di(tetrahydrofuryl)propane (CAS RN 89686-69-1)   | 0 %                     | 31.12.2014                         |
| ex 2932 19 00 | 45    | 1,6-Dichloro-1,6-dideoxy-β-D-fructofuranosyl-4-chloro-4 deoxy-α-D-galactopyranoside, (CAS RN 56038-13-2)   | 0 %                     | 31.12.2014                         |
| ex 2932 19 00 | 50    | 2-Methylfuran (CAS RN 534-22-5)  | 0 %                     | 31.12.2015                         |
| ex 2932 19 00 | 70    | Furfurylamine (CAS RN 617-89-0)  | 0 %                     | 31.12.2014                         |
| ex 2932 19 00 | 75    | Tetrahydro-2-methylfuran (CAS RN 96-47-9)  | 0 %                     | 31.12.2018                         |
| ex 2932 19 00 | 80    | 5-Nitrofurfurylidene di(acetate) (CAS RN 92-55-7)  | 0 %                     | 31.12.2016                         |
| ex 2932 20 90 | 10    | 2'-Anilino-6'-[ethyl(isopentyl)amino]-3'-methylspiro[isobenzofuran-1(3H),9'-xanthen]-3-one (CAS RN 70516-41-5)                                       | 0 %                     | 31.12.2018                         |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
| ex 2932 20 90 | 15    | Coumarin (CAS RN 91-64-5)   | 0 %                     | 31.12.2016                         |
| ex 2932 20 90 | 20    | Ethyl 6'-(diethylamino)-3-oxo-3H-spiro[2-benzofuran-1,9'-xanthene]-2'-carboxylate (CAS RN 154306-60-2)            | 0 %                     | 31.12.2017                         |
| ex 2932 20 90 | 35    | 6'-Diethylamino-3'-methyl-2'-(2,4-xylidino)spiro[isobenzofuran-1(3H),9'-xanthen]-3-one (CAS RN 36431-22-8)        | 0 %                     | 31.12.2018                         |
| ex 2932 20 90 | 40    | (S)-(-)- $\alpha$ -Amino- $\gamma$ -butyrolactonehydrobromide (CAS RN 15295-77-9)                                 | 0 %                     | 31.12.2017                         |
| ex 2932 20 90 | 55    | 6-Dimethylamino-3,3-bis(4-dimethylaminophenyl)phthalide (CAS RN 1552-42-7)  | 0 %                     | 31.12.2018                         |
| ex 2932 20 90 | 60    | 6'-(Diethylamino)-3'-methyl-2'-(phenylamino)-spiro[isobenzofuran-1(3H),9'-[9H]xanthen]-3-one (CAS RN 29512-49-0)  | 0 %                     | 31.12.2016                         |
| ex 2932 20 90 | 70    | 3',6'-Bis(ethylamino)-2',7'-dimethylspiro[isobenzofuran-1(3H),9'-[9H]xanthen]-3-one, (CAS RN 41382-37-0)          | 0 %                     | 31.12.2018                         |
| ex 2932 20 90 | 71    | 6'-(Dibutylamino)-3'-methyl-2'-(phenylamino)-spiro[isobenzofuran-1(3H),9'-[9H]xanthen]-3-one (CAS RN 89331-94-2)  | 0 %                     | 31.12.2016                         |
| ex 2932 20 90 | 72    | 2'-[Bis(phenylmethyl)amino]-6'-(diethylamino)-spiro[isobenzofuran-1(3H),9'-[9H]xanthen]-3-one (CAS RN 34372-72-0) | 0 %                     | 31.12.2016                         |
| ex 2932 20 90 | 80    | Gibberellic acid with a minimum purity by weight of 88 % (CAS RN 77-06-5)   | 0 %                     | 31.12.2018                         |
| ex 2932 20 90 | 84    | Decahydro-3a,6,6,9a-tetramethylnaphth [2,1-b] furan-2 (1H)-one (CAS RN 564-20-5)                                  | 0 %                     | 31.12.2018                         |
| ex 2932 99 00 | 10    | Bendiocarb (ISO) (CAS RN 22781-23-3)  | 0 %                     | 31.12.2018                         |
| ex 2932 99 00 | 15    | 1,3,4,6,7,8-Hexahydro-4,6,6,7,8,8-hexamethylindeno[5,6-c]pyran (CAS RN 1222-05-5)                                 | 0 %                     | 31.12.2016                         |
| ex 2932 99 00 | 20    | Ethyl-2-methyl-1,3-dioxolane-2-acetate (CAS RN 6413-10-1)   | 0 %                     | 31.12.2016                         |
| ex 2932 99 00 | 25    | 1-(2,2-Difluorobenzo[d][1,3]dioxol-5-yl)cyclopropanecarboxylic acid (CAS RN 862574-88-7)                          | 0 %                     | 31.12.2017                         |
| ex 2932 99 00 | 35    | 1,2,3-Trideoxy-4,6:5,7-bis-O-[(4-propylphenyl)methylene]-nonitol, (CAS RN 882073-43-0)                            | 0 %                     | 31.12.2018                         |
| ex 2932 99 00 | 40    | 1,3:2,4-Bis-O-(3,4-dimethylbenzylidene)-D-glucitol (CAS RN 135861-56-2)   | 0 %                     | 31.12.2018                         |
| ex 2932 99 00 | 45    | 2-Butylbenzofuran (CAS RN 4265-27-4)  | 0 %                     | 31.12.2018                         |
| ex 2932 99 00 | 50    | 7-Methyl-3,4-dihydro-2H-1,5-benzodioxepin-3-one (CAS RN 28940-11-6)   | 0 %                     | 31.12.2015                         |
| ex 2932 99 00 | 55    | 6-Fluoro-3,4-dihydro-2H-1-benzopyran-2-carboxylic acid (CAS RN 99199-60-7)  | 0 %                     | 31.12.2018                         |
| ex 2932 99 00 | 70    | 1,3:2,4-bis-O-Benzylidene-D-glucitol (CAS RN 32647-67-9)  | 0 %                     | 31.12.2016                         |
| ex 2932 99 00 | 75    | 3-(3,4-Methylenedioxyphenyl)-2-methylpropanal (CAS RN 1205-17-0)  | 0 %                     | 31.12.2016                         |
| ex 2932 99 00 | 80    | 1,3:2,4-bis-O-(4-Methylbenzylidene)-D-glucitol (CAS RN 32647-67-9)  | 0 %                     | 31.12.2016                         |
| ex 2933 19 90 | 30    | 3-Methyl-1-p-tolyl-5-pyrazolone (CAS RN 86-92-0)  | 0 %                     | 31.12.2018                         |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
| ex 2933 19 90 | 40    | Edaravone (INN) (CAS RN 89-25-8)  | 0 %                     | 31.12.2018                         |
| ex 2933 19 90 | 50    | Fenpyroximate (ISO) (CAS RN 134098-61-6)  | 0 %                     | 31.12.2014                         |
| ex 2933 19 90 | 60    | Pyraflufen-ethyl (ISO) (CAS RN 129630-19-9)   | 0 %                     | 31.12.2014                         |
| ex 2933 19 90 | 70    | 4,5-Diamino-1-(2-hydroxyethyl)-pyrazolsulphate (CAS RN 155601-30-2)   | 0 %                     | 31.12.2018                         |
| ex 2933 19 90 | 80    | 3-(4,5-Dihydro-3-methyl-5-oxo-1H-pyrazol-1-yl)benzenesulphonic acid (CAS RN 119-17-5)   | 0 %                     | 31.12.2017                         |
| ex 2933 19 90 | 85    | Allyl 5-amino-4-(2-methylphenyl)-3-oxo-2,3-dihydro-1H-1-pyrazolcarbothioate (CAS RN 473799-16-5)  | 0 %                     | 31.12.2017                         |
| ex 2933 21 00 | 50    | 1-Bromo-3-chloro-5,5-dimethylhydantoin (CAS RN 16079-88-2)  | 0 %                     | 31.12.2016                         |
| ex 2933 21 00 | 60    | DL-p-Hydroxyphenylhydantoin (CAS RN 2420-17-9)  | 0 %                     | 31.12.2016                         |
| ex 2933 21 00 | 70    | $\alpha$ -(4-Methoxybenzoyl)- $\alpha$ -(1-benzyl-5-ethoxy-3-hydantoinyl)-2-chloro-5-dodecyloxycarbonylacetanilide, (CAS RN 70950-45-7) | 0 %                     | 31.12.2016                         |
| ex 2933 21 00 | 80    | 5,5-Dimethylhydantoin (CAS RN 77-71-4)  | 0 %                     | 31.12.2015                         |
| ex 2933 29 90 | 15    | Ethyl 4-(1-hydroxy-1-methylethyl)-2-propylimidazole-5-carboxylate (CAS RN 144689-93-0)  | 0 %                     | 31.12.2018                         |
| ex 2933 29 90 | 25    | Prochloraz (ISO) (CAS RN 67747-09-5)  | 0 %                     | 31.12.2018                         |
| ex 2933 29 90 | 35    | 1-Trityl-4-formylimidazole (CAS RN 33016-47-6)  | 0 %                     | 31.12.2018                         |
| ex 2933 29 90 | 40    | Triflumizole (ISO) (CAS RN 68694-11-1)  | 0 %                     | 31.12.2014                         |
| ex 2933 29 90 | 45    | Prochloraz copper chloride (ISO) (CAS RN 156065-03-1)   | 0 %                     | 31.12.2018                         |
| ex 2933 29 90 | 50    | 1,3-Dimethylimidazolidin-2-one (CAS RN 80-73-9)   | 0 %                     | 31.12.2018                         |
| ex 2933 29 90 | 60    | 1-Cyano-2-methyl-1-[2-(5-methylimidazol-4-ylmethylthio)ethyl]isothiourea (CAS RN 52378-40-2)  | 0 %                     | 31.12.2016                         |
| ex 2933 29 90 | 70    | Cyazofamid (ISO) (CAS RN 120116-88-3)   | 0 %                     | 31.12.2016                         |
| ex 2933 29 90 | 80    | Imazalil (ISO) (CAS RN 35554-44-0)  | 0 %                     | 31.12.2017                         |
| ex 2933 39 99 | 12    | 2,3-Dichloropyridine (CAS RN 2402-77-9)   | 0 %                     | 31.12.2017                         |
| ex 2933 39 99 | 15    | Pyridine-2,3-dicarboxylic acid (CAS RN 89-00-9)   | 0 %                     | 31.12.2018                         |
| ex 2933 39 99 | 18    | 6-Chloro-3-nitropyridin-2-ylamine (CAS RN 27048-04-0)   | 0 %                     | 31.12.2017                         |
| ex 2933 39 99 | 20    | Copper pyriithione powder (CAS RN 14915-37-8)   | 0 %                     | 31.12.2014                         |
| ex 2933 39 99 | 24    | 2-Chloromethyl-4-methoxy-3,5-dimethylpyridine hydrochloride (CAS RN 86604-75-3)   | 0 %                     | 31.12.2014                         |
| ex 2933 39 99 | 25    | Imazethapyr (ISO) (CAS RN 81335-77-5)   | 0 %                     | 31.12.2018                         |
| ex 2933 39 99 | 30    | Fluazinam (ISO) (CAS RN 79622-59-6)   | 0 %                     | 31.12.2014                         |
| ex 2933 39 99 | 32    | 2-(Chloromethyl)-3,4-dimethoxypyridine hydrochloride (CAS RN 72830-09-2)  | 0 %                     | 31.12.2016                         |
| ex 2933 39 99 | 35    | Aminopyralid (ISO) (CAS RN 150114-71-9)   | 0 %                     | 31.12.2018                         |
| ex 2933 39 99 | 37    | Aqueous solution of pyridine-2-thiol-1-oxide, sodium salt (CAS RN 3811-73-2)  | 0 %                     | 31.12.2016                         |
| ex 2933 39 99 | 40    | 2-Chloropyridine (CAS RN 109-09-1)  | 0 %                     | 31.12.2018                         |

| CN code       | TARIC | Description  | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|------------------------------------|
| ex 2933 39 99 | 42    | 2,2,6,6-Tetramethylpiperidine (CAS RN 768-66-1)  | 0 %                     | 31.12.2016                         |
| ex 2933 39 99 | 45    | 5-Difluoromethoxy-2-[[[(3,4-dimethoxy-2-pyridyl)methyl]thio]-1H-benzimidazole, (CAS RN 102625-64-9)                                | 0 %                     | 31.12.2014                         |
| ex 2933 39 99 | 47    | (-)- <i>trans</i> -4-(4'-Fluorophenyl)-3-hydroxymethyl-N-methylpiperidine (CAS RN 105812-81-5)                                     | 0 %                     | 31.12.2014                         |
| ex 2933 39 99 | 48    | Flonicamid (ISO) (CAS RN 158062-67-0)  | 0 %                     | 31.12.2014                         |
| ex 2933 39 99 | 49    | 2-[[[3-Methyl-4-(2,2,2-trifluoroethoxy)-2-pyridinyl]methyl]thio]-1H-benzimidazole, (CAS RN 103577-40-8)                            | 0 %                     | 31.12.2015                         |
| ex 2933 39 99 | 50    | N-Fluoro-2,6-dichloropyridinium tetrafluoroborate (CAS RN 140623-89-8)   | 0 %                     | 31.12.2016                         |
| ex 2933 39 99 | 53    | 3-Bromopyridine (CAS RN 626-55-1)  | 0 %                     | 31.12.2018                         |
| ex 2933 39 99 | 55    | Pyriproxyfen (ISO) of a purity by weight of 97 % or more (CAS RN 95737-68-1)   | 0 %                     | 31.12.2014                         |
| ex 2933 39 99 | 57    | <i>Tert</i> -butyl 3-(6-amino-3-methylpyridin-2-yl)benzoate (CAS RN 1083057-14-0)  | 0 %                     | 31.12.2017                         |
| ex 2933 39 99 | 60    | 2-Fluoro-6-(trifluoromethyl)pyridine (CAS RN 94239-04-0)   | 0 %                     | 31.12.2018                         |
| ex 2933 39 99 | 63    | 2-Aminomethyl-3-chloro-5-trifluoromethylpyridine hydrochloride (CAS RN 326476-49-7)  | 0 %                     | 31.12.2018                         |
| ex 2933 39 99 | 65    | Acetamiprid (ISO) (CAS RN 135410-20-7)   | 0 %                     | 31.12.2018                         |
| ex 2933 39 99 | 67    | (1R,3S,4S)- <i>tert</i> -Butyl 3-(6-bromo-1H-benzo[d]imidazol-2-yl)-2-azabicyclo[2.2.1]heptane-2-carboxylate (CAS RN 1256387-74-2) | 0 %                     | 31.12.2018                         |
| ex 2933 39 99 | 70    | 2,3-Dichloro-5-trifluoromethylpyridine (CAS RN 69045-84-7)   | 0 %                     | 31.12.2016                         |
| ex 2933 39 99 | 72    | 5,6-Dimethoxy-2-[(4-piperidinyl)methyl]indan-1-one (CAS RN 120014-30-4)  | 0 %                     | 31.12.2016                         |
| ex 2933 39 99 | 77    | Imazamox (ISO) (CAS RN 114311-32-9)  | 0 %                     | 31.12.2018                         |
| ex 2933 39 99 | 85    | 2-Chloro-5-chloromethylpyridine (CAS RN 70258-18-3)  | 0 %                     | 31.12.2015                         |
| ex 2933 49 10 | 10    | Quinmerac (ISO) (CAS RN 90717-03-6)  | 0 %                     | 31.12.2018                         |
| ex 2933 49 10 | 20    | 3-Hydroxy-2-methylquinoline-4-carboxylic acid (CAS RN 117-57-7)  | 0 %                     | 31.12.2018                         |
| ex 2933 49 10 | 30    | Ethyl 4-oxo-1,4-dihydroquinoline-3-carboxylate (CAS RN 52980-28-6)   | 0 %                     | 31.12.2017                         |
| ex 2933 49 90 | 30    | Quinoline (CAS RN 91-22-5)   | 0 %                     | 31.12.2015                         |
| ex 2933 49 90 | 40    | Isoquinoline (CAS RN 119-65-3)   | 0 %                     | 31.12.2015                         |
| ex 2933 49 90 | 60    | 5,6,7,8-Tetrahydroquinoline (CAS RN 10500-57-9)  | 0 %                     | 31.12.2014                         |
| ex 2933 49 90 | 70    | Quinolin-8-ol (CAS RN 148-24-3)  | 0 %                     | 31.12.2018                         |
| ex 2933 52 00 | 10    | Malonylurea (barbituric acid) (CAS RN 67-52-7)   | 0 %                     | 31.12.2016                         |
| ex 2933 59 95 | 15    | Sitagliptin phosphate monohydrate (CAS RN 654671-77-9)   | 0 %                     | 01.07.2014                         |
| ex 2933 59 95 | 17    | N,N'-(4,6-Dichloropyrimidine-2,5-diyl)diformamide (CAS RN 116477-30-6)   | 0 %                     | 31.12.2018                         |
| ex 2933 59 95 | 20    | 2,4-Diamino-6-chloropyrimidine (CAS RN 156-83-2)   | 0 %                     | 31.12.2018                         |
| ex 2933 59 95 | 23    | 6-Chloro-3-methyluracil (CAS RN 4318-56-3)   | 0 %                     | 31.12.2018                         |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
| ex 2933 59 95 | 27    | 2-[(2-Amino-6-oxo-1,6-dihydro-9H-purin-9-yl)methoxy]-3-hydroxypropylacetate (CAS RN 88110-89-8)   | 0 %                     | 31.12.2018                         |
| ex 2933 59 95 | 30    | Mepanipirim (ISO) (CAS RN 110235-47-7)  | 0 %                     | 31.12.2018                         |
| ex 2933 59 95 | 45    | 1-[3-(Hydroxymethyl)pyridin-2-yl]-4-methyl-2-phenylpiperazine (CAS RN 61337-89-1)   | 0 %                     | 31.12.2014                         |
| ex 2933 59 95 | 50    | 2-(2-Piperazin-1-ylethoxy)ethanol (CAS RN 13349-82-1)   | 0 %                     | 31.12.2014                         |
| ex 2933 59 95 | 55    | Thiopental (INN) (CAS RN 76-75-5)   | 0 %                     | 31.12.2014                         |
| ex 2933 59 95 | 60    | 2,6-Dichloro-4,8-dipiperidinopyrimido[5,4-d]pyrimidine (CAS RN 7139-02-8)   | 0 %                     | 31.12.2018                         |
| ex 2933 59 95 | 65    | 1-Chloromethyl-4-fluoro-1,4-diazoniabicyclo[2.2.2]octane bis(tetrafluoroborate), (CAS RN 140681-55-6)   | 0 %                     | 31.12.2014                         |
| ex 2933 59 95 | 70    | N-(4-Ethyl-2,3-dioxopiperazin-1-ylcarbonyl)-D-2-phenylglycine (CAS RN 63422-71-9)   | 0 %                     | 31.12.2018                         |
| ex 2933 59 95 | 72    | Triacetylganciclovir (CAS RN 86357-14-4)  | 0 %                     | 31.12.2016                         |
| ex 2933 59 95 | 75    | (2R,3S/2S,3R)-3-(6-Chloro-5-fluoro pyrimidin-4-yl)-2-(2,4-difluorophenyl)-1-(1H-1,2,4-triazol-1-yl)butan-2-ol hydrochloride, (CAS RN 188416-20-8) | 0 %                     | 31.12.2014                         |
| ex 2933 59 95 | 77    | 3-(Trifluoromethyl)-5,6,7,8-tetrahydro[1,2,4]triazolo[4,3-a]pyrazine hydrochloride (1:1) (CAS RN 762240-92-6)                                     | 0 %                     | 31.12.2017                         |
| ex 2933 69 80 | 25    | 1,3,5-Triazine-2,4,6-triamine monophosphate (CAS RN 20208-95-1)   | 0 %                     | 31.12.2016                         |
| ex 2933 69 80 | 40    | Troclosene sodium (INN) (CAS RN 2893-78-9)  | 0 %                     | 31.12.2016                         |
| ex 2933 69 80 | 50    | 1,3,5-Tris(2,3-dibromopropyl)-1,3,5-triazinane-2,4,6-trione (CAS RN 52434-90-9)   | 0 %                     | 31.12.2018                         |
| ex 2933 69 80 | 55    | Terbutryn (ISO) (CAS RN 886-50-0)   | 0 %                     | 31.12.2015                         |
| ex 2933 69 80 | 60    | Cyanuric acid (CAS RN 108-80-5)   | 0 %                     | 31.12.2015                         |
| ex 2933 69 80 | 80    | Tris(2-hydroxyethyl)-1,3,5-triazinetrione (CAS RN 839-90-7)   | 0 %                     | 31.12.2018                         |
| ex 2933 79 00 | 30    | 5-Vinyl-2-pyrrolidone (CAS RN 7529-16-0)  | 0 %                     | 31.12.2017                         |
| ex 2933 79 00 | 50    | 6-Bromo-3-methyl-3H-dibenz(f,i)isoquinoline-2,7-dione (CAS RN 81-85-6)  | 0 %                     | 31.12.2018                         |
| ex 2933 79 00 | 60    | 3,3-Pentamethylene-4-butyrolactam (CAS RN 64744-50-9)   | 0 %                     | 31.12.2014                         |
| ex 2933 79 00 | 70    | (S)-N-[(Diethylamino)methyl]-alpha-ethyl-2-oxo-1-pyrrolidineacetamide L-(+)-tartrate, (CAS RN 754186-36-2)  | 0 %                     | 31.12.2015                         |
| ex 2933 99 80 | 10    | 2-(2H-Benzotriazol-2-yl)-4,6-di-tert-butylphenol (CAS RN 3846-71-7)   | 0 %                     | 31.12.2018                         |
| ex 2933 99 80 | 13    | 5-Difluoromethoxy-2-mercapto-1H-benzimidazole (CAS RN 97963-62-7)   | 0 %                     | 31.12.2016                         |
| ex 2933 99 80 | 15    | 2-(2H-Benzotriazol-2-yl)-4,6-di-tert-pentylphenol (CAS RN 25973-55-1)   | 0 %                     | 31.12.2018                         |
| ex 2933 99 80 | 18    | 4,4'-[(9-Butyl-9H-carbazol-3-yl)methylene]bis[N-methyl-N-phenylaniline] (CAS RN 67707-04-4)   | 0 %                     | 31.12.2017                         |
| ex 2933 99 80 | 20    | 2-(2H-Benzotriazol-2-yl)-4,6-bis(1-methyl-1-phenylethyl)phenol (CAS RN 70321-86-7)  | 0 %                     | 31.12.2018                         |
| ex 2933 99 80 | 22    | (2S)-2-Benzyl-N,N-dimethylaziridine-1-sulfonamide (CAS RN 902146-43-4)  | 0 %                     | 31.12.2017                         |
| ex 2933 99 80 | 24    | 1,3-Dihydro-5,6-diamino-2H-benzimidazol-2-one (CAS RN 55621-49-3)   | 0 %                     | 31.12.2017                         |

| CN code       | TARIC | Description  | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|------------------------------------|
| ex 2933 99 80 | 28    | N-(2,3-Dihydro-2-oxo-1H-benzimidazol-5-yl)-3-hydroxynaphthalene-2-carboxamide (CAS RN 26848-40-8)                                | 0 %                     | 31.12.2017                         |
| ex 2933 99 80 | 30    | Quizalofop-P-ethyl (ISO) (CAS RN 100646-51-3)  | 0 %                     | 31.12.2018                         |
| ex 2933 99 80 | 32    | 5-[4'-(Bromomethyl)biphenyl-2-yl]-2-trityl-2H-tetrazole (CAS RN 133051-88-4)   | 0 %                     | 31.12.2014                         |
| ex 2933 99 80 | 35    | 1,3,3-Trimethyl-2-methyleneindoline (CAS RN 118-12-7)  | 0 %                     | 31.12.2014                         |
| ex 2933 99 80 | 37    | 8-Chloro-5,10-dihydro-11H-dibenzo [b,e] [1,4]diazepin-11-one (CAS RN 50892-62-1)   | 0 %                     | 31.12.2014                         |
| ex 2933 99 80 | 40    | <i>trans</i> -4-Hydroxy-L-proline (CAS RN 51-35-4)   | 0 %                     | 31.12.2018                         |
| ex 2933 99 80 | 43    | 2,3-Dihydro-1H-pyrrole[3,2,1-ij]quinoline (CAS RN 5840-01-7)   | 0 %                     | 31.12.2017                         |
| ex 2933 99 80 | 45    | Maleic hydrazide (ISO) (CAS RN 123-33-1)   | 0 %                     | 31.12.2018                         |
| ex 2933 99 80 | 47    | Paclobutrazol (ISO) (CAS RN 76738-62-0)  | 0 %                     | 31.12.2017                         |
| ex 2933 99 80 | 50    | Metconazole (ISO) (CAS RN 125116-23-6)   | 3,2 %                   | 31.12.2018                         |
| ex 2933 99 80 | 53    | Potassium (S)-5-(tert-butoxycarbonyl)-5-azaspiro[2.4]heptane-6-carboxylate (CUS 0133723-1) (°)                                   | 0 %                     | 31.12.2018                         |
| ex 2933 99 80 | 55    | Pyridaben (ISO) (CAS RN 96489-71-3)  | 0 %                     | 31.12.2014                         |
| ex 2933 99 80 | 57    | 2-(5-Methoxyindol-3-yl)ethylamine (CAS RN 608-07-1)  | 0 %                     | 31.12.2018                         |
| ex 2933 99 80 | 62    | 1H-Indole-6-carboxylic acid (CAS RN 1670-82-2)   | 0 %                     | 31.12.2018                         |
| ex 2933 99 80 | 64    | ((3R)-1-((1R,2R)-2-[2-(3,4-Dimethoxyphenyl) ethoxy]cyclohexyl)pyrrolidin-3-ol.hydrochloride, (CAS RN 748810-28-8)                | 0 %                     | 31.12.2015                         |
| ex 2933 99 80 | 67    | Candesartan ethyl ester (INN) (CAS RN 139481-58-6)   | 0 %                     | 31.12.2016                         |
| ex 2933 99 80 | 71    | 10-Methoxyiminostilbene (CAS RN 4698-11-7)   | 0 %                     | 31.12.2018                         |
| ex 2933 99 80 | 72    | 1,4,7-Trimethyl-1,4,7-Triazacyclononane  | 0 %                     | 31.12.2018                         |
| ex 2933 99 80 | 74    | Imidazo[1,2-b] pyridazine-hydrochloride (CAS RN 18087-70-2)  | 0 %                     | 31.12.2018                         |
| ex 2933 99 80 | 76    | Manganese(2+), bis(octahydro-1,4,7-trimethyl-1H-1,4,7-triazonine-N1,N4,N7)tri- $\mu$ -oxodi-, acetate (1:2) (CAS RN 916075-10-0) | 0 %                     | 31.12.2014                         |
| ex 2933 99 80 | 78    | 3-Amino-3-azabicyclo (3.3.0) octane hydrochloride (CAS RN 58108-05-7)  | 0 %                     | 31.12.2018                         |
| ex 2933 99 80 | 81    | 1,2,3-Benzotriazole (CAS RN 95-14-7)   | 0 %                     | 31.12.2016                         |
| ex 2933 99 80 | 82    | Tolytriazole (CAS RN 29385-43-1)   | 0 %                     | 31.12.2018                         |
| ex 2933 99 80 | 88    | 2,6-Dichloroquinoxaline (CAS RN 18671-97-1)  | 0 %                     | 31.12.2014                         |
| ex 2933 99 80 | 89    | Carbendazim (ISO) (CAS RN 10605-21-7)  | 0 %                     | 31.12.2018                         |
| ex 2934 10 00 | 10    | Hexythiazox (ISO) (CAS RN 78587-05-0)  | 0 %                     | 31.12.2018                         |
| ex 2934 10 00 | 15    | 4-Nitrophenyl thiazol-5-ylmethyl carbonate (CAS RN 144163-97-3)  | 0 %                     | 31.12.2017                         |
| ex 2934 10 00 | 20    | 2-(4-Methylthiazol-5-yl)ethanol (CAS RN 137-00-8)  | 0 %                     | 31.12.2018                         |

| CN code       | TARIC | Description  | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|------------------------------------|
| ex 2934 10 00 | 25    | (S)-Ethyl-2-(3-((2-isopropylthiazol-4-yl)methyl)-3-methylureido)-4-morpholinobutanoate oxalate (CAS RN 1247119-36-3)   | 0 %                     | 31.12.2017                         |
| ex 2934 10 00 | 35    | (2-Isopropylthiazol-4-yl)-N-methylmethanamine dihydrochloride (CAS RN 1185167-55-8)  | 0 %                     | 31.12.2017                         |
| ex 2934 10 00 | 40    | (Z)-2-(2-tert-butoxycarbonylaminothiazol-4-yl)-2-pentenoic acid (CAS RN 86978-24-7)  | 0 %                     | 31.12.2018                         |
| ex 2934 10 00 | 60    | Fosthiazate (ISO) (CAS RN 98886-44-3)  | 0 %                     | 31.12.2014                         |
| ex 2934 10 00 | 70    | 2-(Formylamino)-4-thiazoleacetyl chloride, hydrochloride (CAS RN 372092-18-7)  | 0 %                     | 31.12.2016                         |
| ex 2934 10 00 | 80    | 3,4-Dichloro-5-carboxyisothiazole (CAS RN 18480-53-0)  | 0 %                     | 31.12.2016                         |
| ex 2934 20 80 | 20    | S-1,3-Benzothiazol-2-yl (2Z)-(5-amino-1,2,4-thiadiazol-3-yl)(methoxyimino)ethanethioate (CAS RN 89604-91-1)  | 0 %                     | 31.12.2016                         |
| ex 2934 20 80 | 30    | 2-[[[Z]-[1-(2-Amino-4-thiazolyl)-2-(2-benzothiazolylthio)-2-oxoethylidene]amino]oxy]-acetic acid, methyl ester (CAS RN 246035-38-1)                                  | 0 %                     | 31.12.2016                         |
| ex 2934 20 80 | 40    | 1,2-Benzisothiazol-3(2H)-one (Benzisothiazolinone (BIT)) (CAS RN 2634-33-5)  | 0 %                     | 31.12.2017                         |
| ex 2934 20 80 | 50    | S-(1,3-Benzothiazol-2-yl)-(Z)-2-(2-aminothiazol-4-yl)-2-(acetyloxyimino)thioacetate, (CAS RN 104797-47-9)  | 0 %                     | 31.12.2018                         |
| ex 2934 20 80 | 60    | Benzothiazol-2-yl-(Z)-2-trityloxyimino-2-(2-aminothiazole-4-yl)-thioacetate (CAS RN 143183-03-3)   | 0 %                     | 31.12.2015                         |
| ex 2934 20 80 | 70    | N,N-Bis(1,3-benzothiazol-2-ylsulphonyl)-2-methylpropan-2-amine (CAS RN 3741-80-8)  | 0 %                     | 31.12.2015                         |
| ex 2934 30 90 | 10    | 2-Methylthiophenothiazine (CAS RN 7643-08-5)   | 0 %                     | 31.12.2017                         |
| ex 2934 99 90 | 11    | Methyl 3-[1,4-dioxaspiro[4.5]dec-8-yl]((trans-4-methylcyclohexyl)carbonyl)amino]-5-iodothiophene-2-carboxylate (CAS RN 1026785-65-8)                                 | 0 %                     | 31.12.2018                         |
| ex 2934 99 90 | 12    | Dimethomorph (ISO) (CAS RN 110488-70-5)  | 0 %                     | 31.12.2018                         |
| ex 2934 99 90 | 13    | Buprofezin (ISO) of a purity by weight of 98,5 % or more (CAS RN 953030-84-7)  | 0 %                     | 31.12.2018                         |
| ex 2934 99 90 | 14    | Ethyl N-[[1-methyl-2-[[4-(5-oxo-4,5-dihydro-1,2,4-oxadiazol-3-yl)phenyl]amino)methyl]-1H-benzimidazol-5-yl]carbonyl]-N-pyridin-2-yl-b-alaninate (CAS RN 872728-84-2) | 0 %                     | 31.12.2017                         |
| ex 2934 99 90 | 15    | Carboxin (ISO) (CAS RN 5234-68-4)  | 0 %                     | 31.12.2018                         |
| ex 2934 99 90 | 17    | Methyl(1,8-diethyl-1,3,4,9-tetrahydropyrano[3,4-b]indol-1-yl)acetate (CAS RN 122188-02-7)  | 0 %                     | 31.12.2016                         |
| ex 2934 99 90 | 18    | 3,3-bis(2-Methyl-1-octyl-1H-indol-3-yl)phthalide (CAS RN 50292-95-0)   | 0 %                     | 31.12.2017                         |
| ex 2934 99 90 | 20    | Thiophene (CAS RN 110-02-1)  | 0 %                     | 31.12.2014                         |
| ex 2934 99 90 | 22    | 7-[4-(Diethylamino)-2-ethoxyphenyl]-7-(2-methyl-1-octyl-1H-indol-3-yl)furo[3,4-b]pyridin-5(7H)-one (CAS RN 87563-89-1)   | 0 %                     | 31.12.2017                         |
| ex 2934 99 90 | 23    | Bromuconazole (ISO) with a purity by weight of 96 % or more (CAS RN 116255-48-2)   | 0 %                     | 31.12.2016                         |
| ex 2934 99 90 | 25    | 2,4-Diethyl-9H-thioxanthen-9-one (CAS RN 82799-44-8)   | 0 %                     | 31.12.2015                         |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
| ex 2934 99 90 | 28    | 11-(Piperazin-1-yl)dibenzo[b,f][1,4]thiazepine dihydrochloride (CAS RN 111974-74-4)   | 0 %                     | 31.12.2016                         |
| ex 2934 99 90 | 30    | Dibenzo[b,f][1,4]thiazepin-11(10H)-one (CAS RN 3159-07-7)   | 0 %                     | 31.12.2014                         |
| ex 2934 99 90 | 33    | [2,2'-Thio-bis(4-tert-octylphenolato)]-n-butylamine nickel (CAS RN 14516-71-3)  | 0 %                     | 31.12.2016                         |
| ex 2934 99 90 | 35    | Dimethenamide (ISO) (CAS RN 87674-68-8)   | 0 %                     | 31.12.2018                         |
| ex 2934 99 90 | 37    | 4-Propan-2-ylmorpholine (CAS RN 1004-14-4)  | 0 %                     | 31.12.2017                         |
| ex 2934 99 90 | 40    | 2-Thiophene ethylamine (CAS RN 30433-91-1)  | 0 %                     | 31.12.2015                         |
| ex 2934 99 90 | 43    | Clopidogrel acid hydrochloride (CAS RN 144750-42-5)   | 0 %                     | 31.12.2016                         |
| ex 2934 99 90 | 45    | Tris(2,3-epoxypropyl)-1,3,5-triazinetrione (CAS RN 2451-62-9)   | 0 %                     | 31.12.2018                         |
| ex 2934 99 90 | 48    | Propan-2-ol - 2-methyl-4-(4-methylpiperazin-1-yl)-10H-thieno[2,3-b][1,5]benzodiazepine (1:2) dihydrate (CAS RN 864743-41-9)   | 0 %                     | 31.12.2016                         |
| ex 2934 99 90 | 50    | 10-[1,1'-Biphenyl]-4-yl-2-(1-methylethyl)-9-oxo-9H-thioxanthenium hexafluorophosphate, (CAS RN 591773-92-1)   | 0 %                     | 31.12.2015                         |
| ex 2934 99 90 | 55    | Olmесartan medoxomil (INN) (CAS RN 144689-63-4)   | 0 %                     | 31.12.2018                         |
| ex 2934 99 90 | 60    | DL-Homocysteine thiolactone hydrochloride (CAS RN 6038-19-3)  | 0 %                     | 31.12.2018                         |
| ex 2934 99 90 | 66    | Tetrahydrothiophene-1,1-dioxide (CAS RN 126-33-0)   | 0 %                     | 31.12.2018                         |
| ex 2934 99 90 | 72    | 1-[3-(5-Nitro-2-furyl)allylideneamino]imidazolidine-2,4-dione (CAS RN 1672-88-4)  | 0 %                     | 31.12.2018                         |
| ex 2934 99 90 | 74    | 2-Isopropylthioxanthone (CAS RN 5495-84-1)  | 0 %                     | 31.12.2017                         |
| ex 2934 99 90 | 75    | (4R-cis)-1,1-Dimethylethyl-6-[2[2-(4-fluorophenyl)-5-(1-isopropyl)-3-phenyl-4-[(phenylamino)carbonyl]-1H-pyrrol-1-yl]ethyl]-2,2-dimethyl-1,3-dioxane-4-acetate (CAS RN 125971-95-1) | 0 %                     | 31.12.2016                         |
| ex 2934 99 90 | 76    | 2,5-Thiophenediylbis(5-tert-butyl-1,3-benzoxazole) (CAS RN 7128-64-5)   | 0 %                     | 31.12.2016                         |
| ex 3204 20 00 | 10    |   |                         |                                    |
| ex 2934 99 90 | 77    | Potassium 5-methyl-1,3,4-oxadiazole-2-carboxylate (CAS RN 888504-28-7)  | 0 %                     | 31.12.2016                         |
| ex 2934 99 90 | 79    | Thiophen-2-ethanol (CAS RN 5402-55-1)   | 0 %                     | 31.12.2018                         |
| ex 2934 99 90 | 83    | Flumioxazin (ISO) of a purity by weight of 96 % or more (CAS RN 103361-09-7)  | 0 %                     | 31.12.2014                         |
| ex 2934 99 90 | 84    | Etoxazole (ISO) of a purity by weight of 94,8 % or more (CAS RN 153233-91-1)  | 0 %                     | 31.12.2014                         |
| ex 2934 99 90 | 85    | N2-[1-(S)-Ethoxycarbonyl-3-phenylpropyl]-N6-trifluoroacetyl-L-lysyl-N2-carboxy anhydride (CAS RN 126586-91-2)   | 0 %                     | 31.12.2015                         |
| ex 2934 99 90 | 86    | Dithianon (ISO) (CAS RN 3347-22-6)  | 0 %                     | 31.12.2015                         |
| ex 2934 99 90 | 87    | 2,2'-(1,4-Phenylene)bis(4H-3,1-benzoxazin-4-one) (CAS RN 18600-59-4)  | 0 %                     | 31.12.2015                         |
| ex 2935 00 90 | 15    | Flupyrsulfuron-methyl-sodium (ISO) (CAS RN 144740-54-5)   | 0 %                     | 31.12.2018                         |
| ex 2935 00 90 | 17    | 6-Methyl-4-oxo-5,6-dihydro-4H-thieno[2,3-b]thiopyran-2-sulfonamide (CAS RN 120279-88-1)   | 0 %                     | 31.12.2018                         |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
| ex 2935 00 90 | 20    | Toluenesulphonamides  | 0 %                     | 31.12.2018                         |
| ex 2935 00 90 | 23    | N-[4-(2-Chloroacetyl)phenyl]methanesulphonamide (CAS RN 64488-52-4)   | 0 %                     | 31.12.2016                         |
| ex 2935 00 90 | 25    | Triflurosulfuron-methyl (ISO) (CAS RN 126535-15-7)  | 0 %                     | 31.12.2018                         |
| ex 2935 00 90 | 27    | Methyl (3R,5S,6E)-7-[4-(4-fluorophenyl)-6-isopropyl-2-[methyl(methylsulfonyl)amino]pyrimidin-5-yl]-3,5-dihydroxyhept-6-enoate (CAS RN 147118-40-9)  | 0 %                     | 31.12.2016                         |
| ex 2935 00 90 | 28    | N-Fluorobenzenesulphonimide (CAS RN 133745-75-2)  | 0 %                     | 31.12.2018                         |
| ex 2935 00 90 | 30    | Mixture of isomers consisting of N-ethyltoluene-2-sulphonamide and N-ethyltoluene-4-sulphonamide  | 0 %                     | 31.12.2014                         |
| ex 2935 00 90 | 35    | Chlorsulfuron (ISO) (CAS RN 64902-72-3)   | 0 %                     | 31.12.2018                         |
| ex 2935 00 90 | 40    | Imazosulfuron (ISO), of a purity by weight of 98 % or more (CAS RN 122548-33-8)   | 0 %                     | 31.12.2015                         |
| ex 2935 00 90 | 42    | Penoxsulam (ISO) (CAS RN 219714-96-2)   | 0 %                     | 31.12.2015                         |
| ex 2935 00 90 | 45    | Rimsulfuron (ISO) (CAS RN 122931-48-0)  | 0 %                     | 31.12.2018                         |
| ex 2935 00 90 | 48    | (3R,5S,6E)-7-[4-(4-Fluorophenyl)-2-[methyl(methylsulfonyl)amino]-6-(propan-2-yl)pyrimidin-5-yl]-3,5-dihydroxyhept-6-enoic acid – 1-[(R)-(4-chlorophenyl)(phenyl)methyl]piperazine (1:1) (CAS RN 1235588-99-4) | 0 %                     | 31.12.2016                         |
| ex 2935 00 90 | 50    | 4,4'-Oxydi(benzenesulphonohydrazide) (CAS RN 80-51-3)   | 0 %                     | 31.12.2018                         |
| ex 2935 00 90 | 53    | 2,4-Dichloro-5-sulphamoylbenzoic acid (CAS RN 2736-23-4)  | 0 %                     | 31.12.2014                         |
| ex 2935 00 90 | 55    | Thifensulfuron-methyl (ISO) (CAS RN 79277-27-3)   | 0 %                     | 31.12.2018                         |
| ex 2935 00 90 | 63    | Nicosulphuron (ISO), of a purity by weight of 91 % or more (CAS RN 111991-09-4)   | 0 %                     | 31.12.2014                         |
| ex 2935 00 90 | 65    | Tribenuron-methyl (ISO) (CAS RN 101200-48-0)  | 0 %                     | 31.12.2018                         |
| ex 2935 00 90 | 75    | Metsulfuron-methyl (ISO) (CAS RN 74223-64-6)  | 0 %                     | 31.12.2018                         |
| ex 2935 00 90 | 77    | [[4-[2-[[[3-Ethyl-2,5-dihydro-4-methyl-2-oxo-1H-pyrrol-1-yl]carbonyl]amino]ethyl]phenyl]sulfonyl]-carbamic acid ethyl ester, (CAS RN 318515-70-7)   | 0 %                     | 31.12.2014                         |
| ex 2935 00 90 | 82    | N-(5,7-Dimethoxy[1,2,4]triazolo[1,5-a]pyrimidin-2-yl)-2-methoxy-4-(trifluoromethyl)pyridine-3-sulphonamide, (CAS RN 422556-08-9)  | 0 %                     | 31.12.2014                         |
| ex 2935 00 90 | 85    | N-[4-(Isopropylaminoacetyl)phenyl]methanesulphonamide hydrochloride   | 0 %                     | 31.12.2018                         |
| ex 2935 00 90 | 88    | N-(2-(4-Amino-N-ethyl-m-toluidino)ethyl)methanesulphonamide sesquisulphate monohydrate, (CAS RN 25646-71-3)   | 0 %                     | 31.12.2018                         |
| ex 2935 00 90 | 89    | 3-(3-Bromo-6-fluoro-2-methylindol-1-ylsulphonyl)-N,N-dimethyl-1,2,4-triazol-1-sulphonamide (CAS RN 348635-87-0)   | 0 %                     | 31.12.2016                         |
| ex 2938 90 30 | 10    | Ammonium glycyrrhizate (CAS RN 53956-04-0)  | 0 %                     | 31.12.2015                         |
| ex 2938 90 90 | 10    | Hesperidin (CAS RN 520-26-3)  | 0 %                     | 31.12.2018                         |
| ex 2938 90 90 | 20    | Ethylvanillin beta-D-glucopyranoside (CAS RN 122397-96-0)   | 0 %                     | 31.12.2018                         |
| ex 2941 20 30 | 10    | Dihydrostreptomycin sulphate (CAS RN 5490-27-7)   | 0 %                     | 31.12.2016                         |
| ex 3102 50 00 | 10    | Natural sodium nitrate  | 0 %                     | 31.12.2017                         |

| CN code       | TARIC | Description  | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|------------------------------------|
| 3201 20 00    |       | Wattle extract   | 0 %                     | 31.12.2018                         |
| ex 3201 90 90 | 20    | Tanning extracts derived from gambier and myrobalan fruits   | 0 %                     | 31.12.2018                         |
| ex 3204 11 00 | 20    | Dye C.I. Disperse Yellow 241 (CAS RN 83249-52-9), with a purity of 97 % or more as determined by high pressure liquid chromatography   | 0 %                     | 31.12.2015                         |
| ex 3204 11 00 | 30    | Preparation of dispersion dyes, containing:<br>— C.I. Disperse Orange 61,<br>— C.I. Disperse Blue 291:1,<br>— C.I. Disperse Violet 93:1,<br>— C.I. Disperse Red 54   | 0 %                     | 31.12.2015                         |
| ex 3204 11 00 | 40    | Dye C.I. Disperse Red 60 (CAS RN 17418-58-5)   | 0 %                     | 31.12.2016                         |
| ex 3204 11 00 | 50    | Dye C.I. Disperse Blue 72 (CAS RN 81-48-1)   | 0 %                     | 31.12.2016                         |
| ex 3204 11 00 | 60    | Dye C.I. Disperse Blue 359 (CAS RN 213328-78-0)  | 0 %                     | 31.12.2016                         |
| ex 3204 11 00 | 70    | Dye C.I. Disperse Red 343 (CAS RN 99035-78-6)  | 0 %                     | 31.12.2017                         |
| ex 3204 11 00 | 80    | Dye preparation, non-ionogenic, containing:<br>— N-[5-(acetylamino)-4-[(2-chloro-4,6-dinitrophenyl)azo]-2-methoxyphenyl]-2-oxo-2-(phenylmethoxy)ethyl-β-alanine (CAS RN 159010-67-0)<br>— N-[4-[(2-cyano-4-nitrophenyl)azo]phenyl]-N-methyl-2-(1,3-dihydro-1,3-dioxo-2H-isoindol-2-yl)ethyl-β-alanine (CAS RN 170222-39-6) and<br>— N-[2-chloro-4-[(4-nitrophenyl)azo]phenyl]-2-[2-(1,3-dihydro-1,3-dioxo-2H-isoindol-2-yl)ethoxy]-2-oxoethyl-β-alanine (CAS RN 371921-34-5) | 0 %                     | 31.12.2017                         |
| ex 3204 12 00 | 10    | Dye C.I. Acid Blue 9 (CAS RN 3844-45-9)  | 0 %                     | 31.12.2016                         |
| ex 3204 12 00 | 20    | Dye preparation, anionic, containing by weight 75 % or more of disodium-7-((4-chloro-6-(dodecylamino)-1,3,5-triazin-2-yl)amino)-4-hydroxy-3-((4-((4-sulfophenyl)azo)phenyl)azo)-2-naphthalenesulfonate (CAS RN 145703-76-0)  | 0 %                     | 31.12.2017                         |
| ex 3204 12 00 | 30    | Acid dye preparation, anionic, containing:<br>— lithium-amino-4-(4-tert-butylanilino)anthraquinone-2-sulfonate (CAS RN 125328-86-1),<br>— C.I. Acid Green 25 (CAS RN 4403-90-1) and<br>— C.I. Acid Blue 80 (CAS RN 4474-24-2)  | 0 %                     | 31.12.2017                         |
| ex 3204 12 00 | 40    | Liquid dye preparation containing anionic acid dye C.I. Acid Blue 182 (CAS RN 12219-26-0)  | 0 %                     | 31.12.2018                         |
| ex 3204 13 00 | 10    | Dye C.I. Basic Red 1 (CAS RN 989-38-8)   | 0 %                     | 31.12.2016                         |
| ex 3204 13 00 | 20    | (2,2'-(3,3'-Dioxidobiphenyl-4,4'-diyldiazo)bis(6-(4-(3-(diethylamino)propylamino)-6-(3-(diethylammonio)propylamino)-1,3,5-triazin-2-ylamino)-3-sulfonato-1-naphtholato))dicopper(II) acetate lactate (CAS RN 159604-94-1)  | 0 %                     | 31.12.2017                         |
| ex 3204 13 00 | 30    | Dye C.I. Basic Blue 7 (CAS RN 2390-60-5)   | 0 %                     | 31.12.2017                         |
| ex 3204 13 00 | 40    | Dye C.I. Basic Violet 1 (CAS RN 603-47-4)/(CAS RN 8004-87-3)   | 0 %                     | 31.12.2017                         |
| ex 3204 15 00 | 10    | Dye C.I. Vat Orange 7 (C.I. Pigment Orange 43) (CAS RN 4424-06-0)  | 0 %                     | 31.12.2017                         |
| ex 3204 15 00 | 60    | Dyestuff C.I. Vat Blue 4 (CAS RN 81-77-6)  | 0 %                     | 31.12.2018                         |
| ex 3204 17 00 | 10    | Dye C.I. Pigment Yellow 81 (CAS RN 22094-93-5)   | 0 %                     | 31.12.2018                         |

| CN code       | TARIC | Description  | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|------------------------------------|
| ex 3204 17 00 | 15    | Dye C.I. Pigment Green 7 (CAS RN 1328-53-6)  | 0 %                     | 31.12.2016                         |
| ex 3204 17 00 | 20    | Dye C.I. Pigment Blue 15:3 (CAS RN 147-14-8)   | 0 %                     | 31.12.2016                         |
| ex 3204 17 00 | 25    | Dye C.I. Pigment Yellow 14 (CAS RN 5468-75-7)  | 0 %                     | 31.12.2016                         |
| ex 3204 17 00 | 30    | Dye C.I. Pigment Yellow 97 (CAS RN 12225-18-2)   | 0 %                     | 31.12.2017                         |
| ex 3204 17 00 | 35    | Dye C.I. Pigment Red 202 (CAS RN 3089-17-6)  | 0 %                     | 31.12.2016                         |
| ex 3204 17 00 | 40    | Dye C.I. Pigment Yellow 120 (CAS RN 29920-31-8)  | 0 %                     | 31.12.2014                         |
| ex 3204 17 00 | 50    | Dye C.I. Pigment Yellow 180 (CAS RN 77804-81-0)  | 0 %                     | 31.12.2014                         |
| ex 3204 17 00 | 60    | Dye C.I. Pigment Red 53:1 (CAS RN 5160-02-1)   | 0 %                     | 31.12.2016                         |
| ex 3204 17 00 | 65    | Dye C.I. Pigment Red 53 (CAS RN 2092-56-0)   | 0 %                     | 31.12.2016                         |
| ex 3204 17 00 | 70    | Dye C.I. Pigment Yellow 13 (CAS RN 5102-83-0)  | 0 %                     | 31.12.2016                         |
| ex 3204 17 00 | 75    | Dye C.I. Pigment Orange 5 (CAS RN 3468-63-1)   | 0 %                     | 31.12.2017                         |
| ex 3204 17 00 | 80    | Dye C.I. Pigment Red 207 (CAS RN 71819-77-7)   | 0 %                     | 31.12.2017                         |
| ex 3204 17 00 | 85    | Dye C.I. Pigment Blue 61 (CAS RN 1324-76-1)  | 0 %                     | 31.12.2017                         |
| ex 3204 17 00 | 88    | Dye C.I. Pigment Violet 3 (CAS RN 1325-82-2)   | 0 %                     | 31.12.2017                         |
| ex 3204 19 00 | 11    | Photochromic dye, 3-(4-butoxyphenyl)-6,7-dimethoxy-3-(4-methoxyphenyl)-13,13-dimethyl-3,13-dihydrobenzo[h]indeno[2,1-f]chromene-11-carbonitrile  | 0 %                     | 31.12.2014                         |
| ex 3204 19 00 | 21    | Photochromic dye, 4-(3-(4-butoxyphenyl)-6-methoxy-3-(4-methoxyphenyl)-13,13-dimethyl-11-(trifluoromethyl)-3,13-dihydrobenzo[h]indeno[2,1-f]chromen-7-yl)morpholine (CAS RN 1021540-64-6)       | 0 %                     | 31.12.2014                         |
| ex 3204 19 00 | 31    | Photochromic dye, N-hexyl -6,7-dimethoxy-3,3-bis(4-methoxyphenyl)-13,13-dimethyl-3,13-dihydrobenzo[h]indeno[2,1-f]chromene-11-carboxamide  | 0 %                     | 31.12.2014                         |
| ex 3204 19 00 | 41    | Photochromic dye, 4,4'-(13,13-dimethyl-3,13-dihydrobenzo[h]indeno[2,1-f]chromene-3,3-diyl)diphenol   | 0 %                     | 31.12.2014                         |
| ex 3204 19 00 | 43    | Photochromic dye, bis(2-(4-(7-methoxy-3-(4-methoxyphenyl)-11-phenyl-13,13-dipropyl-3,13-dihydrobenzo[h]indeno[2,1-f]chromen-3-yl)phenoxy)ethyl) decanedioate (CUS 0133724-2) <sup>(5)</sup>    | 0 %                     | 31.12.2018                         |
| ex 3204 19 00 | 47    | Photochromic dye, 4-(4-(13,13-dimethyl-3,11-diphenyl-3,13-dihydrobenzo[h]indeno[2,1-f]chromen-3-yl)phenyl)morpholine (CUS 0133726-4) <sup>(5)</sup>  | 0 %                     | 31.12.2018                         |
| ex 3204 19 00 | 51    | Photochromic dye, 4-(4-(6,11-difluoro-13,13-dimethyl-3-phenyl-3,13-dihydrobenzo[h]indeno[2,1-f]chromen-3-yl)phenyl)morpholine (CAS RN 1360882-72-6)  | 0 %                     | 31.12.2014                         |
| ex 3204 19 00 | 53    | Photochromic dye, 3-(4-butoxyphenyl)-3-(4-fluorophenyl)-6,7-dimethoxy-13,13-dimethyl-3,13-dihydrobenzo[h]indeno[2,1-f]chromene-11-carbonitrile (CUS 0133725-3) <sup>(5)</sup>                  | 0 %                     | 31.12.2018                         |
| ex 3204 19 00 | 55    | Photochromic dye, 4, 4'-(7-methoxy-11-phenyl-13, 13-dipropyl-3, 13-dihydrobenzo[h]indeno[2, 1-f]chromene-3, 3-diyl)diphenol (CUS 0133728-6) <sup>(5)</sup>                                     | 0 %                     | 31.12.2018                         |
| ex 3204 19 00 | 57    | Photochromic dye, bis(2-(4-[11-cyano-3-(4-fluorophenyl)-6,7-dimethoxy-13,13-dimethyl-3, 13-dihydrobenzo[h]indeno[2,1-f]chromen-3-yl]phenoxy)ethyl) decanedioate (CUS 0133729-7) <sup>(5)</sup> | 0 %                     | 31.12.2018                         |

| CN code       | TARIC | Description  | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|------------------------------------|
| ex 3204 19 00 | 61    | Photochromic dye, 3-(4-butoxyphenyl)-6,7-dimethoxy-3-(4-methoxyphenyl)-13,13-dimethyl-11-(trifluoromethyl)-3,13-dihydrobenzo[h]indeno[2,1-f]chromene (CAS RN 1021540-61-3)   | 0 %                     | 31.12.2014                         |
| ex 3204 19 00 | 63    | Photochromic dye, 1-{4-(6-methoxy-3-(4-methoxyphenyl)-13,13-dimethyl-3,13-dihydrobenzo[h]indeno[2,1-f]chromen-3-yl)phenyl}piperidine (CUS 0133727-5) <sup>(5)</sup>  | 0 %                     | 31.12.2018                         |
| ex 3204 19 00 | 70    | Dye C.I. Solvent Red 49 (CAS RN 509-34-2)  | 0 %                     | 31.12.2018                         |
| ex 3204 19 00 | 71    | Dye C.I. Solvent Brown 53 (CAS RN 64696-98-6)  | 0 %                     | 31.12.2015                         |
| ex 3204 19 00 | 73    | Dye C.I. Solvent Blue 104 (CAS RN 116-75-6) with a purity of 97 % or more determined by high pressure liquid chromatography  | 0 %                     | 31.12.2015                         |
| ex 3204 19 00 | 77    | Dye C.I. Solvent Yellow 98 (CAS RN 27870-92-4)   | 0 %                     | 31.12.2016                         |
| ex 3204 19 00 | 84    | Dye C.I. Solvent Blue 67 (CAS RN 12226-78-7)   | 0 %                     | 31.12.2017                         |
| ex 3204 19 00 | 85    | Dye C.I. Solvent Red HPR   | 0 %                     | 31.12.2017                         |
| ex 3204 20 00 | 20    | Dye C.I. Fluorescent Brightener 71 (CAS RN 16090-02-1)   | 0 %                     | 31.12.2016                         |
| ex 3204 20 00 | 30    | Dye C.I. Fluorescent Brightener 351 (CAS RN 38775-22-3)  | 0 %                     | 31.12.2016                         |
| ex 3204 20 00 | 40    | Disodium 5-[[4-anilino-6-[2-hydroxyethyl(methyl)amino]-1,3,5-triazin-2-yl]amino]-2-[(E)-2-[4-[[4-anilino-6-[2-hydroxyethyl(methyl)amino]-1,3,5-triazin-2-yl]amino]-2-sulfonatophenyl]ethenyl]benzenesulphonate (CAS RN 13863-31-5)   | 0 %                     | 31.12.2018                         |
| ex 3205 00 00 | 10    | Aluminium lakes prepared from dyes for use in the manufacture of pigments for the pharmaceutical industry <sup>(1)</sup>   | 0 %                     | 31.12.2018                         |
| ex 3205 00 00 | 20    | Dye C.I. Carbon Black 7 Lake   | 0 %                     | 31.12.2016                         |
| ex 3206 11 00 | 10    | Titanium dioxide coated with isopropoxytitanium triisostearate, containing by weight 1,5 % or more but not more than 2,5 % of isopropoxytitanium triisostearate  | 0 %                     | 31.12.2018                         |
| ex 3206 19 00 | 10    | Preparation containing by weight:<br>— 72 % ( $\pm$ 2 %) of mica (CAS RN 12001-26-2) and<br>— 28 % ( $\pm$ 2 %) of titanium dioxide (CAS RN 13463-67-7)  | 0 %                     | 31.12.2016                         |
| ex 3206 42 00 | 10    | Lithopone (CAS RN 1345-05-7)   | 0 %                     | 31.12.2018                         |
| 3206 50 00    |       | Inorganic products of a kind used as luminophores  | 0 %                     | 31.12.2018                         |
| ex 3207 30 00 | 10    | Preparation containing:<br>— not more than 85 % by weight of silver,<br>— not less than 2 % by weight of palladium,<br>— barium titanate,<br>— terpineol, and<br>— ethyl cellulose,<br>used for screen printing in the manufacture of multilayer ceramic capacitors <sup>(1)</sup> | 0 %                     | 31.12.2018                         |
| ex 3207 40 85 | 20    | Glass flakes coated with silver, of an average diameter of 40 ( $\pm$ 10) $\mu$ m  | 0 %                     | 31.12.2018                         |
| ex 3207 40 85 | 40    | Glass flakes (CAS RN 65997-17-3):<br>— of a thickness of 0,3 $\mu$ m or more but not more than 10 $\mu$ m, and<br>— coated with titanium dioxide (CAS RN 13463-67-7) or iron oxide (CAS RN 18282-10-5)   | 0 %                     | 31.12.2017                         |

| CN code                        | TARIC    | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|--------------------------------|----------|---|-------------------------|------------------------------------|
| ex 3208 10 90<br>ex 3707 90 90 | 10<br>60 | Anti-reflection coating, consisting of an ester based polymer modified with a chromophore group, in the form of a solution of either 2-methoxy-1-propanol, 2-methoxy-1-methylethyl acetate or methyl-2-hydroxyisobutyrate, containing by weight not more than 10 % of polymer   | 0 %                     | 31.12.2018                         |
| ex 3208 20 10                  | 10       | Copolymer of N-vinylcaprolactam, N-vinyl-2-pyrrolidone and dimethylaminoethyl methacrylate, in the form of a solution in ethanol containing by weight 34 % or more but not more than 40 % of copolymer  | 0 %                     | 31.12.2018                         |
| ex 3208 20 10                  | 20       | Immersion topcoat solution containing by weight 0,5 % or more but not more than 15 % of acrylate-methacrylate-alkenesulphonate copolymers with fluorinated side chains, in a solution of n-butanol and/or 4-methyl-2-pentanol and/or diisoamylether   | 0 %                     | 31.12.2018                         |
| ex 3208 90 19                  | 10       | Copolymer of maleic acid and methyl vinyl ether, monoesterified with ethyl and/or isopropyl and/or butyl groups, in the form of a solution in ethanol, ethanol and butanol, isopropanol or isopropanol and butanol  | 0 %                     | 31.12.2018                         |
| ex 3208 90 19<br>ex 3902 90 90 | 15<br>94 | Modified, chlorinated polyolefins, whether or not in a solution or dispersion   | 0 %                     | 31.12.2018                         |
| ex 3208 90 19<br>ex 3208 90 91 | 25<br>20 | Tetrafluoroethylene copolymer in butylacetate solution with a content of solvent of 50 % ( $\pm 2$ %) by weight   | 0 %                     | 31.12.2017                         |
| ex 3208 90 19                  | 35       | Silicones containing 50 % by weight or more of xylene of a kind used for the manufacture of long term surgical implants   | 0 %                     | 31.12.2018                         |
| ex 3208 90 19                  | 40       | Polymer of methylsiloxane, in the form of a solution in a mixture of acetone, butanol, ethanol and isopropanol, containing by weight 5 % or more but not more than 11 % of polymer of methylsiloxane  | 0 %                     | 31.12.2018                         |
| ex 3208 90 19                  | 50       | Solution containing by weight:<br>— (65 $\pm$ 10) % of $\gamma$ -butyrolactone,<br>— (30 $\pm$ 10) % of polyamide resin,<br>— (3,5 $\pm$ 1,5) % of naphthoquinone ester derivative and<br>— (1,5 $\pm$ 0,5) % of arylsilicic acid   | 0 %                     | 31.12.2018                         |
| ex 3208 90 19                  | 60       | Copolymer of hydroxystyrene with one or more of the following:<br>— styrene<br>— alkoxy styrene<br>— alkylacrylates<br>dissolved in ethyl lactate   | 0 %                     | 31.12.2016                         |
| ex 3208 90 19                  | 75       | Acenaphthalene copolymer in ethyl lactate solution  | 0 %                     | 31.12.2017                         |
| ex 3208 90 99                  | 10       | Solution based on chemically modified natural polymers, containing two or more of the following dyes:<br>— methyl 8'-acetoxy-1,3,3,5,6-pentamethyl-2,3-dihydrospiro[1H-indole-2,3'-naphtho[2,1-b][1,4]oxazine]-9'-carboxylate,<br>— methyl 6-(isobutyryloxy)-2,2-diphenyl-2H-benzo[h]chromene-5-carboxylate,<br>— 13-isopropyl-3,3-bis(4-methoxyphenyl)-6,11-dimethyl-3,13-dihydrobenzo[h]indeno[2,1-f]chromen-13-ol,<br>— ethoxycarbonylmethyl 8-methyl-2,2-diphenyl-2H-benzo[h]chromene-5-carboxylate,<br>— 13-ethyl-3-[4-(morpholino)phenyl]-3-phenyl-3,13-dihydrobenzo[h]indeno[2,1-f]chromen-13-ol | 0 %                     | 31.12.2018                         |
| ex 3215 11 00<br>ex 3215 19 00 | 10<br>10 | Printing ink, liquid, consisting of a dispersion of a vinyl acrylate copolymer and colour pigments in isoparaffins, containing by weight not more than 13 % of vinyl acrylate copolymer and colour pigments   | 0 %                     | 31.12.2018                         |

| CN code       | TARIC | Description  | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|------------------------------------|
| ex 3215 19 00 | 20    | Ink:<br>— consisting of a polyester polymer and a dispersion of silver (CAS RN 7440-22-4) and silver chloride (CAS RN 7783-90-6) in methyl propyl ketone (CAS RN 107-87-9),<br>— with a total solid content by weight of 55 % or more, but not more than 57 %, and<br>— with a specific gravity of 1,40 g/cm <sup>3</sup> or more, but not more than 1,60 g/cm <sup>3</sup> ,<br>used to imprint electrodes <sup>(1)</sup> | 0 %                     | 31.12.2017                         |
| ex 3215 90 00 | 10    | Ink formulation, for use in the manufacture of ink-jet cartridges <sup>(1)</sup>   | 0 %                     | 31.12.2018                         |
| ex 3215 90 00 | 20    | Heat sensitive ink fixed on a plastic film   | 0 %                     | 31.12.2018                         |
| ex 3215 90 00 | 30    | Disposable cartridge ink, containing by weight:<br>— 5 % or more, but not more than 10 % of amorphous silicon dioxide or<br>— 3,8 % or more of dye C.I. Solvent Black 7 in organic solvents<br>for use in the marking of integrated circuits <sup>(1)</sup>  | 0 %                     | 31.12.2018                         |
| ex 3215 90 00 | 40    | Dry ink powder with a base of hybrid resin (made from polystyrene acrylic resin and polyester resin) mixed with:<br>— wax;<br>— a vinyl-based polymer and<br>— a colouring agent<br>for use in the manufacture of toner bottles for photocopiers, fax machines, printers and multifunction devices <sup>(1)</sup>  | 0 %                     | 31.12.2015                         |
| 3301 12 10    |       | Essential oil of orange, not detepernated  | 0 %                     | 31.12.2018                         |
| ex 3402 11 90 | 10    | Sodium lauroyl methyl isethionate  | 0 %                     | 31.12.2015                         |
| ex 3402 13 00 | 10    | Vinyl copolymer surface active agent based on polypropylene glycol   | 0 %                     | 31.12.2018                         |
| ex 3402 13 00 | 20    | Surfactant containing 1,4-dimethyl-1,4-bis(2-methylpropyl)-2-butyne-1,4-diyl ether, polymerised with oxirane, methyl terminated  | 0 %                     | 31.12.2017                         |
| ex 3402 13 00 | 30    | Polyoxyethylated-12-hydroxystearic acid (CAS RN 70142-34-6)  | 0 %                     | 31.12.2018                         |
| ex 3402 90 10 | 20    | Mixture of docusate sodium (INN) and sodium benzoate   | 0 %                     | 31.12.2018                         |
| ex 3402 90 10 | 30    | Surface-active preparation, consisting of a mixture of sodium docusate and ethoxylated 2,4,7,9-tetramethyldec-5-yne-4,7-diol (CAS RN 577-11-7 and 9014-85-1)   | 0 %                     | 31.12.2015                         |
| ex 3402 90 10 | 50    | Surface-active preparation, consisting of a mixture of polysiloxane and poly(ethylene glycol)  | 0 %                     | 31.12.2015                         |
| ex 3402 90 10 | 60    | Surface-active preparation, containing 2-ethylhexyloxymethyl oxirane   | 0 %                     | 31.12.2014                         |
| ex 3402 90 10 | 70    | Surface-active preparation, containing ethoxylated 2,4,7,9-tetramethyl-5-decyne-4,7-diol (CAS RN 9014-85-1)  | 0 %                     | 31.12.2014                         |
| ex 3403 99 00 | 10    | Cutting-fluid preparation based on an aqueous solution of synthetic polypeptides   | 0 %                     | 31.12.2018                         |
| ex 3504 00 90 | 10    | Avidin (CAS RN 1405-69-2)  | 0 %                     | 31.12.2014                         |
| ex 3505 10 50 | 20    | O-(2-Hydroxyethyl)-derivative of hydrolysed maize starch (CAS RN 9005-27-0)  | 0 %                     | 31.12.2018                         |
| ex 3506 91 00 | 10    | Adhesive based on an aqueous dispersion of a mixture of dimerised rosin and a copolymer of ethylene and vinyl acetate (EVA)  | 0 %                     | 31.12.2018                         |

| CN code       | TARIC | Description  | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|------------------------------------|
| ex 3506 91 00 | 30    | Two component microencapsulated epoxy adhesive dispersed in a solvent  | 0 %                     | 31.12.2018                         |
| ex 3506 91 00 | 40    | Acrylic pressure sensitive adhesive with a thickness of 0,076 mm or more but not more than 0,127 mm, put up in rolls of a width of 45,7 cm or more but not more than 132 cm supplied on a release liner with an initial peel adhesion release value of not less than 15 N/25 mm (measured according to ASTM D3330)     | 0 %                     | 31.12.2014                         |
| ex 3601 00 00 | 10    | Pyrotechnical powder in the form of granulate of cylindrical shape, composed of strontium nitrate or copper nitrate in the solution of nitroguanidine, binder and additives, used as a component of airbag inflators <sup>(1)</sup>  | 0 %                     | 31.12.2016                         |
| ex 3701 30 00 | 10    | Relief printing plate, of a kind used for printing on newsprint, consisting of a metal substrate coated with a photopolymer layer of a thickness of 0,2 mm or more but not more than 0,8 mm, not covered with a release film, of a total thickness of not more than 1 mm   | 0 %                     | 31.12.2018                         |
| ex 3701 30 00 | 20    | Photosensitive plate consisting of a photopolymer layer on a polyester foil of a total thickness of more than 0,43 mm but not more than 3,18 mm  | 0 %                     | 31.12.2014                         |
| ex 3701 99 00 | 10    | Plate of quartz or of glass, covered with a film of chromium and coated with a photosensitive or electron-sensitive resin, of a kind used for goods of heading 8541 or 8542  | 0 %                     | 01.07.2014                         |
| ex 3705 90 90 | 10    | Photomasks for photographically transferring circuit diagram patterns onto semiconductor wafers  | 0 %                     | 31.12.2014                         |
| ex 3707 10 00 | 10    | Photosensitive emulsion for the sensitization of silicon discs <sup>(1)</sup>  | 0 %                     | 31.12.2018                         |
| ex 3707 10 00 | 15    | Sensitising emulsion consisting of:<br>— by weight not more than 12 % of diazooxonaphthalenesulphonic acid ester<br>— phenolic resins<br>in a solution containing at least 2-methoxy-1-methylethyl acetate or ethyl lactate or methyl 3-methoxypropionate or 2-heptanone   | 0 %                     | 31.12.2018                         |
| ex 3707 10 00 | 25    | Sensitising emulsion containing:<br>— phenolic or acrylic resins<br>— a maximum 2 % by weight of light sensitive acid precursor,<br>in a solution containing 2-methoxy-1-methylethyl acetate or ethyl lactate  | 0 %                     | 31.12.2018                         |
| ex 3707 10 00 | 30    | Preparation based on photosensitive acrylic containing polymer, containing colour pigments, 2-methoxy-1-methylethylacetate and cyclohexanone and whether or not containing ethyl-3-ethoxypropionate  | 0 %                     | 31.12.2018                         |
| ex 3707 10 00 | 35    | Sensitising emulsion or preparation containing one or more of:   | 0 %                     | 31.12.2016                         |
| ex 3707 90 90 | 70    | — acrylate polymers,<br>— methacrylate polymers,<br>— derivatives of styrene polymers,<br>containing by weight not more than 7 % of photosensitive acid precursors, dissolved in an organic solvent containing at least 2-methoxy-1-methylethyl acetate  |                         |                                    |
| ex 3707 10 00 | 40    | Sensitising emulsion, containing:<br>— not more than 10 % by weight of naphthoquinonediazide esters,<br>— 2 % or more but not more than 20 % by weight of copolymers of hydroxystyrene<br>— not more than 7 % by weight of epoxy-containing derivatives<br>dissolved in 1-ethoxy-2-propyl acetate and/or ethyl lactate | 0 %                     | 31.12.2016                         |

| CN code       | TARIC | Description  | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|------------------------------------|
| ex 3707 10 00 | 45    | Photosensitive emulsion consisting of cyclized polyisoprene containing:<br>— 55 % or more but not more than 75 % by weight of xylene and<br>— 12 % or more but not more than 18 % by weight of ethylbenzene  | 0 %                     | 31.12.2014                         |
| ex 3707 10 00 | 50    | Photosensitive emulsion containing by weight:<br>— 20 % or more but not more than 45 % of copolymers of acrylates and/or methacrylates and hydroxystyrene derivatives,<br>— 25 % or more but not more than 50 % of organic solvent containing at least ethyl lactate and/or propylene glycolmethylether acetate,<br>— 5 % or more but not more than 30 % of acrylates,<br>— not more than 12 % of a photoinitiator | 0 %                     | 31.12.2014                         |
| ex 3707 10 00 | 55    | Dielectric coating, buffering mechanical stress, consisting of a radically photopatternable polyamide-precursor with unsaturated carbon in the side-chains which is convertible into a polyimide, in form of a solution from N-methyl-2-pyrrolidone or N-ethyl-2-pyrrolidone with a polymer content by weight 10 % or more   | 0 %                     | 31.12.2018                         |
| ex 3707 90 20 | 10    | Dry ink powder or toner blend, consisting of a copolymer of styrene and butyl acrylate and either magnetite or carbon black, for use as a developer in the manufacture of cartridges for facsimile machines, computer printers or copiers <sup>(1)</sup>   | 0 %                     | 31.12.2018                         |
| ex 3707 90 20 | 20    | Dry ink powder or toner blend, based on a polyol resin, for use as a developer in the manufacture of cartridges for facsimile machines, computer printers or copiers <sup>(1)</sup>  | 0 %                     | 31.12.2018                         |
| ex 3707 90 20 | 40    | Dry ink powder or toner blend, based on a polyester resin, manufactured by a polymerisation process, for use as a developer in the manufacture of cartridges for facsimile machines, computer printers or copiers <sup>(1)</sup>   | 0 %                     | 31.12.2018                         |
| ex 3707 90 20 | 50    | Dry ink powder or toner blend, consisting of:<br>— styrene acrylate/butadiene copolymer<br>— either carbon black or an organic pigment<br>— whether or not containing polyolefin or amorphous silica<br>for use as a developer in the manufacturing of ink/toner filled bottles or cartridges for facsimile machines, computer printers and copiers <sup>(1)</sup>   | 0 %                     | 31.12.2017                         |
| ex 3707 90 90 | 10    | Anti-reflection coating, consisting of a modified methacrylic polymer, containing by weight not more than 10 % of polymer, in a solution in two or three of the following substances:<br>— 2-methoxy-1-methylethyl acetate (CAS RN 108-65-6)<br>— 1-methoxypropan-2-ol (CAS RN 107-98-2)<br>— ethyl lactate (CAS RN 97-64-3)   | 0 %                     | 31.12.2018                         |
| ex 3707 90 90 | 40    | Anti-reflection coating, in the form of an aqueous solution, containing by weight not more than:<br>— 2 % of halogen-free alkyl sulphonic acid, and<br>— 5 % of a fluorinated polymer  | 0 %                     | 31.12.2014                         |
| ex 3707 90 90 | 80    | Anti-reflection coating, consisting of either a siloxane polymer or an organic polymer having a phenolic hydroxy group modified with a chromophore group, in the form of a solution of an organic solvent containing either 1-ethoxy-2-propanol or 2-methoxy-1-methylethyl acetate containing by weight not more than 10 % of polymer  | 0 %                     | 31.12.2015                         |
| ex 3707 90 90 | 85    | Rolls, containing:<br>— a dry layer of a photosensitive acrylic resin,<br>— on one side a poly(ethylene terephthalate) protecting foil and<br>— on the other side a polyethylene protecting foil   | 0 %                     | 31.12.2014                         |

| CN code       | TARIC | Description  | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|------------------------------------|
| ex 3801 90 00 | 10    | Expandable graphite (CAS RN 90387-90-9 and CAS RN 12777-87-6)  | 0 %                     | 31.12.2016                         |
| ex 3802 90 00 | 11    | Soda flux calcinated diatomaceous earth, acid washed, for use as a filter aid in the manufacture of pharmaceutical and/or biochemical products (1)   | 0 %                     | 31.12.2017                         |
| 3805 90 10    |       | Pine oil   | 1,7 %                   | 31.12.2018                         |
| ex 3806 10 00 | 20    | Rosin modified phenolic resin,   | 0 %                     | 31.12.2016                         |
| ex 3909 40 00 | 50    | — containing 60 % or more but not more than 75 % by weight of rosin,<br>— with an acid value of not more than 25,<br>of a kind used in offset printing   |                         |                                    |
| ex 3808 91 90 | 10    | Indoxacarb (ISO) and its (R) isomer, fixed on a support of silicon dioxide   | 0 %                     | 31.12.2018                         |
| ex 3808 91 90 | 30    | Preparation containing endospores or spores and protein crystals derived from either:<br>— <i>Bacillus thuringiensis</i> Berliner subsp. <i>aizawai</i> and <i>kurstaki</i> or,<br>— <i>Bacillus thuringiensis</i> subsp. <i>kurstaki</i> or,<br>— <i>Bacillus thuringiensis</i> subsp. <i>israelensis</i> or,<br>— <i>Bacillus thuringiensis</i> subsp. <i>aizawai</i> or,<br>— <i>Bacillus thuringiensis</i> subsp. <i>tenebrionis</i> | 0 %                     | 31.12.2014                         |
| ex 3808 91 90 | 40    | Spinosad (ISO)   | 0 %                     | 31.12.2018                         |
| ex 3808 91 90 | 60    | Spinetoram (ISO) (CAS RN 935545-74-7), preparation of two spinosyn components (3'-ethoxy-5,6-dihydro spinosyn J) and (3'-ethoxy- spinosyn L)   | 0 %                     | 31.12.2017                         |
| ex 3808 92 90 | 10    | Fungicide in the form of a powder, containing by weight 65 % or more but not more than 75 % of hymexazole (ISO), not put up for retail sale  | 0 %                     | 31.12.2018                         |
| ex 3808 92 90 | 30    | Preparation consisting of a suspension of pyriithione zinc (INN) in water, containing by weight:<br>— 24 % or more but not more than 26 % of pyriithione zinc (INN), or<br>— 39 % or more but not more than 41 % of pyriithione zinc (INN)   | 0 %                     | 31.12.2018                         |
| ex 3808 92 90 | 50    | Preparations based on copper pyriithione (CAS RN 14915-37-8)   | 0 %                     | 31.12.2014                         |
| ex 3808 93 15 | 10    | Preparation based on a concentrate containing by weight 45 % or more but not more than 55 % of the active herbicidal ingredient Penoxsulam as an aqueous suspension  | 0 %                     | 31.12.2017                         |
| ex 3808 93 23 | 10    | Herbicide containing flazasulfuron (ISO) as an active ingredient   | 0 %                     | 31.12.2014                         |
| ex 3808 93 27 | 40    | Preparation, consisting of a suspension of tepraloxym (ISO), containing by weight:<br>— 30 % or more of tepraloxym (ISO) and<br>— not more than 70 % of a petroleum fraction consisting of aromatic hydrocarbons   | 0 %                     | 31.12.2016                         |
| ex 3808 93 90 | 10    | Preparation, in the form of granules, containing by weight:<br>— 38,8 % or more but not more than 41,2 % of Gibberellin A3, or<br>— 9,5 % or more but not more than 10,5 % of Gibberellin A4 and A7  | 0 %                     | 31.12.2014                         |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
| ex 3808 93 90 | 20    | Preparation consisting of benzyl(purin-6-yl)amine in a glycol solution, containing by weight:<br>— 1,88 % or more but not more than 2,00 % of benzyl(purin-6-yl)amine of a kind used in plant growth regulators   | 0 %                     | 31.12.2015                         |
| ex 3808 93 90 | 30    | Aqueous solution containing by weight:<br>— 1,8 % of sodium para-nitrophenolate,<br>— 1,2 % of sodium ortho-nitrophenolate,<br>— 0,6 % of sodium 5-nitroguaiacolate<br>for use in the manufacture of a plant growth regulator <sup>(1)</sup>  | 0 %                     | 31.12.2015                         |
| ex 3808 93 90 | 40    | Mixed white powder containing by weight:<br>— 3 % or more but not more than 3,6 % of 1-methylcyclopropene with a purity more than 96 % and<br>— containing less than 0,05 % of each impurity of 1-chloro-2-methylpropene and 3-chloro-2-methylpropene<br>for use in the manufacture of a growth regulator of post-harvest fruits, vegetables and ornamentals with a specific generator <sup>(1)</sup> | 0 %                     | 31.12.2015                         |
| ex 3808 93 90 | 50    | Preparation in the form of powder, containing by weight:<br>— 55 % or more of Gibberellin A4,<br>— 1 % or more but not more than 35 % of Gibberellin A7,<br>— 90 % or more of Gibberellin A4 and Gibberellin A7 combined<br>— not more than 10 % of a combination of water and other naturally occurring Gibberellins<br>of a kind used in plant growth regulators                                    | 0 %                     | 31.12.2015                         |
| ex 3808 99 90 | 10    | Oxamyl (ISO) (CAS RN 23135-22-0) in a solution of cyclohexanone and water   | 0 %                     | 31.12.2015                         |
| ex 3808 99 90 | 20    | Abamectin (ISO) (CAS RN 71751-41-2)   | 0 %                     | 31.12.2018                         |
| ex 3809 91 00 | 10    | Mixture of 5-ethyl-2-methyl-2-oxo-1,3,2λ <sup>5</sup> -dioxaphosporan-5-ylmethyl methyl methylphosphonate and bis(5-ethyl-2-methyl-2-oxo-1,3,2λ <sup>5</sup> -dioxaphosporan-5-ylmethyl) methylphosphonate  | 0 %                     | 31.12.2018                         |
| ex 3809 92 00 | 20    | Defoamer, consisting of a mixture of oxydipropanol and 2,5,8,11-tetramethyldodec-6-yn-5,8-diol  | 0 %                     | 31.12.2014                         |
| ex 3810 10 00 | 10    | Soldering or welding paste, consisting of a mixture of metals and resin containing by weight:<br>— 70 % or more, but not more than 90 % of tin<br>— not more than 10 % of one or more metals of silver, copper, bismuth, zinc, or indium<br>for use in the electro technical industry <sup>(1)</sup>  | 0 %                     | 31.12.2018                         |
| ex 3811 19 00 | 10    | Solution of more than 61 % but not more than 63 % by weight of methylcyclopentadienyl manganese tricarbonyl in an aromatic hydrocarbon solvent, containing by weight not more than:<br>— 4,9 % of 1,2,4-trimethyl-benzene,<br>— 4,9 % of naphthalene, and<br>— 0,5 % of 1,3,5-trimethyl-benzene   | 0 %                     | 31.12.2014                         |
| ex 3811 21 00 | 10    | Salts of dinonylnaphthalenesulphonic acid, in the form of a solution in mineral oils  | 0 %                     | 31.12.2018                         |
| ex 3811 21 00 | 20    | Additives for lubricating oils, based on complex organic molybdenum compounds, in the form of a solution in mineral oil   | 0 %                     | 31.12.2018                         |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
| ex 3811 21 00 | 30    | Additives for lubricating oils, containing mineral oils, consisting of calcium salts of reaction products of polyisobutylene substituted phenol with salicylic acid and formaldehyde, used as a concentrated additive for the manufacture of engine oils through a blending process   | 0 %                     | 31.12.2017                         |
| ex 3811 21 00 | 40    | Additives for lubricating oils, containing mineral oils, based on a mixture of dodecylphenol sulphide calcium salts (CAS RN 68784-26-9), used as a concentrated additive for the manufacture of engine oils through a blending process  | 0 %                     | 31.12.2017                         |
| ex 3811 21 00 | 50    | Additives for lubricating oils,<br>— based on calcium C16-24 alkylbenzenesulphonates (CAS RN 70024-69-0),<br>— containing mineral oils,<br>used as a concentrated additive for the manufacture of engine oils through a blending process  | 0 %                     | 31.12.2017                         |
| ex 3811 21 00 | 60    | Additives for lubricating oils, containing mineral oils,<br>— based on calcium polypropylenyl substituted benzenesulphonate (CAS RN 75975-85-8) with a content by weight of 25 % or more but not more than 35 %,<br>— with a total base number (TBN) of 280 or more but not more than 320,<br>used as a concentrated additive for the manufacture of engine oils through a blending process   | 0 %                     | 31.12.2017                         |
| ex 3811 21 00 | 70    | Additives for lubricating oils,<br>— containing polyisobutylene succinimide derived from reaction products of polyethylenepolyamines with polyisobutenyl succinic anhydride (CAS RN 84605-20-9),<br>— containing mineral oils,<br>— with a chlorine content by weight of 0,05 % or more but not more than 0,25 %,<br>— with a total base number (TBN) of more than 20,<br>used as a concentrated additive for the manufacture of engine oils through a blending process | 0 %                     | 31.12.2017                         |
| ex 3811 29 00 | 20    | Additives for lubricating oils, consisting of reaction products of bis(2-methylpentan-2-yl)dithiophosphoric acid with propylene oxide, phosphorus oxide, and amines with C12-14 alkyl chains, used as a concentrated additive for the manufacture of engine oils through a blending process   | 0 %                     | 31.12.2017                         |
| ex 3811 29 00 | 30    | Additives for lubricating oils, consisting of reaction products of butyl-cyclohex-3-enecarboxylate, sulphur and triphenyl phosphite (CAS RN 93925-37-2), used as a concentrated additive for the manufacture of engine oils through a blending process  | 0 %                     | 31.12.2017                         |
| ex 3811 29 00 | 40    | Additives for lubricating oils, consisting of reaction products of 2-methyl-prop-1-ene with sulphur monochloride and sodium sulphide (CAS RN 68511-50-2), with a chlorine content by weight of 0,05 % or more but not more than 0,5 %, used as a concentrated additive for the manufacture of engine oils through a blending process  | 0 %                     | 31.12.2017                         |
| ex 3811 29 00 | 50    | Additives for lubricating oils, consisting of a mixture of N,N-dialkyl -2-hydroxyacetamides with alkyl chain lengths between 12 and 18 carbon atoms (CAS RN 866259-61-2), used as a concentrated additive for the manufacture of engine oils through a blending process   | 0 %                     | 31.12.2017                         |
| ex 3811 90 00 | 10    | Dinonylnaphthylsulphonic acid salt, in a mineral oil solution   | 0 %                     | 31.12.2018                         |
| ex 3811 90 00 | 40    | Solution of a quaternary ammonium salt based on polyisobutenyl succinimide, containing by weight 20 % or more but not more than 29,9 % 2-ethylhexanol   | 0 %                     | 31.12.2017                         |

| CN code       | TARIC | Description  | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|------------------------------------|
| ex 3812 10 00 | 10    | Rubber accelerator based on diphenyl guanidine granules (CAS RN 102-06-7)  | 0 %                     | 31.12.2016                         |
| ex 3812 20 90 | 10    | Plasticizer, containing:<br>— bis(2-ethylhexyl)-1,4-benzene dicarboxylate (CAS RN 6422-86-2)<br>— more than 10 % but not more than 60 % by weight of dibutylterephthalate (CAS RN 1962-75-0)   | 0 %                     | 31.12.2018                         |
| ex 3812 30 80 | 20    | Mixture containing predominantly bis(2,2,6,6-tetramethyl-1-octyloxy-4-piperidyl) sebacate  | 0 %                     | 31.12.2018                         |
| ex 3812 30 80 | 25    | UV photo stabiliser containing:<br>— $\alpha$ -[3-[3-(2H-Benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]- $\omega$ -hydroxypoly(oxy-1,2-ethanediyl) (CAS RN 104810-48-2);<br>— $\alpha$ -[3-[3-(2H-Benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]- $\omega$ -[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]poly (oxy-1,2-ethanediyl) (CAS RN 104810-47-1);<br>— polyethylene glycol of a weight average molecular weight (Mw) of 300 (CAS RN 25322-68-3)<br>— bis (1,2,2,6,6-pentamethyl-4-piperidyl)sebacate (CAS RN 41556-26-7), and<br>— methyl-1,2,2,6,6-pentamethyl-4- piperidyl sebacate (CAS RN 82919-37-7) | 0 %                     | 31.12.2018                         |
| ex 3812 30 80 | 30    | Compound stabilisers containing by weight 15 % or more but not more than 40 % of sodium perchlorate and not more than 70 % of 2-(2-methoxyethoxy)ethanol   | 0 %                     | 31.12.2014                         |
| ex 3812 30 80 | 35    | Mixture containing by weight:<br>— 25 % or more but not more than 50 % of a mixture of C15-18 tetramethylpiperidiny esters (CAS RN 86403-32-9)<br>— not more than 20 % of other organic compounds<br>— on a carrier of polypropylene (CAS RN 9003-07-0)  | 0 %                     | 31.12.2018                         |
| ex 3812 30 80 | 40    | Mixture of:<br>— 80 % ( $\pm$ 10 %) by weight of 2-ethylhexyl 10-ethyl-4,4-dimethyl-7-oxo-8-oxa-3,5-dithia-4-stannatetradecanoate, and<br>— 20 % ( $\pm$ 10 %) by weight of 2-ethylhexyl 10-ethyl-4-[[2-[(2-ethylhexyl)oxy]-2-oxoethyl]thio]-4-methyl-7-oxo-8-oxa-3,5-dithia-4-stannatetradecanoate  | 0 %                     | 31.12.2018                         |
| ex 3812 30 80 | 55    | UV-stabilizer, containing:<br>— 2-(4,6-bis(2,4-dimethylphenyl)-1,3,5-triazin-2-yl)-5-(octyloxy)-phenol (CAS RN 2725-22-6) and<br>— either N,N'-bis(1,2,2,6,6-pentamethyl-4-piperidiny)-1,6-hexanediamine, polymer with 2,4- dichloro-6-(4-morpholinyl)-1,3,5-triazine (CAS RN 193098-40-7) or<br>— N,N'-bis(2,2,6,6-tetramethyl-4-piperidiny)-1,6-hexanediamine, polymer with 2,4- dichloro-6-(4-morpholinyl)-1,3,5-triazine (CAS RN 82451-48-7)   | 0 %                     | 31.12.2016                         |
| ex 3812 30 80 | 60    | Light stabiliser, consisting of branched and linear alkyl esters of 3-(2H-Benzotriazolyl)-5-(1,1-di-methylethyl)-4-hydroxy-benzenepropanoic acid (CAS RN 127519-17-9)  | 0 %                     | 31.12.2016                         |
| ex 3812 30 80 | 65    | Stabiliser for plastic material containing:<br>— 2-ethylhexyl 10-ethyl-4,4-dimethyl-7-oxo-8-oxa-3,5-dithia-4-stannatetradecanoate (CAS RN 57583-35-4),<br>— 2-ethylhexyl 10-ethyl-4-[[2-[(2-ethylhexyl)oxy]-2-oxoethyl]thio]-4-methyl-7-oxo-8-oxa-3,5-dithia-4-stannatetradecanoate (CAS RN 57583-34-3), and<br>— 2-ethylhexyl mercaptoacetate (CAS RN 7659-86-1)  | 0 %                     | 31.12.2016                         |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
| ex 3812 30 80 | 70    | Light stabiliser containing:<br>— branched and linear alkyl esters of 3-(2H-benzotriazolyl)-5-(1,1-dimethylethyl)-4-hydroxybenzenepropanoic acid (CAS RN 127519-17-9), and<br>— 1-methoxy-2-propyl acetate (CAS RN 108-65-6)  | 0 %                     | 31.12.2016                         |
| ex 3812 30 80 | 75    | N,N'-Bis(1,2,2,6,6-pentamethyl-4-piperidiny)-1,6-hexanediamine, polymer with 2,4-dichloro-6-(4-morpholinyl)-1,3,5-triazine (CAS RN 193098-40-7)   | 0 %                     | 31.12.2017                         |
| ex 3812 30 80 | 80    | UV-stabilizer, consisting of:<br>— a hindered amine: N,N'-bis(1,2,2,6,6-pentamethyl-4-piperidiny)-1,6-hexanediamine, polymer with 2,4-dichloro-6-(4-morpholinyl)-1,3,5-triazine (CAS RN 193098-40-7) and<br>— either an o-hydroxyphenyl triazine UV light absorber or<br>— a chemically modified phenolic compound      | 0 %                     | 31.12.2017                         |
| ex 3814 00 90 | 20    | Mixture containing by weight:<br>— 69 % or more but not more than 71 % of 1-methoxypropan-2-ol,<br>— 29 % or more but not more than 31 % of 2-methoxy-1-methylethyl acetate   | 0 %                     | 31.12.2018                         |
| ex 3814 00 90 | 40    | Azeotrope mixtures containing isomers of nonafluorobutyl methyl ether and/or nonafluorobutyl ethyl ether  | 0 %                     | 31.12.2018                         |
| ex 3815 12 00 | 10    | Catalyst, in the form of granules or rings of a diameter of 3 mm or more but not more than 10 mm, consisting of silver on an aluminium oxide support and containing by weight 8 % or more but not more than 40 % of silver  | 0 %                     | 31.12.2018                         |
| ex 3815 19 90 | 10    | Catalysts consisting of chromium trioxide, dichromium trioxide or organometallic compounds of chromium, fixed on a silicon dioxide support with a pore volume of 2 cm <sup>3</sup> /g or more (as determined by the nitrogen absorption method)   | 0 %                     | 31.12.2016                         |
| ex 3815 19 90 | 15    | Catalyst, in the form of a powder, consisting of a mixture of metal oxides fixed on a support of silicon dioxide, containing by weight 20 % or more but not more than 40 % of molybdenum, bismuth and iron evaluated together, for use in the manufacture of acrylonitrile <sup>(1)</sup>                               | 0 %                     | 31.12.2018                         |
| ex 3815 19 90 | 25    | Catalyst in the form of spheres of a diameter of 4,2 mm or more but not more than 9 mm, consisting of a mixture of metal oxides containing predominantly oxides of molybdenum, nickel, cobalt and iron, on a support of aluminium oxide, for use in the manufacture of acrylic aldehyde <sup>(1)</sup>                  | 0 %                     | 31.12.2018                         |
| ex 3815 19 90 | 30    | Catalyst containing titanium tetrachloride supported on magnesium dichloride, for use in the manufacture of polypropylene <sup>(1)</sup>  | 0 %                     | 31.12.2018                         |
| ex 3815 19 90 | 40    | Catalyst, in the form of spheres of a diameter of 4,2 mm or more but not more than 9 mm, consisting of a mixture of metals oxides containing predominantly oxides of molybdenum, vanadium and copper, on a support of silicon dioxide and/or aluminium oxide, for use in the manufacture of acrylic acid <sup>(1)</sup> | 0 %                     | 31.12.2018                         |
| ex 3815 19 90 | 60    | Catalyst consisting of dichromium trioxide, fixed on a support of aluminium oxide   | 0 %                     | 31.12.2014                         |
| ex 3815 19 90 | 65    | Catalyst consisting of phosphoric acid chemically bonded to a support of silicon dioxide  | 0 %                     | 31.12.2018                         |
| ex 3815 19 90 | 70    | Catalyst consisting of organo-metallic compounds of aluminium and zirconium, fixed on a support of silicon dioxide  | 0 %                     | 31.12.2018                         |
| ex 3815 19 90 | 75    | Catalyst consisting of organo-metallic compounds of aluminium and chromium, fixed on a support of silicon dioxide   | 0 %                     | 31.12.2018                         |

| CN code       | TARIC | Description  | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|------------------------------------|
| ex 3815 19 90 | 80    | Catalyst consisting of organo-metallic compounds of magnesium and titanium, fixed on a support of silicon dioxide, in the form of a suspension in mineral oil  | 0 %                     | 31.12.2018                         |
| ex 3815 19 90 | 85    | Catalyst consisting of organo-metallic compounds of aluminium, magnesium and titanium, fixed on a support of silicon dioxide, in the form of powder  | 0 %                     | 31.12.2018                         |
| ex 3815 19 90 | 86    | Catalyst containing titanium tetrachloride supported on magnesium dichloride, for use in the manufacture of polyolefins <sup>(1)</sup>   | 0 %                     | 31.12.2018                         |
| ex 3815 19 90 | 87    | Cathode, in rolls, for air zinc button cell batteries (hearing aid batteries) <sup>(1)</sup>   | 0 %                     | 31.12.2016                         |
| ex 8506 90 00 | 10    |  |                         |                                    |
| ex 3815 90 90 | 16    | Initiator based on dimethylaminopropyl urea  | 0 %                     | 31.12.2017                         |
| ex 3815 90 90 | 18    | Oxidation catalyst with an active ingredient of di[manganese (1+)], 1,2-bis(octahydro-4,7-dimethyl-1H-1,4,7-triazonine-1-yl-kN <sup>1</sup> , kN <sup>4</sup> , kN <sup>7</sup> )ethane-di- $\mu$ -oxo- $\mu$ -(ethanoato-kO, kO <sup>'</sup> )-, di[chloride(1-)], used to accelerate chemical oxidation or bleaching (CAS RN 1217890-37-3) | 0 %                     | 31.12.2017                         |
| ex 3815 90 90 | 20    | Catalyst, in powder form, consisting of a mixture of titanium trichloride and aluminium chloride, containing by weight:<br>— 20 % or more but not more than 30 % of titanium and<br>— 55 % or more but not more than 72 % of chlorine  | 0 %                     | 31.12.2018                         |
| ex 3815 90 90 | 27    | Catalyst, in the form of hollow cylinders with a length of 5 mm or more but not more than 9 mm, consisting of a mixture of metal oxides containing predominantly oxides of molybdenum, bismuth, iron and nickel, containing also a charge of silicon dioxide, for use in the manufacture of acrylic acid <sup>(1)</sup>                      | 0 %                     | 31.12.2018                         |
| ex 3815 90 90 | 30    | Catalyst, consisting of a suspension in mineral oil of:<br>— tetrahydrofuran complexes of magnesium chloride and titanium(III) chloride; and<br>— silicon dioxide<br>— containing 6,6 % ( $\pm$ 0,6 %) by weight of magnesium, and<br>— containing 2,3 % ( $\pm$ 0,2 %) by weight of titanium  | 0 %                     | 31.12.2015                         |
| ex 3815 90 90 | 33    | Catalyst, consisting of a mixture of different alkylnaphthalene sulphonic acids, with aliphatic hydrocarbon chains, containing 12 – 56 carbon atoms  | 0 %                     | 31.12.2018                         |
| ex 3815 90 90 | 50    | Catalyst containing titanium trichloride, in the form of a suspension in hexane or heptane containing by weight, in the hexane- or heptane-free material, 9 % or more but not more than 30 % of titanium   | 0 %                     | 31.12.2018                         |
| ex 3815 90 90 | 70    | Catalyst, consisting of a mixture of (2-hydroxypropyl)trimethylammonium formate and dipropylene glycols  | 0 %                     | 31.12.2014                         |
| ex 3815 90 90 | 71    | Catalyst, containing N-(2-hydroxypropylammonium)diazabicyclo (2,2,2) octane-2-ethyl hexanoate, dissolved in ethane-1,2-diol  | 0 %                     | 31.12.2016                         |
| ex 3815 90 90 | 80    | Catalyst consisting predominantly of dinonylnaphthalenedisulphonic acid in the form of a solution in isobutanol  | 0 %                     | 31.12.2014                         |
| ex 3815 90 90 | 81    | Catalyst, containing by weight 69 % or more but not more than 79 % of (2-hydroxy-1-methylethyl)trimethylammonium 2-ethylhexanoate  | 0 %                     | 31.12.2018                         |
| ex 3815 90 90 | 85    | Catalyst based on aluminosilicate (zeolite), for the alkylation of aromatic hydrocarbons, for the transalkylation of alkylaromatic hydrocarbons or for the oligomerization of olefins <sup>(1)</sup>   | 0 %                     | 31.12.2017                         |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
| ex 3815 90 90 | 86    | Catalyst, in the form of rodlets, consisting of an aluminosilicate (zeolite), containing by weight 2 % or more but not more than 3 % of rare-earth metal oxides and less than 1 % of disodium oxide   | 0 %                     | 31.12.2018                         |
| ex 3815 90 90 | 88    | Catalyst, consisting of titanium tetrachloride and magnesium chloride, containing by weight on an oil- and hexane-free basis:<br>— 4 % or more but not more than 10 % of titanium and<br>— 10 % or more but not more than 20 % magnesium  | 0 %                     | 31.12.2018                         |
| ex 3815 90 90 | 89    | Rhodococcus rhodocrous J1 bacteria, containing enzymes, suspended in a polyacrylamide gel or in water, for use as a catalyst in the production of acrylamide by the hydration of acrylonitrile (1)  | 0 %                     | 31.12.2016                         |
| ex 3817 00 50 | 10    | Mixture of alkylbenzenes (C14-26) containing by weight:<br>— 35 % or more but not more than 60 % of eicosylbenzene,<br>— 25 % or more but not more than 50 % of docosylbenzene,<br>— 5 % or more but not more than 25 % of tetracosylbenzene  | 0 %                     | 31.12.2018                         |
| ex 3817 00 80 | 10    | Mixture of alkylnaphthalenes, containing by weight:<br>— 88 % or more but not more than 98 % of hexadecyl-naphthalene<br>— 2 % or more but not more than 12 % of dihexadecyl-naphthalene  | 0 %                     | 31.12.2018                         |
| ex 3817 00 80 | 20    | Mixture of branched alkyl benzenes mainly containing dodecyl benzenes   | 0 %                     | 31.12.2018                         |
| ex 3817 00 80 | 30    | Mixed alkylnaphthalenes, modified with aliphatic chains, of a chain-length varying from 12 to 56 carbon atoms   | 0 %                     | 31.12.2016                         |
| ex 3819 00 00 | 20    | Fire resistant hydraulic fluid based on phosphate ester   | 0 %                     | 31.12.2018                         |
| ex 3823 19 30 | 20    | Palm fatty acid distillate, whether or not hydrogenated, with free fatty acid content 80 % or more for use in the manufacture of:<br>— industrial monocarboxylic fatty acids of subheading 3823,<br>— stearic acid of subheading 3823,<br>— stearic acid of subheading 2915,<br>— palmitic acid of subheading 2915, or<br>— animal feed preparations of subheading 2309 (1) | 0 %                     | 31.12.2018                         |
| ex 3823 19 90 | 20    | Palm acid oils from refining for use in the manufacture of:<br>— industrial monocarboxylic fatty acids of subheading 3823<br>— stearic acid of subheading 3823<br>— stearic acid of subheading 2915<br>— palmitic acid of subheading 2915<br>— animal feed preparations of subheading 2309 (1)  | 0 %                     | 31.12.2018                         |
| ex 3824 90 15 | 10    | Acid aluminosilicate (artificial zeolite of the Y type) in the sodium form, containing by weight not more than 11 % of sodium evaluated as sodium oxide, in the form of rodlets   | 0 %                     | 31.12.2018                         |
| ex 3824 90 97 | 05    | Mixture of methylmethacrylate monomer and butylacrylate monomer in a solution of xylene and butylacetate, containing by weight more than 54 % but not more than 56 % of solvents  | 0 %                     | 31.12.2014                         |
| ex 3824 90 97 | 06    | Paraffin with a level of chlorination of 70 % or more   | 0 %                     | 31.12.2014                         |
| ex 3824 90 97 | 07    | Film containing oxides of barium or calcium combined with either oxides of titanium or zirconium, in an acrylic binding material  | 0 %                     | 31.12.2014                         |

| CN code       | TARIC | Description  | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|------------------------------------|
| ex 3824 90 97 | 08    | Mixture of divinylbenzene-isomers and ethylvinylbenzene-isomers, containing by weight 56 % or more but not more than 85 % of divinylbenzene (CAS RN 1321-74-0)   | 0 %                     | 31.12.2014                         |
| ex 3824 90 97 | 09    | Anti-corrosion preparations consisting of salts of dinonylnaphthalenesulphonic acid, either:<br>— on a support of mineral wax, whether or not modified chemically, or<br>— in the form of a solution in an organic solvent   | 0 %                     | 31.12.2018                         |
| ex 3824 90 97 | 10    | Calcined bauxite (refractory grade)  | 0 %                     | 31.12.2018                         |
| ex 3824 90 97 | 11    | Mixture of phytosterols, not in powder form, containing by weight:<br>— 40 % or more but not more than 58 % of beta-sitosterols<br>— 20 % or more but not more than 28 % of campesterols<br>— 14 % or more but not more than 23 % of stigmaterols<br>— 0 % or more but not more than 15 % of other sterols                               | 0 %                     | 31.12.2014                         |
| ex 3824 90 97 | 12    | Oligomer of tetrafluoroethylene, having one iodoethyl end-group  | 0 %                     | 31.12.2018                         |
| ex 3824 90 97 | 13    | Preparations containing not less than 92 % but not more than 96,5 % by weight of 1,3:2,4-bis-O-(4-methylbenzylidene)-D-glucitol and also containing carboxylic acid derivatives and an alkyl sulphate  | 0 %                     | 31.12.2016                         |
| ex 3824 90 97 | 14    | Calcium phosphonate phenate, dissolved in mineral oil  | 0 %                     | 31.12.2016                         |
| ex 3824 90 97 | 15    | Structured silica alumina phosphate  | 0 %                     | 31.12.2014                         |
| ex 3824 90 97 | 16    | Mixture of bis{4-(3-(3-phenoxy-carbonylamino)tolyl)ureido}phenylsulphone, diphenyltoluene-2,4-dicarbamate and 1-[4-(4-aminobenzenesulphonyl)-phenyl]-3-(3-phenoxy-carbonylamino-tolyl)-urea  | 0 %                     | 31.12.2018                         |
| ex 3824 90 97 | 17    | Mixture of acetates of 3-butylene-1,2-diol with a content by weight of 65 % or more but not more than 90 %   | 0 %                     | 31.12.2018                         |
| ex 3824 90 97 | 18    | Poly(tetramethylene glycol) bis[(9-oxo-9H-thioxanthen-1-yloxy)acetate] with an average polymer chain length of less than 5 monomer units (CAS RN 515136-48-8)  | 0 %                     | 31.12.2014                         |
| ex 3824 90 97 | 20    | Preparation consisting by weight of 83 % or more of 3a,4,7,7a-tetrahydro-4,7-methanoindene (dicyclopentadiene), a synthetic rubber, whether or not containing by weight 7 % or more of tricyclopentadiene, and:<br>— either an aluminium-alkyl compound,<br>— or an organic complex of tungsten<br>— or an organic complex of molybdenum | 0 %                     | 31.12.2018                         |
| ex 3824 90 97 | 21    | Mixture of 2-propenoic acid, (1-methylethylidene)bis(4,1-phenyleneoxy-2,1-ethanedioxy-2,1-ethanedioyl)ester with 2-propenoic acid, (2,4,6-trioxo-1,3,5-triazine-1,3,5-(2H,4H,6H)-triyloxy)tri-2,1-ethanedioyl ester and 1-hydroxy-cyclohexyl-phenyl ketone in the solution of methyl ethyl ketone and toluene                            | 0 %                     | 31.12.2014                         |
| ex 3824 90 97 | 22    | Preparations containing not less than 47 % by weight of 1,3:2,4-bis-O-benzylidene-D-glucitol   | 0 %                     | 31.12.2016                         |
| ex 3824 90 97 | 23    | Mixture of urethane acrylates, tripropylene glycol diacrylate, ethoxylated bisphenol A acrylate and poly(ethyleneglycol) 400 diacrylate  | 0 %                     | 31.12.2014                         |
| ex 3824 90 97 | 24    | Solution of (chloromethyl)bis(4-fluorophenyl)methylsilane of a nominal concentration of 65 % in toluene  | 0 %                     | 31.12.2015                         |

| CN code       | TARIC | Description  | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|------------------------------------|
| ex 3824 90 97 | 26    | Aqueous dispersion, containing by weight:<br>— 76 % ( $\pm$ 0,5 %) of silicon carbide (CAS RN 409-21-2)<br>— 4,6 % ( $\pm$ 0,05 %) of aluminium oxide (CAS RN 1344-28-1) and<br>— 2,4 % ( $\pm$ 0,05 %) of yttrium oxide (CAS RN 1314-36-9)                                | 0 %                     | 31.12.2016                         |
| ex 3824 90 97 | 27    | Preparation, consisting of a mixture of 2,4,7,9-tetramethyldec-5-yne-4,7-diol and propan-2-ol  | 0 %                     | 31.12.2015                         |
| ex 3824 90 97 | 28    | Preparation containing by weight:<br>— 85 % or more but not more than 95 % of $\alpha$ -4-(2-cyano-2-butoxycarbonyl)vinyl-2-methoxy-phenyl- $\omega$ -hydroxyhexa(oxyethylene), and<br>— 5 % or more but not more than 15 % of polyoxyethylene (20) sorbitan monopalmitate | 0 %                     | 31.12.2015                         |
| ex 3824 90 97 | 29    | Preparation consisting predominantly of $\gamma$ -butyrolactone and quaternary ammonium salts, for the manufacture of electrolytic capacitors <sup>(1)</sup>   | 0 %                     | 31.12.2018                         |
| ex 3824 90 97 | 30    | 2,4,7,9-Tetramethyldec-5-yne-4,7-diol, hydroxyethylated  | 0 %                     | 31.12.2014                         |
| ex 3824 90 97 | 31    | Diethylmethoxyborane (CAS RN 7397-46-8) in the form of a solution in tetrahydrofuran   | 0 %                     | 31.12.2015                         |
| ex 3824 90 97 | 32    | Mixture of:<br>— basic zirconium carbonate (CAS RN 57219-64-4) and<br>— cerium carbonate (CAS RN 537-01-9)   | 0 %                     | 31.12.2016                         |
| ex 3824 90 97 | 33    | Preparation, containing:<br>— trioctylphosphine oxide (CAS RN 78-50-2),<br>— dioctylhexylphosphine oxide (CAS RN 31160-66-4),<br>— octyldihexylphosphine oxide (CAS RN 31160-64-2) and<br>— trihexylphosphine oxide (CAS RN 9084-48-8)                                     | 0 %                     | 31.12.2016                         |
| ex 3824 90 97 | 35    | Mixture of:<br>— 3,3-bis(2-methyl-1-octyl-1H-indol-3-yl)phthalide (CAS RN 50292-95-0) and<br>— ethyl-6'-(diethylamino)-3-oxo-spiro-[isobenzofuran-1(3H),9'-[9H]xanthene]-2'-carboxylate (CAS RN 154306-60-2)   | 0 %                     | 31.12.2017                         |
| ex 3824 90 97 | 36    | Preparation based on 2,5,8,11-tetramethyl-6-dodecyn-5,8-diol ethoxylate (CAS RN 169117-72-0)   | 0 %                     | 31.12.2017                         |
| ex 3824 90 97 | 37    | Liquid crystal mixture for use in the manufacture of displays <sup>(1)</sup>   | 0 %                     | 31.12.2017                         |
| ex 3824 90 97 | 38    | Alkyl carbonate-based preparation, also containing a UV absorber, for use in the manufacture of spectacle lenses <sup>(1)</sup>  | 0 %                     | 31.12.2017                         |
| ex 3824 90 97 | 39    | Mixture containing by weight 40 % or more but not more than 50 % of 2-hydroxyethyl methacrylate and 40 % or more but not more than 50 % of glycerol ester of boric acid  | 0 %                     | 31.12.2018                         |
| ex 3824 90 97 | 40    | Azelaic acid of a purity by weight of 75 % or more but not more than 85 %  | 0 %                     | 31.12.2014                         |
| ex 3824 90 97 | 41    | Preparation, consisting of:<br>— dipropylene glycol<br>— tripropylene glycol<br>— tetrapropylene glycol and<br>— pentapropylene glycol   | 0 %                     | 31.12.2017                         |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
| ex 3824 90 97 | 42    | Mixed metals oxides, in the form of powder, containing by weight:<br>— either 5 % or more of barium, neodymium or magnesium and 15 % or more of titanium,<br>— or 30 % or more of lead and 5 % or more of niobium,<br>for use in the manufacture of dielectric films or for use as dielectric materials in the manufacture of multilayer ceramic capacitors <sup>(1)</sup>  | 0 %                     | 31.12.2018                         |
| ex 3824 90 97 | 43    | Nickel hydroxide, doped with 12 % or more but not more than 18 % by weight of zinc hydroxide and cobalt hydroxide, of a kind used to produce positive electrodes for accumulators   | 0 %                     | 31.12.2017                         |
| ex 3824 90 97 | 44    | Mixture of phytosterols, not in the form of powder, containing by weight:<br>— 75 % or more of sterols,<br>— not more than 25 % of stanols,<br>for use in the manufacture of stanols/sterols or stanol/sterol esters <sup>(1)</sup>   | 0 %                     | 31.12.2017                         |
| ex 3824 90 97 | 45    | Preparations consisting predominantly of ethylene glycol and:<br>— either diethylene glycol, dodecandioic acid and ammonia water,<br>— or N,N-dimethylformamide,<br>— or $\gamma$ -butyrolactone,<br>— or silicon oxide,<br>— or ammonium hydrogen azelate,<br>— or ammonium hydrogen azelate and silicon oxide,<br>— or dodecandioic acid, ammonia water and silicon oxide,<br>for the manufacture of electrolytic capacitors <sup>(1)</sup> | 0 %                     | 31.12.2018                         |
| ex 3824 90 97 | 47    | Platinum oxide (CAS RN 12035-82-4) fixed on a porous support of aluminium oxide (CAS RN 1344-28-1), containing by weight:<br>— 0,1 % or more but not more than 1 % of platinum, and<br>— 0,5 % or more but not more than 5 % of ethylaluminium dichloride (CAS RN 563-43-9)   | 0 %                     | 31.12.2017                         |
| ex 3824 90 97 | 49    | Preparation containing:<br>— C,C'-azodi(formamide) (CAS RN 123-77-3),<br>— magnesium oxide (CAS RN 1309-48-4) and<br>— zinc bis(p-toluene sulphinate) (CAS RN 24345-02-6)<br>in which the gas formation from C,C'-azodi(formamide) occurs at 135 °C   | 0 %                     | 31.12.2017                         |
| ex 3824 90 97 | 50    | Powder mixture containing by weight:<br>— 85 % or more of zinc diacrylate (CAS RN 14643-87-9)<br>— and not more than 5 % of 2,6-di-tert-butyl-alpha-dimethylamino-p-cresol (CAS RN 88-27-7)   | 0 %                     | 31.12.2018                         |
| ex 3824 90 97 | 51    | Diethylene glycol propylene glycol triethanolamine titanate complexes (CAS RN 68784-48-5) dissolved in diethylene glycol (CAS RN 111-46-6)  | 0 %                     | 31.12.2017                         |
| ex 3824 90 97 | 52    | Poly(tetramethylene glycol) bis[(2-benzoyl-phenoxy)acetate] with an average polymer chain length of less than 5 monomer units   | 0 %                     | 31.12.2014                         |
| ex 3824 90 97 | 53    | Poly(ethylene glycol) bis(p-dimethyl)aminobenzoate with an average polymer chain length of less than 5 monomer units  | 0 %                     | 31.12.2014                         |
| ex 3824 90 97 | 54    | 2-Hydroxybenzotrile, in the form of a solution in N,N-dimethylformamide, containing by weight 45 % or more but not more than 55 % of 2-hydroxybenzotrile  | 0 %                     | 31.12.2018                         |

| CN code       | TARIC | Description  | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|------------------------------------|
| ex 3824 90 97 | 55    | Preparation consisting of:<br>— 50 % ( $\pm$ 2 %) by weight of bis-alkoxylated ethyl acetoacetate aluminium chelates,<br>— in an ink oil (white mineral) solvent<br>with a boiling point of 160 °C or more but not more than 180 °C  | 0 %                     | 31.12.2018                         |
| ex 3824 90 97 | 56    | Potassium tert-butanolate (CAS RN 865-47-4) in the form of a solution in tetrahydrofuran   | 0 %                     | 31.12.2018                         |
| ex 3824 90 97 | 58    | N2-[1-(S)-Ethoxycarbonyl-3-phenylpropyl]-N6-trifluoroacetyl-L-lysyl-N2-carboxy anhydride in a solution of dichloromethane at 37 %  | 0 %                     | 31.12.2015                         |
| ex 3824 90 97 | 59    | 3',4',5'-Trifluorobiphenyl-2-amine, in the form of a solution in toluene containing by weight 80 % or more but not more than 90 % of 3',4',5'-trifluorobiphenyl-2-amine  | 0 %                     | 31.12.2015                         |
| ex 3824 90 97 | 60    | $\alpha$ -Phenoxycarbonyl- $\omega$ -phenoxy poly[oxy(2,6-dibromo-1,4-phenylene)isopropylidene(3,5-dibromo-1,4-phenylene)oxycarbonyl]  | 0 %                     | 31.12.2018                         |
| ex 3824 90 97 | 62    | Fused magnesia containing by weight 15 % or more of dichromium trioxide  | 0 %                     | 31.12.2016                         |
| ex 3824 90 97 | 64    | Aluminium sodium silicate, in the form of spheres of a diameter of:<br>— either 1,6mm or more but not more than 3,4mm,<br>— or 4mm or more but not more than 6mm   | 0 %                     | 31.12.2018                         |
| ex 3824 90 97 | 65    | Preparation containing by weight:<br>— 89 % or more but not more than 98,9 % of 1,2,3-trideoxy-4,6:5,7-bis-O-[(4-propylphenyl)methylene]-nonitol<br>— 0,1 % or more but not more than 1 % of colorants<br>— 1 % or more but not more than 10 % of fluoropolymers   | 0 %                     | 31.12.2016                         |
| ex 3824 90 97 | 66    | Mixture of primary <i>tert</i> -alkylamines  | 0 %                     | 31.12.2014                         |
| ex 3824 90 97 | 78    | Mixture of phytosterols derived from wood and wood based oils (tall oil), in the form of powder with a particle size not more than 300 $\mu$ m, containing by weight:<br>— 60 % or more, but not more than 80 % of sitosterols,<br>— not more than 15 % of campesterols,<br>— not more than 5 % of stigmasterols,<br>— not more than 15 % of betasitostanols | 0 %                     | 31.12.2017                         |
| ex 3824 90 97 | 79    | Mixture of 80 % ( $\pm$ 10 %) of 1-[2-(2-aminobutoxy)ethoxy]but-2-ylamine and 20 % ( $\pm$ 10 %) of 1-([2-(2-aminobutoxy)ethoxy]methyl) propoxybut-2-ylamine   | 0 %                     | 31.12.2014                         |
| ex 3824 90 97 | 82    | $\alpha$ -(2,4,6-Tribromophenyl)- $\omega$ -(2,4,6-tribromophenoxy)poly[oxy(2,6-dibromo-1,4-phenylene)isopropylidene(3,5-dibromo-1,4-phenylene)oxycarbonyl]  | 0 %                     | 31.12.2018                         |
| ex 3824 90 97 | 84    | Reaction product, containing by weight:<br>— 1 % or more but not more than 40 % of molybdenum oxide,<br>— 10 % or more but not more than 50 % of nickel oxide,<br>— 30 % or more but not more than 70 % of tungsten oxide  | 0 %                     | 31.12.2014                         |
| ex 3824 90 97 | 87    | Paste containing by weight:<br>— 75 % or more, but not more than 85 % of copper,<br>— inorganic oxides,<br>— ethyl cellulose, and<br>— a solvent   | 0 %                     | 31.12.2017                         |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
| ex 3824 90 97 | 88    | Oligomeric reaction product, consisting of bis(4-hydroxyphenyl) sulfone and 1,1'-oxybis(2-chloroethane)   | 0 %                     | 31.12.2014                         |
| ex 3824 90 97 | 89    | Oligomer of tetrafluoroethylene, having tetrafluoroiodoethyl end-groups   | 0 %                     | 31.12.2018                         |
| ex 3824 90 97 | 90    | Hollow spheres of fused aluminosilicate containing 65-80 % amorphous aluminosilicate, with the following characteristics:<br>— a melting point of between 1 600 °C and 1 800 °C,<br>— a density of 0,6 - 0,8 g/cm <sup>3</sup> ,<br>for use in the manufacture of particle filters in motor vehicles ( <sup>1</sup> )                           | 0 %                     | 31.12.2018                         |
| ex 3824 90 97 | 92    | Preparation, consisting of 2,4,7,9-tetramethyldec-5-yne-4,7-diol and silicon dioxide  | 0 %                     | 31.12.2014                         |
| ex 3824 90 97 | 94    | Particles of silicon dioxide on which are covalently bonded organic compounds, for use in the manufacture of high performance liquid chromatography columns (HPLC) and sample preparation cartridges ( <sup>1</sup> )   | 0 %                     | 31.12.2018                         |
| ex 3824 90 97 | 95    | Mixture of phytosterols, in the form of flakes and balls, containing by weight 80 % or more of sterols and not more than 4 % of stanols   | 0 %                     | 31.12.2014                         |
| ex 3824 90 97 | 97    | Preparation containing by weight either 10 % or more but not more than 20 % of lithiumfluorophosphate or 5 % or more but not more than 10 % of lithium perchlorate in mixtures of organic solvents  | 0 %                     | 31.12.2018                         |
| ex 3826 00 10 | 20    | Mixture of fatty acid methyl esters containing by weight at least:  | 0 %                     | 31.12.2018                         |
| ex 3826 00 10 | 29    | — 65 % or more but not more than 75 % of C12 FAME,<br>— 21 % or more but not more than 28 % of C14 FAME,<br>— 4 % or more but not more than 8 % of C16 FAME,<br>for use in the manufacture of detergents and home and personal care products ( <sup>1</sup> )   |                         |                                    |
| ex 3826 00 10 | 30    | Mixture of fatty acid methyl esters containing by weight at least:  | 0 %                     | 31.12.2018                         |
| ex 3826 00 10 | 39    | — 50 % or more but not more than 58 % of C8-FAME<br>— 35 % or more but not more than 50 % of C10-FAME<br>for use in the manufacture of agricultural chemistry, (animal and human) food ingredients, additives to lubricant, solvents, lamp oil and firelighter components ( <sup>1</sup> )  |                         |                                    |
| ex 3826 00 10 | 40    | Mixture of fatty acid methyl esters containing by weight at least:  | 0 %                     | 31.12.2018                         |
| ex 3826 00 10 | 49    | — 15 % or more but not more than 32 % of C16 FAME<br>— 65 % or more but not more than 85 % of C18 FAME<br>for use in the manufacture of detergents and home and personal cleaning products, agricultural chemistry, (animal and human) food ingredients, additives to lubricant, solvents, lamp oil and firelighter components ( <sup>1</sup> ) |                         |                                    |
| ex 3901 10 90 | 20    | Polyethylene, in the form of granules, of a specific gravity of 0,925 ( $\pm$ 0,0015), a melt flow index of 0,3 g/10 min ( $\pm$ 0,05 g/10 min), for the manufacture of blown films of a haze value not more than 6 % and an elongation at break (MD/TD) of 210/340 ( <sup>1</sup> )  | 0 %                     | 31.12.2018                         |
| ex 3901 10 90 | 30    | Polyethylene granules, containing by weight 10 % or more but not more than 25 % of copper   | 0 %                     | 31.12.2016                         |
| ex 3901 20 90 | 10    | Polyethylene, in one of the forms mentioned in note 6 (b) to Chapter 39, of a specific gravity of 0,945 or more but not more than 0,985, for the manufacture of films for typewriter ribbon or similar ribbon ( <sup>1</sup> )  | 0 %                     | 31.12.2018                         |
| ex 3901 20 90 | 20    | Polyethylene, containing by weight 35 % or more but not more than 45 % of mica  | 0 %                     | 31.12.2018                         |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
| ex 3901 30 00 | 80    | Ethylene-vinyl acetate copolymer,<br>— containing 27,8 % or more but not more than 29,3 % by weight of vinyl acetate<br>— with a melt flow index of 22 g/10 min or more but no more than 28 g/10 min<br>— containing not more than 15 mg/kg vinyl acetate monomer   | 0 %                     | 31.12.2015                         |
| ex 3901 30 00 | 82    | Ethylene-vinyl acetate copolymer,<br>— containing 9,8 % or more but not more than 10,8 % by weight of vinyl acetate<br>— with a melt flow index of 2,5 g/10 min or more but no more than 3,5 g/10 min<br>— containing not more than 15 mg/kg vinyl acetate monomer  | 0 %                     | 31.12.2015                         |
| ex 3901 90 90 | 80    | Block copolymer of ethylene with octene in the form of pellets:<br>— with a specific gravity of 0,862 or more, but not more than 0,865,<br>— able to stretch to at least 200 % its original length,<br>— with a hysteresis of 50 % ( $\pm 10$ %),<br>— with permanent deformation of not more than 20 %, for use in the manufacture of napkin liners for babies ( <sup>1</sup> )                                  | 0 %                     | 31.12.2015                         |
| ex 3901 90 90 | 82    | Copolymer of ethylene and methacrylic acid  | 0 %                     | 31.12.2015                         |
| ex 3901 90 90 | 91    | Ionomer resin consisting of a salt of a copolymer of ethylene with methacrylic acid   | 4 %                     | 31.12.2018                         |
| ex 3901 90 90 | 92    | Chlorosulphonated polyethylene  | 0 %                     | 31.12.2018                         |
| ex 3901 90 90 | 93    | Copolymer of ethylene, vinyl acetate and carbon monoxide, for use as a plasticizer in the manufacture of roof sheets ( <sup>1</sup> )   | 0 %                     | 31.12.2018                         |
| ex 3901 90 90 | 94    | Mixtures of A-B block copolymer of polystyrene and ethylene-butylene copolymer and A-B-A block copolymer of polystyrene, ethylene-butylene copolymer and polystyrene, containing by weight not more than 35 % of styrene  | 0 %                     | 31.12.2018                         |
| ex 3901 90 90 | 97    | Chlorinated polyethylene, in the form of powder   | 0 %                     | 31.12.2018                         |
| ex 3902 10 00 | 10    | Polypropylene containing no plasticizer and not more than:<br>— 7 mg/kg of aluminium,<br>— 2 mg/kg of iron,<br>— 1 mg/kg of magnesium,<br>— 8 mg/kg of chloride   | 0 %                     | 31.12.2018                         |
| ex 3902 10 00 | 20    | Polypropylene, containing no plasticiser,<br>— of a melting point of more than 150 °C (as determined by the ASTM D 3 417 method),<br>— of a heat of fusion of 15 J/g or more but not more than 70 J/g,<br>— of an elongation at break of 1 000 % or more (as determined by the ASTM D 638 method),<br>— of a tensile modulus of 69 MPa or more but not more than 379 MPa (as determined by the ASTM D 638 method) | 0 %                     | 31.12.2018                         |
| ex 3902 10 00 | 30    | Polypropylene, containing not more than 1 mg/kg of aluminium, 0,05 mg/kg of iron, 1 mg/kg of magnesium and 1 mg/kg of chloride, for use in the manufacture of packaging for disposable contact lenses ( <sup>1</sup> )  | 0 %                     | 31.12.2018                         |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
| ex 3902 10 00 | 40    | Polypropylene, containing no plasticizer:<br>— of a tensile strength: of 32-60 MPa (as determined by the ASTM D638 method);<br>— of a flexural strength of 50-90 MPa (as determined by the ASTM D790 method);<br>— of a Melt Flow Rate (MFR) at 230 °C/ 2,16 kg of 5-15 g/10 min (as determined by the ASTM D1238 method);<br>— with 40 % or more but not more than 80 % by weight of polypropylene,<br>— with 10 % or more but not more than 30 % by weight of glass fibre,<br>— with 10 % or more but not more than 30 % by weight of mica  | 0 %                     | 31.12.2014                         |
| ex 3902 10 00 | 50    | High isotactic polypropylene (HIPP), whether or not coloured, intended for the manufacture of plastic components for air freshener with the following properties:<br>— a density of 0,880 g/cm <sup>3</sup> or more but not more than 0,913 g/cm <sup>3</sup> (as determined by test method ASTM D1505),<br>— a tensile strength at yield of 350 kg/cm <sup>2</sup> or more but not more than 390 kg/cm <sup>2</sup> (as determined by test method ASTM D638)<br>— a heat deflection temperature of 135 °C or more under load of 0,45 MPa (as determined by test method ASTM 648) (1) | 0 %                     | 31.12.2015                         |
| ex 3902 20 00 | 10    | Polyisobutylene, of a number average molecular weight (M <sub>n</sub> ) of 700 or more but not more than 800  | 0 %                     | 31.12.2018                         |
| ex 3902 20 00 | 20    | Hydrogenated polyisobutene, in liquid form  | 0 %                     | 31.12.2018                         |
| ex 3902 30 00 | 91    | A-B Block copolymer of polystyrene and an ethylene-propylene copolymer, containing by weight 40 % or less of styrene, in one of the forms mentioned in note 6 (b) to Chapter 39   | 0 %                     | 31.12.2018                         |
| ex 3902 30 00 | 95    | A-B-A block copolymer, consisting of:<br>— a copolymer of propylene and ethylene and<br>— 21 % (± 3 %) by weight of polystyrene   | 0 %                     | 31.12.2016                         |
| ex 3902 30 00 | 97    | Liquid ethylene-propylene-copolymer with:<br>— a flashpoint of 250 °C or more,<br>— a viscosity index of 150 or more,<br>— of a number average molecular weight (M <sub>n</sub> ) of 650 or more  | 0 %                     | 31.12.2016                         |
| ex 3902 90 90 | 52    | Amorphous poly-alpha-olefin copolymer blend of poly(propylene-co-1-butene) and petroleum hydrocarbon resin  | 0 %                     | 31.12.2018                         |
| ex 3902 90 90 | 55    | Thermoplastic elastomer, with an A-B-A block copolymer structure of polystyrene, polyisobutylene and polystyrene containing by weight 10 % or more but not more than 35 % of polystyrene  | 0 %                     | 31.12.2018                         |
| ex 3902 90 90 | 60    | Non-hydrogenated 100 % aliphatic resin (polymer), with the following characteristics:<br>— liquid at room temperature<br>— obtained by cationic polymerisation of C-5 alkenes monomers<br>— with a number average molecular weight (M <sub>n</sub> ) of 370 (± 50)<br>— with a weight average molecular weight (M <sub>w</sub> ) of 500 (± 100)   | 0 %                     | 31.12.2014                         |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
| ex 3902 90 90 | 84    | Blend of hydrogenated styrenic block copolymer, polyethylene wax, and tackifier resin, in the form of pellets, containing by weight:<br>— 70 (± 5) % of styrenic block copolymer,<br>— 15 (± 5) % of polyethylene wax, and<br>— 15 (± 5) % of tackifier resin<br>with the following physical properties:<br>— able to stretch to at least 200 % of its original length<br>— with a hysteresis of 50 (± 10) %<br>— with a permanent deformation of no more than 20 %<br>for use in the manufacture of napkins and napkin liners for babies (!) | 0 %                     | 31.12.2015                         |
| ex 3902 90 90 | 92    | Polymers of 4-methylpent-1-ene  | 0 %                     | 31.12.2018                         |
| ex 3902 90 90 | 93    | Synthetic poly-alpha-olefin having a viscosity of at least $38 \times 10^{-6} \text{m}^2 \text{s}^{-1}$ (38 centistokes) at 100 °C measured using the ASTM D 445 method   | 0 %                     | 31.12.2016                         |
| ex 3902 90 90 | 98    | Synthetic poly-alpha-olefin with a viscosity at 100 ° Celsius (measured according to method ASTM D 445) ranging from 3 centistokes to 9 centistokes and obtained by polymerization of a mixture of dodecene and tetradecene, containing a maximum of 40 % of tetradecene  | 0 %                     | 31.12.2016                         |
| ex 3903 11 00 | 10    | White expandable polystyrene beads with a thermal conductivity of not more than 0,034 W/mK at a density of 14,0 kg/m <sup>3</sup> (± 1,5 kg/m <sup>3</sup> ), containing 50 % recycled material   | 0 %                     | 31.12.2018                         |
| ex 3903 19 00 | 30    | Crystalline polystyrene with a melting point of 268 °C or more but not more than 272 °C and a setting point of 232 °C or more but not more than 242 °C, whether or not containing additives and filling material  | 0 %                     | 31.12.2016                         |
| ex 3903 90 90 | 10    | Butadiene-styrene copolymer pellets or granules, with:<br>— a specific gravity of 1,05 (± 0,02),<br>— a melt flow index at 200 °C/5 kg of 13 g/10 min (± 1 g/10 min)  | 0 %                     | 31.12.2016                         |
| ex 3903 90 90 | 15    | Dry ink powder or toner blend, consisting of a copolymer of styrene, n-butyl acrylate, n-butyl methacrylate, methacrylic acid and polyolefin wax, for use as a developer in the manufacture of cartridges for facsimile machines, computer printers or copiers (!)  | 0 %                     | 31.12.2016                         |
| ex 3903 90 90 | 20    | Dry ink powder or toner blend, consisting of a copolymer of styrene, n-butyl acrylate, n-butyl methacrylate and polyolefin wax, for use as a developer in the manufacture of cartridges for facsimile machines, computer printers or copiers (!)  | 0 %                     | 31.12.2016                         |
| ex 3903 90 90 | 25    | Dry ink powder or toner blend, consisting of a copolymer of styrene, n-butyl acrylate, methacrylic acid and polyolefin wax, for use as a developer in the manufacture of cartridges for facsimile machines, computer printers or copiers (!)  | 0 %                     | 31.12.2016                         |
| ex 3903 90 90 | 30    | Butadiene-styrene copolymer pellets or granules with a melting point of 85 °C (± 5 °C), containing by weight:<br>— 2 % or more but not more than 4 % of tris(tribromophenyl) triazine,<br>— 5 % or more but not more than 10 % of ethane-1,2-bis(pentabromophenyl),<br>— 3 % or more but not more than 5 % of antimony trioxide   | 0 %                     | 31.12.2016                         |
| ex 3903 90 90 | 35    | Copolymer of $\alpha$ -methylstyrene and styrene, having a softening point of more than 113 °C  | 0 %                     | 31.12.2018                         |
| ex 3911 90 99 | 43    |   |                         |                                    |

| CN code                        | TARIC    | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|--------------------------------|----------|---|-------------------------|------------------------------------|
| ex 3903 90 90<br>ex 3911 90 99 | 40<br>50 | Copolymer of styrene with $\alpha$ -methylstyrene and acrylic acid, of a number average molecular weight ( $M_n$ ) of 500 or more but not more than 6 000   | 0 %                     | 31.12.2018                         |
| ex 3903 90 90                  | 50       | Crystalline copolymer of styrene and p-methylstyrene:<br>— with a melting point of 240 °C or more but not more than 260 °C,<br>— containing 5 % or more but not more than 15 % by weight of p-methylstyrene   | 0 %                     | 31.12.2015                         |
| ex 3903 90 90<br>ex 3911 90 99 | 60<br>60 | Copolymer of styrene with maleic anhydride, either partially esterified or completely chemically modified, of an average molecular weight ( $M_n$ ) of not more than 4 500, in flake or powder form   | 0 %                     | 31.12.2016                         |
| ex 3903 90 90                  | 75       | Copolymer of styrene and vinyl pyrrolidone, containing by weight not more than 1 % of sodium dodecyl sulphate, in the form of an aqueous emulsion, for the manufacture of goods of subheading 3305 20 00 or of hair dyes of subheading 3305 90 <sup>(1)</sup>   | 0 %                     | 31.12.2014                         |
| ex 3903 90 90                  | 80       | Granules of copolymer of styrene and divinylbenzene of a minimum diameter of 150 $\mu$ m and a maximum diameter of 800 $\mu$ m and containing by weight:<br>— minimum 65 % styrene,<br>— maximum 25 % divinylbenzene<br>for use in the manufacture of ion exchange resins <sup>(1)</sup>  | 0 %                     | 31.12.2018                         |
| ex 3903 90 90                  | 86       | Mixture containing by weight:<br>— 45 % or more but not more than 65 % of polymers of styrene<br>— 35 % or more but not more than 45 % of poly(phenylene ether)<br>— not more than 10 % of other additives<br>and with one or more of the following special colour effects:<br>— metallic or pearlescent with a visual angular metamerism caused by at least 0,3 % flake-based pigment<br>— fluorescent, as characterized by emitting light during absorption of ultraviolet radiation<br>— bright white, as characterized by L* not less than 92 and b* not more than 2 and a* between -5 and 7 on the CIELab colour scale | 0 %                     | 31.12.2018                         |
| ex 3904 10 00                  | 20       | Poly(vinyl chloride) powder, not mixed with any other substances or containing any vinyl acetate monomers, with:<br>— a degree of polymerisation of 1 000 ( $\pm$ 300) monomer units,<br>— a coefficient of heat transmission (K-value) of 60 or more, but not more than 70,<br>— a volatile material content of less than 2,00 % by weight,<br>— a sieve non-passing fraction at a mesh width of 120 $\mu$ m of not more than 1 % by weight,<br>for use in the manufacture of battery separators <sup>(1)</sup>  | 0 %                     | 31.12.2014                         |
| ex 3904 30 00                  | 20       | Copolymer of vinyl chloride with vinyl acetate and maleic acid, containing by weight:<br>— 80,5 % or more but not more than 81,5 % of vinyl chloride,<br>— 16,5 % or more but not more than 17,5 % of vinyl acetate and<br>— 1,5 % or more but not more than 2,5 % of maleic acid,<br>for use in the heat-sealing of plastics onto steel substrate for industrial uses <sup>(1)</sup>   | 0 %                     | 31.12.2014                         |
| ex 3904 30 00<br>ex 3904 40 00 | 30<br>91 | Copolymer of vinyl chloride with vinyl acetate and vinyl alcohol, containing by weight:<br>— 87 % or more but not more than 92 % of vinyl chloride,<br>— 2 % or more but not more than 9 % of vinyl acetate and<br>— 1 % or more but not more than 8 % of vinyl alcohol,  | 0 %                     | 31.12.2018                         |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
|               |       | in one of the forms mentioned in note 6 (a) or (b) to Chapter 39, for the manufacture of goods of headings 3215 or 8523 or for use in the manufacture of coatings for containers and closures of a kind used for preserving food and drink <sup>(1)</sup>   |                         |                                    |
| ex 3904 40 00 | 93    | Copolymer of vinyl chloride and methyl acrylate, containing by weight 80 % ( $\pm$ 1 %) of vinyl chloride and 20 % ( $\pm$ 1 %) of methyl acrylate, in the form of a aqueous emulsion   | 0 %                     | 31.12.2018                         |
| ex 3904 50 90 | 92    | Vinylidene-chloride methacrylate co-polymer for use in the manufacture of monofilaments <sup>(1)</sup>  | 0 %                     | 31.12.2014                         |
| ex 3904 61 00 | 20    | Copolymer of tetrafluoroethylene and trifluoro(heptafluoropropoxy)ethylene, containing 3,2 % or more but not more than 4,6 % by weight of trifluoro(heptafluoropropoxy)ethylene and less than 1 mg/kg of extractable fluoride ions  | 0 %                     | 31.12.2018                         |
| ex 3904 61 00 | 30    | Polytetrafluoroethylene, in the form of powder, of a specific surface of 8 m <sup>2</sup> /g or more but not more than 12 m <sup>2</sup> /g, a particle size distribution of 10 % of less than 10 $\mu$ m and 90 % of less than 35 $\mu$ m and an average particle size of 20 $\mu$ m   | 0 %                     | 31.12.2018                         |
| ex 3904 69 80 | 81    | Poly(vinylidene fluoride) (CAS RN 24937-79-9)   | 0 %                     | 31.12.2015                         |
| ex 3904 69 80 | 85    | Copolymer of ethylene with chlorotrifluoroethylene, whether or not modified with hexafluoroisobutylene, in powder, whether or not with fillers  | 0 %                     | 31.12.2017                         |
| ex 3904 69 80 | 93    | Copolymer of ethylene with chlorotrifluoroethylene, in one of the forms mentioned in note 6 (b) to Chapter 39   | 0 %                     | 31.12.2018                         |
| ex 3904 69 80 | 94    | Copolymer of ethylene and tetrafluoroethylene   | 0 %                     | 31.12.2018                         |
| ex 3904 69 80 | 96    | Polychlorotrifluoroethylene, in one of the forms mentioned in note 6 (a) and (b) to Chapter 39  | 0 %                     | 31.12.2018                         |
| ex 3904 69 80 | 97    | Copolymer of chlorotrifluoroethylene and vinylidene difluoride  | 0 %                     | 31.12.2018                         |
| ex 3905 30 00 | 10    | Viscous preparation, essentially consisting of poly(vinyl alcohol) (CAS RN 9002-89-5), an organic solvent and water for use as protective coating of wafers during the manufacturing of semiconductors <sup>(1)</sup>   | 0 %                     | 31.12.2017                         |
| ex 3905 91 00 | 20    | Water soluble copolymer of ethylene and vinyl alcohol (CAS RN 26221-27-2), containing by weight not more than 13 % of the monomer unit ethylene   | 0 %                     | 31.12.2017                         |
| ex 3905 99 90 | 92    | Polymer of vinylpyrrolidone and dimethylaminoethyl methacrylate, containing by weight 97 % or more but not more than 99 % of vinylpyrrolidone, in the form of a solution in water   | 0 %                     | 31.12.2018                         |
| ex 3905 99 90 | 95    | Hexadecylated or eicosylated polyvinylpyrrolidone   | 0 %                     | 31.12.2018                         |
| ex 3905 99 90 | 96    | Polymer of vinyl formal, in one of the forms mentioned in note 6 (b) to Chapter 39, of a weight average molecular weight ( $M_w$ ) of 25 000 or more but not more than 150 000 and containing by weight: <ul style="list-style-type: none"> <li>— 9,5 % or more but not more than 13 % of acetyl groups evaluated as vinyl acetate and</li> <li>— 5 % or more but not more than 6,5 % of hydroxy groups evaluated as vinyl alcohol</li> </ul> | 0 %                     | 31.12.2018                         |
| ex 3905 99 90 | 97    | Povidone (INN)-iodine (CAS RN 25655-41-8)   | 0 %                     | 31.12.2018                         |
| ex 3905 99 90 | 98    | Poly(vinyl pyrrolidone) partially substituted by triacontyl groups, containing by weight 78 % or more but not more than 82 % of triacontyl groups   | 0 %                     | 31.12.2018                         |
| 3906 90 60    |       | Copolymer of methyl acrylate with ethylene and a monomer containing a non-terminal carboxy group as a substituent, containing by weight 50 % or more of methyl acrylate, whether or not mixed with silicon dioxide  | 0 %                     | 31.12.2018                         |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
| ex 3906 90 90 | 10    | Polymerization product of acrylic acid with small quantities of a polyunsaturated monomer, for the manufacture of medicaments of heading 3003 or 3004 <sup>(1)</sup>  | 0 %                     | 31.12.2018                         |
| ex 3906 90 90 | 15    | Photosensitive resin consisting of modified acrylate, acrylic monomer, catalyst (photoinitiator) and stabilizer   | 0 %                     | 31.12.2018                         |
| ex 3906 90 90 | 27    | Copolymer of stearyl methacrylate, isooctyl acrylate and acrylic acid, dissolved in isopropyl palmitate   | 0 %                     | 31.12.2017                         |
| ex 3906 90 90 | 30    | Copolymer of styrene with hydroxyethyl methacrylate and 2-ethylhexyl acrylate, of a number average molecular weight ( $M_n$ ) of 500 or more but not more than 6 000  | 0 %                     | 31.12.2018                         |
| ex 3906 90 90 | 35    | White powder of 1,2-ethanediol dimethacrylate-methyl methacrylate copolymer of a particle size of not more than 18 $\mu$ m, insoluble in water  | 0 %                     | 31.12.2018                         |
| ex 3906 90 90 | 40    | Transparent acrylic polymer in packages of not more than 1 kg, and not for retail sale with:<br>— a viscosity of not more than 50 000 Pa·s at 120 °C as determined by the test method ASTM D 3835<br>— a weight average molecular weight ( $M_w$ ) of more than 500 000 but not more than 1 200 000 according to the Gel Permeation Chromatography (GPC) test,<br>— a residual monomer content of less than 1 % | 0 %                     | 31.12.2015                         |
| ex 3906 90 90 | 41    | Poly(alkyl acrylate) with an ester alkyl chain of C10 to C30  | 0 %                     | 31.12.2014                         |
| ex 3906 90 90 | 45    | Acrylonitrile-butadiene-styrene-methylmethacrylate copolymer pellets with:<br>— a melting point of 96 °C ( $\pm$ 3 °C),<br>— a specific gravity of 1,03 or more but not more than 1,07, and containing by weight:<br>— 25 % or more but not more than 50 % of acrylonitrile-butadiene-styrene, and<br>— 50 % or more but not more than 75 % of methylmethacrylate   | 0 %                     | 31.12.2016                         |
| ex 3906 90 90 | 50    | Polymers of esters of acrylic acid with one or more of the following monomers in the chain:<br>— chloromethyl vinyl ether,<br>— chloroethyl vinyl ether,<br>— chloromethylstyrene,<br>— vinyl chloroacetate,<br>— methacrylic acid,<br>— butenedioic acid monobutyl ester,<br>containing by weight not more than 5 % of each of the monomeric units, in one of the forms mentioned in note 6 (b) to Chapter 39  | 0 %                     | 31.12.2018                         |
| ex 3906 90 90 | 65    | Polyalkylacrylate, chemically modified with cobalt, with a melting temperature ( $T_m$ ) of 65 °C ( $\pm$ 5 °C), measured with Differential Scanning Calorimetry (DSC)  | 0 %                     | 31.12.2018                         |
| ex 3906 90 90 | 80    | Polydimethylsiloxane-graft-(polyacrylates; polymethacrylates)   | 0 %                     | 31.12.2018                         |
| ex 3906 90 90 | 85    | Non aqueous dispersion type polymers of esters of acrylic acid with a hydrolyzable silyl group at one or both polymer ends  | 0 %                     | 31.12.2014                         |
| ex 3907 20 11 | 10    | Poly(ethylene oxide) of a number average molecular weight ( $M_n$ ) of 100 000 or more  | 0 %                     | 31.12.2018                         |
| ex 3907 20 11 | 20    | Bis[Methoxypoly(ethyleneglycol)]-maleimidopropionamide, chemically modified with lysine, of a number average molecular weight ( $M_n$ ) of 40 000   | 0 %                     | 31.12.2018                         |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
| ex 3907 20 11 | 40    | Polyethylene glycol with an ethylene oxide chain length of not more than 30, having butyl-2-cyano 3-(4-hydroxyphenyl) acrylate end groups, for use as a UV barrier in liquid masterbatches (!)  | 0 %                     | 31.12.2015                         |
| ex 3907 20 11 | 50    | [3-[3-(2H-Benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-hydroxypoly(oxo-1,2-ethanediy) (CAS RN 104810-48-2)  | 0 %                     | 31.12.2016                         |
| ex 3907 20 11 | 60    | Preparation containing:<br>— $\alpha$ -[3-[3-(2H-Benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]- $\omega$ -hydroxypoly(oxy-1,2-ethanediy) (CAS RN 104810-48-2) and<br>— $\alpha$ -[3-[3-(2H-Benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]- $\omega$ -[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]poly(oxy-1,2-ethanediy) (CAS RN 104810-47-1) | 0 %                     | 31.12.2016                         |
| ex 3907 20 20 | 20    | Polytetramethylene ether glycol with a weight average molecular weight (Mw) of 2 700 or more but not more than 3 100 (CAS RN 25190-06-1)  | 0 %                     | 31.12.2017                         |
| ex 3907 20 20 | 30    | Mixture, containing by weight 70 % or more but not more than 80 % of a polymer of glycerol and 1,2-epoxypropane and 20 % or more but not more than 30 % of a copolymer of dibutyl maleate and N-vinyl-2-pyrrolidone   | 0 %                     | 31.12.2018                         |
| ex 3907 20 20 | 40    | Copolymer of tetrahydrofuran and tetrahydro-3-methylfuran with a number average molecular weight (M <sub>n</sub> ) of 3 500 ( $\pm$ 100)  | 0 %                     | 31.12.2018                         |
| ex 3907 20 99 | 15    | Poly(oxypropylene) having alkoxyethyl end-groups  | 0 %                     | 31.12.2018                         |
| ex 3907 20 99 | 30    | Homopolymer of 1-chloro-2,3-epoxypropane (epichlorohydrin)  | 0 %                     | 31.12.2018                         |
| ex 3907 20 99 | 35    | Polyethylene glycol chemically modified with an isocyanate group containing a carbodiimide group, in the form of a solution in 2-methoxy-1-methylethyl acetate  | 0 %                     | 31.12.2018                         |
| ex 3907 20 99 | 45    | Copolymer of ethylene oxide and propylene oxide, having aminopropyl and methoxy end-groups  | 0 %                     | 31.12.2018                         |
| ex 3907 20 99 | 50    | Vinyl-silyl terminated perfluoropolyether polymer or an assortment of two components consisting of the same type of vinyl-silyl terminated perfluoropolyether polymer as the main ingredient  | 0 %                     | 31.12.2018                         |
| ex 3907 20 99 | 55    | Succinimidyl ester of methoxy poly(ethylene glycol)propionic acid, of a number average molecular weight (M <sub>n</sub> ) of 5 000  | 0 %                     | 31.12.2018                         |
| ex 3907 20 99 | 60    | Polytetramethylene oxide di-p-aminobenzoate   | 0 %                     | 31.12.2016                         |
| ex 3907 20 99 | 65    | L-Lysine N-hydroxysuccinimidyl ester.alpha.,.epsilon.-bis(polyethylene glycol monomethylether carbamate) (CAS RN 266318-38-1) of a number average molecular weight (M <sub>n</sub> ) of 38 000 or more but not more than 40 000   | 0 %                     | 31.12.2018                         |
| ex 3907 30 00 | 40    | Epoxide resin, containing by weight 70 % or more of silicon dioxide, for the encapsulation of goods of headings 8533, 8535, 8536, 8541, 8542 or 8548 (!)  | 0 %                     | 31.12.2018                         |
| ex 3926 90 97 | 70    |   |                         |                                    |
| ex 3907 30 00 | 50    | Liquid epoxide resin of 2-propenenitrile/1,3-butadiene-epoxide copolymer, not containing any solvent, with:<br>— a zinc borate hydrate content of not more than 40 % by weight,<br>— a diantimony trioxide content of not more than 5 % by weight   | 0 %                     | 31.12.2018                         |
| ex 3907 30 00 | 60    | Polyglycerol polyglycidyl ether resin (CAS RN 105521-63-9)  | 0 %                     | 31.12.2017                         |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
| ex 3907 40 00 | 10    | Polycarbonate pellets or granules:<br>— containing 7 % or more but not more than 15 % by weight of non halogen flame retardant, and<br>— with a specific gravity of 1,20 ( $\pm 0,01$ )   | 0 %                     | 31.12.2016                         |
| ex 3907 40 00 | 20    | Polycarbonate pellets or granules with a specific gravity of 1,32 ( $\pm 0,03$ ), containing 20 % ( $\pm 5$ %) of glass fibre   | 0 %                     | 31.12.2016                         |
| ex 3907 40 00 | 30    | Polycarbonate pellets or granules with a specific gravity of 1,18 or more but not more than 1,25, containing by weight:<br>— 77 % or more but not more than 90 % of polycarbonate,<br>— 8 % or more but not more than 20 % of phosphoric acid ester,<br>— 0,1 % or more but not more than 1 % of antioxidant, and<br>whether or not containing 1 % or more but not more than 5 % of flame retardant                             | 0 %                     | 31.12.2016                         |
| ex 3907 40 00 | 40    | Polycarbonate granules with:<br>— a melt flow rate of 18 g/10 min/300 °C/1,2 kg (according to ASTM D 1238)<br>— a tensile strength of 69 MPa according to ASTM D 638 and<br>— a flexural strength of 112 MPa according to ASTM D 790  | 0 %                     | 31.12.2016                         |
| ex 3907 40 00 | 50    | Polycarbonate resin, pellets or granules, with:<br>— a specific gravity of 1,20 ( $\pm 0,05$ ),<br>— a heat deflection temperature of 146 °C ( $\pm 3$ °C) at 4,6 kgf/cm <sup>2</sup> , and<br>— a melt flow index of 20 ( $\pm 10$ ) g/10 min at 300 °C/1,2 kg   | 0 %                     | 31.12.2016                         |
| ex 3907 40 00 | 60    | Polycarbonate acrylonitrile-butadiene-styrene pellets or granules with specific gravity of 1,20 ( $\pm 0,05$ ), containing by weight:<br>— 65 % or more but not more than 90 % of polycarbonate,<br>— 5 % or more but not more than 15 % of acrylonitrile-butadiene-styrene,<br>— 5 % or more but not more than 20 % of phosphoric acid ester and,<br>— 0,1 % or more but not more than 5 % of antioxidant                      | 0 %                     | 31.12.2016                         |
| ex 3907 60 80 | 10    | Copolymer of terephthalic acid and isophthalic acid with ethylene glycol, butane-1,4-diol and hexane-1,6-diol   | 0 %                     | 31.12.2018                         |
| ex 3907 60 80 | 30    | Oxygen binding concentrate consisting of a blend of:<br>— a copolymer obtained from poly(ethylene terephthalate), pyromellitic dianhydride (PMDA) and a hydroxyl substituted polybutadiene<br>— a barrier co-polymer (as determined by the ASTM method F1115-95 (2001)) obtained from xylylene diamines and adipic acid, and<br>— organic dyes and/or organic and inorganic pigments<br>where the first co-polymer predominates | 0 %                     | 31.12.2014                         |
| ex 3907 60 80 | 40    | Poly(ethylene terephthalate) pellets or granules:<br>— with a specific gravity of 1,23 or more but not more than 1,27 at 23 °C, and<br>— containing not more than 10 % by weight of other modifiers or additives  | 0 %                     | 31.12.2016                         |
| ex 3907 60 80 | 50    | Flexible packages (for oxygen sensitive polymers) manufactured from a laminate of:<br>— not more than 75 $\mu\text{m}$ of polyethylene,<br>— not more than 50 $\mu\text{m}$ of polyamide,<br>— not more than 15 $\mu\text{m}$ of polyethylene terephthalate and<br>— not more than 9 $\mu\text{m}$ of aluminium   | 0 %                     | 31.12.2017                         |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
| 3907 70 00    |       | with a tensile strength of more than 70 N/15 mm and oxygen transmission rate of less than 0,1 cm <sup>3</sup> /m <sup>2</sup> /24 hrs at 0,1 MPa<br>Poly(lactic acid)   | 0 %                     | 31.12.2018                         |
| ex 3907 91 90 | 10    | Diallyl phthalate prepolymer, in powder form  | 0 %                     | 31.12.2014                         |
| ex 3907 99 90 | 10    | Poly(oxy-1,4-phenylenecarbonyl) (CAS RN 26099-71-8), in the form of powder  | 0 %                     | 31.12.2018                         |
| ex 3907 99 90 | 20    | Liquid crystal copolyester with a melting point of not less than 270 °C, whether or not containing fillers  | 0 %                     | 31.12.2018                         |
| ex 3907 99 90 | 25    | Copolymer, containing 72 % by weight or more of terephthalic acid and/or isomers thereof and cyclohexanedimethanol  | 0 %                     | 31.12.2017                         |
| ex 3907 99 90 | 30    | Poly(hydroxyalkanoate), predominantly consisting of poly(3-hydroxybutyrate)   | 0 %                     | 31.12.2015                         |
| ex 3913 90 00 | 20    |   |                         |                                    |
| ex 3907 99 90 | 60    | Copolymer of terephthalic acid and isophthalic acid with bisphenol A  | 0 %                     | 31.12.2017                         |
| ex 3907 99 90 | 70    | Copolymer of poly(ethylene terephthalate) and cyclohexane dimethanol, containing more than 10 % by weight of cyclohexane dimethanol   | 0 %                     | 31.12.2014                         |
| ex 3907 99 90 | 80    | Copolymer, consisting of 72 % by weight or more of terephthalic acid and/ or derivatives thereof and cyclohexanedimethanol, completed with linear and/ or cyclic dioles   | 0 %                     | 31.12.2015                         |
| ex 3908 90 00 | 10    | Poly(iminomethylene-1,3-phenylenemethyleneiminoadipoyl), in one of the forms mentioned in note 6 (b) to Chapter 39  | 0 %                     | 31.12.2018                         |
| ex 3908 90 00 | 30    | Reaction product of mixtures of octadecanecarboxylic acids polymerised with an aliphatic polyetherdiamine   | 0 %                     | 31.12.2018                         |
| ex 3908 90 00 | 50    | Oxygen binding concentrate consisting of a blend of:<br>— a copolymer obtained from poly(ethyleneterephthalate), pyromellitic dianhydride (PMDA) and a hydroxyl substituted polybutadiene<br>— a barrier co-polymer (as determined by the ASTM method F1115-95 (2001)) obtained from xylylene diamines and adipic acid, and<br>— organic dyes and/or organic and inorganic pigments<br>where the second co-polymer predominates | 0 %                     | 31.12.2014                         |
| ex 3908 90 00 | 60    | Copolymer consisting of:<br>— hexanedioic acid<br>— 12-aminododecanoic acid<br>— hexahydro-2H-azepin-2-one, and<br>— 1,6-hexanediamine  | 0 %                     | 31.12.2017                         |
| ex 3909 40 00 | 10    | Polycondensation product of phenol with formaldehyde, in the form of hollow spheres of a diameter of less than 150 µm   | 0 %                     | 31.12.2018                         |
| ex 3909 40 00 | 20    | Powder of thermosetting resin in which magnetic particles have been evenly distributed, for use in the manufacture of ink for photocopiers, fax machines, printers and multifunction devices <sup>(1)</sup>   | 0 %                     | 31.12.2015                         |
| ex 3909 40 00 | 30    | Mixture of:<br>— alkylphenol - formaldehyde resin, whether or not brominated, and<br>— zinc oxide   | 0 %                     | 31.12.2017                         |

| CN code       | TARIC | Description  | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|------------------------------------|
| ex 3909 40 00 | 40    | Polymer in powder form with a content of:<br>— phenolic resin polymer (CAS RN 9003-35-4) with 80 % by weight or more but not more than 90 %<br>— phenol (CAS RN 108-95-2) with not more than 5 % and<br>— hexamethylenetetramine (CAS RN 100-97-0) with 5 % by weight or more but not more than 15 %   | 0 %                     | 31.12.2018                         |
| ex 3909 50 90 | 10    | UV curable water soluble liquid photopolymer consisting of a mixture by weight of<br>— 60 % or more of two-functional acrylated polyurethane oligomers and<br>— 30 % ( $\pm$ 8 %) of mono-functional and tri-functional (metha) acrylates, and<br>— 10 % ( $\pm$ 3 %) of hydroxyl functionalized mono-functional (metha) acrylates   | 0 %                     | 31.12.2014                         |
| ex 3910 00 00 | 20    | Block copolymer of poly(methyl-3,3,3-trifluoropropylsiloxane) and poly[methyl(vinyl)siloxane]  | 0 %                     | 31.12.2018                         |
| ex 3910 00 00 | 40    | Biocompatible silicones for the manufacture of long term surgical implants <sup>(1)</sup>  | 0 %                     | 31.12.2016                         |
| ex 3910 00 00 | 50    | Silicone based pressure sensitive adhesive in solvent containing copoly(dimethylsiloxane/diphenylsiloxane) gum   | 0 %                     | 31.12.2017                         |
| ex 3910 00 00 | 60    | Polydimethylsiloxane, whether or not polyethylene glycol and trifluoropropyl substituted, with methacrylate end groups   | 0 %                     | 31.12.2014                         |
| ex 3910 00 00 | 70    | Passivating silicon coating in primary form, to protect edges and prevent short circuits in semiconductor devices  | 0 %                     | 31.12.2018                         |
| ex 3911 10 00 | 81    | Non-hydrogenated hydrocarbon resin, obtained by polymerization of more than 75 % by weight C-5 to C-12 cycloaliphatic alkenes and more than 10 % but not more than 25 % by weight aromatic alkenes yielding a hydrocarbon resin with:<br>— an iodine value of more than 120 and<br>— a Gardner Colour of more than 10 for the pure product or<br>— a Gardner Colour of more than 8 for a 50 % solution by weight in toluene (as determined by the ASTM method D6166) | 0 %                     | 31.12.2018                         |
| ex 3911 90 19 | 10    | Poly(oxy-1,4-phenylenesulfonyl-1,4-phenyleneoxy-4,4'-biphenylene)  | 0 %                     | 31.12.2018                         |
| ex 3911 90 19 | 30    | Copolymer of ethyleneimine and ethyleneimine dithiocarbamate, in an aqueous solution of sodium hydroxide   | 0 %                     | 31.12.2017                         |
| ex 3911 90 19 | 40    | m- Xylene formaldehyde resin   | 0 %                     | 31.12.2016                         |
| ex 3911 90 99 | 25    | Copolymer of vinyltoluene and $\alpha$ -methylstyrene  | 0 %                     | 31.12.2018                         |
| ex 3911 90 99 | 30    | 1,4:5,8- Dimethanonaphthalene, 2-ethylidene-1,2,3,4,4a,5,8,8a-octahydro-, polymer with 3a,4,7,7a- tetrahydro- 4,7-methano-1H-indene, hydrogenated  | 0 %                     | 31.12.2015                         |
| ex 3911 90 99 | 31    | Copolymers of butadiene and maleic acid, whether or not containing its ammonium salts  | 0 %                     | 31.12.2014                         |
| ex 3911 90 99 | 35    | Alternated copolymer of ethylene and maleic anhydride (EMA)  | 0 %                     | 31.12.2015                         |
| ex 3911 90 99 | 40    | Mixed calcium and sodium salt of a copolymer of maleic acid and methyl vinyl ether, having a calcium content of 9 % or more but not more than 16 % by weight   | 0 %                     | 31.12.2018                         |
| ex 3911 90 99 | 45    | Copolymer of maleic acid and methyl vinyl ether  | 0 %                     | 31.12.2018                         |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
| ex 3911 90 99 | 53    | Hydrogenated polymer of 1,2,3,4,4a,5,8,8a-octahydro-1,4:5,8-dimethanonaphthalene with 3a,4,7,7a-tetrahydro-4,7-methano-1H-indene and 4,4a,9,9a-tetrahydro-1,4-methano-1H-fluorene (CAS RN 503442-46-4)  | 0 %                     | 31.12.2017                         |
| ex 3911 90 99 | 57    | Hydrogenated polymer of 1,2,3,4,4a,5,8,8a-octahydro-1,4:5,8-dimethanonaphthalene with 4,4a,9,9a-tetrahydro-1,4-methano-1H-fluorene (CAS RN 503298-02-0)   | 0 %                     | 31.12.2017                         |
| ex 3911 90 99 | 65    | Calcium zinc salt of a copolymer of maleic acid and methyl vinyl ether  | 0 %                     | 31.12.2018                         |
| ex 3911 90 99 | 86    | Copolymer of methyl vinyl ether and maleic acid anhydride (CAS RN 9011-16-9)  | 0 %                     | 31.12.2016                         |
| ex 3912 11 00 | 30    | Cellulose triacetate (CAS RN 9012-09-3)   | 0 %                     | 31.12.2016                         |
| ex 3912 11 00 | 40    | Cellulose diacetate powder  | 0 %                     | 31.12.2015                         |
| ex 3912 20 11 | 10    | Nitrocellulose (CAS RN 9004-70-0)   | 0 %                     | 31.12.2016                         |
| ex 3912 39 85 | 10    | Ethylcellulose, not plasticized   | 0 %                     | 31.12.2018                         |
| ex 3912 39 85 | 20    | Ethylcellulose, in the form of an aqueous dispersion containing hexadecan-1-ol and sodium dodecyl sulphate, containing by weight 27 (± 3) % of ethylcellulose   | 0 %                     | 31.12.2018                         |
| ex 3912 39 85 | 30    | Cellulose, both hydroxyethylated and alkylated with alkyl chain-lengths of 3 or more carbon atoms   | 0 %                     | 31.12.2018                         |
| ex 3912 39 85 | 40    | Hypromellose (INN) (CAS RN 9004-65-3)   | 0 %                     | 31.12.2016                         |
| ex 3912 90 10 | 10    | Cellulose acetate propionate, non-plasticised, in the form of powder:<br>— containing by weight 25 % or more of propionyl (as determined by the ASTM D 817-72 method) and<br>— of a viscosity of not more than 120 poise (as determined by the ASTM D 817-72 method),<br>for the manufacture of printing inks, paints, lacquers and other coatings, and reprographic coatings <sup>(1)</sup>  | 0 %                     | 31.12.2018                         |
| ex 3912 90 10 | 20    | Hydroxypropyl methylcellulose phthalate   | 0 %                     | 31.12.2018                         |
| ex 3913 90 00 | 85    | Sterile sodium hyaluronate (CAS RN 9067-32-7)   | 0 %                     | 31.12.2018                         |
| ex 3913 90 00 | 92    | Protein, chemically modified by carboxylation and/or phthalic acid addition, having a weight average molecular weight ( $M_w$ ) of 100 000 to 300 000   | 0 %                     | 31.12.2018                         |
| ex 3913 90 00 | 94    | Granules containing by weight:<br>— 35 % or more but less than 75 % of a high amylose extruded biopolymer produced from corn starch,<br>— 5 % or more but less than 16 % polyvinyl alcohol,<br>— 10 % or more but less than 46 % of polyol plasticisers,<br>— 0,25 % or more but less than 3 % of stearic acid,<br>— whether or not containing 30 % (± 10 %) of biodegradable polyester resin but never to a level that exceeds the amount of the high amylose biopolymer | 0 %                     | 31.12.2016                         |
| ex 3913 90 00 | 95    | Chondroitinsulphuric acid, sodium salt (CAS RN 9082-07-9)   | 0 %                     | 31.12.2018                         |
| ex 3913 90 00 | 96    | Powder consisting of 90 % (± 5 %) by weight of a high amylose extruded biopolymer produced from corn starch, 10 % (± 5 %) by weight of a synthetic polymer and 0,5 % (± 0,25 %) of stearic acid   | 0 %                     | 31.12.2016                         |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
| ex 3916 20 00 | 91    | Profiles of poly(vinyl chloride) of a kind used in the manufacture of sheet pilings and facings, containing the following additives:<br>— titanium dioxide<br>— poly(methyl methacrylate)<br>— calcium carbonate<br>— binding agents  | 0 %                     | 31.12.2014                         |
| ex 3916 90 10 | 10    | Rods with cellular structure, containing by weight:<br>— polyamide-6 or poly(epoxy anhydride)<br>— 7 % or more but not more than 9 % of polytetrafluoroethylene if present<br>— 10 % or more but not more than 25 % of inorganic fillers  | 0 %                     | 31.12.2018                         |
| ex 3917 32 00 | 91    | Pipe consisting of a block copolymer of polytetrafluoroethylene and polyperfluoroalkoxytrifluoroethylene, of a length of not more than 600 mm, a diameter of not more than 85 mm and a wall-thickness of 30 µm or more but not more than 110 µm   | 0 %                     | 31.12.2018                         |
| ex 3917 40 00 | 91    | Plastic connectors containing O-rings, a retainer clip and a release system for insertion into car fuel hoses   | 0 %                     | 31.12.2014                         |
| ex 3919 10 19 | 10    | Reflecting film, consisting of a layer of polyurethane, with, on one side, security imprints against counterfeiting, alteration or substitution of data or duplication, or an official mark for an intended use, and embedded glass beads and, on the other side, an adhesive layer, covered on one side or on both sides with a release film   | 0 %                     | 31.12.2018                         |
| ex 3919 10 80 | 25    |   |                         |                                    |
| ex 3919 90 00 | 31    |   |                         |                                    |
| ex 3919 10 19 | 20    | Rolls of two-sided adhesive tape:<br>— coated with non-vulcanised natural or synthetic rubber<br>— with a width of 20 mm or more but not more than 40 mm<br>— containing silicone, aluminium hydroxide, acryl and urethane  | 0 %                     | 31.12.2018                         |
| ex 3919 10 80 | 21    | Reflecting sheet, consisting of:<br>— a polycarbonate or acrylic polymer film totally embossed on one side in a regular shaped pattern,<br>— covered on both sides with one or more layers of plastic material,<br>— whether or not covered on one side with a self-adhesive layer and a release sheet  | 0 %                     | 31.12.2018                         |
| ex 3919 90 00 | 21    |   |                         |                                    |
| ex 3920 61 00 | 20    |   |                         |                                    |
| ex 3919 10 80 | 23    | Reflecting film, consisting of several layers including:<br>— poly(vinyl chloride);<br>— polyurethane with, on one side, imprints against counterfeiting, alteration or substitution of data or duplication, and on the other side, a layer of glass microspheres;<br>— a layer incorporating a security and/or official mark which changes appearance with angle of view;<br>— metallized aluminium;<br>— and adhesive, covered on one side with a release liner | 0 %                     | 31.12.2014                         |
| ex 3919 10 80 | 27    | Polyester film:   | 0 %                     | 31.12.2014                         |
| ex 3919 90 00 | 20    | — coated on one side with an acrylic thermal release adhesive that debonds at temperatures of 90 °C or more but not more than 200 °C, and a polyester liner, and<br>— on the other side not coated or coated with an acrylic pressure sensitive adhesive or with an acrylic thermal release adhesive that debonds at temperatures of 90 °C or more but not more than 200 °C, and a polyester liner  |                         |                                    |

| CN code       | TARIC | Description  | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|------------------------------------|
| ex 3919 10 80 | 30    | Double-sided, self-adhesive modified epoxy resin foil, put up in rolls, 10 to 20 cm wide, 10 to 210 m long and with a total thickness of 10 to 50 µm, not for retail sale  | 0 %                     | 31.12.2016                         |
| ex 3919 10 80 | 32    | Polytetrafluoroethylene film:<br>— with a thickness of 110 µm or more,<br>— with a surface resistance of between 10 <sup>2</sup> -10 <sup>14</sup> ohms as determined by test method ASTM D 257,<br>— coated on one side with an acrylic pressure sensitive adhesive   | 0 %                     | 31.12.2014                         |
| ex 3919 10 80 | 35    | Reflecting film, consisting of a layer of poly(vinyl chloride), a layer of alkyd polyester, with, on one side, security imprints against counterfeiting, alteration or substitution of data or duplication, or an official mark for an intended use, only visible by means of a retroreflecting lighting, and embedded glass beads and, on the other side, an adhesive layer, covered on one side or on both sides with a release film | 0 %                     | 31.12.2018                         |
| ex 3919 10 80 | 37    | Polytetrafluoroethylene film:<br>— with a thickness of 100 µm or more,<br>— an elongation at break of not more than 100 %,<br>— coated on one side with a pressure sensitive silicon adhesive  | 0 %                     | 31.12.2014                         |
| ex 3919 10 80 | 40    | Black poly(vinyl chloride) film:   | 0 %                     | 31.12.2016                         |
| ex 3919 90 00 | 43    | — with a gloss of more than 30 degrees according to ASTM D2457,<br>— whether or not covered on one side with a protective poly(ethyleneterephthalate) film, and on the other side with a pressure sensitive adhesive with channels and a release liner   |                         |                                    |
| ex 3919 10 80 | 43    | Ethylene vinyl acetate film:   | 0 %                     | 31.12.2014                         |
| ex 3919 90 00 | 26    | — of a thickness of 100 µm or more,<br>— coated on one side with an acrylic pressure sensitive or UV-sensitive adhesive and a polyester liner  |                         |                                    |
| ex 3919 10 80 | 45    | Reinforced polyethylene foam tape, coated on both sides with an acrylic micro channelled pressure sensitive adhesive and on one side a liner, with an application thickness of 0,38 mm or more but not more than 1,53 mm   | 0 %                     | 31.12.2017                         |
| ex 3919 90 00 | 45    |  |                         |                                    |
| ex 3919 10 80 | 47    | Polyester, polyurethane or polycarbonate foil:   | 0 %                     | 31.12.2017                         |
| ex 3919 90 00 | 32    | — with pressure sensitive silicone polymer adhesive,<br>— of a total thickness of not more than 0,7 mm,<br>— of a total width of 1 cm or more, but not more than 1 m,<br>— whether or not in rolls<br>of a kind used for the protection of the surface of products of headings 8521 and 8528   |                         |                                    |
| ex 3919 10 80 | 50    | Adhesive film consisting of a base of a copolymer of ethylene and vinyl acetate (EVA) of a thickness of 70 µm or more and an adhesive part of acrylic type of a thickness of 5 µm or more, for use in the grinding and/or dicing process of silicon discs <sup>(1)</sup>   | 0 %                     | 31.12.2018                         |
| ex 3919 90 00 | 41    |  |                         |                                    |
| ex 3920 10 89 | 25    |  |                         |                                    |
| ex 3919 10 80 | 53    | Polyethylene foil:   | 0 %                     | 31.12.2017                         |
| ex 3919 90 00 | 34    | — with pressure sensitive, non-rubber adhesive adhering solely to clean and smooth surfaces,   |                         |                                    |
| ex 3920 10 28 | 93    |  |                         |                                    |
| ex 3920 10 89 | 50    | — of a total thickness of 0,025 mm or more, but not more than 0,7 mm, and  |                         |                                    |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
|               |       | — of a total width of 6 cm or more, but not more than 1 m,<br>— whether or not in rolls,<br>of a kind used for the protection of the surface of products of headings 8521 and 8528  |                         |                                    |
| ex 3919 10 80 | 55    | Acrylic foam tape, covered on one side with a heat activatable adhesive or an acrylic pressure sensitive adhesive and on the other side with an acrylic pressure sensitive adhesive and a release sheet, of a peel adhesion at an angle of 90 ° of more than 25 N/cm (as determined by the ASTM D 3330 method)                  | 0 %                     | 31.12.2017                         |
| ex 3919 90 00 | 53    |   |                         |                                    |
| ex 3919 10 80 | 60    | Reflecting laminated sheet showing a regular pattern, consisting of a film of poly(methylmethacrylate), followed by a layer of acrylic polymer containing microprisms, a film of poly(methylmethacrylate), an adhesive layer and a release sheet  | 0 %                     | 31.12.2018                         |
| ex 3919 10 80 | 65    | Self-adhesive reflecting sheet whether or not in segmented pieces:  | 0 %                     | 31.12.2018                         |
| ex 3919 90 00 | 57    | — showing a regular pattern,<br>— with or without an application tape layer,<br>— consisting of a film of acrylic polymer followed by a layer of poly(methyl methacrylate) containing microprisms,<br>— whether or not containing an additional layer of polyester and<br>— an adhesive with a final release sheet              |                         |                                    |
| ex 3919 10 80 | 70    | Rolls of polyethylene foil:   | 0 %                     | 31.12.2016                         |
| ex 3919 90 00 | 75    | — self-adhesive on one side,<br>— of a total thickness of 0,025 mm or more, but not more than 0,09 mm,<br>— of a total width of 60 mm or more, but not more than 1 110 mm,<br>of a kind used for the protection of the surface of products of headings 8521 or 8528   |                         |                                    |
| ex 3919 10 80 | 75    | Self-adhesive reflecting film, consisting of several layers including:  | 0 %                     | 31.12.2016                         |
| ex 3919 90 00 | 80    | — a copolymer of acrylic resin,<br>— polyurethane,<br>— a metalised layer with, on one side, laser imprints against counterfeiting, alteration or substitution of data or duplications, or an official mark for an intended use,<br>— glass microspheres, and<br>— an adhesive layer, with a release liner on one or both sides |                         |                                    |
| ex 3919 10 80 | 80    | Acrylic tape put up in rolls:   | 0 %                     | 31.12.2016                         |
| ex 3919 90 00 | 83    | — self-adhesive on both sides,<br>— of a total thickness of 0,04 mm or more, but not more than 1,25 mm,<br>— of a total width of 5 mm or more but not more than 1 205 mm<br>for use in the manufacture of products of headings 8521 and 8528 <sup>(1)</sup>   |                         |                                    |
| ex 3919 10 80 | 85    | Poly(vinyl chloride) or polyethylene or any other polyolefine film:   | 0 %                     | 31.12.2014                         |
| ex 3919 90 00 | 28    | — of a thickness of 65 µm or more,<br>— coated on one side with an acrylic UV-sensitive adhesive and a polyester liner  |                         |                                    |
| ex 3919 90 00 | 19    | Transparent poly(ethylene terephthalate) self-adhesive film:<br>— free from impurities or faults,<br>— coated on one side with an acrylic pressure sensitive adhesive and a protective liner, and on the other side with an antistatic layer of ionic organic choline compound,   | 0 %                     | 31.12.2018                         |

| CN code                        | TARIC    | Description  | Rate of autonomous duty | Date foreseen for mandatory review |
|--------------------------------|----------|--|-------------------------|------------------------------------|
| ex 3919 90 00                  | 22       | <ul style="list-style-type: none"> <li>— whether or not with a printable dust-proof layer of modified long chain alkyl organic compound,</li> <li>— with a total thickness without the liner of 54 µm or more but not more than 64 µm, and</li> <li>— a width of more than 1 295 mm but not more than 1 305 mm</li> </ul> Black polypropylene film: <ul style="list-style-type: none"> <li>— with a gloss of more than 20 degrees as determined by test method ASTM D2457,</li> <li>— whether or not covered on one side with a protective poly(ethylene terephthalate) film and on the other side with a pressure sensitive adhesive with channels and a release liner</li> </ul> | 0 %                     | 31.12.2014                         |
| ex 3919 90 00                  | 23       | Film consisting of 1 to 3 laminated layers of poly(ethylene terephthalate) and a copolymer of terephthalic acid, sebacic acid and ethylene glycol, coated on one side with an acrylic abrasion resistant coating and on the other side with an acrylic pressure sensitive adhesive, a water soluble methylcellulose coating and a poly(ethylene terephthalate) protective liner  | 0 %                     | 31.12.2018                         |
| ex 3919 90 00                  | 24       | Reflecting laminated sheet: <ul style="list-style-type: none"> <li>— consisting of an epoxy acrylate layer embossed on one side in a regular shaped pattern,</li> <li>— covered on both sides with one or more layers of plastic material and</li> <li>— covered on one side with an adhesive layer and a release sheet</li> </ul>   | 0 %                     | 31.12.2014                         |
| ex 3919 90 00                  | 25       | Film consisting of a multi-layer construction of poly(ethylene terephthalate) and copolymer of butylacrylate and methylmethacrylate, coated on one side with an acrylic abrasion resistant coating incorporating nanoparticles of antimony tin oxide and carbon black, and on the other side with an acrylic pressure sensitive adhesive and a silicone-coated poly(ethylene terephthalate) protective liner   | 0 %                     | 31.12.2017                         |
| ex 3919 90 00                  | 27       | Poly(ethylene terephthalate) film, with an adhesive strength of not more than 0,147 N/25 mm and an electrostatic discharge of not more than 500 V  | 0 %                     | 31.12.2018                         |
| ex 3919 90 00                  | 29       | Polyester film coated on both sides with an acrylic and/or rubber (pressure sensitive) adhesive put up in rolls of a width of 45,7 cm or more but not more than 132 cm (supplied with a release liner)   | 0 %                     | 31.12.2014                         |
| ex 3919 90 00                  | 33       | Transparent poly(ethylene) self-adhesive film, free from impurities or faults, coated on one side with an acrylic pressure sensitive adhesive, with a thickness of 60 µm or more, but not more than 70 µm, and with a width of more than 1 245 mm but not more than 1 255 mm   | 0 %                     | 31.12.2018                         |
| ex 3919 90 00                  | 35       | Reflecting layered sheet on rolls, with a width of more than 20 cm, showing an embossed regular pattern, consisting of poly(vinyl chloride) film coated on one side with: <ul style="list-style-type: none"> <li>— a layer of polyurethane containing glass micro beads,</li> <li>— a layer of poly(ethylene vinyl acetate),</li> <li>— an adhesive layer, and</li> <li>— a release sheet</li> </ul>   | 0 %                     | 31.12.2018                         |
| ex 3919 90 00<br>ex 3920 49 10 | 36<br>95 | Printed laminated sheet with a central layer of poly(vinyl chloride), coated on both sides with a layer of poly(vinyl fluoride) <ul style="list-style-type: none"> <li>— whether or not with a pressure or heat sensitive adhesive layer</li> <li>— whether or not with a release film</li> </ul>  | 0 %                     | 31.12.2017                         |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
|               |       | <ul style="list-style-type: none"> <li>— with a toxicity (as determined by test method ABD 0031) of not more than 70 ppm hydrogen fluoride, not more than 120 ppm hydrogen chloride, not more than 10 ppm hydrogen cyanide, not more than 10 ppm nitrogen oxides, not more than 300 ppm carbon monoxide and not more than 10 ppm dihydrogen sulphide and sulphur dioxide taken together</li> <li>— with a flammability within 60 seconds of not more than 130 mm (as determined by test method FAR 25 App.F Pt. I Amdt.83)</li> <li>— with a weight (without release film) of 240 g/m<sup>2</sup> (± 30 g/m<sup>2</sup>) without adhesive layer, of 340 g/m<sup>2</sup> (± 40 g/m<sup>2</sup>) with heat sensitive adhesive layer or of 330 g/m<sup>2</sup> (± 40 g/m<sup>2</sup>) with pressure sensitive layer</li> </ul> |                         |                                    |
| ex 3919 90 00 | 37    | <p>UV-absorbing film of poly (vinyl chloride):</p> <ul style="list-style-type: none"> <li>— with a thickness of 78 µm or more,</li> <li>— covered on one side with an adhesive layer and with a release sheet,</li> <li>— with an adhesive strength of 1 764 mN / 25 mm or more</li> </ul>  | 0 %                     | 31.12.2014                         |
| ex 3919 90 00 | 38    | <p>Self-adhesive film composed of:</p> <ul style="list-style-type: none"> <li>— a top layer predominantly of polyurethane mixed with acrylic polymer emulsions and titanium dioxide,</li> <li>— whether or not containing a second layer of a mixture of vinyl acetate-ethylene copolymer and cross-linkable vinyl acetate polymer emulsions,</li> <li>— not more than 6 % by weight of other additives,</li> <li>— a pressure sensitive adhesive; and</li> <li>— covered on one side with a release liner,</li> <li>— whether or not with a separate self-adhesive over laminate protective film,</li> <li>— of a total thickness of not more than 400 µm</li> </ul>   | 0 %                     | 31.12.2017                         |
| ex 3919 90 00 | 39    | <p>Poly(vinyl chloride) sheeting, of a thickness of less than 1 mm, coated with an adhesive in which are embedded glass balls of a diameter of not more than 100 µm</p>   | 0 %                     | 31.12.2018                         |
| ex 3919 90 00 | 40    | <p>Film, with a total thickness of 40 µm or more, consisting of one or more layers of transparent polyester film:</p> <ul style="list-style-type: none"> <li>— containing at least one infrared reflective layer with a total normal reflectance according to EN 12898 of 80 % or more</li> <li>— having on one side a layer with a normal emissivity according to EN 12898 of not more than 0,2</li> <li>— coated on the other side with a pressure sensitive adhesive and a release liner</li> </ul>  | 0 %                     | 31.12.2017                         |
| ex 3919 90 00 | 42    | <p>Self-adhesive film composed of:</p> <ul style="list-style-type: none"> <li>— a first layer containing a mixture of thermoplastic polyurethane and anti-blocking agent,</li> <li>— a second layer containing a maleic anhydride copolymer,</li> <li>— a third layer containing a mixture of low density polyethylene, titanium dioxide and additives,</li> <li>— a fourth layer containing a mixture of low density polyethylene, titanium dioxide, additives and colour pigment,</li> <li>— a pressure sensitive adhesive; and</li> <li>— covered on one side with a release liner</li> <li>— whether or not with a separate self-adhesive over laminate protective film</li> <li>— of a total thickness of not more than 400 µm</li> </ul>  | 0 %                     | 31.12.2017                         |

| CN code       | TARIC | Description  | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|------------------------------------|
| ex 3919 90 00 | 44    | Printed laminated sheet  | 0 %                     | 31.12.2017                         |
| ex 3921 90 60 | 95    | <ul style="list-style-type: none"> <li>— with a core layer of glass fabric, coated on each side with a layer of poly(vinyl chloride),</li> <li>— on one side covered with a layer of poly(vinyl fluoride),</li> <li>— whether or not with a pressure sensitive adhesive layer and a release film on the other side,</li> <li>— with a toxicity (as determined by test method ABD 0031) of not more than 50 ppm hydrogen fluoride, not more than 85 ppm hydrogen chloride, not more than 10 ppm hydrogen cyanide, not more than 10 ppm nitrogen oxides, not more than 300 ppm carbon monoxide and not more than 10 ppm dihydrogen sulphide and sulphur dioxide taken together,</li> <li>— with a flammability within 60 seconds of not more than 110 mm (as determined by test method FAR 25 App.F Pt. I Amdt.83), and</li> <li>— with a weight (without release film) of 490 g/m<sup>2</sup> (± 45 g/m<sup>2</sup>) without adhesive layer or of 580 g/m<sup>2</sup> (± 50 g/m<sup>2</sup>) with pressure sensitive layer</li> </ul> |                         |                                    |
| ex 3919 90 00 | 47    | Polariser film, in rolls, consisting of a multilayered polyvinyl alcohol film, supported on either side by a triacetyl cellulose film, with a pressure sensitive adhesive and release film on one side   | 0 %                     | 31.12.2017                         |
| ex 9001 20 00 | 40    |  |                         |                                    |
| ex 3919 90 00 | 49    | Reflecting laminated sheet consisting of a film of poly(methyl methacrylate) embossed on one side in a regular shaped pattern, a film of a polymer containing glass microspheres, an adhesive layer and a release sheet  | 0 %                     | 31.12.2018                         |
| ex 3919 90 00 | 51    | Biaxially-oriented film of poly(methyl methacrylate), of a thickness of 50 µm or more but not exceeding 90 µm, covered on one side with an adhesive layer and a release sheet  | 0 %                     | 31.12.2018                         |
| ex 3919 90 00 | 60    | Reflecting film containing: <ul style="list-style-type: none"> <li>— a poly(vinyl chloride) layer,</li> <li>— a polyurethane layer,</li> <li>— a glass microspheres layer,</li> <li>— a layer whether or not incorporating a security and/or official mark which changes appearance with angle of view,</li> <li>— a metallised aluminium layer, and</li> <li>— an adhesive, covered on one side with a release liner</li> </ul>   | 0 %                     | 31.12.2015                         |
| ex 3919 90 00 | 63    | Co-extruded trilayer film, <ul style="list-style-type: none"> <li>— each layer containing a mixture of polypropylene and polyethylene,</li> <li>— containing not more than 3 % by weight of other polymers,</li> <li>— whether or not containing titanium dioxide in the core layer,</li> <li>— coated with an acrylic pressure sensitive adhesive and</li> <li>— with a release liner</li> <li>— of an overall thickness of not more than 110 µm</li> </ul>   | 0 %                     | 31.12.2015                         |
| ex 3919 90 00 | 65    | Self-adhesive film with a thickness of 40 µm or more, but not more than 400 µm, consisting of one or more layers of transparent, metallised or dyed poly(ethylene terephthalate), covered on one side with a scratch resistant coating and on the other side with a pressure sensitive adhesive and a release liner  | 0 %                     | 31.12.2015                         |
| ex 3919 90 00 | 70    | Self-adhesive polishing discs of microporous polyurethane, whether or not coated with a pad  | 0 %                     | 31.12.2015                         |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
| ex 3919 90 00 | 81    | Film of a minimum thickness of 0,36 mm, consisting of the following:<br>— an embossed polyester layer,<br>— a caprolactone-cyclohexylene isocyanate copolymer layer,<br>— a pressure sensitive adhesive<br>and covered on one side with a release liner   | 0 %                     | 31.12.2018                         |
| ex 3919 90 00 | 85    | Multi-layered film of poly(methyl methacrylate) and metallised layers of silver and copper:<br>— having a minimum reflectance of 93,5 % as determined by ASTM G173-03,<br>— covered on one side with a removable layer of polyethylene,<br>— covered on the other side with an acrylic pressure sensitive adhesive and a siliconised polyester liner  | 0 %                     | 31.12.2016                         |
| ex 3919 90 00 | 87    | Self-adhesive transparent film, having a transmittance of more than 90 % and a haze of less than 3 % (as determined by ASTM D1003), consisting of several layers including:<br>— an acrylic adhesive layer with a thickness of 20 µm or more but not more than 70 µm,<br>— a polyurethane based layer with a thickness of 100 µm or more but not more than 300 µm   | 0 %                     | 31.12.2016                         |
| ex 3920 10 25 | 10    | Film of a thickness of not more than 0,20 mm, of a blend of polyethylene and a copolymer of ethylene with oct-1-ene, embossed in a regular rhomboidal pattern, for coating both sides of a layer of unvulcanized rubber (!)   | 0 %                     | 31.12.2018                         |
| ex 3920 10 89 | 20    |   |                         |                                    |
| ex 3920 10 25 | 20    | Film of polyethylene, of a kind used for typewriter ribbon  | 0 %                     | 31.12.2018                         |
| ex 3920 10 28 | 91    | Poly(ethylene) film printed with a graphic design, which is achieved by using four base colours in ink plus specialist colours, to achieve multiple colours in ink on one side of the film, and one colour on the opposite side, the graphic design also has the following characteristics:<br>— is repetitive and equally spaced along the length of the film<br>— is equally and visibly aligned when viewed from the back or front of the film | 0 %                     | 31.12.2018                         |
| ex 3920 10 40 | 30    | Co-extruded seven to nine layered film predominately of copolymers of ethylene or functionalized polymers of ethylene, consisting of:<br>— a tri-layer barrier with a core layer predominantly of ethylene vinyl alcohol covered on either side with a layer predominantly of cyclic olefin polymers,<br>— covered on either side with two or more layers of polymeric material, and having an overall total thickness of not more than 110 µm    | 0 %                     | 31.12.2017                         |
| ex 3920 10 89 | 30    | Ethylene vinyl acetate (EVA) film with:<br>— a raised relief surface with embossed undulations, and<br>— a thickness of more than 0,125 mm  | 0 %                     | 31.12.2016                         |
| ex 3920 10 89 | 40    | Composite sheet containing an acrylic coating and laminated to a high-density polyethylene layer, of a total thickness of 0,8 mm or more but not more than 1,2 mm   | 0 %                     | 31.12.2016                         |
| ex 3920 20 21 | 30    | Biaxially oriented polypropylene film with a coextruded layer of polyethylene on one side and a total thickness of 11,5 µm or more but not more than 13,5 µm  | 0 %                     | 31.12.2018                         |
| ex 3920 20 21 | 40    | Sheets of biaxially - oriented polypropylene film:<br>— with the thickness of not more than 0,1 mm,<br>— printed on both sides with specialised coatings to allow banknote security printing  | 0 %                     | 31.12.2016                         |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
| ex 3920 20 29 | 50    | Sheet of polypropylene in the form of a roll:   | 0 %                     | 31.12.2016                         |
| ex 8507 90 30 | 95    | — with a thickness of not more than 30 µm,<br>— of a width of not more than 210 mm,<br>— conforming to ASTM D882,<br>for use in the manufacture of separators for lithium-ion electric vehicle batteries (!)  |                         |                                    |
| ex 3920 20 29 | 55    | Co-extruded seven to nine layered film predominately of copolymers of propylene, consisting of:   | 0 %                     | 31.12.2017                         |
| ex 3920 20 80 | 93    | — a tri-layer barrier with a core layer predominantly of ethylene vinyl alcohol covered on either side with a layer predominantly of cyclic olefin polymers,<br>— covered on either side with two or more layers of polymeric material, and having an overall total thickness of not more than 110 µm   |                         |                                    |
| ex 3920 20 29 | 92    | Mono-axial oriented film, of a total thickness of not more than 75 µm, consisting of two or three layers, each layer containing a mixture of polypropylene and polyethylene, with a core layer whether or not containing titanium dioxide, having:<br>— a tensile strength in the machine direction of 140 MPa or more but not more than 270 MPa and<br>— a tensile strength in the transverse direction of 20 MPa or more but not more than 40 MPa<br>as determined by test method ASTM D882/ISO 527-3 | 0 %                     | 31.12.2018                         |
| ex 3920 20 29 | 93    | Mono-axial oriented film, consisting of three layers, each layer consisting of a mixture of polypropylene and a copolymer of ethylene and vinyl acetate, having:<br>— a thickness of 55 µm or more but not more than 97 µm,<br>— a tensile modulus in the machine direction of 0,75 GPa or more but not more than 1,45 GPa, and<br>— a tensile modulus in the transverse direction of 0,20 GPa or more but not more than 0,55 GPa   | 0 %                     | 31.12.2014                         |
| ex 3920 20 29 | 94    | Co-extruded trilayer film,<br>— each layer containing a mixture of polypropylene and polyethylene,<br>— containing not more than 3 % by weight of other polymers,<br>— whether or not containing titanium dioxide in the core layer,<br>— of an overall thickness of not more than 70 µm  | 0 %                     | 31.12.2016                         |
| ex 3920 20 80 | 92    | Laminated sheet or strip, consisting of a film of a thickness of 181 µm or more but not more than 223 µm composed of a blend of a copolymer of propylene with ethylene and a copolymer of styrene-ethylene-butylene-styrene (SEBS) coated or covered on one side with a layer of a copolymer of styrene-ethylene-butylene-styrene (SEBS) and a layer of polyester   | 0 %                     | 31.12.2018                         |
| ex 3920 20 80 | 95    | Polypropylene sheet, put up in rolls, with:<br>— flame retardant level of UL 94 V-0 for material thicknesses of 0,25 mm or more and level UL 94 VTM-0 for material thicknesses of 0,05 mm or more but not more than 0,25 mm (as determined by Flammability Standard UL-94)<br>— dielectric breakdown of 13,1 kV or more but not more than 60,0 kV(as determined by ASTM D149)<br>— tensile yield in a machine direction of 30 MPa or more but not more than 33 MPa (as determined by ASTM D882)         | 0 %                     | 31.12.2017                         |

| CN code       | TARIC | Description  | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|------------------------------------|
|               |       | <p>— tensile yield in a transverse direction of 22 MPa or more but not more than 25 MPa (as determined by ASTM D882)</p> <p>— density range of 0,988 g/cm<sup>3</sup> or more but not more than 1,035 g/cm<sup>3</sup> (as determined by ASTM D792)</p> <p>— moisture absorption of 0,01 % or more but not more than 0,06 % (as determined by ASTM D570)</p> <p>for use in the manufacture of insulators used in the electronics and electrical industries <sup>(1)</sup></p>                                      |                         |                                    |
| ex 3920 43 10 | 92    | Sheeting of poly(vinyl chloride), stabilized against ultraviolet rays, without any holes, even microscopic, of a thickness of 60 µm or more but not more than 80 µm, containing 30 or more but not more than 40 parts of plasticizer to 100 parts of poly(vinyl chloride)  | 0 %                     | 31.12.2018                         |
| ex 3920 43 10 | 94    | Film of a specular gloss of 70 or more, measured at an angle of 60 ° using a glossmeter (as determined by the ISO 2813:2000 method), consisting of one or two layers of poly(vinyl chloride) coated on both sides with a layer of plastic, of a thickness of 0,26 mm or more but not more than 1,0 mm, covered on the gloss surface with a protective film of polyethylene, in rolls of a width of 1 000 mm or more but not more than 1 450 mm, for use in the manufacture of goods of heading 9403 <sup>(1)</sup> | 0 %                     | 31.12.2018                         |
| ex 3920 49 10 | 93    |  |                         |                                    |
| ex 3920 43 10 | 95    | Reflecting laminated sheet, consisting of a film of poly(vinyl chloride) and a film of an other plastic totally embossed in a regular pyramidal pattern, covered on one side with a release sheet  | 0 %                     | 31.12.2018                         |
| ex 3920 49 10 | 30    | Film of a (polyvinyl)chloride-copolymer<br>— containing by weight 45 % or more of fillers<br>— on a support <sup>(1)</sup>   | 0 %                     | 31.12.2018                         |
| ex 3920 51 00 | 20    | Plate of poly(methyl methacrylate) containing aluminium trihydroxide, of a thickness of 3,5 mm or more but not more than 19 mm   | 0 %                     | 31.12.2018                         |
| ex 3920 51 00 | 30    | Biaxially-oriented film of poly(methyl methacrylate), of a thickness of 50 µm or more but not exceeding 90 µm  | 0 %                     | 31.12.2018                         |
| ex 3920 51 00 | 40    | Sheets of polymethylmethacrylate conforming to standard EN 4366 (MIL-PRF-25690)  | 0 %                     | 31.12.2018                         |
| ex 3920 59 90 | 10    | Non-cellular and non-laminated sheet of modified copolymer of acrylonitrile-methyl acrylate with a thickness of 1,0 mm or more but not more than 1,3 mm, put up in rolls   | 0 %                     | 31.12.2016                         |
| ex 3920 59 90 | 20    | Reflecting laminated sheet, consisting of an epoxy acrylate layer embossed on one side in a regular shaped pattern, covered on both sides with one or more layers of plastic material  | 0 %                     | 31.12.2014                         |
| ex 3920 59 90 | 30    | Non-self-adhesive reflecting film, consisting of several layers including:<br>— a copolymer of acrylic resin<br>— polyurethane<br>— a metallised layer with, on one side, laser imprints against counterfeiting, alteration or substitution of data or duplications, or an official mark for an intended use<br>— glass microspheres, and<br>— a permanent liner of poly(ethyleneterephthalate)  | 0 %                     | 31.12.2016                         |
| ex 3920 62 19 | 02    | Coextruded opaque sheet of poly(ethylene terephthalate), of a thickness of 50 µm or more but not more than 350 µm, consisting especially of a layer containing carbon black  | 0 %                     | 31.12.2018                         |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
| ex 3920 62 19 | 08    | Poly(ethylene terephthalate) film, not coated with an adhesive, of a thickness of not more than 25 µm, either:<br>— only dyed in the mass, or<br>— dyed in the mass and metallised on one side  | 0 %                     | 31.12.2018                         |
| ex 3920 62 19 | 12    | Film of poly(ethylene terephthalate) only, of a total thickness of not more than 120 µm, consisting of one or two layers each containing a colouring and/or UV-absorbing material throughout the mass, uncoated with an adhesive or any other material  | 0 %                     | 31.12.2018                         |
| ex 3920 62 19 | 18    | Laminated film of poly(ethylene terephthalate) only, of a total thickness of not more than 120 µm, consisting of one layer which is metallised only and one or two layers each containing a colouring and/or UV-absorbing material throughout the mass, uncoated with an adhesive or any other material   | 0 %                     | 31.12.2018                         |
| ex 3920 62 19 | 20    | Reflecting polyester sheeting embossed in a pyramidal pattern, for the manufacture of safety stickers and badges, safety clothing and accessories thereof, or of school satchels, bags or similar containers <sup>(1)</sup>   | 0 %                     | 31.12.2018                         |
| ex 3920 62 19 | 25    | Film of poly(ethylene terephthalate) of a thickness of 186 µm or more but not more than 191 µm coated on one side with an acrylic layer in a matrix pattern   | 0 %                     | 31.12.2014                         |
| ex 3920 62 19 | 38    | Poly(ethylene terephthalate) film, of a thickness of not more than 12 µm, coated on one side with a layer of aluminium oxide of a thickness of not more than 35 nm  | 0 %                     | 31.12.2018                         |
| ex 3920 62 19 | 48    | Sheets or rolls of poly(ethylene terephthalate):<br>— coated on both sides with a layer of epoxy acrylic resin,<br>— of a total thickness of 37 µm (± 3 µm)   | 0 %                     | 31.12.2015                         |
| ex 3920 62 19 | 52    | Film of poly(ethylene terephthalate), poly(ethylene naphthalate) or similar polyester, coated on one side with metal and/or metal oxides, containing by weight less than 0,1 % of aluminium, of a thickness of not more than 300 µm and having a surface resistivity of not more than 10 000 ohms (per square) (as determined by the ASTM D 257-99 method)  | 0 %                     | 31.12.2018                         |
| ex 3920 62 19 | 73    | Iridescent film of polyester and poly(methyl methacrylate)  | 0 %                     | 31.12.2018                         |
| ex 3920 69 00 | 40    |   |                         |                                    |
| ex 3920 62 19 | 76    | Transparent poly(ethylene terephthalate) film:<br>— coated on both sides with layers of organic substances on the basis of acryl of a thickness of 7 nm or more but not more than 80 nm,<br>— with a surface tension of 36 Dyne/cm or more but not more than 39 Dyne/cm,<br>— with a light transmission of more than 93 %,<br>— with a haze value of not more than 1,3 %,<br>— with a total thickness of 10 µm or more but not more than 350 µm,<br>— with a width of 800 mm or more but not more than 1 600 mm | 0 %                     | 31.12.2018                         |
| ex 3920 62 19 | 81    | Poly(ethylene terephthalate) film:<br>— of a thickness of not more than 20 µm,<br>— coated on at least one side with a gas barrier layer consisting of a polymeric matrix in which silica has been dispersed and of a thickness of not more than 2 µm   | 0 %                     | 31.12.2017                         |
| ex 3920 69 00 | 20    | Film of poly(ethylene naphthalene-2,6-dicarboxylate)  | 0 %                     | 31.12.2018                         |
| ex 3920 91 00 | 51    | Poly(vinyl butyral) film containing by weight 25 % or more but not more than 28 % of tri-isobutyl phosphate as a plasticizer  | 0 %                     | 31.12.2014                         |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
| ex 3920 91 00 | 52    | Poly(vinyl butyral) film:<br>— containing by weight 26 % or more but not more than 30 % of triethyleneglycol bis(2-ethyl hexanoate) as a plasticizer,<br>— with a thickness of 0,73 mm or more but not more than 1,50 mm  | 0 %                     | 31.12.2014                         |
| ex 3920 91 00 | 91    | Poly(vinyl butyral) film having a graduated coloured band   | 3 %                     | 31.12.2018                         |
| ex 3920 91 00 | 92    | Plasticised film of polyvinyl butyral, containing by weight:<br>— either 14,5 % or more but not more than 17,5 % of dihexyl adipate,<br>— or 14,5 % or more but not more than 28,5 % of dibutyl sebacate  | 0 %                     | 31.12.2014                         |
| ex 3920 91 00 | 93    | Film of poly(ethylene terephthalate), whether or not metallised on one or both sides, or laminated film of poly(ethylene terephthalate) films, metallised on the external sides only, and having the following characteristics:<br>— a visible light transmission of 50 % or more,<br>— coated on one or both sides with a layer of poly(vinyl butyral) but not coated with an adhesive or any other material except poly(vinyl butyral),<br>— a total thickness of not more than 0,2 mm without taking the presence of poly(vinyl butyral) into account and a thickness of poly(vinyl butyral) of more than 0,2 mm<br>for use in the manufacture of heat-reflecting or decorative laminated glass <sup>(1)</sup> | 0 %                     | 31.12.2014                         |
| ex 3920 91 00 | 95    | Co-extruded trilayer poly(vinyl butyral) film with a graduated colour band containing by weight 29 % or more but not more than 31 % of 2,2'-ethylenedioxydiethyl bis(2-ethylhexanoate) as a plasticiser   | 0 %                     | 31.12.2018                         |
| ex 3920 92 00 | 30    | Polyamide film:<br>— of a thickness of not more than 20 µm,<br>— coated on at least one side with a gas barrier layer which consists of a polymeric matrix in which silica has been dispersed and of a thickness of not more than 2 µm  | 0 %                     | 31.12.2018                         |
| ex 3920 99 28 | 35    | Polyether imide sheets, in rolls, with<br>— a thickness of 5 µm or more, but not more than 14 µm,<br>— a width of 478 mm or more, but not more than 532 mm,<br>— a tensile strength at break of 78 MPa or more (as determined by JIS C-2318 for a film thickness of 50 µm),<br>— an elongation at break of 50 % or more (as determined by JIS C-2318 for a film thickness of 50 µm),<br>— a glass transition point (Tg) of 226 °C,<br>— a continuous service temperature of 180 °C (as determined by UL-746 B for a film thickness of 50 µm),<br>— a flammability of VTM-0 (as determined by UL 94 for a film thickness of 25 µm)   | 0 %                     | 31.12.2018                         |
| ex 3920 99 28 | 40    | Polymer film containing the following monomers:<br>— poly (tetramethylene ether glycol),<br>— bis (4-isocyanotocyclohexyl) methane,<br>— 1,4-butanediol or 1,3-butanediol,<br>— with a thickness of 0,25 mm or more but not more than 5,0 mm,<br>— embossed with a regular pattern on one surface,<br>— and covered with a release sheet  | 0 %                     | 31.12.2018                         |
| ex 3920 99 28 | 45    | Transparent polyurethane film metallised on one side:<br>— with a gloss of more than 90 degrees according to ASTM D2457<br>— covered on the metalized side with a heat bonding adhesive layer consisting of polyethylene/polypropylene copolymer  | 0 %                     | 31.12.2018                         |

| CN code       | TARIC | Description  | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|------------------------------------|
| ex 3920 99 28 | 50    | — covered on the other side with a protective poly(ethylene terephthalate) film<br>— with a total thickness of more than 204 µm but not more than 244 µm<br>Thermoplastic polyurethane film, of a thickness of 250 µm or more but not more than 350 µm, covered on one side with a removable protective film   | 0 %                     | 31.12.2016                         |
| ex 3920 99 28 | 55    | Thermoplastic polyurethane film extruded, with:<br>— not self-adhesive,<br>— an index of yellow lower of more than 1,0 but not more than 2,5 for 10 mm stacked films (as determined by test method ASTM E 313-10),<br>— a light transmission higher to 87 % for 10 mm stacked films (as determined by test method ASTM D 1003-11),<br>— a total thickness of 0,38 mm or more, but not more than 7,6 mm,<br>— a width of 99 cm or more, but not more than 305 cm,<br>of a kind used in the production of laminated safety glass | 0 %                     | 31.12.2017                         |
| ex 3920 99 28 | 60    | Silicone tape, plate or strip:<br>— of a total thickness of 2 mm or more, but not more than 9 mm,<br>— of a total width of 12 mm or more, but not more than 65 mm,<br>for use in the manufacture of products of headings 8521 or 8528 (1)  | 0 %                     | 31.12.2016                         |
| ex 3920 99 28 | 70    | Sheets on rolls, consisting of epoxy resin, with conducting properties, containing:<br>— microspheres with a coating of metal, whether or not alloyed with gold,<br>— an adhesive layer,<br>— with a protective layer of silicone or poly(ethylene terephthalate) on one side,<br>— with a protective layer of poly(ethylene terephthalate) on the other side, and<br>— with a width of 5 cm or more but not more than 100 cm<br>— with a length of not more than 2 000 m  | 0 %                     | 31.12.2016                         |
| ex 3920 99 59 | 25    | Poly(1-chlorotrifluoroethylene) film   | 0 %                     | 31.12.2018                         |
| ex 3920 99 59 | 50    | Polytetrafluoroethylene film, non-microporous, in the form of rolls, of a thickness of 0,019 mm or more but not more than 0,14 mm, impermeable to water vapour   | 0 %                     | 31.12.2018                         |
| ex 3920 99 59 | 55    | Ion-exchange membranes of fluorinated plastic material   | 0 %                     | 31.12.2018                         |
| ex 3920 99 59 | 60    | Film of a vinyl alcohol copolymer, soluble in cold water, of a thickness of 34 µm or more but not more than 90 µm, a tensile strength at break of 20 MPa or more but not more than 45 MPa and an elongation at break of 250 % or more but not more than 900 %  | 0 %                     | 31.12.2018                         |
| ex 3920 99 90 | 20    | Anisotropic conductive film, in rolls, of a width of 1,5 mm or more but not more than 3,15 mm and a maximum length of 300 m, used for joining electronic components in the production of LCD or plasma displays  | 0 %                     | 31.12.2018                         |
| ex 3921 13 10 | 10    | Sheet of polyurethane foam, of a thickness of 3 mm (± 15 %) and of a specific gravity of 0,09435 or more but not more than 0,10092   | 0 %                     | 31.12.2018                         |
| ex 3921 13 10 | 20    | Rolls of open-cell polyurethane foam:<br>— with a thickness of 2,29 mm (± 0,25 mm),<br>— surface-treated with a foraminous adhesion promoter, and<br>— laminated to a polyester film and a layer of textile material   | 0 %                     | 31.12.2017                         |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
| ex 3921 19 00 | 30    | Blocks with cellular structure, containing by weight:<br>— polyamide-6 or poly(epoxy anhydride)<br>— 7 % or more but not more than 9 % of polytetrafluoroethylene if present<br>— 10 % or more but not more than 25 % of inorganic fillers  | 0 %                     | 31.12.2018                         |
| ex 3921 19 00 | 91    | Microporous polypropylene film of a thickness of not more than 100 µm   | 0 %                     | 31.12.2018                         |
| ex 3921 19 00 | 93    | Strip of microporous polytetrafluoroethylene on a support of a non-woven, for use in the manufacture of filters for kidney dialysis equipment <sup>(1)</sup>  | 0 %                     | 31.12.2018                         |
| ex 3921 19 00 | 95    | Film of polyethersulfone, of a thickness of not more than 200 µm  | 0 %                     | 31.12.2018                         |
| ex 3921 19 00 | 96    | Cellular film, consisting of a layer of polyethylene of a thickness of 90 µm or more but not more than 140 µm and a layer of regenerated cellulose of a thickness of 10 µm or more but not more than 40 µm  | 0 %                     | 31.12.2018                         |
| ex 3921 90 10 | 10    | Composite plate of poly(ethylene terephthalate) or of poly(butylene terephthalate), reinforced with glass fibres  | 0 %                     | 31.12.2018                         |
| ex 3921 90 10 | 20    | Poly(ethylene terephthalate) film, laminated on one side or on both sides with a layer of unidirectional nonwoven poly(ethylene terephthalate) and impregnated with polyurethane or epoxide resin   | 0 %                     | 31.12.2018                         |
| ex 3921 90 55 | 20    | Pre-impregnated reinforced fibreglass containing cyanate ester resin or bismaleimide (B) triazine (T) resin mixed with epoxide resin, measuring:<br>— 469,9 mm (± 2 mm) × 622,3 mm (± 2 mm), or<br>— 469,9 mm (± 2 mm) × 414,2 mm (± 2 mm), or<br>— 546,1 mm (± 2 mm) × 622,3 mm (± 2 mm)<br>for use in the manufacture of printed circuit boards <sup>(1)</sup>  | 0 %                     | 31.12.2018                         |
| ex 3921 90 55 | 25    | Prepreg sheets or rolls containing polyimide resin  | 0 %                     | 31.12.2014                         |
| ex 7019 40 00 | 20    |   |                         |                                    |
| ex 3921 90 55 | 30    | Prepreg sheets or rolls containing brominated epoxy resin reinforced with glass fabric, having<br>— a flow of not more than 3,6 mm (as determined by IPC-TM 650.2.3.17.2), and<br>— a glass transition temperature (T <sub>g</sub> ) of more than 170 °C (as determined by IPC-TM 650.2.4.25)<br>for use in the manufacture of printed circuit boards <sup>(1)</sup>  | 0 %                     | 31.12.2014                         |
| ex 3921 90 60 | 91    | Woven polytetrafluoroethylene fabric, coated or covered with a copolymer of tetrafluoroethylene and trifluoroethylene having perfluorinated alkoxy side-chains ending in carboxylic acid or sulphonic acid groups, whether or not in the potassium or sodium salt form  | 0 %                     | 31.12.2018                         |
| ex 5407 71 00 | 20    |   |                         |                                    |
| ex 5903 90 99 | 10    |   |                         |                                    |
| ex 3921 90 60 | 93    | Film, of a specular gloss of 30 or more but not more than 60 measured at an angle of 60 ° using a glossmeter (as determined by the ISO 2813:2000 method), consisting of a layer of poly(ethylene terephthalate) and a layer of coloured poly(vinyl chloride), joined by a metallised adhesive coating, for coating panels and doors of a kind used in the manufacture of domestic appliances <sup>(1)</sup> | 0 %                     | 31.12.2018                         |
| ex 3921 90 90 | 10    | Roll of polymer-metal laminate comprising:  | 0 %                     | 31.12.2016                         |
| ex 8507 90 80 | 50    | — a layer of poly(ethylene terephthalate),<br>— a layer of aluminium,<br>— a layer of polypropylene,  |                         |                                    |

| CN code       | TARIC | Description  | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|------------------------------------|
| ex 3923 10 00 | 10    | <p>— with a width of not more than 275 mm,<br/> — a total thickness of not more than 165 µm, and<br/> — conforming to ASTM D1701-91 and ASTM D882-95A<br/> for use in the manufacture of lithium-ion electric vehicle batteries <sup>(1)</sup></p> <p>Photomask or wafer compacts:<br/> — consisting of antistatic materials or blended thermoplastics proving special electrostatic discharge (ESD) and outgassing properties,<br/> — having non porous, abrasion resistant or impact resistant surface properties,<br/> — fitted with a specially designed retainer system that protects the photomask or wafers from surface or cosmetic damage and<br/> — with or without a gasket seal,<br/> of a kind used in the photolithography or other semiconductor production to house photomasks or wafers</p> | 0 %                     | 31.12.2016                         |
| ex 3923 30 90 | 10    | <p>Polyethylene container, for compressed hydrogen:<br/> — with aluminium bosses at both ends,<br/> — wholly embedded in an overwrap of carbon fibres impregnated with epoxide resin,<br/> — of a diameter of 213 mm or more, but not more than 368 mm,<br/> — a length of 860 mm or more, but not more than 1 260 mm and<br/> — a capacity of 18 litres or more, but not more than 50 litres</p>  | 0 %                     | 31.12.2018                         |
| ex 3926 90 92 | 20    | Reflecting sheeting or tape, consisting of a facing-strip of poly(vinyl chloride) embossed in a regular pyramidal pattern, heat-sealed in parallel lines or in a grid-pattern to a backing-strip of plastic material, or of knitted or woven fabric covered on one side with plastic material  | 0 %                     | 31.12.2018                         |
| ex 3926 90 97 | 10    | Microspheres of a polymer of divinylbenzene, of a diameter of 4,5 µm or more but not more than 80 µm   | 0 %                     | 31.12.2018                         |
| ex 3926 90 97 | 15    | Glass fibre reinforced plastic traverse leaf spring for use in the manufacture of motor vehicle suspension systems <sup>(1)</sup>  | 0 %                     | 31.12.2018                         |
| ex 3926 90 97 | 25    | Unexpansible microspheres of a copolymer of acrylonitrile, methacrylonitrile and isobornyl methacrylate, of a diameter of 3 µm or more but not more than 4,6 µm  | 0 %                     | 31.12.2018                         |
| ex 3926 90 97 | 55    | Flat product of polyethylene, perforated in opposing directions, of a thickness of 600 µm or more but not more than 1 200 µm and of a weight of 21 g/m <sup>2</sup> or more but not more than 42 g/m <sup>2</sup>  | 0 %                     | 31.12.2018                         |
| ex 3926 90 97 | 65    | Die-cast decoration element made of polycarbonate resin, coated with<br>— a silver-colour acrylic paint, and<br>— a transparent scratch-resistant paint<br>of a kind used in the manufacture of car radio front panels   | 0 %                     | 31.12.2018                         |
| ex 3926 90 97 | 80    | Parts of car radio front panels<br>— of acrylonitrile-butadiene-styrene with or without polycarbonate,<br>— coated with a copper, a nickel and a chrome layers,<br>— with a total thickness of coating of 5,54 µm or more but not more than 22,3 µm  | 0 %                     | 31.12.2016                         |
| ex 4007 00 00 | 10    | Siliconated vulcanised rubber thread and cord  | 0 %                     | 31.12.2018                         |
| ex 4016 99 97 | 20    | Soft rubber sealing stoppers for the manufacture of electrolytic capacitors <sup>(1)</sup>   | 0 %                     | 31.12.2018                         |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
| ex 4016 99 97 | 30    | Tyre moulding bladder   | 0 %                     | 31.12.2016                         |
| ex 4104 41 19 | 10    | Buffalo leather, split, chrome tanned synthetic retanned ("crust"), dry   | 0 %                     | 31.12.2017                         |
| 4105 10 00    |       | Sheep or lamb skin leather, without wool on, tanned or retanned but not further prepared, whether or not split, other than leather of heading 4114  | 0 %                     | 31.12.2018                         |
| 4105 30 90    |       |   |                         |                                    |
| 4106 21 00    |       | Goat or kid skin leather, without hair on, tanned or retanned but not further prepared, whether or not split, other than leather of heading 4114  | 0 %                     | 31.12.2018                         |
| 4106 22 90    |       |   |                         |                                    |
| 4106 31 00    |       | Leather of other animals, without hair on, not further prepared than tanned, other than leather of heading 4114   | 0 %                     | 31.12.2018                         |
| 4106 32 00    |       |   |                         |                                    |
| 4106 40 90    |       |   |                         |                                    |
| 4106 92 00    |       |   |                         |                                    |
| ex 5004 00 10 | 10    | Silk yarn (other than yarn spun from silk waste) not put up for retail sale, unbleached, scoured or bleached, entirely of silk  | 0 %                     | 31.12.2016                         |
| ex 5005 00 10 | 10    | Yarn spun entirely from silk waste (noil), not put up for retail sale   | 0 %                     | 31.12.2018                         |
| ex 5005 00 90 | 10    |   |                         |                                    |
| ex 5205 31 00 | 10    | Six ply yarn of bleached cotton, measuring 925 dtex or more but not more than 989 dtex per single yarn, for the manufacture of tampons <sup>(1)</sup>   | 0 %                     | 31.12.2018                         |
| 5208 11 10    |       | Fabrics for the manufacture of bandages, dressings and medical gauzes   | 5,2 %                   | 31.12.2018                         |
| ex 5402 45 00 | 20    | Yarn of synthetic textile fibres solely of aromatic polyamides obtained by the polycondensation of <i>m</i> -phenylenediamine and isophthalic acid  | 0 %                     | 31.12.2018                         |
| ex 5402 47 00 | 10    | Synthetic bicomponent filament yarn, not textured, untwisted, measuring 1 650 decitex or more but not more than 1 800 decitex, consisting of 110 filaments or more but not more than 120 filaments, each having a core of poly(ethylene terephthalate) and a skin of polyamide-6, containing by weight 75 % or more but not more than 77 % of poly(ethylene terephthalate), for use in the manufacture of roofings <sup>(1)</sup> | 0 %                     | 31.12.2016                         |
| ex 5402 47 00 | 20    | Bicomponent monofilament yarn of not more than 30 dtex, consisting of:<br>— a poly(ethylene terephthalate) core, and<br>— an outer layer of a copolymer of poly(ethyleneterephthalate) and poly(ethylenisophthalate),<br>for use in the manufacture of filtration fabrics <sup>(1)</sup>  | 0 %                     | 31.12.2015                         |
| ex 5402 49 00 | 30    | Yarn of a copolymer of glycollic acid with lactic acid, for the manufacture of surgical sutures <sup>(1)</sup>  | 0 %                     | 31.12.2018                         |
| ex 5402 49 00 | 50    | Non-textured filament yarn of poly(vinyl alcohol)   | 0 %                     | 31.12.2018                         |
| ex 5402 49 00 | 70    | Synthetic filament yarn, single, containing by weight 85 % or more of acrylonitrile, in the form of a wick containing 1 000 continuous filaments or more but not more than 25 000 continuous filaments, of a weight per metre of 0,12 g or more but not more than 3,75 g and of a length of 100 m or more, for the manufacture of carbon-fibre yarn <sup>(1)</sup>  | 0 %                     | 31.12.2018                         |
| ex 5404 19 00 | 20    | Monofilament of poly(1,4-dioxanone)   | 0 %                     | 31.12.2018                         |
| ex 5404 19 00 | 30    | Unsterilised monofilament of a copolymer of 1,3-dioxan-2-one with 1,4-dioxan-2,5-dione, for the manufacture of surgical sutures <sup>(1)</sup>  | 0 %                     | 31.12.2014                         |
| ex 5404 19 00 | 50    | Monofilaments of polyester or poly(butylene terephthalate), with cross-sectional dimension of 0,5 mm or more but not more than 1 mm, for use in the manufacture of zippers <sup>(1)</sup>   | 0 %                     | 31.12.2018                         |

| CN code       | TARIC | Description  | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|------------------------------------|
| ex 5404 90 90 | 20    | Strip of polyimide   | 0 %                     | 31.12.2018                         |
| ex 5407 10 00 | 10    | Textile fabric, consisting of warp filament yarns of polyamide-6,6 and weft filament yarns of polyamide-6,6, polyurethane and a copolymer of terephthalic acid, <i>p</i> -phenylenediamine and 3,4'-oxybis(phenyleneamine)   | 0 %                     | 31.12.2017                         |
| ex 5503 11 00 | 10    | Synthetic staple fibres of a copolymer of terephthalic acid, <i>p</i> -phenylenediamine and 3,4'-oxybis(phenyleneamine), of a length of not more than 7 mm   | 0 %                     | 31.12.2018                         |
| ex 5601 30 00 | 40    |  |                         |                                    |
| ex 5503 40 00 | 10    | Hollow polypropylene staple fibres:<br>— measuring 6 decitex or more but not more than 10 decitex,<br>— of a strength of 3,5 cN/dtex or more<br>— of a diameter of 30 µm or more<br>for use in the manufacture of napkins and napkin liners for babies and other sanitary products <sup>(1)</sup>  | 0 %                     | 31.12.2016                         |
| ex 5503 90 00 | 20    | Poly(vinyl alcohol) fibres, whether or not acetalized  | 0 %                     | 31.12.2018                         |
| ex 5506 90 00 | 10    |  |                         |                                    |
| ex 5601 30 00 | 10    |  |                         |                                    |
| ex 5603 11 10 | 10    | Poly(vinyl alcohol) non-wovens, in the piece or cut into rectangles:<br>— of a thickness of 200 µm or more but not more than 280 µm and<br>— of a weight of 20g/m <sup>2</sup> or more but not more than 50g/m <sup>2</sup>  | 0 %                     | 31.12.2018                         |
| ex 5603 11 90 | 10    |  |                         |                                    |
| ex 5603 12 10 | 10    |  |                         |                                    |
| ex 5603 12 90 | 10    |  |                         |                                    |
| ex 5603 91 10 | 10    |  |                         |                                    |
| ex 5603 91 90 | 10    |  |                         |                                    |
| ex 5603 92 10 | 10    |  |                         |                                    |
| ex 5603 92 90 | 10    |  |                         |                                    |
| ex 5603 11 10 | 20    |  |                         |                                    |
| ex 5603 11 90 | 20    |  |                         |                                    |
| ex 5603 12 90 | 30    | Non-wovens of aromatic polyamide fibres obtained by polycondensation of <i>m</i> -phenylenediamine and isophthalic acid, in the piece or cut into rectangles   | 0 %                     | 31.12.2018                         |
| ex 5603 13 90 | 30    |  |                         |                                    |
| ex 5603 14 90 | 10    |  |                         |                                    |
| ex 5603 92 90 | 60    |  |                         |                                    |
| ex 5603 93 90 | 40    |  |                         |                                    |
| ex 5603 94 90 | 30    | Non-woven:<br>— weighing 30 g/m <sup>2</sup> or more, but not more than 60 g/m <sup>2</sup> ,<br>— containing fibres of polypropylene or of polypropylene and polyethylene,<br>— whether or not printed, with:<br>— on one side, 65 % of the total surface area having circular bobbles of 4mm in diameter, consisting of anchored, elevated un-bonded curly fibres, suitable for the engagement of extruded hook materials, and the remaining 35 % of the surface area being bonded,<br>— and on other side a smooth untextured surface,<br>for use in the manufacture of napkins and napkin liners for babies and similar sanitary articles <sup>(1)</sup> | 0 %                     | 31.12.2017                         |
| ex 5603 12 90 | 50    |  |                         |                                    |

| CN code  | TARIC                | Description  | Rate of autonomous duty | Date foreseen for mandatory review |
|--|----------------------|--|-------------------------|------------------------------------|
| ex 5603 12 90<br>ex 5603 13 90                                   | 60<br>60             | Non-woven of spunbonded polyethylene, of a weight of more than 60 g/m <sup>2</sup> but not more than 80 g/m <sup>2</sup> and an air resistance (Gurley) of 8 s or more but not more than 36 s (as determined by the ISO 5636/5 method)   | 0 %                     | 31.12.2018                         |
| ex 5603 12 90<br>ex 5603 13 90<br>ex 5603 92 90<br>ex 5603 93 90 | 70<br>70<br>40<br>10 | Non-wovens of polypropylene,<br>— with a melt blown layer, laminated on each side with spunbonded filaments of polypropylene,<br>— with a weight of not more than 150 g/m <sup>2</sup> ,<br>— in the piece or simply cut into squares or rectangles, and<br>— not impregnated  | 0 %                     | 31.12.2018                         |
| ex 5603 13 10<br>ex 5603 14 10                                   | 10<br>10             | Electrically nonconductive nonwovens, consisting of a central film of poly(ethylene terephthalate) laminated on each side with unidirectionally aligned fibres of poly(ethylene terephthalate), coated on both sides with high grade temperature resistant electrical nonconductive resin, weighing 147 g/m <sup>2</sup> or more but not more than 265 g/m <sup>2</sup> , with non-isotropic tensile strength on both directions, to be used as electrical insulation material | 0 %                     | 31.12.2018                         |
| ex 5603 13 10  | 20                   | Non-woven of spunbonded polyethylene, with a coating,<br>— of a weight of more than 80 g/m <sup>2</sup> but not more than 105 g/m <sup>2</sup> and<br>— an air resistance (Gurley) of 8 seconds or more but not more than 75 seconds (as determined by the ISO 5636/5 method)  | 0 %                     | 31.12.2015                         |
| ex 5603 14 90  | 40                   | Non-wovens, consisting of poly(ethylene terephthalate) spun bonded media:<br>— of weight of 160 g/m <sup>2</sup> or more but not more than 300 g/m <sup>2</sup> ,<br>— whether or not laminated on one side with a membrane or a membrane and aluminium<br>of a kind used for the manufacture of industrial filters  | 0 %                     | 31.12.2018                         |
| ex 5603 92 90<br>ex 5603 93 90                                   | 20<br>20             | Non-wovens consisting of a meltblown central layer of a thermoplastic elastomer laminated on each side with spunbonded filaments of polypropylene  | 0 %                     | 31.12.2018                         |
| ex 5603 92 90<br>ex 5603 94 90                                   | 70<br>40             | Non-wovens, consisting of multiple layers of a mixture of meltblown fibres and staple fibres of polypropylene and polyester, whether or not laminated on one side or on both sides with spunbonded filaments of polypropylene  | 0 %                     | 31.12.2018                         |
| ex 5603 92 90<br>ex 5603 93 90                                   | 80<br>50             | Non-woven polyolefin fabric, consisting of an elastomeric layer, laminated on each side with polyolefin filaments:<br>— a weight of 25 g/m <sup>2</sup> or more but not more than 150 g/m <sup>2</sup> ,<br>— in the piece or simply cut into squares or rectangles,<br>— not impregnated,<br>— with cross-directional or machine-directional stretch properties<br>for use in the manufacture of infant/child care products <sup>(1)</sup>                                    | 0 %                     | 31.12.2016                         |
| ex 5603 94 90  | 20                   | Acrylic fibre rods, having a length of not more than 50 cm, for the manufacture of pen tips <sup>(1)</sup>   | 0 %                     | 31.12.2018                         |
| ex 5607 50 90  | 10                   | Unsterilised twine of poly(glycolic acid) or of poly(glycolic acid) and its copolymers with lactic acid, plaited or braided, with an inner core, for the manufacture of surgical sutures <sup>(1)</sup>  | 0 %                     | 31.12.2014                         |
| ex 5803 00 10  | 91                   | Gauze of cotton, of a width of less than 1 500 mm  | 0 %                     | 31.12.2018                         |
| ex 5903 10 90<br>ex 5903 20 90<br>ex 5903 90 99                  | 10<br>10<br>20       | Knitted or woven fabrics, coated or covered on one side with artificial plastic material in which are embedded microspheres  | 0 %                     | 31.12.2018                         |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
| ex 5906 99 90 | 10    | Rubberised textile fabric, consisting of warp yarns of polyamide-6,6 and weft yarns of polyamide-6,6, polyurethane and a copolymer of terephthalic acid, <i>p</i> -phenylenediamine and 3,4'-oxybis(phenyleneamine)   | 0 %                     | 31.12.2018                         |
| ex 5907 00 00 | 10    | Textile fabrics, coated with adhesive in which are embedded spheres of a diameter of not more than 150 µm   | 0 %                     | 31.12.2016                         |
| ex 5911 10 00 | 10    | Needle-punched synthetic-fibre felts, not containing polyester, whether or not containing catalytic particles entrapped within the synthetic fibres, coated or covered on one side with polytetrafluoroethylene film, for the manufacture of filtration products <sup>(1)</sup>   | 0 %                     | 31.12.2018                         |
| ex 5911 90 90 | 30    | Parts of equipment for the purification of water by reverse osmosis, consisting essentially of plastic-based membranes, supported internally by woven or non-woven textile materials which are wound round a perforated tube, and enclosed in a cylindrical plastic casing of a wall-thickness of not more than 4 mm, whether or not housed in a cylinder of a wall-thickness of 5 mm or more   | 0 %                     | 31.12.2018                         |
| ex 8421 99 00 | 92    |   |                         |                                    |
| ex 5911 90 90 | 40    | Multi-layered non-woven polyester polishing pads, impregnated with polyurethane   | 0 %                     | 31.12.2014                         |
| ex 6813 89 00 | 10    | Friction material, of a thickness of less than 20 mm, not mounted, for the manufacture of friction components of a kind used in automatic transmissions and clutches <sup>(1)</sup>   | 0 %                     | 31.12.2018                         |
| ex 6814 10 00 | 10    | Agglomerated mica with a thickness of not more than 0,15 mm, on rolls, whether or not calcined, whether or not reinforced with aramid fibres, for use in the manufacture of insulation products for high voltage applications <sup>(1)</sup>  | 0 %                     | 31.12.2018                         |
| ex 6903 90 90 | 20    | Silicon carbide reactor tubes and holders, of a kind used for insertion into diffusion and oxidation furnaces for production of semiconductor materials   | 0 %                     | 31.12.2018                         |
| ex 6909 19 00 | 15    | Ceramic ring with rectangular transversal section having an external diameter of 19 mm or more (+ 0,00 mm/- 0,10 mm) but not more than 29 mm (+ 0,00 mm/- 0,20 mm), an internal diameter of 10 mm or more (+ 0,00 mm/- 0,20 mm) but not more than 19 mm (+ 0,00 mm/-0,30 mm), a thickness variable from 2 mm (± 0,10 mm) to 3,70 mm (± 0,20 mm) and heat resistance 240 °C or more, containing by weight:<br>— 90 % (± 1,5 %) of aluminium oxide<br>— 7 % (± 1 %) of titanium oxide | 0 %                     | 31.12.2017                         |
| ex 6909 19 00 | 20    | Silicon nitride (Si <sub>3</sub> N <sub>4</sub> ) rollers or balls  | 0 %                     | 31.12.2015                         |
| ex 6909 19 00 | 30    | Supports for catalysts, consisting of porous cordierite or mullite ceramic pieces, of an overall volume of not more than 65 l, having, per cm <sup>2</sup> of the cross-section, not less than one continuous channel which may be open at both ends or stopped at one end  | 0 %                     | 31.12.2018                         |
| ex 6909 19 00 | 50    | Ceramic articles made of continuous filaments of ceramic oxides, containing by weight:<br>— 2 % or more of diboron trioxide,<br>— 28 % or less of silicon dioxide and<br>— 60 % or more of dialuminium trioxide   | 0 %                     | 31.12.2018                         |
| ex 6914 90 00 | 20    |   |                         |                                    |
| ex 6909 19 00 | 60    | Supports for catalysts, consisting of porous ceramic pieces, of a blend of silicon carbide and silicon, with a hardness of less than 9 on the Mohs scale, with a total volume of not more than 65 litres, having, per cm <sup>2</sup> of the surface of the cross section one or more closed channels at the tail end   | 0 %                     | 31.12.2018                         |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
| ex 6909 19 00 | 70    | Supports for catalysts or filters, consisting of porous ceramics made primarily from oxides of aluminium and titanium; with a total volume of not more than 65 litres and at least one duct (open on one or both ends) per cm <sup>2</sup> of cross section   | 0 %                     | 31.12.2018                         |
| ex 6909 19 00 | 80    | Ceramic heat sinks, containing by weight:<br>— 66 % or more of silicon carbide,<br>— 15 % or more of aluminium oxide<br>for maintaining the operating temperature of transistors, diodes and integrated circuits in products of headings 8521 or 8528 (1)   | 0 %                     | 31.12.2016                         |
| ex 6914 90 00 | 30    | Ceramic microspheres, transparent, obtained from silicon dioxide and zirconium dioxide, of a diameter of more than 125 µm   | 0 %                     | 31.12.2018                         |
| ex 7005 10 30 | 10    | Float glass:<br>— of a thickness of 4,0 mm or more but not more than 4,2 mm,<br>— with a light transmission of 91 % or more measured using a D-type light source,<br>— coated on one surface with a fluorine doped tin dioxide reflective layer   | 0 %                     | 31.12.2017                         |
| ex 7006 00 90 | 70    | Float glass:<br>— with a thickness of 1,7 mm or more but not more than 1,9 mm,<br>— with light transmission of 91 % or more, measured with a D-type light source,<br>— coated on one side with fluorine-doped tin dioxide as a reflecting layer,<br>— with worked edges   | 0 %                     | 31.12.2016                         |
| ex 7007 19 20 | 10    | Glass plate of a diagonal size of 81,28 cm (± 1,5 cm) or more, but not more than 185,42 cm (± 1,5 cm), consisting of tempered glass; provided either with a mesh film and a near-infrared absorbing film or a sputtered conductive layer, with optional additional anti-reflex layer on one or both sides, for use in the manufacture of products falling within heading 8528 (1)   | 0 %                     | 31.12.2018                         |
| ex 7007 29 00 | 10    | Glass plate of a diagonal size of 81,28 cm (± 1,5 cm) or more, but not more than 185,42 cm (± 1,5 cm), consisting of 2 sandwich plates laminated together; provided either with a mesh film and a near-infrared absorbing film or a sputtered conductive layer, with optional additional anti-reflex layer on one or both sides   | 0 %                     | 31.12.2018                         |
| ex 7009 10 00 | 10    | Electro-cromic auto-dimming glass for motor vehicle mirrors:<br>— whether or not equipped with plastic backing plate,<br>— whether or not equipped with a heating element,<br>— whether or not equipped with Blind Spot Module (BSM) display  | 0 %                     | 31.12.2017                         |
| ex 7009 91 00 | 10    | Unframed glass mirrors with:<br>— a length of 1 516 mm (± 1 mm);<br>— a width of 553 mm (± 1 mm);<br>— a thickness of 3 mm (± 0,1 mm);<br>— the back of the mirror covered with protective polyethylene (PE) film, with a thickness of 0,11 mm or more but not more than 0,13 mm;<br>— a lead content of not more than 90 mg/kg and<br>— a corrosion resistance of 72 hours or more according to ISO 9227 salt spray test | 0 %                     | 31.12.2015                         |
| 7011 20 00    |       | Glass envelopes (including bulbs and tubes), open, and glass parts thereof, without fittings, for cathode ray tubes   | 0 %                     | 31.12.2018                         |

| CN code       | TARIC | Description  | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|------------------------------------|
| ex 7014 00 00 | 10    | Optical elements of glass (other than those of heading 7015), not optically worked, other than signalling glassware  | 0 %                     | 31.12.2018                         |
| ex 7019 12 00 | 01    | Rovings, measuring 2 600 tex or more but not more than 3 300 tex and of a loss on ignition of 4 % or more but not more than 8 % by weight (as determined by the ASTM D 2584-94 method)   | 0 %                     | 31.12.2018                         |
| ex 7019 12 00 | 21    |  |                         |                                    |
| ex 7019 12 00 | 02    | Rovings, measuring 650 tex or more but not more than 2 500 tex, coated with a layer of polyurethane whether or not mixed with other materials  | 0 %                     | 31.12.2018                         |
| ex 7019 12 00 | 22    |  |                         |                                    |
| ex 7019 12 00 | 03    | Rovings, measuring 392 tex or more but not more than 2 884 tex, coated with a layer of an acrylic copolymer  | 0 %                     | 31.12.2018                         |
| ex 7019 12 00 | 23    |  |                         |                                    |
| ex 7019 12 00 | 05    | Rovings ranging from 1 980 to 2 033 tex, composed of continuous glass filaments of 9 µm (± 0,5 µm)   | 0 %                     | 31.12.2017                         |
| ex 7019 12 00 | 25    |  |                         |                                    |
| ex 7019 19 10 | 10    | Yarn of 33 tex or a multiple thereof (± 7,5 %), obtained from continuous spun-glass filaments of a nominal diameter of 3,5 µm or of 4,5 µm, in which filaments of a diameter of 3 µm or more but not more than 5,2 µm predominate, other than those treated so as to improve their adhesion to elastomers  | 0 %                     | 31.12.2018                         |
| ex 7019 19 10 | 15    | S-glass yarn of 33 tex or a multiple of 33 tex (± 13 %) made from continuous spun-glass filaments with fibres of a diameter of 9 µm (− 1 µm / + 1,5 µm)  | 0 %                     | 31.12.2017                         |
| ex 7019 19 10 | 20    | Yarn of 10,3 tex or more but not more than 11,9 tex, obtained from continuous spun-glass filaments, in which filaments of a diameter of 4,83 µm or more but not more than 5,83 µm predominate  | 0 %                     | 31.12.2015                         |
| ex 7019 19 10 | 25    | Yarn of 5,1 tex or more but not more than 6,0 tex, obtained from continuous spun-glass filaments, in which filaments of a diameter of 4,83 µm or more but not more than 5,83 µm predominate  | 0 %                     | 31.12.2015                         |
| ex 7019 19 10 | 30    | Yarn of E-glass of 22 tex (± 1,6 tex), obtained from continuous spun-glass filaments of a nominal diameter of 7 µm, in which filaments of a diameter of 6,35 µm or more but not more than 7,61 µm predominate  | 0 %                     | 31.12.2014                         |
| ex 7019 19 10 | 50    | Yarn of 11 tex or a multiple thereof (± 7,5 %), obtained from continuous spun-glass filaments, containing 93 percent by weight or more of silicon dioxide, of a nominal diameter of 6 µm or 9 µm, other than those treated   | 0 %                     | 31.12.2016                         |
| ex 7019 19 10 | 55    | Glass cord impregnated with rubber or plastic, obtained from K- or U-glass filaments, made up of: <ul style="list-style-type: none"> <li>— 9 % or more but not more than 16 % of magnesium oxide,</li> <li>— 19 % or more but not more than 25 % of aluminium oxide,</li> <li>— 0 % or more but not more than 2 % of boron oxide,</li> <li>— without calcium oxide,</li> </ul> coated with a latex comprising at least a resorcinol- formaldehyde resin and chlorosulphonated polyethylene | 0 %                     | 31.12.2014                         |
| ex 7019 19 10 | 60    | High modulus glass cord (K) impregnated with rubber, obtained from twisted high modulus glass filament yarns, coated with a latex comprising a resorcinol-formaldehyde resin with or without vinylpyridine and/or hydrogenated acrylonitrile-butadiene rubber (HNBR)   | 0 %                     | 31.12.2018                         |
| ex 7019 90 00 | 30    |  |                         |                                    |
| ex 7019 19 10 | 70    | Glass cord impregnated with rubber or plastic, obtained from twisted glass filament yarns, coated with a latex comprising at least a resorcinol-formaldehyde-vinylpyridine resin and an acrylonitrile-butadiene rubber (NBR)   | 0 %                     | 31.12.2018                         |
| ex 7019 90 00 | 20    |  |                         |                                    |
| ex 7019 19 10 | 80    | Glass cord impregnated with rubber or plastic, obtained from twisted glass filament yarns, coated with a latex comprising at least a resorcinol-formaldehyde resin and chlorosulphonated polyethylene  | 0 %                     | 31.12.2018                         |
| ex 7019 90 00 | 40    |  |                         |                                    |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
| ex 7019 39 00 | 50    | Non-woven product of non-textile glass fibre, for the manufacture of air filters or catalysts <sup>(1)</sup>  | 0 %                     | 31.12.2016                         |
| ex 7019 40 00 | 10    | Woven fabrics of rovings, impregnated with epoxy resin, with a coefficient of thermal expansion between 30 °C and 120 °C (measured according to IPC-TM-650) of:<br>— 10ppm per °C or more but not more than 12ppm per °C in the length and width, and<br>— 20ppm per °C or more but not more than 30ppm per °C in the thickness, with a glass transition temperature of 152 °C or more but not more than 153 °C (measured according to IPC-TM-650)                                    | 0 %                     | 31.12.2018                         |
| ex 7019 90 00 | 10    | Non-textile glass fibres in which fibres of a diameter of less than 4,6 µm predominate  | 0 %                     | 31.12.2018                         |
| ex 7020 00 10 | 10    | Television pedestal stands with or without bracket for fixation to and  | 0 %                     | 31.12.2016                         |
| ex 7616 99 90 | 77    | stabilization of television cabinet case/body   |                         |                                    |
| ex 7201 10 11 | 10    | Pig iron ingots with a length of not more than 350 mm, a width of not more than 150 mm, a height of not more than 150 mm  | 0 %                     | 31.12.2016                         |
| ex 7201 10 30 | 10    | Pig iron ingots with a length of not more than 350 mm, a width of not more than 150 mm, a height of not more than 150 mm, containing by weight not more than 1 % of silicon   | 0 %                     | 31.12.2016                         |
| 7202 50 00    |       | Ferro-silico-chromium   | 0 %                     | 31.12.2018                         |
| ex 7202 99 80 | 10    | Ferro-dysprosium, containing by weight:<br>— 78 % or more of dysprosium, and<br>— 18 % or more but not more than 22 % of iron   | 0 %                     | 31.12.2015                         |
| ex 7318 14 99 | 20    | Rock bolt:  | 0 %                     | 31.12.2016                         |
| ex 7318 14 99 | 29    | — being a self-tapping screw,<br>— with a length of more than 300 mm,<br>of a kind used for support of mines  |                         |                                    |
| ex 7320 90 10 | 91    | Flat spiral spring of tempered steel, with:<br>— a thickness of 2,67 mm or more, but not more than 4,11 mm,<br>— a width of 12,57 mm or more, but not more than 16,01 mm,<br>— a torque of 18,05 Nm or more, but not more than 73,5 Nm<br>— an angle between the free position and the nominal position in exercise of 76 ° or more, but not more than 218 °<br>for use in the manufacture of tensioners for power transmission belts, for internal combustion engines <sup>(1)</sup> | 0 %                     | 31.12.2018                         |
| ex 7325 99 10 | 20    | Anchor head of hot dipped galvanized ductile cast iron of the kind used in the production of earth anchors  | 0 %                     | 31.12.2014                         |
| ex 7326 20 00 | 20    | Metal fleece, consisting of a mass of stainless steel wires of diameters of 0,017 mm or more but not more than 0,070 mm, compacted by sintering and rolling   | 0 %                     | 31.12.2016                         |
| ex 7410 11 00 | 10    | Roll of laminate foil of graphite and copper, with:   | 0 %                     | 31.12.2016                         |
| ex 8507 90 80 | 60    | — a width of 610 mm or more but not more than 620 mm, and   |                         |                                    |
| ex 8545 90 90 | 30    | — a diameter of 690 mm or more but not more than 710 mm,<br>for use in the manufacture of lithium-ion electric vehicle batteries <sup>(1)</sup>   |                         |                                    |
| ex 7410 21 00 | 10    | Sheet or plate of polytetrafluoroethylene, containing aluminium oxide or titanium dioxide as filler or reinforced with glass-fibre fabric, covered on both sides with copper foil   | 0 %                     | 31.12.2018                         |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
| ex 7410 21 00 | 30    | Film of polyimide, whether or not containing epoxide resin and/or glass fibre, covered on one side or on both sides with a copper foil  | 0 %                     | 31.12.2018                         |
| ex 7410 21 00 | 40    | Sheet or plates:<br>— consisting of at least a central layer of paper or one central sheet of any type of nonwoven fibre, laminated on each side with glass-fibre fabric and impregnated with epoxide resin, or<br>— consisting of multiple layers of paper, impregnated with phenolic resin, coated on one or both sides with a copper film with a maximum thickness of 0,15 mm  | 0 %                     | 31.12.2018                         |
| ex 7410 21 00 | 50    | Plates:<br>— consisting of at least one layer of fibreglass fabric impregnated with epoxide resin,<br>— covered on one or both sides with copper foil with a thickness of not more than 0,15 mm and<br>— with a dielectric constant (DK) of less than 3,9 and a loss factor (Df) of less than 0,015 at a measuring frequency of 10 GHz, as measured according to IPC-TM-650   | 0 %                     | 31.12.2018                         |
| ex 7410 21 00 | 60    | Plates, rolls and sheets of synthetic or artificial resin:<br>— with a maximum thickness of not more than 25 µm,<br>— coated on both sides with a copper film with a maximum thickness of 0,15 mm,<br>— with a minimum capacitance of 1,09 pF/mm <sup>2</sup> ,<br>for use in the manufacture of circuit boards <sup>(1)</sup>  | 0 %                     | 31.12.2018                         |
| ex 7410 21 00 | 70    | Plates, rolls or sheets:<br>— with at least one layer of woven glass fibre, impregnated with a fire-retardant artificial or synthetic resin with a glass transition temperature (T <sub>g</sub> ) of more than 170 °C (according to IPC-TM-650, method 2.4.25),<br>— coated on one or both sides with a copper film with a thickness of not more than 0,15 mm,<br>for use in the manufacture of circuit boards <sup>(1)</sup> | 0 %                     | 31.12.2018                         |
| ex 7419 99 90 | 91    | Disc (target) with deposition material, consisting of molybdenum silicide:  | 0 %                     | 31.12.2018                         |
| ex 7616 99 90 | 60    | — containing 1 mg/kg or less of sodium and<br>— mounted on a copper or aluminium support  |                         |                                    |
| 7601 20 20    |       | Slabs and billets of unwrought aluminium alloys   | 4 %                     | 31.12.2018                         |
| ex 7601 20 20 | 10    | Slabs and billets of aluminium alloy containing lithium   | 0 %                     | 31.12.2017                         |
| ex 7604 21 00 | 10    | Profiles made of aluminium alloy conforming to EN standard AW-6063 T5   | 0 %                     | 31.12.2018                         |
| ex 7604 29 90 | 30    | — anodized<br>— whether or not lacquered<br>— with a wall thickness of 0,5 mm (± 1,2 %) or more but not more than 0,8 mm (± 1,2 %)<br>for use in the manufacture of goods of heading 8302 <sup>(1)</sup>  |                         |                                    |
| ex 7604 29 10 | 10    | Sheets and bars of aluminium-lithium alloys   | 0 %                     | 31.12.2015                         |
| ex 7606 12 99 | 20    |   |                         |                                    |
| ex 7605 19 00 | 10    | Not alloyed aluminium wire, of a diameter of 2 mm or more but not more than 6 mm, covered with a layer of copper of a thickness of 0,032 mm or more but not more than 0,117 mm  | 0 %                     | 31.12.2018                         |

| CN code   | TARIC          | Description  | Rate of autonomous duty | Date foreseen for mandatory review |
|---|----------------|--|-------------------------|------------------------------------|
| ex 7606 12 92<br>ex 7607 11 90                  | 20<br>20       | Aluminium and magnesium alloy strip:<br>— in rolls,<br>— of a thickness of 0,14 mm or more but not more than 0,40 mm,<br>— a width of 12,5 mm or more but not more than 359 mm,<br>— a tensile strength of 285 N/mm <sup>2</sup> or more, and<br>— an elongation at break of 1 % or more, and<br>containing by weight:<br>— 93,3 % or more of aluminium,<br>— 2,2 % or more but not more than 5 % of magnesium, and<br>— not more than 1,8 % of other elements | 0 %                     | 31.12.2017                         |
| ex 7607 11 90                                   | 10             | Plain aluminium foil with the following parameters:<br>— an aluminium content of 99,98 % or more<br>— a thickness of 0,070 mm or more but not more than 0,125 mm<br>— with a cubic texture<br>of a kind used for high voltage etching <sup>(1)</sup>   | 0 %                     | 31.12.2016                         |
| ex 7607 11 90                                   | 40             | Aluminium foil in rolls:<br>— having a purity of 99,99 % by weight,<br>— of a thickness of 0,021 mm or more but not more than 0,2 mm,<br>— with a width of 500 mm,<br>— with a surface oxide layer by 3 to 4 nm thick,<br>— and with a cubic texture of more than 95 %   | 0 %                     | 31.12.2016                         |
| ex 7607 19 90<br>ex 8507 90 80                  | 10<br>80       | Sheet in the form of a roll consisting of a laminate of lithium and manganese bonded to aluminium, with:<br>— a width of 595 mm or more but not more than 605 mm, and<br>— a diameter of 690 mm or more but not more than 710 mm,<br>for use in the manufacture of cathodes for lithium-ion electric vehicle batteries <sup>(1)</sup>  | 0 %                     | 31.12.2016                         |
| ex 7607 20 90                                   | 10             | Aluminium laminated film of a total thickness of not more than 0,123 mm, comprising of a layer of aluminium of a thickness of not more than 0,040 mm, polyamide and polypropylene base films, and a protective coating against corrosion by hydrofluoric acid, for use in the manufacture of lithium polymer batteries <sup>(1)</sup>  | 0 %                     | 31.12.2017                         |
| ex 7607 20 90                                   | 20             | Lubricating entry sheet of a total thickness of not more than 350 µm, comprising of:<br>— a layer of aluminium foil of a thickness of 70 µm or more but not more than 150 µm,<br>— a water soluble lubricant of a thickness of 20 µm or more but not more than 200 µm and solid at room temperature  | 0 %                     | 31.12.2015                         |
| ex 7613 00 00                                   | 20             | Aluminium container, seamless, for compressed natural gas or compressed hydrogen, wholly embedded in an overwrap of epoxy-carbon fibres composite, of a storage capacity of 172 l (± 10 %) and an unfilled weight of not more than 64 kg   | 0 %                     | 31.12.2018                         |
| ex 7616 99 90                                   | 15             | Honeycomb aluminium blocks of the type used in the manufacture of aircraft parts   | 0 %                     | 31.12.2018                         |
| ex 7616 99 90<br>ex 8482 80 00<br>ex 8803 30 00 | 70<br>10<br>40 | Connecting components for use in the production of helicopter tail rotor shafts <sup>(1)</sup>   | 0 %                     | 31.12.2016                         |

| CN code       | TARIC | Description  | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|------------------------------------|
| ex 7616 99 90 | 75    | Parts in the shape of a rectangular frame:<br>— of painted aluminium,<br>— with a length of 1 011 mm or more but not more than 1 500 mm,<br>— with a width of 622 mm or more but not more than 900 mm,<br>— with a thickness of 0,6 mm ( $\pm$ 0,1 mm),<br>of a kind used in the manufacture of TV sets    | 0 %                     | 31.12.2017                         |
| ex 8102 10 00 | 10    | Molybdenum powder with:<br>— a purity by weight of 99 % or more and<br>— a particle size of 1,0 $\mu$ m or more, but not more than 5,0 $\mu$ m   | 0 %                     | 31.12.2017                         |
| 8104 11 00    |       | Unwrought magnesium, containing at least 99,8 % by weight of magnesium   | 0 %                     | 31.12.2018                         |
| ex 8104 30 00 | 30    | Magnesium powder:<br>— of purity by weight of 99,5 % or more,<br>— with a particle size of 0,2 mm or more but not more than 0,8 mm   | 0 %                     | 31.12.2015                         |
| ex 8104 90 00 | 10    | Ground and polished magnesium sheets, of dimensions not more than 1 500 mm $\times$ 2 000 mm, coated on one side with an epoxy resin insensitive to light  | 0 %                     | 31.12.2018                         |
| ex 8105 90 00 | 10    | Bars or wires made of cobalt alloy containing, by weight:<br>— 35 % ( $\pm$ 2 %) cobalt,<br>— 25 % ( $\pm$ 1 %) nickel,<br>— 19 % ( $\pm$ 1 %) chromium and<br>— 7 % ( $\pm$ 2 %) iron<br>conforming to the material specifications AMS 5842, of a kind used in the aerospace industry                     | 0 %                     | 31.12.2017                         |
| ex 8108 20 00 | 10    | Titanium sponge  | 0 %                     | 31.12.2018                         |
| ex 8108 20 00 | 30    | Titanium powder of which 90 % by weight or more passes through a sieve with an aperture of 0,224 mm  | 0 %                     | 31.12.2018                         |
| ex 8108 30 00 | 10    | Waste and scrap of titanium and titanium alloys, except those containing by weight 1 % or more but not more than 2 % of aluminium  | 0 %                     | 31.12.2018                         |
| ex 8108 90 30 | 10    | Titanium alloy rods complying with standard EN 2002-1, EN 4267 or DIN 65040  | 0 %                     | 31.12.2014                         |
| ex 8108 90 30 | 20    | Bars, rods and wire of alloy of titanium and aluminium, containing by weight 1 % or more but not more than 2 % of aluminium, for use in the manufacture of silencers and exhaust pipes of subheadings 8708 92 or 8714 10 00 (!)  | 0 %                     | 31.12.2017                         |
| ex 8108 90 30 | 30    | Titanium-aluminium-vanadium alloy (TiAl6V4) wire, complying with AMS standards 4928 and 4967   | 0 %                     | 31.12.2015                         |
| ex 8108 90 30 | 40    | Wire of an titanium alloy containing by weight:<br>— 22 % ( $\pm$ 3 %) of vanadium and<br>— 4 % ( $\pm$ 0,5 %) of aluminium  | 0 %                     | 31.12.2016                         |
| ex 8108 90 50 | 10    | Alloy of titanium and aluminium, containing by weight 1 % or more but not more than 2 % of aluminium, in sheets or rolls, of a thickness of 0,49 mm or more but not more than 3,1 mm, of a width of 1 000 mm or more but not more than 1 254 mm, for the manufacture of goods of subheading 8714 10 00 (!) | 0 %                     | 31.12.2018                         |

| CN code       | TARIC | Description  | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|------------------------------------|
| ex 8108 90 50 | 30    | Alloy of titanium and silicon, containing by weight 0,15 % or more but not more than 0,60 % of silicon, in sheets or rolls, for use in the manufacture of:<br>— exhaust systems for internal combustion engines or<br>— tubes and pipes of subheading 8108 90 60 <sup>(1)</sup>            | 0 %                     | 31.12.2017                         |
| ex 8108 90 50 | 50    | Plates, sheets, strips and foils of an alloy of titanium, copper and niobium, containing by weight 0,8 % or more but not more than 1,2 % of copper and 0,4 % or more but not more than 0,6 % of niobium  | 0 %                     | 31.12.2017                         |
| ex 8108 90 50 | 60    | Plates, sheets, strips and foils of an alloy of titanium, aluminium, silicon and niobium, containing by weight:<br>— 0,4 % or more but not more than 0,6 % of aluminium,<br>— 0,35 % or more but not more than 0,55 % of silicon and<br>— 0,1 % or more but not more than 0,3 % of niobium | 0 %                     | 31.12.2018                         |
| ex 8108 90 50 | 70    | Strip of an alloy of titanium, containing by weight:<br>— 15 % ( $\pm 1$ %) of vanadium<br>— 3 % ( $\pm 0,5$ %) of chromium<br>— 3 % ( $\pm 0,5$ %) of tin and<br>— 3 % ( $\pm 0,5$ %) of aluminium  | 0 %                     | 31.12.2016                         |
| ex 8108 90 50 | 75    | Plates, sheets, strips and foil of titanium alloy, containing by weight:<br>— 0,3 % or more but not more than 0,7 % of aluminium and<br>— 0,25 % or more but not more than 0,6 % of silicon  | 0 %                     | 31.12.2016                         |
| ex 8108 90 50 | 85    | Plates, sheets, strip and foil of non-alloyed titanium   | 0 %                     | 31.12.2017                         |
| ex 8108 90 90 | 20    | Parts of spectacle frames and mountings, including bolts of the kind used for spectacle frames and mountings, of an alloy of titanium  | 0 %                     | 31.12.2016                         |
| ex 9003 90 00 | 10    |  |                         |                                    |
| ex 8109 20 00 | 10    | Non-alloy zirconium sponges or ingots, containing by weight more than 0,01 % of hafnium for use in the manufacture of tubes, bars or ingots enlarged by remelting for the chemical industry <sup>(1)</sup>   | 0 %                     | 31.12.2018                         |
| ex 8110 10 00 | 10    | Antimony in the form of ingots   | 0 %                     | 31.12.2018                         |
| ex 8112 99 30 | 10    | Alloy of niobium (columbium) and titanium, in the form of bars and rods  | 0 %                     | 31.12.2018                         |
| ex 8113 00 20 | 10    | Cermet blocks containing by weight 60 % or more of aluminium and 5 % or more of boron carbide  | 0 %                     | 31.12.2016                         |
| ex 8113 00 90 | 10    | Carrier plate of aluminium silicon carbide (AlSiC-9) for electronic circuits   | 0 %                     | 31.12.2017                         |
| ex 8207 30 10 | 10    | Set of transfer and/or tandem press tools for cold-forming, pressing, drawing, cutting, punching, bending, calibrating, bordering and throating of metal sheets, for use in the manufacture of frame parts of motor vehicles <sup>(1)</sup>  | 0 %                     | 31.12.2017                         |
| ex 8301 60 00 | 10    | Keypads, wholly of either silicone or polycarbonate, including printed keys with electrical contacting elements  | 0 %                     | 31.12.2015                         |
| ex 8413 91 00 | 20    |  |                         |                                    |
| ex 8419 90 85 | 20    |  |                         |                                    |
| ex 8438 90 00 | 10    |  |                         |                                    |
| ex 8468 90 00 | 10    |  |                         |                                    |
| ex 8476 90 00 | 10    |  |                         |                                    |
| ex 8479 90 80 | 87    |  |                         |                                    |
| ex 8481 90 00 | 20    |  |                         |                                    |
| ex 8503 00 99 | 45    |  |                         |                                    |
| ex 8515 90 00 | 20    |  |                         |                                    |
| ex 8531 90 85 | 20    |  |                         |                                    |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
| ex 8536 90 85 | 96    |   |                         |                                    |
| ex 8543 90 00 | 50    |   |                         |                                    |
| ex 8708 91 99 | 10    |   |                         |                                    |
| ex 8708 99 97 | 30    |   |                         |                                    |
| ex 9031 90 85 | 30    |   |                         |                                    |
| ex 8309 90 90 | 10    | Aluminium can ends with so-called "ring pull" full aperture with a diameter of 136,5 mm ( $\pm$ 1 mm)   | 0 %                     | 31.12.2018                         |
| ex 8401 30 00 | 20    | Non-irradiated hexagonal fuel modules (elements) for use in nuclear reactors <sup>(1)</sup>   | 0 %                     | 31.12.2018                         |
| ex 8405 90 00 | 10    | Metal casing for automobile safety belt pre-tension gas generators  | 0 %                     | 31.12.2014                         |
| ex 8708 21 10 | 10    |   |                         |                                    |
| ex 8708 21 90 | 10    |   |                         |                                    |
| ex 8407 33 20 | 10    | Spark-ignition reciprocating or rotary internal combustion piston engines, having a cylinder capacity of not less than 300 cm <sup>3</sup> and a power of not less than 6 kW but not exceeding 20,0 kW, for the manufacture of:   | 0 %                     | 31.12.2017                         |
| ex 8407 33 80 | 10    |   |                         |                                    |
| ex 8407 90 80 | 10    | — self-propelled lawn mowers with a seat of subheading 8433 11 51, and hand-operated lawn mowers of heading 8433 11 90,   |                         |                                    |
| ex 8407 90 90 | 10    | — tractors of subheading 8701 90 11, whose main function is that of a lawn mower,<br>— four stroke mowers with motor of a cylinder capacity of not less than 300 cc of subheading 8433 20 10 or<br>— snowploughs and snow blowers of subheading 8430 20 <sup>(1)</sup>  |                         |                                    |
| ex 8407 90 10 | 10    | Four-stroke petrol engines of a cylinder capacity of not more than 250 cm <sup>3</sup> for use in the manufacture of lawnmowers of subheading 8433 11, mowers with motor of subheading 8433 20 10, rotovators of subheading 8432 29 50, garden shredders of subheading 8436 80 90 or scarifiers of subheading 8432 29 10 <sup>(1)</sup> | 0 %                     | 31.12.2016                         |
| ex 8407 90 90 | 20    | Compact Liquid Petroleum Gas (LPG) Engine System, with:<br>— 6 cylinders,<br>— an output of 75 kW or more, but not more than 80 kW,<br>— inlet and exhaust valves modified to operate continuously in heavy duty applications,<br>for use in the manufacture of vehicles of heading 8427 <sup>(1)</sup>                                 | 0 %                     | 31.12.2015                         |
| ex 8408 90 41 | 20    | Diesel engines of a power of not more than 15 kW, with 2 or 3 cylinders, for use in the manufacture of vehicle mounted temperature control systems <sup>(1)</sup>   | 0 %                     | 31.12.2018                         |
| ex 8408 90 43 | 20    | Diesel engines of a power of not more than 30 kW, with 4 cylinders, for use in the manufacture of vehicle mounted temperature control systems <sup>(1)</sup>  | 0 %                     | 31.12.2018                         |
| ex 8408 90 43 | 30    | 4 Cylinder, 4 cycle, liquid cooled, compression-ignition engine having:   | 0 %                     | 31.12.2017                         |
| ex 8408 90 45 | 20    | — a capacity of not more than 3 850 cm <sup>3</sup> , and   |                         |                                    |
| ex 8408 90 47 | 30    | — a rated output of 15 kW or more but not more than 55 kW,<br>for use in the manufacture of vehicles of heading 8427 <sup>(1)</sup>   |                         |                                    |

| CN code       | TARIC | Description  | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|------------------------------------|
| ex 8408 90 47 | 40    | 4 Cylinder, 4 cycle, liquid cooled, compression-ignition engine having:<br>— a capacity of not more than 3 850 cm <sup>3</sup> ,<br>— a rated output of 55 kW or more but not more than 85 kW,<br>for use in the manufacture of vehicles of heading 8427 <sup>(1)</sup>  | 0 %                     | 31.12.2018                         |
| ex 8409 91 00 | 10    | Exhaust manifold complying with standard DIN EN 13835, whether or not with turbine housing, with four inlet ports, for use in the manufacture of exhaust manifold that is turned, milled, drilled and/or processed by other means <sup>(1)</sup>   | 0 %                     | 31.12.2016                         |
| ex 8409 99 00 | 20    |  |                         |                                    |
| ex 8409 99 00 | 10    | Injectors with solenoid valve for optimised atomisation in the engine combustion chamber   | 0 %                     | 31.12.2016                         |
| ex 8479 90 80 | 85    |  |                         |                                    |
| ex 8411 99 00 | 30    | Wheel-shaped gas turbine component with blades, of a kind used in turbochargers:<br>— of a precision-cast nickel based alloy complying with standard DIN G-NiCr13Al16MoNb or DIN NiCo10W10Cr9AlTi or AMS AISI:686,<br>— with a heat-resistance of not more than 1 100 °C;<br>— with a diameter of 30 mm or more, but not more than 80 mm;<br>— with a height of 30 mm or more, but not more than 50 mm | 0 %                     | 31.12.2017                         |
| ex 8411 99 00 | 40    | Spiral-shaped gas turbine turbocharger component:<br>— of a stainless alloy,<br>— with a heat-resistance of not more than 1 050 °C,<br>— with a diameter of 100 mm or more, but not more than 200 mm,<br>— with a height of 100 mm or more, but not more than 150 mm,<br>— whether or not with an engine exhaust manifold  | 0 %                     | 31.12.2018                         |
| ex 8411 99 00 | 50    | Actuator for a single-stage turbocharger:<br>— with a built-in conducting horn and connecting sleeve,<br>— of a stainless steel alloy,<br>— with conducting horns having an operating distance of 20 mm,<br>— with a length of not more than 350 mm,<br>— with a diameter of not more than 75 mm,<br>— with a height of not more than 50 mm  | 0 %                     | 31.12.2018                         |
| ex 8413 70 35 | 20    | Single phase centrifugal pump:<br>— discharging at least 400 cm <sup>3</sup> fluid per minute,<br>— with a noise level limited to 6 dBA,<br>— with the inside diameter of the suction opening and discharge outlet of not more than 15 mm, and<br>— working at ambient temperatures down to -10 °C   | 0 %                     | 31.12.2015                         |
| ex 8414 30 81 | 50    | Hermetic or semi-hermetic variable-speed electric scroll compressors, with a nominal power rating of 0,5 kW or more but not more than 10 kW, with a displacement volume of not more than 35 cm <sup>3</sup> , of the type used in refrigeration equipment  | 0 %                     | 31.12.2014                         |
| ex 8414 30 89 | 20    | Vehicle air conditioning system part, consisting of an open shaft reciprocating compressor of a power of more than 0,4 kW but not more than 10 kW  | 0 %                     | 31.12.2018                         |
| ex 8414 59 20 | 30    | Axial fan:<br>— with an electric motor,<br>— of an output of not more than 125 W<br>for use in the manufacture of computers <sup>(1)</sup>   | 0 %                     | 31.12.2018                         |

| CN code       | TARIC | Description  | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|------------------------------------|
| ex 8414 59 20 | 40    | Axial fan with an electric motor, of an output of not more than 2 W, for use in the manufacture of products of heading 8521 or 8528 <sup>(1)</sup>   | 0 %                     | 31.12.2015                         |
| ex 8414 59 80 | 40    | Cross-flow fan with:   | 0 %                     | 31.12.2016                         |
| ex 8414 90 00 | 60    | — a height of 575 mm ( $\pm$ 1,0 mm) or more, but not more than 850 mm ( $\pm$ 1,0 mm),<br>— a diameter of 95mm ( $\pm$ 0,6 mm) or 102 mm ( $\pm$ 0,6 mm),<br>— an anti-static, anti-bacterial and heat-resistant, 30 % glass fibre reinforced plastic raw material that has a minimum temperature resistance of 70 °C ( $\pm$ 5 °C),<br>for use in the manufacture of indoor units of split-type air conditioning machines <sup>(1)</sup> |                         |                                    |
| ex 8414 90 00 | 20    | Aluminium pistons, for incorporation into compressors of air conditioning machines of motor vehicles <sup>(1)</sup>  | 0 %                     | 31.12.2014                         |
| ex 8414 90 00 | 30    | Pressure-regulating system, for incorporation into compressors of air conditioning machines of motor vehicles <sup>(1)</sup>   | 0 %                     | 31.12.2018                         |
| ex 8414 90 00 | 40    | Drive part, for compressors of air conditioning machines of motor vehicles <sup>(1)</sup>  | 0 %                     | 31.12.2018                         |
| ex 8415 90 00 | 20    | Evaporator made of aluminium for use in the manufacture of air conditioning machines for automobiles <sup>(1)</sup>  | 0 %                     | 31.12.2016                         |
| ex 8418 99 10 | 50    | Evaporator composed of aluminium fins and a copper coil of the kind used in refrigeration equipment  | 0 %                     | 31.12.2014                         |
| ex 8418 99 10 | 60    | Condenser composed of two concentric copper tubes of the kind used in refrigeration equipment  | 0 %                     | 31.12.2014                         |
| ex 8421 99 00 | 91    | Parts of equipment, for the purification of water by reverse osmosis, consisting of a bundle of hollow fibres of artificial plastic material with permeable walls, embedded in a block of artificial plastic material at one end and passing through a block of artificial plastic material at the other end, whether or not housed in a cylinder  | 0 %                     | 31.12.2018                         |
| ex 8421 99 00 | 93    | Components of separators for the separation or purification of gases from gas mixtures, consisting of a bundle of permeable hollow fibres enclosed within a container, whether or not perforated, of an overall length of 300 mm or more but not more than 3 700 mm and a diameter of not more than 500 mm   | 0 %                     | 31.12.2018                         |
| ex 8422 30 00 | 10    | Machines and apparatus, other than injection moulding machines, for the manufacture of ink-jet printer cartridges <sup>(1)</sup>   | 0 %                     | 31.12.2018                         |
| ex 8479 89 97 | 30    |  |                         |                                    |
| ex 8424 90 00 | 30    | Containers of poly(ethylene terephthalate), with a content of 50 ml or more but not more than 600 ml, equipped with a nozzle, of a kind used as a part of mechanical appliances for spraying liquids   | 0 %                     | 31.12.2018                         |
| ex 8431 20 00 | 30    | Drive axle assembly containing differential, reduction gears, crown wheel, drive shafts, wheel hubs, brakes and mast mounting arms for use in the manufacture of vehicles in heading 8427 <sup>(1)</sup>   | 0 %                     | 31.12.2017                         |
| ex 8439 99 00 | 10    | Suction-roll shells, produced by centrifugal casting, not drilled, in the form of alloy-steel tubes, of a length of 3 000 mm or more and an external diameter of 550 mm or more  | 0 %                     | 31.12.2018                         |
| ex 8467 99 00 | 10    | Mechanical switches for connecting electrical circuits, with:  | 0 %                     | 31.12.2014                         |
| ex 8536 50 11 | 35    | — a voltage of 14,4 V or more but not more than 42 V,<br>— an amperage of 10 A or more but not more than 42 A,<br>for use in the manufacture of machines falling within heading 8467 <sup>(1)</sup>  |                         |                                    |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
| ex 8477 80 99 | 10    | Machines for casting or for surface modification of plastic membranes of heading 3921   | 0 %                     | 31.12.2018                         |
| ex 8479 89 97 | 40    | Isobaric pressure exchanger with a flow rate of not more than 50 m <sup>3</sup> /h, whether or not with a booster pump  | 0 %                     | 31.12.2014                         |
| ex 8479 89 97 | 50    | Machinery, being components of a production line for the manufacture of lithium ion batteries for passenger electric motor vehicles, for the construction of such a production line <sup>(1)</sup>  | 0 %                     | 31.12.2015                         |
| ex 8479 90 80 | 80    |   |                         |                                    |
| ex 8481 30 91 | 91    | Steel check (non-return) valves with:<br>— an opening pressure of not more than 800 kPa<br>— an external diameter not more than 37 mm   | 0 %                     | 31.12.2014                         |
| ex 8481 80 59 | 10    | Air control valve, consisting of a stepping motor and a valve pintle, for the regulation of idle air flow in fuel injection engines   | 0 %                     | 31.12.2018                         |
| ex 8481 80 69 | 60    | Four-way reversing valve for refrigerants, consisting of:<br>— a solenoid pilot valve<br>— a brass valve body including valve slider and copper connections with a working pressure up to 4,5 MPa   | 0 %                     | 31.12.2017                         |
| ex 8481 80 79 | 20    | Solenoid valve device that can withstand a pressure of 875 bar  | 0 %                     | 31.12.2018                         |
| ex 8481 80 99 | 50    | Service valve, consisting a combination of a two way valve on the liquid line and a three way valve on the gas line with:<br>— a minimum enclosing pressure of 30 kgf/cm <sup>2</sup> ,<br>— a minimum withstanding pressure of 45 kgf/cm <sup>2</sup> ,<br>for use in the manufacture of outdoor air conditioning units <sup>(1)</sup>       | 0 %                     | 31.12.2016                         |
| ex 8481 80 99 | 60    | our way valve, consisting of:<br>— a core plunger,<br>— a sealing plunger,<br>— a 220 V-240 V AC 50/60 Hz solenoid coil,<br>— a working pressure up to 4,3 MPa,<br>— a housing<br>for directing the flow of the refrigerant, for use in the manufacture of outdoor air conditioning units <sup>(1)</sup>                                      | 0 %                     | 31.12.2016                         |
| ex 8483 30 38 | 30    | Cylindrical bearing housing:<br>— of precision-cast grey cast iron complying with standard DIN EN 1561,<br>— with oil chambers,<br>— without bearings,<br>— with a diameter of 60 mm or more, but not more than 180 mm,<br>— with a height of 60 mm or more, but not more than 120 mm,<br>— whether or not with water chambers and connectors | 0 %                     | 31.12.2017                         |
| ex 8483 40 29 | 50    | Gear set of cycloid gear type with:<br>— a rated torque of 50 Nm or more but not more than 7 000 Nm,<br>— standard ratios of 1:50 or more but not more than 1:270,<br>— lost motion of not more than one arc minute,<br>— an efficiency of more than 80 %,<br>of a kind used in robot arms  | 0 %                     | 31.12.2016                         |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
| ex 8483 40 29 | 60    | Epicyclic gearing, of a kind used in driving hand-held power tools with:<br>— a rated torque of 25 Nm or more, but not more than 70 Nm,<br>— standard gear ratios of 1:12.7 or more, but not more than 1:64.3   | 0 %                     | 31.12.2018                         |
| ex 8483 40 51 | 20    | Gear box, having a differential with wheel axle, for use in the manufacture of self-propelled lawnmowers with a seat of subheading 8433 11 51 (!)   | 0 %                     | 31.12.2018                         |
| ex 8483 40 59 | 20    | Hydrostatic speed changer, having a hydro pump and a differential with wheel axle, for use in the manufacture of self-propelled lawnmowers with a seat of subheading 8433 11 51 (!)   | 0 %                     | 31.12.2018                         |
| ex 8483 40 90 | 80    | Transmission gearbox, with:<br>— not more than 3 gears,<br>— an automatic deceleration system and<br>— a power reversal system,<br>for use in the manufacture of goods of heading 8427 (!)  | 0 %                     | 31.12.2015                         |
| ex 8501 10 99 | 54    | DC motor, brushless, with an external diameter of not more than 25,4 mm, a rated speed of 2 260 ( $\pm 15\%$ ) rpm or 5 420 ( $\pm 15\%$ ) rpm, a supply voltage of 1,5 V or 3 V  | 0 %                     | 31.12.2018                         |
| ex 8501 10 99 | 60    | DC motor:<br>— with a rotor speed of 3 500 rpm or more but not more than 5 000 rpm loaded and not more than 6 500 rpm when not loaded<br>— with a power supply voltage of 100 V or more but not more than 240 V for use in the manufacture of electric fryers (!)   | 0 %                     | 31.12.2017                         |
| ex 8501 10 99 | 79    | DC motor with brushes and an internal rotor with a three-phase winding, whether or not equipped with a worm, of a specified temperature range covering at least $-20\text{ }^{\circ}\text{C}$ to $+70\text{ }^{\circ}\text{C}$  | 0 %                     | 31.12.2018                         |
| ex 8501 10 99 | 80    | DC stepping motor, with:<br>— an angle of step of $7,5^{\circ}$ ( $\pm 0,5^{\circ}$ ),<br>— a pull-out torque at $25\text{ }^{\circ}\text{C}$ of 25 mNm or more,<br>— a pull-out pulse rate of 1 960 pps or more,<br>— a two-phase winding, and<br>— a rated voltage of 10,5 V or more, but not more than 16,0 V  | 0 %                     | 31.12.2018                         |
| ex 8501 10 99 | 81    | DC stepping motor, with an angle of step of $18^{\circ}$ or more, a holding torque of 0,5 mNm or more, a coupling bracket the exterior dimensions of which do not exceed $22\text{ mm} \times 68\text{ mm}$ , a two phase winding and an output of not more than 5 W  | 0 %                     | 31.12.2018                         |
| ex 8501 10 99 | 82    | DC motor, brushless, with an external diameter of not more than 29 mm, a rated speed of 1 500 ( $\pm 15\%$ ) rpm or 6 800 ( $\pm 15\%$ ) rpm, a supply voltage of 2 V or 8 V  | 0 %                     | 31.12.2014                         |
| ex 8501 31 00 | 30    | DC motor, brushless, with a three-phase winding, an external diameter of 85 mm or more, but not more than 115 mm, a nominal torque of 2,23 Nm ( $\pm 1,0\text{ Nm}$ ), of an output of more than 120 W but not more than 520 W, calculated with 1 550 rpm ( $\pm 350\text{ rpm}$ ) at a supply voltage of 12 V equipped with electronic circuit with sensors using the Hall effect, for use with an electric power steering control module (power steering motor) (!) | 0 %                     | 31.12.2016                         |
| ex 8501 31 00 | 40    | Permanently excited DC motor with<br>— a multiple-phase winding,<br>— an external diameter of 30 mm or more but not more than 80 mm,  | 0 %                     | 31.12.2014                         |

| CN code       | TARIC | Description  | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|------------------------------------|
| ex 8501 31 00 | 45    | <ul style="list-style-type: none"> <li>— a rated speed of not more than 15 000 rpm,</li> <li>— an output of 45 W or more but not more than 300 W and</li> <li>— a supply voltage of 9 V or more but not more than 25 V</li> </ul> DC motors, brushless, with: <ul style="list-style-type: none"> <li>— an external diameter of 90 mm or more, but not more than 110 mm,</li> <li>— a rated speed of not more than 3 680 rpm,</li> <li>— an output of 600 W or more but not more than 740 W at 2 300 rpm and at 80 °C,</li> <li>— a supply voltage of 12 V,</li> <li>— a torque of not more than 5,67 Nm,</li> <li>— a rotor position sensor,</li> <li>— an electronic star-point relay, and</li> <li>— for use with an electric power steering control module</li> </ul> | 0 %                     | 31.12.2018                         |
| ex 8501 31 00 | 55    | DC motor with commutator, with <ul style="list-style-type: none"> <li>— an external diameter of 27,5 mm or more, but not more than 45 mm,</li> <li>— a rated speed of 11 000 rpm or more, but not more than 23 200 rpm,</li> <li>— a rated supply voltage of 3.6 V or more, but not more than 230 V,</li> <li>— an output power of not more than 529 W,</li> <li>— a free load current of not more than 3.1 A,</li> <li>— a maximum efficiency of 54 % or more,</li> </ul> for driving hand-held power tools   | 0 %                     | 31.12.2018                         |
| ex 8501 31 00 | 60    | Brushless DC motor that can revolve counter clockwise (CCW), with: <ul style="list-style-type: none"> <li>— an input voltage of 264 V or more, but not more than 391 V,</li> <li>— an external diameter of 81 mm (<math>\pm</math> 2,5 mm) or more, but not more than 150 mm (<math>\pm</math> 0,8 mm),</li> <li>— an output power of not more than 125 W,</li> <li>— E or B class winding insulation,</li> </ul> for use in the manufacture of indoor or outdoor units of split-type air conditioning machines <sup>(1)</sup>   | 0 %                     | 31.12.2016                         |
| ex 8501 31 00 | 65    | Fuel cell module containing at least polymer electrolyte membrane fuel cells in a housing with an integrated cooling system, for use in the manufacture of motor vehicle propulsion systems <sup>(1)</sup>   | 0 %                     | 31.12.2018                         |
| ex 8501 31 00 | 70    | DC motors, brushless, with: <ul style="list-style-type: none"> <li>— an external diameter of 80 mm or more, but not more than 100 mm,</li> <li>— a supply voltage of 12 V,</li> <li>— an output at 20 °C of 300 W or more, but not more than 550 W,</li> <li>— a torque 20 °C of 2,90 Nm or more, but not more than 5,30 Nm,</li> <li>— a rated speed at 20 °C of 600 rpm or more, but not more than 1 200 rpm,</li> <li>— equipped with the rotor angle position sensor of resolver type or Hall effect type,</li> </ul> of the kind used in power steering systems for cars  | 0 %                     | 31.12.2017                         |
| ex 8501 33 00 | 30    | Electric drive for motor vehicles, with an output of not more than 315 kW, with:   | 0 %                     | 31.12.2016                         |
| ex 8501 40 80 | 50    |  |                         |                                    |
| ex 8501 53 50 | 10    |  |                         |                                    |

| CN code                        | TARIC    | Description  | Rate of autonomous duty | Date foreseen for mandatory review |
|--------------------------------|----------|--|-------------------------|------------------------------------|
| ex 8501 51 00<br>ex 8501 52 20 | 30<br>50 | AC synchronous servo motor with resolver and brake for a maximum speed of not more than 6 000 rpm, with:<br>— an output of 340 W or more but not more than 7,4 kW,<br>— a flange of dimensions of not more than 180 mm × 180 mm, and<br>— a length from flange to extreme end of resolver of not more than 271 mm  | 0 %                     | 31.12.2016                         |
| ex 8501 62 00                  | 30       | Fuel cell system<br>— consisting of at least phosphoric acid fuel cells,<br>— in a housing with integrated water management and gas treatment,<br>— for permanent, stationary energy supply  | 0 %                     | 31.12.2017                         |
| ex 8503 00 91<br>ex 8503 00 99 | 31<br>32 | Rotor, at the innerside provided with one or two magnetic rings whether or not incorporated in a steel ring  | 0 %                     | 31.12.2018                         |
| ex 8503 00 99                  | 31       | Stamped collector of an electric motor, having an external diameter of not more than 16 mm   | 0 %                     | 31.12.2018                         |
| ex 8503 00 99                  | 33       | Stator for brushless motor of electrical power steering with a roundness tolerance of 50 µm  | 0 %                     | 31.12.2016                         |
| ex 8503 00 99                  | 34       | Rotor for brushless motor of electrical power steering with a roundness tolerance of 50 µm   | 0 %                     | 31.12.2016                         |
| ex 8503 00 99                  | 35       | Transmitter resolver for brushless motors of electrical power steering   | 0 %                     | 31.12.2014                         |
| ex 8503 00 99                  | 40       | Fuel cell membrane, in rolls or sheets, with a width of not more than 150 cm, of a kind used for manufacture of fuel cells in heading 8501   | 0 %                     | 31.12.2017                         |
| ex 8504 31 80                  | 20       | Transformer for use in the manufacture of inverters in LCD modules <sup>(1)</sup>  | 0 %                     | 31.12.2017                         |
| ex 8504 31 80                  | 30       | Switching transformers, having a power handling capacity of not more than 1 kVA for use in the manufacture of static converters <sup>(1)</sup>   | 0 %                     | 31.12.2018                         |
| ex 8504 31 80                  | 40       | Electrical transformers:<br>— with a capacity of 1 kVA or less<br>— without plugs or cables,<br>for internal use in the manufacture of set top boxes and TVs <sup>(1)</sup>  | 0 %                     | 31.12.2017                         |
| ex 8504 40 82                  | 40       | Printed circuit board equipped with a bridge rectifier circuit and other active and passive components:<br>— with two output connectors<br>— with two input connectors which are available and useable in parallel<br>— able to switch between bright and dimmed operation mode<br>— with an input voltage of 40 V (+ 25 % – 15 %) or 42 V (+ 25 % – 15 %) in bright operation mode, with an input voltage of 30 V (± 4 V) in dimmed operation mode, or<br>— with an input voltage of 230 V (+ 20 % – 15 %) in bright operation mode, with an input voltage of 160 V (± 15 %) in dimmed operation mode, or<br>— with an input voltage of 120 V (15 % – 35 %) in bright operation mode, with an input voltage of 60 V (± 20 %) in dimmed operation mode<br>— with an input current reaching 80 % of its nominal value within 20 ms<br>— with an input frequency of 45 Hz or more, but not more than 65 Hz for 42 V and 230 V, and 45-70 Hz for 120 V versions<br>— with an maximum inrush current overshoot of not more than 250 % of the input current | 0 %                     | 31.12.2017                         |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
| ex 8504 40 82 | 50    | <ul style="list-style-type: none"> <li>— with a period of the inrush current overshoot of not more than 100 ms</li> <li>— with an input current undershoot of not less than 50 % of the input current</li> <li>— with a period of the inrush current undershoot of not more than 20 ms</li> <li>— with a presettable output current</li> <li>— with an output current reaching 90 % of its nominal pre-set value within 50 ms</li> <li>— with an output current reaching zero within 30 ms after removal of the input voltage</li> <li>— with an defined failure status in case of no-load or too-high load (end-of-life function)</li> </ul> Rectifier in a housing with <ul style="list-style-type: none"> <li>— a rated power of not more than 250 W</li> <li>— an input voltage of 90 V or more, but not more than 305 V</li> <li>— a certified input frequency of 47 Hz or more, but not more than 440 Hz</li> <li>— a constant current output of 350 mA or more, but not more than 15 A</li> <li>— an inrush current of not more than 10 A</li> <li>— an operating temperature range of <math>-40^{\circ}\text{C}</math> or more, but not more than <math>+85^{\circ}\text{C}</math>,</li> <li>— suitable for driving of LED-illuminants</li> </ul> | 0 %                     | 31.12.2017                         |
| ex 8504 40 90 | 20    | Direct current to direct current converter  | 0 %                     | 31.12.2018                         |
| ex 8504 40 90 | 30    | Static converter comprising a power switch with insulated-gate bipolar transistors (IGBTs), contained in a housing, for use in the manufacture of microwave ovens of subheading 8516 50 00 ( <sup>1</sup> )   | 0 %                     | 31.12.2018                         |
| ex 8504 40 90 | 40    | Semiconductor power modules comprising: <ul style="list-style-type: none"> <li>— power transistors,</li> <li>— integrated circuits,</li> <li>— whether or not containing diodes and with or without thermistors,</li> <li>— an operating voltage of not more than 600 V,</li> <li>— not more than three electrical outputs each containing two power switches (whether MOSFET (Metal Oxide Semiconductor Field-Effect Transistor) or IGBT (Insulated Gate Bi-polar Transistors)) and internal drives, and</li> <li>— a rms (root mean square) current rating of not more than 15,7 A</li> </ul>   | 0 %                     | 31.12.2018                         |
| ex 8504 40 90 | 50    | Drive unit for industrial robot with: <ul style="list-style-type: none"> <li>— one or six 3-phase motor outputs with maximum <math>3 \times 32</math> A,</li> <li>— a main power input of 220 V AC or more, but not more than 480 V AC, or 280 V DC or more, but not more than 800 V DC</li> <li>— a logic power input of 24 V DC,</li> <li>— an EtherCat communication interface,</li> <li>— and a dimension of <math>150 \times 140 \times 120</math> mm or more, but not more than <math>335 \times 430 \times 179</math> mm</li> </ul>  | 0 %                     | 31.12.2018                         |
| ex 8504 40 90 | 60    | Transfer moulded semiconductor power module comprising: <ul style="list-style-type: none"> <li>— power transistors,</li> <li>— integrated circuits,</li> <li>— whether or not containing diodes and with or without thermistors,</li> <li>— a circuit configuration,</li> <li>— either containing a direct drive stage with an operating voltage of more than 600 V,</li> </ul>   | 0 %                     | 31.12.2018                         |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
|               |       | — or containing a direct drive stage with an operating voltage of not more than 600 V and a rms current of more than 15,7 A,<br>— or including one or more power factor correction modules  |                         |                                    |
| ex 8504 50 95 | 20    | Inductor with an inductance of not more than 62 mH  | 0 %                     | 31.12.2018                         |
| ex 8504 50 95 | 40    | Coil choke with:<br>— an inductance of 4,7 µH (± 20 %),<br>— a DC resistance of not more than 0,1 Ohms,<br>— an insulation resistance of 100 MOhms or more at 500 V (DC)<br>for use in the manufacture of LCD and LED module power boards <sup>(1)</sup>  | 0 %                     | 31.12.2015                         |
| ex 8504 50 95 | 50    | Solenoid coil with<br>— a power consumption of not more than 6 W,<br>— an insulation resistance of more than 100 M ohms, and<br>— an insert hole of 11,4 mm or more, but not more than 11,8 mm  | 0 %                     | 31.12.2017                         |
| ex 8504 90 11 | 10    | Ferrite cores, other than for deflection yokes  | 0 %                     | 31.12.2018                         |
| ex 8505 11 00 | 31    | Permanent magnet having a remanence of 455 mT (± 15 mT)   | 0 %                     | 31.12.2018                         |
| ex 8505 11 00 | 33    | Permanent magnets consisting of an alloy of neodymium, iron and boron, either in the shape of a rounded rectangle with measurements of not more than 15 mm × 10 mm × 2 mm, or in the shape of a disc with a diameter of not more than 90mm, whether or not containing a hole in the centre  | 0 %                     | 31.12.2018                         |
| ex 8505 11 00 | 35    | Permanent magnets of an alloy of either neodymium, iron and boron, or samarium and cobalt coated having undergone inorganic passivation (inorganic coating) using zinc phosphate for the industrial manufacture of products in motor or sensory applications <sup>(1)</sup>   | 0 %                     | 31.12.2017                         |
| ex 8505 11 00 | 50    | Bars specifically shaped, intended to become permanent magnets after magnetization, containing neodymium, iron and boron, with dimensions:<br>— a length of 15 mm or more but not more than 52 mm,<br>— a width of 5 mm or more but not more than 42 mm,<br>of a kind to be used in the manufacture of electric servomotors for industrial automation | 0 %                     | 31.12.2017                         |
| ex 8505 11 00 | 60    | Rings, tubes, bushings or collars made from an alloy of neodymium, iron and boron, with<br>— a diameter of not more than 45 mm,<br>— a height of not more than 45 mm,<br>of a kind used in the manufacture of permanent magnets after magnetisation   | 0 %                     | 31.12.2017                         |
| ex 8505 11 00 | 70    | Disc:<br>— with a diameter of not more than 90 mm,<br>— whether or not containing a hole in the centre,<br>— consisting of an alloy of neodymium, iron and boron, covered with nickel, that after magnetisation is intended to become permanent magnet,<br>of a kind used in car loudspeakers   | 0 %                     | 31.12.2018                         |
| ex 8505 11 00 | 80    | Articles in the form of a triangle, square or rectangle, intended to become permanent magnets after magnetization, containing neodymium, iron and boron, with dimensions:<br>— a length of 15 mm or more but not more than 105 mm,<br>— a width of 5 mm or more but not more than 105 mm,<br>— a height of 3 mm or more but not more than 55 mm       | 0 %                     | 31.12.2018                         |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
| ex 8505 19 90 | 30    | Articles of agglomerated ferrite in the shape of a disc with a diameter of not more than 120 mm, containing a hole in the centre intended to become permanent magnets after magnetization with a remanence between 350 mT and 470 mT  | 0 %                     | 31.12.2018                         |
| ex 8505 20 00 | 30    | Electromagnetic clutch, for use in the manufacture of compressors of air conditioning machines of motor vehicles <sup>(1)</sup>   | 0 %                     | 31.12.2018                         |
| ex 8505 90 20 | 91    | Solenoid with a plunger, operating at a nominal supply voltage of 24 V at a nominal DC of 0,08 A, for use in the manufacture of products falling within heading 8517 <sup>(1)</sup>   | 0 %                     | 31.12.2018                         |
| ex 8506 50 90 | 10    | Lithium iodine single cell battery the dimensions of which do not exceed 9 mm × 23 mm × 45 mm and a voltage of not more than 2,8 V  | 0 %                     | 31.12.2018                         |
| ex 8506 50 90 | 20    | Unit consisting of not more than 2 lithium batteries embedded in a socket for integrated circuits (battery-buffered socket), with not more than 32 connections and incorporating a control circuit  | 0 %                     | 31.12.2018                         |
| ex 8506 50 90 | 30    | Lithium-iodine or lithium-silver vanadium oxide single cell battery of dimensions of not more than 28 mm × 45 mm × 15 mm and a capacity of not less than 1,05 Ah  | 0 %                     | 31.12.2018                         |
| ex 8507 10 20 | 80    | Lead acid starter battery, with:<br>— a charge acceptance capacity of 200 % or more of the level of an equivalent conventional flooded battery during the first 5 seconds of charge,<br>— a liquid electrolyte,<br>for use in the manufacture of passenger cars and light commercial vehicles employing high regenerative alternator controls or start/stop systems with high regenerative alternator controls <sup>(1)</sup> | 0 %                     | 31.12.2015                         |
| ex 8507 30 20 | 30    | Cylindrical nickel-cadmium accumulator, with a length of 65,3 mm (± 1,5 mm) and a diameter of 14,5 mm (± 1 mm), having a nominal capacity of 1 000 mAh or more, for use in the manufacture of rechargeable batteries <sup>(1)</sup>   | 0 %                     | 31.12.2018                         |
| ex 8507 50 00 | 20    | Rectangular accumulator, with a length of not more than 69 mm, a width of not more than 36 mm and a thickness of not more than 12 mm, for use in the manufacture of rechargeable batteries <sup>(1)</sup>   | 0 %                     | 31.12.2018                         |
| ex 8507 60 00 | 20    |   |                         |                                    |
| ex 8507 50 00 | 30    | Cylindrical nickel-hydride accumulator, of a diameter of not more than 14,5 mm, for the manufacture of rechargeable batteries <sup>(1)</sup>  | 0 %                     | 31.12.2018                         |
| ex 8507 60 00 | 25    | Rectangular modules for incorporation in lithium-ion rechargeable batteries, with:<br>— a width of 352,5 mm (± 1 mm) or 367,1 mm (± 1mm)<br>— a depth of 300 mm (± 2 mm) or 272,6 mm (± 1 mm)<br>— a height of 268,9 mm (± 1,4 mm) or 229,5 mm (± 1mm)<br>— a weight of 45,9 kg or 46,3 kg<br>— a rating of 75 Ah and<br>— a nominal voltage of 60 V  | 0 %                     | 31.12.2017                         |
| ex 8507 60 00 | 30    | Cylindrical lithium-ion accumulator, with a length of 63 mm or more and a diameter of 17,2 mm or more, having a nominal capacity of 1 200 mAh or more, for use in the manufacture of rechargeable batteries <sup>(1)</sup>  | 0 %                     | 31.12.2014                         |
| ex 8507 60 00 | 35    | Lithium-ion rechargeable batteries, with:<br>— a length of 1 475 mm or more, but not more than 2 200 mm<br>— a width of 935 mm or more, but not more than 1 400 mm<br>— a height of 260 mm or more, but not more than 310 mm  | 0 %                     | 31.12.2017                         |

| CN code       | TARIC | Description  | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|------------------------------------|
| ex 8507 60 00 | 40    | <ul style="list-style-type: none"> <li>— a weight of 320 kg or more, but not more than 390 kg</li> <li>— a nominal capacity of 18,4 Ah or more, but not more than 130 Ah,</li> <li>— put up in packs of 12 or 16 modules</li> </ul> Batteries of ion-lithium electric accumulators rechargeable with: <ul style="list-style-type: none"> <li>— a length of 1 203 mm or more, but not more than 1 297 mm,</li> <li>— a width of 282 mm or more, but not more than 772 mm,</li> <li>— a height of 792 mm or more, but not more than 839 mm,</li> <li>— a weight of 260 kg or more, but not more than 293 kg,</li> <li>— power of 22 kWh or 26 kWh, and</li> <li>— constituted of 24 or 48 modules</li> </ul> | 0 %                     | 31.12.2017                         |
| ex 8507 60 00 | 50    | Modules for the assembly of batteries of ion lithium electric accumulators with: <ul style="list-style-type: none"> <li>— a length of 298 mm or more, but not more than 408 mm,</li> <li>— a width of 33,5 mm or more, but not more than 209 mm,</li> <li>— a height of 138 mm or more, but not more than 228 mm,</li> <li>— a weight of 3,6 kg or more, but not more than 17 kg, and</li> <li>— a power of 458 kWh or more, but not more than 2 158 kWh</li> </ul>  | 0 %                     | 31.12.2017                         |
| ex 8507 60 00 | 55    | Lithium-ion accumulator in cylindrical form, with: <ul style="list-style-type: none"> <li>— a base similar to an ellipse squeezed in the middle,</li> <li>— a length of 49 mm or more (not including terminals),</li> <li>— a width of 33,5 mm or more,</li> <li>— a thickness of 9,9 mm or more,</li> <li>— a rated capacity of 1,75 Ah or more, and</li> <li>— a rated voltage of 3,7 V,</li> </ul> for the manufacture of rechargeable batteries <sup>(1)</sup>   | 0 %                     | 31.12.2017                         |
| ex 8507 60 00 | 57    | Lithium-ion accumulator, cuboid in shape, with: <ul style="list-style-type: none"> <li>— some of the corners rounded off,</li> <li>— a length of 76 mm or more (not including terminals),</li> <li>— a width of 54,5 mm or more,</li> <li>— a thickness of 5,2 mm or more,</li> <li>— a rated capacity of 3 100 mAh or more, and</li> <li>— a rated voltage of 3,7 V,</li> </ul> for the manufacture of rechargeable batteries <sup>(1)</sup>  | 0 %                     | 31.12.2017                         |
| ex 8507 60 00 | 60    | Lithium-ion rechargeable batteries, with: <ul style="list-style-type: none"> <li>— a length of 1 213 mm or more, but not more than 1 575 mm,</li> <li>— a width of 245 mm or more but not more than 1 200 mm,</li> <li>— a height of 265 mm or more, but not more than 755 mm,</li> <li>— a weight of 265 kg or more but not more than 294 kg,</li> <li>— a nominal capacity of 66,6 Ah,</li> </ul> put up in packs of 48 modules  | 0 %                     | 31.12.2015                         |
| ex 8507 60 00 | 65    | Cylindrical Lithium Ion Cell with <ul style="list-style-type: none"> <li>— 3,5 VDC to 3,8 VDC,</li> <li>— 300 mAh to 900 mAh and</li> <li>— a diameter of 10,0 mm to 14,5 mm</li> </ul>  | 0 %                     | 31.12.2016                         |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
| ex 8507 60 00 | 70    | Rectangular modules for incorporation in lithium-ion rechargeable batteries:<br>— of a length of 350 mm or 312 mm,<br>— of a width of 79,8 mm or 225 mm,<br>— of a height of 168 mm or 35 mm,<br>— of a weight of 6,2 kg or 3,95 kg,<br>— with a rating of 129 Ah or 66,6 Ah  | 0 %                     | 31.12.2015                         |
| ex 8507 60 00 | 75    | Rectangular lithium-ion-accumulator, with<br>— a metal casing,<br>— a length of 173 mm ( $\pm 0,15$ mm),<br>— a width of 21 mm ( $\pm 0,1$ mm),<br>— a height of 91 mm ( $\pm 0,15$ mm),<br>— a nominal voltage of 3,3 V and,<br>— a nominal capacity of 21 Ah or more  | 0 %                     | 31.12.2016                         |
| ex 8507 60 00 | 80    | Rectangular lithium-ion-accumulator, with<br>— a metal casing,<br>— a length of 171 mm ( $\pm 3$ mm),<br>— a width of 45,5 mm ( $\pm 1$ mm),<br>— a height of 115 mm ( $\pm 1$ mm),<br>— a nominal voltage of 3,75 V and<br>— a nominal capacity of 50 Ah<br>for use in the manufacture of rechargeable batteries for motor vehicles <sup>(1)</sup>                             | 0 %                     | 31.12.2015                         |
| ex 8507 90 80 | 70    | Cut plate of nickel-plated copper foil, with:<br>— a width of 70 mm ( $\pm 5$ mm),<br>— a thickness of 0,4 mm ( $\pm 0,2$ mm),<br>— a length of not more than 55 mm,<br>for use in the manufacture of lithium-ion electric vehicle batteries <sup>(1)</sup>   | 0 %                     | 31.12.2016                         |
| ex 8508 70 00 | 10    | Electronic circuit card without separate housing for actuating and controlling vacuum cleaner brushes powered by not more than 300 W  | 0 %                     | 31.12.2015                         |
| ex 8537 10 99 | 96    |   |                         |                                    |
| ex 8508 70 00 | 20    | Electronic circuit cards that:  | 0 %                     | 31.12.2015                         |
| ex 8537 10 99 | 98    | — are connected by wire or radio frequency to each other and the motor controller card, and<br>— regulate the functioning (switching on or off and suction capacity) of vacuum cleaners according to a stored program,<br>— whether or not fitted with indicators that display the functioning of the vacuum cleaner (suction capacity and/or dust bag full and/or filter full) |                         |                                    |
| ex 8512 40 00 | 10    | Car door mirror heating foil:   | 0 %                     | 31.12.2018                         |
| ex 8516 80 20 | 20    | — with two electrical contacts,<br>— with an adhesive layer on both sides (on the side of the plastic holder of the mirror and on the side of the mirror glass),<br>— with a protective paper film on both sides  |                         |                                    |
| ex 8516 90 00 | 60    | Ventilation sub-assembly of an electric deep-fat fryer:<br>— fitted with a motor having a power rating of 8 W at 4 600 rpm,<br>— governed by an electronic circuit,<br>— operating at ambient temperatures above 110 °C,<br>— fitted with a thermoregulator   | 0 %                     | 31.12.2014                         |

| CN code       | TARIC | Description  | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|------------------------------------|
| ex 8516 90 00 | 70    | Inner pot:<br>— containing side and central openings,<br>— of annealed aluminium,<br>— with a ceramic coating, heat resistant to more than 200 °C<br>for use in the manufacture of an electric fryer <sup>(1)</sup>  | 0 %                     | 31.12.2017                         |
| ex 8518 29 95 | 30    | Loudspeakers of:<br>— an impedance of 4 Ohm or more, but not more than 16 Ohm,<br>— a nominal power of 2 W or more, but not more than 20 W,<br>— with or without plastic bracket, and<br>— with or without electric cable fitted with connectors,<br>of a kind used for TV sets and video monitors manufacture   | 0 %                     | 31.12.2017                         |
| ex 8518 30 95 | 20    | Headphone and earphone for hearing aids, contained in a housing the exterior dimensions of which, excluding connecting points, do not exceed 5 mm × 6 mm × 8 mm  | 0 %                     | 31.12.2018                         |
| ex 8518 40 80 | 91    | Circuit board sub-assembly, comprising digital audio signal decoding, audio signal processing and amplification with dual and/or multi-channel functionality   | 0 %                     | 31.12.2014                         |
| ex 8518 40 80 | 92    | Circuit board sub-assembly, comprising power supply, active equalizer and power amplifier circuits   | 0 %                     | 31.12.2015                         |
| ex 8518 90 00 | 91    | Integrally cold-upsetted steel coreplate, in the form of a disk on one side provided with a cylinder, for use in the manufacture of loudspeakers <sup>(1)</sup>  | 0 %                     | 31.12.2018                         |
| ex 8521 90 00 | 20    | Digital video recorder:<br>— without a hard disk drive,<br>— with or without a DVD-RW drive,<br>— with either motion detection or capability of motion detection through IP connectivity via LAN connector<br>— with or without a USB serial port,<br>for use in the manufacture of Closed-circuit television (CCTV) surveillance systems <sup>(1)</sup>   | 0 %                     | 31.12.2014                         |
| ex 8522 90 49 | 50    | Electronic assembly for a laser read-head of a compact disc player, comprising:<br>— a printed circuit,<br>— a photo-detector, in the form of a monolithic integrated circuit, contained in a housing,<br>— not more than 3 connectors,<br>— not more than 1 transistor,<br>— not more than 3 variable and 4 fixed resistors,<br>— not more than 5 capacitors,<br>the whole mounted on a support | 0 %                     | 31.12.2018                         |
| ex 8522 90 49 | 60    | Printed circuit board assembly comprising:   | 0 %                     | 31.12.2014                         |
| ex 8527 99 00 | 10    | — a radio tuner (capable of receiving and decoding radio signals and transmitting those signals within the assembly) without signal processing capabilities,   |                         |                                    |
| ex 8529 90 65 | 25    | — a microprocessor capable of receiving remote control messages and controlling the tuner chipset,<br>for use in the manufacture of home entertainment systems <sup>(1)</sup>  |                         |                                    |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
| ex 8522 90 49 | 65    | Printed circuit board subassembly, comprising:  | 0 %                     | 31.12.2014                         |
| ex 8527 99 00 | 20    | — a radio tuner, capable of receiving and decoding radio signals and transmitting those signals within the assembly, with a signal decoder,   |                         |                                    |
| ex 8529 90 65 | 40    | — a radio frequency (RF) remote control receiver,<br>— an infrared remote control signal transmitter,<br>— a SCART signal generator<br>— a TV state sensor<br>for use in the manufacture of home entertainment systems <sup>(1)</sup>   |                         |                                    |
| ex 8522 90 49 | 70    | Assembly, comprising at least a flexible printed circuit, a laser driver integrated circuit and a signal converter integrated circuit   | 0 %                     | 31.12.2018                         |
| ex 8522 90 80 | 15    | Heat sinks and cooling fins of aluminium, for maintaining the operating temperature of transistors and/or integrated circuits in products of heading 8521   | 0 %                     | 31.12.2017                         |
| ex 8522 90 80 | 30    | Holder, fixing item or internal stiffener of metal, for use in the manufacture of televisions, monitors and video players <sup>(1)</sup>  | 0 %                     | 31.12.2016                         |
| ex 8529 90 92 | 30    |   |                         |                                    |
| ex 8522 90 80 | 65    | Assembly for optical discs, comprising at least an optical unit and DC motors, whether or not capable of double layer recording   | 0 %                     | 31.12.2018                         |
| ex 8522 90 80 | 70    | Video tape recording/reproducing assembly comprising at least a motor and a printed circuit board containing integrated circuits with driver or control functions, whether or not incorporating a transformer, for use in the manufacture of products falling within heading 8521 <sup>(1)</sup>  | 0 %                     | 31.12.2018                         |
| ex 8522 90 80 | 75    | Optical reading head for CD player, consisting of one laser diode, one photo detector integrated circuit and one beam splitter  | 0 %                     | 31.12.2018                         |
| ex 8522 90 80 | 80    | Laser optical drive unit assembly (so called mecha units) for the recording and/or reproduction of digital video and/or audio signals, comprising at least a laser optical reading and/or writing unit, one or more DC motors and not containing a printed circuit board or containing a printed circuit board not capable of signal processing for sounds and images, for use in the manufacture of products falling within headings 8519, 8521, 8526, 8527, 8528 or 8543 <sup>(1)</sup> | 0 %                     | 31.12.2018                         |
| ex 8522 90 80 | 81    | Laser optical pick up unit for the reproduction of optical signals from CD or DVD and the recording of optical signal on DVD, comprising at least<br>— a laser diode,<br>— a laser driver integrated circuit,<br>— a photo detector integrated circuit,<br>— a front monitor integrated circuit and an actuator,<br>for use in the manufacture of products falling within heading 8521 <sup>(1)</sup>   | 0 %                     | 31.12.2016                         |
| ex 8522 90 80 | 83    | Blu-ray optical pick-up unit, whether or not recordable, for use with Blu-ray, DVD and CD discs, comprising at least:<br>— laser diodes operating at three different wavelengths,<br>— a photo detector integrated circuit and<br>— an actuator,<br>for the manufacture of products falling within heading 8521 <sup>(1)</sup>  | 0 %                     | 31.12.2018                         |
| ex 8522 90 80 | 84    | Blu-ray drive mechanism, whether or not recordable, for use with Blu-ray, DVD and CD discs, comprising at least:<br>— an optical pick up unit with laser diodes operating at three different wavelengths,<br>— a spindle motor,<br>— a stepping motor   | 0 %                     | 31.12.2018                         |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
| ex 8522 90 80 | 85    | Video head drum, with video heads or with video and audio heads and an electric motor, for use in the manufacture of products falling within heading 8521 <sup>(1)</sup>  | 0 %                     | 31.12.2018                         |
| ex 8522 90 80 | 96    | Hard disk drive, for incorporation in products of heading 8521 <sup>(1)</sup>   | 0 %                     | 31.12.2017                         |
| ex 8522 90 80 | 97    | Tuner transforming high-frequency signals into mid-frequency signals, for use in the manufacture of products falling under headings 8521 and 8528 <sup>(1)</sup>  | 0 %                     | 31.12.2016                         |
| ex 8529 90 65 | 50    |   |                         |                                    |
| ex 8525 80 19 | 20    | Assembly for television cameras of dimensions of not more than 10 mm × 15 mm × 18 mm, comprising an image sensor, an objective and a color processor, having an image resolution of not more than 1 024 × 1 280 pixels, whether or not fitted with cable and/or housing, for the manufacture of goods of subheading 8517 12 00 <sup>(1)</sup>   | 0 %                     | 31.12.2018                         |
| ex 8525 80 19 | 25    | Long wavelength infrared camera (LWIR camera) (according to ISO/TS 16949), with: <ul style="list-style-type: none"> <li>— a sensitivity in the wavelength area of 8 µm or more, but not more than 14 µm,</li> <li>— a resolution of 324 × 256 pixels,</li> <li>— a weight of not more than 400 g,</li> <li>— measurements of not more than 70 mm × 67 mm × 75 mm,</li> <li>— a waterproof housing and an automotive- qualified plug and</li> <li>— a deviation of the output signal over the entire work temperature range of not more than 20 %</li> </ul> | 0 %                     | 31.12.2014                         |
| ex 8525 80 19 | 31    | Closed circuit television (CCTV) camera:  | 0 %                     | 01.07.2014                         |
| ex 8525 80 91 | 10    | <ul style="list-style-type: none"> <li>— of a weight of not more than 5,9 kg,</li> <li>— without a housing,</li> <li>— of dimensions of not more than 405 mm × 315 mm,</li> <li>— with a single Charge-Couple-Device (CCD) or Complementary Metal-Oxide-Semiconductor (CMOS) sensor,</li> <li>— with effective pixels of not more than 5 megapixels,</li> </ul> for use in CCTV surveillance systems <sup>(1)</sup>   |                         |                                    |
| ex 8525 80 19 | 35    | Image scanning cameras, using: <ul style="list-style-type: none"> <li>— a „Dynamic overlay lines“ system,</li> <li>— an output NTSC video signal,</li> <li>— a voltage of 6,5 V,</li> <li>— an illuminance of 0,5 lux or more</li> </ul>  | 0 %                     | 31.12.2014                         |
| ex 8525 80 19 | 40    | Assembly for cameras used in computer notebooks of dimensions of not more than 15 mm × 25 mm × 25 mm, comprising an image sensor, an objective and a colour processor, having an image resolution of not more than 1 600 × 1 200 pixels, whether or not fitted with cable and/or housing, whether or not mounted on a base and containing a LED chip <sup>(1)</sup>   | 0 %                     | 31.12.2016                         |
| ex 8525 80 19 | 45    | Camera module with a resolution of 1 280 * 720 P HD, with two microphones, for use in the manufacture of products of heading 8528 <sup>(1)</sup>  | 0 %                     | 31.12.2017                         |
| ex 8526 91 20 | 80    | Integrated audio module (IAM) with a digital video output for connection to an LCD touch screen monitor, interfaced over the Media Oriented Systems Transport (MOST) network and transported over the MOST High protocol, with or without   | 0 %                     | 31.12.2015                         |
| ex 8527 29 00 | 10    | <ul style="list-style-type: none"> <li>— a printed circuit board (PCB) containing a Global Positioning System (GPS) receiver, a gyroscope, and a Traffic Message Channel (TMC) tuner,</li> <li>— a hard disk drive supporting multiple maps,</li> <li>— a HD radio,</li> <li>— a voice recognition system,</li> </ul>   |                         |                                    |

| CN code       | TARIC | Description  | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|------------------------------------|
|               |       | — a CD and DVD drive,<br>and including<br>— Bluetooth, MP3 and USB input connectivity,<br>— a voltage of 10 V or more but not more than 16 V,<br>for the use in the manufacture of vehicles in Chapter 87 <sup>(1)</sup>   |                         |                                    |
| ex 8527 91 99 | 10    | Assembly consisting of at least:   | 0 %                     | 31.12.2014                         |
| ex 8529 90 65 | 35    | — an audio frequency amplifier unit, comprising at least an audio frequency amplifier and a sound generator,<br>— a transformer and<br>— a radio broadcast receiver  |                         |                                    |
| ex 8528 49 10 | 10    | Video monitor comprising:<br>— a flat screen monochrome cathode-ray tube with a diagonal measurement of the screen of not more than 110 mm and equipped with a deflector yoke, and<br>— a printed circuit on which are mounted a deflection unit, a video-amplifier and a transformer,<br>the whole mounted or not on a chassis, for the manufacture of video entry-phones, video telephones or surveillance apparatus <sup>(1)</sup>                        | 0 %                     | 31.12.2018                         |
| ex 8528 59 70 | 10    | Liquid crystal display colour video monitors, excluding those combined with other apparatus, having a DC input voltage of 7 V or more but not more than 30 V, with a diagonal measurement of the screen of 33,2 cm or less,<br>— without a housing, with back cover and mounting frame,<br>— or with a housing,<br>used for permanent incorporation or permanent mounting, during industrial assembly, into goods of Chapters 84 to 90 and 94 <sup>(1)</sup> | 0 %                     | 30.06.2014                         |
| ex 8529 10 80 | 20    | Ceramic filter package comprising 2 ceramic filters and 1 ceramic resonator for a frequency of 10,7 MHz ( $\pm$ 30 kHz), contained in a housing  | 0 %                     | 31.12.2018                         |
| ex 8529 10 80 | 50    | Ceramic filter for a centre frequency of 450 kHz ( $\pm$ 1,5 kHz) or 455 kHz ( $\pm$ 1,5 kHz), with a bandwidth of not more than 30 kHz at 6 dB and not more than 70 kHz at 40 dB, contained in a housing  | 0 %                     | 31.12.2018                         |
| ex 8529 10 80 | 60    | Filters, excluding surface acoustic wave filters, for a center frequency of 485 MHz or more but not more than 1 990 MHz with an insertion loss of not more than 3,5 dB, contained in a housing   | 0 %                     | 31.12.2018                         |
| ex 8529 90 65 | 30    | Parts of TV-apparatus, having micro-processor and video-processor functions, comprising at least a micro-controller and a video-processor, mounted on a leadframe and contained in a plastic housing   | 0 %                     | 31.12.2018                         |
| ex 8548 90 90 | 44    |  |                         |                                    |
| ex 8529 90 65 | 45    | Satellite radio receiver module transforming satellite high frequency signals to digital audio coded signal, for use in the manufacture of products falling within heading 8527 <sup>(1)</sup>   | 0 %                     | 31.12.2014                         |
| ex 8529 90 65 | 55    | Ambient light LED board to be incorporated in goods of heading 8528 <sup>(1)</sup>   | 0 %                     | 31.12.2015                         |
| ex 8529 90 65 | 60    | Tuner transforming high frequency signals to mid frequency signals for use in the manufacture of satellite or terrestrial TV receivers for set-top boxes <sup>(1)</sup>  | 0 %                     | 31.12.2016                         |
| ex 8529 90 65 | 65    | Printed circuit board for distributing supply voltage and control signals directly to a control circuit on a TFT glass panel of a LCD module   | 0 %                     | 31.12.2015                         |
| ex 8529 90 65 | 70    | Unit driver consisting of an electronic integrated circuit and a flexible printed circuit, for use in the manufacture of LCD modules <sup>(1)</sup>  | 0 %                     | 31.12.2016                         |

| CN code       | TARIC | Description  | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|------------------------------------|
| ex 8529 90 65 | 75    | Modules comprising at least semiconductor chips for:<br>— the generation of driving signals for pixel addressing, or<br>— driving addressing pixels  | 0 %                     | 31.12.2017                         |
| ex 8529 90 92 | 25    | LCD modules, not combined with touch screen facilities, solely consisting of:<br>— one or more TFT glass or plastic cells,<br>— a die cast heat sink,<br>— a backlight unit,<br>— one printed circuit board with micro controller, and<br>— LVDS (Low Voltage Differential Signalling) interface,<br>for use in the manufacture of radios for motor vehicles <sup>(1)</sup>  | 0 %                     | 31.12.2015                         |
| ex 8529 90 92 | 32    | Optical unit for video projection, comprising a colour separation system, a positioning mechanism and lenses, for use in the manufacture of products falling within heading 8528 <sup>(1)</sup>  | 0 %                     | 31.12.2018                         |
| ex 8529 90 92 | 40    | Assembly comprising prisms, digital micromirror device (DMD) chips and electronic control circuits, for the manufacture of television projection equipments or video projectors <sup>(1)</sup>   | 0 %                     | 31.12.2018                         |
| ex 8529 90 92 | 41    | Digital micromirror device (DMD)-chips, for use in the manufacture of video projectors <sup>(1)</sup>  | 0 %                     | 31.12.2018                         |
| ex 8529 90 92 | 42    | Heat sinks and cooling fins of aluminium, for maintaining the operating temperature of transistors and integrated circuits in television sets <sup>(1)</sup>   | 0 %                     | 31.12.2018                         |
| ex 8529 90 92 | 43    | Plasma display module incorporating only address and display electrodes, with or without driver and/or control electronics for pixel address only and with or without a power supply   | 0 %                     | 31.12.2018                         |
| ex 8529 90 92 | 44    | LCD modules, solely consisting of one or more TFT glass or plastic cells, not combined with touch screen facilities, with or without backlight unit, with or without inverters and one or more printed circuit boards with control electronics for pixel addressing only   | 0 %                     | 31.12.2018                         |
| ex 8529 90 92 | 45    | Integrated circuit package with TV reception functionality containing a channel decoder die, tuner die, power management die, GSM filters and discrete as well as embedded passive circuit elements for reception of digitally broadcasting videosegments of DVB-T and DVB-H formats   | 0 %                     | 31.12.2018                         |
| ex 8529 90 92 | 47    | Area image sensors ("progressive scan" Interline CCD-Sensor or CMOS-Sensor) for digital video cameras in the form of analogue or digital, monolithic integrated circuit with pixels of not more than 12 µm × 12 µm in monochromatic version with microlenses applied to each individual pixel (microlens array) or in polychromatic version with a colour filter, whether or not with a lenslet (micro lens) array with one lenslet mounted on each individual pixel | 0 %                     | 31.12.2014                         |
| ex 8529 90 92 | 48    | Aluminium die cast heat sink, for maintaining the operating temperature of transistors and integrated circuits, for use in the manufacture of products falling within heading 8527 <sup>(1)</sup>  | 0 %                     | 31.12.2014                         |
| ex 8529 90 92 | 49    | AC socket with a noise filter, composed of:  | 0 %                     | 31.12.2014                         |
| ex 8536 69 90 | 83    | — AC socket (for power cord connection) of 230 V,<br>— integrated noise filter composed of capacitors and inductors,<br>— cable connector for connecting an AC socket with the PDP (Plasma display panel) power supply unit,<br>whether or not equipped with a metal support, which joins the AC socket to the PDP TV set  |                         |                                    |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
| ex 8529 90 92 | 50    | Colour LCD display panel for LCD monitors of heading 8528:<br>— with a diagonal measurement of the screen of 14,48 cm or more but not more than 31,24 cm,<br>— with backlight, micro-controller,<br>— with a CAN (Controller area network)-controller with LVDS (Low-voltage differential signalling) interface and CAN/power supply socket or with an APIX (Automotive Pixel Link) controller with APIX interface,<br>— in a housing with or without a heat sink at the back of the housing,<br>— without a signal-processing module,<br>for use in the manufacture of vehicles of chapter 87 <sup>(1)</sup> | 0 %                     | 31.12.2015                         |
| ex 8529 90 92 | 70    | Rectangular fastening and covering frame:<br>— of an aluminium alloy containing silicon and magnesium,<br>— with a length of 900 mm or more but not more than 1 500 mm,<br>— with a width of 600 mm or more but not more than 950 mm,<br>of a kind used for the production of TV sets   | 0 %                     | 31.12.2017                         |
| ex 8531 80 95 | 40    | Electro-acoustic transducer   | 0 %                     | 31.12.2018                         |
| ex 8535 90 00 | 20    | Printed circuit board in the form of plates consisting of isolating material with electrical connections and solder points, for use in the manufacture of back light units for LCD modules <sup>(1)</sup>   | 0 %                     | 31.12.2018                         |
| ex 8535 90 00 | 30    | Semiconductor module switch in a casing:  | 0 %                     | 31.12.2015                         |
| ex 8536 50 80 | 83    | — consisting of an IGBT transistor chip and a diode chip on one or more lead frames,<br>— for a voltage of 600 V or 1 200 V   |                         |                                    |
| ex 8536 30 30 | 11    | Thermo-electric switch with a cut-off current of 50 A or more, comprising a snap action switch, for direct mounting on an electric motor coil, contained in a hermetically sealed housing   | 0 %                     | 31.12.2018                         |
| ex 8536 49 00 | 91    | Thermal relays contained in a hermetically sealed glass cartridge of not more than 35 mm in length excluding wires, with a maximum leakage rate of $10^{-6}$ cm <sup>3</sup> He/sec at one bar in the temperature range 0 °C to 160 °C, to be incorporated into compressors for refrigerating equipment <sup>(1)</sup>  | 0 %                     | 31.12.2018                         |
| ex 8536 50 11 | 31    | Switch of the printed circuit mount type, operating at a force of 4,9 N ( $\pm$ 0,9 N), contained in a housing  | 0 %                     | 31.12.2018                         |
| ex 8536 50 11 | 32    | Mechanical tact switch for connecting electronic circuits, operating at a voltage of not more than 60V and at a current strength of not more than 50mA, for use in the manufacture of products of headings 8521 or 8528 <sup>(1)</sup>  | 0 %                     | 31.12.2018                         |
| ex 8536 50 19 | 91    | Hall effect switch, comprising 1 magnet, 1 Hall effect sensor and 2 capacitors, contained in a housing with 3 connections   | 0 %                     | 31.12.2018                         |
| ex 8536 50 19 | 93    | Devices, having adjustable controller and switching functions, comprising one   | 0 %                     | 31.12.2018                         |
| ex 8536 50 80 | 97    | ore more monolithic integrated circuits whether or not combined with semiconductor elements, mounted together on a leadframe and contained in a plastic housing   |                         |                                    |
| ex 8536 50 80 | 81    | Mechanical speed governor switches for connecting electrical circuits, with:<br>— a voltage of 240 V or more but not more than 250 V,<br>— an amperage of 4 A or more but not more than 6 A,<br>for use in the manufacture of machines falling within heading 8467 <sup>(1)</sup>   | 0 %                     | 31.12.2014                         |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
| ex 8536 50 80 | 82    | Mechanical switches for connecting electrical circuits, with:<br>— a voltage of 240 V or more but not more than 300 V,<br>— an amperage of 3 A or more but not more than 15 A,<br>for use in the manufacture of machines falling within heading 8467 <sup>(1)</sup>   | 0 %                     | 31.12.2014                         |
| ex 8536 50 80 | 93    | Switch unit for coaxial cable, comprising 3 electromagnetic switches, with a switching time of not more than 50 ms and an actuating current of not more than 500 mA at a voltage of 12 V  | 0 %                     | 31.12.2018                         |
| ex 8536 50 80 | 98    | Mechanical push-button switch for connecting electronic circuits, operating at a voltage of 220 V or more but not more than 250 V and at a current strength of not more than 5 A, for use in the manufacture of products of headings 8521 or 8528 <sup>(1)</sup>  | 0 %                     | 31.12.2018                         |
| ex 8536 69 90 | 51    | SCART type connectors, built into a plastic or metal housing, with 21 pins in 2 rows, for use in the manufacture of products falling within headings 8521 and 8528 <sup>(1)</sup>   | 0 %                     | 31.12.2017                         |
| ex 8536 69 90 | 81    | Pitch connector for use in the manufacture of LCD television reception apparatus <sup>(1)</sup>   | 0 %                     | 31.12.2017                         |
| ex 8536 69 90 | 82    | Modular socket or plug for local area networks, whether or not combined with other sockets, integrating at least:<br>— a pulse transformer, including a wide-band ferrite core,<br>— a common mode coil,<br>— a resistor,<br>— a capacitor,<br>for use in the manufacture of products falling within headings 8521 or 8528 <sup>(1)</sup>               | 0 %                     | 31.12.2014                         |
| ex 8536 69 90 | 84    | Universal serial bus (USB) socket or plug in a single or multiple form for connecting with other USB devices, for use in the manufacture of goods falling within headings 8521 or 8528 <sup>(1)</sup>   | 0 %                     | 31.12.2015                         |
| ex 8536 69 90 | 85    | Socket or plug, built into a plastic or metal housing, with no more than 8 pins, for use in the manufacture of products falling within headings 8521 or 8528 <sup>(1)</sup>   | 0 %                     | 31.12.2016                         |
| ex 8536 69 90 | 86    | High-Definition Multimedia Interface (HDMI) type socket or plug, built into a plastic or metal housing, with 19 pins or 20 pins in 2 rows, for use in the manufacture of products falling within headings 8521 or 8528 <sup>(1)</sup>   | 0 %                     | 31.12.2016                         |
| ex 8536 69 90 | 87    | D-Subminiature (D-sub) type socket or plug, built into a plastic or metal housing, with 15 pins in 3 rows, for use in the manufacture of products falling within headings 8521 or 8528 <sup>(1)</sup>   | 0 %                     | 31.12.2016                         |
| ex 8536 69 90 | 88    | Secure Digital (SD), CompactFlash, "Smart Card" and 64-pin PC-card female connectors, of a kind used for soldering on printed circuit boards, for connecting electrical apparatus and circuits and switching or protecting electrical circuits with a voltage of not more than 1 000 V  | 0 %                     | 31.12.2017                         |
| ex 8536 70 00 | 10    | Optical socket or plug, for use in the manufacture of goods falling within headings 8521 or 8528 <sup>(1)</sup>   | 0 %                     | 31.12.2016                         |
| ex 8536 70 00 | 20    | Metal plugs, sockets and connectors in plastic or metal housing for optically and mechanically aligning optical fibre cables:<br>— having an operating temperature of -20 °C or more, but not more than 70 °C,<br>— having a signal transmission speed of not more than 25 Mbps,<br>— having a supply voltage of -0,5 V or more, but not more than 7 V, | 0 %                     | 31.12.2016                         |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
|               |       | — having an input voltage of -0,5 V or more, but not more than 7,5 V,<br>— without an integrated circuit,<br>for use in the manufacture of products of headings 8521 and 8528 <sup>(1)</sup>  |                         |                                    |
| ex 8536 90 85 | 92    | Metallic stamped frame with connections   | 0 %                     | 31.12.2018                         |
| ex 8536 90 85 | 94    | Elastomeric connector, of rubber or silicone, consisting of one or more conductor elements  | 0 %                     | 31.12.2018                         |
| ex 8544 49 93 | 10    |   |                         |                                    |
| ex 8536 90 85 | 97    | Secure Digital (SD) type memory card slot, push-push or push-pull type, for use in the manufacture of goods falling within headings 8521 or 8528 <sup>(1)</sup>   | 0 %                     | 31.12.2016                         |
| ex 8537 10 91 | 30    | Data processing and evaluation vehicle dashboard control module, operating through the CAN - bus protocol, containing at least:<br>— microprocessor relays,<br>— a stepper motor,<br>— Electrically Erasable Programmable Read-Only (EEPROM) memory, and<br>— other passive components (such as connectors, diodes, voltage stabilizer, resistors, capacitors, transistors),<br>with a voltage of 13,5 V  | 0 %                     | 31.12.2017                         |
| ex 8537 10 99 | 92    | Touch sensitive screen panel, consisting of a conductive grid between two glass or plastic plates or sheets, fitted with electric conductors and connectors   | 0 %                     | 31.12.2018                         |
| ex 8537 10 99 | 93    | Electronic control units for a voltage of 12 V, for use in the manufacture of vehicle mounted temperature control systems <sup>(1)</sup>  | 0 %                     | 31.12.2018                         |
| ex 8537 10 99 | 94    | Unit consisting of two junction field effect transistors contained in a dual lead frame housing   | 0 %                     | 31.12.2018                         |
| ex 8543 70 90 | 20    |   |                         |                                    |
| ex 8537 10 99 | 97    | Electronic controller card for actuating and controlling of a single-phase electric AC commutator motor, with an output of 750 W or more and an input power of more than 1 600 W but not more than 2 700 W  | 0 %                     | 31.12.2015                         |
| ex 8538 90 99 | 92    | Part of an electrothermal fuse, consisting of a tin coated copper wire attached to a cylindrical casing, the exterior dimensions of which do not exceed 5 mm × 48 mm  | 0 %                     | 31.12.2018                         |
| ex 8538 90 99 | 95    | Copper base plate, of a kind used as a heatsink in the manufacture of IGBT modules of heading 8535 or 8536 with a voltage of 650 V or more but not more than 1 200 V <sup>(1)</sup>   | 0 %                     | 31.12.2018                         |
| ex 8539 39 00 | 20    | Cold cathode (CCFL) or external electrode (EEFL) fluorescent lamps, of a diameter of not more than 5 mm and with a length of more than 120 mm but not more than 1 570 mm  | 0 %                     | 31.12.2016                         |
| ex 8540 11 00 | 93    | Colour cathode-ray tube equipped with electron guns placed side by side (in-line technology), with a diagonal measurement of the screen of 79 cm or more  | 0 %                     | 31.12.2016                         |
| ex 8540 20 80 | 91    | Photomultiplier   | 0 %                     | 31.12.2016                         |
| ex 8540 71 00 | 20    | Continuous wave magnetron with a fixed frequency of 2 460 MHz, packaged magnet, probe output, for use in the manufacture of products falling within subheading 8516 50 00 <sup>(1)</sup>  | 0 %                     | 31.12.2018                         |
| ex 8540 89 00 | 91    | Displays in the form of a tube consisting of a glass housing mounted on a board the dimensions of which do not exceed 300 mm × 350 mm excluding leads. The tube contains one or more rows of characters or lines arranged in rows, each character or line consisting of fluorescent or phosphorescent elements. These elements are mounted on a metallised base which is covered with fluorescent substances or phosphorescent salts which give off light when bombarded with electrons | 0 %                     | 31.12.2018                         |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
| ex 8540 89 00 | 92    | Vacuum fluorescent display tube   | 0 %                     | 31.12.2018                         |
| ex 8543 70 90 | 23    | Semiconductor device for the conversion of electrical energy into visible, infra-red or ultra-violet rays:  | 0 %                     | 31.12.2018                         |
| ex 9405 40 39 | 50    | — whether or not with a housing   |                         |                                    |
| ex 9405 40 99 | 03    | — with electrical leads,<br>— including one or more light-emitting semiconductor chips which may be electrically connected among each other and which may be furnished for their protection with one or multiple protective diodes,<br>— formed/shaped as an indivisible entity<br>— for use in the manufacture of lighting gear employed for solid state lighting / for general lighting purposes <sup>(1)</sup>   |                         |                                    |
| ex 8543 70 90 | 30    | Amplifier, consisting of active and passive elements mounted on a printed circuit, contained in a housing   | 0 %                     | 31.12.2018                         |
| ex 8543 70 90 | 35    | Radio frequency (RF) modulator, operating with a frequency range of 43 MHz or more but not more than 870 MHz, capable of switching VHF and UHF signals, consisting of active and passive elements mounted on a printed circuit, contained in a housing  | 0 %                     | 31.12.2018                         |
| ex 8543 70 90 | 40    | High-frequency amplifier comprising one or more integrated circuits and discrete capacitor chips on a metal flange in a housing   | 0 %                     | 31.12.2015                         |
| ex 8543 70 90 | 45    | Piezo-electric crystal oscillator with a fixed frequency, within a frequency range of 1,8 MHz to 67 MHz, contained in a housing   | 0 %                     | 31.12.2018                         |
| ex 8543 70 90 | 55    | Opto-electronic circuit comprising one or more light-emitting diodes (LEDs), whether or not equipped with an integrated driving circuit, and one photodiode with amplifier circuit, whether or not with an integrated logic gate arrays circuit or one or more light-emitting diodes and at least 2 photodiodes with an amplifier circuit, whether or not with an integrated logic gate arrays circuit or other integrated circuits, contained in a housing | 0 %                     | 31.12.2018                         |
| ex 8543 70 90 | 60    | Oscillator, with a centre frequency of 20 GHz or more but not more than 42 GHz, consisting of active and passive elements not mounted on a substrate, contained in a housing  | 0 %                     | 31.12.2018                         |
| ex 8543 70 90 | 65    | Audio recording and reproducing circuit, capable of stereo audio data storage and simultaneous record and playback, comprising 2 or 3 monolithic integrated circuits mounted on a printed circuit or a lead frame, contained in a housing   | 0 %                     | 31.12.2018                         |
| ex 8543 70 90 | 80    | Temperature compensated oscillator, comprising a printed circuit on which are mounted at least a piezo-electric crystal and an adjustable capacitor, contained in a housing   | 0 %                     | 31.12.2018                         |
| ex 8543 70 90 | 85    | Voltage controlled oscillator (VCO), other than temperature compensated oscillators, consisting of active and passive elements mounted on a printed circuit, contained in a housing   | 0 %                     | 31.12.2018                         |
| ex 8543 70 90 | 95    | Mobile telephone view and control module comprising of:<br>— a mains power/ CAN (Controller area network) output socket,<br>— a universal serial bus (USB) and audio IN/OUT ports and<br>— incorporating a video switching device for the interface of smart phone operating systems with the Media Orientated Systems Transport network (MOST),<br>for use in the manufacture of vehicles of Chapter 87 <sup>(1)</sup>                                     | 0 %                     | 31.12.2015                         |
| ex 8543 90 00 | 20    | Stainless steel cathode in the form of a plate with a hanger bar, whether or not with plastic side strips   | 0 %                     | 31.12.2014                         |
| ex 8543 90 00 | 30    | Assembly of products falling within heading 8541 or 8542 mounted on a printed circuit, contained in a housing   | 0 %                     | 31.12.2018                         |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
| ex 8543 90 00 | 40    | Part of an electrolysis device, consisting of a pan of nickel equipped with a wire mesh of nickel, fixed via ribs of nickel, and a pan of titanium equipped with a wire mesh of titanium, fixed via ribs of titanium, of which both pans are fixed together back to back  | 0 %                     | 31.12.2017                         |
| ex 8544 20 00 | 10    | PET/PVC insulated flexible cable with:  | 0 %                     | 31.12.2018                         |
| ex 8544 42 90 | 20    | — a voltage of not more than 60 V,  |                         |                                    |
| ex 8544 49 93 | 20    | — a current of not more than 1 A,   |                         |                                    |
| ex 8544 49 95 | 10    | — a heat resistance of not more than 105 °C,<br>— individual wires of a thickness of not more than 0,1 mm ( $\pm$ 0,01 mm) and a width of not more than 0,8 mm ( $\pm$ 0,03 mm),<br>— a distance between conductors of not more than 0,5 mm and<br>— a pitch (distance from centreline to centreline of conductors) of not more than 1,25 mm                                    |                         |                                    |
| ex 8544 42 90 | 10    | Data transmission cable capable of a bit rate transmission of 600 Mbit/s or more, with:<br>— a voltage of 1,25 V ( $\pm$ 0,25 V)<br>— connectors fitted at one or both ends, at least one of which contains pins with a pitch of 1 mm,<br>— outer screening shielding,<br>used solely for communication between LCD, PDP or OLED panel and video processing electronic circuits | 0 %                     | 31.12.2018                         |
| ex 8544 42 90 | 30    | PET insulated electric conductor with:<br>— 10 or 80 individual wires,<br>— a length of 50 mm or more, but not more than 800 mm,<br>— connector(s) and/or plug(s) fitted at one or both ends,<br>for use in the manufacture of products falling within headings 8521 and 8528 <sup>(1)</sup>  | 0 %                     | 31.12.2017                         |
| ex 8545 19 00 | 20    | Carbon electrodes, for use in the manufacture of zinc-carbon batteries <sup>(1)</sup>   | 0 %                     | 31.12.2018                         |
| ex 8545 90 90 | 20    | Carbon fibre paper of a kind used for gas diffusion layers in fuel cell electrodes  | 0 %                     | 31.12.2015                         |
| ex 8547 10 00 | 10    | Insulated fitting of ceramics, containing by weight 90 % or more of aluminium oxide, metallised, in the form of a hollow cylindrical body of an external diameter of 20 mm or more but not more than 250 mm, for the manufacture of vacuum interrupters <sup>(1)</sup>  | 0 %                     | 31.12.2018                         |
| ex 8548 10 29 | 10    | Spent lithium-ion or nickel metal hydride electric accumulators   | 0 %                     | 31.12.2016                         |
| ex 8548 90 90 | 41    | Unit, consisting of a resonator operating within a frequency range of 1,8 MHz or more but not more than 40 MHz and a capacitor, contained in a housing  | 0 %                     | 31.12.2018                         |
| ex 8548 90 90 | 43    | Contact image sensor  | 0 %                     | 31.12.2018                         |
| ex 8548 90 90 | 47    | Unit consisting of two or more light emitting diode chips operating at a typical wavelength of 440 nm or more but not more than 660 nm, contained in a lead frame housing whose exterior dimensions - without fittings - do not exceed 12 mm $\times$ 12 mm   | 0 %                     | 31.12.2018                         |
| ex 8548 90 90 | 48    | Optical unit, consisting at least of a laserdiode and a photodiode operating at a typical wavelength of 635 nm or more but not more than 815 nm   | 0 %                     | 31.12.2018                         |
| ex 8548 90 90 | 49    | LCD modules, solely consisting of one or more TFT glass or plastic cells, combined with touch screen facilities, with or without backlight unit, with or without inverters and one or more printed circuit boards with control electronics for pixel addressing only  | 0 %                     | 31.12.2018                         |

| CN code                        | TARIC    | Description  | Rate of autonomous duty | Date foreseen for mandatory review |
|--------------------------------|----------|--|-------------------------|------------------------------------|
| ex 8548 90 90                  | 50       | Filters with a ferromagnetic core, used to suppress high frequency noise in electronic circuits, for the manufacture of TV sets and monitors of heading 8528 <sup>(1)</sup>  | 0 %                     | 31.12.2017                         |
| ex 8704 23 91                  | 20       | Motor chassis with a self-ignition capacity of at least 8 000 cm <sup>3</sup> , fitted with a cabin on either 3, 4 or 5 wheels having a wheelbase of at least 480 cm, not containing working machinery, to be built into special purpose motor vehicles with a width of at least 300 cm <sup>(1)</sup>   | 0 %                     | 31.12.2017                         |
| ex 8708 30 91                  | 10       | Drum type parking brake:<br>— operating within the service brake disk,<br>— with a diameter of 170 mm or more but not more than 175 mm,<br>for use in the manufacture of motor vehicles <sup>(1)</sup>   | 0 %                     | 31.12.2015                         |
| ex 8708 99 97                  | 20       | Metal housing caps for incorporation into balancing-arms or spherical bearings used in the suspension systems for the front wheels of motor vehicles <sup>(1)</sup>  | 0 %                     | 31.12.2016                         |
| ex 8803 30 00                  | 50       | Pre-formed helicopter rotor shafts:<br>— of circular cross-section,<br>— with a length of 1 249,68 mm or more, but not more than 1 496,06 mm,<br>— of an external diameter of 81,356 mm or more, but not more than 82,2198 mm,<br>— swaged on both ends to an external diameter of 63,8683 mm or more, but not more than 66,802 mm,<br>— heat treated according to standards MIL-H-6088, AMS 2770 or AMS 2772                          | 0 %                     | 31.12.2016                         |
| ex 9001 10 90                  | 10       | Image reverser made up from an assembly of optical fibres  | 0 %                     | 31.12.2018                         |
| ex 9001 10 90                  | 30       | Polymer optical fibre with:<br>— a poly(methyl methacrylate) core,<br>— a cladding of fluorinated polymer,<br>— a diameter of not more than 3,0 mm, and<br>— a length of more than 150 m,<br>of a kind used in the manufacture of polymer fibre cables   | 0 %                     | 31.12.2016                         |
| ex 9001 20 00                  | 10       | Material consisting of a polarising film, whether or not on rolls, supported on one or both sides by transparent material, whether or not with an adhesive layer, covered on one side or on both sides with a release film   | 0 %                     | 31.12.2017                         |
| ex 9001 20 00<br>ex 9001 90 00 | 20<br>55 | Optical, diffuser, reflector or prism sheets, unprinted diffuser plates, whether or not possessing polarising properties, specifically cut   | 0 %                     | 31.12.2018                         |
| ex 9001 90 00                  | 21       | Multi-Optical-Path (MOP) film, in rolls, based on poly(ethylene terephthalate) (PET) material:<br>— having a total thickness of 100 µm or more, but not more than 240 µm,<br>— having a total transmittance of more than 55 % but not more than 65 %, determined by standard method JIS K7105 related to ASTM D1003 and<br>— haze more than 70 % but not more than 80 %, determined by standard method JIS K7105 related to ASTM D1003 | 0 %                     | 31.12.2014                         |
| ex 9001 90 00                  | 25       | Unmounted optical elements made from moulded infrared transmitting chalcogenide glass, or a combination of infrared transmitting chalcogenide glass and another lens material  | 0 %                     | 31.12.2017                         |
| ex 9001 90 00                  | 35       | Rear projection screen, comprising a lenticular plastic plate  | 0 %                     | 31.12.2018                         |

| CN code       | TARIC | Description  | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|------------------------------------|
| ex 9001 90 00 | 45    | Rod of neodymium-doped yttrium-aluminium garnet (YAG) material, polished at both ends  | 0 %                     | 31.12.2018                         |
| ex 9001 90 00 | 60    | Reflector or diffuser sheets in rolls  | 0 %                     | 31.12.2018                         |
| ex 9001 90 00 | 65    | Optical film with a minimum of 5 multi-layer structures, including a back side reflector, a front side coating and a contrast filter with a pitch of not more than 0,65 µm, for use in the manufacture of front projection screens <sup>(1)</sup>  | 0 %                     | 31.12.2014                         |
| ex 9001 90 00 | 70    | Poly(ethylene terephthalate) film with a thickness of less than 300 µm according to ASTM D2103, having on one side prisms of acrylic resin with a prism angle of 90 ° and a prism pitch of 50 µm   | 0 %                     | 31.12.2016                         |
| ex 9001 90 00 | 75    | Front filter comprising glass panels with special printing and film coating, for use in the manufacture of plasma display modules <sup>(1)</sup>   | 0 %                     | 31.12.2017                         |
| ex 9001 90 00 | 85    | Light guide panel made of poly(methyl methacrylate):<br>— whether or not cut,<br>— whether or not printed,<br>for use in the manufacture of backlight units for flat screen TVs <sup>(1)</sup>   | 0 %                     | 31.12.2015                         |
| ex 9002 11 00 | 10    | Adjustable lens unit, having a focal length of 90 mm or more but not more than 180 mm and comprising a combination of between 4 and 8 glass or methacrylic lenses with a diameter of 120 mm or more but not more than 180 mm, each lens coated on at least one side with a magnesium fluoride layer, for use in the manufacture of video projectors <sup>(1)</sup> | 0 %                     | 31.12.2018                         |
| ex 9002 11 00 | 20    | Lenses<br>— measuring not more than 80 mm × 55 mm × 50 mm,<br>— with a resolution of 160 lines/mm or better, and<br>— with a zoom ratio of 18 times,<br>of a kind used for the production of visualizers or live image cameras   | 0 %                     | 31.12.2017                         |
| ex 9002 11 00 | 30    | Lenses<br>— measuring not more than 180 mm × 100 mm × 100 mm at a maximum focal length of more than 200 mm,<br>— with a resolution of 130 lines/mm or better, and<br>— with a zoom ratio of 18 times<br>of a kind used for the production of visualizers or live image cameras   | 0 %                     | 31.12.2017                         |
| ex 9002 11 00 | 40    | Lenses<br>— measuring not more than 125 mm × 65 mm × 65 mm,<br>— with a resolution of 125 lines/mm or better, and<br>— with a zoom ratio of 16 times<br>of a kind used for the production of visualizers or live image cameras   | 0 %                     | 31.12.2017                         |
| ex 9002 11 00 | 50    | Lens unit, having a focal length of 25 mm or more but not more than 150 mm, consisting of glass or plastic lenses, with a diameter of 60 mm or more but not more than 190 mm   | 0 %                     | 31.12.2018                         |
| ex 9002 11 00 | 70    | Lenses<br>— measuring not more than 180 mm×100 mm×100 mm at a maximum focal length of more than 200 mm,<br>— with an etendue of 7 steradian mm <sup>2</sup> or better, and<br>— with a zoom ratio of 16 times<br>of a kind used for the production of visualizers or live image cameras  | 0 %                     | 31.12.2017                         |

| CN code       | TARIC | Description  | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|------------------------------------|
| ex 9002 20 00 | 10    | Filter, consisting of a plastic polarising membrane, a glass plate and a transparent protective film, mounted on a metal frame, for use in the manufacture of products falling within heading 8528 <sup>(1)</sup>  | 0 %                     | 31.12.2018                         |
| ex 9002 90 00 | 20    | Lens, mounted, having a fixed focal length of 3,8 mm ( $\pm$ 0,19 mm) or 8 mm ( $\pm$ 0,4 mm), with a relative aperture of F2.0 and a diameter of not more than 33 mm, for use in the manufacture of charged-coupled (CCD) cameras <sup>(1)</sup>  | 0 %                     | 31.12.2018                         |
| ex 9002 90 00 | 30    | Optical unit, comprising 1 or 2 rows of optical glass fibres in the form of lenses and with a diameter of 0,85 mm or more but not more than 1,15 mm, embedded between 2 plastic plates   | 0 %                     | 31.12.2018                         |
| ex 9002 90 00 | 40    | Mounted lenses made from infrared transmitting chalcogenide glass, or a combination of infrared transmitting chalcogenide glass and another lens material  | 0 %                     | 31.12.2017                         |
| ex 9012 90 90 | 10    | Energy filters, to be installed on the column of electron microscopes  | 0 %                     | 31.12.2016                         |
| ex 9013 20 00 | 10    | Carbon dioxide laser, stimulated by high frequency, having an output power of 12 W or more, but not more than 200 W  | 0 %                     | 31.12.2018                         |
| ex 9013 20 00 | 20    | Laser head assemblies for use in the manufacture of measuring or checking machines for semiconductor wafers or devices <sup>(1)</sup>  | 0 %                     | 31.12.2018                         |
| ex 9013 20 00 | 30    | Laser for use in the manufacture of measuring or checking machines for semiconductor wafers or devices <sup>(1)</sup>  | 0 %                     | 31.12.2018                         |
| ex 9022 90 00 | 10    | Panels for x-ray apparatus (x-ray flat panel sensors/x-ray sensors) consisting of a glass plate with a matrix of thin-film transistors, covered with a film of amorphous silicon, coated with a scintillator layer of caesium iodide and a metallised protective layer, with an active surface of 409,6 mm <sup>2</sup> × 409,6 mm <sup>2</sup> and a pixel size of 200 µm <sup>2</sup> × 200 µm <sup>2</sup>  | 0 %                     | 31.12.2018                         |
| ex 9025 80 40 | 30    | Electronic barometric semiconductor pressure sensor in a housing, mainly consisting of <ul style="list-style-type: none"> <li>— a combination of one or more monolithic application-specific integrated circuits (ASIC) and</li> <li>— at least one or more microelectromechanical sensor elements (MEMS) manufactured with semiconductor technology, with mechanical components arranged in three-dimensional structures on the semiconductor material</li> </ul> | 0 %                     | 31.12.2018                         |
| ex 9027 10 90 | 10    | Sensor element for gas or smoke analysis in motor vehicles, essentially consisting of a zirconium-ceramic element in a metal housing   | 0 %                     | 31.12.2018                         |
| ex 9029 10 00 | 20    | Device for measuring wheel speed in vehicles (semi-conductor wheel speed sensor), consisting of: <ul style="list-style-type: none"> <li>— a monolithic integrated circuit in a housing, and</li> <li>— one or more discrete SMD capacitors connected in parallel to the integrated circuit</li> <li>— whether or not with integrated permanent magnets</li> </ul> for detecting the movement of a pulse generator  | 0 %                     | 31.12.2018                         |
| ex 9031 80 34 | 30    | Apparatus for measuring the angle and direction of rotation of motor vehicles, consisting of at least one yaw rate sensor in the form of a monocrystalline quartz, whether or not combined with one or more measuring sensors, the whole contained in a housing  | 0 %                     | 31.12.2018                         |
| ex 9031 80 38 | 10    | Acceleration measurement device for automotive applications, comprising one or more active and/or passive elements and one or more sensors, the whole contained in a housing   | 0 %                     | 31.12.2018                         |

| CN code       | TARIC | Description  | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|------------------------------------|
| ex 9031 80 38 | 20    | Electronic semiconductor accelerometer in a housing, mainly consisting of<br>— a combination of one or more monolithic application-specific integrated circuits (ASIC) and<br>— one or more microelectromechanical sensor elements (MEMS) manufactured with semiconductor technology, with mechanical components arranged in three-dimensional structures on the semiconductor material<br>to be fitted in products under chapter 84 - 90 and 94 | 0 %                     | 31.12.2018                         |
| ex 9031 90 85 | 20    | Assembly for a laser align sensor, in the form of a printed circuit comprising optical filters and a charge-coupled image (CCD) sensor, the whole contained in a housing   | 0 %                     | 31.12.2018                         |
| ex 9032 89 00 | 20    | Automotive airbag shock-sensor, comprising a contact capable of switching a current of 12 A at a voltage of 30 V, having a typical contact resistance of 80 mOhm   | 0 %                     | 31.12.2018                         |
| ex 9032 89 00 | 30    | Electronic controller of electric power steering (EPS controller)  | 0 %                     | 31.12.2018                         |
| ex 9032 89 00 | 40    | Digital valve controller for controlling liquids and gases   | 0 %                     | 31.12.2017                         |
| ex 9401 90 80 | 10    | Ratchet disk of a kind used in the manufacture of reclining car seats  | 0 %                     | 31.12.2015                         |
| ex 9401 90 80 | 20    | Sidemember with a thickness of 0,8 or more but not more than 3,0 mm, used in the manufacture of reclining car seats <sup>(1)</sup>   | 0 %                     | 31.12.2018                         |
| ex 9401 90 80 | 30    | Steel bracket for mounting safety features seats with thickness of 1 mm or more but not more than 2,5 mm used in the manufacture of reclining car seats <sup>(1)</sup>   | 0 %                     | 31.12.2018                         |
| ex 9401 90 80 | 40    | Steel handles for controlling the seat adjustment mechanism used in the manufacture of reclining car seats <sup>(1)</sup>  | 0 %                     | 31.12.2018                         |
| ex 9405 40 35 | 10    | Electric light assembly of synthetic material containing 3 fluorescent tubes (RBG) of a diameter of 3,0 mm ( $\pm$ 0,2 mm), of a length of 420 mm ( $\pm$ 1 mm) or more but not more than 600 mm ( $\pm$ 1 mm), for the manufacture of goods of heading 8528 <sup>(1)</sup>  | 0 %                     | 31.12.2018                         |
| ex 9405 40 39 | 10    | Ambient light module with a length of 300 mm or more but not more than 600 mm, based on a light engine of a series of 3 or more but not more than 9 specific one chip red green and blue light emitting diodes mounted on a PCB, with light coupled to the front and/or back of the flat TV set <sup>(1)</sup>   | 0 %                     | 31.12.2018                         |
| ex 9405 40 39 | 20    | LED array of white silicone, containing:<br>— an LED matrix module measuring 38,6 mm $\times$ 20,6 mm ( $\pm$ 0,1 mm), equipped with 128 red and green LED chips, and<br>— a flexible printed circuit board, equipped with a Negative Temperature Coefficient Thermistor   | 0 %                     | 31.12.2018                         |
| ex 9405 40 39 | 60    | LED components (equipped with light emitting diodes) fitted with<br>— a plastic casing,<br>— one or more light emitting diode chips either chips manufactured using thin-film technology or so-called sapphire emitter chips and<br>— one or more optional semiconductor chips with electric protection function.<br>— for use in the manufacture of lighting gear employed for general lighting purposes <sup>(1)</sup>                         | 0 %                     | 31.12.2018                         |

| CN code       | TARIC | Description   | Rate of autonomous duty | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|------------------------------------|
| ex 9405 40 99 | 06    | LED components (equipped with light emitting diodes) fitted with<br>— a casing made of ceramic or circuit board material,<br>— one or more light emitting diode chips either chips manufactured using thin-film technology or so-called sapphire emitter chips<br>— one or more optional semiconductor chips with electric protection function<br>— for use in the manufacture of lighting gear employed for general lighting purposes <sup>(1)</sup> | 0 %                     | 31.12.2018                         |
| ex 9503 00 75 | 10    | Plastic cable car scale models, whether or not with a motor, for printing <sup>(1)</sup>  | 0 %                     | 31.12.2015                         |
| ex 9503 00 95 | 10    |   |                         |                                    |
| ex 9608 91 00 | 10    | Non-fibrous plastic pen-tips with an internal canal   | 0 %                     | 31.12.2018                         |
| ex 9608 91 00 | 20    | Felt tips and other porous-tips for markers, without internal canal   | 0 %                     | 31.12.2018                         |
| ex 9612 10 10 | 10    | Ribbons of plastic with segments of different colours, providing the penetration of dyes by heat into a support (so called dye-sublimation)   | 0 %                     | 31.12.2018                         |

<sup>(1)</sup> Suspension of duties is subject to Articles 291 to 300 of Commission Regulation (EEC) No 2454/93 of 2 July 1993 laying down provisions for the implementation of Council Regulation (EEC) No 2913/92 establishing the Community Customs Code (OJ L 253 11.10.1993, p. 1).

<sup>(2)</sup> However, the measure is not allowed where processing is carried out by retail or catering undertakings.

<sup>(3)</sup> The specific duty shall apply.

<sup>(4)</sup> A surveillance of imports of goods covered by this tariff suspension shall be established in accordance with the procedure laid down in Article 308d of Regulation (EEC) No 2454/93.

<sup>(5)</sup> CUS (Customs Union and Statistics Number) is assigned to each ECICS record (product). ECICS (European Customs Inventory of Chemical Substances) is an information tool managed by the European Commission, General Directorate for Taxation and Customs Union. More information can be found via the following link: [http://ec.europa.eu/taxation\\_customs/common/databases/ecics/index\\_en.htm](http://ec.europa.eu/taxation_customs/common/databases/ecics/index_en.htm)

## ANNEX II

| CN code       | TARIC | Supplementary unit     |
|---------------|-------|------------------------|
| ex 6909 19 00 | 15    | Number of Items (p/st) |
| ex 7020 00 10 | 10    | p/st                   |
| ex 7616 99 90 | 77    | p/st                   |
| ex 6909 19 00 | 80    | p/st                   |
| ex 7006 00 90 | 70    | p/st                   |
| ex 7009 91 00 | 10    | p/st                   |
| 7011 20 00    |       | p/st                   |
| ex 7320 90 10 | 91    | p/st                   |
| ex 7325 99 10 | 20    | p/st                   |
| ex 7604 21 00 | 10    | p/st                   |
| ex 7604 29 90 | 30    | p/st                   |
| ex 7613 00 00 | 20    | p/st                   |
| ex 7616 99 90 | 15    | p/st                   |
| ex 7616 99 90 | 70    | p/st                   |
| ex 8482 80 00 | 10    | p/st                   |
| ex 8803 30 00 | 40    | p/st                   |
| ex 7616 99 90 | 75    | p/st                   |
| ex 8108 90 90 | 20    | p/st                   |
| ex 9003 90 00 | 10    | p/st                   |
| ex 8207 30 10 | 10    | p/st                   |
| ex 8301 60 00 | 10    | p/st                   |
| ex 8413 91 00 | 20    | p/st                   |
| ex 8419 90 85 | 20    | p/st                   |
| ex 8438 90 00 | 10    | p/st                   |
| ex 8468 90 00 | 10    | p/st                   |
| ex 8476 90 00 | 10    | p/st                   |
| ex 8479 90 80 | 87    | p/st                   |
| ex 8481 90 00 | 20    | p/st                   |
| ex 8503 00 99 | 45    | p/st                   |
| ex 8515 90 00 | 20    | p/st                   |
| ex 8531 90 85 | 20    | p/st                   |
| ex 8536 90 85 | 96    | p/st                   |
| ex 8543 90 00 | 50    | p/st                   |
| ex 8708 91 99 | 10    | p/st                   |
| ex 8708 99 97 | 30    | p/st                   |
| ex 9031 90 85 | 30    | p/st                   |
| ex 8309 90 90 | 10    | p/st                   |
| ex 8405 90 00 | 10    | p/st                   |
| ex 8409 91 00 | 10    | p/st                   |
| ex 8409 99 00 | 20    | p/st                   |

| CN code       | TARIC | Supplementary unit |
|---------------|-------|--------------------|
| ex 8409 99 00 | 10    | p/st               |
| ex 8479 90 80 | 85    | p/st               |
| ex 8411 99 00 | 30    | p/st               |
| ex 8414 90 00 | 20    | p/st               |
| ex 8414 90 00 | 30    | p/st               |
| ex 8414 90 00 | 40    | p/st               |
| ex 8415 90 00 | 20    | p/st               |
| ex 8418 99 10 | 50    | p/st               |
| ex 8418 99 10 | 60    | p/st               |
| ex 8421 99 00 | 91    | p/st               |
| ex 8421 99 00 | 93    | p/st               |
| ex 8422 30 00 | 10    | p/st               |
| ex 8479 89 97 | 30    | p/st               |
| ex 8431 20 00 | 30    | p/st               |
| ex 8439 99 00 | 10    | p/st               |
| ex 8467 99 00 | 10    | p/st               |
| ex 8536 50 11 | 35    | p/st               |
| ex 8477 80 99 | 10    | p/st               |
| ex 8479 89 97 | 40    | p/st               |
| ex 8479 89 97 | 50    | p/st               |
| ex 8479 90 80 | 80    | p/st               |
| ex 8481 30 91 | 91    | p/st               |
| ex 8481 80 59 | 10    | p/st               |
| ex 8481 80 69 | 60    | p/st               |
| ex 8481 80 79 | 20    | p/st               |
| ex 8481 80 99 | 50    | p/st               |
| ex 8481 80 99 | 60    | p/st               |
| ex 8483 30 38 | 30    | p/st               |
| ex 8483 40 29 | 50    | p/st               |
| ex 8483 40 51 | 20    | p/st               |
| ex 8483 40 59 | 20    | p/st               |
| ex 8483 40 90 | 80    | p/st               |
| ex 8503 00 91 | 31    | p/st               |
| ex 8503 00 99 | 32    | p/st               |
| ex 8503 00 99 | 31    | p/st               |
| ex 8503 00 99 | 33    | p/st               |
| ex 8503 00 99 | 34    | p/st               |
| ex 8503 00 99 | 35    | p/st               |
| ex 8503 00 99 | 40    | p/st               |
| ex 8504 40 82 | 40    | p/st               |

| CN code       | TARIC | Supplementary unit |
|---------------|-------|--------------------|
| ex 8504 40 82 | 50    | p/st               |
| ex 8504 40 90 | 20    | p/st               |
| ex 8504 40 90 | 30    | p/st               |
| ex 8504 40 90 | 40    | p/st               |
| ex 8504 50 95 | 20    | p/st               |
| ex 8504 50 95 | 40    | p/st               |
| ex 8504 50 95 | 50    | p/st               |
| ex 8504 90 11 | 10    | p/st               |
| ex 8505 11 00 | 31    | p/st               |
| ex 8505 11 00 | 33    | p/st               |
| ex 8505 11 00 | 35    | p/st               |
| ex 8505 11 00 | 50    | p/st               |
| ex 8505 20 00 | 30    | p/st               |
| ex 8505 90 20 | 91    | p/st               |
| ex 8507 90 80 | 70    | p/st               |
| ex 8508 70 00 | 10    | p/st               |
| ex 8537 10 99 | 96    | p/st               |
| ex 8516 90 00 | 60    | p/st               |
| ex 8516 90 00 | 70    | p/st               |
| ex 8518 30 95 | 20    | p/st               |
| ex 8518 90 00 | 91    | p/st               |
| ex 8522 90 49 | 50    | p/st               |
| ex 8522 90 49 | 60    | p/st               |
| ex 8529 90 65 | 25    | p/st               |
| ex 8522 90 49 | 65    | p/st               |
| ex 8529 90 65 | 40    | p/st               |
| ex 8522 90 49 | 70    | p/st               |
| ex 8522 90 80 | 15    | p/st               |
| ex 8522 90 80 | 30    | p/st               |
| ex 8529 90 92 | 30    | p/st               |
| ex 8522 90 80 | 65    | p/st               |
| ex 8522 90 80 | 70    | p/st               |
| ex 8522 90 80 | 75    | p/st               |
| ex 8522 90 80 | 80    | p/st               |
| ex 8522 90 80 | 81    | p/st               |
| ex 8522 90 80 | 83    | p/st               |
| ex 8522 90 80 | 84    | p/st               |
| ex 8522 90 80 | 85    | p/st               |
| ex 8522 90 80 | 96    | p/st               |
| ex 8522 90 80 | 97    | p/st               |
| ex 8529 90 65 | 50    | p/st               |
| ex 8529 10 80 | 20    | p/st               |

| CN code       | TARIC | Supplementary unit |
|---------------|-------|--------------------|
| ex 8529 10 80 | 50    | p/st               |
| ex 8529 10 80 | 60    | p/st               |
| ex 8529 90 65 | 30    | p/st               |
| ex 8548 90 90 | 44    | p/st               |
| ex 8529 90 65 | 45    | p/st               |
| ex 8529 90 65 | 55    | p/st               |
| ex 8529 90 65 | 60    | p/st               |
| ex 8529 90 65 | 65    | p/st               |
| ex 8529 90 65 | 70    | p/st               |
| ex 8529 90 65 | 75    | p/st               |
| ex 8529 90 92 | 25    | p/st               |
| ex 8529 90 92 | 32    | p/st               |
| ex 8529 90 92 | 40    | p/st               |
| ex 8529 90 92 | 41    | p/st               |
| ex 8529 90 92 | 42    | p/st               |
| ex 8529 90 92 | 43    | p/st               |
| ex 8529 90 92 | 44    | p/st               |
| ex 8529 90 92 | 45    | p/st               |
| ex 8529 90 92 | 47    | p/st               |
| ex 8529 90 92 | 48    | p/st               |
| ex 8529 90 92 | 49    | p/st               |
| ex 8536 69 90 | 83    | p/st               |
| ex 8529 90 92 | 50    | p/st               |
| ex 8529 90 92 | 70    | p/st               |
| ex 8531 80 95 | 40    | p/st               |
| ex 8535 90 00 | 20    | p/st               |
| ex 8535 90 00 | 30    | p/st               |
| ex 8536 50 80 | 83    | p/st               |
| ex 8536 30 30 | 11    | p/st               |
| ex 8536 49 00 | 91    | p/st               |
| ex 8536 50 11 | 31    | p/st               |
| ex 8536 50 11 | 32    | p/st               |
| ex 8536 50 19 | 91    | p/st               |
| ex 8536 50 19 | 93    | p/st               |
| ex 8536 50 80 | 97    | p/st               |
| ex 8536 50 80 | 81    | p/st               |
| ex 8536 50 80 | 82    | p/st               |
| ex 8536 50 80 | 93    | p/st               |
| ex 8536 50 80 | 98    | p/st               |
| ex 8536 69 90 | 51    | p/st               |
| ex 8536 69 90 | 81    | p/st               |
| ex 8536 69 90 | 82    | p/st               |

| CN code       | TARIC | Supplementary unit |
|---------------|-------|--------------------|
| ex 8536 69 90 | 84    | p/st               |
| ex 8536 69 90 | 85    | p/st               |
| ex 8536 69 90 | 86    | p/st               |
| ex 8536 69 90 | 87    | p/st               |
| ex 8536 69 90 | 88    | p/st               |
| ex 8536 70 00 | 10    | p/st               |
| ex 8536 70 00 | 20    | p/st               |
| ex 8536 90 85 | 92    | p/st               |
| ex 8536 90 85 | 94    | p/st               |
| ex 8544 49 93 | 10    | p/st               |
| ex 8536 90 85 | 97    | p/st               |
| ex 8537 10 91 | 30    | p/st               |
| ex 8537 10 99 | 92    | p/st               |
| ex 8537 10 99 | 93    | p/st               |
| ex 8537 10 99 | 94    | p/st               |
| ex 8543 70 90 | 20    | p/st               |
| ex 8537 10 99 | 97    | p/st               |
| ex 8538 90 99 | 92    | p/st               |
| ex 8543 70 90 | 30    | p/st               |
| ex 8543 70 90 | 35    | p/st               |
| ex 8543 70 90 | 40    | p/st               |
| ex 8543 70 90 | 45    | p/st               |
| ex 8543 70 90 | 55    | p/st               |
| ex 8543 70 90 | 60    | p/st               |
| ex 8543 70 90 | 65    | p/st               |
| ex 8543 70 90 | 80    | p/st               |
| ex 8543 70 90 | 85    | p/st               |
| ex 8543 70 90 | 95    | p/st               |
| ex 8543 90 00 | 20    | p/st               |
| ex 8543 90 00 | 30    | p/st               |
| ex 8543 90 00 | 40    | p/st               |
| ex 8544 42 90 | 10    | p/st               |
| ex 8545 19 00 | 20    | p/st               |
| ex 8547 10 00 | 10    | p/st               |
| ex 8548 90 90 | 41    | p/st               |
| ex 8548 90 90 | 43    | p/st               |
| ex 8548 90 90 | 47    | p/st               |
| ex 8548 90 90 | 48    | p/st               |
| ex 8548 90 90 | 49    | p/st               |
| ex 8548 90 90 | 50    | p/st               |
| ex 8708 30 91 | 10    | p/st               |
| ex 8708 99 97 | 20    | p/st               |

| CN code       | TARIC | Supplementary unit             |
|---------------|-------|--------------------------------|
| ex 8803 30 00 | 50    | p/st                           |
| ex 9001 90 00 | 75    | p/st                           |
| ex 9002 90 00 | 20    | p/st                           |
| ex 9002 90 00 | 30    | p/st                           |
| ex 9002 90 00 | 40    | p/st                           |
| ex 9012 90 90 | 10    | p/st                           |
| ex 9013 20 00 | 10    | p/st                           |
| ex 9013 20 00 | 20    | p/st                           |
| ex 9013 20 00 | 30    | p/st                           |
| ex 9022 90 00 | 10    | p/st                           |
| ex 9031 80 34 | 30    | p/st                           |
| ex 9031 80 38 | 10    | p/st                           |
| ex 9031 90 85 | 20    | p/st                           |
| ex 9032 89 00 | 20    | p/st                           |
| ex 9032 89 00 | 30    | p/st                           |
| ex 9032 89 00 | 40    | p/st                           |
| ex 9401 90 80 | 10    | p/st                           |
| ex 9405 40 35 | 10    | p/st                           |
| ex 9405 40 39 | 10    | p/st                           |
| ex 9405 40 39 | 20    | p/st                           |
| ex 9503 00 75 | 10    | p/st                           |
| ex 9503 00 95 | 10    | p/st                           |
| ex 3919 90 00 | 36    | Square meter (m <sup>2</sup> ) |
| ex 3919 90 00 | 44    | m <sup>2</sup>                 |
| ex 3920 49 10 | 95    | m <sup>2</sup>                 |
| ex 3921 90 60 | 95    | m <sup>2</sup>                 |
| ex 5603 11 10 | 10    | m <sup>2</sup>                 |
| ex 5603 11 10 | 20    | m <sup>2</sup>                 |
| ex 5603 11 90 | 10    | m <sup>2</sup>                 |
| ex 5603 11 90 | 20    | m <sup>2</sup>                 |
| ex 5603 12 10 | 10    | m <sup>2</sup>                 |
| ex 5603 12 90 | 10    | m <sup>2</sup>                 |
| ex 5603 12 90 | 50    | m <sup>2</sup>                 |
| ex 5603 12 90 | 60    | m <sup>2</sup>                 |
| ex 5603 12 90 | 70    | m <sup>2</sup>                 |
| ex 5603 13 10 | 10    | m <sup>2</sup>                 |
| ex 5603 13 10 | 20    | m <sup>2</sup>                 |
| ex 5603 13 90 | 60    | m <sup>2</sup>                 |
| ex 5603 13 90 | 70    | m <sup>2</sup>                 |
| ex 5603 14 10 | 10    | m <sup>2</sup>                 |
| ex 5603 91 10 | 10    | m <sup>2</sup>                 |

| CN code       | TARIC | Supplementary unit            |
|---------------|-------|-------------------------------|
| ex 5603 91 90 | 10    | m <sup>2</sup>                |
| ex 5603 92 10 | 10    | m <sup>2</sup>                |
| ex 5603 92 90 | 10    | m <sup>2</sup>                |
| ex 5603 92 90 | 40    | m <sup>2</sup>                |
| ex 5603 92 90 | 80    | m <sup>2</sup>                |
| ex 5603 93 90 | 10    | m <sup>2</sup>                |
| ex 5603 93 90 | 50    | m <sup>2</sup>                |
| ex 3824 90 97 | 90    | Cubic Metre (m <sup>3</sup> ) |
| ex 3901 10 90 | 20    | m <sup>3</sup>                |
| ex 3901 20 90 | 10    | m <sup>3</sup>                |

| CN code       | TARIC | Supplementary unit |
|---------------|-------|--------------------|
| ex 3902 10 00 | 50    | m <sup>3</sup>     |
| ex 3903 11 00 | 10    | m <sup>3</sup>     |
| ex 3903 90 90 | 10    | m <sup>3</sup>     |
| ex 3907 40 00 | 50    | m <sup>3</sup>     |
| ex 3907 40 00 | 60    | m <sup>3</sup>     |
| ex 3907 60 80 | 40    | m <sup>3</sup>     |
| ex 3920 20 80 | 95    | m <sup>3</sup>     |
| ex 5402 49 00 | 70    | Metre (m)          |
| ex 3215 19 00 | 20    | Litre (l)          |