### COUNCIL REGULATION (EU) 2017/1134

#### of 20 June 2017

#### amending Regulation (EU) No 1387/2013 suspending the autonomous Common Customs Tariff duties on certain agricultural and industrial products

THE COUNCIL OF THE EUROPEAN UNION,

Having regard to the Treaty on the Functioning of the European Union, and in particular Article 31 thereof,

Having regard to the proposal from the European Commission,

Whereas:

- (1) The Union production of 69 agricultural and industrial products that are not listed in the Annex to Council Regulation (EU) No 1387/2013 (<sup>1</sup>) is inadequate or non-existent. It is, therefore, in the interest of the Union to completely suspend the autonomous Common Customs Tariff ('CCT') duties on those products.
- (2) It is necessary to modify the conditions for 71 suspensions of autonomous CCT duties currently listed in the Annex to Regulation (EU) No 1387/2013 in order to take into account technical product developments and economic trends on the market. Certain product classifications have been amended to allow the industry to fully benefit from the suspensions in force. Moreover, the Annex to Regulation (EU) No 1387/2013 should be updated due to the need to align or clarify texts in some cases. The modified conditions relate to changes in the product description, classification or end-use requirements. The suspensions that require modifications should be deleted from the list of suspensions in the Annex to Regulation (EU) No 1387/2013, and the modified suspensions should be inserted into that list.
- (3) It is no longer in the interest of the Union to maintain the suspension of autonomous CCT duties for two of the products that are currently listed in the Annex to Regulation (EU) No 1387/2013.
- (4) In the interests of clarity, the entries modified by this Regulation should be marked with an asterisk.
- (5) Regulation (EU) No 1387/2013 should therefore be amended accordingly.
- (6) As the changes regarding the suspensions for the products concerned provided for in this Regulation have to apply from 1 July 2017, this Regulation should enter into force as a matter of urgency,

HAS ADOPTED THIS REGULATION:

#### Article 1

The Annex to Regulation (EU) No 1387/2013 is amended as follows:

- the rows for the products listed in Annex I to this Regulation are inserted following the order of the CN codes indicated in the first column of the table in the Annex to Regulation (EU) No 1387/2013;
- (2) the rows for the products for which the CN and TARIC codes are set out in Annex II to this Regulation are deleted.

### Article 2

This Regulation shall enter into force on the date of its publication in the Official Journal of the European Union.

It shall apply from 1 July 2017.

<sup>(&</sup>lt;sup>1</sup>) Council Regulation (EU) No 1387/2013 of 17 December 2013 suspending the autonomous Common Customs Tariff duties on certain agricultural and industrial products and repealing Regulation (EU) No 1344/2011 (OJ L 354, 28.12.2013, p. 201).

This Regulation shall be binding in its entirety and directly applicable in all Member States.

Done at Luxembourg, 20 June 2017.

For the Council The President H. DALLI

# ANNEX I

CN code	TARIC	Description	Rate of autonomous duty	Supplemen- tary Unit	Date foreseen for mandatory review
*ex 2818 30 00	30	Aluminium hydroxide oxide in the form of boehmite or pseudoboehmite (CAS RN 1318-23-6)	0 %	_	31.12.2018
ex 2825 70 00	20	Molybdic Acid (CAS RN 7782-91-4)	0 %	—	31.12.2021
*ex 2842 10 00	40	Aluminosilicate (CAS RN 1318-02-1) with a zeolite structure of Aluminophosphate-eighteen (AEI) for use in the manufacture of catalytic preparations ( <sup>2</sup> )	0 %	_	31.12.2021
*ex 2905 11 00	20	Methyl methanesulphonate (CAS RN 66-27-3)	0 %	_	31.12.2021
ex 2905 19 00	35				
ex 2905 22 00	20	3,7-Dimethyloct-6-en-1-ol (CAS RN 106-22-9)	0 %	—	31.12.2021
ex 2909 30 90	15	{[(2,2-dimethylbut-3-yn-1-yl)oxy]methyl}benzene (CAS RN 1092536-54-3)	0 %	_	31.12.2021
ex 2909 30 90	25	1,2-Diphenoxyethane (CAS RN 104-66-5) in the form of powder or as an aqueous dispersion containing by weight 30 % or more but not more than 60 % of 1,2-diphenoxyethane	0 %		31.12.2021
*ex 2909 60 00	40	1,4-Di(2-tert-butylperoxyisopropyl)benzene (CAS RN 2781-00-2) or mixture of isomers 1,4-Di(2-tert-butylperoxyisopropyl)benzene and 1,3-di(2-tert-butylperoxyisopropyl)benzene (CAS RN 25155-25-3)	0 %	_	31.12.2017
ex 2912 19 00	10	Undecanal (CAS RN 112-44-7)	0 %	—	31.12.2021
ex 2915 12 00	10	Aqueous solution containing by weight 60 % or more but not more than 84 % of caesium formate (CAS RN 3495-36-1)	0 %	_	31.12.2021
*ex 2916 14 00	30	Allyl methacrylate (CAS RN 96-05-9) and its' isomers with a purity by weight of 98 % or more and contain- ing at least:	0 %	—	31.12.2020
		<ul> <li>— 0,01 % or more but not more than 0,02 % of Allyl alcohol (CAS RN 107-18-6),</li> </ul>			
		— 0,01 % or more but not more than 0,1 % of Methacrylic acid (CAS RN 79-41-4), and			
		<ul> <li>— 0,5 % or more but not more than 1 % of 4-Me- thoxyphenol (CAS RN 150-76-5)</li> </ul>			
ex 2916 39 90	33	Methyl 4'-(bromomethyl)biphenyl-2-carboxylate (CAS RN 114772-38-2)	0 %	_	31.12.2021
ex 2916 39 90	73	(2,4-Dichlorophenyl)acetyl chloride (CAS RN 53056-20-5)	0 %	_	31.12.2021
*ex 2920 29 00	50	Fosetyl-aluminium (CAS RN 39148-24-8)	0 %	_	31.12.2018
ex 2920 90 70	50				
*ex 2920 29 00 ex 2920 90 70	60 40	Fosetyl-sodium (CAS RN 39148-16-8) in form of an aqueous solution with a content by weight of fosetyl-so- dium of 35 % or more but not more than 45 % for use in the manufacture of pesticides $(^2)$	0 %	_	31.12.2021

CN code	TARIC	Description	Rate of autonomous duty	Supplemen- tary Unit	Date foreseen for mandatory review
ex 2922 19 00	40	(R)-1-((4-amino-2-bromo-5-fluorophenyl)amino)-3-(ben- zyloxy)propan-2-ol 4-methylbenzenesulphonate (CAS RN 1294504-64-5)	0 %	_	31.12.2021
ex 2924 29 70	30	Sodium 4-(4-methyl-3-nitrobenzoylamino)benzenesul- phonate (CAS RN 84029-45-8)	0 %	_	31.12.2021
ex 2924 29 70	50	N-Benzyloxycarbonyl-L-tert-leucine isopropylamine salt (CAS RN 1621085-33-3)	0 %	_	31.12.2021
ex 2926 90 70	30	4,5-Dichloro-3,6-dioxocyclohexa-1,4-diene-1,2-dicarbo- nitrile (CAS RN 84-58-2)	0 %	_	31.12.2021
*ex 2931 90 00	05	Diethylmethoxyborane (CAS RN 7397-46-8), whether or not in the form of a solution in tetrahydrofuran according to note 1e to Chapter 29 of the CN	0 %	_	31.12.2020
*ex 2932 14 00	10	1,6-Dichloro-1,6-dideoxy-β-D-fructofuranosyl-4-chloro-	0 %	—	31.12.2019
ex 2940 00 00	40	4 deoxy-α-D-galactopyranoside (CAS RN 56038-13-2)			
ex 2932 99 00	13	(4-Chloro-3-(4-ethoxybenzyl)phenyl)((3aS,5R,6S,6aS)-6- hydroxy 2,2-dimethyltetrahydrofuro[2,3-d][1,3]dioxol- 5-yl)methanone (CAS RN 1103738-30-2)	0 %		31.12.2021
ex 2932 99 00	18	4-(4-Bromo-3-((tetrahydro-2H-pyran-2-yloxy)methyl) phenoxy)benzonitrile (CAS RN 943311-78-2)	0 %	_	31.12.2021
ex 2933 19 90	45	5-Amino-1-[2,6-dichloro-4-(trifluoromethyl)phenyl]- 1H-pyrazole-3-carbonitrile (CAS RN 120068-79-3)	0 %	—	31.12.2021
ex 2933 19 90	55	5-Methyl-1-(naphthalen-2-yl)-1,2-dihydro-3H-pyrazol-3- one (CAS RN 1192140-15-0)	0 %	—	31.12.2021
ex 2933 29 90	75	2,2'-Azobis[2-(2-imidazolin-2-yl)propane] dihydrochlo- ride (CAS RN 27776-21-2)	0 %	—	31.12.2021
ex 2933 39 99	10	2-Aminopyridin-4-ol hydrochloride (CAS RN 1187932- 09-7)	0 %	_	31.12.2021
ex 2933 39 99	33	5-(3-chlorophenyl)-3-methoxypyridine-2-carbonitrile (CAS RN 1415226-39-9)	0 %	_	31.12.2021
ex 2933 39 99	41	2-chloro-6-(3-fluoro-5-isobutoxyphenyl)nicotinic acid (CAS RN 1897387-01-7)	0 %	_	31.12.2021
ex 2933 39 99	46	Fluopicolide (ISO) (CAS RN 239110-15-7) for use in the manufacture of pesticides ( <sup>2</sup> )	0 %	_	31.12.2021
*ex 2933 59 95	88	Diquat dibromide (ISO) (CAS RN 85-00-7) in aqueous	0 %	_	31.12.2021
ex 2933 99 80	51	solution for use in the manufacture of herbicides (2)			
ex 2933 99 80	42	(S)-2,2,4-Trimethylpyrrolidine hydrochloride (CAS RN 1897428-40-8)	0 %	—	31.12.2021
ex 2933 99 80	44	(2S, 3S, 4R)-Methyl 3-ethyl-4-hydroxypyrrolidine-2-car- boxylate 4-methylbenzenesulphonate (CAS RN 1799733-43-9)	0 %	—	31.12.2021
*ex 2933 99 80	53	Potassium (S)-5-(tert-butoxycarbonyl)-5-azaspiro[2.4] heptane-6-carboxylate (CUS 0133723-1) ( <sup>5</sup> )	0 %	_	31.12.2018

CN code	TARIC	Description	Rate of autonomous duty	Supplemen- tary Unit	Date foreseen for mandatory review
*ex 2933 99 80	72	1,4,7-Trimethyl-1,4,7-triazacyclononane (CAS RN 96556-05-7)	0 %	_	31.12.2018
ex 2934 99 90	46	4-Methoxy-5-(3-morpholin-4-yl-propoxy)-2-nitro-ben- zonitrile (CAS RN 675126-26-8)	0 %	_	31.12.2021
ex 2934 99 90	47	Thidiazuron (ISO) (CAS RN 51707-55-2) for use in the manufacture of pesticides ( <sup>2</sup> )	0 %	_	31.12.2021
ex 2934 99 90	49	Cytidine 5'-(disodium phosphate) (CAS RN 6757-06-8)	0 %	_	31.12.2021
ex 2934 99 90	53	4-Methoxy-3-(3-morpholin-4-yl-propoxy)-benzonitrile (CAS RN 675126-28-0)	0 %	_	31.12.2021
ex 2935 90 90	30	6-Aminopyridine-2-sulfonamide (CAS RN 75903-58-1)	0 %	—	31.12.2021
*ex 3204 16 00	30	Preparations based on Colourant Reactive Black 5 (CAS RN 17095-24-8) with a content thereof of 60 % or more but not more than 75 % by weight, and including one or more of the following:	0 %	_	31.12.2019
		<ul> <li>Colourant Reactive Yellow 201 (CAS RN 27624-67- 5),</li> </ul>			
		<ul> <li>— 1-Naphthalenesulphonicacid,4-amino-3-[[4-[[2-(sul-phooxy)ethyl]sulphonyl]phenyl]azo]-, disodium salt (CAS RN 250688-43-8), or</li> </ul>			
		<ul> <li>— 3,5-diamino-4-[[4-[[2-(sulphooxy)ethyl]sulphonyl]fe- nyl]azo]-2-[[2-sulfo-4-[[2-(sulphooxy)ethyl]sulfonyl] phenyl]azobenzoic acid sodium salt (CAS RN 906532-68-1)</li> </ul>			
ex 3204 17 00	22	Colourant C.I. Pigment Red 169 (CAS RN 12237-63-7) and preparations based thereon with a colourant C.I. Pigment Red 169 content of 50 % or more by weight	0 %	_	31.12.2021
*ex 3204 17 00	24	Colourant C.I. Pigment Red 57:1 (CAS RN 5281-04-9) and preparations based thereon with a Colourant C.I. Pigment Red 57:1 content of 50 % or more by weight	0 %	_	31.12.2018
*ex 3215 90 70	30	Disposable cartridge ink, containing by weight:	0 %	—	31.12.2018
		<ul> <li>— 1 % or more, but not more than 10 % of amor- phous silicon dioxide or</li> </ul>			
		— 3,8 % or more of dye C.I. Solvent Black 7 in organic solvents			
		for use in the marking of integrated circuits (2)			
*ex 3506 91 10	50	Preparation containing by weight:	0 %	—	31.12.2020
ex 3506 91 90	50	<ul> <li>— 15 % or more but not more than 60 % of styrene butadiene copolymers or styrene isoprene copoly- mers and</li> </ul>			
		<ul> <li>— 10 % or more but not more than 30 % of pinene polymers or pentadiene copolymers</li> </ul>			
		dissolved in:			
		— Methyl ethyl ketone (CAS RN 78-93-3)			
		— Heptane (CAS RN 142-82-5), and			
		<ul> <li>Toluene (CAS RN 108-88-3) or light aliphatic solvent naphta (CAS RN 64742-89-8)</li> </ul>			

CN code	TARIC	Description	Rate of autonomous duty	Supplemen- tary Unit	Date foreseen for mandatory review
ex 3811 21 00	11	Dispersing agent and oxidation inhibitor containing:	0 %		31.12.2021
		<ul> <li>o-amino polyisobutylenephenol (CAS RN 78330- 13-9),</li> </ul>			
		<ul> <li>more than 30 % by weight but not more than 50 % by weight of mineral oils,</li> </ul>			
		used in the manufacture of blends of additives for lubricating oils $(^{2})$			
*ex 3811 21 00	19	Additives containing:	0 %	_	31.12.2019
		— a polyisobutylene succinimide based mixture, and			
		<ul> <li>more than 30 % but not more than 50 % by weight of mineral oils,</li> </ul>			
		having a total base number of more than 40, for use in the manufacture of lubricating oils $(^2)$			
ex 3811 29 00	75	Oxidation inhibitor mainly containing a mixture of isomers of 1-(tert-dodecylthio)propan-2-ol (CAS RN 67124-09-8), used in the manufacture of blends of additives for lubricating oils ( <sup>2</sup> )	0 % (²)	_	31.12.2021
ex 3811 90 00	50	<ul> <li>Corrosion inhibitor containing:</li> <li>polyisobutenyl succinic acid and</li> <li>more than 5 % and not more than 20 % by weight of mineral oils</li> <li>for use in the manufacture of blends of additives for fuels (<sup>2</sup>)</li> </ul>	0 %	_	31.12.2021
*ex 3815 90 90	40	Catalyst: — containing molybdenum oxide and other metal	0 %	_	31.12.2018
		<ul> <li>oxides in a silicon dioxide matrix,</li> <li>in the form of hollow cylindrical solids of a length of 4 mm or more but not more than 12 mm</li> <li>for use in the manufacture of acrylic acid (<sup>2</sup>)</li> </ul>			
ex 3824 99 92	25	<ul> <li>Preparation containing by weight:</li> <li>25 % or more but not more than 50 % of diethyl carbonate (CAS RN 105-58-8)</li> </ul>	0 %	—	31.12.2021
		<ul> <li>25 % or more but not more than 50 % of ethylene carbonate (CAS RN 96-49-1)</li> </ul>			
		<ul> <li>— 10 % or more but not more than 20 % of lithium hexafluorophosphate (CAS RN 21324-40-3)</li> </ul>			
		<ul> <li>5 % or more but not more than 10 % of ethyl methyl carbonate (CAS RN 623-53-0)</li> </ul>			
		<ul> <li>— 1 % or more but not more than 2 % of vinylene carbonate (CAS RN 872-36-6)</li> </ul>			
		<ul> <li>— 1 % or more but not more than 2 % of 4-fluoro- 1,3-dioxolane-2-one (CAS RN 114435-02-8)</li> </ul>			
		<ul> <li>— Not more than 1 % of 1,5,2,4-Dioxadithiane 2,2,4,4-tetraoxide (CAS RN 99591-74-9)</li> </ul>			

CN code	TARIC	Description	Rate of autonomous duty	Supplemen- tary Unit	Date foreseen for mandatory review
ex 3824 99 92	27	4-Methoxy-3-(3-morpholin-4-yl-propoxy)-benzonitrile (CAS RN 675126-28-0) in an organic solvent	0 %		31.12.2021
ex 3824 99 92	30	Aqueous solution of caesium formate and potassium formate containing by weight:	0 %	—	31.12.2021
		<ul> <li>— 1 % or more but not more than 84 % of caesium formate (CAS RN 3495-36-1),</li> </ul>			
		<ul> <li>— 1 % or more but not more than 76 % of potassium formate (CAS RN 590-24-1), and</li> </ul>			
		<ul> <li>whether or not containing not more than 9 % of additives</li> </ul>			
*ex 3824 99 92	40	Solution of 2-chloro-5-(chloromethyl)-pyridine (CAS RN 70258-18-3) in organic diluent	0 %		31.12.2020
*ex 3824 99 92	69	Preparation containing by weight:	0 %	_	31.12.2020
		— 80 % or more but not more than 92 % of Bisphe- nol-A bis(diphenyl phosphate) (CAS RN 5945-33-5)			
		<ul> <li>7 % or more but not more than 20 % oligomers of Bisphenol-A bis(diphenyl phosphate) and</li> </ul>			
		<ul> <li>not more than 1 % triphenyl phosphate (CAS RN 115-86-6)</li> </ul>			
ex 3824 99 93	45	Sodium hydrogen 3-aminonaphthalene-1,5-disulphonate (CAS RN 4681-22-5) containing by weight:	0 %	_	31.12.2021
		<ul> <li>not more than 20 % of disodium sulphate, and</li> <li>not more than 10 % of sodium chloride</li> </ul>			
		— not more than 10 % of sodium chloride			
ex 3824 99 96	70	Powder containing by weight:	0 %	—	31.12.2021
		— 28 % or more but not more than 51 % of talc (CAS RN 14807-96-6)			
		<ul> <li>30,5 % or more but not more than 48 % of silicon dioxide (quartz) (CAS RN 14808-60-7)</li> </ul>			
		<ul> <li>— 17 % or more but not more than 26 % of alumin- ium oxide (CAS RN 1344-28-1)</li> </ul>			
ex 3824 99 96	74	Mixture with a non-stoichiometric composition:	0 %	—	31.12.2021
		— with a crystalline structure,			
		— with a content of fused magnesia-alumina spinel and with admixtures of silicate phases and alumi- nates, at least 75 % by weight of which consists of fractions with a grain size of 1-3 mm and at most 25 % consists of fractions with a grain size of 0-1 mm			
ex 3824 99 96	80	Mixture consisting of:	0 %	—	31.12.2021
		<ul> <li>64 % or more, but not more than 74 % by weight of amorphous silica (CAS RN 7631-86-9)</li> </ul>			
		<ul> <li>25 % or more, but not more than 35 % by weight of butanone (CAS RN 78-93-3) and</li> </ul>			
		<ul> <li>not more than 1 % by weight of 3-(2,3-epoxypro- poxy)propyltrimethoxysilane (CAS RN 2530-83-8)</li> </ul>			

CN code	TARIC	Description	Rate of autonomous duty	Supplemen- tary Unit	Date foreseen for mandatory review
*ex 3901 10 10 ex 3901 90 80	20 50	High flow linear low density polyethylene-1-bute- ne/LLDPE (CAS RN 25087-34-7) in form of powder, with	0 %		31.12.2019
		<ul> <li>a melt flow rate (MFR 190 °C/2,16 kg) of 16 g/ 10 min or more, but not more than 24 g/10 min and</li> </ul>			
		<ul> <li>a density (ASTM D 1505) of 0,922 g/cm<sup>3</sup> or more, but not more than 0,926 g/cm<sup>3</sup> and</li> <li>a visat softening temperature of min 0.4 °C</li> </ul>			
		— a vicat softening temperature of min. 94 °C			
ex 3906 90 90	53	Polyacrylamide powder having an average particle size of less than 2 microns and a melting point of more than 260 °C, containing by weight:	0 %	_	31.12.2021
		<ul> <li>75 % or more but not more than 85 % of polyacry- lamide and</li> </ul>			
		<ul> <li>— 15 % or more but not more than 25 % of polyethy- lene glycol</li> </ul>			
ex 3906 90 90	63	Copolymer of (Dimethoxymethylsilyl)propyl methacry- late, butylacrylate, allyl methacrylate, methyl methacry- late and cyclosiloxanes (CAS RN 143106-82-5)	0 %	_	31.12.2021
ex 3910 00 00	45	Dimethyl Siloxane, hydroxy-terminated polymer with a viscosity of 38-45 mPa $\cdot$ s (CAS RN 70131-67-8)	0 %	_	31.12.2021
ex 3910 00 00	55	Preparation containing by weight:	0 %	_	31.12.2021
		— 55 % or more but not more than 65 % of vinyl terminated polydimethylsiloxane (CAS RN 68083-19-2),			
		<ul> <li>— 30 % or more but not more than 40 % of dimethyl- vinylated and trimethylated silica (CAS RN 68988- 89-6), and</li> </ul>			
		<ul> <li>— 1 % or more but not more than 5 % of silicic acid, sodium salt, reaction products with chlorotrimethyl- silane and isopropyl alcohol (CAS RN 68988-56-7)</li> </ul>			
*ex 3913 90 00	30	Protein, chemically or enzymatically modified by car- boxylation and/or phthalic acid addition, whether or not hydrolysed, having a weight average molecular weight (Mw) of less than 350 000	0 %	_	31.12.2018
ex 3920 99 59	70	Tetrafluoroethylene film, put up in rolls, with: — a thickness of 50 µm,	0 %	_	31.12.2021
		<ul> <li>a melting point of 260 °C, and</li> <li>a specific gravity of 1,75 (ASTM D792)</li> <li>for use in the manufacture of semiconductor devices (<sup>2</sup>)</li> </ul>			
*ex 3921 13 10	10	Sheet of polyurethane foam, of a thickness of 3 mm (± 15 %) and of a specific gravity of 0,09435 or more but not more than 0,10092	0 %	_	31.12.2018

CN code	TARIC	Description	Rate of autonomous duty	Supplemen- tary Unit	Date foreseen for mandatory review
ex 3921 19 00	50	Porous membrane of polytetrafluorethylene (PTFE) lami- nated to a polyester spunbonded non-woven cloth with:	0 %	_	31.12.2021
		<ul> <li>a total thickness of more than 0,05 mm but not more than 0,20 mm,</li> </ul>			
		<ul> <li>a water entry pressure between 5 and 200 kPa according to ISO 811, and</li> </ul>			
		<ul> <li>an air permeability of 0,08 cm<sup>3</sup>/cm<sup>2</sup>/s or more according to ISO 5636-5</li> </ul>			
*ex 3923 10 90	10	Photomask or wafer compacts:	0 %	_	31.12.2021
		<ul> <li>consisting of antistatic materials or blended thermo- plastics proving special electrostatic discharge (ESD) and outgassing properties,</li> </ul>			
		<ul> <li>having non porous, abrasion resistant or impact resistant surface properties,</li> </ul>			
		<ul> <li>fitted with a specially designed retainer system that protects the photomask or wafers from surface or cosmetic damage and</li> </ul>			
		— with or without a gasket seal,			
		of a kind used in the photolithography or other semi- conductor production to house photomasks or wafers			
*ex 3926 30 00	10	Plastic cover with cips for the exterior rear-view mirror	0 %	p/st	31.12.2020
ex 8708 29 10	10	of motor vehicles			
ex 8708 29 90	10				
*ex 3926 90 97	20	Housings, housing parts, drums, setting wheels, frames, covers and other parts of acrylonitrile-butadiene-styrene of a kind used for the manufacture of remote controls	0 %	p/st	31.12.2019
ex 3926 90 97	77	Silicone decoupling ring, with an inner diameter of	0 %	p/st	31.12.2021
ex 8512 90 90	10	15,4 mm (+ 0,0 mm/ $-$ 0,1 mm), of a kind used in car parking aid sensor systems			
ex 4016 99 57	10	Air intake hose for air supply to the combustion part of the engine comprising at least: — one flexible rubber hose,	0 %	p/st	31.12.2021
		— one plastic hose, and			
		— metal clips,			
		— whether or not a resonator for use in the manufacture of goods of Chapter 87 ( <sup>2</sup> )			
ex 4016 99 57	20	Rubber bumper strip with a silicone coating of a length not more than 1 200 mm and with at least five plastic clips for use in the manufacture of goods of Chap- ter 87 $(^2)$	0 %	p/st	31.12.2021

CN code	TARIC	Description	Rate of autonomous duty	Supplemen- tary Unit	Date foreseen for mandatory review
*ex 5911 90 99 ex 8421 99 90	30 92	Parts of equipment for the purification of water by reverse osmosis, consisting essentially of plastic-based membranes, supported internally by woven or non-woven textile materials which are wound round a perforated tube, and enclosed in a cylindrical plastic casing of a wall-thickness of not more than 4 mm, whether or not housed in a cylinder of a wall-thickness of 5 mm or more	0 %		31.12.2018
*ex 5911 90 99	40	Multi-layered non-woven polyester polishing pads, impregnated with polyurethane	0 %	_	31.12.2019
ex 6805 30 00	10	Probe tips cleaning material consisting of a polymer matrix containing abrasive particles mounted on a sub- strate for use in the manufacture of semiconductors ( <sup>2</sup> )	0 %	_	31.12.2021
ex 7318 19 00	30	Connecting rod for the master brake cylinder with screw threads on both ends for use in the manufacture of goods of Chapter $87$ ( <sup>2</sup> )	0 %	p/st	31.12.2021
*ex 7410 11 00 ex 8507 90 80 ex 8545 90 90	10 60 30	<ul> <li>Roll of laminate foil of graphite and copper, with:</li> <li>a width of 610 mm or more but not more than 620 mm, and</li> <li>a diameter of 690 mm or more but not more than 710 mm,</li> <li>for use in the manufacture of lithium-ion electric rechargeable batteries (<sup>2</sup>)</li> </ul>	0 %	_	31.12.2021
*ex 7607 11 90 ex 7607 11 90	47 57	<ul> <li>Aluminium foil in rolls:</li> <li>having a purity of 99,99 % by weight,</li> <li>of a thickness of 0,021 mm or more but not more than 0,2 mm,</li> <li>with a width of 500 mm,</li> <li>with a surface oxide layer by 3 to 4 nm thick,</li> <li>and with a cubic texture of more than 95 %</li> </ul>	0 %		31.12.2021
*ex 7607 19 90 ex 8507 90 80	10 80	<ul> <li>Sheet in the form of a roll consisting of a laminate of lithium and manganese bonded to aluminium, with:</li> <li>a width of 595 mm or more but not more than 605 mm, and</li> <li>a diameter of 690 mm or more but not more than 710 mm,</li> <li>for use in the manufacture of cathodes for lithium-ion electric rechargeable batteries (<sup>2</sup>)</li> </ul>	0 %		31.12.2021
*ex 7616 99 10 ex 8708 99 10 ex 8708 99 97	30 60 50	<ul> <li>Aluminium engine bracket, with dimensions of:</li> <li>height of more than 10 mm but not more than 200 mm</li> <li>width of more than 10 mm but not more than 200 mm</li> <li>length of more than 10 mm but not more than 200 mm</li> </ul>	0 %	p/st	31.12.2019

CN code	TARIC	Description	Rate of autonomous duty	Supplemen- tary Unit	Date foreseen for mandatory review
		equipped with at least two fixing holes, made of alumin- ium alloys ENAC-46100 or ENAC-42100 (based on the norm EN:1706) with following characteristics:			
		— internal porosity not more than 1 mm;			
		— outer porosity not more than 2 mm;			
		— Rockwell hardness HRB 10 or more			
		of a kind used in the production of suspensions systems for engines in motor vehicles			
*ex 8108 90 30	20	Bars, rods and wire of alloy of titanium and aluminium, containing by weight 1 % or more but not more than 2 % of aluminium, for use in the manufacture of silencers and exhaust pipes of subheadings 8708 92 or 8714 10 40 $(^2)$	0 %	_	31.12.2017
*ex 8108 90 50	10	Alloy of titanium and aluminium, containing by weight 1 % or more but not more than 2 % of aluminium, in sheets or rolls, of a thickness of 0,49 mm or more but not more than 3,1 mm, of a width of 1 000 mm or more but not more than 1 254 mm, for the manufacture of goods of subheading 8714 10 ( <sup>2</sup> )	0 %	_	31.12.2018
*ex 8108 90 50	35	Plates, sheets and strips of an alloy of titanium	0 %	—	31.12.2021
*ex 8301 60 00	20	Keypads of silicone or plastic,	0 %	p/st	31.12.2020
ex 8413 91 00	40	— whether or not with parts of metal, plastic, glass		.,	
ex 8419 90 85	30	fibre reinforced epoxide resin or wood,			
ex 8438 90 00	20	— whether or not printed or surface treated,			
ex 8468 90 00	20	— whether or not with electrical conducting elements,			
ex 8476 90 90	20	<ul> <li>whether or not with keypads foil glued on the key- board,</li> </ul>			
ex 8479 90 70	83	<ul> <li>whether or not with protective foil,</li> </ul>			
ex 8481 90 00	30	<ul> <li>— single or multilayer</li> </ul>			
ex 8503 00 99	70	single of matchayer			
ex 8515 90 80	30				
ex 8536 90 95	95				
ex 8537 10 98	70				
ex 8708 91 20	10				
ex 8708 91 99	20				
ex 8708 99 10	50				
ex 8708 99 97	40				
*ex 8409 91 00	30	Exhaust manifold with spiral-shaped gas turbine turbo-	0 %	p/st	31.12.2018
ex 8409 99 00	50	charger component with:	0 /0	Plot	<i>J</i> 1.12.2010
CR 0107 77 00	20	- a heat-resistance of not more than 1 050 °C, and			
		<ul> <li>a turbine wheel hole diameter of 30 mm or more, but not more than 110 mm</li> </ul>			
ex 8409 99 00	40	Plastic or aluminum cylinder head cover with:	0 %	p/st	31.12.2021
		— a camshaft position sensor (CMPS),			

CN code	TARIC	Description	Rate of autonomous duty	Supplemen- tary Unit	Date foreseen for mandatory review
		— metal brackets for mounting on an engine, and			
		— two or more gaskets,			
		for use in the manufacture of engines of motor vehicles ( <sup>2</sup> )			
ex 8411 99 00	65	Spiral-shaped gas turbine turbocharger component: — with a heat-resistance of not more than 1 050 °C, and	0 %	p/st	31.12.2021
		<ul> <li>with a turbine wheel hole diameter of 30 mm or more, but not more than 110 mm</li> </ul>			
ex 8413 30 20	30	Single-cylinder radial-piston high pressure pump for gasoline direct injection with:	0 %	_	31.12.2021
		<ul> <li>an operating pressure of 200 bar or more, but not more than 350 bar,</li> </ul>			
		— a flow control, and			
		— a pressure relief valve,			
		for use in the manufacture of engines of motor vehicles ( <sup>2</sup> )			
ex 8479 90 70	87	Fuel hose for internal combustion piston engines with a fuel temperature sensor, with at least two inlet hoses and three outlet hoses for use in the manufacture of engines of motor vehicles ( <sup>2</sup> )	0 %	p/st	31.12.2021
ex 8481 80 59	20	Pressure regulating valve for incorporation into com- pressors of motor vehicle air condition units ( <sup>2</sup> )	0 %	p/st	31.12.2021
ex 8484 20 00	10	Mechanical shaft seal for incorporation into rotary com- pressors for use in the manufacture of motor vehicle air condition units ( <sup>2</sup> )	0 %	p/st	31.12.2021
ex 8501 10 99	56	DC Motor:	0 %		31.12.2021
ex 8901 10 99	50	<ul> <li>with a speed rotation of not more than 7 000 rpm (without load),</li> </ul>	0 78		91.12.2021
		— with a nominal voltage of 12 V (± 4 V),			
		— with a maximum power of 13,78 W (at 3,09 A),			
		— with a specified temperature range from – 40 °C to 160 °C,			
		— with a gear connection,			
		— with a mechanical attachment interface,			
		— with 2 electrical connections,			
		— with a maximum torque of 100 Nm			
ex 8501 10 99	58	DC Motor:	0 %	_	31.12.2021
		— with a speed rotation of not more than 6 500 rpm (without load),			
		— with a nominal voltage of $12 \text{ V} (\pm 4 \text{ V})$ ,			

CN code	TARIC	Description	Rate of autonomous duty	Supplemen- tary Unit	Date foreseen for mandatory review
		— with a maximal power below than 20 W,			
		<ul> <li>— with a specified temperature range from – 40 °C to 160 °C,</li> </ul>			
		— with a worm gear drive,			
		— with a mechanical attachment interface,			
		— with 2 electrical connections,			
		— with a maximum torque of 75 Nm			
*ex 8501 10 99	65	Electric turbocharger actuator, with:	0 %	_	31.12.2020
		— a DC motor,			
		— an integrated gear mechanism,			
		<ul> <li>a (pulling)force of 200 N or more at a minimum of 140 °C elevated ambient temperature,</li> </ul>			
		<ul> <li>a (pulling) force of 250 N or more in each position of its stroke,</li> </ul>			
		— an effective stroke of 15 mm or more but not more than 25 mm,			
		— with or without an on-board diagnostics interface			
*ex 8504 31 80	50	Transformers for use in the manufacture of electronic drivers, control devices and LED light sources for light-ing industry ( <sup>2</sup> )	0 %	_	31.12.2021
*ex 8504 40 90	25	Direct current to direct current converter — without housing or	0 %	p/st	31.12.2021
		<ul> <li>without housing of</li> <li>with housing with connection pins, connection studs, screw connectors, unprotected line connec- tions, connection elements which allow the mount- ing to a printed circuit board by soldering or any other technology, or other wiring connections re- quiring further processing</li> </ul>			
ex 8504 50 95	70	Solenoid coil with:	0 %	p/st	31.12.2021
CA 0704 70 77	70	<ul> <li>a rated power of more than 10 W but not more than 15 W,</li> </ul>	0 /0	pjst	91.12.2021
		— an insulation resistance of 100 M Ohms or more,			
		- a DC resistance of not more than $34,8$ Ohm (± 10 %) at 20 °C,			
		— a rated current of not more than 1,22 A,			
		<ul> <li>a rated current of not more than 1,22 Å,</li> <li>a rated voltage of not more than 25 V</li> </ul>			
*ex 8505 11 00	65	Permanent magnets consisting of an alloy of neody- mium, iron and boron, either in the shape of a rectangle, whether or not rounded, with a rectangular or a trape- zoidal section having	0 %	p/st	31.12.2018
		— a length of not more than 140 mm,			
		— a width of not more than 90 mm, and			
		— a thickness of not more than 55 mm,			

CN code	TARIC	Description	Rate of autonomous duty	Supplemen- tary Unit	Date foreseen for mandatory review
		or in the shape of curved rectangle (tile type) having			
		— a length of not more than 75 mm,			
		— a width of not more than 40 mm,			
		— a thickness of not more than 7 mm, and			
		<ul> <li>a radius of curvature of more than 86 mm but not more than 241 mm</li> </ul>			
		or in the shape of a disc with a diameter of not more than 90 mm, whether or not containing a hole in the centre			
*ex 8505 11 00	75	A quarter sleeve intended to become permanent magnet after magnetization,	0 %	p/st	31.12.2019
		— consisting of at least neodymium, iron and boron,			
		<ul> <li>— with a width of 9,1 mm or more but not more than 10,5 mm,</li> </ul>			
		<ul> <li>— with a length of 20 mm or more but not more than 30,1 mm,</li> </ul>			
		of a kind used on rotors for the manufacture of fuel pumps			
*ex 8507 90 80	70	Cut plate of nickel-plated copper foil, with:	0 %	p/st	31.12.2021
		— a width of 70 mm (± 5 mm),			
		— a thickness of 0,4 mm ( $\pm$ 0,2 mm),			
		— a length of not more than 55 mm,			
		for use in the manufacture of lithium-ion electric re- chargeable batteries ( <sup>2</sup> )			
ex 8518 40 80	93	Audio power amplifier with:	0 %	p/st	31.12.2021
		— an output power of 50 W,			
		<ul> <li>an operating voltage of more than 9 V but not more than 16 V,</li> </ul>			
		— an electrical impedance of not more than 4 Ohm,			
		— a sensitivity of more than 80 dB			
		— in a metal housing			
		for use in the manufacture of motor vehicles (2)			
*ex 8522 90 80	30	Metal holder, metal fixing item or internal stiffener of metal, for use in the manufacture of televisions, moni-	0 %	p/st	31.12.2021
ex 8529 90 92	57	tors and video players ( <sup>2</sup> )			
*ex 8529 90 65	65	Printed circuit board for distributing supply voltage and	0 %	p/st	31.12.2020
ex 8529 90 92	53	control signals directly to a control circuit on a TFT glass panel of a LCD module			
*ex 8529 90 92	59	LCD modules with:	0 %	p/st	31.12.2020
		<ul> <li>a diagonal measurement of the screen of 14,5 cm or more but not more than 25,5 cm,</li> </ul>			
		— a LED backlight,			

CN code	TARIC	Description	Rate of autonomous duty	Supplemen- tary Unit	Date foreseen for mandatory review
		<ul> <li>a printed circuit board with EPROM (Erasable Pro- grammable Read-only Memory), microcontroller, timing controller, LIN (Local Interconnect Network) bus or APIX2 (Automative Pixel Link) driver module and other active and passive components,</li> <li>6 to 8 pin plug for power supply and 2 to 4- pin LVDS (Low-voltage differential signalling) or APIX2 interface,</li> </ul>			
		— whether or not in a housing,			
		for permanent incorporation or permanent mounting into motor vehicles of Chapter 87 (2)			
*ex 8529 90 92	63	LCD module	0 %	p/st	31.12.2020
		<ul> <li>— with a diagonal measurement of the screen of 14,5 cm or more but not more than 38,5 cm,</li> </ul>			
		— with or without a touch screen,			
		— with an LED backlight,			
		<ul> <li>with a printed circuit board with EEPROM, micro- controller, LVDS receiver and other active and pas- sive components,</li> </ul>			
		<ul> <li>with a plug for power supply and CAN and LVDS interfaces,</li> </ul>			
		<ul> <li>with or without electronic components for dynamic adjustments of colour,</li> </ul>			
		<ul> <li>in a housing, with or without mechanical, touch- sensitive or contactless control functions and with or without active cooling system,</li> </ul>			
		suitable for installation in motor vehicles of Chapter 87 $(^2\!)$			
*ex 8529 90 92	67	Colour LCD display panel for LCD monitors of head-	0 %	p/st	31.12.2020
		<ul> <li>ing 8528:</li> <li>— with a diagonal measurement of the screen of 14,48 cm or more but not more than 31,24 cm,</li> </ul>			
		<ul> <li>with or without a touch screen,</li> </ul>			
		— with backlight, micro-controller,			
		<ul> <li>with a CAN (Controller area network)-controller with one or more LVDS (Low-voltage differential signalling) interfaces and one or more CAN/power supply sockets or with an APIX (Automotive Pixel Link) controller with APIX interface,</li> </ul>			
		<ul> <li>in a housing with or without a heat sink at the back of the housing,</li> </ul>			
		— without a signal-processing module,			
		— whether or not with haptic and acoustical feedback,			
		for use in the manufacture of vehicles of Chapter 87 (2)			1

CN code	TARIC	Description	Rate of autonomous duty	Supplemen- tary Unit	Date foreseen for mandatory review
*ex 8536 90 95	20	Semiconductor chip housing in the form of a plastic frame containing a lead frame equipped with contact pads, for voltages of not more than 1 000 V	0 %	p/st	31.12.2020
*ex 8536 90 95	92	Metallic stamped frame with connections	0 %	p/st	31.12.2018
*ex 8536 90 95	94	Elastomeric connector, of rubber or silicone, consisting of one or more conductor elements	0 %	p/st	31.12.2018
ex 8544 49 93	10				
ex 8537 10 98	65	Lever for control module under the steering wheel: — with one or more single or multi-positional electri- cal switches (push-button, rotary or other),	0 %	p/st	31.12.2021
		<ul> <li>whether or not equipped with printed circuit boards and electrical cables,</li> </ul>			
		<ul> <li>for a voltage of 9 V or more but not more than 16 V,</li> </ul>			
		of a kind used in the manufacture of motor vehicles of Chapter 87			
ex 8537 10 98	75	Control unit for keyless access to vehicle and vehicle starting, with electrical switching apparatus, in a plastic housing, for a voltage of 12 V, whether or not with:	0 %	p/st	31.12.2021
		<ul> <li>an antenna,</li> <li>a connector,</li> </ul>			
		— a metal holder,			
		for use in the manufacture of goods of Chapter 87 $\left(^2\right)$			
*ex 8537 10 98	92	Touch sensitive screen panel, consisting of a conductive grid between two glass or plastic plates or sheets, fitted with electric conductors and connectors	0 %	p/st	31.12.2018
ex 8538 90 99	60	Front control panel, in the form of a plastic box, with light guides, rotary switches, pressure switches and but- tons switches, or other type of switches, without any electrical component, of a kind used in the dashboard of motor vehicles of Chapter 87	0 %	p/st	31.12.2021
ex 8543 70 90	15	Laminated electrochromic film consisting of: — two outer layers of polyester, — a middle layer of acrylic polymer and silicone, and — two electric connection terminals	0 %	_	31.12.2021
*ex 8543 70 90	33	High-frequency amplifier comprising one or more inte- grated circuits and one or more discrete capacitor chips, whether or not with IPD (integrated passive devices) on a metal flange in a housing	0 %	—	31.12.2021

CN code	TARIC	Description	Rate of autonomous duty	Supplemen- tary Unit	Date foreseen for mandatory review
ex 8544 42 90	80	12-wire connecting cable containing two connectors	0 %	p/st	31.12.2021
		<ul> <li>of a voltage of 5 V,</li> <li>with a length of not more than 300 mm</li> </ul>			
		for use in the manufacture of goods of Chapter 87 <sup>(2)</sup>			
		for use in the manufacture of goods of Chapter 87 ()			
ex 8708 10 10	10	Plastic cover for filling the space between the fog lights	0 %	p/st	31.12.2021
ex 8708 10 90	10	and the bumper whether or not with a chrome strip for use in the manufacture of goods of Chapter 87 ( <sup>2</sup> )			
*ex 8708 30 10	20	Motor powered brake actuation unit	0 %	p/st	31.12.2019
ex 8708 30 91	60	— with a rating of 13,5 V ( $\pm$ 0,5 V) and	- , •	F/	
ex 8708 30 99	10	— a ball screw mechanism to control brake fluid pres- sure in the master cylinder			
		for use in the manufacture of electric motor vehicles ( <sup>2</sup> )			
*ex 8708 30 10	40	Body of disc type brake in BIR ('Ball in Ramp') or EPB	0 %	p/st	31.12.2019
ex 8708 30 91	30	('Electronic Parking Brake') or with hydraulic function only, containing functional and mounting openings and guide grooves, of a kind used in the manufacture of goods of Chapter 87	0 70	pjst	51.12.2019
*ex 8708 30 10	50	Drum type parking brake:	0 %	p/st	31.12.2021
ex 8708 30 91	10	<ul> <li>operating within the service brake disk,</li> </ul>	0 /0	P/50	91.12.2021
CK 0/00 90 71	10	<ul> <li>with a diameter of 170 mm or more but not more than 195 mm</li> </ul>			
		for use in the manufacture of motor vehicles (2)			
*ex 8708 30 10	60	Non-asbestos organic brake pads with friction material	0 %	p/st	31.12.2019
ex 8708 30 91	20	mounted to the band steel back plate for use in the manufacture of goods of Chapter 87 (2)			
*ex 8708 30 10	70	Ductile cast iron brake caliper jaw, of a kind used in the	0 %	p/st	31.12.2020
ex 8708 30 91	40	manufacture of goods of Chapter 87			
*ex 8708 40 20	20	Automatic hydrodynamic gearbox	0 %	p/st	31.12.2020
ex 8708 40 50	10	— with a hydraulic torque converter,			
		<ul> <li>without transfer box and cardan shaft,</li> <li>whether or not with front differential,</li> </ul>			
		for use in the manufacture of motor vehicles of Chap- ter $87 (^2)$			
*ex 8708 50 20	10	Car axle side-shaft fitted with a constant velocity joint at each end, of a kind used in the manufacture of goods	0 %	p/st	31.12.2020
ex 8708 50 55	10	of CN heading 8703			

CN code	TARIC	Description	Rate of autonomous duty	Supplemen- tary Unit	Date foreseen for mandatory review
*ex 8708 50 20	20	Transmission shaft in carbon fibre reinforced plastics	0 %	p/st	31.12.2020
ex 8708 50 99	10	consisting of a unique piece without any joint in the middle			
		— of a length of 1 m or more but not more than 2 m,			
		— of a weight of 6 kg or more but not more than 9 kg			
*ex 8708 50 20	30	Single input, dual output gearcase (transmission) in	0 %	_	31.12.2021
ex 8708 50 99	20	a cast aluminum housing, with overall dimensions of			
ex 8708 99 10	20	273 mm (width) $\times$ 131 mm (height) $\times$ 187 mm (length), comprising at least:			
ex 8708 99 97	70	<ul> <li>two electro-magnetic one direction clutches, work- ing in opposite sides,</li> </ul>			
		<ul> <li>an input shaft with an outer diameter of 24 mm (± 1 mm), ended with 22 teeth spline, and</li> </ul>			
		<ul> <li>a coaxial output bushing with an inner diameter of 22 mm (± 1 mm), ended with 22 teeth spline</li> </ul>			
		for use in the manufacture of all-terrain vehicles or utility task vehicles $(^{2})$			
*ex 8708 80 20	10	Upper strut insulator containing	0 %	p/st	31.12.2020
ex 8708 80 35	10	— a metal holder with three mounting screws, and		.,	
		— a rubber bump			
		of a kind used in the manufacture of goods of Chap- ter 87			
*ex 8708 80 20	20	Rear chassis arm with a protective plastic label equipped	0 %	p/st	31.12.2020
ex 8708 80 91	10	with two metal casings with pressed-in rubber silent blocks, of kind used in the manufacture of goods of Chapter 87			
*ex 8708 80 20	30	Rear chassis arm equipped with a ball pivot and metal	0 %	p/st	31.12.2020
ex 8708 80 91	20	casing with a pressed-in rubber silent block, of kind used in the manufacture of goods of Chapter 87			
ex 8708 80 99	10	Stabilizer bar for front axle equipped with a ball pivot on both ends for use in the manufacture of goods of	0 %	p/st	31.12.2021
		Chapter 87 (²)			
*ex 8708 91 20	20	Aluminium cooler using compressed air with a ribbed design of a kind used in the manufacture of goods of	0 %	p/st	31.12.2019
ex 8708 91 35	10	Chapter 87			
<sup>6</sup> ex 8708 91 20	30	Aluminium alloy inlet or outlet air tank manufactured	0 %	p/st	31.12.2020
ex 8708 91 99	30	to standard EN AC 42100 with: — an insulating area flatness of not more than			
		0,1 mm,			
		— a permissible particle quantity of 0,3 mg per tank,			
		— a distance between pores of 2 mm or more,			

CN code	TARIC	Description	Rate of autonomous duty	Supplemen- tary Unit	Date foreseen for mandatory review
		— pore sizes of not more than 0,4 mm, and			
		— not more than 3 pores larger than 0,2 mm			
		of a kind used in heat exchangers for car cooling systems			
*ex 8708 94 20	10	Rack steering gear in aluminium housing with homo-	0 %	p/st	31.12.2019
ex 8708 94 35	20	kinetic hinges of a kind used in the manufacture of goods of Chapter 87			
*ex 8708 95 10	40	Front passenger airbag composed of:	0 %	p/st	31.12.2020
ex 8708 95 99	10	- a metal housing with at least six mounting brackets,			
		— an embedded safety cushion,			
		— a cartridge filled with compressed gas			
		of a kind used in the manufacture of goods of Chap- ter 87			
ex 8708 99 10	30	Front radiator holder whether or not with rubber cush-	0 %	p/st	31.12.2021
ex 8708 99 97	15	ioning for use in the manufacture of goods of Chapter 87 $\left(^2\right)$			
ex 8708 99 10	40	Support bracket of iron or steel, with mounting holes,	0 %	p/st	31.12.2021
ex 8708 99 97	25	whether or not with fixation nuts, for connecting the gearbox to the car body for use in the manufacture of goods of Chapter 87 $(^2)$			
*ex 8714 91 30	25	Front forks, except rigid (non-telescopic) front forks	0 %	_	31.12.2018
ex 8714 91 30	35	made entirely of steel, for use in the manufacture of bicycles ( <sup>2</sup> )			
ex 8714 91 30	72	bicycles (-)			
*ex 9013 80 90	20	Electronic semiconductor micro-mirror in a housing suitable for the automatic printing of conductor boards, mainly consisting of a combination of:	0 %	p/st	31.12.2019
		<ul> <li>one or more monolithic application-specific inte- grated circuits (ASIC),</li> </ul>			
		<ul> <li>one or more microelectromechanical mirrors (MEMS) manufactured with semiconductor tech- nology, with mechanical components arranged in three-dimensional structures on the semiconductor material</li> </ul>			
		of a kind used for incorporation into products of Chap- ters 84 to 90 and 95			

# ANNEX II

CN code	TARIC
ex 2818 30 00	30
ex 2842 10 00	40
ex 2905 11 00	20
ex 2909 60 00	20
ex 2916 14 00	30
ex 2920 90 70	40
ex 2920 90 70	50
ex 2931 90 00	05
ex 2933 59 95	88
ex 2933 99 80	53
ex 2933 99 80	72
ex 2940 00 00	40
ex 3204 16 00	20
ex 3204 17 00	67
ex 3215 90 70	30
ex 3506 91 10	50
ex 3506 91 90	50
ex 3811 21 00	57
ex 3815 90 90	40
ex 3824 99 92	21
ex 3824 99 92	24
ex 3824 99 92	69
ex 3901 10 10	20
ex 3901 90 80	50
ex 3913 90 00	92
ex 3921 13 10	10
ex 3923 10 00	10
ex 3926 30 00	10
ex 3926 90 97	20
ex 5911 90 90	30
ex 5911 90 90	40
ex 7410 11 00	10
ex 7607 11 90	40
ex 7607 19 90	10
ex 7616 99 10	30
ex 8108 90 30	20
ex 8108 90 50	10
ex 8108 90 50	25
ex 8301 60 00	20
ex 8409 91 00	65
ex 8409 99 00	30
ex 8411 99 00	70
ex 8413 91 00	40

CN code	TARIC
ex 8419 90 85	30
ex 8421 99 00	92
ex 8438 90 00	20
ex 8468 90 00	20
ex 8476 90 10	20
ex 8476 90 90	20
ex 8479 90 70	83
ex 8481 90 00	30
ex 8501 10 99	55
ex 8503 00 99	70
ex 8504 31 80	50
ex 8504 40 90	20
ex 8505 11 00	33
ex 8505 11 00	45
ex 8507 90 80	60
ex 8507 90 80	70
ex 8507 90 80	80
ex 8515 90 80	30
ex 8522 90 80	30
ex 8529 90 65	65
ex 8529 90 92	35
ex 8529 90 92	36
ex 8529 90 92	50
ex 8536 90 40	20
ex 8536 90 40	92
ex 8536 90 40	94
ex 8536 90 40	95
ex 8536 90 95	20
ex 8536 90 95	92
ex 8536 90 95	94
ex 8536 90 95	95
ex 8537 10 98	70
ex 8537 10 98	92
ex 8543 70 90	33
ex 8543 90 00	15
ex 8544 49 93	10
ex 8545 90 90	30
ex 8708 29 90	10
ex 8708 30 10	20
ex 8708 30 10	30
ex 8708 30 91	10
ex 8708 30 91	20
ex 8708 30 91	30
ex 8708 30 91	40
ex 8708 30 91	50

CN code	TARIC
ex 8708 40 20	20
ex 8708 40 50	10
ex 8708 50 55	10
ex 8708 50 99	10
ex 8708 50 99	20
ex 8708 80 35	10
ex 8708 80 91	10
ex 8708 80 91	20
ex 8708 91 35	10
ex 8708 91 99	20
ex 8708 91 99	30
ex 8708 94 35	20
ex 8708 95 99	10
ex 8708 99 10	20
ex 8708 99 97	40
ex 8708 99 97	50
ex 8708 99 97	70
ex 8714 91 30	24
ex 8714 91 30	34
ex 8714 91 30	71
ex 9013 80 90	10