

## II

(Non-legislative acts)

## REGULATIONS

## COUNCIL REGULATION (EU) 2022/1008

of 17 June 2022

**amending Regulation (EU) 2021/2278 suspending the Common Customs Tariff duties referred to in Article 56(2), point (c), of Regulation (EU) No 952/2013 on certain agricultural and industrial products**

THE COUNCIL OF THE EUROPEAN UNION,

Having regard to the Treaty on the Functioning of the European Union, and in particular Article 31 thereof,

Having regard to the proposal from the European Commission,

Whereas:

- (1) In order to ensure a sufficient and uninterrupted supply of certain agricultural and industrial products which are not produced in the Union and thereby avoid any disturbances on the market for those products, Common Customs Tariff duties of the type referred to in Article 56(2), point (c), of Regulation (EU) No 952/2013 of the European Parliament and of the Council <sup>(1)</sup> ('CCT duties') on those products have been suspended by Council Regulation (EU) 2021/2278 <sup>(2)</sup>. As a result, the products listed in the Annex to Regulation (EU) 2021/2278 can be imported into the Union at reduced or zero duty rates.
- (2) The Union production of certain products that are not listed in the Annex to Regulation (EU) 2021/2278 is inadequate to meet the specific requirements of the user industries in the Union. As it is in the Union's interest to ensure an adequate supply of certain products, and having regard to the fact that that identical, equivalent or substitute products are not produced in sufficient quantities within the Union, it is necessary to grant a complete suspension of the CCT duties on those products.
- (3) With a view to promoting integrated battery production in the Union in accordance with the communication from the Commission of 17 May 2018 entitled 'Europe on the Move – Sustainable Mobility for Europe: safe, connected, and clean', a partial suspension of the CCT duties should be granted in respect of certain products related to battery production that are not listed in the Annex to Regulation (EU) 2021/2278. The date for the mandatory review of those suspensions should be 31 December 2022, in order for that review to take into account the short-term evolution of the battery sector in the Union.
- (4) It is necessary to amend the product description and classification for certain CCT duty suspensions listed in the Annex to Regulation (EU) 2021/2278 in order to take into account technical product developments and economic trends in the market.
- (5) It is no longer in the interest of the Union to maintain the suspension of CCT duties for certain products listed in the Annex to Regulation (EU) 2021/2278. The suspensions for those products should therefore be deleted with effect from 1 July 2022.

<sup>(1)</sup> Regulation (EU) No 952/2013 of the European Parliament and of the Council of 9 October 2013 laying down the Union Customs Code (OJ L 269, 10.10.2013, p. 1).

<sup>(2)</sup> Council Regulation (EU) 2021/2278 of 20 December 2021 suspending the Common Customs Tariff duties referred to in Article 56(2), point (c), of Regulation (EU) No 952/2013 on certain agricultural and industrial products, and repealing Regulation (EU) No 1387/2013 (OJ L 466, 29.12.2021, p. 1).

- (6) Regulation (EU) 2021/2278 should therefore be amended accordingly.
- (7) In order to avoid any interruption in the application of the autonomous tariff suspension scheme and to comply with the guidelines set out in the communication from the Commission of 13 December 2011 concerning autonomous tariff suspensions and quotas, the changes provided for in this Regulation regarding the tariff suspensions for the products concerned should apply from 1 July 2022. This Regulation should therefore enter into force as a matter of urgency,

HAS ADOPTED THIS REGULATION:

*Article 1*

The Annex to Regulation (EU) 2021/2278 is amended in accordance with the Annex to this Regulation.

*Article 2*

This Regulation shall enter into force on the day following that of its publication in the *Official Journal of the European Union*.

It shall apply from 1 July 2022.

This Regulation shall be binding in its entirety and directly applicable in all Member States.

Done at Luxembourg, 17 June 2022.

*For the Council*  
*The President*  
B. LE MAIRE

## ANNEX

The Annex to Regulation (EU) 2021/2278 is amended as follows:

- (1) the entries with the following serial numbers are deleted: 0.3965, 0.4050, 0.4890, 0.4934, 0.5487, 0.7369, 0.8088 and 0.8210;
- (2) the following entries replace those entries that have the same serial numbers:

Serial number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary unit	Date envisaged for mandatory review
0.7284	ex 2106 90 92 ex 3504 00 90	50 10	Casein protein hydrolysate consisting of: — by weight 20 % or more but not more than 70 % free amino acids, and — peptones of which by weight more than 90 % having a molecular weight of not more than 2 000 Da	0 %	-	31.12.2022
0.2542	ex 2903 47 00	20	1,1,1,3,3-Pentafluoropropane (HFC-245fa) (CAS RN 460-73-1)	0 %	-	31.12.2023
0.3616	ex 2922 19 00	53	2-(2-Methoxyphenoxy) ethanamine (CAS RN 1836-62-0) with a purity by weight of 98 % or more	0 %	-	31.12.2024
0.8137	ex 3208 90 19 ex 3911 90 99	13 63	Mixture, containing by weight: — 20 % or more but not more than 40 % of a copolymer of methyl vinyl ether and monobutyl maleate (CAS RN 25119-68-0), — 7 % or more but not more than 20 % of a copolymer of methyl vinyl ether and monoethyl maleate (CAS RN 25087-06-3), — 40 % or more, but not more than 65 % of ethanol (CAS RN 64-17-5), — 1 % or more but not more than 7 % of butan-1-ol (CAS RN 71-36-3)	0 %	-	31.12.2025
0.5560	ex 3904 69 80	85	Copolymer of ethylene and chlorotrifluoroethylene, whether or not modified with hexafluoroisobutylene, whether or not containing fillers	0 %	-	31.12.2022
0.2759	ex 3907 30 00	40	Epoxide resin, containing by weight 70 % or more of silicon dioxide, for the encapsulation of goods of headings 8504, 8533, 8535, 8536, 8541, 8542 or 8548 (!)	0 %	-	31.12.2023

0.5172	ex 3912 39 85	40	Hypromellose (INN) (CAS RN 9004-65-3)	0 %	-	31.12.2022
0.4844	ex 3921 90 55	25	Prepreg sheets or rolls containing polyimide resin	0 %	-	31.12.2024
0.8024	ex 5603 14 10	30	Non-wovens, consisting of poly (ethylene terephthalate) spun bonded media: — of weight of 160 g/m <sup>2</sup> or more but not more than 300 g/m <sup>2</sup> , — with a filtration efficiency of class M or better (according to DIN 60335-2-69), — pleatable, with at least one of following treatments: — a coating or covering with polytetrafluoroethylene (PTFE), — a coating with aluminium particles, — a coating of phosphorous based flame retardants, — a nano fiber coating of a polyamide, a polyurethane or a fluorine-containing polymer	0 %	m <sup>2</sup>	31.12.2023
0.5987	ex 5603 14 90	60	Non-wovens, consisting of poly (ethylene terephthalate) spun bonded media: — of weight of 160 g/m <sup>2</sup> or more but not more than 300 g/m <sup>2</sup> , — with a filtration efficiency of class M or better (according to DIN 60335-2-69), — pleatable, — with or without an expanded polytetrafluoroethylene (ePTFE) membrane	0 %	m <sup>2</sup>	31.12.2023
0.4476	ex 7019 61 00 ex 7019 61 00 ex 7019 65 00 ex 7019 65 00 ex 7019 65 00 ex 7019 65 00 ex 7019 65 00 ex 7019 65 00 ex 7019 65 00 ex 7019 66 00 ex 7019 66 00 ex 7019 66 00 ex 7019 66 00 ex 7019 66 00 ex 7019 66 00 ex 7019 66 00 ex 7019 66 00 ex 7019 66 00 ex 7019 90 00 ex 7019 90 00	11 19 11 12 13 14 15 18 19 11 12 13 14 15 18 19 11 12 13 14 15 18 19 11 19	Woven fabrics of rovings, impregnated with epoxy resin, with a coefficient of thermal expansion between 30°C and 120°C (measured according to IPC-TM-650) of: — 10ppm per°C or more but not more than 12ppm per°C in the length and width, and — 20ppm per°C or more but not more than 30ppm per°C in the thickness, with a glass transition temperature of 152°C or more but not more than 153°C (measured according IPC-TM-650)	0 %	-	31.12.2023

0.7996	ex 8418 99 90	20	Aluminium connecting block for connecting to a condenser manifold in welding process: — hardened to T6 or T5 temper, — with a weight of not more than 150 g, — with a length of 20 mm or more but not more than 150 mm, — with a fixing rail in one piece	0 %	p/st	31.12.2025
0.8004	ex 8418 99 90	30	Receiver dryer profile for connecting to a condenser manifold in welding process with: — a braze flatness of not more than 0,2 mm, — a weight of 100 g or more but not more than 600 g, — a fixing rail in one piece	0 %	p/st	31.12.2025
0.7375	ex 8481 10 19 ex 8481 10 99	30 20	Electromagnetic pressure reducing valve — with a plunger, — with an operating pressure of not more than 325 MPa, — with a plastic connector with 2 silver or tin, or silver-plated, or tin-plated, or silver and tin plated pins	0 %	-	31.12.2022
0.7029	ex 8505 11 00	47	Articles in the form of a triangle, square, rectangle, or trapezoid, whether or not arched, with rounded corners or oblique sides, intended to become permanent magnets after magnetisation, containing neodymium, iron and boron, with the following dimensions: — a length of 9 mm or more but not more than 105 mm, — a width of 5 mm or more but not more than 105 mm, and — a height of 2 mm or more but not more than 55 mm	0 %	-	31.12.2026
0.5548	ex 8507 60 00	50	Modules for the assembly of batteries of ion lithium electric accumulators with: — a length of 298 mm or more, but not more than 500 mm, — a width of 33,5 mm or more, but not more than 209 mm, — a height of 75 mm or more, but not more than 228 mm, — a weight of 3,6 kg or more, but not more than 17 kg, and — a power of 458 Wh or more, but not more than 2 900 Wh	1,3 %	-	31.12.2022

0.7489	ex 8529 90 92	78	OLED modules, consisting of one or more TFT glass or plastic cells, — a diagonal measurement of the screen of 121 cm or more, but not more than 224 cm, — with a thickness of not more than 55mm, — containing organic material, — with control electronic for pixel addressing only, — with V-by-One Interface and with or without a plug for power supply, — with back cover, of a kind used in the manufacture of TV sets and monitors	0 %	-	31.12.2023
0.3959	ex 8540 71 00	20	Continuous wave magnetron with: — a fixed frequency of 2 460 MHz, — a packaged magnet, — a probe output, — an output power of 960 or more but not more than 1 500 W	0 %	-	31.12.2023
0.6687	ex 8708 95 10 ex 8708 95 99	30 40	Inflatable sewn safety cushion of high strength polyamide fibre: — folded into three-dimensional packing form, fixed by thermal forming, dedicated fixation seams, fabric cover or plastic staples, or — flat safety cushion with or without thermal folding	0 %	p/st	31.12.2025

(<sup>1</sup>) Suspension of duties is subject to end-use customs supervision in accordance with Article 254 of Regulation (EU) No 952/2013<sup>1</sup>;

- (3) the following entries are inserted according to the numerical order of the CN and TARIC codes in the second and third columns:

Serial number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary unit	Date envisaged for mandatory review
0.8296	ex 2826 90 80	30	Lithium hexafluorophosphate (CAS RN 21324-40-3) with a purity by weight of 99 % or more	2,7 %	-	31.12.2022
0.8237	ex 2845 90 10	10	4-(Tert-Butyl)-2-(2-(methyl-d3)propan-2-yl-1,1,1,3,3,3-d6)phenol (CAS RN 2342594-40-3) with a purity by weight of 98 % or more	0 %	-	31.12.2026

0.8282	ex 2903 19 00	20	1,3-Dichloropropane (CAS RN 142-28-9) with a purity by weight of 99 % or more	0 %	-	31.12.2026
0.8241	ex 2909 49 80	30	3,4-Dimethoxybenzyl alcohol (CAS RN 93-03-8) with a purity by weight of 98 % or more	0 %	-	31.12.2026
0.8288	ex 2914 40 90	10	Benzoin (CAS RN 119-53-9) with a purity by weight of 99 % or more	0 %	-	31.12.2026
0.8311	ex 2915 90 70	38	Pelargonic acid (CAS RN 112-05-0) with a purity by weight of 95 % or more	0 %	-	31.12.2026
0.8302	ex 2917 19 80	55	Maleic acid (CAS RN 110-16-7) with a purity by weight of 99 % or more	3,2 %	-	31.12.2022
0.8255	ex 2917 39 95	45	3-(4-Chlorophenyl)glutaric acid (CAS RN 35271-74-0) with a purity by weight of 98 % or more	0 %	-	31.12.2026
0.8256	ex 2918 30 00	55	Methyl 3-oxo-pentanoate (CAS RN 30414-53-0) with a purity by weight of 98 % or more	0 %	-	31.12.2026
0.8297	ex 2920 90 10	45	Ethylene carbonate (CAS RN 96-49-1) with a purity by weight of 99 % or more	3,2 %	-	31.12.2022
0.8298	ex 2920 90 10	55	Vinylene carbonate (CAS RN 872-36-6) with a purity by weight of 99,9 % or more	3,2 %	-	31.12.2022
0.8299	ex 2920 90 10	65	Vinyl ethylene carbonate (CAS RN 4427-96-7) with a purity by weight of 99 % or more	3,2 %	-	31.12.2022
0.8234	ex 2922 49 85	33	4-Amino-2-chlorobenzoic acid (CAS RN 2457-76-3) with a purity by weight of 98 % or more	0 %	-	31.12.2026
0.8236	ex 2922 49 85	43	(E)-Ethyl 4-(dimethylamino)but-2-enoate maleate (CAS RN 1690340-79-4) with a purity by weight of 98 % or more	0 %	-	31.12.2026

0.8283	ex 2924 19 00	48	N,N-Dimethylcarbamoyl chloride (CAS RN 79-44-7) with a purity by weight of 99 % or more	0 %	-	31.12.2026
0.8235	ex 2924 29 70	32	N-(4-Amino-2-ethoxyphenyl)acetamide (CAS RN 848655-78-7) with a purity by weight of 98 % or more	0 %	-	31.12.2026
0.8258	ex 2924 29 70	36	N,N'-(2-Chloro-5-methyl-1,4-phenylene)bis [3-oxobutyramide] (CAS RN 41131-65-1) with a purity by weight of 97 % or more	0 %	-	31.12.2026
0.8272	ex 2931 90 00	30	Tert-Butylchlorodimethylsilane (CAS RN 18162-48-6) with a purity by weight of 99 % or more	0 %	-	31.12.2026
0.8252	ex 2932 19 00	55	(3S)-3-[4-[(5-Bromo-2-chlorophenyl)methyl]phenoxy]tetrahydro-furan (CAS RN 915095-89-5) with a purity by weight of 97 % or more	0 %	-	31.12.2026
0.8257	ex 2932 99 00	28	1,4,7,10,13-Pentaoxacyclopentadecane (CAS RN 33100-27-5) with a purity by weight of 90 % or more, the remainder mainly consisting of linear precursors	0 %	-	31.12.2026
0.8240	ex 2933 19 90	53	3-[2-(Dispiro[2.0.2 <sup>4</sup> .1 <sup>3</sup> ]heptan-7-yl)ethoxy]-1H-pyrazole-4-carboxylic acid (CAS RN 2608048-67-3) with a purity by weight of 98 % or more	0 %	-	31.12.2026
0.8312	ex 2933 21 00	45	Sodium (5S,8S)-8-methoxy-2,4-dioxo-1,3-diazaspiro [4.5]decan-3-ide (CAS RN 1400584-86-2) with a purity by weight of 90 % or more	0 %	-	31.12.2026
0.8238	ex 2933 39 99	15	(S)-6-Bromo-2-(4-(3-(1,3-dioxoisindolin-2-yl)propyl)-2,2-dimethylpyrrolidin-1-yl)nicotinamide (CAS RN 2606972-45-4) with a purity by weight of 98 % or more	0 %	-	31.12.2026
0.8239	ex 2933 39 99	18	Perfluorophenyl 6-fluoropyridine-2-sulfonate (CAS RN 2608048-81-1) with a purity by weight of 98 % or more	0 %	-	31.12.2026



0.8266	ex 2933 39 99	42	Glasdegib maleate (INN) (CAS RN 2030410-25-2) with a purity by weight of 98 % or more	0 %	-	31.12.2026
0.8248	ex 2933 59 95	38	5-(5-Chlorosulfonyl-2-ethoxyphenyl)-1-methyl-3-propyl-1,6-dihydro-7H-pyrazolo[4,3-d]pyrimidin-7-one (CAS No 139756-22-2) with a purity by weight of 98 % or more	0 %	-	31.12.2026
0.8243	ex 2933 59 95	41	2-(4-Phenoxyphenyl)-7-(piperidin-4-yl)-4,5,6,7-tetrahydropyrazolo[1,5-a]pyrimidine-3-carbonitrile (CAS RN 2190506-57-9) with a purity by weight of 98 % or more	0 %	-	31.12.2026
0.8290	ex 2933 99 80	18	2-(2-Ethoxyphenyl)-5-methyl-7-propylimidazolo[5,1-f][1,2,4]-triazin-4(3H)-one (CAS RN 224789-21-3) with a purity by weight of 95 % or more	0 %	-	31.12.2026
0.8249	ex 2933 99 80	22	Dibenz[b,f]azepine-5-carbonyl chloride (CAS RN 33948-22-0) with a purity by weight of 98 % or more	0 %	-	31.12.2026
0.8284	ex 2933 99 80	32	1H-1,2,3-Triazole (CAS RN 288-36-8) or 2H-1,2,3-triazole (CAS RN 288-35-7) with a purity by weight of 99 % or more	0 %	-	31.12.2026
0.8250	ex 2934 99 90	18	Methyl (1R,3R)-1-(1,3-benzodioxol-5-yl)-2-(2-chloroacetyl)-1,3,4,9-tetrahydropyrido[5,4-b]indole-3-carboxylate (CAS RN 171489-59-1) with a purity by weight of 99 % or more	0 %	-	31.12.2026
0.8253	ex 2934 99 90	22	4-(Oxiran-2-ylmethoxy)-9H-carbazole (CAS RN 51997-51-4) with a purity by weight of 97 % or more	0 %	-	31.12.2026
0.8267	ex 2934 99 90	35	Nusinersen sodium (INN) (CAS RN 1258984-36-9) with a purity by weight of 95 % or more	0 %	-	31.12.2026
0.8289	ex 2934 99 90	71	3,4-Dichloro-1,2,5-thiadiazole (CAS RN 5728-20-1) with a purity by weight of 99 % or more	0 %	-	31.12.2026

0.8276	ex 2935 90 90	22	Methyl 2-(chlorosulfonyl)-4-(methylsulfonamidomethyl)benzoate (CAS RN 393509-79-0) with a purity by weight of 90 % or more	0 %	-	31.12.2026
0.8277	ex 2935 90 90	24	3-(((4-methylphenyl)sulfonyl)carbamoyl)amino)phenyl 4-methylbenzenesulfonate (CAS RN 232938-43-1) with a purity by weight of 99 % or more	0 %	-	31.12.2026
0.8273	ex 3812 39 90	45	2-Aminoethanol reaction products with cyclohexane and peroxidized N-butyl-2,2,6,6-tetramethyl-4-piperidinamine-2,4,6-trichloro-1,3,5-triazine reaction products (CAS RN 191743-75-6) with a purity by weight of 99 % or more	0 %	-	31.12.2026
0.8278	ex 3824 99 92	94	(((2-(trifluoromethyl)phenyl)carbonyl)amino)methyl acetate (CAS RN 895525-72-1) with a content of at least 45 % by weight dissolved in N,N-dimethylacetamide (CAS RN 127-19-5)	0 %	-	31.12.2026
0.8287	ex 3824 99 92	95	Solution of methyl cis-1-(((2,5-dimethylphenyl)acetyl)amino)-4-methoxycyclohexanecarboxylate (CAS RN 203313-47-7) in N,N-dimethylacetamide (CAS RN 127-19-5), containing by weight 25 % or more but not more than 45 % of the carboxylate	0 %	-	31.12.2026
0.8268	ex 3917 32 00	30	Heat shrinkable tube: — containing by weight 80 % or more polymer, — with an insulation resistance of 90 MW or more, — with a dielectric strength of 35 kV / mm or more, — with a wall thickness of 0,04 mm or more, but not more than 0,9 mm, — with a lay-flat width of 18 mm or more, but not more than 156 mm, for use in the manufacture of aluminium electrolytic capacitors (!)	0 %	-	31.12.2022
0.8274	ex 3920 61 00	50	Coextruded film of polycarbonate main layer and polymethyl methacrylate top layer with a: — total thickness of more than 230 µm but not more than 270 µm,	0 %	-	31.12.2026

			<ul style="list-style-type: none"> <li>— top layer thickness of more than 40 µm but not more than 55 µm,</li> <li>— defined surface roughness of the top layer of 0,5 µm or less (according to ISO 4287),</li> <li>— UV-stabilized top layer</li> </ul>			
0.8291	ex 3921 90 55	60	<p>Membrane composed of a polyamide layer and a polysulfone layer on a cellulose support layer with:</p> <ul style="list-style-type: none"> <li>— a total thickness of 0,25 mm or more but not more than 0,40 mm,</li> <li>— a total weight of 109 g/m<sup>2</sup> or more but not more than 114 g/m<sup>2</sup></li> </ul>	0 %	-	31.12.2026
0.8265	ex 7007 11 10	10	<p>Specifically shaped and toughened safety glass:</p> <ul style="list-style-type: none"> <li>— with a width of 200 mm or more but not more than 600 mm,</li> <li>— with a height of 150 mm or more but not more than 500 mm,</li> </ul> <p>for use in the manufacture of motor vehicle window assemblies (1)</p>	0 %	-	31.12.2026
0.8247	ex 8302 10 00	20	<p>Armrest hinge made of magnesium with:</p> <ul style="list-style-type: none"> <li>— a length of 255 mm or more but not more than 265 mm,</li> <li>— a width of 155 mm or more but not more than 165 mm,</li> <li>— a height of 115 mm or more but not more than 125 mm,</li> <li>— mounting holes for a lock mechanism</li> </ul>	0 %	-	31.12.2026
0.8304	ex 8302 30 00	20	<p>Two cold-formed steel supports:</p> <ul style="list-style-type: none"> <li>— with a length of 160 mm or more but not more than 180 mm,</li> <li>— with a width of 60 mm or more but not more than 80 mm,</li> <li>— with a height of 60 mm or more but not more than 80 mm,</li> <li>— with a movable riveted connection,</li> <li>— with or without elastomeric bumper,</li> <li>— forming a mechanism for indirect movement of the mechanism of the longitudinal positioner of car seats, interacting with the safety latch,</li> <li>— attached to the mechanism of the longitudinal positioner by means of a detachable screw connection, riveting, welding or spot welding</li> </ul>	0 %	-	31.12.2026

0.8260	ex 8407 34 10	10	Spark-ignition reciprocating or rotary internal combustion piston engines, with: <ul style="list-style-type: none"> <li>— a cylinder capacity of 1 200 cm<sup>3</sup> or more but not more than 2 000 cm<sup>3</sup></li> <li>— a power of 95 kW but not more than 135 kW,</li> <li>— a weight of not more than 120 kg,</li> </ul> for use in the manufacture of motor vehicles of 8703 <sup>(1)</sup>	0 %	-	31.12.2026
0.8300	ex 8408 90 65 ex 8408 90 67 ex 8408 90 81	20 20 20	Compression-ignition internal combustion piston engines: <ul style="list-style-type: none"> <li>— of the inline type,</li> <li>— with a cylinder capacity of 7 100 cm<sup>3</sup> or more but not more than 18 000 cm<sup>3</sup>,</li> <li>— with a power of 205 kW or more but not more than 597 kW,</li> <li>— with an exhaust after-treatment module,</li> <li>— with external width/height/depth dimensions of not more than 1 310/1 300/1 040 mm or 2 005/1 505/1 300 mm or 2 005/1 505/1 800 mm,</li> </ul> for use in the manufacture of crushing, screening or separation machines <sup>(1)</sup>	0 %	-	31.12.2026
0.8244	ex 8409 91 00	85	Cylinder head blank for a four cylinder engine with 10 cores, made of aluminium alloy EN AC-45500, with: <ul style="list-style-type: none"> <li>— no other components,</li> <li>— a hardness of 52 HRB or more,</li> <li>— casting defects size of not more than 0,4 mm and not more than 10 defects per cm<sup>2</sup>,</li> <li>— a dendrite arm space in combustion chamber of not more than 25 µm,</li> <li>— a double deck water jacket design and</li> <li>— a weight of 18 kg or more but not more than 19 kg,</li> <li>— a length of 506 mm or more but not more than 510 mm,</li> <li>— a height of 282 mm or more but not more than 286 mm,</li> <li>— a width of 143,7 mm or more but not more than 144,3 mm,</li> </ul> in one single consignment of 1 000 pieces or more	0 %	-	31.12.2026
0.8303	ex 8483 40 25	20	Worm gearbox <ul style="list-style-type: none"> <li>— in an aluminium alloy housing,</li> <li>— with a plastic or steel worm,</li> <li>— with mounting holes,</li> <li>— with a 90 degree reversible drive direction,</li> <li>— with a 4:19 transmission ratio,</li> </ul>	0 %	-	31.12.2026

			<ul style="list-style-type: none"> <li>— equipped with a lead screw with a length of 333 mm and a guide nut incorporated into the assembly bracket, with or without a lead screw support,</li> </ul> <p>for indirect connection to the drive motor of a car seat guide system <sup>(1)</sup></p>			
0.8285	ex 8501 53 50	40	<p>Permanent magnet traction AC motor, with:</p> <ul style="list-style-type: none"> <li>— a continuous power of 110 kW or more but not more than 150 kW,</li> <li>— a liquid cooled system,</li> <li>— a total length of 460 mm or more but not more than 590 mm,</li> <li>— a total width of 450 mm or more but not more than 580 mm,</li> <li>— a total height of 490 mm or more but not more than 590 mm,</li> <li>— a weight of not more than 310 kg,</li> <li>— 4 mounting points</li> </ul>	0 %	-	31.12.2026
0.8259	ex 8507 60 00	73	<p>Lithium-ion Electric accumulators consisting of 3 modules containing 102 cells in total, with:</p> <ul style="list-style-type: none"> <li>— a nominal capacity of 51 Ah per cell,</li> <li>— a nominal voltage of 285 V or more but not more than 426V,</li> <li>— a weight of 33 kg or more but not more than 36 kg per module,</li> <li>— a length of 1 400 mm or more but not more than 1 600 mm,</li> <li>— a height of 340 mm or more but not more than 395 mm,</li> <li>— a width of 220 mm or more but not more than 420 mm,</li> </ul> <p>for use in the manufacture of vehicles of subheadings 8703 60 and 8703 80 <sup>(1)</sup></p>	1,3 %	-	31.12.2022
0.8275	ex 8507 60 00	83	<p>Modules for the assembly of ion lithium electric accumulators with:</p> <ul style="list-style-type: none"> <li>— a length of 570 mm or more, but not more than 610 mm,</li> <li>— a width of 210 mm or more, but not more than 240 mm,</li> <li>— a height of 100 mm or more, but not more than 120 mm,</li> <li>— a weight of 28 kg or more, but not more than 35 kg, and</li> <li>— a capacity of not more than 2 500 Ah and a nominal energy of less than 7,5 kW,</li> </ul> <p>for use in the manufacture of vehicles of subheadings 8703 60, 8703 70, 8703 80 and 8704 60 <sup>(1)</sup></p>	1,3 %	-	31.12.2022

0.8286	ex 8507 60 00	88	A rechargeable lithium-ion battery, with: <ul style="list-style-type: none"> <li>— a fuse,</li> <li>— a cell-to-pack design,</li> <li>— a length of 1 050 mm or more but not more than 1 070 mm,</li> <li>— a width of 624 mm or more but not more than 636 mm,</li> <li>— a height of 235 mm or more but not more than 245 mm,</li> <li>— a mass of 214,4 kg or more but not more than 227,6 kg,</li> <li>— a capacity of 228 Ah,</li> <li>— an upper outer casing of a composite material,</li> <li>— an IP68 protection rating,</li> <li>— an energy density of 220Wh/l or more,</li> <li>— a specific energy of 159 Wh/kg or more,</li> <li>— without contactors,</li> </ul> for the manufacture of batteries for electric buses <sup>(1)</sup>	1,3 %	-	31.12.2022
0.8279	ex 8708 40 20	80	Transmission gearbox without torque converter, with: <ul style="list-style-type: none"> <li>— dual clutch,</li> <li>— 7 or more forward gears,</li> <li>— 1 reverse gear,</li> <li>— a maximum torque of 390 Nm,</li> <li>— whether or not with electric motor integrated,</li> <li>— a height of 480 mm or more but not more than 600 mm,</li> <li>— a width of 350 mm or more but not more than 450 mm, and</li> <li>— a weight of 80kg or more but not more than 110 kg,</li> </ul> for use in the manufacture of motor vehicles of Heading 8703 <sup>(1)</sup>	0 %	-	31.12.2026
0.8292	ex 8708 95 99	50	Airbag inflator containing both pyrotechnics and cold gas as propellant for safety airbags of vehicles, in each individual consignment of 1 000 pieces or more	0 %	-	31.12.2026

<sup>(1)</sup> Suspension of duties is subject to end-use customs supervision in accordance with Article 254 of Regulation (EU) No 952/2013.