

Official Journal

of the European Communities

ISSN 0378-6978

L 318

Volume 38

30 December 1995

English edition

Legislation

Contents

I *Acts whose publication is obligatory*

- ★ Council Regulation (EC) No 3021/95 of 22 December 1995 temporarily suspending the autonomous Common Customs Tariff duty on certain industrial products (in the chemical and allied sectors) 1
- ★ Council Regulation (EC) No 3022/95 of 22 December 1995 temporarily suspending the autonomous Common Customs Tariff duty on certain industrial products (in the microelectronics and allied sectors) 8

2

EN

Acts whose titles are printed in light type are those relating to day-to-day management of agricultural matters, and are generally valid for a limited period.

The titles of all other Acts are printed in bold type and preceded by an asterisk.

I

(Acts whose publication is obligatory)

COUNCIL REGULATION (EC) No 3021/95

of 22 December 1995

temporarily suspending the autonomous Common Customs Tariff duty on certain industrial products (in the chemical and allied sectors)

THE COUNCIL OF THE EUROPEAN UNION,

Having regard to the Treaty establishing the European Community, and in particular Article 28 thereof,

Having regard to the proposal from the Commission,

Whereas production of the products referred to in this Regulation is at present inadequate or non-existent within the Community and producers are thus unable to meet the needs of user industries in the Community;

Whereas it is in the Community's interest in certain cases to suspend the autonomous Common Customs Tariff duties only partially, particularly because of the existence of Community production, and in other cases to suspend them completely;

Whereas the decision for the suspension of these autonomous duties should be taken by the Community;

Whereas, taking account of the difficulties involved in accurately assessing the development of the economic

situation in the sectors concerned in the near future, these suspension measures should be taken only temporarily, by fixing their period of validity by reference to the interests of Community production,

HAS ADOPTED THIS REGULATION:

Article 1

The autonomous Common Customs Tariff duties for the products listed in the Annex shall be suspended at the level indicated in respect of each of them.

These suspensions shall apply from 1 January to 30 June 1996.

Article 2

This Regulation shall enter into force on 1 January 1996.

This Regulation shall be binding in its entirety and directly applicable in all Member States.

Done at Brussels, 22 December 1995.

For the Council
The President
L. ATIENZA SERNA

ANNEX

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 2805 30 10	*20	Alloy of lanthanum and other rare earth metals, containing by weight 43 % or more of lanthanum	0
ex 2823 00 00	*10	Titanium dioxide, of a purity by weight of 99,9 % or more, with an average grain-size of 1,2 micrometres or more but not exceeding 1,8 micrometres, for the manufacture of goods of heading No 8532 or 8533 (a)	0
ex 2826 90 90	*10	Potassium hexafluorophosphate	0
ex 2839 90 00	*10	Lead silicate hydrate, of a lead content by weight of 84,5 % ($\pm 1,5$ %), evaluated as lead monoxide, in the form of powder	0
ex 2843 90 90	*20	Palladium monoxide	0
ex 2909 50 90	*10	4-(2-Methoxyethyl)phenol	0
ex 2914 70 90	*20	21-Chloro-9 β ,11 β -epoxy-17-hydroxy-16 α -methylpregna-1,4-diene-3,20-dione	0
ex 2917 13 00	*10	Sebacic acid	0
ex 2917 20 00	*30	1,4,5,6,7,7-Hexachloro-8,9,10-trinorborn-5-ene-2,3-dicarboxylic anhydride	0
ex 2917 39 90	*35	Dimethyl naphthalene-2,6-dicarboxylate	0
ex 2918 17 00	*10	Phenylglycolic acid (mandelic acid)	0
ex 2918 90 00	*75	Sodium phenoxyacetate	0
ex 2920 10 00	*10	Fenitrothion (ISO)	0
2920 90 30		Trimethyl phosphite	0
ex 2921 42 10	*10	2,6-Dichloro-4-nitroaniline	0
ex 2921 42 10	*20	2-Bromo-4,6-dinitroaniline	0
ex 2921 42 10	*30	4-Aminobenzene-1,3-disulphonic acid and its salts	0
ex 2921 51 10	*10	<i>m</i> -Phenylenediamine, of a purity by weight of 99 % or more and containing: — 1 % or less by weight of water, — 200 mg/kg or less of <i>o</i> -phenylenediamine and — 450 mg/kg or less of <i>p</i> -phenylenediamine	0
ex 2921 59 00	*60	Mixture of isomers of 3,5-diethyltoluenediamine	0
ex 2922 19 00	*55	4,4-Dimethoxybutylamine	0
ex 2922 21 00	*10	2-Amino-5-hydroxynaphthalene-1,7-disulphonic acid and its salts, of a purity by weight of 60 % or more	0
ex 2922 29 00	*30	4-Amino-5-methoxy-2-methylbenzenesulphonic acid	0
ex 2922 29 00	*40	2-Amino-4- <i>tert</i> -pentyl-6-nitrophenol	0

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 2922 30 00	*10	1-Amino-4-bromo-9,10-dioxanthracene-2-sulphonic acid and its salts	0
ex 2923 90 00	*10	Tetramethylammonium hydroxide, in the form of an aqueous solution containing: — 25 % ($\pm 0,1$ %) by weight of tetramethylammonium hydroxide, — 5 mg/kg or less of halide, — 10 micrograms/kg or less of sodium, — 10 micrograms/kg or less of calcium, — 10 micrograms/kg or less of iron and — 10 micrograms/kg or less of zinc	0
ex 2924 29 90	*50	3'-Diethylamino-4'-methoxyacetanilide	0
ex 2924 29 90	*60	5-[N-(2-Acetoxyethyl)acetoxyacetamido]-N,N'-bis(2,3-diacetoxypropyl)-2,4,6-triiodoisophthalamide	0
ex 2926 90 90	*65	2-Amino-5-nitrobenzotrile	0
ex 2926 90 90	*75	Chlorothalonil (ISO)	0
ex 2930 90 95	*17	3,3'-Thiodi(propionic acid)	0
2931 00 10		Dimethyl methylphosphonate	0
ex 2931 00 80	*70	N-(Phosphonomethyl)iminodiacetic acid	0
ex 2933 21 00	*30	3'-[4,4-Dimethyl-2-(4,4-dimethyl-2,5-dioximidazolin-1-yl)-3-oxovalerylamino]-4'-methoxystearanilide	0
ex 2933 69 90	*35	Tris(2,3-epoxypropyl)-1,3,5-triazinetrione	0
ex 2933 69 90	*40	Cyanazine (ISO)	0
ex 2934 10 00	*20	2-(4-Methylthiazol-5-yl)ethanol	0
ex 2934 90 99	*38	4-[4-(Tridecyl[branched]oxy)phenyl]-1,4-thiazinane 1,1-dioxide	0
ex 2935 00 00	*45	Mixture of isomers consisting of N-ethyltoluene-2-sulphonamide and N-ethyltoluene-4-sulphonamide	0
ex 3204 15 00	*30	Dye C.I. Vat Red 74	0
ex 3204 17 00	*10	Dye C.I. Pigment Yellow 81	0
3301 12 10		Essential oil of orange, not dewatered	0
ex 3506 91 00	*10	Adhesive based on an aqueous dispersion of a mixture of dimerized rosin and a copolymer of ethylene and vinyl acetate (EVA)	0
ex 3507 90 00	*65	Asparaginase	0
ex 3815 12 00	*20	Catalyst consisting of palladium and rhenium, fixed on a support of active carbon, in the form of powder, containing: — 0,5 % or more but not more than 1,5 % by weight of palladium, — 3 % or more but not more than 5 % by weight of rhenium and — 0,1 mole % or more but not more than 1 mole % of alkaline metals, for use in the manufacture of tetrahydrofuran (a)	0

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 3815 19 00	*16	Catalyst consisting of dichromium trioxide, fixed on a support of aluminium oxide	0
ex 3818 00 10	*10	Silicon discs, with phosphorus diffused into one side, of a thickness not exceeding 310 micrometres, for use in the manufacture of semiconductor devices of heading No 8541 (a)	0
ex 3824 90 90	*03	Grains, consisting of a mixture of dialuminium trioxide and zirconium dioxide, containing by weight: — 70 % or more but not more than 78 % of dialuminium trioxide and — 19 % or more but not more than 26 % of zirconium dioxide	5,2
ex 3824 90 90	*35	Preparation consisting predominantly of ethylene glycol and <i>N,N</i> -dimethylformamide or ethylene glycol and γ -butyrolactone, for the manufacture of electrolytic capacitors (a)	0
ex 3824 90 90	*36	Preparation consisting predominantly of γ -butyrolactone and quaternary ammonium salts, for the manufacture of electrolytic capacitors (a)	0
ex 3824 90 90	*37	2,4,7,9-Tetramethyldec-5-yn-4,7-diol, hydroxyethylated	0
ex 3824 90 90	*38	Copper zinc ferrite, in the form of granules of a size not exceeding 120 micrometres, coated with a silicone resin	0
ex 3824 90 90	*39	Styrene oligomer	0
ex 3824 90 90	*41	Preparation consisting of α -(4-allyloxycarbonylbenzoyl)- ω -allyloxypoly[oxy(2-methylethylene)oxyterephthaloyl] and either diallyl-2,2'-oxydiethyl dicarbonate or diallyl isophthalate	0
ex 3901 90 00	*97	Copolymer of ethylene, vinyl acetate and carbon monoxide, for use as a plasticizer in the manufacture of roof sheets (a)	0
ex 3903 19 00	*20	Polystyrene of a molecular weight not exceeding 5 000	0
ex 3903 90 00	*80	Copolymer of α -methylstyrene and styrene, having a softening point exceeding 113 °C	0
ex 3911 90 90	*89		
ex 3904 61 90	*10	Mixture of polytetrafluoroethylene and mica, in one of the forms mentioned in note 6 (b) to Chapter 39	0
ex 3905 99 00	*94	Polyvinyl acetate phthalate	0
ex 3906 90 00	*70	Polymerization product of acrylic acid with small quantities of a polyunsaturated monomer, for the manufacture of medicaments of heading No 3003 or 3004 (a)	0
ex 3906 90 00	*80	Polymerization product of acrylic acid with small quantities of a polyunsaturated monomer, for use as a stabilizer in emulsions or dispersions with a pH of more than 13 (a)	6
ex 3907 30 00	*20	Epoxyde resin in the form of powder, containing by weight 44 % or more but not more than 55 % of quartz and 0,5 % or more but not more than 1 % of diantimony trioxide, for the coating of film capacitors (a)	0
ex 3911 90 90	*85	Copolymer of dibutyl maleate and <i>N</i> -vinyl-2-pyrrolidone, in one of the forms mentioned in note 6 (a) of Chapter 39	0

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 3911 90 90	*87	Copolymer of vinyltoluene and α -methylstyrene	0
ex 3911 90 90	*88	Hydrogenated copolymers of vinyltoluene and α -methylstyrene	0
ex 3919 90 10	*10	Shaped sheet of plastic, with an adhesive layer containing polyisobutylene and pectin, for the manufacture of colostomy bags (a)	0
ex 3919 90 31	*10	Reflecting laminated sheeting, metallized, not containing glass balls or pyramidal patterns, consisting of one sheet of polyester and at least another sheet of polyester or other plastic material and coated on one side with an adhesive, whether or not protected by a release sheet, in rolls, each roll of a width of 150 cm or more and a gross weight of 75 kg or more	0
ex 3920 69 00	*80		
ex 3919 90 31	*40	Reflecting polyester sheeting embossed in a regular pyramidal pattern, for the manufacture of safety stickers and badges, safety clothing and accessories thereof, or of school satchels, bags or similar containers (a)	0
ex 3920 62 10	*40		
ex 3920 62 90	*20		
ex 3920 63 00	*30		
ex 3920 69 00	*30		
ex 3919 90 61	*92	Polyvinyl chloride sheeting, of a thickness of less than 1 mm, coated with an adhesive in which are embedded glass balls of a diameter not exceeding 100 micrometres	0
ex 3919 90 69	*92		
ex 3919 90 61	*93	Adhesive film consisting of a base of a copolymer of ethylene and vinyl acetate (EVA) of a thickness of 120 micrometres or more and an adhesive part of acrylic type of a thickness of 10 micrometres or more, for the protection of the surface of silicon discs (a)	0
ex 3919 90 69	*93		
ex 3920 51 00	*10	Polymethyl methacrylate plate, with an antistatic coating, of dimensions of 738 x 972 mm ($\pm 1,5$ mm)	0
ex 3920 62 10	*10	Polyethylene terephthalate film, of a thickness of less than 11 micrometres, for the manufacture of digital audio cassettes (a)	0
ex 3920 62 10	*20	Polyethylene terephthalate film, not coated with an adhesive, of a thickness not exceeding 25 micrometres, either: — only dyed in the mass, or — dyed in the mass and metallized on one side	0
ex 3920 62 10	*45	Film of polyethylene terephthalate only, of a total thickness not exceeding 120 micrometres, consisting of one or two layers each containing a colouring and/or UV-absorbing material throughout the mass, uncoated with an adhesive or any other material	0
ex 3920 62 10	*50	Polyethylene terephthalate film, of a thickness of 20 micrometres or more but not exceeding 30 micrometres, coated on one side with silicone, for use in the manufacture of window film (a)	5,6
ex 3920 62 10	*55	Laminated film of polyethylene terephthalate only, of a total thickness not exceeding 120 micrometres, consisting of one layer which is metallized only and one or two layers each containing a colouring and/or UV-absorbing material throughout the mass, uncoated with an adhesive or any other material	0
ex 3920 62 10	*65	Single ply film of polyethylene terephthalate only, of a thickness not exceeding 120 micrometres, which only: — contains a colouring and/or UV-absorbing material throughout the mass and — is metallized on one side, whether or not coated on one or both sides with a vinyl acrylate polymer but having no other coating or adhesive	0

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 3921 19 90	*91	Microporous polypropylene film of a thickness not exceeding 30 micrometres	0
ex 4016 99 88	*10	Soft rubber sealing stoppers for the manufacture of electrolytic capacitors (a)	0
ex 4805 60 90	*10	Overlay paper, of a width of more than 205 cm and an abrasion resistance of at least 6 000 rpm (as determined by the EN 438-2:1991 method)	0
ex 4811 39 00	*10	Kraft paper impregnated with an acrylic polymer with a nominal weight of 85 g/m ²	0
ex 4911 99 00	*10	Polyester film, partially coated with a magnetic metal layer showing a regular repeating logo or motif, for the manufacture of security threads (a)	0
ex 5402 33 10 ex 5402 33 90	*10 *10	Textured yarn of polyester, single or two ply, measuring per single yarn 120 decitex and consisting of 36 filaments or measuring per single yarn 167 decitex and consisting of 48 filaments each having a random variation of diameter along its length	0
ex 5402 33 90	*20	Textured yarn of polyester, measuring per single yarn 167 decitex and consisting of 60 filaments or measuring per single yarn 334 decitex and consisting of 78 filaments, having filaments both of polyethylene terephthalate and of a polyethylene terephthalate which has been chemically modified to allow it to be dyeable with cationic dyestuffs	0
ex 5911 90 90	*40	Acrylic fibre rods, having a length of not more than 50 cm, for the manufacture of pen tips (a)	0
ex 6903 90 80 ex 6909 19 00	*10 *40	Beryllium oxide, of a purity by weight of more than 99 %, in the form of blanks, bars, blocks or plates	0
ex 7011 10 90	*10	Glass lenses with a stippled front refractor or with a front refractor composed of prismatic elements, with an external diameter of more than 121 mm but not exceeding 125 mm	0
ex 7011 10 90	*20	Parabolic glass reflectors, with an external diameter of more than 121 mm but not exceeding 125 mm	0
ex 7011 20 00	*40	Glass face-plate: — with a diagonal measurement of 366,4 mm ($\pm 1,5$ mm) and of dimensions of 246,4 x 315,4 mm ($\pm 1,5$ mm), — with a diagonal measurement of 391 mm ($\pm 1,5$ mm) and of dimensions of 261,4 x 326,8 mm ($\pm 1,5$ mm), — with a diagonal measurement of 442 mm ($\pm 1,5$ mm) and of dimensions of 293,4 x 369,2 mm ($\pm 1,5$ mm), — with a diagonal measurement of 513,5 mm ($\pm 1,6$ mm) and of dimensions of 341,8 x 440,5 mm ($\pm 1,6$ mm), — with a diagonal measurement of 544,5 mm ($\pm 1,6$ mm) and of dimensions of 358 x 454 mm ($\pm 1,6$ mm), — with a diagonal measurement of 629,8 mm (± 3 mm) and of dimensions of 406,5 x 519 mm (± 2 mm), — with a diagonal measurement of 639,3 mm (± 3 mm) and of dimensions of 413,6 x 527 mm (± 2 mm) or — with a diagonal measurement of 838,2 mm ($\pm 1,5$ mm) and of dimensions of 549,9 x 695,6 mm ($\pm 1,5$ mm), and with a raised edge, for the manufacture of colour cathode-ray tubes (a)	0

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 7011 20 00	*80	Glass cone: — with a diagonal measurement of 365,0 mm ($\pm 1,5$ mm) and of dimensions of 243,2 x 312,8 mm ($\pm 1,5$ mm), — with a diagonal measurement of 389,6 mm ($\pm 1,5$ mm) and of dimensions of 258,5 x 324,5 mm ($\pm 1,5$ mm) or — with a diagonal measurement of 439,9 mm ($\pm 1,5$ mm) and of dimensions of 290 x 366,6 mm ($\pm 1,5$ mm)	0
ex 7019 32 00	*10	Non-woven product of non-textile glass fibre, for the manufacture of air-filters or of air-filtration products (a)	0
ex 7019 39 10	*10		
ex 7019 39 90	*10		
ex 7306 30 29	*91	Non-alloy steel precision tube, welded and cold-finished, of an external diameter exceeding 160 mm and a wall thickness exceeding 2 mm	0
ex 8418 99 90	*91	Welded cooling micro-elements, of an alloy of aluminium, for the manufacture of condensers (a)	0
ex 8421 99 00	*95	Parts of equipment for the filtration of magnetic dispersions, consisting essentially of nylon-6 fibres, enclosed in a plastic casing of a diameter of 70 mm (± 2 mm) and a length of 520 mm (± 5 mm)	0

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

COUNCIL REGULATION (EC) No 3022/95

of 22 December 1995

temporarily suspending the autonomous Common Customs Tariff duty on certain industrial products (in the microelectronics and allied sectors)

THE COUNCIL OF THE EUROPEAN UNION,

Having regard to the Treaty establishing the European Community, and in particular Article 28 thereof,

Having regard to the proposal from the Commission,

Whereas production of the products referred to in this Regulation is at present inadequate or non-existent within the Community and producers are thus unable to meet the needs of user industries in the Community;

Whereas it is in the Community's interest in certain cases to suspend the autonomous Common Customs Tariff duties only partially, particularly because of the existence of Community production, and in other cases to suspend them completely;

Whereas the decision for the suspension of these autonomous duties should be taken by the Community;

Whereas, taking account of the difficulties involved in accurately assessing the development of the economic situation in the sectors concerned in the near future, these suspension measures should be taken only temporarily, by fixing their period of validity by reference to the interests of Community production,

HAS ADOPTED THIS REGULATION:

Article 1

The autonomous Common Customs Tariff duties for the products listed in the tables appearing in the Annex shall be suspended at the level indicated in respect of each of them.

These suspensions shall apply:

- from 22 November to 31 December 1995 for the product listed in the table appearing in Table I,
- from 1 January to 30 June 1996 for the products listed in the table appearing in Table II.

Article 2

This Regulation shall enter into force on 1 January 1996.

This Regulation shall be binding in its entirety and directly applicable in all Member States.

Done at Brussels, 22 December 1995.

For the Council

The President

L. ATIENZA SERNA

ANNEX

TABLE I

CN code	TARIC	Description	Rate of autonomous duty %
ex 8521 90 00	*91	Drive-unit for reading optical CD-ROM discs	3,9

TABLE II

CN code	TARIC	Description	Rate of autonomous duty %
ex 8471 60 90	*20	Pointing device (so-called 'trackball'), consisting of printed circuit on which are mounted an optical encoder in the form of a monolithic integrated circuit and a housing comprising a ball and a retainer ring, for use in the manufacture of products falling within subheading 8471 30 00 (a)	0
ex 8471 70 51 ex 8521 90 00	*30 *91	Drive-unit for reading optical CD-ROM discs	0
ex 8471 70 53	*40	Disc storage unit of the 3,5 inch type, capable of data-transfer at a rate per second of 7,5 megabytes or more but not exceeding 100 megabytes, comprising not more than 10 magnetic heads and not more than 5 rigid magnetic discs with a total storage capacity, formatted, not exceeding 4,35 gigabytes, for use in the manufacture of products falling within heading 8471 (a)	0
ex 8473 30 10	*01	Microprocessor, in the form of a monolithic integrated circuit contained in a housing on which are mounted at least one of the following components: — a decoupling capacitor, — a ventilator with a cooling element, — a control circuit, in the form of a monolithic integrated circuit	0
ex 8473 30 10	*02	Microprocessor module, only consisting of 7 monolithic integrated circuits consisting of: — a microprocessor unit associated with a cache memory with a storage capacity of 64 Kbits, — a floating point unit, — a microprocessor interface unit, — 4 memory control units associated with 4 cache memories with a total storage capacity of 2 Mbits the whole contained in a housing with decoupling capacitors	0
ex 8473 30 10	*03	Microprocessor with a processing capacity of 32 bits, only consisting of 2 monolithic integrated circuits contained in a housing bearing: — an identification marking consisting of or including the following combination of figures and letters: 80521EX or — other identification markings relating to devices complying with the abovementioned description	0

CN code	TARIC	Description	Rate of autonomous duty %
ex 8473 30 10	*04	Microprocessor module comprising 8 monolithic integrated circuits consisting of: — a fixed point unit, — a floating point unit, — an instruction cache memory unit, — a memory control unit, — 4 data cache memories, the whole contained in a housing with decoupling capacitors	0
ex 8473 30 10	*60	Microprocessor of C-MOS technology, with a processing capacity of 32 bits, in the form of a monolithic integrated circuit, contained in a housing mounted on a printed circuit the exterior dimensions of which do not exceed 60 × 60 mm, and with decoupling capacitors, and bearing: — an identification marking consisting of or including one of the following combinations of figures: 486 80386 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8473 30 10	*70	Microprocessor of C-MOS technology, with a processing capacity of 32 bits, comprising a bus controller and a memory controller, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 48 × 48 mm, and with decoupling capacitors, and bearing: — an identification marking consisting of or including the following combination of figures and letters: 390 Z 50 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8473 30 90	*01	Parts, for use in the manufacture of products falling within subheading 8471 60 40 (a)	0
ex 8473 30 90	*02	Assembly for a magnetic 36 track tape storage unit, comprising a read/write head of thin film technology and a tape drive unit	0
ex 8473 30 90	*85	Read/write assembly for hard disc storage units, comprising only one magnetic head of thin-film technology mounted on a carrier arm, capable of reading/writing to a density of 78 tracks or more per mm	0
ex 8501 10 99	*73	DC motor, for use in the manufacture of hard disc drives (a)	0
8504 90 11		Ferrite cores	0
ex 8505 11 00	*31	Ferrite magnet having a remanence of 455 mT (± 15 mT)	0
ex 8507 30 91	*20	Rectangular accumulator, with a length not exceeding 67,1 mm, a width not exceeding 18 mm and a thickness not exceeding 10,6 mm, for use in the manufacture of rechargeable batteries (a)	0
ex 8507 80 91	*10		
ex 8507 80 99	*10		
ex 8516 90 00	*31	Dual diode, consisting of a power rectifying diode connected with a transformer protector diode through a wire, for use in the manufacture of products falling within subheading 8516 50 00 (a)	0

CN code	TARIC	Description	Rate of autonomous duty %
ex 8517 90 82	*50	Assembly comprising light-emitting diodes (LEDs)	0
ex 8517 90 88	*20	Parts, for use in the manufacture of products falling within subheading 8517 21 00 (a)	0
ex 8518 29 90	*10	Loudspeaker having a power of 5 W and an impedance of 4 ohm, the dimensions of which do not exceed 23 × 50 mm, for use in the manufacture of portable phones (a)	0
ex 8522 90 91	*92	Electronic assembly for a laser read-head of a compact disc player, comprising: <ul style="list-style-type: none"> — a flexible printed circuit, — a photo-detector, in the form of a monolithic integrated circuit, contained in a housing, — not more than 2 connectors, — not more than 1 transistor, — not more than 3 variable and 4 fixed resistors, — not more than 5 capacitors, the whole mounted on a support	0
ex 8522 90 98	*31	Thin-film recording and reproducing device, having at least 9 parallel channels for digital signals and at least 2 channels for analogue signals, to which a non-magnetic ceramic substrate is fixed, the whole rounded at one side, for use in the manufacture of magnetic heads for digital sound recording and digital/analogue sound reproducing apparatus of the cassette-type (a)	0
ex 8522 90 98	*32	Sound reproducing assembly, consisting of a compact disc mechanism, comprising an optical reading system and 3 DC motors, for use in the manufacture of products falling within subheading 8527 21 70 (a)	0
ex 8522 90 98	*38	Read-head assembly, comprising a laser read-head, 2 motors, a flexible printed circuit, the whole mounted on a plastic support, for use in the manufacture of compact disc players (a)	0
ex 8523 12 00	*10	Magnetic tape, with a thickness not exceeding 16 µm and a width of 6,274 (±0,013 mm), on reels, not mounted in a cartridge	0
ex 8529 10 70	*50	Dielectric filter for centre frequencies of 902,5 and 947,5 MHz, with a bandwidth of at least 25 MHz, contained in a housing	0
ex 8529 10 70	*75	Bandpass filter, excluding surface acoustic wave filters, for a centre frequency of 485 or 1 212 MHz, with an insertion loss not exceeding 3 dB, contained in a housing bearing: <ul style="list-style-type: none"> — an identification marking consisting of or including one of the following combinations of figures and letters: 916571 919046 or — other identification markings relating to devices complying with the abovementioned description 	0
ex 8531 20 51	*10	Liquid crystal colour display (LCD) with an active matrix and 480 × 640 or 600 × 800 pixels, consisting of a layer of liquid crystals between two glass sheets or plates, comprising electronic components providing drive and/or control functions, for use in the manufacture of products falling within subheading 8471 30 00 (a)	0
ex 8531 20 51	*20	Liquid crystal colour display (LCD) with an active matrix and 768 × 1 024 or 900 × 1 152 pixels, consisting of a layer of liquid crystals between two glass sheets or plates, comprising electronic components providing drive and/or control functions	0

CN code	TARIC	Description	Rate of autonomous duty %
ex 8531 20 51	*30	Liquid crystal colour display (LCD) with an active matrix and 1 024 × 1 280 pixels, consisting of a layer of liquid crystals between two glass sheets or plates, mounted on a printed circuit comprising electronic components providing drive and/or control functions	0
ex 8531 20 59	*20	Liquid crystal monochrome display (LCD) with an active matrix and 900 × 1 152 pixels, consisting of a layer of liquid crystals between two glass sheets or plates, comprising electronic components providing drive and/or control functions	0
ex 8531 20 80	*10	Liquid crystal display (LCD) with a passive matrix, comprising electronic components providing drive and/or control functions	0
ex 8532 29 00	*31	Capacitor with 2 dielectric materials, one in ceramic, the other in epoxy resin, having an initial capacitance of 500 pF ($\pm 30\%$) and a dissipation factor not exceeding 2,5 %	0
ex 8532 90 00	*32	Anode or cathode, for use in the manufacture of aluminium electrolytic capacitors (a)	0
ex 8534 00 11	*93	Multiple printed circuit, with connectors, and in an aluminium casing	0
ex 8534 00 19	*92	Single-face printed circuits, each with not more than 268 conductive leads, on a plastic tape with sprocket holes on both edges and having a width of not more than 48 mm and a thickness of not more than 0,26 mm	0
ex 8534 00 19	*94	Printed circuit, consisting of 29 or 31 conductor elements fixed on a flexible plastic film, for use in the manufacture of magnetic heads for digital sound recording and digital/analogue sound reproducing apparatus of the cassette-type (a)	0
ex 8536 41 90	*92	Dual relay operating at a nominal voltage of 12 V, with a contact switching continuous voltage not exceeding 30 V and a contact switching current not exceeding 25 A, contained in a housing	0
ex 8536 41 90	*93	Relay having a coil resistance not exceeding 84 ohm, an initial contact resistance of 5 mV/A, a continuous current of 30 A or more and a surge current of 60 A or more, contained in a housing	0
ex 8536 50 11	*31	Switch of the printed circuit mount type, operating at a force of 4,9 N ($\pm 0,9$ N), contained in a housing	0
ex 8536 50 90	*94	Airbag sensor, capable of maintaining a switching current of 20 A after 3 make/break at a voltage of 26 V, with an insulation resistance of 100 Mohm or more at a continuous voltage of 500 V and a contact closed resistance not exceeding 150 mohm at a current of 2 A ($\pm 0,5$ A) for a period of 2 ms (± 1 ms), contained in a housing the exterior dimensions of which do not exceed 17 × 22 × 32 mm	0
ex 8536 90 85	*92	Metallic stamped frame with connections	0
ex 8540 11 13	*91	Colour cathode-ray tube with a slit mask, having a distance between stripes of the same colour of less than 0,42 mm and a diagonal measurement of the screen of 49 cm, for use in the manufacture of professional video monitors including security and medical monitor applications (a)	0
ex 8540 11 91	*31	Colour cathode-ray tube with a screen width/height ratio of 16/9 and a diagonal measurement of the screen of 39,8 cm ($\pm 0,3$ cm)	0

CN code	TARIC	Description	Rate of autonomous duty %
ex 8540 12 00	*81	Flat screen monochrome cathode-ray tube with a diagonal measurement of the screen of 100 mm or more but not exceeding 155 mm and an anode voltage of 5 kV or more but not exceeding 32 kV	0
ex 8540 91 00	*98	Frame of molybdenum chrome steel, for use in the manufacture of cathode-ray tubes (a)	0
ex 8541 10 91	*10	Silicon power rectifier diodes of planar technology, with a recovery time of less than 100 ns, a maximum recurring reverse voltage of 200 V, and average forward current of 2,5 A or more, contained in a housing	0
ex 8541 10 91	*20	Silicon power rectifier diode, with a reverse peak voltage not exceeding 1 500 V and an average output current of 5 A or more but not exceeding 8 A, contained in a housing bearing: — an identification marking consisting of or including the following combination of figures and letters: PG151S15 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8541 10 91	*40	Voltage rectifier diode, with a reverse peak voltage of 6, 8, 10, 12 or 14 kV, an average forward current of 5 mA and a reverse current of 2 μ A, contained in a housing	0
ex 8541 29 10	*10	Wafer, not yet cut into chips, consisting of field-effect transistors (FETs) of the P-channel type, having a drain-to-source breakdown-voltage of -30 V or more, operating with a continuous drain-current not exceeding 10 A, a drain-to-source resistance not exceeding 0,2 ohm, and with a dissipation rate not exceeding 60 W, for use in the manufacture of goods of subheading 8542 40 90 (a)	0
ex 8541 29 20	*75	Field-effect transistor (FET) of the P-channel type, having a drain-to-source breakdown-voltage of -250 V, operating with a continuous drain-current not exceeding -6 A, a drain-to-source resistance not exceeding 1 ohm, and with a dissipation rate not exceeding 30 W, contained in a housing bearing: — an identification marking consisting of or including the following combination of figures and letters: 2SJ307 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8541 29 20	*80	Field-effect transistor (FET) of the P-channel type, having a drain-to-source breakdown-voltage of -30 V or more, operating with a continuous drain-current not exceeding 10 A, a drain-to-source resistance not exceeding 0,2 ohm, and with a dissipation rate not exceeding 60 W, contained in a housing bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: RFD10P03L RFD10P03LSM RFP10P03L or — other identification markings relating to devices complying with the abovementioned description	0

CN code	TARIC	Description	Rate of autonomous duty %
ex 8541 29 30	*10	Insulated gate bipolar transistor (IGBT), with a collector-emitter current not exceeding 20 A, an emitter-collector breakdown-voltage of 320 V or more, and with a dissipation rate not exceeding 150 W, contained in a housing bearing: — an identification marking consisting of or including the following combination of figures and letters: 5401GM or — other identification markings relating to devices complying with the abovementioned description	0
ex 8541 29 80	*60	Transistor of the NPN type, having a collector-base breakdown voltage of 120 V or more, an emitter-base breakdown voltage of 3 V or more and a continuous collector current not exceeding 200 mA, contained in a housing bearing: — an identification marking consisting of or including the following combination of figures and letters: KSC 3953 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8541 30 90	*10	Diac, with a breakover voltage of 77 V or more but not exceeding 270 V and a state current not exceeding 1 A, contained in a housing	0
ex 8541 30 90	*20	Diac, with a breakover voltage of 65 V or more and a capacitance of 200 pF, contained in a housing	0
ex 8541 40 19	*40	Light-emitting diode (LED), contained in a housing of the SMD (Surface mounted device) type	0
ex 8541 60 00	*94	Piezo-electric crystal, excluding surface acoustic wave filters, oscillating at centre frequency of 450 kHz or more but not exceeding 1 843 MHz	0
ex 8541 90 00	*10	Housing or ceramic substrate, with connections	0
ex 8542 90 00	*20		
ex 8542 13 01	*09	Wafer, not yet cut into chips, consisting only of microcontrollers or microcomputers of C-MOS technology, with a processing capacity of 8 bits, comprising a data memory with a storage capacity of 4 Kbits or more but not exceeding 8 Kbits, a programme memory with a storage capacity of 64 Kbits or more but not exceeding 480 Kbits and either a buffer memory or a display random access memory (RAM) with a storage capacity not exceeding 512 bits, for use in the manufacture of goods of subheading 8542 13 63 contained in a housing bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: 78011 78014 78044 78053 78056 78063 78012 78042 78045 78054 78058 78064 78013 78043 78052 78055 78062 or — other identification markings relating to devices complying with the abovementioned description (a)	0
ex 8542 13 01	*10	Wafer, not yet cut into chips, consisting only of microcontrollers or microcomputers with a processing capacity of 4 bits, for use in the manufacture of goods of subheading 8542 13 61 contained in a housing bearing:	

CN code	TARIC	Description	Rate of autonomous duty %																									
ex 8542 13 01 (cont'd)		<p>— an identification marking consisting of or including one of the following combinations of figures or of figures and letters:</p> <table style="width: 100%; border: none;"> <tr> <td style="width: 20%;">7507</td> <td style="width: 20%;">75108</td> <td style="width: 20%;">75304</td> <td style="width: 20%;">75336</td> <td style="width: 20%;">75P008</td> </tr> <tr> <td>7508</td> <td>75112</td> <td>75306</td> <td>75352</td> <td>75P116</td> </tr> <tr> <td>75004</td> <td>75116</td> <td>75308</td> <td>75512</td> <td>75P216</td> </tr> <tr> <td>75006</td> <td>75216</td> <td>75312</td> <td>75516</td> <td>75P308</td> </tr> <tr> <td>75028</td> <td>75217</td> <td>75316</td> <td>75617</td> <td>75P316</td> </tr> </table> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description (a)</p>	7507	75108	75304	75336	75P008	7508	75112	75306	75352	75P116	75004	75116	75308	75512	75P216	75006	75216	75312	75516	75P308	75028	75217	75316	75617	75P316	0
7507	75108	75304	75336	75P008																								
7508	75112	75306	75352	75P116																								
75004	75116	75308	75512	75P216																								
75006	75216	75312	75516	75P308																								
75028	75217	75316	75617	75P316																								
ex 8542 13 05	*12	<p>Data or image compression/decompression circuit of C-MOS technology, in the form of a monolithic integrated circuit not contained in a housing (chip), for use in the manufacture of goods of subheading 8542 13 72 or 8542 13 99 contained in a housing bearing:</p> <p>— an identification marking consisting of or including one of the following combinations of figures or of figures and letters:</p> <table style="width: 100%; border: none;"> <tr> <td style="width: 33%;">3H6414</td> <td style="width: 33%;">MPEGCD1</td> <td style="width: 33%;">MPEGSD1</td> </tr> </table> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description (a)</p>	3H6414	MPEGCD1	MPEGSD1	0																						
3H6414	MPEGCD1	MPEGSD1																										
ex 8542 13 05	*13	<p>Graphic control circuit of C-MOS technology, in the form of a monolithic integrated circuit not contained in a housing (chip), for use in the manufacture of goods of subheading 8542 13 70 contained in a housing bearing:</p> <p>— an identification marking consisting of or including one of the following combinations of figures or of figures and letters:</p> <table style="width: 100%; border: none;"> <tr> <td style="width: 33%;">51G8286</td> <td style="width: 33%;">88G2562</td> <td style="width: 33%;">88G2734</td> </tr> </table> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description (a)</p>	51G8286	88G2562	88G2734	0																						
51G8286	88G2562	88G2734																										
ex 8542 13 11	*11	<p>Random-access memory, with separate in- and outputs and serial shift registers (so-called field memories), of C-MOS technology, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including one of the following combinations of figures and letters:</p> <table style="width: 100%; border: none;"> <tr> <td style="width: 25%;">MSM 514222B</td> <td style="width: 25%;">MSM 548333</td> <td style="width: 25%;">TMS 4C1081</td> <td style="width: 25%;">TMS 4C2970</td> </tr> <tr> <td>MSM 548332</td> <td>TC 521 000</td> <td>TMS 4C2070</td> <td>TMS 53805</td> </tr> </table> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	MSM 514222B	MSM 548333	TMS 4C1081	TMS 4C2970	MSM 548332	TC 521 000	TMS 4C2070	TMS 53805	0																	
MSM 514222B	MSM 548333		TMS 4C1081	TMS 4C2970																								
MSM 548332	TC 521 000		TMS 4C2070	TMS 53805																								
ex 8542 13 13	*02																											
ex 8542 13 15	*01																											
ex 8542 13 17	*02																											
ex 8542 13 22	*16	<p>Dual port static random-access memory of C-MOS technology (C-MOS dual port S-RAM), providing sequential access on one port and random access on the other one, with a storage capacity of 4 K × 16 bits or 8 K × 16 bits, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including one of the following combinations of figures and letters:</p> <table style="width: 100%; border: none;"> <tr> <td style="width: 50%;">IDT 70824</td> <td style="width: 50%;">IDT 70825</td> </tr> </table> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	IDT 70824	IDT 70825	0																							
IDT 70824	IDT 70825																											

CN code	TARIC	Description	Rate of autonomous duty %
ex 8542 13 22	*17	Asynchronous dual port static random-access memory of C-MOS technology (C-MOS dual port S-RAM), with a storage capacity of 16 K × 8 bits or 32 K × 8 bits, in the form of a monolithic integrated circuit contained in a housing bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: IDT 7006 IDT 7007 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 13 22	*18	Static random-access memory of C-MOS technology (C-MOS S-RAM), operating with a supply voltage of 3,3 V (±0,3 V), with a storage capacity of 256 Kbits and an access time not exceeding 15 ns, in the form of a monolithic integrated circuit contained in a housing bearing: — an identification marking consisting of or including the following combination of figures and letters: KM 68V257-15 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 13 22	*19	Static asynchronous random-access memory of C-MOS technology (C-MOS asynchronous S-RAM), with a storage capacity of 16 K × 16 bits, excluding static random-access cache memory (S-Cache-RAM), in the form of a monolithic integrated circuit contained in a housing bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: MCM 62995-17 MCM 62995-20 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 13 25 ex 8542 19 25	*04 *06	Static random-access memory (S-RAM), with a storage capacity of 1 Mbit, in the form of a monolithic integrated circuit contained in a housing bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: CXX581 000 CY7C108 HM 624257 MCM 6729 CXX581020 CY7C109 HM 628128 MT 5C1008 CY7C101 EDI 88128 KM 681 000 TC 551001 CY7C102 GM 76C8128 M5M 51004 TC 55B4256 CY7C106 HM 621100A M5M 51008 TC 55B4257 CY7C107 HM 624256 MCM 6228 TC 55B8128 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 13 25	*05	Static random-access memory of C-MOS technology (C-MOS S-RAM), with a storage capacity of 288 Kbits, in the form of a monolithic integrated circuit contained in a housing bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: CY7C1388 MCM 62486B or — other identification markings relating to devices complying with the abovementioned description	0

CN code	TARIC	Description	Rate of autonomous duty %
ex 8542 13 27	*03	<p>Static random-access memory of C-MOS technology (C-MOS S-RAM), with a storage capacity of 32 K × 36 bits, 64 K × 18 bits or 128 K × 9 bits, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including one of the following combinations of figures and letters: CXX 77910 CY7C1031 CY7C1032 MT 58LC32 MT 58LC64 or — other identification markings relating to devices complying with the abovementioned description 	0
ex 8542 13 27	*04	<p>Static random-access memory of C-MOS technology (C-MOS S-RAM), with a storage capacity of more than 1 Mbit, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including one of the following combinations of figures and letters: TC 554002 MT5C1M4B2 MT5LC1M4D4 MT58LC128K MT5C256K16B2 MT5LC256K16D4 MT58LC64K MT5C512K8B2 MT5LC512K8D4 or — other identification markings relating to devices complying with the abovementioned description 	0
ex 8542 13 32	*11	<p>UV erasable or non-erasable, programmable, read only memory (EPROM or PROM) with a storage capacity of 1 Mbit and an access time not exceeding 45 ns, in the form of a monolithic integrated circuit contained in a housing, with or without a quartz window on the upper surface, bearing :</p> <ul style="list-style-type: none"> — an identification marking consisting of or including one of the following combinations of figures and letters: CY27H010-25 CY27H010-35 CY7B201 CY7B211 CY27H010-30 CY27H010-45 CY7B210 or — other identification markings relating to devices complying with the abovementioned description 	0
ex 8542 13 53	*08		
ex 8542 19 31	*08		
ex 8542 19 49	*07		
ex 8542 13 35	*01	<p>UV erasable, programmable, read only memory (EPROM) of C-MOS technology (C-MOS EPROM), capable of operating with an unregulated battery supply voltage of 2,7 V or more but not exceeding 3,6 V, with a storage capacity of 2 Mbits or more but not exceeding 4 Mbits and an access time not exceeding 120 ns, in the form of a monolithic integrated circuit contained in a housing, with a quartz window on the upper surface, and bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including one of the following combinations of figures and letters: 27BV020 27BV040 or — other identification markings relating to devices complying with the abovementioned description 	0
ex 8542 13 41	*03	<p>Flash electrically erasable, programmable, read only memory (Flash-E²PROM) with a storage capacity of 1 Mbit, excluding memories only bulk-erasable and erasable and programmable at a voltage of 12 V and readable at a voltage of 5 V, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including one of the following combinations of figures and letters: 29 F 010 29 F 100 48 F 010 or — other identification markings relating to devices complying with the abovementioned description 	0

CN code	TARIC	Description	Rate of autonomous duty %
ex 8542 13 43	*01	Flash electrically erasable, programmable, read only memory (Flash-E ² PROM) with a storage capacity of 2 Mbits, in the form of a monolithic integrated circuit contained in a housing bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: 28 F 002 28 F 020 28 F 200 29 F 200 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 13 43	*02	Flash electrically erasable, programmable, read only memory (Flash-E ² PROM) with a storage capacity of 4 Mbits, in the form of a monolithic integrated circuit contained in a housing bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: 28 F 004 28 F 400 29 F 040 28 F 040 29 C 040 TC 584 000 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 13 45	*01	Flash electrically erasable, programmable, read only memory (Flash-E ² PROM) with a storage capacity of 8 Mbits, in the form of a monolithic integrated circuit contained in a housing bearing: — an identification marking consisting of or including the following combination of figures and letters: 28 F 008 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 13 45	*02	Flash electrically erasable, programmable, read only memory (Flash-E ² PROM) with a storage capacity of 16 Mbits, in the form of a monolithic integrated circuit contained in a housing bearing: — an identification marking consisting of or including the following combination of figures and letters: 28 F 016SA or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 13 49	*02	Electrically erasable, programmable, read only memory (E ² PROM) of C-MOS technology (C-MOS E ² PROM), with a storage capacity of 1 Kbit or more but not exceeding 16 Kbits and having not more than 10 000 logic gates, in the form of a monolithic integrated circuit contained in a housing bearing: — an identification marking consisting of or including the following combination of figures and letters: AT 88SC or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 13 49	*03	Electrically erasable, programmable, read only memory (E ² PROM), with a storage capacity of 256 Kbits or more, excluding flash electrically erasable, programmable, read only memory (Flash-E ² PROM), in the form of a monolithic integrated circuit contained in a housing bearing:	

CN code	TARIC	Description	Rate of autonomous duty %
ex 8542 13 49 (cont'd)		<p>— an identification marking consisting of or including one of the following combinations of figures or of figures and letters: 2928256 28 C 512 AT 28C1 024 28 C 256 48 C 256 E/M 28C010</p> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8542 13 49	*04	<p>Electrically erasable, programmable, read only memory (E²PROM), with a storage capacity of 8 K × 8 bits, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including one of the following combinations of figures and letters: 28 C 64 28 H 64 28 HC 64 28 LV 64 28 PC 64</p> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8542 13 51	*11	<p>FIFO (first in, first out) read/write memory of C-MOS technology, capable of asynchronous reading and writing, with a storage capacity of 256 × 9 bits, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including the following combination of figures and letters: CY7C419</p> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8542 13 51	*12	<p>FIFO (first in, first out) read/write memory of C-MOS technology, capable of asynchronous reading and writing, with a storage capacity of 512 × 9 bits, 1 K × 9 bits, 2 K × 9 bits or 4 K × 9 bits and an access time not exceeding 15 ns, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including one of the following combinations of figures and letters: Am 7204A-15 CY7C425 CY7C433 CY7C421 CY7C429</p> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8542 13 63	*14	<p>Microcontroller or microcomputer of C-MOS technology, with a processing capacity of 8 bits, comprising 5 data memories with a total storage capacity not exceeding 160 512 bits, a programme memory with a storage capacity of 21 Kbit, a keyboard controller, a video synchronization controller and 1 or 2 universal asynchronous receiver/transmitters (UARTs), in the form of a monolithic integrated circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including the following combination of figures and letters: VY 27085</p> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8542 13 63	*15	<p>Microcontroller or microcomputer of C-MOS technology, with a processing capacity of 8 bits, comprising a data memory, a programme memory and a display control or drive circuit, in the form of a monolithic integrated circuit contained in a housing bearing:</p>	

CN code	TARIC	Description	Rate of autonomous duty %																																												
ex 8542 13 63 (cont'd)		<p>— an identification marking consisting of or including one of the following combinations of figures and letters:</p> <table border="0" data-bbox="507 409 1281 589"> <tr> <td>83C751</td> <td>CXP 85228</td> <td>M 3817</td> <td>PD 75316</td> </tr> <tr> <td>83C752</td> <td>CXP 85232</td> <td>M 38203E4</td> <td>TMP 87CC20F</td> </tr> <tr> <td>87C750</td> <td>CXP 85340</td> <td>M 38203M2</td> <td>TMP 87CH20F</td> </tr> <tr> <td>87C751</td> <td>CXP 85452</td> <td>M 38207E8</td> <td>TMP 87CK70AF</td> </tr> <tr> <td>87C752</td> <td>CXP 85460</td> <td>M 38207M8</td> <td></td> </tr> <tr> <td>CXP 82316</td> <td>M 37500M5</td> <td>M 3825</td> <td></td> </tr> <tr> <td>CXP 82320</td> <td>M 37500M8</td> <td>MB 89098</td> <td></td> </tr> </table> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	83C751	CXP 85228	M 3817	PD 75316	83C752	CXP 85232	M 38203E4	TMP 87CC20F	87C750	CXP 85340	M 38203M2	TMP 87CH20F	87C751	CXP 85452	M 38207E8	TMP 87CK70AF	87C752	CXP 85460	M 38207M8		CXP 82316	M 37500M5	M 3825		CXP 82320	M 37500M8	MB 89098		0																
83C751	CXP 85228	M 3817	PD 75316																																												
83C752	CXP 85232	M 38203E4	TMP 87CC20F																																												
87C750	CXP 85340	M 38203M2	TMP 87CH20F																																												
87C751	CXP 85452	M 38207E8	TMP 87CK70AF																																												
87C752	CXP 85460	M 38207M8																																													
CXP 82316	M 37500M5	M 3825																																													
CXP 82320	M 37500M8	MB 89098																																													
ex 8542 13 63	*16	<p>Microcontroller or microcomputer of C-MOS technology, with a processing capacity of 8 bits, comprising a data memory with a storage capacity not exceeding 9 Kbits, a programme memory with a storage capacity not exceeding 256 Kbits, a serial synchronous communication interface consisting of an 8-bit serial shift register with serial data input, serial data output and serial shift clock, and in the form of a monolithic integrated circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including one of the following combinations of figures and letters:</p> <table border="0" data-bbox="507 954 1246 1032"> <tr> <td>COP 820</td> <td>COP 881C</td> <td>COP 888CG</td> <td>MB 89152</td> </tr> <tr> <td>COP 840</td> <td>COP 884CF</td> <td>COP 888EG</td> <td>MB 89P657A</td> </tr> <tr> <td>COP 880C</td> <td>COP 888CF</td> <td>MB 89145</td> <td>MB 89W147</td> </tr> </table> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	COP 820	COP 881C	COP 888CG	MB 89152	COP 840	COP 884CF	COP 888EG	MB 89P657A	COP 880C	COP 888CF	MB 89145	MB 89W147	0																																
COP 820	COP 881C	COP 888CG	MB 89152																																												
COP 840	COP 884CF	COP 888EG	MB 89P657A																																												
COP 880C	COP 888CF	MB 89145	MB 89W147																																												
ex 8542 13 63	*17	<p>Microcontroller or microcomputer of C-MOS-technology, with a processing capacity of 8 bits, comprising a read only memory, non-programmable (ROM) with a storage capacity of 16,5 Kbits and a random-access memory (RAM) with a storage capacity of 1 Kbit, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including the following combination of figures and letters:</p> <p>76032KC</p> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0																																												
ex 8542 13 63	*18	<p>Microcontroller or microcomputer of C-MOS or N-MOS (including H-MOS) technology, with a processing capacity of 8 bits, comprising one or more data memories with a total storage capacity not exceeding 8 Kbits and a programme memory with a storage capacity of 32 Kbits or more but not exceeding 256 Kbits, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including one of the following combinations of figures and letters:</p> <table border="0" data-bbox="507 1709 1257 1989"> <tr> <td>5A41</td> <td>87C055</td> <td>CXP 80524</td> <td>PCA 84C640</td> </tr> <tr> <td>5B11</td> <td>87C504</td> <td>M 37450E8</td> <td>PCA 84C840</td> </tr> <tr> <td>76C75T</td> <td>87C51</td> <td>M 37450M8</td> <td>PCA 84C841</td> </tr> <tr> <td>7742</td> <td>87C52</td> <td>M 38063M6</td> <td>PD 78014</td> </tr> <tr> <td>80C51</td> <td>87C54</td> <td>M 38063E8</td> <td>PD 78064</td> </tr> <tr> <td>80C52</td> <td>87C58</td> <td>M 38067M8</td> <td>PD 78134</td> </tr> <tr> <td>83C055</td> <td>87L51</td> <td>M50958</td> <td>TMP 87PM70</td> </tr> <tr> <td>83C504</td> <td>C 1900</td> <td>M50959</td> <td>TMP 91P642</td> </tr> <tr> <td>83C51</td> <td>C 2900</td> <td>MC68HC05i8</td> <td></td> </tr> <tr> <td>83L51</td> <td>C 3900</td> <td>MC68HC705i8</td> <td></td> </tr> <tr> <td>8751</td> <td>CXD 80724</td> <td>MN 1871215</td> <td></td> </tr> </table> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	5A41	87C055	CXP 80524	PCA 84C640	5B11	87C504	M 37450E8	PCA 84C840	76C75T	87C51	M 37450M8	PCA 84C841	7742	87C52	M 38063M6	PD 78014	80C51	87C54	M 38063E8	PD 78064	80C52	87C58	M 38067M8	PD 78134	83C055	87L51	M50958	TMP 87PM70	83C504	C 1900	M50959	TMP 91P642	83C51	C 2900	MC68HC05i8		83L51	C 3900	MC68HC705i8		8751	CXD 80724	MN 1871215		0
5A41	87C055	CXP 80524	PCA 84C640																																												
5B11	87C504	M 37450E8	PCA 84C840																																												
76C75T	87C51	M 37450M8	PCA 84C841																																												
7742	87C52	M 38063M6	PD 78014																																												
80C51	87C54	M 38063E8	PD 78064																																												
80C52	87C58	M 38067M8	PD 78134																																												
83C055	87L51	M50958	TMP 87PM70																																												
83C504	C 1900	M50959	TMP 91P642																																												
83C51	C 2900	MC68HC05i8																																													
83L51	C 3900	MC68HC705i8																																													
8751	CXD 80724	MN 1871215																																													

CN code	TARIC	Description	Rate of autonomous duty %
ex 8542 13 63	*19	<p>Microcontroller or microcomputer of C-MOS technology, with a processing capacity of 8 bits, comprising a random-access memory (RAM) with a storage capacity not exceeding 2 Kbits, a programmable, non-erasable, read only memory (PROM) or a UV erasable, programmable, read only memory (EPROM) with a storage capacity of 64 Kbits or a flash electrically erasable, programmable, read only memory (Flash-E²PROM) or a read only memory, non-programmable (ROM) with a storage capacity of 32, 64 or 480 Kbits, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including one of the following combinations of figures and letters: 77 C 82 AT 89C51 M 50747 PD 78058 80 C 152 M 50743 MC 68HC11A8 or — other identification markings relating to devices complying with the abovementioned description 	0
ex 8542 13 63	*20	<p>Microcontroller or microcomputer of C-MOS technology, with a processing capacity of 8 bits, comprising a read only memory, non-programmable (ROM) with a storage capacity of 256, 320 or 384 Kbits and a random-access memory (RAM) with a storage capacity of 10 496, 11 008, 20 736 or 21 760 bits, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including one of the following combinations of figures and letters: CXP 87132 CXP 87240 MN 1883220 CXP 87140 CXP 87248 MN 1884820 or — other identification markings relating to devices complying with the abovementioned description 	0
ex 8542 13 63	*21	<p>Microcontroller or microcomputer of C-MOS technology, with a processing capacity of 8 bits, comprising a random-access memory (RAM) with a storage capacity not exceeding 16 Kbits, a read only memory, non-programmable (ROM) or a programmable, non-erasable, read only memory (PROM) or an UV erasable, programmable, read only memory (EPROM), with a storage capacity not exceeding 384 Kbits, an electrically erasable programmable, read only memory (E²PROM) with a storage capacity not exceeding 6 Kbits and an 8-channel analogue-to-digital converter, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including one of the following combinations of figures and letters: MC 68HC11 MC 68HC711 or — other identification markings relating to devices complying with the abovementioned description 	0
ex 8542 13 65	*01	<p>Microcontroller or microcomputer of C-MOS technology, with a processing capacity of 16 bits, capable of modulator/demodulator (modem) signal processing, comprising a data memory with a storage capacity 4 Kbits and a programme memory with a storage capacity of 256 Kbits, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including one of the following combinations of figures and letters: SC 11066 SC 11077 SC 11088 or — other identification markings relating to devices complying with the abovementioned description 	0

CN code	TARIC	Description	Rate of autonomous duty %
ex 8542 13 65	*02	<p>Microcontroller or microcomputer of C-MOS technology, with a processing capacity of 16 bits, comprising a data memory with a storage capacity of 32 Kbits, one or more programme memories with a total storage capacity not exceeding 240 Kbits and a 14-bit external bus, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including one of the following combinations of figures and letters: ADSP 2171 ADSP 2178 or — other identification markings relating to devices complying with the abovementioned description 	0
ex 8542 13 65	*03	<p>Microcontroller or microcomputer of C-MOS technology, with a processing capacity of 16 bits, comprising an arithmetic-logic shifter, a data memory with a storage capacity of 8 Kbits and a programme memory with a storage capacity of 96 Kbits, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including the following combination of figures and letters: ADSP 2164 or — other identification markings relating to devices complying with the abovementioned description 	0
ex 8542 13 65	*04	<p>Microcontroller or microcomputer of C-MOS technology, with a processing capacity of 16 bits, comprising a random-access memory (RAM) having the function of data and programme memory and with a storage capacity of 8 Kbits, an audio interface, a video interface and a descrambler circuit, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including the following combination of figures and letters: CL 9110 or — other identification markings relating to devices complying with the abovementioned description 	0
ex 8542 13 65	*05	<p>Microcontroller or microcomputer of N-MOS technology (including H-MOS), with a processing capacity of 16 bits, comprising at least one read only memory, non-programmable (ROM) with a storage capacity of 510×13 bits or an UV erasable, programmable, read only memory (EPROM) with a storage capacity of 512×13 bits, a random-access memory (RAM) with a storage capacity of 2 Kbits, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including one of the following combinations of figures and letters: PD 7720 PD 77 P 20 or — other identification markings relating to devices complying with the abovementioned description 	0
ex 8542 13 65	*06	<p>Microcontroller or microcomputer of C-MOS technology, with a processing capacity of 16 bits, comprising a random-access memory (RAM) with a storage capacity of 48 Kbits and having the function of programme memory, a random-access memory (RAM) with a storage capacity of 32 Kbits, a digital-to-analogue converter and an analogue-to-digital converter, in the form of a monolithic integrated circuit contained in a housing bearing:</p>	

CN code	TARIC	Description	Rate of autonomous duty %
ex 8542 13 65 (cont'd)		<ul style="list-style-type: none"> — an identification marking consisting of or including one of the following combinations of figures and letters: ADSP 21msp58 ADSP 21msp59 or — other identification markings relating to devices complying with the abovementioned description 	0
ex 8542 13 65	*07	<p>Microcontroller or microcomputer of C-MOS technology, with a processing capacity of 16 bits and a 16-bit address-bus and an 8-bit data-bus, comprising a random-access memory (RAM) with a storage capacity of 4 Kbits or more, a read only memory, non-programmable (ROM) or a programmable non-erasable read only memory (PROM) or a UV-erasable, programmable, read only memory (EPROM) with a storage capacity of 128 Kbits or more, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including one of the following combinations of figures and letters: MB 89715 MB 89P715 MB 89W715 or — other identification markings relating to devices complying with the abovementioned description 	0
ex 8542 13 65	*08	<p>Microcontroller or microcomputer of C-MOS technology, with a processing capacity of 16 bits, comprising sixteen 8-bit or eight 16-bit registers, a read only memory, non-programmable (ROM) or a programmable, read only memory (PROM), with a storage capacity of 128 Kbits, a random-access memory (RAM) with a storage capacity of 4 Kbits, 3 timers, a serial communications interface, an 8-channel analogue-to-digital converter and 9 input/output ports, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including the following combination of figures and letters: HD 6473308CP or — other identification markings relating to devices complying with the abovementioned description 	0
ex 8542 13 65	*09	<p>Microcontroller or microcomputer of C-MOS technology, with a processing capacity of 16 bits, comprising an 8-bit or 16-bit external data-bus, a random-access memory (RAM) with a storage capacity of 16 Kbits and having the function of programme memory, a random-access memory (RAM) with a storage capacity of 16 Kbits, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including the following combination of figures and letters: DSP 56116 or — other identification markings relating to devices complying with the abovementioned description 	0
ex 8542 13 65	*10	<p>Microcontroller or microcomputer of C-MOS technology, with a processing capacity of 16 bits, for controlling dataflows between a twisted-pair-cable local area network (LAN) and a central processing unit (CPU), comprising a read only memory, non-programmable (ROM) with a storage capacity not exceeding 32 Kbits, a random-access memory (RAM) with a storage capacity not exceeding 128 Kbits, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including the following combination of figures and letters: SMC 83C825 	

CN code	TARIC	Description	Rate of autonomous duty %
ex 8542 13 65 (cont'd)		<p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8542 13 65	*11	<p>Microcontroller or microcomputer of C-MOS technology, with a processing capacity of 16 bits, providing local network bus communication control, comprising a random-access memory (RAM) with a storage capacity of 2 Kbits, 2 read only memories, non-programmable (ROMs) or 2 programmable, non-erasable, read only memories (PROMs) or 2 UV erasable, programmable, read only memories (EPROMs) with a total storage capacity of 56 or 128 Kbits and a serial-port interface circuit, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including one of the following combinations of figures and letters: TMS 8370C03 TMS 8370C73</p> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8542 13 65	*12	<p>Microcontroller or microcomputer of C-MOS technology, with a processing capacity of 16 bits, having the function of charge control of nickel-cadmium batteries, comprising a read only memory, non-programmable (ROM) with a storage capacity of 42 000 bits, a read only memory, non-programmable (ROM) with a storage capacity of 1 Kbit, a random-access memory (RAM) with a storage capacity of 1 Kbit and a 10-bit analogue-to-digital converter, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including the following combination of figures and letters: ICS 1 700</p> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8542 13 65	*13	<p>Microcontroller or microcomputer of C-MOS technology, with a processing capacity of 16 bits, comprising of a read only memory, non-programmable (ROM) with a storage capacity of 64 Kbits, a random-access memory (RAM) with a storage capacity of 32 Kbits and a static random-access cache memory (S-Cache-RAM) with a storage capacity of 15 × 16 bits, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including the following combination of figures and letters: DSP16A</p> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8542 13 65	*14	<p>Microcontroller or microcomputer of C-MOS technology, with a processing capacity of 16 bits, comprising a data memory with a storage capacity of 2 Kbits, a programme memory with a storage capacity of 32 Kbits or more but not exceeding 128 Kbits and an 8-channel analogue-to-digital converter, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including one of the following combinations of figures and letters: 78C11 78C12 78C12AG 78C14 78CP14G</p> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0

CN code	TARIC	Description	Rate of autonomous duty %									
ex 8542 13 65	*15	<p>Microcontroller or microcomputer with a processing capacity of 16 bits, comprising a data memory with a storage capacity not exceeding 20 Kbits, a programme memory with a storage capacity not exceeding 992 Kbits and an analogue-to-digital converter with sample/hold, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including one of the following combinations of figures or figures and letters: <table data-bbox="446 537 989 616"> <tr> <td>8396</td> <td>83C196</td> <td>H8/532</td> </tr> <tr> <td>8397</td> <td>83C198</td> <td>HD 6435368</td> </tr> <tr> <td>8796</td> <td>87C196</td> <td>HD 6475368</td> </tr> </table> or — other identification markings relating to devices complying with the abovementioned description 	8396	83C196	H8/532	8397	83C198	HD 6435368	8796	87C196	HD 6475368	0
8396	83C196	H8/532										
8397	83C198	HD 6435368										
8796	87C196	HD 6475368										
ex 8542 13 65	*16	<p>Microcontroller or microcomputer of C-MOS technology, with a processing capacity of 16 bits, comprising a read only memory, non-programmable (ROM) or a programmable, non-erasable, read only memory (PROM) or a UV erasable, programmable, read only memory (EPROM) with a storage capacity of 128, 192, 256, 384 or 480 Kbits, a random-access memory (RAM) with a storage capacity of 4, 8 or 16 Kbits and an 8-bit analogue-to-digital converter, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including one of the following combinations of figures and letters: <table data-bbox="446 1108 1013 1187"> <tr> <td>M 37702 E2</td> <td>M 37702 M2</td> <td>M 37702 M4</td> </tr> <tr> <td>M 37702 E4</td> <td>M 37702 M8</td> <td>M 37702 M6L</td> </tr> <tr> <td>M 37702 E8</td> <td>M 37702 M3B</td> <td>M 37702 MDB</td> </tr> </table> or — other identification markings relating to devices complying with the abovementioned description 	M 37702 E2	M 37702 M2	M 37702 M4	M 37702 E4	M 37702 M8	M 37702 M6L	M 37702 E8	M 37702 M3B	M 37702 MDB	0
M 37702 E2	M 37702 M2	M 37702 M4										
M 37702 E4	M 37702 M8	M 37702 M6L										
M 37702 E8	M 37702 M3B	M 37702 MDB										
ex 8542 13 65	*17	<p>Microcontroller or microcomputer of C-MOS technology, with a processing capacity of 16 bits, comprising a multiplier/accumulator (MAC), an arithmetic-logic shifter, a microprocessor interface port, a read only memory (ROM) with a storage capacity of 48 Kbits, a static random-access memory (S-RAM) with a storage capacity of 16 Kbits, an analogue-to-digital converter, a digital-to-analogue converter and a programmable timer, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including the following combination of figures and letters: <p>21msp52BS-52</p> or — other identification markings relating to devices complying with the abovementioned description 	0									
ex 8542 13 65	*18	<p>Microcontroller or microcomputer of C-MOS technology, with a processing capacity of 16 bits, comprising a multiplier/accumulator (MAC), an arithmetic-logic shifter, a data memory with a storage capacity not exceeding 16 Kbits, a programme memory with a storage capacity not exceeding 48 Kbits and a programmable timer, in the form of a monolithic integrated circuit contained in a housing bearing:</p>										

CN code	TARIC	Description	Rate of autonomous duty %
ex 8542 13 65 (cont'd)		<p>— an identification marking consisting of or including one of the following combinations of figures and letters: ADSP 2101 ADSP 2103 ADSP 2111 ADSP 2102BS-50 ADSP 2105 ADSP 2115</p> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8542 13 65	*20	<p>Microcontroller or microcomputer of C-MOS technology, with a processing capacity of 16 bits, comprising a programmable, read only memory (PROM) with a storage capacity of 48 Kbits and a random-access memory (RAM) with a storage capacity of 4 Kbits, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including the following combination of figures and letters: PD 77P25</p> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8542 13 67	*10	<p>Microcontroller or microcomputer of C-MOS technology, with a processing capacity of 28 bits, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including the following combination of figures and letters: VY 27015</p> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8542 13 70	*36	<p>Interface and control circuit of C-MOS technology, comprising a digital-to-analogue and analogue-to-digital converter, a digital signal modulator, a serial bus, a 16-bit interface circuit and an ¼-bit counter, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including the following combination of figures and letters: CSP 1088</p> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8542 13 70	*37	<p>Data detection and phase correction circuit of C-MOS technology, comprising a clock frequency correction circuit, status and control registers and a microprocessor interface, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including the following combination of figures: 110014903</p> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8542 13 70	*38	<p>Data compression circuit of C-MOS technology, in the form of a monolithic integrated circuit contained in a housing bearing:</p>	

CN code	TARIC	Description	Rate of autonomous duty %																																																
ex 8542 13 70 (cont'd)		<ul style="list-style-type: none"> — an identification marking consisting of or including the following combination of figures and letters: 110017103 or — other identification markings relating to devices complying with the abovementioned description 	0																																																
ex 8542 13 70	*39	<p>16-bit audio signal control circuit of C-MOS technology, comprising a bus interface, a sound generator, an universal asynchronous receiver/transmitter circuit (UART) and a microprocessor interface, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including the following combination of figures and letters: OTI 605 or — other identification markings relating to devices complying with the abovementioned description 	0																																																
ex 8542 13 70	*40	<p>Read sequencer and error detection circuit of C-MOS technology, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including the following combination of figures and letters: 110016404 or — other identification markings relating to devices complying with the abovementioned description 	0																																																
ex 8542 13 70	*41	<p>Bus controller of C-MOS technology, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including one of the following combinations of figures or figures and letters: <table border="0" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 33%;">2782376</td> <td style="width: 33%;">82 C 101</td> <td style="width: 33%;">82 C 591</td> <td style="width: 33%;">L1A 4601</td> </tr> <tr> <td>2782654</td> <td>82 C 103</td> <td>82 C 597</td> <td>MSM 6307</td> </tr> <tr> <td>69G1705</td> <td>82 C 211</td> <td>82 C 599</td> <td>R 4220</td> </tr> <tr> <td>82303</td> <td>82 C 288</td> <td>82 C 801B</td> <td>R 4230</td> </tr> <tr> <td>82304</td> <td>82 C 301</td> <td>82 C 802G</td> <td>TACT 83443</td> </tr> <tr> <td>82306</td> <td>82 C 320</td> <td>82 C 822</td> <td>VAC 068</td> </tr> <tr> <td>82308</td> <td>82 C 362</td> <td>82 C 88</td> <td>VIC 068</td> </tr> <tr> <td>82309</td> <td>82 C 461</td> <td>CA 91C014</td> <td>VIC 64</td> </tr> <tr> <td>82355</td> <td>82 C 463</td> <td>ET 6 000</td> <td>VL 82 C 331</td> </tr> <tr> <td>82358</td> <td>82 C 465</td> <td>GC 181</td> <td>VY 86 C 410</td> </tr> <tr> <td>82374EB</td> <td>82 C 493</td> <td>HT 216</td> <td></td> </tr> <tr> <td>82434LX</td> <td>82 C 496</td> <td>HT 321</td> <td></td> </tr> </table> or — other identification markings relating to devices complying with the abovementioned description 	2782376	82 C 101	82 C 591	L1A 4601	2782654	82 C 103	82 C 597	MSM 6307	69G1705	82 C 211	82 C 599	R 4220	82303	82 C 288	82 C 801B	R 4230	82304	82 C 301	82 C 802G	TACT 83443	82306	82 C 320	82 C 822	VAC 068	82308	82 C 362	82 C 88	VIC 068	82309	82 C 461	CA 91C014	VIC 64	82355	82 C 463	ET 6 000	VL 82 C 331	82358	82 C 465	GC 181	VY 86 C 410	82374EB	82 C 493	HT 216		82434LX	82 C 496	HT 321		0
2782376	82 C 101	82 C 591	L1A 4601																																																
2782654	82 C 103	82 C 597	MSM 6307																																																
69G1705	82 C 211	82 C 599	R 4220																																																
82303	82 C 288	82 C 801B	R 4230																																																
82304	82 C 301	82 C 802G	TACT 83443																																																
82306	82 C 320	82 C 822	VAC 068																																																
82308	82 C 362	82 C 88	VIC 068																																																
82309	82 C 461	CA 91C014	VIC 64																																																
82355	82 C 463	ET 6 000	VL 82 C 331																																																
82358	82 C 465	GC 181	VY 86 C 410																																																
82374EB	82 C 493	HT 216																																																	
82434LX	82 C 496	HT 321																																																	
ex 8542 13 70	*42	<p>Video controller, with at least one of the following functions:</p> <ol style="list-style-type: none"> a) cathode-ray tube controlling, b) liquid crystal display (LCD) driving or controlling, c) graphics or graphic symbols controlling, d) colour selection controlling, 																																																	

CN code	TARIC	Description	Rate of autonomous duty %																																																																																	
ex 8542 13 70 (cont'd)		<p>in the form of a monolithic integrated circuit, either contained in a housing or fixed on a plastic support, and bearing:</p> <p>— an identification marking consisting of or including one of the following combinations of figures and letters:</p> <table border="0"> <tr> <td>a) 82 C 434</td> <td>b) HD 66100</td> <td>b) V 6117</td> </tr> <tr> <td>a) 82 C 453</td> <td>b) HD 61104T</td> <td>b) V 6355-DJ</td> </tr> <tr> <td>a) 86 C 805</td> <td>b) HD 61105T</td> <td>b) WD 90C24</td> </tr> <tr> <td>a) 86 C 911</td> <td>b) HD 66106T</td> <td>c) 82 C 431</td> </tr> <tr> <td>a) 86 C 928</td> <td>b) HD 66107T</td> <td>c) 82 C 435</td> </tr> <tr> <td>a) AM 8052</td> <td>b) LC 7582</td> <td>c) 82 C 441</td> </tr> <tr> <td>a) ATI 68800</td> <td>b) M 6003</td> <td>c) 82 C 451</td> </tr> <tr> <td>a) CL-GD542</td> <td>b) M 6004</td> <td>c) 82 C 452</td> </tr> <tr> <td>a) CL-GD543</td> <td>b) MSM 5259</td> <td>c) 84 C 451</td> </tr> <tr> <td>a) CRT 9007</td> <td>b) MSM 5298</td> <td>c) 86 C 864</td> </tr> <tr> <td>a) CRT 97 C 11</td> <td>b) MSM 5299</td> <td>c) 86 C 964</td> </tr> <tr> <td>a) M 50452</td> <td>b) MSM 5839</td> <td>c) ATI 264CT</td> </tr> <tr> <td>a) MB 89321</td> <td>b) PCF 8576</td> <td>c) AVGA1</td> </tr> <tr> <td>a) MB 89322</td> <td>b) SED 1520</td> <td>c) CL-GD5410</td> </tr> <tr> <td>a) TVP 9512</td> <td>b) SED 1521</td> <td>c) GD 5430</td> </tr> <tr> <td>a) V 6363</td> <td>b) SED 1600</td> <td>c) HT 208</td> </tr> <tr> <td>a) WD 90 C 10</td> <td>b) SED 1610</td> <td>c) HT 209</td> </tr> <tr> <td>a) WD 90 C 11</td> <td>b) T 6A39</td> <td>c) L 64845</td> </tr> <tr> <td>a) WD 90 C 30</td> <td>b) T 6A40</td> <td>c) LC 74780</td> </tr> <tr> <td>a) WD 90 C 31</td> <td>b) TMS 3491</td> <td>c) NCR 77C22</td> </tr> <tr> <td>a) WD 90 C 33</td> <td>b) TMS 3492</td> <td>c) OTI 067</td> </tr> <tr> <td>b) 82 C 425</td> <td>b) TMS 57202</td> <td>c) PEGA</td> </tr> <tr> <td>b) CL-GD6410</td> <td>b) TMS 57206</td> <td>c) PVGA</td> </tr> <tr> <td>b) COP 472</td> <td>b) TMS 57207</td> <td>c) SC 1 5064</td> </tr> <tr> <td>b) H 5050</td> <td>b) TMS 57210</td> <td>c) WD 90 C 00</td> </tr> <tr> <td>b) HD 44100</td> <td>b) TMS 57212</td> <td>d) 82 C 433</td> </tr> <tr> <td>b) HD 44780</td> <td>b) TMS 57213</td> <td></td> </tr> </table> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	a) 82 C 434	b) HD 66100	b) V 6117	a) 82 C 453	b) HD 61104T	b) V 6355-DJ	a) 86 C 805	b) HD 61105T	b) WD 90C24	a) 86 C 911	b) HD 66106T	c) 82 C 431	a) 86 C 928	b) HD 66107T	c) 82 C 435	a) AM 8052	b) LC 7582	c) 82 C 441	a) ATI 68800	b) M 6003	c) 82 C 451	a) CL-GD542	b) M 6004	c) 82 C 452	a) CL-GD543	b) MSM 5259	c) 84 C 451	a) CRT 9007	b) MSM 5298	c) 86 C 864	a) CRT 97 C 11	b) MSM 5299	c) 86 C 964	a) M 50452	b) MSM 5839	c) ATI 264CT	a) MB 89321	b) PCF 8576	c) AVGA1	a) MB 89322	b) SED 1520	c) CL-GD5410	a) TVP 9512	b) SED 1521	c) GD 5430	a) V 6363	b) SED 1600	c) HT 208	a) WD 90 C 10	b) SED 1610	c) HT 209	a) WD 90 C 11	b) T 6A39	c) L 64845	a) WD 90 C 30	b) T 6A40	c) LC 74780	a) WD 90 C 31	b) TMS 3491	c) NCR 77C22	a) WD 90 C 33	b) TMS 3492	c) OTI 067	b) 82 C 425	b) TMS 57202	c) PEGA	b) CL-GD6410	b) TMS 57206	c) PVGA	b) COP 472	b) TMS 57207	c) SC 1 5064	b) H 5050	b) TMS 57210	c) WD 90 C 00	b) HD 44100	b) TMS 57212	d) 82 C 433	b) HD 44780	b) TMS 57213		0
a) 82 C 434	b) HD 66100	b) V 6117																																																																																		
a) 82 C 453	b) HD 61104T	b) V 6355-DJ																																																																																		
a) 86 C 805	b) HD 61105T	b) WD 90C24																																																																																		
a) 86 C 911	b) HD 66106T	c) 82 C 431																																																																																		
a) 86 C 928	b) HD 66107T	c) 82 C 435																																																																																		
a) AM 8052	b) LC 7582	c) 82 C 441																																																																																		
a) ATI 68800	b) M 6003	c) 82 C 451																																																																																		
a) CL-GD542	b) M 6004	c) 82 C 452																																																																																		
a) CL-GD543	b) MSM 5259	c) 84 C 451																																																																																		
a) CRT 9007	b) MSM 5298	c) 86 C 864																																																																																		
a) CRT 97 C 11	b) MSM 5299	c) 86 C 964																																																																																		
a) M 50452	b) MSM 5839	c) ATI 264CT																																																																																		
a) MB 89321	b) PCF 8576	c) AVGA1																																																																																		
a) MB 89322	b) SED 1520	c) CL-GD5410																																																																																		
a) TVP 9512	b) SED 1521	c) GD 5430																																																																																		
a) V 6363	b) SED 1600	c) HT 208																																																																																		
a) WD 90 C 10	b) SED 1610	c) HT 209																																																																																		
a) WD 90 C 11	b) T 6A39	c) L 64845																																																																																		
a) WD 90 C 30	b) T 6A40	c) LC 74780																																																																																		
a) WD 90 C 31	b) TMS 3491	c) NCR 77C22																																																																																		
a) WD 90 C 33	b) TMS 3492	c) OTI 067																																																																																		
b) 82 C 425	b) TMS 57202	c) PEGA																																																																																		
b) CL-GD6410	b) TMS 57206	c) PVGA																																																																																		
b) COP 472	b) TMS 57207	c) SC 1 5064																																																																																		
b) H 5050	b) TMS 57210	c) WD 90 C 00																																																																																		
b) HD 44100	b) TMS 57212	d) 82 C 433																																																																																		
b) HD 44780	b) TMS 57213																																																																																			
ex 8542 13 70	*43	<p>Error detection and correction circuit of C-MOS or N-MOS (including H-MOS) technology, capable of detecting and correcting single bit errors and detecting all double bit errors, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including one of the following combinations of figures and letters:</p> <table border="0"> <tr> <td>8206</td> <td>Am 29C60</td> <td>Am 29C660</td> </tr> </table> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	8206	Am 29C60	Am 29C660	0																																																																														
8206	Am 29C60	Am 29C660																																																																																		
ex 8542 13 70	*44	<p>Bus interface circuit, whether or not with bus control functions, in the form of a monolithic integrated circuit contained in a housing bearing:</p>																																																																																		

CN code	TARIC	Description	Rate of autonomous duty %																																																															
ex 8542 13 70 (cont'd)		<p>— an identification marking consisting of or including one of the following combinations of figures or of figures and letters:</p> <table border="0"> <tr><td>03H6300</td><td>AIC 6250</td><td>LIA 6396</td></tr> <tr><td>53 C 700</td><td>AIC 7770</td><td>LIA 6732</td></tr> <tr><td>53 C 710</td><td>Am 29C983</td><td>MB 86980</td></tr> <tr><td>53 C 720</td><td>Am 29C985</td><td>NCR 5380</td></tr> <tr><td>82335</td><td>CL PD6710</td><td>NCR 5381</td></tr> <tr><td>82351</td><td>CL PD6720</td><td>NCR 53 C 80</td></tr> <tr><td>82352</td><td>CY7C960</td><td>NCR 53 C 90</td></tr> <tr><td>82353</td><td>CY7C961</td><td>PBI</td></tr> <tr><td>82365SL</td><td>CY7C964</td><td>PCF 85474</td></tr> <tr><td>82375EB</td><td>ES 688</td><td>TACT 84544</td></tr> <tr><td>82378IB</td><td>ESP 216</td><td>TMS 38030</td></tr> <tr><td>82423TX</td><td>ESP 226</td><td>VY 06765</td></tr> <tr><td>82433LX</td><td>FAS 216</td><td>VY 06925</td></tr> <tr><td>82C100</td><td>FAS 226</td><td>WD 33 C 92</td></tr> <tr><td>82C300</td><td>FAS 236</td><td>WD 33 C 93</td></tr> <tr><td>82C596</td><td>FE 3030</td><td>WD 33 C 95</td></tr> <tr><td>82C611</td><td>GC 132</td><td>WD 33 C 96</td></tr> <tr><td>82C836</td><td>GC 133</td><td>WD 76 C 10</td></tr> <tr><td>89C100</td><td>HDL 33A112-00HQ</td><td>Z 16C32</td></tr> <tr><td>89C105</td><td>HS 3282</td><td>Z 86017</td></tr> <tr><td>94G0207</td><td>L 64853A</td><td></td></tr> </table> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	03H6300	AIC 6250	LIA 6396	53 C 700	AIC 7770	LIA 6732	53 C 710	Am 29C983	MB 86980	53 C 720	Am 29C985	NCR 5380	82335	CL PD6710	NCR 5381	82351	CL PD6720	NCR 53 C 80	82352	CY7C960	NCR 53 C 90	82353	CY7C961	PBI	82365SL	CY7C964	PCF 85474	82375EB	ES 688	TACT 84544	82378IB	ESP 216	TMS 38030	82423TX	ESP 226	VY 06765	82433LX	FAS 216	VY 06925	82C100	FAS 226	WD 33 C 92	82C300	FAS 236	WD 33 C 93	82C596	FE 3030	WD 33 C 95	82C611	GC 132	WD 33 C 96	82C836	GC 133	WD 76 C 10	89C100	HDL 33A112-00HQ	Z 16C32	89C105	HS 3282	Z 86017	94G0207	L 64853A		0
03H6300	AIC 6250	LIA 6396																																																																
53 C 700	AIC 7770	LIA 6732																																																																
53 C 710	Am 29C983	MB 86980																																																																
53 C 720	Am 29C985	NCR 5380																																																																
82335	CL PD6710	NCR 5381																																																																
82351	CL PD6720	NCR 53 C 80																																																																
82352	CY7C960	NCR 53 C 90																																																																
82353	CY7C961	PBI																																																																
82365SL	CY7C964	PCF 85474																																																																
82375EB	ES 688	TACT 84544																																																																
82378IB	ESP 216	TMS 38030																																																																
82423TX	ESP 226	VY 06765																																																																
82433LX	FAS 216	VY 06925																																																																
82C100	FAS 226	WD 33 C 92																																																																
82C300	FAS 236	WD 33 C 93																																																																
82C596	FE 3030	WD 33 C 95																																																																
82C611	GC 132	WD 33 C 96																																																																
82C836	GC 133	WD 76 C 10																																																																
89C100	HDL 33A112-00HQ	Z 16C32																																																																
89C105	HS 3282	Z 86017																																																																
94G0207	L 64853A																																																																	
ex 8542 13 70 ex 8542 19 71	*45 *10	<p>Interface circuit or control circuit, for a local area network (LAN), in the form of a monolithic integrated circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including one of the following combinations of figures and letters:</p> <table border="0"> <tr><td>8003</td><td>Am 79C961</td><td>DP 83932</td></tr> <tr><td>80C03</td><td>Am 79C965</td><td>LXT 901</td></tr> <tr><td>82586</td><td>Am 79C970</td><td>MB 86950</td></tr> <tr><td>82588</td><td>Am 79C987</td><td>MB 86965A</td></tr> <tr><td>82590</td><td>COM 9026</td><td>SMC 83C790</td></tr> <tr><td>82592</td><td>DP 8025</td><td>T 7213</td></tr> <tr><td>83C795</td><td>DP 83251</td><td>WD 80 C 24</td></tr> <tr><td>Am 7990</td><td>DP 83255</td><td>WD 83 C 503</td></tr> <tr><td>Am 79C830</td><td>DP 83261</td><td>WD 83 C 510</td></tr> <tr><td>Am 79C90</td><td>DP 83265</td><td>WD 83 C 603</td></tr> <tr><td>Am 79C940</td><td>DP 8390</td><td>WD 83 C 690</td></tr> <tr><td>Am 79C950</td><td>DP 83902</td><td></td></tr> <tr><td>Am 79C960</td><td>DP 83905</td><td></td></tr> </table> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	8003	Am 79C961	DP 83932	80C03	Am 79C965	LXT 901	82586	Am 79C970	MB 86950	82588	Am 79C987	MB 86965A	82590	COM 9026	SMC 83C790	82592	DP 8025	T 7213	83C795	DP 83251	WD 80 C 24	Am 7990	DP 83255	WD 83 C 503	Am 79C830	DP 83261	WD 83 C 510	Am 79C90	DP 83265	WD 83 C 603	Am 79C940	DP 8390	WD 83 C 690	Am 79C950	DP 83902		Am 79C960	DP 83905		0																								
8003	Am 79C961	DP 83932																																																																
80C03	Am 79C965	LXT 901																																																																
82586	Am 79C970	MB 86950																																																																
82588	Am 79C987	MB 86965A																																																																
82590	COM 9026	SMC 83C790																																																																
82592	DP 8025	T 7213																																																																
83C795	DP 83251	WD 80 C 24																																																																
Am 7990	DP 83255	WD 83 C 503																																																																
Am 79C830	DP 83261	WD 83 C 510																																																																
Am 79C90	DP 83265	WD 83 C 603																																																																
Am 79C940	DP 8390	WD 83 C 690																																																																
Am 79C950	DP 83902																																																																	
Am 79C960	DP 83905																																																																	
ex 8542 13 70 ex 8542 14 50	*46 *07	<p>Serial interface, capable of implementing the data stream encoding, decoding and associated control functions for a local area network (LAN), in the form of a monolithic integrated circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including one of the following combinations of figures or figures and letters:</p> <table border="0"> <tr><td>8002</td><td>82501</td><td>AM 7991</td><td>COM 91 C 32</td></tr> <tr><td>8023</td><td>82 C 501</td><td>COM 9032</td><td></td></tr> </table> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	8002	82501	AM 7991	COM 91 C 32	8023	82 C 501	COM 9032		0																																																							
8002	82501	AM 7991	COM 91 C 32																																																															
8023	82 C 501	COM 9032																																																																

CN code	TARIC	Description	Rate of autonomous duty %
ex 8542 13 70	*47	<p>Arithmetic-logic unit (ALU) of C-MOS technology, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including one of the following combinations of figures and letters: CY2901 CY7C9115 CY7C9117 CY7C9101 CY7C9116 CY7C901</p> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8542 13 70	*48	<p>Adaptive differentiated pulse-code-modulation encoder/decoder of C-MOS technology, comprising a transmit and receive control circuit, a microprocessor bus interface circuit and a parallel port, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including one of the following combinations of figures and letters: VP 06565 VP 23070 VP 23071</p> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8542 13 84	*11	<p>Counter of C-MOS technology, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including one of the following combinations of figures and letters: 54 AC 161 54 ACT 161 74 AC 161 74 ACT 161 54 AC 163 54 ACT 163 74 AC 163 74 ACT 163</p> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8542 13 84	*12	<p>Logic circuit of C-MOS technology, having only one of the following functions:</p> <p>— NAND, — OR, — multiplexer,</p> <p>in the form of a monolithic integrated circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including one of the following combinations of figures and letters: 54 AC 00 54 ACT 00 74 AC 00 74 ACT 00 54 AC 257 54 ACT 257 74 AC 257 74 ACT 257 54 AC 258 54 ACT 258 74 AC 258 74 ACT 258 54 AC 32 54 ACT 32 74 AC 32 74 ACT 32</p> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8542 13 84	*13	<p>8-bit identity comparator of C-MOS technology, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including the following combination of figures and letters: 54 AC 521 74 AC 521 74 ACT 521 54 ACT 521 74 ACT 520</p> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0

CN code	TARIC	Description	Rate of autonomous duty %																		
ex 8542 13 84	*14	<p>Register of C-MOS technology, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including one of the following combinations of figures and letters:</p> <table style="margin-left: 40px;"> <tr> <td>74FCT162374</td> <td>74FCT374</td> <td>74HC597</td> </tr> <tr> <td>74FCT162823BT</td> <td>74FCT534</td> <td>74HCT595</td> </tr> <tr> <td>74FCT162823CT</td> <td>74FCT574</td> <td>Am 29C818 A</td> </tr> <tr> <td>74FCT16374</td> <td>54HC595</td> <td>Am 29C821A</td> </tr> <tr> <td>74FCT16823BT</td> <td>54HC597</td> <td>Am 29C823A</td> </tr> <tr> <td>74FCT16823CT</td> <td>74HC595</td> <td></td> </tr> </table> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	74FCT162374	74FCT374	74HC597	74FCT162823BT	74FCT534	74HCT595	74FCT162823CT	74FCT574	Am 29C818 A	74FCT16374	54HC595	Am 29C821A	74FCT16823BT	54HC597	Am 29C823A	74FCT16823CT	74HC595		0
74FCT162374	74FCT374	74HC597																			
74FCT162823BT	74FCT534	74HCT595																			
74FCT162823CT	74FCT574	Am 29C818 A																			
74FCT16374	54HC595	Am 29C821A																			
74FCT16823BT	54HC597	Am 29C823A																			
74FCT16823CT	74HC595																				
ex 8542 13 91	*18	<p>Line interface circuit of C-MOS technology, capable of transmitting and receiving data at a rate of 25,6 Mbits per second, comprising a FIFO (first in, first out) read/write memory, a 4/5-bit encoder and a 5/4-bit decoder, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including the following combination of figures and letters:</p> <p style="margin-left: 40px;">TXC 07125</p> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0																		
ex 8542 13 99	*39	<p>Serial/parallel converter for a synchronised serial bus, of C-MOS technology, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including the following combination of figures and letters:</p> <p style="margin-left: 40px;">HD 49783</p> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0																		
ex 8542 13 99	*40	<p>Transmitter/receiver of C-MOS technology, for the reception and transmission of data at a speed of 51,84 or 44,736 Mbits/s, comprising a NRZ (non-return-to-zero) data-format encoder, a decoder, an adaptive equalizer associated with an automatic gain controller, a receive control circuit, an emitter control circuit and a clock recovery circuit, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including one of the following combinations of figures and letters:</p> <table style="margin-left: 40px;"> <tr> <td>TXC 02020</td> <td>TXC 02021</td> </tr> </table> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	TXC 02020	TXC 02021	0																
TXC 02020	TXC 02021																				
ex 8542 13 99	*41	<p>Video noise reduction circuit of C-MOS technology, comprising inputs for 8-bit chrominance and luminance signals, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including the following combination of figures and letters:</p> <p style="margin-left: 40px;">CXD 2036</p> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0																		

CN code	TARIC	Description	Rate of autonomous duty %
ex 8542 13 99	*42	<p>FM stereo sound generator of C-MOS technology, comprising a phase generator, a timer, a registers array, a bus controller and at least 1 accumulator, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including one of the following combinations of figures and letters: YMF 262 YMF 289</p> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8542 13 99	*43	<p>Decoder of C-MOS technology, capable of error correction, comprising a serial bus and a descrambling circuit, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including the following combination of figures and letters: VES 5453</p> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8542 13 99	*44	<p>Demodulator of C-MOS technology, comprising reception filters, polyphase filters, a clock synchronization circuit and an automatic gain controller, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including the following combination of figures and letters: VES 4133</p> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8542 13 99	*45	<p>Infrared transmitter/receiver of C-MOS technology, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including the following combination of figures and letters: CS 8130</p> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8542 13 99	*46	<p>Transmitter/receiver of C-MOS technology, capable of data transfer at a frequency of 1,544 MHz or 2,048 MHz, comprising an equaliser and a clock generator, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including one of the following combinations of figures and letters: LXT 304 LXT 310 LXT 311</p> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8542 13 99	*47	<p>Digital-to-analogue converter of C-MOS technology, with at least one of the following characteristics:</p> <p>a) with a capacity of 8 bits, with an output buffer amplifier, a serial interface circuit and at least 12 channels,</p> <p>b) with a capacity of 8 bits, capable of double buffering 8-bit words,</p>	

CN code	TARIC	Description	Rate of autonomous duty %																																													
ex 8542 13 99 (cont'd)		<p>c) with a capacity of 8 bits, capable of converting serial data input towards 36 output channels,</p> <p>d) single or triple converter, with at least one random-access memory (RAMDAC), having one or more colour palette registers,</p> <p>e) with a dynamic audio range of 90 dB or more,</p> <p>f) 8- or 10-bit video converter, with 3 channels for the separate conversion of colour signals,</p> <p>g) with a capacity of 16 bits, capable of converting data in floating point form, comprising a 10-bit digital-to-analogue converter, and a shift register,</p> <p>in the form of a monolithic integrated circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including one of the following combinations of figures and letters:</p> <table border="0" data-bbox="427 723 1018 1106"> <tr> <td>a) M 62352P</td> <td>d) Bt458</td> <td>d) SC 11489</td> </tr> <tr> <td>b) DAC 0830</td> <td>d) Bt459</td> <td>d) SC 15025</td> </tr> <tr> <td>b) DAC 0831</td> <td>d) Bt460</td> <td>d) SC 15026</td> </tr> <tr> <td>b) DAC 0832</td> <td>d) Bt461</td> <td>d) TR 9C1710</td> </tr> <tr> <td>c) MB 88344B</td> <td>d) Bt462</td> <td>d) TVP 3020</td> </tr> <tr> <td>d) 357S0010</td> <td>d) Bt463</td> <td>d) TVP 3030</td> </tr> <tr> <td>d) 357S0011</td> <td>d) Bt467</td> <td>e) CS 4328</td> </tr> <tr> <td>d) 357S0012</td> <td>d) Bt473</td> <td>e) CXD 2564</td> </tr> <tr> <td>d) ATT 20C490</td> <td>d) Bt475</td> <td>e) PD 6376</td> </tr> <tr> <td>d) ATT 20C491</td> <td>d) MU 9C9760</td> <td>e) TMS 57010</td> </tr> <tr> <td>d) ATT 20C492</td> <td>d) SC 11482</td> <td>f) CXD 1178</td> </tr> <tr> <td>d) ATT 20C493</td> <td>d) SC 11483</td> <td>f) CXD 2307R</td> </tr> <tr> <td>d) ATT 20C497</td> <td>d) SC 11484</td> <td>f) CXD 2309</td> </tr> <tr> <td>d) Bt445</td> <td>d) SC 11485</td> <td>g) YAC 512</td> </tr> <tr> <td>d) Bt451</td> <td>d) SC 11487</td> <td>g) YAC 513</td> </tr> </table> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	a) M 62352P	d) Bt458	d) SC 11489	b) DAC 0830	d) Bt459	d) SC 15025	b) DAC 0831	d) Bt460	d) SC 15026	b) DAC 0832	d) Bt461	d) TR 9C1710	c) MB 88344B	d) Bt462	d) TVP 3020	d) 357S0010	d) Bt463	d) TVP 3030	d) 357S0011	d) Bt467	e) CS 4328	d) 357S0012	d) Bt473	e) CXD 2564	d) ATT 20C490	d) Bt475	e) PD 6376	d) ATT 20C491	d) MU 9C9760	e) TMS 57010	d) ATT 20C492	d) SC 11482	f) CXD 1178	d) ATT 20C493	d) SC 11483	f) CXD 2307R	d) ATT 20C497	d) SC 11484	f) CXD 2309	d) Bt445	d) SC 11485	g) YAC 512	d) Bt451	d) SC 11487	g) YAC 513	0
a) M 62352P	d) Bt458	d) SC 11489																																														
b) DAC 0830	d) Bt459	d) SC 15025																																														
b) DAC 0831	d) Bt460	d) SC 15026																																														
b) DAC 0832	d) Bt461	d) TR 9C1710																																														
c) MB 88344B	d) Bt462	d) TVP 3020																																														
d) 357S0010	d) Bt463	d) TVP 3030																																														
d) 357S0011	d) Bt467	e) CS 4328																																														
d) 357S0012	d) Bt473	e) CXD 2564																																														
d) ATT 20C490	d) Bt475	e) PD 6376																																														
d) ATT 20C491	d) MU 9C9760	e) TMS 57010																																														
d) ATT 20C492	d) SC 11482	f) CXD 1178																																														
d) ATT 20C493	d) SC 11483	f) CXD 2307R																																														
d) ATT 20C497	d) SC 11484	f) CXD 2309																																														
d) Bt445	d) SC 11485	g) YAC 512																																														
d) Bt451	d) SC 11487	g) YAC 513																																														
ex 8542 13 99	*48	<p>Analogue-to-digital converter, with at least one of the following characteristics:</p> <p>a) 8-bit parallel converter of C-MOS technology,</p> <p>b) with a capacity of 16 or 20 bits of C-MOS technology, comprising a synchronisation circuit, 2 modulators, 2 digital filters, a 4-bit digital-to-analogue converter and an amplifier,</p> <p>c) 16-, 18- or 20-bit stereo audio converter of C-MOS technology,</p> <p>d) with a capacity of 16 bits, comprising a digital filter with a passband of 45,5 kHz at 3 dB,</p> <p>e) capable of driving a liquid crystal (LCD) or light emitting diode (LED) display with not more 4 digits,</p> <p>f) 8-bit video converter of C-MOS technology, comprising a synchronizing clamp circuit,</p> <p>in the form of a monolithic integrated circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including one the following combinations of figures and letters:</p> <table border="0" data-bbox="427 1697 1005 1980"> <tr> <td>a) IDT 75C48</td> <td>c) CS 5339</td> <td>e) ICL 7137</td> </tr> <tr> <td>a) IDT 75C58</td> <td>c) CS 5349</td> <td>e) MAX 130</td> </tr> <tr> <td>a) MP 7683</td> <td>d) DSP 56ADC16</td> <td>e) MAX 131</td> </tr> <tr> <td>a) MP 7684</td> <td>e) HI 7131</td> <td>e) MAX 133</td> </tr> <tr> <td>b) CS 5516</td> <td>e) HI 7133</td> <td>e) MAX 138</td> </tr> <tr> <td>b) CS 5520</td> <td>e) ICL 7106</td> <td>e) MAX 139</td> </tr> <tr> <td>c) CS 5326</td> <td>e) ICL 7107</td> <td>e) MAX 140</td> </tr> <tr> <td>c) CS 5327</td> <td>e) ICL 7116</td> <td>e) MAX 136</td> </tr> <tr> <td>c) CS 5328</td> <td>e) ICL 7117</td> <td>f) CXD 1176</td> </tr> <tr> <td>c) CS 5329</td> <td>e) ICL 7126</td> <td>f) CXD 2300</td> </tr> <tr> <td>c) CS 5336</td> <td>e) ICL 7136</td> <td></td> </tr> </table> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	a) IDT 75C48	c) CS 5339	e) ICL 7137	a) IDT 75C58	c) CS 5349	e) MAX 130	a) MP 7683	d) DSP 56ADC16	e) MAX 131	a) MP 7684	e) HI 7131	e) MAX 133	b) CS 5516	e) HI 7133	e) MAX 138	b) CS 5520	e) ICL 7106	e) MAX 139	c) CS 5326	e) ICL 7107	e) MAX 140	c) CS 5327	e) ICL 7116	e) MAX 136	c) CS 5328	e) ICL 7117	f) CXD 1176	c) CS 5329	e) ICL 7126	f) CXD 2300	c) CS 5336	e) ICL 7136		0												
a) IDT 75C48	c) CS 5339	e) ICL 7137																																														
a) IDT 75C58	c) CS 5349	e) MAX 130																																														
a) MP 7683	d) DSP 56ADC16	e) MAX 131																																														
a) MP 7684	e) HI 7131	e) MAX 133																																														
b) CS 5516	e) HI 7133	e) MAX 138																																														
b) CS 5520	e) ICL 7106	e) MAX 139																																														
c) CS 5326	e) ICL 7107	e) MAX 140																																														
c) CS 5327	e) ICL 7116	e) MAX 136																																														
c) CS 5328	e) ICL 7117	f) CXD 1176																																														
c) CS 5329	e) ICL 7126	f) CXD 2300																																														
c) CS 5336	e) ICL 7136																																															

CN code	TARIC	Description	Rate of autonomous duty %
ex 8542 13 99	*49	<p>Data segmentation or reassembly circuit of C-MOS technology, providing fragmentation of 16 382 packets of 8- or 16-bit words into cells or providing reassembly of these cells in 16 382 packets of 8- or 16-bit words, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including one of the following combinations of figures and letters: TXC 05501 TXC 05601 or — other identification markings relating to devices complying with the abovementioned description 	0
ex 8542 13 99	*50	<p>Subscriber line audio-processing circuit (SLAC) of C-MOS technology, comprising 2 digital signal processors, at least 1 analogue-to-digital converter and at least 1 digital-to-analogue converter, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including one of the following combinations of figures and letters: Am 7901 Am 7905 Am 79C02 Am 79C03 Am 79C04 or — other identification markings relating to devices complying with the abovementioned description 	0
ex 8542 13 99	*51	<p>Signal synthesizer of N-MOS (including H-MOS) technology with a frequency generator, a memory of 15 instrumental tones, a digital-to-analogue converter and a quartz oscillator, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including the following combination of figures and letters: YM 2413 or — other identification markings relating to devices complying with the abovementioned description 	0
ex 8542 13 99	*52	<p>Video processing circuit of C-MOS technology, having subpicture display (picture-in-picture) functions, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including the following combination of figures and letters: CXD 2031R CXD 2033 or — other identification markings relating to devices complying with the abovementioned description 	0
ex 8542 13 99	*53	<p>Audio decoder of C-MOS technology, capable of decoding and decompressing audio signals at a rate per second not exceeding 15 Mbits, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including one of the following combinations of figures and letters: 74 ACT 6350 TMS 320AV120 or — other identification markings relating to devices complying with the abovementioned description 	0

CN code	TARIC	Description	Rate of autonomous duty %																																				
ex 8542 13 99 ex 8542 19 98	*54 *21	<p>Clock generator, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including one of the following combinations of figures or figures and letters:</p> <table> <tr> <td>D4661CL</td> <td>CY7B992</td> <td>ICS 2494</td> <td>MK 1450</td> </tr> <tr> <td>82 C 402</td> <td>CY7B993</td> <td>ICS 90C64</td> <td>MSM 5547</td> </tr> <tr> <td>AV 9129</td> <td>DP 8531</td> <td>ICS 9161</td> <td>PCLK 1</td> </tr> <tr> <td>Bt 438</td> <td>DP 8532</td> <td>LZ 93F31</td> <td>PCLK 2</td> </tr> <tr> <td>Bt 439</td> <td>DP 83241</td> <td>LZ 93F33</td> <td>SC 11410</td> </tr> <tr> <td>CXD 1035</td> <td>ICD 2023</td> <td>LZ 93N61</td> <td>SC 11411</td> </tr> <tr> <td>CXD 1252</td> <td>ICD 2027</td> <td>MK 1418</td> <td>SC 11412</td> </tr> <tr> <td>CXD 1255</td> <td>ICD 2028</td> <td>MK 1442</td> <td>TCK 9002</td> </tr> <tr> <td>CY7B991</td> <td>ICS 1394</td> <td>MK 1448</td> <td>WD 90 C 61</td> </tr> </table> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	D4661CL	CY7B992	ICS 2494	MK 1450	82 C 402	CY7B993	ICS 90C64	MSM 5547	AV 9129	DP 8531	ICS 9161	PCLK 1	Bt 438	DP 8532	LZ 93F31	PCLK 2	Bt 439	DP 83241	LZ 93F33	SC 11410	CXD 1035	ICD 2023	LZ 93N61	SC 11411	CXD 1252	ICD 2027	MK 1418	SC 11412	CXD 1255	ICD 2028	MK 1442	TCK 9002	CY7B991	ICS 1394	MK 1448	WD 90 C 61	0
D4661CL	CY7B992	ICS 2494	MK 1450																																				
82 C 402	CY7B993	ICS 90C64	MSM 5547																																				
AV 9129	DP 8531	ICS 9161	PCLK 1																																				
Bt 438	DP 8532	LZ 93F31	PCLK 2																																				
Bt 439	DP 83241	LZ 93F33	SC 11410																																				
CXD 1035	ICD 2023	LZ 93N61	SC 11411																																				
CXD 1252	ICD 2027	MK 1418	SC 11412																																				
CXD 1255	ICD 2028	MK 1442	TCK 9002																																				
CY7B991	ICS 1394	MK 1448	WD 90 C 61																																				
ex 8542 13 99	*55	<p>Circuit for the recording and reproduction of speech of C-MOS technology, working at a speed of 8 Kbits/sec or more, with at least one of the following characteristics:</p> <p>a) comprising an amplifier and a 10-bit digital-to-analogue converter,</p> <p>b) comprising a memory interface circuit, an encoding/decoding circuit, a central processing unit (CPU) interface,</p> <p>c) comprising a 12-bit digital-to-analogue converter,</p> <p>in the form of a monolithic integrated circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including one of the following combinations of figures and letters:</p> <table> <tr> <td>a) T 6668</td> <td>a) TC 8830</td> <td>b) TC 88401</td> <td>c) M5M6388</td> </tr> </table> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	a) T 6668	a) TC 8830	b) TC 88401	c) M5M6388	0																																
a) T 6668	a) TC 8830	b) TC 88401	c) M5M6388																																				
ex 8542 14 15	*03	<p>Random-access memory of ECL technology (ECL-RAM) with a storage capacity not exceeding 64 Kbits, in the form of a monolithic integrated circuit, either contained in a housing or fixed on a plastic support, and bearing:</p> <p>— an identification marking consisting of or including one of the following combinations of figures:</p> <table> <tr> <td>100474</td> <td>100490</td> <td>101 480</td> <td>10470</td> <td>10484</td> </tr> <tr> <td>100480</td> <td>100A474</td> <td>101A474</td> <td>10474</td> <td>10490</td> </tr> <tr> <td>100484</td> <td>101474</td> <td>10422</td> <td>10480</td> <td>10A474</td> </tr> </table> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	100474	100490	101 480	10470	10484	100480	100A474	101A474	10474	10490	100484	101474	10422	10480	10A474	0																					
100474	100490	101 480	10470	10484																																			
100480	100A474	101A474	10474	10490																																			
100484	101474	10422	10480	10A474																																			
8542 14 80		Standard logic circuits	0																																				
ex 8542 14 99	*27	<p>Transmitter/receiver of bipolar technology, for bidirectional differential buses, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including the following combination of figures and letters:</p> <p>DS 36277</p> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0																																				

CN code	TARIC	Description	Rate of autonomous duty %
ex 8542 14 99	*28	<p>Transmitter/receiver of bipolar technology, capable of converting data into serial or parallel format and serial data transfer at a rate not exceeding 200 megabytes per second, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including the following combination of figures and letters: MC 100SX1451 or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8542 14 99	*29	<p>Transmitter/receiver of bipolar technology, capable of data transmission over a twisted-pair cable, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including one of the following combinations of figures and letters: Am 26LS38 DP 83220 or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8542 14 99	*30	<p>Prescaler of bipolar technology, having an input frequency not exceeding 2,8 GHz and a selectable 32/33, 64/65, 64/128 or 128/129 divide ratio, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including one of the following combinations of figures and letters: MC 12022 MC 12034 MC 12053 SC 12022 MC 12032 MC 12052 MC 12089 or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8542 19 22	*07	<p>Static random-access cache memory of BiMOS technology (BiMOS S-Cache-RAM), with a storage capacity of 240 Kbits, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including one of the following combinations of figures and letters: IDT 71215 IDT 71 216 or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8542 19 22	*09	<p>Static random-access memory of MOS technology combined with ECL technology, with a storage capacity not exceeding 64 Kbits, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including one of the following combinations of figures and letters: 100474 101474 10474 10C494-15 100480 101 480 10480 100A474 101A474 10A474 or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0

CN code	TARIC	Description	Rate of autonomous duty %
ex 8542 19 22	*10	<p>Static random-access cache memory of BiMOS technology (BiMOS S-Cache-RAM), with a storage capacity of 64 Kbits and an access time not exceeding 20 ns, comprising an 8-bit address comparator, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including the following combination of figures and letters: IDT 71B74 or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8542 19 25	*05	<p>Static random-access memory of BiMOS technology (BiMOS S-RAM), with a storage capacity of 576 Kbits, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including one of the following combinations of figures and letters: IDT 71419 IDT 71420 or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8542 19 84 ex 8542 19 98	*03 *19	<p>Transmitter/receiver of BiMOS technology, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including one of the following combinations of figures and letters: 74ABT543 CY7B956 SN 74 BCT 2423 CY7B923 DS 3884 SN 74 BCT 2424 CY7B933 DS 3886 SN 74 BCT 2425 CY7B955 SN 74 BCT 2420 SN 75 LBC 976 or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8542 19 92	*04	<p>Subscriber line interface circuit (SLIC) of dielectric isolation technology, with an internal programmed constant line current, comprising a resistor network and an operational amplifier, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including one of the following combinations of figures and letters: HC 5502 HC 5504 or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8542 19 98	*18	<p>12-bit analogue-to-digital converter of BiMOS technology, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including one the following combinations of figures and letters: AD 871 AD 872 or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0

CN code	TARIC	Description	Rate of autonomous duty %
ex 8542 19 98	*20	<p>Quadruple digital-to-analogue converter with a capacity of 12 bits, of BiMOS technology, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including the following combination of figures and letters: AD 664 or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8542 30 10	*07	<p>Wafer, not yet cut into chips, consisting of speech circuits of C-MOS technology, for use in the manufacture of goods of subheading 8542 30 95 contained in a housing bearing:</p> <p>— an identification marking consisting of or including one of the following combinations of figures and letters: AS 2520 AS 2531 or</p> <p>— other identification markings relating to devices complying with the abovementioned description (a)</p>	0
ex 8542 30 20	*08	<p>Amplifier with an input current not exceeding 80 nA, in the form of a monolithic integrated analogue circuit not contained in a housing (chip), for use in the manufacture of goods of subheading 8542 30 30 contained in a housing bearing:</p> <p>— an identification marking consisting of or including one of the following combinations of figures and letters: INA 101 OPA 111 OPA 121 OPA 2111 or</p> <p>— other identification markings relating to devices complying with the abovementioned description (a)</p>	0
ex 8542 30 20	*09	<p>Amplifier with a programmable gain factor, in the form of a monolithic integrated analogue circuit not contained in a housing (chip), for use in the manufacture of goods of subheading 8542 40 50 contained in a housing bearing:</p> <p>— an identification marking consisting of or including the following combination of figures and letters: 3606G or</p> <p>— other identification markings relating to devices complying with the abovementioned description (a)</p>	0
ex 8542 30 30	*16	<p>Logarithmic amplifier, in the form of a monolithic integrated analogue circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including the following combination of figures and letters: AD 606 or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8542 30 30	*17	<p>Audio amplifier, with a voltage noise density not exceeding 108 nV/Hz at a frequency of 1 kHz, in the form of a monolithic integrated analogue circuit contained in a housing bearing:</p>	

CN code	TARIC	Description	Rate of autonomous duty %
ex 8542 30 30 (cont'd)		<ul style="list-style-type: none"> — an identification marking consisting of or including the following combination of figures and letters: SSM 2017 or — other identification markings relating to devices complying with the abovementioned description 	0
ex 8542 30 30	*18	<p>Variable gain amplifier, in the form of a monolithic integrated analogue circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including one of the following combinations of figures and letters: AD 600 AD 602 or — other identification markings relating to devices complying with the abovementioned description 	0
ex 8542 30 30	*19	<p>Amplifier for processing read signals in a storage unit, in the form of a monolithic integrated analogue circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including the following combination of figures and letters: 111 0004-01 or — other identification markings relating to devices complying with the abovementioned description 	0
ex 8542 30 30	*20	<p>Video amplifier of bipolar technology, with a typical gain of 8 dB at 300 kHz, in the form of a monolithic integrated analogue circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including the following combination of figures and letters: CXA 1704 or — other identification markings relating to devices complying with the abovementioned description 	0
ex 8542 30 30	*21	<p>Intermediate frequency (IF) or FM amplifier of bipolar technology, comprising a mixer, a receive signal strength indicator (RSSI), a detector and an oscillator in the form of a monolithic integrated analogue circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including one of the following combinations of figures and letters: CXA 1343 CXA 1744R SA 607D SA 617D or — other identification markings relating to devices complying with the abovementioned description 	0
ex 8542 30 30	*22	<p>Amplifier of gallium arsenide (GaAs) semiconductor material, having a nominal gain of 15,4 dB or more but not exceeding 30 dB and a frequency range of not more than 8 GHz, in the form of a monolithic integrated analogue circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including one of the following combinations of figures and letters: 16G071 16G072 16G074 865 MGF 7131 or — other identification markings relating to devices complying with the abovementioned description 	0

CN code	TARIC	Description	Rate of autonomous duty %
ex 8542 30 30	*23	<p>Audio amplifier of bipolar technology, with a typical gain of 26 dB or more but not exceeding 47 dB in a frequency range of 20 Hz to 20 kHz, in the form of a monolithic integrated analogue circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including one of the following combinations of figures and letters: LM 3875 TA 201S</p> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8542 30 30	*24	<p>Single, dual or quadruple amplifier operating with a supply current per amplifier not exceeding 8 mA, in the form of a monolithic integrated analogue circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including one of the following combinations of figures and letters: 014B LM 2902 LT 1079 MC 14574 MC 3503 AD 826 LM 324 LT 1178 MC 14575 OP 292 LM 124 LS 404 LT 1179 MC 3303 OP 492 LM 224 LT 1078 MC 14573 MC 3403</p> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8542 30 50	*15	<p>Voltage regulator, with an input voltage not exceeding 6 V, a typical output voltage of 3,3 V, a quiescent current not exceeding 16 mA and a dropout voltage not exceeding 1,3 V, in the form of a monolithic integrated analogue circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including one of the following combinations of figures and letters: EZ 1083 EZ 1084 EZ 1085 EZ 1086</p> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8542 30 50	*16	<p>Voltage regulator, with an input voltage of 4 V or more but not exceeding 11 V and a typical output voltage of 12 or 15 V, in the form of a monolithic integrated analogue circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including one of the following combinations of figures and letters: MAX 732 MAX 733</p> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8542 30 50	*17	<p>Voltage regulator with an input voltage range of 3 V or more but not exceeding 64 V and a quiescent current of 6 mA or more but not exceeding 8,5 mA, comprising an internal 1,25 A, 2,5 A, 4 A or 5 A switch circuit, in the form of a monolithic integrated analogue circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including one of the following combinations of figures and letters: LT 1070 LT 1074 LT 1170 LT 1172 LT 1071 LT 1076 LT 1171 LT 1271</p> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0

CN code	TARIC	Description	Rate of autonomous duty %
ex 8542 30 50	*18	<p>Voltage regulator, with an input voltage of $-0,5$ V or more but not exceeding 26 V, an typical output voltage of 5 V, a quiescent current not exceeding 15 mA and a dropout voltage not exceeding 1,5 V at an output current of 500 mA, in the form of a monolithic integrated analogue circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including one of the following combinations of figures and letters: CS 8140 CS 8141 or — other identification markings relating to devices complying with the abovementioned description 	0
ex 8542 30 61	*04	<p>Smartpower circuit, capable of controlling battery voltage charge, in the form of a monolithic integrated analogue circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including one of the following combinations of figures and letters: MPC 1825VM TOP 201 TOP 203 TOP 214 TOP 200 TOP 202 TOP 204 or — other identification markings relating to devices complying with the abovementioned description 	0
ex 8542 30 65	*12	<p>3-phase motor control circuit, comprising a 9-bit digital-to-analogue converter, an 11-bit serial port, with a spindle drive current not exceeding 1 A and a voice coil motor current not exceeding 400 mA, in the form of a monolithic integrated mixed analogue-digital circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including the following combination of figures and letters: HA 13544 or — other identification markings relating to devices complying with the abovementioned description 	0
ex 8542 30 65	*13	<p>Bidirectional DC motor control circuit of bipolar technology, comprising a drive current switching circuit, in the form of a monolithic integrated mixed analogue-digital circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including the following combination of figures and letters: TA 8050P or — other identification markings relating to devices complying with the abovementioned description 	0
ex 8542 30 65	*14	<p>Control circuit, capable of driving field-effect transistors (FETs), in the form of a monolithic integrated mixed analogue-digital circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including the following combination of figures: HAA9P-51123R or — other identification markings relating to devices complying with the abovementioned description 	0

CN code	TARIC	Description	Rate of autonomous duty %
ex 8542 30 65	*15	<p>3-phase DC motor control circuit of bipolar technology, comprising an oscillator, power and phase changeover circuits and a ring counter, in the form of a monolithic integrated mixed analogue-digital circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including the following combination of figures and letters: AN 8225 or — other identification markings relating to devices complying with the abovementioned description 	0
ex 8542 30 65	*16	<p>Circuit for driving linear motors or motors with rotating arms, of C-MOS technology, comprising a drive current switching circuit and a power fault detection circuit, in the form of a monolithic integrated mixed analogue-digital circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including one of the following combinations of figures or of figures and letters: 32H6810 50G2996 or — other identification markings relating to devices complying with the abovementioned description 	0
ex 8542 30 65	*17	<p>Video control circuit of bipolar technology, capable of switching and clamping video signals, in the form of a monolithic integrated mixed analogue-digital circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including the following combination of figures and letters: CXA 1860 or — other identification markings relating to devices complying with the abovementioned description 	0
ex 8542 30 65	*18	<p>Gain control circuit, capable of controlling and amplification of read signals for a storage unit, in the form of a monolithic integrated mixed analogue-digital circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including the following combination of figures and letters: 111 0005-04 or — other identification markings relating to devices complying with the abovementioned description 	0
ex 8542 30 69	*14	<p>Control circuit, capable of recording and reproduction of signals in a video servo system, in the form of a monolithic integrated analogue circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including the following combination of figures and letters: TA 8823N or — other identification markings relating to devices complying with the abovementioned description 	0

CN code	TARIC	Description	Rate of autonomous duty %
ex 8542 30 69	*16	Drive circuit for heads of a storage unit, in the form of a monolithic integrated analogue circuit contained in a housing bearing: — an identification marking consisting of or including the following combination of figures: 111 0007-01 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 30 69	*17	Control circuit of bipolar technology, providing volume control, in the form of a monolithic integrated analogue circuit contained in a housing bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: BA 3574 CXA 1646 CXA 1946 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 30 69	*18	Control circuit, capable of driving power field-effect transistors (FETs), in the form of a monolithic integrated analogue circuit contained in a housing bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: 71009SB LTC 1155 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 30 70	*06	Subscriber line interface circuit (SLIC), in the form of a monolithic integrated analogue circuit contained in a housing bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: Am 79M535 Am 79M574 Am 79M576 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 30 95	*22	16-bit digital-to-analogue converter, having a hands free function, in the form of a monolithic integrated mixed analogue-digital circuit contained in a housing bearing: — an identification marking consisting of or including the following combination of figures: 10485 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 30 95	*23	6-bit dual analogue-to-digital converter BiMOS technology, comprising a voltage reference circuit, in the form of a monolithic integrated mixed analogue-digital circuit contained in a housing bearing: — an identification marking consisting of or including the following combination of figures and letters: AD 9066 or — other identification markings relating to devices complying with the abovementioned description	0

CN code	TARIC	Description	Rate of autonomous duty %
ex 8542 30 95	*24	<p>4-channel 12-bit pulse width modulation generator, in the form of a monolithic integrated mixed analogue-digital circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including the following combination of figures and letters: M 66242 or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8542 30 95	*25	<p>Circuit for detecting pre-ignition of an automotive engine, comprising at least 1 amplifier and 1 bandpass filter operating at a frequency of 1 kHz or more but not exceeding 20 kHz, in the form of a monolithic integrated mixed analogue-digital circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including one of the following combinations of figures and letters: HIP 9010 HIP 9011 or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8542 30 95	*26	<p>Hall effect sensor with digital signal outputs, comprising a differentiator and peak detector, in the form of a monolithic integrated mixed analogue-digital circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including the following combination of figures and letters: AD 22402 or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8542 30 95	*27	<p>Audio signal processing circuit of C-MOS technology, operating at a typical supply voltage of 3 V, comprising a dual-tone multifrequency (DTMF) generator, mute switches, digitally controlled signal attenuators and passband filters, in the form of a monolithic integrated mixed analogue-digital circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including the following combination of figures and letters: SA 5753 or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8542 30 95	*28	<p>Transmitter/receiver of bipolar technology, comprising an UHF frequency oscillator, an oscillator operating at a frequency of 117 MHz and an oscillator operating at a frequency of 284 MHz, in the form of a monolithic integrated mixed analogue-digital circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including the following combination of figures and letters: W 2020 or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8542 30 95	*29	<p>Serial/parallel or parallel/serial converter for a network with an optical-fibre or coaxial cable, in the form of a monolithic integrated mixed analogue-digital circuit contained in a housing bearing:</p>	

CN code	TARIC	Description	Rate of autonomous duty %
ex 8542 30 95 (cont'd)		<ul style="list-style-type: none"> — an identification marking consisting of or including one of the following combinations of figures and letters: 64G0175 64G0176 or — other identification markings relating to devices complying with the abovementioned description 	0
ex 8542 30 95	*30	<p>Audio/video switching circuit, capable of independant swithching of audio signals and video signals, in the form of a monolithic integrated mixed analogue–digital circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including one of the following combinations of figures and letters: CXA 1114P CXA 1434P or — other identification markings relating to devices complying with the abovementioned description 	0
ex 8542 30 95	*31	<p>Amplifier/filter of BiMOS technology, capable of extracting signals having a frequency of 16 or 47 kHz from radio frequency (RF) signals, in the form of a monolithic integrated mixed analogue–digital circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including the following combination of figures and letters: MB 4470 or — other identification markings relating to devices complying with the abovementioned description 	0
ex 8542 30 95	*32	<p>Audio circuit of C–MOS technology, with a dynamic range of 70 dB or more, comprising 2 digital–to–analogue converters and 2 analogue–to–digital converters, in the form of a monolithic integrated mixed analogue–digital circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including one of the following combinations of figures and letters: AD 1845 AD 1847 AD 1848 CS 4231 CS 4248 or — other identification markings relating to devices complying with the abovementioned description 	0
ex 8542 30 95	*33	<p>Voice signal processing circuit of C–MOS technology, comprising an encoding circuit, a decoding circuit, a compression circuit and a decompression circuit, in the form of a monolithic integrated mixed analogue–digital circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including one of the following combinations of figures and letters: AK 2342 AK 2353 TC 35492 TC 35493 or — other identification markings relating to devices complying with the abovementioned description 	0
ex 8542 30 95	*34	<p>Frequency synthesizer, operating with an input frequency not exceeding 2 GHz and a DC supply voltage not exceeding 10 V, comprising a phase–locked loop (PLL) circuit and a programmable 14–bit or 20–bit counter, in the form of a monolithic integrated mixed analogue–digital circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including one of the following combinations of figures and letters: LC 7216 LMX 2320 MC 145158 MC 145162 or — other identification markings relating to devices complying with the abovementioned description 	0

CN code	TARIC	Description	Rate of autonomous duty %
ex 8542 30 95	*35	Passive decoder of BiMOS technology, comprising a fixed matrix, a 7-kHz filter, a noise-reducing circuit and a digital delay circuit, in the form of a monolithic integrated mixed analogue-digital circuit contained in a housing bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: LV 1 000 LV 1011 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 30 95	*36	Matrix decoder, comprising an adaptive matrix circuit, a noise generator and a automatic-balance control circuit, in the form of a monolithic integrated mixed analogue-digital circuit contained in a housing bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: LA 2785 M 69032P SSM 2125 SSM 2126 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 30 95	*37	Video processing circuit of bipolar technology, providing discrimination of synchronization signals, in the form of a monolithic integrated mixed analogue-digital circuit contained in a housing bearing: — an identification marking consisting of or including the following combination of figures and letters: CXA 1616 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 30 95	*38	Video processing circuit of bipolar technology, for colour and synchronization signals, in the form of a monolithic integrated mixed analogue-digital circuit contained in a housing bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: CXA 1213BS CXA 1587 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 30 95	*39	Signal measurement circuit for current and position sensors, of C-MOS technology, comprising 3 analogue-to-digital converters, a digital-to-analogue converter, multiplexers and sample and hold control circuits, in the form of a monolithic integrated mixed analogue/digital circuit contained in a housing bearing: — an identification marking consisting of or including the following combination of figures and letters: VECANA 01 or — other identification markings relating to devices complying with the abovementioned description	7

CN code	TARIC	Description	Rate of autonomous duty %
ex 8542 30 99	*49	<p>Level indicator circuit, capable of interfacing between a thermal sensor and a display unit, in the form of a monolithic integrated analogue circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including the following combination of figures and letters: TL 527 or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8542 30 99	*50	<p>Timer, in the form of a monolithic integrated analogue circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including one of the following combinations of figures and letters: NE 555 TS 555 or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8542 30 99	*51	<p>Audio compression/decompression circuit, operating at a supply voltage of 3 V or more but not exceeding 18 V, in the form of a monolithic integrated analogue circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including one of the following combinations of figures and letters: SA 5752 SA 578 or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8542 30 99	*52	<p>FM-band receiver, providing FM-signal demodulation, comprising at least a mixer, an intermediate frequency (IF) amplifier and a limiter amplifier, in the form of a monolithic integrated analogue circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including one of the following combinations of figures and letters: SA 605 SA 607 SA 617 or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8542 30 99	*53	<p>Mixer of bipolar technology, with a typical distortion factor of 251 mW (24 dBm), in the form of a monolithic integrated analogue circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including the following combination of figures: AD 831 or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8542 30 99	*54	<p>RF-band receiver of bipolar technology, comprising a mixer, a receive signal strength indicator (RSSI) and a logarithmic/limiting amplifier, in the form of a monolithic integrated analogue circuit contained in a housing bearing:</p>	

CN code	TARIC	Description	Rate of autonomous duty %
ex 8542 30 99 (cont'd)		<ul style="list-style-type: none"> — an identification marking consisting of or including the following combination of figures and letters: AD 608 or — other identification markings relating to devices complying with the abovementioned description 	0
ex 8542 30 99	*55	<p>Dual frequency synthesizer of BiMOS technology, with an input frequency per synthesizer not exceeding 1,2 GHz, comprising one or more phase locked loop circuits (PLLs), shift registers, dividers and latches, in the form of a monolithic integrated analogue circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including one of the following combinations of figures and letters: UMA1015M UMA1018M or — other identification markings relating to devices complying with the abovementioned description 	0
ex 8542 30 99	*56	<p>Video signal discriminator, in the form of a monolithic integrated analogue circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including one of the following combinations of figures and letters: LA 7311 LA 7356 or — other identification markings relating to devices complying with the abovementioned description 	0
ex 8542 30 99	*57	<p>Current breaking device, comprising an array of 8 field effect transistors (FETs) of the N- or P-channel type, having a typical drain-to-source breakdown-voltage of +380 or -380 V, in the form of a monolithic integrated analogue circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including one of the following combinations of figures and letters: AN0132NAR AP0130NA or — other identification markings relating to devices complying with the abovementioned description 	0
ex 8542 30 99	*58	<p>Frequency-to-voltage converter, comprising a voltage regulator and an output protected against short-circuit, in the form of a monolithic integrated analogue circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including the following combination of figures and letters: SN29736P1 or — other identification markings relating to devices complying with the abovementioned description 	0
ex 8542 30 99	*59	<p>Speech-transfer circuit of bipolar technology, comprising a transmitted signal attenuator, a received signal attenuator, an attenuator controller, a mute controller, 3 amplifiers, a dial tone detector and 2 noise generators, in the form of a monolithic integrated analogue circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including the following combination of figures and letters: MC 34118 or — other identification markings relating to devices complying with the abovementioned description 	0

CN code	TARIC	Description	Rate of autonomous duty %
ex 8542 30 99	*60	<p>FM-band receiver of bipolar technology, providing FM-signal demodulation, comprising at least a mixer, an intermediate frequency (IF) amplifier and a limiter amplifier, in the form of a monolithic integrated analogue circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including one of the following combinations of figures and letters: MC 13156 MC 13158 TA 2027F</p> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8542 30 99	*61	<p>Attenuator circuit of gallium arsenide (GaAs) semiconductor material, providing a voltage variable attenuation range not exceeding 40 dB at a frequency of 0,9 GHz, in the form of a monolithic integrated analogue circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including the following combination of figures and letters: AT 108</p> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8542 30 99	*62	<p>Video processing circuit of bipolar technology, for colour or luminance signals, in the form of a monolithic integrated analogue circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including one of the following combinations of figures and letters: CXA 1207 CXA 1208 CXA 1779P</p> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8542 30 99	*63	<p>Voltage comparator, operating within a common voltage range of -12 V or more but not exceeding +16 V and a differential voltage range of -24 V or more but not exceeding +24 V and a response time not exceeding 2,2 µs, in the form of a monolithic integrated analogue circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including one of the following combinations of figures and letters: EL 2019 LM 119 LM 219 LM 319 LT 1016 TS 3702</p> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8542 30 99	*64	<p>Phase-locked loop (PLL) circuit of bipolar technology, comprising an oscillator and a frequency and/or phase detector, in the form of a monolithic integrated analogue circuit contained in a housing bearing:</p> <p>— an identification marking consisting of or including one of the following combinations of figures and letters: M52319SP SN 28967</p> <p>or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0

CN code	TARIC	Description	Rate of autonomous duty %
ex 8542 40 50	*08	<p>Amplifier, operating within a frequency range of 400 MHz to 470 MHz, with an output power of 2 W at 6 V and an input power not exceeding 30 mW, in the form of a hybrid integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including the following combination of figures and letters: M 678710 or — other identification markings relating to devices complying with the abovementioned description 	0
ex 8542 40 50	*09	<p>Amplifier with an input power of 1 mW and an output power not exceeding 3,5 W at a frequency range of 1 710 MHz or more but not exceeding 1 785 MHz, in the form of a hybrid integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including the following combination of figures and letters: FA 01314 or — other identification markings relating to devices complying with the abovementioned description 	0
ex 8542 40 90	*07	<p>Clock generator, in the form of a hybrid integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including the following combination of figures and letters: 64G0211 or — other identification markings relating to devices complying with the abovementioned description 	0
ex 8542 40 90	*08	<p>Voltage regulating and relay circuit for central locking and alarm system, comprising a constant voltage circuit and a sampling circuit, in the form of a hybrid integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including one of the following combinations of figures and letters: BX 6531 BX 6563 or — other identification markings relating to devices complying with the abovementioned description 	0
ex 8542 40 90	*09	<p>Transmitter of gallium arsenide (GaAs) semiconductor material, operating with frequencies of 21 GHz or more but not exceeding 40 GHz, in the form of a hybrid integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> — an identification marking consisting of or including one of the following combinations of figures and letters: 371-230 371-380 or — other identification markings relating to devices complying with the abovementioned description 	0
ex 8542 50 00	*05	<p>Assembly for overvoltage protection, consisting of an array of 4 diodes, with a breakdown-voltage of 6 V or more, a peak pulse power of 300 W for 8 overvoltage periods of 20 µs each, in the form of a microassembly contained in a housing of the SMD (Surface mounted device) type</p>	0
ex 8543 89 90	*44	<p>Rectifier assembly of power barrier diodes, consisting of 2 diodes with an average forward current not exceeding 600 A and a repetitive reverse peak voltage not exceeding 40 V, each contained in a housing and connected by a common cathode</p>	0

CN code	TARIC	Description	Rate of autonomous duty %
ex 8543 89 90	*45	<p>Amplifier of gallium arsenide (GaAs) semiconductor material, operating with a frequency range of 890 MHz to 915 MHz, with an input level not exceeding 16 mW (12 dBm) and a typical output level of 850 mW (29,3 dBm) at 5 V, consisting of active and passive elements mounted on a printed circuit, contained in a housing bearing:</p> <p>— an identification marking consisting of or including the following combination of figures and letters: FMC 080901-70 or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8543 89 90	*46	<p>Piezo-electric crystal clock oscillator with a fixed frequency, within a frequency range of 1,8 MHz to 67 MHz, contained in a housing bearing:</p> <p>— an identification marking consisting of or including one of the following combinations of figures and letters: R4 000.8 R4 000.9 or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8543 89 90	*47	<p>Transmitter/receiver powered by a received pulse with a frequency of 134,2 kHz, capable of transmitting message identifications with error correction codes, comprising a solenoid, a capacitor and an integrated circuit, the whole contained in a hermetically sealed glass capsule</p>	0
ex 8543 89 90	*48	<p>Mechanical vibratory gyroscope driven by a 25 or 26 kHz oscillator, comprising a differential amplifier and a detector circuit, contained in a housing bearing:</p> <p>— an identification marking consisting of or including the following combination of figures and letters: ENC05D or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8543 89 90	*49	<p>Amplifier of bipolar technology, operating within a frequency range of 800 MHz to 950 MHz, with at least one of the following characteristics:</p> <p>a) an output power of 1,41 W at an input power of 5 mW,</p> <p>b) an output power of 2 W at an input power of 1 mW,</p> <p>c) an output power of 3,2 W at an input power of 2 mW,</p> <p>d) an output power of 3,5 W at an input power of 1 or 100 mW,</p> <p>e) an output power of 6 W at an input power of 100 mW,</p> <p>f) an output power of 14 W at an input power of 1 or 100 mW,</p> <p>g) an output power of 7 W at an input power of 20 mW,</p> <p>consisting of active and passive elements mounted on a printed circuit, contained in a housing bearing:</p> <p>— an identification marking consisting of or including one of the following combinations of figures and letters: a) MHW 9002 d) MHW 953 e) XHW 5115 g) PF 0146 b) MHW 803 d) XHW 903 f) MHW 914 c) PHW 902 e) SHW 5115 f) MHW 915 or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0

CN code	TARIC	Description	Rate of autonomous duty %
ex 8543 89 90	*50	<p>Opto-electronic circuit comprising one or more light-emitting diodes (LEDs) and one photodiode with amplifier circuit and an integrated logic gate arrays circuit or one or more light-emitting diodes (LEDs) and at least 2 photodiodes with amplifier circuit, contained in a plastic housing bearing:</p> <p>— an identification marking consisting of or including one of the following combinations of figures and letters: HC PL 2 400 HC PL 2730 or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8543 89 90	*51	<p>Temperature compensating frequency oscillator with a nominal frequency of 12,8 or 13 MHz and operating at a supply voltage of 3 V ($\pm 0,3$ V), comprising a printed circuit on which are mounted at least a piezo-electric crystal and an adjustable capacitor, contained in a housing with not more than 5 connections and bearing:</p> <p>— an identification marking consisting of or including one of the following combinations of figures and letters: TCXO-111 TX 02603 or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8543 89 90	*52	<p>Oscillator, with a centre frequency of 20 GHz or more but not exceeding 42 GHz, consisting of active and passive elements not mounted on a substrate, contained in a housing bearing:</p> <p>— an identification marking consisting of or including one of the following combinations of figures and letters: 372-02 372-03 or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8543 89 90	*55	<p>Voltage regulator with an output voltage of 5 V or more but not exceeding 12 V and a dropout voltage not exceeding 1 V at an output current of 1,5 A, consisting of a power transistor and an integrated circuit mounted on a metallic baseplate, contained in a housing bearing:</p> <p>— an identification marking consisting of or including one of the following combinations of figures and letters: 3050C 3090C 3120C or</p> <p>— other identification markings relating to devices complying with the abovementioned description</p>	0
ex 8543 90 90	*10	<p>Dual field-effect transistor (FET) with at least one of following characteristics:</p> <p>a) of the P-channel type, having a drain-to-source breakdown-voltage of -20 V, operating with a drain-current not exceeding 9,2 A and with a dissipation rate not exceeding 2 W,</p> <p>b) of the N-channel type, having a drain-to-source breakdown-voltage of 20 V or more, operating with a drain-current not exceeding 3,5 A and with a dissipation rate not exceeding 2 W,</p> <p>contained in a housing bearing:</p> <p>— an identification marking consisting of or including one of the following combinations of figures:</p> <p>a) 9947 a) MMDF2P02HD b) MMDF1N50E a) 9953 b) 9956 b) MMDF2C02E a) MMDF2C02E b) 9959</p>	

CN code	TARIC	Description	Rate of autonomous duty %
ex 8543 90 90 (cont'd)		or — other identification markings relating to devices complying with the abovementioned description	0
ex 8548 90 00	*35	Optical unit consisting of a laser diode, a photodiode and a lens, operating at a typical wavelength of 1 310 or 1 550 nm, contained in a housing	0
ex 9001 90 90	*10	Fresnel lens of plastic, unmounted, with a diagonal of more than 100 cm, for use in the manufacture of products falling within heading 8528 (a)	0
ex 9001 90 90	*20	Rear projection screen, comprising a Fresnel lens of plastic and a polarizing sheet of plastic, for use in the manufacture of products falling within subheading No 8528 (a)	0
ex 9001 90 90	*30	Lens of plastic, unmounted, having a focal length of 3,86 mm ($\pm 0,1$ mm) and with a diameter not exceeding 8 mm, for use in the manufacture of compact disc players (a)	0
ex 9010 90 00	*10	Parts of apparatus for the projection of drawings of circuit patterns on sensitised semiconductor material, only consisting of a plastic membrane with a thickness not exceeding 3 μ m and a metallic frame	0
9013 80 30		Liquid crystal devices, other than active matrix liquid crystal devices	0
ex 9031 90 90	*10	Assembly for a laser align sensor, in the form of a printed circuit comprising optical filters and a charge-coupled (CCD) image sensor, the whole contained in a housing	0

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.